

TEST REPORT

On behalf of

Shanghai Teraoka Electronic Co., Ltd.

Product Name: SMART CARD TERMINAL

Model No.: WB-20

FCC ID: 2ARYWWB-20

Prepared For: Shanghai Teraoka Electronic Co., Ltd.
Tinglin Industry Development Zone, Jinshan District,
Shanghai, China

Prepared By: Audix Technology (Shanghai) Co., Ltd.
3F and 4F, 34Bldg, 680 Guiping Rd.,
Caohejing Hi-Tech Park,
Shanghai 200233, China

Tel: +86-21-64955500



File No. : C1D2011005
Report No. : ACI-F21109
Date of Test : 2020.11.11-2021.04.20
Date of Report : 2021.05.26

The statement is based on a single evaluation of one sample of the above-mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab logo. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

TABLE OF CONTENTS

	Page
1 SUMMARY OF STANDARDS AND RESULTS.....	5
1.1 Description of Standards and Results.....	5
2 GENERAL INFORMATION.....	6
2.1 Description of Equipment Under Test.....	6
2.2 EUT Specifications Assessed in Current Report.....	7
2.3 Test Information.....	7
2.4 Sample Description.....	7
2.5 Supported equipment.....	8
2.6 Description of Test Facility.....	8
3 CONDUCTED EMISSION TEST.....	9
3.1 Test Equipment.....	9
3.2 Block Diagram of Test Setup.....	9
3.3 Conducted Emission Limits (§15.207).....	10
3.4 Test Configuration.....	10
3.5 Operating Condition of EUT.....	10
3.6 Test Procedures.....	10
3.7 Test Results.....	11
4 RADIATED EMISSION TEST.....	13
4.1 Test Equipment.....	13
4.2 Block Diagram of Test Setup.....	13
4.3 Radiated Emission Limit (§15.209).....	14
4.4 Test Configuration.....	14
4.5 Operating Condition of EUT.....	15
4.6 Test Procedures.....	15
4.7 Test Results.....	16
5 6 DB BANDWIDTH MEASUREMENT.....	24
5.1 Test Equipment.....	24
5.2 Block Diagram of Test Setup.....	24
5.3 Specification Limits (§15.247(a)(2)).....	24
5.4 Operating Condition of EUT.....	24
5.5 Test Procedure.....	24
5.6 Test Results.....	25
6 MAXIMUM PEAK OUTPUT POWER MEASUREMENT.....	31
6.1 Test Equipment.....	31
6.2 Block Diagram of Test Setup.....	31
6.3 Specification Limits (§15.247(b)(3)).....	31
6.4 Operating Condition of EUT.....	31
6.5 Test Procedure.....	31
6.6 Test Results.....	32
7 EMISSION LIMITATIONS MEASUREMENT.....	38
7.1 Test Equipment.....	38
7.2 Block Diagram of Test Setup.....	38
7.3 Specification Limits (§15.247(d)).....	38
7.4 Operating Condition of EUT.....	38

7.5	Test Procedure	38
7.6	Test Results	40
8	BAND EDGES MEASUREMENT	59
8.1	Test Equipment.....	59
8.2	Block Diagram of Test Setup	59
8.3	Specification Limits (§15.247(d))	59
8.4	Operating Condition of EUT	59
8.5	Test Procedure.....	59
8.6	Test Results	60
9	POWER SPECTRAL DENSITY MEASUREMENT	64
9.1	Test Equipment.....	64
9.2	Block Diagram of Test Setup	64
9.3	Specification Limits (§15.247(e))	64
9.4	Operating Condition of EUT	64
9.5	Test Procedure.....	64
9.6	Test Results	65
10	DEVIATION TO TEST SPECIFICATIONS	71
11	MEASUREMENT UNCERTAINTY LIST	72

TEST REPORT

Applicant : Shanghai Teraoka Electronic Co., Ltd.
EUT Description : SMART CARD TERMINAL
(A) Model No. : Refer to Sec.2.1
(B) Power Supply : DC5V
(C) Test Voltage : DC5V (Via Adaptor)

Test Procedure Used:

*FCC RULES AND REGULATIONS PART 15 SUBPART C
AND ANSI C63.10-2013*

The device described above is tested by Audix Technology (Shanghai) Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits.

The test results are contained in this test report and Audix Technology (Shanghai) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. This report also shows that the EUT (M/N: Refer to Sec2.1), which was tested is technically compliance with the FCC limits.

This report applies to above tested Sample only. This report shall not be reproduced in part without written approval of Audix Technology (Shanghai) Co., Ltd.

The test results for EUT's BLE /DFS/BT/ WIFI (5G) function are contained in No.ACI-F21108, ACI-F21123, ACI-F21121, ACI-F21122 report.

Date of Test : 2020.11.11-2021.04.20 Date of Report : 2021.05.26

Producer : Huimin Yan
HUIMIN YAN / Assistant

Review : Byron Wu
BYRON WU/ Deputy Assistant Manager

 For and on behalf of
Audix Technology (Shanghai) Co., Ltd.

Signatory : Byron Kwo
BYRON KWO/ Assistant General Manager

Authorized Signature(s)

1 SUMMARY OF STANDARDS AND RESULTS

1.1 Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Description / Test Item	Test Standard	Results	Meets Limit
EMISSION			
Conducted Emission	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.207
Radiated Emission	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.209(a) 15.205(a)(c)
6 dB Bandwidth Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(a)(2)
Maximum Peak Output Power Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(b)(3)
Emission Limitations Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(d)
Band Edge Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(d)
Power Spectral Density Measurement	FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013	Pass	15.247(e)
N/A is an abbreviation for Not Applicable.			

2 GENERAL INFORMATION

2.1 Description of Equipment Under Test

Description	:	SMART CARD TERMINAL
Type of EUT	:	☒ Production ☐ Pre-product ☐ Pro-type
Model Number	:	WB-20
Radio Tech	:	Bluetooth 4.2; IEEE 802.11 a/b/g/n/ac.
Channel Freq.	:	BLE: 2402MHz-2480MHz; BT: 2402MHz-2480MHz IEEE 802.11a: 5180MHz—5240MHz; 5260MHz—5320MHz 5500MHz—5700MHz; 5745MHz—5825MHz IEEE 802.11ac VHT20: 5180MHz—5240MHz; 5260MHz—5320MHz 5500MHz—5700MHz; 5745MHz—5825MHz IEEE 802.11ac VHT40: 5190MHz—5230MHz; 5270MHz—5310MHz 5510MHz—5670MHz; 5755MHz—5795MHz IEEE 802.11ac VHT80: 5210MHz, 5290MHz; 5530MHz—5610MHz; 5775MHz IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE802.11nHT20: 2412MHz—2462MHz; 5180MHz—5240MHz; 5260MHz—5320MHz 5500MHz—5700MHz; 5745MHz—5825MHz IEEE802.11nHT40: 5190MHz—5230MHz; 5270MHz—5310MHz 5510MHz—5670MHz; 5755MHz—5795MHz
Modulation	:	BLE: GFSK; BT: FHSS, GFSK, DPSK, DQPSK; 802.11b: DSSS (CCK, DQPSK, DBPSK); 802.11a/g/n: OFDM (64QAM, 16QAM, QPSK, BPSK); 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK).
Antenna Info.	:	Antenna Type: SMA Antenna Antenna Gain: 5 dBi The Antenna was an antenna that uses a unique coupling to the intentional radiator that is comply with 15.203 requirement.
Applicant	:	Shanghai Teraoka Electronic Co., Ltd. Tinglin Industry Development Zone, Jinshan District, Shanghai, China

Manufacturer : same as Applicant

Factory : same as Applicant

2.2 EUT Specifications Assessed in Current Report

Mode	Modulation	Data Rate(Mbps)
802.11b	DSSS (DQPSK, DBPSK, CCK)	Up to 11
802.11g	OFDM (64-QAM, 16-QAM, QPSK, BPSK)	Up to 54
802.11n-HT 20	OFDM (64-QAM, 16-QAM, QPSK, BPSK)	Up to 72.2

Channel List			
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

2.3 Test Information

The test software “ RFTTestTool.apk” was used to control EUT work in TX mode, Power Index and select test channel.

Modulation	data rate (Mbps)	Power Index	Test Channel		Frequency (MHz)
802.11b	1	Default	Low:	1	2412
		Default	Middle:	6	2437
		Default	High:	11	2462
802.11g	6	Default	Low:	1	2412
		Default	Middle:	6	2437
		Default	High:	11	2462
802.11n20	MCS0	Default	Low:	1	2412
		Default	Middle:	6	2437
		Default	High:	11	2462

2.4 Sample Description

Test Item	Model Number	Sample Number	Date of receipted
Conducted Emission	WB-20	E20111479-01/02	2020.11.02
Radiated Emission	WB-20	E20111479-02/02	2020.11.02
Conducted RF Test	WB-20	E20111479-01/02	2020.11.02

2.5 Supported equipment

Brand : HUAWEI
Product Name: : Adaptor
Model Name : HW-050200C01

2.6 Description of Test Facility

Name of Firm : Audix Technology (Shanghai) Co., Ltd.
Site Location : 3F and 4F, 34Bldg, 680 Guiping Rd.,
Caohejing Hi-Tech Park,
Shanghai 200233, China.
Accredited by NVLAP, Lab Code : 200371-0
FCC Designation Number : CN5027
Test Firm Registration Number : 954668

3 CONDUCTED EMISSION TEST


3.1 Test Equipment

The following test equipments are used during the conducted emission test in a shielded room:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Test Receiver	R&S	ESCI	100841	2020.02.11	1 Year
2.	Artificial Mains Network (AMN)	R&S	ESH2-Z5	843890/011	2020.01.06	1 Year
3.	Software	Audix	e3	6.2009-1-15	--	--

3.2 Block Diagram of Test Setup

3.2.1 Conducted Disturbance Test Setup



3.3 Conducted Emission Limits (§15.207)

Frequency Range (MHz)	Limits dB(μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66~56	56~46
0.5 ~ 5	56	46
5 ~ 30	60	50
NOTE 1 – The lower limit shall apply at the transition frequencies. NOTE 2 – The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz~0.50 MHz		

3.4 Test Configuration

The EUT (listed in Sec.2.1) was installed as shown on Sec.3.2 to meet FCC requirement and operating in a manner which tends to maximize its emission level in a normal application.

3.5 Operating Condition of EUT

3.5.1 Setup the EUT as shown in Sec. 3.2.

3.5.2 Turn on the power of all equipment.

3.5.3 Turn the EUT on the test mode, and then test.

3.6 Test Procedures

The EUT was placed upon a non-metallic table, which is 0.8 m above the horizontal conducting ground plane and 0.4 m from a vertical reference plane. The EUT was connected to the power mains through an Artificial Mains Network (AMN) to provide a 50 Ω coupling impedance for the measuring equipment. Both sides of AC line (Line & Neutral) were checked to find out the maximum conducted emission according to FCC Part 15 Subpart C and ANSI C63.10: 2013 requirements during conducted disturbance test.

The I.F. bandwidth of Test Receiver ESCI was set at 9 kHz.

The frequency range from 150 kHz to 30 MHz was checked.

Test with a dummy load in lieu of the antenna to determine compliance with Section 15.207 limits within the transmitter's fundamental emission band. (According to KDB 174176 D01 Line Conducted FAQ)

The test modes were done on conducted disturbance test and all the test results are listed in Sec. 3.7

3.7 Test Results

< **PASS** >

The frequency and amplitude of the highest conducted emission relative the limit is reported. All the emissions not reported below are too low against the FCC limit.

Worst case emission:

No.	Operation	Modulation	Channel	Frequency (MHz)	Data Page
1.	Transmitting	--	--	--	P12

NOTE 1 – Level = Read Level + AMN Factor + Cable Loss

NOTE 2 – “QP” means “Quasi-Peak” values

NOTE 3 – The emission levels which not reported are too low against the official limit.

Worst case emission

EUT : SMART CARD TERMINAL Temperature : 22°C

Model No. : WB-20 Humidity : 51%RH

Test Mode : Transmitting Date of Test : 2020.11.11

Polarization	Frequency (MHz)	Meter Reading dB (μV)	AMN Factor (dB)	Cable Loss (dB)	Emission Level dB (μV)	Limits dB (μV)	Margin (dB)	Remark
Line	0.1565	39.79	0.08	0.08	39.95	65.65	25.7	QP
	0.1565	27.78	0.08	0.08	27.94	55.65	27.71	Average
	0.3712	45.5	0.09	0.18	45.77	58.47	12.7	QP
	0.3712	43.2	0.09	0.18	43.47	48.47	5	Average
	0.743	40.44	0.11	0.16	40.71	56	15.29	QP
	0.743	32.23	0.11	0.16	32.5	46	13.5	Average
	1.065	35.9	0.11	0.14	36.15	56	19.85	QP
	1.065	27.92	0.11	0.14	28.17	46	17.83	Average
	2.707	30.37	0.15	0.17	30.69	56	25.31	QP
	2.707	24.34	0.15	0.17	24.66	46	21.34	Average
	13.989	26	0.18	0.13	26.31	60	33.69	QP
	13.989	16.7	0.18	0.13	17.01	50	32.99	Average
Neutral	0.1549	41.04	0.09	0.08	41.21	65.74	24.53	QP
	0.1549	26.99	0.09	0.08	27.16	55.74	28.58	Average
	0.3465	41.19	0.1	0.17	41.46	59.05	17.59	QP
	0.3465	27.16	0.1	0.17	27.43	49.05	21.62	Average
	0.7274	37.46	0.12	0.16	37.74	56	18.26	QP
	0.7274	27.13	0.12	0.16	27.41	46	18.59	Average
	1.032	35.78	0.13	0.14	36.05	56	19.95	QP
	1.032	23.57	0.13	0.14	23.84	46	22.16	Average
	3.436	27.79	0.19	0.18	28.16	56	27.84	QP
	3.436	20.4	0.19	0.18	20.77	46	25.23	Average
	13.551	34.32	0.41	0.13	34.86	60	25.14	QP
	13.551	23.93	0.41	0.13	24.47	50	25.53	Average

TEST ENGINEER: Jarey

4 RADIATED EMISSION TEST


4.1 Test Equipment

The following test equipment are used during the radiated emission test in a semi-anechoic chamber:


Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Preamplifier	Agilent	8447D	2944A10548	2020.04.26	1 Year
2.	Preamplifier	HP	8449B	3008A00864	2021.01.05	1 Year
3.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2020.09.16	1 Year
4.	Test Receiver	R&S	ESCI	101303	2020.04.26	1 Year
5.	Bilog Antenna+6dB Attenuator	Schwarz beck	VULB 9168+EMCI-N-6-06	708+AT-N0638	2020.07.06	1 Year
6.	Horn Antenna	EMCO	3115	9607-4878	2020.07.13	1 Year
7.	Horn Antenna	EMCO	3116	00062643	2020.09.08	1 Year
8.	Cavity Band Rejection Filter	Microwave	WT-A3882-R10	WT200312-1-1	2020.07.07	1 Year
9.	Software	Audix	e3	SET002009912M295-2	--	--

4.2 Block Diagram of Test Setup


4.2.1 EUT & Peripherals



4.2.2 Below 1GHz



4.2.3 Above 1GHz



4.3 Radiated Emission Limit (§15.209)

Frequency (MHz)	Distance (m)	Field strength limits (μV/m)	
		(μV/m)	dB(μV/m)
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
Above 960	3	500	54.0

NOTE 1 - Emission Level dB (V/m) = 20 log Emission Level (V/m)

NOTE 2 - The tighter limit applies at the band edges.

NOTE 3 - Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

NOTE 4 - The limits shown are based on Quasi-peak value detector below or equal to 1GHz and Average value detector above 1GHz.

NOTE 5 - Above 1 GHz, the limit on peak emission is 20 dB above the maximum permitted average emission limit applicable to the EUT

4.4 Test Configuration

The EUT (listed in Sec.2.1) and the simulators (listed in Sec.2.2) were installed as shown on Sec.4.2 to meet FCC requirements and operating in a manner that tends to maximize its emission level in a normal application.

4.5 Operating Condition of EUT

4.5.1 Setup the EUT as shown in Sec. 4.2.

4.5.2 Turn on the power of all equipment.

4.5.3 Turn the EUT on the test mode, and then test.

4.6 Test Procedures

Radiated emission test applies to harmonics/spurs that fall in the restricted bands listed in Section 15.205. The maximum permitted average field strength is listed in Section 15.209. A pre-amp is necessary for this measurement. For measurement above 1 GHz, set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.

The EUT was placed on a turntable. Below 1 GHz, the table height is 80 cm above the reference ground plane. Above 1 GHz, the table height is 1.5 m. The turntable rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna, which was mounted on an antenna tower. The antenna moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (Calibrated Bilog Antenna) or Horn antenna was used as receiving antenna. Both horizontal and vertical polarizations of the antenna were set on measurement. In order to find the maximum emission, all of the interference cables were manipulated according to ANSI C63.10: 2013 requirements during radiated emission test.

The bandwidth of Test Receiver R&S ESCI was set at 120 kHz from 30MHz to 1000MHz.

The bandwidth of Agilent N9010A was set at 1MHz for above 1GHz.

The frequency range from 30 MHz to 25 GHz (Up to 10th harmonics from fundamental frequency) was checked.

All the test results are listed in Sec.4.7.

4.7 Test Results

<PASS>

The frequency and amplitude of the highest radiated emission relative the limit is reported. All the emissions not reported below are too low against the FCC limit.

Frequency range: below 1GHz (Worst case emission)

No.	Operation	Modulation	Channel	Frequency	Data Page
1.	Transmitting	--	--	--	P17

Frequency range: above 1GHz

No.	Operation	Modulation	Channel	Frequency	Data Page
1.	Transmitting	802.11b	1	2412 MHz	P18
2.			6	2437 MHz	P18
3.			11	2462 MHz	P19
4.	Transmitting	802.11g	11	2462 MHz	P19
5.	Transmitting	802.11n20	11	2462 MHz	P20

Restricted bands:

No.	Operation	Modulation	Channel	Frequency	Data Page
1.	Transmitting	802.11b	1	2412 MHz	P21
			11	2462 MHz	
2.		802.11g	1	2412 MHz	P22
			11	2462 MHz	
3.		802.11n20	1	2412 MHz	P23
			11	2462 MHz	

NOTE 1 – Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

NOTE 2 – “QP” means “Quasi-Peak” values

NOTE 3 – 0° was the table front facing the antenna. Degree is calculated from 0° clockwise facing the antenna.

NOTE 4 – The emission levels which not reported are too low against the official limit.

NOTE 5 – The emission levels recorded below is data of EUT configured in Lying direction, for Standing direction was the maximum emission direction during the test. The data of Side & Standing direction are too low against the official limit to be reported.

NOTE 6 – All reading are Quasi-Peak values below or equal to 1GHz, Peak and Average values above 1GHz.

For above 1GHz test, if the peak measured value complies with the average limit, it is unnecessary to perform an average measurement.

NOTE 7 – The frequency range 2310-2390MHz & 2483.5-2500MHz were tested for Restricted bands.

Worst case emission < 1GHz

EUT : SMART CARD TERMINAL Temperature : 22°C

Model No. : WB-20 Humidity : 51%RH

Test Mode : Transmitting Date of Test : 2021.04.20

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
Horizontal	52.76	28.02	19.63	0.45	28.35	19.75	40	20.25	QP
	150.02	37.2	19.1	0.59	27.74	29.15	43.5	14.35	QP
	254.73	37.79	17.77	0.76	27.41	28.91	46	17.09	QP
	300	40.4	19	0.88	27.35	32.93	46	13.07	QP
	450	46.8	22.8	1.17	27.2	43.57	46	2.43	QP
	750	40.9	27.5	1.83	27.44	42.79	46	3.21	QP
Vertical	51.843	41.06	19.69	0.45	28.35	32.85	40	7.15	QP
	66.266	40.11	18.11	0.5	28.25	30.47	40	9.53	QP
	150.01	39.86	19.1	0.59	27.74	31.81	43.5	11.69	QP
	450	42.7	22.8	1.17	27.2	39.47	46	6.53	QP
	600	41.5	25.3	1.51	27.28	41.03	46	4.97	QP
	750	41.9	27.5	1.83	27.44	43.79	46	2.21	QP

TEST ENGINEER: Jarey

Radiated Emission > 1GHz

EUT	:	SMART CARD TERMINAL	Temperature :	22°C
Model No.	:	WB-20	Humidity :	51%RH
Test Mode	:	Transmitting	Date of Test :	2021.04.20

802.11b CH2412MHz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
Horizontal	1513	45.32	25.56	3.02	37.54	36.36	74	37.64	Peak
	3475	38.83	31.16	4.54	37.08	37.45	74	36.55	Peak
	5122	35.35	33.52	5.71	37.06	37.52	74	36.48	Peak
	6967	33.97	35.36	6.19	37.01	38.51	74	35.49	Peak
	8470	34.01	38.45	6.62	36.98	42.1	74	31.9	Peak
	9982	34.41	38.4	7.33	36.96	43.18	74	30.82	Peak
Vertical	1657	44.04	26.16	3.19	37.4	35.99	74	38.01	Peak
	3376	38.76	30.95	4.49	37.09	37.11	74	36.89	Peak
	5131	35.39	33.55	5.71	37.06	37.59	74	36.41	Average
	7174	33.75	35.96	6.24	37.01	38.94	74	35.06	Peak
	8461	34.43	38.45	6.62	36.98	42.52	74	31.48	Peak
	9784	35.77	38.4	7.26	36.96	44.47	74	29.53	Peak

802.11b CH2437MHz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
Horizontal	1846	43.71	26.87	3.39	37.24	36.73	74	37.27	Peak
	3808	38.38	32.09	4.7	37.08	38.09	74	35.91	Peak
	5086	36.14	33.46	5.68	37.06	38.22	74	35.78	Peak
	6931	34.24	35.29	6.19	37.01	38.71	74	35.29	Peak
	8515	33.94	38.49	6.69	36.98	42.14	74	31.86	Peak
	9937	34.21	38.4	7.33	36.96	42.98	74	31.02	Peak
Vertical	1846	43.63	26.87	3.39	37.24	36.65	74	37.35	Peak
	3754	37.87	31.94	4.67	37.08	37.4	74	36.6	Peak
	5644	34.97	34.2	5.85	37.04	37.98	74	36.02	Peak
	7165	34.18	35.9	6.24	37.01	39.31	74	34.69	Peak
	8425	33.72	38.36	6.62	36.99	41.71	74	32.29	Peak
	9838	34.97	38.4	7.26	36.96	43.67	74	30.33	Peak

802.11b CH2462MHz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
Horizontal	1891	43	27.02	3.45	37.21	36.26	74	37.74	Peak
	3430	39.54	31.05	4.51	37.08	38.02	74	35.98	Peak
	4699	36.62	32.76	5.43	37.06	37.75	74	36.25	Peak
	6337	35.13	34.4	6.05	37.03	38.55	74	35.45	Peak
	8209	34.05	37.93	6.49	36.99	41.48	74	32.52	Peak
	9640	34.44	38.4	7.2	36.97	43.07	74	30.93	Peak
Vertical	1612	44.55	25.98	3.14	37.44	36.23	74	37.77	Peak
	3331	39.73	30.85	4.46	37.09	37.95	74	36.05	Peak
	4681	36.96	32.74	5.43	37.06	38.07	74	35.93	Peak
	6409	34.7	34.45	6.07	37.02	38.2	74	35.8	Peak
	8308	34.15	38.17	6.56	36.99	41.89	74	32.11	Peak
	9730	35.71	38.4	7.26	36.96	44.41	74	29.59	Peak

802.11g CH2412MHz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
Horizontal	1846	43.08	26.87	3.39	37.24	36.1	74	37.9	Peak
	3610	39.5	31.53	4.59	37.08	38.54	74	35.46	Peak
	5311	35.4	33.87	5.76	37.05	37.98	74	36.02	Peak
	7021	34.82	35.46	6.21	37.01	39.48	74	34.52	Peak
	8452	34.35	38.4	6.62	36.98	42.39	74	31.61	Peak
	9658	35.53	38.4	7.2	36.97	44.16	74	29.84	Peak
Vertical	1792	43.4	26.68	3.33	37.29	36.12	74	37.88	Peak
	3556	39.11	31.38	4.57	37.08	37.98	74	36.02	Peak
	5527	35.05	34.2	5.83	37.05	38.03	74	35.97	Peak
	7273	34.79	36.21	6.26	37.01	40.25	74	33.75	Peak
	8974	35.45	38.31	6.88	36.98	43.66	74	30.34	Peak
	9793	35.15	38.4	7.26	36.96	43.85	74	30.15	Peak

802.11n20 CH2412MHz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
Horizontal	1513	45.14	25.56	3.02	37.54	36.18	74	37.82	Peak
	3151	40.32	30.45	4.36	37.09	38.04	74	35.96	Peak
	4960	36.39	33.23	5.6	37.06	38.16	74	35.84	Peak
	7048	34.27	35.59	6.21	37.01	39.06	74	34.94	Peak
	8479	34.76	38.5	6.62	36.98	42.9	74	31.1	Peak
	9784	34.59	38.4	7.26	36.96	43.29	74	30.71	Peak
Vertical	1702	45.03	26.34	3.25	37.37	37.25	74	36.75	Peak
	3457	39.77	31.12	4.51	37.08	38.32	74	35.68	Peak
	5257	35.46	33.76	5.73	37.05	37.9	74	36.1	Peak
	7165	34.53	35.9	6.24	37.01	39.66	74	34.34	Peak
	8893	34.92	38.34	6.88	36.98	43.16	74	30.84	Peak
	9784	34.84	38.4	7.26	36.96	43.54	74	30.46	Peak

TEST ENGINEER: Jarey

Emissions in restricted frequency bands:

EUT	:	SMART CARD TERMINAL	Temperature :	22°C
Model No.	:	WB-20	Humidity :	51%RH
Test Mode	:	Transmitting	Date of Test :	2021.04.20

802.11b

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
Horizontal	2340.1	50.76	28.17	3.83	37.11	45.65	74	28.35	Peak
	2340.1	39.37	28.17	3.83	37.11	34.26	54	19.74	Average
	2366.2	51.18	28.23	3.85	37.11	46.15	74	27.85	Peak
	2366.2	39.62	28.23	3.85	37.11	34.59	54	19.41	Average
	2389.2	57.96	28.27	3.85	37.11	52.97	74	21.03	Peak
	2389.2	40.8	28.27	3.85	37.11	35.81	54	18.19	Average
	2484.4	57.57	28.47	3.93	37.11	52.86	74	21.14	Peak
	2484.4	41.16	28.47	3.93	37.11	36.45	54	17.55	Average
	2491.1	55.12	28.49	3.93	37.11	50.43	74	23.57	Peak
	2491.1	40.23	28.49	3.93	37.11	35.54	54	18.46	Average
	2498.1	51.42	28.5	3.93	37.11	46.74	74	27.26	Peak
	2498.1	39.55	28.5	3.93	37.11	34.87	54	19.13	Average
Vertical	2323.1	49.87	28.14	3.83	37.11	44.73	74	29.27	Peak
	2323.1	38.59	28.14	3.83	37.11	33.45	54	20.55	Average
	2355.9	49.59	28.2	3.85	37.11	44.53	74	29.47	Peak
	2355.9	38.76	28.2	3.85	37.11	33.7	54	20.3	Average
	2389.7	58.77	28.27	3.85	37.11	53.78	74	20.22	Peak
	2389.7	40.98	28.27	3.85	37.11	35.99	54	18.01	Average
	2484	50.27	28.47	3.93	37.11	45.56	74	28.44	Peak
	2484	38.53	28.47	3.93	37.11	33.82	54	20.18	Average
	2492	50.01	28.49	3.93	37.11	45.32	74	28.68	Peak
	2492	38.5	28.49	3.93	37.11	33.81	54	20.19	Average
	2498.7	49.41	28.5	3.93	37.11	44.73	74	29.27	Peak
	2498.7	38.25	28.5	3.93	37.11	33.57	54	20.43	Average

802.11g

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
Horizontal	2335.2	51.67	28.16	3.83	37.11	46.55	74	27.45	Peak
	2335.2	40.46	28.16	3.83	37.11	35.34	54	18.66	Average
	2361.3	53.23	28.21	3.85	37.11	48.18	74	25.82	Peak
	2361.3	41.53	28.21	3.85	37.11	36.48	54	17.52	Average
	2390	73.19	28.27	3.85	37.11	68.2	74	5.8	Peak
	2390	55.52	28.27	3.85	37.11	50.53	54	3.47	Average
	2483.5	73.76	28.47	3.93	37.11	69.05	74	4.95	Peak
	2483.5	52.58	28.47	3.93	37.11	47.87	54	6.13	Average
	2491.7	61.37	28.49	3.93	37.11	56.68	74	17.32	Peak
	2491.7	43.24	28.49	3.93	37.11	38.55	54	15.45	Average
	2498.3	55.06	28.5	3.93	37.11	50.38	74	23.62	Peak
	2498.3	40.31	28.5	3.93	37.11	35.63	54	18.37	Average
Vertical	2320.4	49.51	28.13	3.83	37.11	44.36	74	29.64	Peak
	2320.4	37.45	28.13	3.83	37.11	32.3	54	21.7	Average
	2348.5	49.48	28.19	3.83	37.11	44.39	74	29.61	Peak
	2348.5	38.64	28.19	3.83	37.11	33.55	54	20.45	Average
	2387.1	61.3	28.27	3.85	37.11	56.31	74	17.69	Peak
	2387.1	43.33	28.27	3.85	37.11	38.34	54	15.66	Average
	2483.5	59.09	28.47	3.93	37.11	54.38	74	19.62	Peak
	2483.5	41.82	28.47	3.93	37.11	37.11	54	16.89	Average
	2489.7	53.63	28.49	3.93	37.11	48.94	74	25.06	Peak
	2489.7	39.76	28.49	3.93	37.11	35.07	54	18.93	Average
	2497.9	50.11	28.5	3.93	37.11	45.43	74	28.57	Peak
	2497.9	38.42	28.5	3.93	37.11	33.74	54	20.26	Average

802.11n20

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
Horizontal	2334.1	50.57	28.16	3.83	37.11	45.45	74	28.55	Peak
	2334.1	39.35	28.16	3.83	37.11	34.23	54	19.77	Average
	2360	51.68	28.21	3.85	37.11	46.63	74	27.37	Peak
	2360	40.37	28.21	3.85	37.11	35.32	54	18.68	Average
	2389.3	69.06	28.27	3.85	37.11	64.07	74	9.93	Peak
	2389.3	52.03	28.27	3.85	37.11	47.04	54	6.96	Average
	2484.4	73.03	28.47	3.93	37.11	68.32	74	5.68	Peak
	2484.4	49.57	28.47	3.93	37.11	44.86	54	9.14	Average
	2491.7	57.15	28.49	3.93	37.11	52.46	74	21.54	Peak
	2491.7	41.32	28.49	3.93	37.11	36.63	54	17.37	Average
	2496.5	58.12	28.5	3.93	37.11	53.44	74	20.56	Peak
	2496.5	40.42	28.5	3.93	37.11	35.74	54	18.26	Average
Vertical	2329.8	50.66	28.16	3.83	37.11	45.54	74	28.46	Peak
	2329.8	38.46	28.16	3.83	37.11	33.34	54	20.66	Average
	2359.8	50	28.21	3.85	37.11	44.95	74	29.05	Peak
	2359.8	37.61	28.21	3.85	37.11	32.56	54	21.44	Average
	2390	55.96	28.27	3.85	37.11	50.97	74	23.03	Peak
	2390	40.7	28.27	3.85	37.11	35.71	54	18.29	Average
	2483.7	55.53	28.47	3.93	37.11	50.82	74	23.18	Peak
	2483.7	38.36	28.47	3.93	37.11	33.65	54	20.35	Average
	2491.6	50.19	28.49	3.93	37.11	45.5	74	28.5	Peak
	2491.6	38.62	28.49	3.93	37.11	33.93	54	20.07	Average
	2498.6	49.6	28.5	3.93	37.11	44.92	74	29.08	Peak
	2498.6	38.33	28.5	3.93	37.11	33.65	54	20.35	Average

TEST ENGINEER: Jarey


5 6 dB BANDWIDTH MEASUREMENT

5.1 Test Equipment

The following test equipment was used during the Emission Bandwidth measurement:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
4.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2020.09.16	1 Year
5.	Coaxial Cable	WOKEN	SFL402-105F LEX	F02-150819-0 45	2020.03.08	1 Year
6.	20 dB Attenuator	Mini-Circuits	VAT-20+	001	2020.08.06	1 Year

5.2 Block Diagram of Test Setup



5.3 Specification Limits (§15.247(a)(2))

The minimum 6 dB bandwidth shall be at least 500 kHz.

5.4 Operating Condition of EUT

The switch ON/OFF was used to enable the EUT to change the channel one by one.

5.5 Test Procedure

The transmitter output was connected to the spectrum analyzer. The bandwidth of the fundamental frequency was measure by spectrum analyzer with settings: RBW = 100kHz, VBW $\geq 3 \times$ RBW.

The 6 dB bandwidth is defined as the total spectrum the power of which is lower than peak power minus 6 dB .

The test procedure is defined in ANSI C63.10-2013 (the 11.8.2 Measurement Procedure “Option 2” was used).

5.6 Test Results


PASSED.

All the test results are attached in next pages.


(Test Date: 2020.11.30 Temperature: 23°C Humidity: 51 %)

Modulation	Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit
802.11b	1	2412	8.137	500 kHz
	6	2437	8.137	500 kHz
	11	2462	8.576	500 kHz
802.11g	1	2412	16.31	500 kHz
	6	2437	16.31	500 kHz
	11	2462	15.86	500 kHz
802.11n20	1	2412	17.1	500 kHz
	6	2437	17.32	500 kHz
	11	2462	16.96	500 kHz


802.11b CH2412MHz




802.11b CH2437MHz




802.11b CH2462MHz




802.11g CH2412MHz




802.11g CH2437MHz




802.11g CH2462MHz



802.11n20 CH2412MHz



802.11n20 CH2437MHz



802.11n20 CH2462MHz



6 MAXIMUM PEAK OUTPUT POWER MEASUREMENT

6.1 Test Equipment

The following test equipment was used during the maximum peak output power measurement:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2020.09.16	1 Year
2.	Coaxial Cable	WOKEN	SFL402-105F LEX	F02-150819-0 45	2020.03.08	1 Year
3.	20 dB Attenuator	Mini-Circuits	VAT-20+	001	2020.08.06	1 Year

6.2 Block Diagram of Test Setup

The Same as Section. 5.2.

6.3 Specification Limits ((§15.247(b)(3))

The Limits of maximum Peak Output Power for digital modulation in 2400-2483.5 MHz is: 1 Watt. (30 dBm)

6.4 Operating Condition of EUT

The switch ON/OFF was used to enable the EUT to change the channel one by one.

6.5 Test Procedure

The transmitter output was connected to the spectrum analyzer.

The following procedure can be used when the maximum available RBW of the instrument is less than the DTS bandwidth:

- Set the RBW = 1 MHz.
- Set the VBW $\geq$ [3 RBW].
- Set the span $\geq$ [1.5 DTS bandwidth].
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector). If the instrument does not have a band power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS channel bandwidth

The test procedure is defined in ANSI C63.10-2013 (11.9.1.2 Measurement Procedure “ Integrated band power method” was used).

6.6 Test Results

PASSED.

All the test results are listed below.


(Test Date: 2020.11.30 Temperature: 23°C Humidity: 51 %)

Modulation	Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit
802.11b	1	2412	15.34	30 dBm
	6	2437	15.36	30 dBm
	11	2462	15.3	30 dBm
802.11g	1	2412	20.81	30 dBm
	6	2437	21.01	30 dBm
	11	2462	20.64	30 dBm
802.11n20	1	2412	20.37	30 dBm
	6	2437	20.04	30 dBm
	11	2462	20.05	30 dBm

802.11b CH2412MHz



802.11b CH2437MHz



802.11b CH2462MHz



802.11g CH2412MHz



802.11g CH2437MHz



802.11g CH2462MHz



802.11n20 CH2412MHz



802.11n20 CH2437MHz



802.11n20 CH2462MHz



7 EMISSION LIMITATIONS MEASUREMENT

7.1 Test Equipment

The following test equipment was used during the emission limitations test:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2020.09.16	1 Year
2.	Coaxial Cable	WOKEN	SFL402-105F LEX	F02-150819-045	2020.03.08	1 Year
3.	20 dB Attenuator	Mini-Circuits	VAT-20+	001	2020.08.06	1 Year

7.2 Block Diagram of Test Setup

The Same as Section. 5.2.

7.3 Specification Limits (§15.247(d))

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). (※ This test result attaching to Section. 3.7)

7.4 Operating Condition of EUT

The switch ON/OFF was used to enable the EUT to change the channel one by one.

7.5 Test Procedure

The transmitter output was connected to the spectrum analyzer.

Establish a reference level by using the following procedure:

- Set instrument center frequency to DTS channel center frequency.
 - Set the span to ≥ 1.5 times the DTS bandwidth.
 - Set the RBW = 100 kHz.
 - Set the VBW $\geq [3 \times \text{RBW}]$.
 - Detector = peak.
 - Sweep time = auto couple.
 - Trace mode = max hold.
 - Allow trace to fully stabilize.
 - Use the peak marker function to determine the maximum PSD level.
- Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

Scan up through 10th harmonic.

The test procedure is defined in ANSI C63.10-2013 (11.11.2 Reference level measurement and 11.11.3 Emission level measurement was used).

7.6 Test Results

PASSED.

The test data was attached in the next pages.

(Test Date: 2020.12.03 Temperature: 23°C Humidity: 51 %)

Modulation	Channel	Frequency (MHz)	Data Page
802.11b	1	2412 MHz	P41-42
	6	2437 MHz	P43-44
	11	2462 MHz	P45-46
802.11g	1	2412 MHz	P47-48
	6	2437 MHz	P49-50
	11	2462 MHz	P51-52
802.11n20	1	2412 MHz	P53-54
	6	2437 MHz	P55-56
	11	2462 MHz	P57-58

802.11b CH2412MHz

Reference level



Emission level






802.11b CH2437MHz

Reference level




Emission level






802.11b CH2462MHz

Reference level



Emission level







802.11g CH2412MHz

Reference level



Emission level







802.11g CH2437MHz

Reference level



Emission level





802.11g CH2462MHz

Reference level




Emission level







802.11n20 CH2412MHz

Reference level




Emission level






802.11n20 CH2437MHz

Reference level




Emission level





802.11n20 CH2462MHz

Reference level



Emission level





8 BAND EDGES MEASUREMENT

8.1 Test Equipment

The following test equipment was used during the band edges measurement:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2020.09.16	1 Year
2.	Coaxial Cable	WOKEN	SFL402-105F LEX	F02-150819-045	2020.03.08	1 Year
3.	20 dB Attenuator	Mini-Circuits	VAT-20+	001	2020.08.06	1 Year

8.2 Block Diagram of Test Setup

The Same as section. 5.2.

8.3 Specification Limits (§15.247(d))

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

8.4 Operating Condition of EUT

The switch ON/OFF was used to enable the EUT to change the channel one by one.

8.5 Test Procedure

The transmitter output was connected to the spectrum analyzer. Set RBW of Test Receiver to 100kHz and VBW to 300kHz with suitable frequency span including 100kHz bandwidth from band edge.

The test procedure is defined in ANSI C63.10-2013 (11.11.3 Emission level measurement was used).

8.6 Test Results

PASSED.

All the test results are attached in next pages.

(Test Date: 2020.12.03 Temperature: 23°C Humidity: 51 %)

Modulation	Location	Channel	Frequency (MHz)	Delta Marker (dB)	Result
802.11b	Below Band Edge	1	2412	60.196	More than 20 dB below the highest level of the desired power
	Upper Band Edge	11	2462	59.535	
802.11g	Below Band Edge	1	2412	42.174	More than 20 dB below the highest level of the desired power
	Upper Band Edge	11	2462	42.157	
802.11n20	Below Band Edge	1	2412	45.376	More than 20 dB below the highest level of the desired power
	Upper Band Edge	11	2462	47.617	

802.11b CH2412MHz (Below Edge 2390 MHz)



802.11b CH2462MHz (Upper Edge 2483.5 MHz)



802.11g CH2412MHz (Below Edge 2390 MHz)



802.11g CH2462MHz (Upper Edge 2483.5 MHz)



802.11n20 CH2412MHz (Below Edge 2390 MHz)



802.11n20 CH2462MHz (Upper Edge 2483.5 MHz)



9 POWER SPECTRAL DENSITY MEASUREMENT

9.1 Test Equipment

The following test equipment was used during the power spectral density measurement:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2020.09.16	1 Year
2.	Coaxial Cable	WOKEN	SFL402-105F LEX	F02-150819-045	2020.03.08	1 Year
3.	20 dB Attenuator	Mini-Circuits	VAT-20+	001	2020.08.06	1 Year

9.2 Block Diagram of Test Setup

The Same as section 5.2.

9.3 Specification Limits (§15.247(e))

The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band.

9.4 Operating Condition of EUT

The switch ON/OFF was used to enable the EUT to change the channel one by one.

9.5 Test Procedure

The transmitter output was connected to the spectrum analyzer.

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

The test procedure is defined in ANSI C63.10-2013 (11.10.2 Measurement Procedure “Method PKPSD (peak PSD)” was used).

9.6 Test Results

PASSED.

All the test results are attached in next pages.

(Test Date: 2020.11.30 Temperature: 23°C Humidity: 51 %)

Modulation	Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limit
802.11b	1	2412	-7.496	8 dBm
	6	2437	-8.313	8 dBm
	11	2462	-8.146	8 dBm
802.11g	1	2412	-10.479	8 dBm
	6	2437	-10.317	8 dBm
	11	2462	-9.926	8 dBm
802.11n20	1	2412	-11.004	8 dBm
	6	2437	-12.193	8 dBm
	11	2462	-10.971	8 dBm

802.11b CH2412 MHz




802.11b CH2437 MHz




802.11b CH2462 MHz




802.11g CH2412 MHz




802.11g CH2437 MHz




802.11g CH2462 MHz




802.11n20 CH2412 MHz



802.11n20 CH2437 MHz



802.11n20 CH2462 MHz



10 DEVIATION TO TEST SPECIFICATIONS

None.

11 MEASUREMENT UNCERTAINTY LIST

The measurement uncertainty was estimated for test on the EUT according to CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage of K=2.

The uncertainties value is not used in determining the PASS/FAIL results.

Test Items/Facilities	Frequency/Equipment/Unit	Uncertainty
Conducted Emission No.1 Shielded Room	9kHz~150kHz	±3.2 dB
	150kHz~30MHz	±3.1 dB
Conducted Emission No.3 Shielded Room	150kHz~30MHz	±3.1 dB
Radiated Emission	30MHz~200MHz, Horizontal	±3.4 dB
	30MHz~200MHz, Vertical	±4.0 dB
	200MHz~1000MHz, Horizontal	±3.7 dB
	200MHz~1000MHz, Vertical	±5.1 dB
	1GHz~6GHz	±5.7 dB
	6GHz~18GHz	±4.7 dB
Output Power Test	50MHz~18GHz	0.77 dB
Power Density Test	9kHz~6GHz	1.08 dB
RF Frequency Test	9kHz~40GHz	6×10^{-4}
Bandwidth Test	9kHz~6GHz	1.5×10^{-3}
RF Radiated Power Test	30MHz~1000MHz	3.06 dB
Conducted Output Power Test	50MHz~18GHz	0.83 dB
AC Voltage(<10kHz) Test	120V~230V	0.04 %
DC Power Test	0V~30V	0.4 %
Temperature	-40°C~+100°C	0.52 °C
Humidity	30%~95%	2.6 %