


## **TEST REPORT**

**Application No.:** SZEM1909018949CR  
**Applicant:** ZOBELE Instrument (Shenzhen) Co., LTD  
**Address of Applicant:** ShangNan East Road, HuangPu, XinQiao Street, Bao'an District, ShenZhen, China  
**Manufacturer:** ZOBELE Instrument (Shenzhen) Co., LTD  
**Address of Manufacturer:** The 1st, 2nd, 3rd and 4th floors of Building 16, HongTian ShangNan East Road, HuangPu Community, XinQiao Street, Bao'an District, ShenZhen (CHINA)  
**Factory:** ZOBELE Instrument (Shenzhen) Co., LTD  
**Address of Factory:** The 1st, 2nd, 3rd and 4th floors of Building 16, HongTian ShangNan East Road, HuangPu Community, XinQiao Street, Bao'an District, ShenZhen (CHINA)  
**Equipment Under Test (EUT):**  
**EUT Name:** Air freshener  
**Model No.:** RB063  
**Trade mark:** Air Wick  
**FCC ID:** 2AURX-ZISRB063  
**Standard(s) :** 47 CFR Part 15, Subpart C 15.247  
**Date of Receipt:** 2019-10-09  
**Date of Test:** 2019-10-11 to 2019-12-19  
**Date of Issue:** 2019-12-26

|                     |              |
|---------------------|--------------|
| <b>Test Result:</b> | <b>Pass*</b> |
|---------------------|--------------|

\* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu  
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

| Revision Record |         |            |          |          |
|-----------------|---------|------------|----------|----------|
| Version         | Chapter | Date       | Modifier | Remark   |
| 01              |         | 2019-12-26 |          | Original |
|                 |         |            |          |          |
|                 |         |            |          |          |

|                                 |  |                                                                                     |  |
|---------------------------------|--|-------------------------------------------------------------------------------------|--|
| <b>Authorized for issue by:</b> |  |                                                                                     |  |
|                                 |  |    |  |
|                                 |  | <hr/> <b>Calvin Weng /Project Engineer</b>                                          |  |
|                                 |  |  |  |
|                                 |  | <hr/> <b>Eric Fu /Reviewer</b>                                                      |  |

## 2 Test Summary

| Radio Spectrum Technical Requirement |                                  |        |                                                 |        |
|--------------------------------------|----------------------------------|--------|-------------------------------------------------|--------|
| Item                                 | Standard                         | Method | Requirement                                     | Result |
| Antenna Requirement                  | 47 CFR Part 15, Subpart C 15.247 | N/A    | 47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4) | Pass   |

| Radio Spectrum Matter Part                            |                                  |                                        |                                           |        |
|-------------------------------------------------------|----------------------------------|----------------------------------------|-------------------------------------------|--------|
| Item                                                  | Standard                         | Method                                 | Requirement                               | Result |
| Minimum 6dB Bandwidth                                 | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 11.8.1      | 47 CFR Part 15, Subpart C 15.247a(2)      | Pass   |
| Conducted Peak Output Power                           | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 11.9.1      | 47 CFR Part 15, Subpart C 15.247(b)(3)    | Pass   |
| Power Spectrum Density                                | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 11.10.2     | 47 CFR Part 15, Subpart C 15.247(e)       | Pass   |
| Conducted Band Edges Measurement                      | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 11.13.3.2   | 47 CFR Part 15, Subpart C 15.247(d)       | Pass   |
| Conducted Spurious Emissions                          | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 11.11       | 47 CFR Part 15, Subpart C 15.247(d)       | Pass   |
| Radiated Emissions which fall in the restricted bands | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 6.10.5      | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |
| Radiated Spurious Emissions                           | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 6.4,6.5,6.6 | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |

### 3 Contents

|                                                                 | Page      |
|-----------------------------------------------------------------|-----------|
| <b>1 COVER PAGE .....</b>                                       | <b>1</b>  |
| <b>2 TEST SUMMARY .....</b>                                     | <b>3</b>  |
| <b>3 CONTENTS .....</b>                                         | <b>4</b>  |
| <b>4 GENERAL INFORMATION .....</b>                              | <b>6</b>  |
| 4.1 DETAILS OF E.U.T. ....                                      | 6         |
| 4.2 DESCRIPTION OF SUPPORT UNITS .....                          | 6         |
| 4.3 MEASUREMENT UNCERTAINTY .....                               | 6         |
| 4.4 TEST LOCATION .....                                         | 7         |
| 4.5 TEST FACILITY .....                                         | 7         |
| 4.6 DEVIATION FROM STANDARDS .....                              | 7         |
| 4.7 ABNORMALITIES FROM STANDARD CONDITIONS .....                | 7         |
| <b>5 EQUIPMENT LIST .....</b>                                   | <b>8</b>  |
| <b>6 RADIO SPECTRUM TECHNICAL REQUIREMENT .....</b>             | <b>11</b> |
| 6.1 ANTENNA REQUIREMENT .....                                   | 11        |
| 6.1.1 Test Requirement: .....                                   | 11        |
| 6.1.2 Conclusion .....                                          | 11        |
| <b>7 RADIO SPECTRUM MATTER TEST RESULTS .....</b>               | <b>12</b> |
| 7.1 MINIMUM 6DB BANDWIDTH .....                                 | 12        |
| 7.1.1 E.U.T. Operation .....                                    | 12        |
| 7.1.2 Test Setup Diagram .....                                  | 12        |
| 7.1.3 Measurement Procedure and Data .....                      | 12        |
| 7.2 CONDUCTED PEAK OUTPUT POWER .....                           | 13        |
| 7.2.1 E.U.T. Operation .....                                    | 14        |
| 7.2.2 Test Setup Diagram .....                                  | 14        |
| 7.2.3 Measurement Procedure and Data .....                      | 14        |
| 7.3 POWER SPECTRUM DENSITY .....                                | 15        |
| 7.3.1 E.U.T. Operation .....                                    | 15        |
| 7.3.2 Test Setup Diagram .....                                  | 15        |
| 7.3.3 Measurement Procedure and Data .....                      | 15        |
| 7.4 CONDUCTED BAND EDGES MEASUREMENT .....                      | 16        |
| 7.4.1 E.U.T. Operation .....                                    | 17        |
| 7.4.2 Test Setup Diagram .....                                  | 17        |
| 7.4.3 Measurement Procedure and Data .....                      | 17        |
| 7.5 CONDUCTED SPURIOUS EMISSIONS .....                          | 18        |
| 7.5.1 E.U.T. Operation .....                                    | 19        |
| 7.5.2 Test Setup Diagram .....                                  | 19        |
| 7.5.3 Measurement Procedure and Data .....                      | 19        |
| 7.6 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS ..... | 20        |
| 7.6.1 E.U.T. Operation .....                                    | 20        |
| 7.6.2 Test Setup Diagram .....                                  | 20        |
| 7.6.3 Measurement Procedure and Data .....                      | 21        |

|       |                                               |       |
|-------|-----------------------------------------------|-------|
| 7.7   | RADIATED SPURIOUS EMISSIONS .....             | 26    |
| 7.7.1 | <i>E.U.T. Operation</i> .....                 | 27    |
| 7.7.2 | <i>Test Setup Diagram</i> .....               | 27    |
| 7.7.3 | <i>Measurement Procedure and Data</i> .....   | 28    |
| 8     | <b>PHOTOGRAPHS</b> .....                      | 37    |
| 8.1   | TEST SETUP .....                              | 37    |
| 8.2   | EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS) ..... | 37    |
| 9     | <b>APPENDIX</b> .....                         | 38    |
| 9.1   | APPENDIX 15.247 .....                         | 38-50 |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 4 General Information

### 4.1 Details of E.U.T.

|                      |                                     |
|----------------------|-------------------------------------|
| Power supply:        | DC 4.5V by 1.5V AA type battery * 3 |
| Operation Frequency: | 2402MHz to 2480MHz                  |
| Bluetooth Version:   | 5.0                                 |
| Modulation Type:     | GFSK                                |
| Number of Channels:  | 40                                  |
| Channel Spacing:     | 2MHz                                |
| Antenna Type:        | PCB antenna                         |
| Antenna Gain:        | 1.26dBi                             |

### 4.2 Description of Support Units

The EUT has been tested as an independent unit.

### 4.3 Measurement Uncertainty

| No. | Item                            | Measurement Uncertainty         |
|-----|---------------------------------|---------------------------------|
| 1   | Radio Frequency                 | $\pm 7.25 \times 10^{-8}$       |
| 2   | Duty cycle                      | $\pm 0.37\%$                    |
| 3   | Occupied Bandwidth              | $\pm 3\%$                       |
| 4   | RF conducted power              | $\pm 0.75\text{dB}$             |
| 5   | RF power density                | $\pm 2.84\text{dB}$             |
| 6   | Conducted Spurious emissions    | $\pm 0.75\text{dB}$             |
| 7   | RF Radiated power               | $\pm 4.5\text{dB}$ (Below 1GHz) |
| 8   |                                 | $\pm 4.8\text{dB}$ (Above 1GHz) |
| 9   | Radiated Spurious emission test | $\pm 4.5\text{dB}$ (Below 1GHz) |
|     |                                 | $\pm 4.8\text{dB}$ (Above 1GHz) |
|     | Temperature test                | $\pm 1^\circ\text{C}$           |
| 10  | Humidity test                   | $\pm 3\%$                       |
| 11  | Supply voltages                 | $\pm 1.5\%$                     |
| 12  | Time                            | $\pm 3\%$                       |

#### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

#### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

#### 4.6 Deviation from Standards

None

#### 4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch / Shenzhen EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 5 Equipment List

| Minimum 6dB Bandwidth |                      |                         |              |            |              |
|-----------------------|----------------------|-------------------------|--------------|------------|--------------|
| Equipment             | Manufacturer         | Model No                | Inventory No | Cal Date   | Cal Due Date |
| Shielding Room        | SAEMC                | MSR733                  | SEM001-09    | 2019-06-13 | 2022-06-12   |
| DC Power Supply       | Zhao Xin             | KXN-6020D               | SEM011-08    | 2019-09-24 | 2020-09-23   |
| Spectrum Analyzer     | Rohde & Schwarz      | FSP                     | SEM004-06    | 2019-09-24 | 2020-09-23   |
| Measurement Software  | JS Tonscend          | JS1120-2<br>BT/WIFI V2. | N/A          | N/A        | N/A          |
| Coaxial Cable         | SGS                  | N/A                     | SEM031-02    | 2019-07-11 | 2020-07-10   |
| Attenuator            | Weinschel Associates | WA41                    | SEM021-09    | N/A        | N/A          |

| Conducted Peak Output Power |                      |                         |              |            |              |
|-----------------------------|----------------------|-------------------------|--------------|------------|--------------|
| Equipment                   | Manufacturer         | Model No                | Inventory No | Cal Date   | Cal Due Date |
| Shielding Room              | SAEMC                | MSR733                  | SEM001-09    | 2019-06-13 | 2022-06-12   |
| DC Power Supply             | Zhao Xin             | KXN-6020D               | SEM011-08    | 2019-09-24 | 2020-09-23   |
| Spectrum Analyzer           | Rohde & Schwarz      | FSP                     | SEM004-06    | 2019-09-24 | 2020-09-23   |
| Measurement Software        | JS Tonscend          | JS1120-2<br>BT/WIFI V2. | N/A          | N/A        | N/A          |
| Coaxial Cable               | SGS                  | N/A                     | SEM031-02    | 2019-07-11 | 2020-07-10   |
| Attenuator                  | Weinschel Associates | WA41                    | SEM021-09    | N/A        | N/A          |

| Power Spectrum Density |                      |                         |              |            |              |
|------------------------|----------------------|-------------------------|--------------|------------|--------------|
| Equipment              | Manufacturer         | Model No                | Inventory No | Cal Date   | Cal Due Date |
| Shielding Room         | SAEMC                | MSR733                  | SEM001-09    | 2019-06-13 | 2022-06-12   |
| DC Power Supply        | Zhao Xin             | KXN-6020D               | SEM011-08    | 2019-09-24 | 2020-09-23   |
| Spectrum Analyzer      | Rohde & Schwarz      | FSP                     | SEM004-06    | 2019-09-24 | 2020-09-23   |
| Measurement Software   | JS Tonscend          | JS1120-2<br>BT/WIFI V2. | N/A          | N/A        | N/A          |
| Coaxial Cable          | SGS                  | N/A                     | SEM031-02    | 2019-07-11 | 2020-07-10   |
| Attenuator             | Weinschel Associates | WA41                    | SEM021-09    | N/A        | N/A          |

| Conducted Band Edges Measurement |                      |                         |              |            |              |
|----------------------------------|----------------------|-------------------------|--------------|------------|--------------|
| Equipment                        | Manufacturer         | Model No                | Inventory No | Cal Date   | Cal Due Date |
| Shielding Room                   | SAEMC                | MSR733                  | SEM001-09    | 2019-06-13 | 2022-06-12   |
| DC Power Supply                  | Zhao Xin             | KXN-6020D               | SEM011-08    | 2019-09-24 | 2020-09-23   |
| Spectrum Analyzer                | Rohde & Schwarz      | FSP                     | SEM004-06    | 2019-09-24 | 2020-09-23   |
| Measurement Software             | JS Tonscend          | JS1120-2<br>BT/WIFI V2. | N/A          | N/A        | N/A          |
| Coaxial Cable                    | SGS                  | N/A                     | SEM031-02    | 2019-07-11 | 2020-07-10   |
| Attenuator                       | Weinschel Associates | WA41                    | SEM021-09    | N/A        | N/A          |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)  
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

|                  |          |        |           |            |            |
|------------------|----------|--------|-----------|------------|------------|
| Signal Generator | KEYSIGHT | N5173B | SEM006-05 | 2019-09-24 | 2020-09-23 |
|------------------|----------|--------|-----------|------------|------------|

## Conducted Spurious Emissions

| Equipment            | Manufacturer         | Model No                | Inventory No | Cal Date   | Cal Due Date |
|----------------------|----------------------|-------------------------|--------------|------------|--------------|
| Shielding Room       | SAEMC                | MSR733                  | SEM001-09    | 2019-06-13 | 2022-06-12   |
| DC Power Supply      | Zhao Xin             | KXN-6020D               | SEM011-08    | 2019-09-24 | 2020-09-23   |
| Spectrum Analyzer    | Rohde & Schwarz      | FSP                     | SEM004-06    | 2019-09-24 | 2020-09-23   |
| Measurement Software | JS Tonscend          | JS1120-2<br>BT/WIFI V2. | N/A          | N/A        | N/A          |
| Coaxial Cable        | SGS                  | N/A                     | SEM031-02    | 2019-07-11 | 2020-07-10   |
| Attenuator           | Weinschel Associates | WA41                    | SEM021-09    | N/A        | N/A          |
| Signal Generator     | KEYSIGHT             | N5173B                  | SEM006-05    | 2019-09-24 | 2020-09-23   |

## Radiated Emissions which fall in the restricted bands

| Equipment                   | Manufacturer                       | Model No        | Inventory No | Cal Date   | Cal Due Date |
|-----------------------------|------------------------------------|-----------------|--------------|------------|--------------|
| 3m Semi-Anechoic Chamber    | AUDIX                              | N/A             | SEM001-02    | 2018-03-13 | 2021-03-12   |
| Measurement Software        | AUDIX                              | e3 V8.2014-6-27 | N/A          | N/A        | N/A          |
| Coaxial Cable               | SGS                                | N/A             | SEM026-01    | 2019-07-11 | 2020-07-10   |
| EXA Spectrum Analyzer       | Agilent Technologies Inc           | N9010A          | SEM004-12    | 2019-04-12 | 2020-04-11   |
| Horn Antenna (1-18GHz)      | Rohde & Schwarz                    | HF907           | SEM003-07    | 2018-04-13 | 2021-04-12   |
| Horn Antenna (15GHz-40GHz)  | Schwarzbeck                        | BBHA 9170       | SEM003-15    | 2017-10-17 | 2020-10-16   |
| Pre-Amplifier (0.1-26.5GHz) | Compliance Directions Systems Inc. | PAP-0126        | SEM004-11    | 2019-09-24 | 2020-09-23   |
| Pre-amplifier (18-26GHz)    | Rohde & Schwarz                    | CH14-H052       | SEM005-17    | 2019-04-01 | 2020-03-31   |
| Pre-amplifier (26GHz-40GHz) | Compliance Directions Systems Inc. | PAP-2640-50     | SEM005-08    | 2019-04-01 | 2020-03-31   |
| DC Power Supply             | Zhao Xin                           | KXN-6020D       | SEM011-08    | 2019-09-24 | 2020-09-23   |
| Active Loop Antenna         | ETS-Lindgren                       | 6502            | SEM003-08    | 2017-08-22 | 2020-08-21   |

## RE in Chamber

| Test Equipment            | Manufacturer | Model No.       | Inventory No. | Cal. Date  | Cal. Due date |
|---------------------------|--------------|-----------------|---------------|------------|---------------|
| 10m Semi-Anechoic Chamber | SAEMC        | FSAC1018        | SEM001-03     | 2018-03-31 | 2021-03-30    |
| Measurement Software      | AUDIX        | e3 V8.2014-6-27 | N/A           | N/A        | N/A           |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: [CN.Doocheck@sgs.com](mailto:CN.Doocheck@sgs.com)  
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

|                                      |                                    |                 |           |            |            |
|--------------------------------------|------------------------------------|-----------------|-----------|------------|------------|
| Coaxial Cable                        | SGS                                | N/A             | SEM029-01 | 2019-07-11 | 2020-07-10 |
| EMI Test Receiver (9kHz-7GHz)        | Rohde & Schwarz                    | ESR             | SEM004-03 | 2019-04-01 | 2020-03-31 |
| Trilog-Broadband Antenna(30MHz-1GHz) | Schwarzbeck                        | VULB9168        | SEM003-18 | 2019-08-08 | 2022-08-07 |
| Pre-amplifier                        | Sonoma Instrument Co               | 310N            | SEM005-04 | 2019-04-12 | 2020-04-11 |
| 3m Semi-Anechoic Chamber             | AUDIX                              | N/A             | SEM001-02 | 2018-03-13 | 2021-03-12 |
| Measurement Software                 | AUDIX                              | e3 V8.2014-6-27 | N/A       | N/A        | N/A        |
| Coaxial Cable                        | SGS                                | N/A             | SEM026-01 | 2019-07-11 | 2020-07-10 |
| EXA Spectrum Analyzer                | AgilentTechnologies Inc            | N9010A          | SEM004-12 | 2019-04-12 | 2020-04-11 |
| Horn Antenna (1-18GHz)               | Rohde & Schwarz                    | HF907           | SEM003-07 | 2018-04-13 | 2021-04-12 |
| Horn Antenna (15GHz-40GHz)           | Schwarzbeck                        | BBHA 9170       | SEM003-15 | 2017-10-17 | 2020-10-16 |
| Pre-Amplifier (0.1-26.5GHz)          | Compliance Directions Systems Inc. | PAP-0126        | SEM004-11 | 2019-09-24 | 2020-09-23 |
| Pre-amplifier (18-26GHz)             | Rohde & Schwarz                    | CH14-H052       | SEM005-17 | 2019-04-01 | 2020-03-31 |
| Pre-amplifier (26GHz-40GHz)          | Compliance Directions Systems Inc. | PAP-2640-50     | SEM005-08 | 2019-04-01 | 2020-03-31 |
| DC Power Supply                      | Zhao Xin                           | KXN-6020D       | SEM011-08 | 2019-09-24 | 2020-09-23 |
| Active Loop Antenna                  | ETS-Lindgren                       | 6502            | SEM003-08 | 2017-08-22 | 2020-08-21 |

## General used equipment

| Equipment                       | Manufacturer                              | Model No | Inventory No | Cal Date   | Cal Due Date |
|---------------------------------|-------------------------------------------|----------|--------------|------------|--------------|
| Humidity/ Temperature Indicator | Shanghai Meteorological Industry Factory  | ZJ1-2B   | SEM002-03    | 2019-09-26 | 2020-09-25   |
| Humidity/ Temperature Indicator | Shanghai Meteorological Industry Factory  | ZJ1-2B   | SEM002-04    | 2019-09-26 | 2020-09-25   |
| Humidity/ Temperature Indicator | Mingle                                    | N/A      | SEM002-08    | 2019-09-26 | 2020-09-25   |
| Barometer                       | Changchun Meteorological Industry Factory | DYM3     | SEM002-01    | 2019-04-04 | 2020-04-03   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: [CN.Dorochack@sgs.com](mailto:CN.Dorochack@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch, Inspection & Testing Services Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.26dBi.

Antenna location: Refer to Internal photos



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch / 深圳分公司 / 实验室

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 7 Radio Spectrum Matter Test Results

### 7.1 Minimum 6dB Bandwidth


Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)  
Test Method: ANSI C63.10 (2013) Section 11.8.1  
Limit:  $\geq 500$  kHz

#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25.6 °C Humidity: 43.4 % RH Atmospheric Pressure: 1015 mbar  
Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with GFSK modulation

#### 7.1.2 Test Setup Diagram



#### 7.1.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.2 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)  
Test Method: ANSI C63.10 (2013) Section 11.9.1  
Limit:


| Frequency range(MHz) | Output power of the intentional radiator(watt)         |
|----------------------|--------------------------------------------------------|
| 902-928              | 1 for $\geq 50$ hopping channels                       |
|                      | 0.25 for $25 \leq$ hopping channels $< 50$             |
|                      | 1 for digital modulation                               |
| 2400-2483.5          | 1 for $\geq 75$ non-overlapping hopping channels       |
|                      | 0.125 for all other frequency hopping systems          |
|                      | 1 for digital modulation                               |
| 5725-5850            | 1 for frequency hopping systems and digital modulation |

### 7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 25.6 °C Humidity: 43.4 % RH Atmospheric Pressure: 1015 mbar  
Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with GFSK modulation

### 7.2.2 Test Setup Diagram



### 7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247


### 7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)  
Test Method: ANSI C63.10 (2013) Section 11.10.2  
Limit:  $\leq 8\text{dBm}$  in any 3 kHz band during any time interval of continuous transmission

#### 7.3.1 E.U.T. Operation

Operating Environment:  
Temperature: 25.6 °C Humidity: 43.4 % RH Atmospheric Pressure: 1015 mbar  
Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with GFSK modulation

#### 7.3.2 Test Setup Diagram



#### 7.3.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



#### **7.4 Conducted Band Edges Measurement**

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement | 47 CFR Part 15, Subpart C 15.247(d)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Test Method:     | ANSI C63.10 (2013) Section 11.13.3.2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Limit:           | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)) |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


### 7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 25.6 °C Humidity: 43.3 % RH Atmospheric Pressure: 1015 mbar

Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with GFSK modulation

### 7.4.2 Test Setup Diagram



### 7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11


Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))

### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 25.6 °C Humidity: 43.3 % RH Atmospheric Pressure: 1015 mbar  
Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with GFSK modulation

### 7.5.2 Test Setup Diagram



### 7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209  
Test Method: ANSI C63.10 (2013) Section 6.10.5  
Measurement Distance: 3m  
Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| 0.009-0.490    | 2400/F(kHz)                      | 300                          |
| 0.490-1.705    | 24000/F(kHz)                     | 30                           |
| 1.705-30.0     | 30                               | 30                           |
| 30-88          | 100                              | 3                            |
| 88-216         | 150                              | 3                            |
| 216-960        | 200                              | 3                            |
| Above 960      | 500                              | 3                            |


Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 20.6 °C Humidity: 58 % RH Atmospheric Pressure: 1015 mbar  
Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with GFSK modulation

### 7.6.2 Test Setup Diagram




### 7.6.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.


Mode:a; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 18949CR  
Mode : 2402 Band edge  
Note : BLE

|     | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark |
|-----|----------|------------|------------|---------------|------------|--------|------------|------------|--------|
|     | MHz      | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1   | 2338.565 | 5.40       | 28.43      | 40.95         | 48.92      | 41.80  | 74.00      | -32.20     | peak   |
| 2   | 2390.000 | 5.47       | 28.52      | 40.97         | 47.68      | 40.70  | 74.00      | -33.30     | peak   |
| 3 * | 2402.000 | 5.49       | 28.54      | 40.98         | 93.61      | 86.66  | 74.00      | 12.66      | peak   |


Mode:a; Polarization:Vertical; Modulation:GFSK; ; Channel:Low



Site : chamber  
Condition: 3m VERTICAL  
Job No : 18949CR  
Mode : 2402 Band edge  
Note : BLE

|     | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over   | Remark |
|-----|----------|------------|------------|---------------|------------|--------|--------|--------|--------|
|     | MHz      | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m | dB     |        |
| 1   | 2322.860 | 5.38       | 28.40      | 40.94         | 48.28      | 41.12  | 74.00  | -32.88 | peak   |
| 2   | 2390.000 | 5.47       | 28.52      | 40.97         | 46.06      | 39.08  | 74.00  | -34.92 | peak   |
| 3 * | 2402.000 | 5.49       | 28.54      | 40.98         | 85.71      | 78.76  | 74.00  | 4.76   | peak   |

Mode:a; Polarization:Horizontal; Modulation:GFSK; ; Channel:High



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 18949CR  
Mode : 2480 Band edge  
Note : BLE

|              | Cable | Ant    | Preamp | Read  |        | Limit  | Over   |        |
|--------------|-------|--------|--------|-------|--------|--------|--------|--------|
| Freq         | Loss  | Factor | Factor | Level | Level  | Line   | Limit  | Remark |
| MHz          | dB    | dB/m   | dB     | dBuV  | dBuV/m | dBuV/m | dB     |        |
| 1 * 2480.000 | 5.59  | 28.67  | 41.01  | 95.31 | 88.56  | 74.00  | 14.56  | peak   |
| 2 2483.500   | 5.60  | 28.67  | 41.01  | 56.66 | 49.92  | 74.00  | -24.08 | peak   |
| 3 2483.821   | 5.60  | 28.67  | 41.01  | 55.78 | 49.04  | 74.00  | -24.96 | peak   |




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode:a; Polarization:Vertical; Modulation:GFSK; ; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 18949CR  
Mode : 2480 Band edge  
Note : BLE

|     |          | Cable | Ant    | Preamp | Read  |        | Limit  | Over   |        |
|-----|----------|-------|--------|--------|-------|--------|--------|--------|--------|
|     | Freq     | Loss  | Factor | Factor | Level | Level  | Line   | Limit  | Remark |
|     | MHz      | dB    | dB/m   | dB     | dBuV  | dBuV/m | dBuV/m | dB     |        |
| 1 * | 2480.000 | 5.59  | 28.67  | 41.01  | 90.08 | 83.33  | 74.00  | 9.33   | peak   |
| 2   | 2483.500 | 5.60  | 28.67  | 41.01  | 50.31 | 43.57  | 74.00  | -30.43 | peak   |
| 3   | 2483.871 | 5.60  | 28.67  | 41.01  | 51.16 | 44.42  | 74.00  | -29.58 | peak   |



## 7.7 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209  
Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6  
Measurement Distance: 3m for frequency above 1GHz, 10m for frequency below 1GHz  
Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| 0.009-0.490    | 2400/F(kHz)                      | 300                          |
| 0.490-1.705    | 24000/F(kHz)                     | 30                           |
| 1.705-30.0     | 30                               | 30                           |
| 30-88          | 100                              | 3                            |
| 88-216         | 150                              | 3                            |
| 216-960        | 200                              | 3                            |
| Above 960      | 500                              | 3                            |

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

For frequency from 30MHz to 1GHz, test was conducted at 10meters, therefore, a convert factor of  $20 \cdot \log(10/3)$  is taken into consideration. Therefore, limit at 10 meters is as below:

| Frequency(MHz) | Field strength(dBuV/m) | Measurement distance(meters) |
|----------------|------------------------|------------------------------|
| 30-88          | 29.5                   | 10                           |
| 88-216         | 33.0                   | 10                           |
| 216-960        | 35.5                   | 10                           |
| Above 960      | 43.5                   | 10                           |




### 7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 45 % RH Atmospheric Pressure: 1015 mbar  
Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with GFSK modulation

### 7.7.2 Test Setup Diagram



### 7.7.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


#### Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the middle channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

30MHz~1GHz

QP value:

Mode: a; Polarization: Horizontal




Condition: 10m HORIZONTAL

Job No. : 18949CR

Test Mode: a

|      |         | Ant    | Preamp | Cable | Read  |        | Limit  | Over   |        |
|------|---------|--------|--------|-------|-------|--------|--------|--------|--------|
|      | Freq    | Factor | Factor | Loss  | Level | Level  | Line   | Limit  | Remark |
|      | MHz     | dB/m   | dB     | dB    | dBuV  | dBuV/m | dBuV/m | dB     |        |
| 1    | 42.600  | 20.37  | 32.44  | 0.94  | 26.91 | 15.78  | 29.50  | -13.72 | QP     |
| 2    | 70.090  | 17.57  | 32.39  | 1.08  | 26.06 | 12.32  | 29.50  | -17.18 | QP     |
| 3    | 150.011 | 20.20  | 32.30  | 1.47  | 27.05 | 16.42  | 33.00  | -16.58 | QP     |
| 4    | 467.235 | 23.67  | 32.35  | 2.78  | 27.41 | 21.51  | 35.50  | -13.99 | QP     |
| 5    | 647.386 | 26.45  | 32.14  | 3.20  | 27.28 | 24.79  | 35.50  | -10.71 | QP     |
| 6 pp | 851.035 | 28.71  | 31.71  | 3.40  | 28.18 | 28.58  | 35.50  | -6.92  | QP     |

Mode: a; Polarization: Vertical



Condition: 10m VERTICAL


Job No. : 18949CR

Test Mode: a

|      | Freq    | Ant Factor | Preamp Factor | Cable Loss | Read Level | Level  | Limit Line | Over Limit | Remark |
|------|---------|------------|---------------|------------|------------|--------|------------|------------|--------|
|      | MHz     |            | dB/m          | dB         | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1    | 46.016  | 20.50      | 32.45         | 0.96       | 25.91      | 14.92  | 29.50      | -14.58     | QP     |
| 2    | 72.847  | 16.69      | 32.38         | 1.10       | 26.38      | 11.79  | 29.50      | -17.71     | QP     |
| 3    | 160.909 | 19.75      | 32.30         | 1.50       | 25.96      | 14.91  | 33.00      | -18.09     | QP     |
| 4    | 457.507 | 23.58      | 32.32         | 2.74       | 26.20      | 20.20  | 35.50      | -15.30     | QP     |
| 5    | 642.861 | 26.36      | 32.13         | 3.19       | 26.57      | 23.99  | 35.50      | -11.51     | QP     |
| 6 pp | 851.035 | 28.71      | 31.71         | 3.40       | 26.93      | 27.33  | 35.50      | -8.17      | QP     |

Above 1GHz


Mode:a; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 18949CR  
Mode : 2402 TX RSE  
Note : BLE

|   | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|----------|------------|------------|---------------|------------|--------|------------|------------|--------|
|   | MHz      | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 1525.000 | 5.45       | 25.91      | 40.52         | 46.52      | 37.36  | 74.00      | -36.64     | peak   |
| 2 | 4405.090 | 7.46       | 33.60      | 42.48         | 47.21      | 45.79  | 74.00      | -28.21     | peak   |
| 3 | 4804.000 | 7.89       | 34.16      | 42.77         | 47.23      | 46.51  | 74.00      | -27.49     | peak   |
| 4 | 6954.852 | 10.25      | 36.38      | 41.71         | 46.40      | 51.32  | 74.00      | -22.68     | peak   |
| 5 | 7206.000 | 10.08      | 36.42      | 41.58         | 45.39      | 50.31  | 74.00      | -23.69     | peak   |
| 6 | 9608.000 | 10.75      | 37.52      | 38.57         | 39.85      | 49.55  | 74.00      | -24.45     | peak   |


Mode:a; Polarization:Vertical; Modulation:GFSK; ; Channel:Low



Site : chamber  
Condition: 3m VERTICAL  
Job No : 18949CR  
Mode : 2402 TX RSE  
Note : BLE

|   | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|----------|------------|------------|---------------|------------|--------|------------|------------|--------|
|   | MHz      | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 1547.199 | 5.42       | 26.02      | 40.54         | 46.32      | 37.22  | 74.00      | -36.78     | peak   |
| 2 | 3790.361 | 6.77       | 33.04      | 41.98         | 47.79      | 45.62  | 74.00      | -28.38     | peak   |
| 3 | 4804.000 | 7.89       | 34.16      | 42.77         | 46.03      | 45.31  | 74.00      | -28.69     | peak   |
| 4 | 6621.375 | 11.19      | 35.45      | 41.88         | 46.82      | 51.58  | 74.00      | -22.42     | peak   |
| 5 | 7206.000 | 10.08      | 36.42      | 41.58         | 45.35      | 50.27  | 74.00      | -23.73     | peak   |
| 6 | 9608.000 | 10.75      | 37.52      | 38.57         | 39.59      | 49.29  | 74.00      | -24.71     | peak   |


Mode:a; Polarization:Horizontal; Modulation:GFSK; ; Channel:Middle



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 18949CR  
Mode : 2440 TX RSE  
Note : BLE

|   | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level | Limit Line | Over Limit | Remark |
|---|----------|------------|------------|---------------|------------|-------|------------|------------|--------|
|   | MHz      | dB         |            | dB/m          | dB         | dBuV  | dBuV/m     | dBuV/m     | dB     |
| 1 | 1620.431 | 5.32       | 26.34      | 40.58         | 46.05      | 37.13 | 74.00      | -36.87     | peak   |
| 2 | 3879.027 | 6.86       | 33.28      | 42.06         | 47.00      | 45.08 | 74.00      | -28.92     | peak   |
| 3 | 4882.000 | 7.97       | 34.30      | 42.82         | 46.77      | 46.22 | 74.00      | -27.78     | peak   |
| 4 | 6954.852 | 10.25      | 36.38      | 41.71         | 45.93      | 50.85 | 74.00      | -23.15     | peak   |
| 5 | 7323.000 | 10.05      | 36.37      | 41.52         | 44.58      | 49.48 | 74.00      | -24.52     | peak   |
| 6 | 9764.000 | 10.82      | 37.55      | 38.34         | 40.95      | 50.98 | 74.00      | -23.02     | peak   |


Mode:a; Polarization:Vertical; Modulation:GFSK; ; Channel:Middle



Site : chamber  
Condition: 3m VERTICAL  
Job No : 18949CR  
Mode : 2440 TX RSE  
Note : BLE

|   | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|----------|------------|------------|---------------|------------|--------|------------|------------|--------|
|   | MHz      | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 1615.754 | 5.33       | 26.32      | 40.58         | 45.96      | 37.03  | 74.00      | -36.97     | peak   |
| 2 | 3812.336 | 6.79       | 33.10      | 42.00         | 47.72      | 45.61  | 74.00      | -28.39     | peak   |
| 3 | 4882.000 | 7.97       | 34.30      | 42.82         | 45.58      | 45.03  | 74.00      | -28.97     | peak   |
| 4 | 6488.754 | 11.52      | 35.09      | 41.96         | 46.85      | 51.50  | 74.00      | -22.50     | peak   |
| 5 | 7323.000 | 10.05      | 36.37      | 41.52         | 44.40      | 49.30  | 74.00      | -24.70     | peak   |
| 6 | 9764.000 | 10.82      | 37.55      | 38.34         | 40.54      | 50.57  | 74.00      | -23.43     | peak   |


Mode:a; Polarization:Horizontal; Modulation:GFSK; ; Channel:High



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 18949CR  
Mode : 2480 TX RSE  
Note : BLE

|      |          | Cable | Ant    | Preamp | Read  |        | Limit  | Over   |        |
|------|----------|-------|--------|--------|-------|--------|--------|--------|--------|
| Freq |          | Loss  | Factor | Factor | Level | Level  | Line   | Limit  | Remark |
| MHz  |          | dB    | dB/m   | dB     | dBuV  | dBuV/m | dBuV/m | dB     |        |
| 1    | 1460.295 | 5.35  | 25.64  | 40.48  | 45.66 | 36.17  | 74.00  | -37.83 | peak   |
| 2    | 4443.453 | 7.50  | 33.60  | 42.51  | 46.82 | 45.41  | 74.00  | -28.59 | peak   |
| 3    | 4960.000 | 8.05  | 34.43  | 42.87  | 44.85 | 44.46  | 74.00  | -29.54 | peak   |
| 4    | 6717.762 | 10.91 | 35.72  | 41.83  | 47.91 | 52.71  | 74.00  | -21.29 | peak   |
| 5    | 7440.000 | 10.02 | 36.32  | 41.46  | 44.08 | 48.96  | 74.00  | -25.04 | peak   |
| 6    | 9920.000 | 10.90 | 37.58  | 38.12  | 39.76 | 50.12  | 74.00  | -23.88 | peak   |

Mode:a; Polarization:Vertical; Modulation:GFSK; ; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 18949CR  
Mode : 2480 TX RSE  
Note : BLE

|   | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|----------|------------|------------|---------------|------------|--------|------------|------------|--------|
|   | MHz      | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 1629.825 | 5.31       | 26.38      | 40.59         | 44.99      | 36.09  | 74.00      | -37.91     | peak   |
| 2 | 4430.628 | 7.48       | 33.60      | 42.50         | 47.04      | 45.62  | 74.00      | -28.38     | peak   |
| 3 | 4960.000 | 8.05       | 34.43      | 42.87         | 46.54      | 46.15  | 74.00      | -27.85     | peak   |
| 4 | 6934.778 | 10.31      | 36.32      | 41.72         | 46.63      | 51.54  | 74.00      | -22.46     | peak   |
| 5 | 7440.000 | 10.02      | 36.32      | 41.46         | 45.27      | 50.15  | 74.00      | -23.85     | peak   |
| 6 | 9920.000 | 10.90      | 37.58      | 38.12         | 38.30      | 48.66  | 74.00      | -25.34     | peak   |



## 8 Photographs

### 8.1 Test Setup

Refer to Setup Photos

### 8.2 EUT Constructional Details (EUT Photos)

Refer to EUT external and internal photos



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)



## 9 Appendix

### 9.1 Appendix 15.247


#### 1.6dB Bandwidth

| Test Mode | Test Channel | Ant  | EBW[MHz] | Limit[MHz] | Verdict |
|-----------|--------------|------|----------|------------|---------|
| BLE       | 2402         | Ant1 | 0.702    | $\geq 0.5$ | PASS    |
| BLE       | 2440         | Ant1 | 0.711    | $\geq 0.5$ | PASS    |
| BLE       | 2480         | Ant1 | 0.702    | $\geq 0.5$ | PASS    |





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 6dB Bandwidth\_BLE\_2402\_Ant1



### 6dB Bandwidth\_BLE\_2440\_Ant1








**2.Maximum peak conducted output power**

| Test Mode | Test Channel | Ant  | Power[dBm] | Limit[dBm] | Verdict |
|-----------|--------------|------|------------|------------|---------|
| BLE       | 2402         | Ant1 | 1.01       | <30        | PASS    |
| BLE       | 2440         | Ant1 | 1.06       | <30        | PASS    |
| BLE       | 2480         | Ant1 | 1          | <30        | PASS    |









### 3.Maximum Peak power spectral density


| Test Mode | Test Channel | Ant  | PSD[dBm/3kHz] | Limit[dBm/3kHz] | Verdict |
|-----------|--------------|------|---------------|-----------------|---------|
| BLE       | 2402         | Ant1 | -15.38        | <8.00           | PASS    |
| BLE       | 2440         | Ant1 | -15.37        | <8.00           | PASS    |
| BLE       | 2480         | Ant1 | -15.47        | <8.00           | PASS    |

### Maximum Peak power spectral density\_BLE\_2402\_Ant1



### Maximum Peak power spectral density\_BLE\_2440\_Ant1







#### 4. Band-edge for RF Conducted Emissions

| Test Mode | Test Channel | Ant  | Carrier Power[dBm] | Max. Spurious Level [dBm] | Limit [dBm] | Verdict |
|-----------|--------------|------|--------------------|---------------------------|-------------|---------|
| BLE       | 2402         | Ant1 | 0.210              | -52.622                   | <-19.79     | PASS    |
| BLE       | 2480         | Ant1 | -0.040             | -53.876                   | <-20.04     | PASS    |

### Band-edge for RF Conducted Emissions\_BLE\_2402\_Ant1



### Band-edge for RF Conducted Emissions\_BLE\_2480\_Ant1



## 5.RF Conducted Spurious Emissions

| Test Mode | Test Channel | StartFre [MHz] | StopFre [MHz] | RBW [kHz] | VBW [kHz] | Pref[dBm] | Max. Level [dBm] | Limit [dBm] | Verdict |
|-----------|--------------|----------------|---------------|-----------|-----------|-----------|------------------|-------------|---------|
| BLE       | 2402         | 30             | 10000         | 1000      | 3000      | 0.27      | -37.230          | <-19.73     | PASS    |
| BLE       | 2402         | 10000          | 25000         | 1000      | 3000      | 0.27      | -54.700          | <-19.73     | PASS    |
| BLE       | 2440         | 30             | 10000         | 1000      | 3000      | 0.32      | -36.250          | <-19.68     | PASS    |
| BLE       | 2440         | 10000          | 25000         | 1000      | 3000      | 0.32      | -53.760          | <-19.68     | PASS    |
| BLE       | 2480         | 30             | 10000         | 1000      | 3000      | 0.14      | -36.790          | <-19.86     | PASS    |
| BLE       | 2480         | 10000          | 25000         | 1000      | 3000      | 0.14      | -54.590          | <-19.86     | PASS    |




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch


No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

### RF Conducted Spurious Emissions\_BLE\_2402\_Ant1

Pref



CSE\_1




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

CSE\_2




RF Conducted Spurious Emissions\_BLE\_2440\_Ant1


Pref



CSE\_1




CSE\_2




RF Conducted Spurious Emissions\_BLE\_2480\_Ant1




Pref



CSE\_1



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



- End of the Report -