



PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.pctestlab.com>



MEASUREMENT REPORT FCC Part 15C

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Yeongtong-gu
Suwon-city, Gyeonggi-do, 443-803
Republic of Korea

Date of Testing:

2/27-3/15/2013

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0Y1302270363.A3L

FCC ID: A3LEPP100IJWU

IC CERTIFICATION NO.: 649E-EPP100IJWU

APPLICANT: Samsung Electronics Co., Ltd.

Application Type:

Certification

EUT Type:

Wireless Charging Pad

Model(s):

EP-P100IJWU

FCC Rule Part(s):

FCC Part 15 Subpart C

IC Specification(s):

RSS-Gen Issue 3

FCC Classification:


Part 15 Low Power Transmitter Below 1705 kHz (DCD)

Test Procedure:

ANSI C63.4-2009

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C-63.4-2009. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortanez
President




FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager	
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 1 of 26	

TABLE OF CONTENTS

FCC Class B MEASUREMENT REPORT	3
1.0 INTRODUCTION	4
1.1 SCOPE	4
1.2 PCTEST TEST LOCATION	4
2.0 PRODUCT INFORMATION	5
2.1 EQUIPMENT DESCRIPTION	5
2.2 DEVICE CAPABILITIES	5
2.3 TEST CONFIGURATION	5
2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS	5
2.5 LABELING REQUIREMENTS	5
3.0 DESCRIPTION OF TEST	6
3.1 EVALUATION PROCEDURE	6
3.2 AC LINE CONDUCTED EMISSIONS	6
3.3 RADIATED EMISSIONS	7
4.0 SAMPLE CALCULATIONS	8
4.1 CONDUCTED EMISSION MEASUREMENT SAMPLE CALCULATION	8
4.2 RADIATED EMISSION MEASUREMENT SAMPLE CALCULATION	8
5.0 TEST EQUIPMENT CALIBRATION DATA	9
6.0 ENVIRONMENTAL CONDITIONS	10
7.0 TEST DATA	11
7.1 SUMMARY	11
7.2 20DB BANDWIDTH MEASUREMENT	12
7.3 IN-BAND RADIATED SPURIOUS EMISSION MEASUREMENTS	13
7.4 RADIATED MEASUREMENT DATA	14
7.5 LINE CONDUCTED MEASUREMENT DATA	18
8.0 CONCLUSION	26

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 2 of 26



MEASUREMENT REPORT

FCC Part 15C – Intentional Radiators



§ 2.1033 General Information

APPLICANT: Samsung Electronics Co., Ltd.

APPLICANT ADDRESS: 129, Samsung-ro, Yeongtong-gu
Suwon-city, Gyeonggi-do, 443-803

TEST SITE: PCTEST ENGINEERING LABORATORY, INC.

TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA

FCC RULE PART(S): FCC Part 15 Subpart C

FCC ID: A3LEPP100IJWU

Test Device Serial No.: RT0D208AS E ☐ Production ☒ Pre-Production ☐ Engineering

FCC CLASSIFICATION: Part 15 Low Power Transmitter Below 1705 kHz (DCD)

DATE(S) OF TEST: 2/27-3/15/2013

Test Methodology

Both conducted and radiated measurements were taken using the methods and procedures described in ANSI C63.4-2009. Radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility / NVLAP Accreditation

Conducted and radiated tests were performed at PCTEST Engineering Lab in Columbia, MD 21046, U.S.A.

- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP) in EMC, Telecommunication, and FCC for satisfactory compliance with criteria established in Title 15, Part 285 Code of Federal Regulations. (NVLAP Lab code: 100431-0).
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 3 of 26

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Internt'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on February 15, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: A3LEPP100IJWU	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 4 of 26

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Wireless Charging Pad FCC ID: A3LEPP100IJWU**. The test data contained in this report pertains only to the emissions due to the wireless charging circuitry and function of the EUT.

2.2 Device Capabilities

The Samsung Model: EP-P100IEWE is a wireless charging pad containing a wireless charging circuit using a frequency of 112 – 205kHz.

2.3 Test Configuration

The **Samsung Wireless Charging Pad FCC ID: A3LEPP100IJWU** was connected to an AC power adapter while wirelessly charging a mobile handset with FCC ID: A3LSCHI535. No other ports exist on the EUT. The EUT was evaluated with the battery of the phone at 3 different charge conditions: battery at 0% (depleted), battery at 50% charge, and battery near 100% charge. Additionally, a resistive load for drawing maximum power (WCC with resistor attached) was also evaluated. All equipment is placed on the test table top and arranged in a typical configuration in accordance with ANSI C63.4-2009

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

2.5 Labeling Requirements

Per 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(a)(5).

Please see attachment for FCC ID label and label location.

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 5 of 26

3.0 DESCRIPTION OF TEST

3.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2009) was used in the measurement of the **Samsung Wireless Charging Pad FCC ID: A3LEPP100IJWU**.

Note:

No deviations from the specified test procedure.

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or resolution, clock or data exchange speed, scrolling H pattern to the EUT and/or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.5. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 8.51.0.

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 6 of 26

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by varying: the mode of operation or resolution, clock or data rate, scrolling H pattern to the EUT and/or support equipment, and changing the polarity of the receive antenna, whichever produced the worst-case emissions. To record the final measurements, the analyzer detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 120kHz for frequencies below 1GHz or 1MHz for frequencies above 1GHz. For average measurements above 1GHz, the analyzer was set to peak detector with a reduced VBW setting (RBW = 1MHz, VBW = 10Hz).

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 7 of 26

4.0 SAMPLE CALCULATIONS

4.1 Conducted Emission Measurement Sample Calculation

@ 20.3 MHz

Class C limit = 60.0 dB μ V (Quasi-peak limit)
Reading = - 57.8 dBm (calibrated quasi-peak level)
Convert to dB μ V = - 57.8 + 107 = 49.2 dB μ V

Margin = 49.2 - 60.0 = - 10.8 dB
= 10.8 dB below limit

4.2 Radiated Emission Measurement Sample Calculation

@ 66.7 MHz

Class C limit = 100 μ V/m = 40.0 dB μ V/m
Reading = - 76.0 dBm (calibrated level)
Convert to dB μ V = - 76.0 + 107 = 31.0 dB μ V
Antenna Factor + Cable Loss = 5.8 dB/m
Total = 36.8 dB μ V/m

Margin = 36.8 - 40.0 = - 3.2 dB
= 3.2 dB below limit

Note:

$$\text{Level [dB}\mu\text{V]} = 20 \log_{10} (\text{Level } [\mu\text{V/m}])$$

$$\text{Level [dB}\mu\text{V]} = \text{Level [dBm]} + 107$$

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 8 of 26

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	7/10/2012	Annual	7/10/2013	N/A
-	RE2	Radiated Emissions Cable Set (VHF/UHF)	3/13/2012	Annual	3/13/2013	N/A
Agilent	8447D	Broadband Amplifier	5/8/2012	Annual	5/8/2013	2443A01900
Agilent	N9020A	MXA Signal Analyzer	10/9/2012	Annual	10/9/2013	US46470561
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	5/10/2012	Annual	5/10/2013	121034
Rohde & Schwarz	ESU26	EMI Test Receiver	2/25/2013	Annual	2/25/2014	100342
Solar Electronics	8012-50-R-24-BNC	LISN	6/23/2011	Biennial	6/23/2013	310233
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/26/2012	Biennial	1/26/2014	A051107

Table 5-1. Annual Test Equipment Calibration Schedule

Note: For equipment list above that has a calibration due date that falls within the test date range, care was taken to ensure that this equipment was utilized prior to the calibration due date.

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 9 of 26

6.0 ENVIRONMENTAL CONDITIONS

The temperature is controlled within range of 15°C to 35°C.

The relative humidity is controlled within range of 10% to 75%.

The atmospheric pressure is controlled within the range 86-106kPa (860-1060mbar).

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 10 of 26

7.0 TEST DATA

7.1 Summary

Test Date(s): 2/27-3/15/2013

Test Engineer:



FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)						
2.1049	N/A	20 dB Bandwidth	N/A	RADIATED	PASS	Section 7.2
15.209 (a)	RSS-210 [A2.6]	In-Band Emissions	2400 / f[kHz] μ V/m @ 300m 0.009 – 0.490 MHz		PASS	Section 7.3
15.209	RSS-Gen [7.2.4]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-210 table 3 limits)		PASS	Section 7.2
15.207	RSS-Gen [7.2.5]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits or < RSS-Gen table 2 limits	LINE CONDUCTED	PASS	Section 7.5

Table 7-1. Summary of Test Results

Notes:

1. The WCP was tested with the Samsung handset model SCH-I535.
2. The device was evaluated with the battery at 4 different charge conditions: battery at 0% (depleted), battery at 50% charger, battery near 100% charge, max resistive load (WCC with resistor attached).

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 11 of 26

7.2 20dB Bandwidth Measurement

§2.1049

The 20dB bandwidth is measured with a spectrum analyzer connected via a receive antenna placed near the EUT while wirelessly charging a mobile handset.

Frequency	Occupied Bandwidth
112 – 205 kHz	29.55 kHz

Table 7-2. 20dB Bandwidth Measurement




Figure 7-1. Test Instrument & Measurement Setup




Figure 7-2. 20dB Bandwidth Plot

FCC ID: A3LEPP100IJWU	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 12 of 26

7.3 In-Band Radiated Spurious Emission Measurements

§15.225(a), (b), (c); RSS-210 [A2.6]

Radiated emission testing was performed in the band 112 – 205 KHz.

EUT Battery States	Frequency [MHz]	Level [dBm]	AFCL [dB/m]	Antenna Position	EUT Pol. [H/V]	3m Field Strength [dBμV/m]	300m Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
Battery at 0% (depleted)	0.161	-73.28	13.86	Y	H	47.58	-32.42	21.37	-53.79
Battery at 50% charge	0.180	-71.96	13.83	Y	H	48.87	-31.13	21.37	-52.50
Battery near 100% charge	0.163	-74.68	13.86	Y	H	46.18	-33.82	21.37	-55.19
WCC (max resistive load)	0.186	-70.00	13.82	Y	H	50.82	-29.18	21.37	-50.55

Table 7-3. In-Band Radiated Measurements

NOTES:

1. All measurements were performed using a loop antenna. The antenna was positioned in three orthogonal positions (X front, Y side, Z top) and the position with the highest emission level was recorded.
2. The EUT was positioned in three orthogonal planes to determine the orientation resulting in the worst case emissions.
3. Measurements were performed at 3m and the data was extrapolated to the specified measurement distance of 300m using the square of an inverse linear distance extrapolation factor (40 dB/decade) as specified in §15.31(f)(2). Extrapolation Factor = $20 \log_{10}(300/3)^2 = 80\text{dB}$
4. All measurements were recorded using a spectrum analyzer employing a peak detector.
5. The limit above was calculated based on the highest operating frequency of 205 kHz, which yields the worst case limit.
6. Field Strength Level $_{[\text{dB}\mu\text{V/m}]} = \text{Analyzer Level}_{[\text{dBm}]} + 107 + \text{AFCL}_{[\text{dB/m}]}$
7. $\text{AFCL}_{[\text{dB/m}]} = \text{Antenna Factor}_{[\text{dB/m}]} + \text{Cable Loss}_{[\text{dB}]}$
8. $\text{Margin}_{[\text{dB}]} = \text{Field Strength Level}_{[\text{dB}\mu\text{V/m}]} - \text{Limit}_{[\text{dB}\mu\text{V/m}]}$

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 13 of 26

7.4 Radiated Measurement Data – Battery at 0%

§15.209; RSS-Gen [7.2.4]

Frequency [MHz]	Level [dBm]	AFCL [dB/m]	Pol [H/V]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
49.58	-90.28	9.61	H	26.33	40.00	-13.67
75.19	-91.88	10.54	H	25.66	40.00	-14.34
118.88	-94.74	12.37	H	24.63	43.52	-18.89
151.27	-91.56	13.80	H	29.24	43.52	-14.28
194.95	-97.02	13.92	H	23.90	43.52	-19.62
230.35	-90.58	13.68	H	30.10	46.02	-15.92

Table 7-4. Radiated Measurements at 3-meters

NOTES:

1. All modes of operation were investigated and the worst-case emissions are reported.
2. Radiated emissions were measured from 9kHz – 6000MHz to ensure that the provisions of 15.33(b)(1) are satisfied with respect to the upper frequency scanning range.
3. No harmonics of the operating frequency were detected.
4. The radiated limits for unintentional radiators at a distance of 3 meters are used in the table above, as specified in 15.209(a).
5. All readings are calibrated by a signal generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
6. AFCL (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
7. Level (dB μ V/m) = Analyzer Reading (dBm) + AFCL (dB/m) + 107
8. Margin (dB) = Field strength (dB μ V/m) – Limit (dB μ V/m)
9. Measurements are made using a CISPR quasi-peak detector with a 120kHz resolution bandwidth. Above 1GHz, peak measurements are made using a peak detector with a resolution bandwidth of 1MHz and a video bandwidth of 3MHz and average measurements are made with a peak detector using a resolution bandwidth of 1MHz and a video bandwidth of 10Hz.
10. Calibrated linearly polarized broadband and horn antennas were used for measurements below and above 1GHz, respectively. For measurements made below 1GHz, the results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy.
11. Calibrated low-loss microwaves cables and broadband amplifiers are used.

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 14 of 26

Radiated Measurement Data (Cont'd) – Battery at 50%

§15.209; RSS- Gen [7.2.4]

Frequency [MHz]	Level [dBm]	AFCL [dB/m]	Pol [H/V]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
42.44	-89.48	13.23	H	30.75	40.00	-9.25
75.08	-91.58	10.54	H	25.95	40.00	-14.05
126.38	-95.11	12.75	H	24.64	43.52	-18.89
145.03	-91.25	13.59	H	29.34	43.52	-14.18
190.11	-96.69	13.91	H	24.22	43.52	-19.31
225.87	-93.68	13.72	H	27.03	46.02	-18.99

Table 7-5. Radiated Measurements at 3-meters

NOTES:

1. All modes of operation were investigated and the worst-case emissions are reported.
2. Radiated emissions were measured from 9kHz – 6000MHz to ensure that the provisions of 15.33(b)(1) are satisfied with respect to the upper frequency scanning range.
3. No harmonics of the operating frequency were detected.
4. The radiated limits for unintentional radiators at a distance of 3 meters are used in the table above, as specified in 15.209(a).
5. All readings are calibrated by a signal generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
6. AFCL (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
7. Level (dB μ V/m) = Analyzer Reading (dBm) + AFCL (dB/m) + 107
8. Margin (dB) = Field strength (dB μ V/m) – Limit (dB μ V/m)
9. Measurements are made using a CISPR quasi-peak detector with a 120kHz resolution bandwidth. Above 1GHz, peak measurements are made using a peak detector with a resolution bandwidth of 1MHz and a video bandwidth of 3MHz and average measurements are made with a peak detector using a resolution bandwidth of 1MHz and a video bandwidth of 10Hz.
10. Calibrated linearly polarized broadband and horn antennas were used for measurements below and above 1GHz, respectively. For measurements made below 1GHz, the results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy.
11. Calibrated low-loss microwaves cables and broadband amplifiers are used.

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 15 of 26

Radiated Measurement Data (Cont'd) – Battery at 100%

§15.209; RSS- Gen [7.2.4]

Frequency [MHz]	Level [dBm]	AFCL [dB/m]	Pol [H/V]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
51.76	-90.89	9.53	H	25.64	40.00	-14.36
75.08	-93.09	10.54	H	24.44	40.00	-15.56
126.38	-97.40	12.75	H	22.35	43.52	-21.18
154.36	-95.51	13.81	H	25.30	43.52	-18.22
191.67	-97.24	13.91	H	23.67	43.52	-19.85
227.42	-94.68	13.70	H	26.02	46.02	-20.00

Table 7-6. Radiated Measurements at 3-meters

NOTES:

1. All modes of operation were investigated and the worst-case emissions are reported.
2. Radiated emissions were measured from 9kHz – 6000MHz to ensure that the provisions of 15.33(b)(1) are satisfied with respect to the upper frequency scanning range.
3. No harmonics of the operating frequency were detected.
4. The radiated limits for unintentional radiators at a distance of 3 meters are used in the table above, as specified in 15.209(a).
5. All readings are calibrated by a signal generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
6. AFCL (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
7. Level (dB μ V/m) = Analyzer Reading (dBm) + AFCL (dB/m) + 107
8. Margin (dB) = Field strength (dB μ V/m) – Limit (dB μ V/m)
9. Measurements are made using a CISPR quasi-peak detector with a 120kHz resolution bandwidth. Above 1GHz, peak measurements are made using a peak detector with a resolution bandwidth of 1MHz and a video bandwidth of 3MHz and average measurements are made with a peak detector using a resolution bandwidth of 1MHz and a video bandwidth of 10Hz.
10. Calibrated linearly polarized broadband and horn antennas were used for measurements below and above 1GHz, respectively. For measurements made below 1GHz, the results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy.
11. Calibrated low-loss microwaves cables and broadband amplifiers are used.

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 16 of 26

Radiated Measurement Data (Cont'd) – Max Resistive Load

§15.209; RSS- Gen [7.2.4]

Frequency [MHz]	Level [dBm]	AFCL [dB/m]	Pol [H/V]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
50.21	-87.66	9.45	H	28.79	40.00	-11.21
76.63	-91.33	10.59	H	26.26	40.00	-13.74
148.14	-97.73	13.72	H	22.99	43.52	-20.54
168.35	-95.88	13.85	H	24.97	43.52	-18.55
188.56	-92.44	13.90	H	28.46	43.52	-15.06
225.87	-93.96	13.72	H	26.75	46.02	-19.27

Table 7-7. Radiated Measurements at 3-meters


NOTES:

12. All modes of operation were investigated and the worst-case emissions are reported.
13. Radiated emissions were measured from 9kHz – 6000MHz to ensure that the provisions of 15.33(b)(1) are satisfied with respect to the upper frequency scanning range.
14. No harmonics of the operating frequency were detected.
15. The radiated limits for unintentional radiators at a distance of 3 meters are used in the table above, as specified in 15.209(a).
16. All readings are calibrated by a signal generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
17. AFCL (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
18. Level (dB μ V/m) = Analyzer Reading (dBm) + AFCL (dB/m) + 107
19. Margin (dB) = Field strength (dB μ V/m) – Limit (dB μ V/m)
20. Measurements are made using a CISPR quasi-peak detector with a 120kHz resolution bandwidth. Above 1GHz, peak measurements are made using a peak detector with a resolution bandwidth of 1MHz and a video bandwidth of 3MHz and average measurements are made with a peak detector using a resolution bandwidth of 1MHz and a video bandwidth of 10Hz.
21. Calibrated linearly polarized broadband and horn antennas were used for measurements below and above 1GHz, respectively. For measurements made below 1GHz, the results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy.
22. Calibrated low-loss microwaves cables and broadband amplifiers are used.

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 17 of 26

7.5 Line Conducted Measurement Data

§15.207; RSS-Gen (7.2.5)



Plot 7-1. Line Conducted Plot (L1) – Battery at 0%

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.294	L1	0.1	44.20	60.40	16.20	38.50	50.40	11.90
0.726	L1	0.1	39.00	56.00	17.00	19.20	46.00	26.80
0.790	L1	0.1	43.10	56.00	12.90	31.50	46.00	14.50
0.846	L1	0.1	34.50	56.00	21.50	17.80	46.00	28.20
2.498	L1	0.2	36.20	56.00	19.80	26.50	46.00	19.50
3.842	L1	0.2	25.20	56.00	30.80	17.30	46.00	28.70

Table 7-8. Line Conducted Data (L1) – Battery at 0%


Notes:

1. Emissions with the battery at the 0% test state are reported above.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. L1 = Phase; N = Neutral
4. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
5. QP/AV Level (dBμV) = QP/AV Reading (dBμV) + Factor (dB)
6. Margin (dB) = QP/AV Limit (dBμV) – QP/AV Level (dBμV)
7. Traces shown in plot are made using a peak detector.
8. Deviations to the Specifications: None.

FCC ID: A3LEPP100IJWU	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 18 of 26

Line Conducted Measurement Data (Cont'd)

§15.207; RSS-Gen (7.2.5)



Plot 7-2. Line Conducted Plot (LN) – Battery at 0%

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.726	N	0.1	43.20	56.00	12.80	22.80	46.00	23.20
0.770	N	0.1	46.60	56.00	9.40	31.70	46.00	14.30
0.882	N	0.1	40.50	56.00	15.50	27.60	46.00	18.40
1.566	N	0.2	40.70	56.00	15.30	28.00	46.00	18.00
1.630	N	0.2	42.20	56.00	13.80	26.20	46.00	19.80
1.722	N	0.2	42.40	56.00	13.60	27.70	46.00	18.30

Table 7-9. Line Conducted Data (LN) – Battery at 0%


Notes:

- Emissions with the battery at the 0% test state are reported above.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Reading (dBμV) + Factor (dB)
- Margin (dB) = QP/AV Limit (dBμV) – QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 19 of 26

Line Conducted Measurement Data (Cont'd)

§15.207; RSS-Gen (7.2.5)



Plot 7-3. Line Conducted Plot (L1) – Battery at 50%

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.718	L1	0.1	37.60	56.00	18.40	23.00	46.00	23.00
0.770	L1	0.1	41.60	56.00	14.40	26.80	46.00	19.20
0.878	L1	0.1	36.50	56.00	19.50	24.30	46.00	21.70
1.610	L1	0.2	34.10	56.00	21.90	20.30	46.00	25.70
29.554	L1	1.0	36.30	60.00	23.70	22.40	50.00	27.60
29.914	L1	1.0	39.60	60.00	20.40	21.30	50.00	28.70

Table 7-10. Line Conducted Data (L1) – Battery at 50%


Notes:

- Emissions with the battery at the 50% test state are reported above.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Reading (dBμV) + Factor (dB)
- Margin (dB) = QP/AV Limit (dBμV) – QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LEPP100IJWU	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 20 of 26

Line Conducted Measurement Data (Cont'd)

§15.207; RSS-Gen (7.2.5)



Plot 7-4. Line Conducted Plot (LN) – Battery at 50%

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.786	N	0.1	46.90	56.00	9.10	35.20	46.00	10.80
0.994	N	0.2	41.80	56.00	14.20	21.60	46.00	24.40
1.538	N	0.2	40.50	56.00	15.50	23.30	46.00	22.70
1.630	N	0.2	43.00	56.00	13.00	27.10	46.00	18.90
2.262	N	0.2	41.60	56.00	14.40	27.20	46.00	18.80
13.782	N	0.5	39.40	60.00	20.60	30.00	50.00	20.00

Table 7-11. Line Conducted Data (LN) – Battery at 50%


Notes:

- Emissions with the battery at the 50% test state are reported above.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Reading (dBμV) + Factor (dB)
- Margin (dB) = QP/AV Limit (dBμV) – QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LEPP100IJWU	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 21 of 26

Line Conducted Measurement Data (Cont'd)

§15.207; RSS-Gen (7.2.5)



Plot 7-5. Line Conducted Plot (L1) – Battery at 100%

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.294	L1	0.1	47.40	60.40	13.00	41.60	50.40	8.80
0.786	L1	0.1	40.90	56.00	15.10	26.00	46.00	20.00
14.674	L1	0.5	42.50	60.00	17.50	35.80	50.00	14.20
29.142	L1	1.0	47.00	60.00	13.00	37.20	50.00	12.80
29.554	L1	1.0	43.20	60.00	16.80	32.90	50.00	17.10
29.970	L1	1.0	42.70	60.00	17.30	30.80	50.00	19.20

Table 7-12. Line Conducted Data (L1) – Battery at 100%


Notes:

- Emissions with the battery at the 100% test state are reported above.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Reading (dBμV) + Factor (dB)
- Margin (dB) = QP/AV Limit (dBμV) – QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LEPP100IJWU	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 22 of 26

Line Conducted Measurement Data (Cont'd)

§15.207; RSS-Gen (7.2.5)



Plot 7-6. Line Conducted Plot (LN) – Battery at 100%

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.790	N	0.1	44.40	56.00	11.60	31.20	46.00	14.80
0.818	N	0.1	36.50	56.00	19.50	22.60	46.00	23.40
1.110	N	0.2	37.90	56.00	18.10	24.30	46.00	21.70
2.046	N	0.2	39.70	56.00	16.30	25.80	46.00	20.20
14.110	N	0.5	40.70	60.00	19.30	29.70	50.00	20.30
29.970	N	1.0	46.10	60.00	13.90	35.80	50.00	14.20

Table 7-13. Line Conducted Data (LN) – Battery at 100%


Notes:

- Emissions with the battery at the 100% test state are reported above.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Reading (dBμV) + Factor (dB)
- Margin (dB) = QP/AV Limit (dBμV) – QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LEPP100IJWU	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 23 of 26

Line Conducted Measurement Data (Cont'd)

§15.207; RSS-Gen (7.2.5)



Plot 7-7. Line Conducted Plot (L1) – Max Resistive Load

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.294	L1	0.1	47.50	60.40	12.90	43.40	50.40	7.00
0.518	L1	0.1	36.40	56.00	19.60	23.80	46.00	22.20
0.586	L1	0.1	38.90	56.00	17.10	30.20	46.00	15.80
0.774	L1	0.1	40.90	56.00	15.10	27.70	46.00	18.30
0.830	L1	0.1	38.30	56.00	17.70	20.60	46.00	25.40
0.978	L1	0.1	25.30	56.00	30.70	11.10	46.00	34.90

Table 7-14. Line Conducted Data (L1) – Max Resistive Load


Notes:

- Emissions with the battery at the max resistive load test state are reported above.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Reading (dBμV) + Factor (dB)
- Margin (dB) = QP/AV Limit (dBμV) – QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LEPP100IJWU	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 24 of 26

Line Conducted Measurement Data (Cont'd)

§15.207; RSS-Gen (7.2.5)



Plot 7-8. Line Conducted Plot (LN) – Max Resistive Load

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.798	N	0.1	44.80	56.00	11.20	29.10	46.00	16.90
0.842	N	0.1	42.30	56.00	13.70	29.30	46.00	16.70
1.982	N	0.2	38.80	56.00	17.20	25.60	46.00	20.40
2.058	N	0.2	37.70	56.00	18.30	26.70	46.00	19.30
2.134	N	0.2	39.50	56.00	16.50	26.00	46.00	20.00
13.590	N	0.5	41.00	60.00	19.00	30.20	50.00	19.80

Table 7-15. Line Conducted Data (LN) – Max Resistive Load

Notes:

- Emissions with the battery at the max resistive load test state are reported above.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Reading (dBμV) + Factor (dB)
- Margin (dB) = QP/AV Limit (dBμV) – QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LEPP100IJWU	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 25 of 26

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Wireless Charging Pad FCC ID: A3LEPP100IJWU** has been tested to comply with the requirements specified in §15.207 and §15.209 of the FCC Rules and Industry Canada Standard RSS-Gen.

FCC ID: A3LEPP100IJWU		FCC Pt. 15C MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1302270363.A3L	Test Dates: 2/27-3/15/2013	EUT Type: Wireless Charging Pad		Page 26 of 26