

	1	2	3	4	5	6	7	8
A			Rev. No					
B								
C								
D								
E								
F								
G	Technical Description 1. Use 'FILM' provided by 'SAMSUNG' for letter and contents 2. Background color is 'WHITE', letter color is 'BLACK' (reverse for SAMSUNG LOGO) 3. Put 'release paper' on the back side after the adhesive. 4. No blur and spread for letter 5. Proceed with manufacturing process after the approval of R&D Group 6. The spec. of product must be based on approved limit samples. 7. Stock on as a ROLL 8. Follow drawing instruction above for CE or WEEE mark 9. Unify material and color as one color (blue) for glassine paper							
H								
I								
J								
K								
L								

Technical drawing of a label with dimensions and markings. The label is rectangular with a width of 26.5 ± 0.1 mm and a height of 18.5 ± 0.1 mm. It features a 6-R1 rounded corner. The label contains the following text: 'TELEFONO CELULAR/CELLULAR PHONE', 'MODELO: GT-E1182L', 'SSN: -E1182LGSNH', 'FCC ID: A3LGT E1182L', 'ALIMENTACION: 3.7 V', '800 mA', 'PRODUCTO COREANO/KOREAN PRODUCT', 'NOM', 'CE', and '0168'. The dimensions are: 10.0 ± 0.1 mm (width of the top section), 12.5 ± 0.1 mm (width of the bottom section), 5.0 mm (height of the top section), 10.0 mm (height of the middle section), 15.5 ± 0.1 mm (height of the bottom section), 8.5 ± 0.1 mm (height of the bottom section), and 3.0 mm (height of the bottom section). The label is shown in a 'ROLLING' position with a 2.0 mm width and a 2.0 mm height.

MAT.	White polypropylene 80μ			FIN.			Semitransparency OPP Lamination + UVP Coating	
TITLE	GT-E1182L			LABEL(R)-MAIN-LTN				
UNIT	mm	DESIGNED	CHECKED	APPROVED	PROJECTION			
TOLERANCE	+0.0 -0.1	jukyun Kim	kyeonghwan jo	junesop kim				
SCALE	N / S							
Manufacture	HANSUNG P&I	11-03-14	11-03-14	11-03-14	SHEET NO		1/1	
		Doc. CODE		GH68-00000A				