



FCC CFR47 PART 15 SUBPART C

CERTIFICATION TEST REPORT

FOR

BAR PHONE WITH 802.11B/G/N WLAN AND BLUETOOTH

MODEL NUMBER: GT-I8552B

FCC ID: A3LGTI8552B

REPORT NUMBER: 13I14969-2A

ISSUE DATE: APRIL 22, 2013

Prepared for

SAMSUNG ELECTRONICS CO., LTD.

416, MAETAN 3-DONG, YEONGTONG-GU

SUWON-CITY, GYEONGGI-DO 443-742, SOUTH KOREA

Prepared by

UL CCS

47173 BENICIA STREET

FREMONT, CA 94538, U.S.A.

TEL: (510) 771-1000

FAX: (510) 661-0888



NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	4/14/2013	Initial Creation	Philip Kim
A	4/22/2013	Maximum output power table filled out.	Philip Kim

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION.....	6
4.3. MEASUREMENT UNCERTAINTY	6
5. EQUIPMENT UNDER TEST	7
5.1. DESCRIPTION OF EUT.....	7
5.2. MAXIMUM OUTPUT POWER.....	7
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	8
5.4. SOFTWARE AND FIRMWARE	8
5.5. WORST-CASE CONFIGURATION AND MODE.....	9
5.1. DESCRIPTION OF TEST SETUP.....	10
6. TEST AND MEASUREMENT EQUIPMENT	12
7. MEASUREMENT METHODS.....	13
7.1. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS	14
7.2. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS	14
7.2.1. ON TIME AND DUTY CYCLE RESULTS	14
7.2.2. MEASUREMENT METHOD FOR POWER AND PPSD	14
7.2.3. MEASUREMENT METHOD FOR AVERAGE SPURIOUS EMISSIONS ABOVE 1 GHz	15
7.2.4. DUTY CYCLE PLOTS.....	16
8. ANTENNA PORT TEST RESULTS	18
8.1. 802.11b MODE IN THE 2.4 GHz BAND.....	18
8.1.1. 6 dB BANDWIDTH	18
8.1.2. AVERAGE POWER	21
8.1.3. OUTPUT POWER.....	22
8.1.4. PSD.....	26
8.1.5. OUT-OF-BAND EMISSIONS	29
8.2. 802.11g MODE IN THE 2.4 GHz BAND.....	34
8.2.1. 6 dB BANDWIDTH	34
8.2.2. AVERAGE POWER	37
8.2.3. OUTPUT POWER	38
8.2.4. PSD	42
8.2.5. OUT-OF-BAND EMISSIONS	45
8.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND.....	50

8.3.1.	6 dB BANDWIDTH	50
8.3.2.	AVERAGE POWER	53
8.3.3.	OUTPUT POWER	54
8.3.4.	PSD	58
8.3.5.	OUT-OF-BAND EMISSIONS	61
9.	RADIATED TEST RESULTS	66
9.1.	<i>LIMITS AND PROCEDURE</i>	<i>66</i>
9.2.	<i>TRANSMITTER ABOVE 1 GHz</i>	<i>67</i>
9.2.1.	TX ABOVE 1 GHz 802.11b MODE IN THE 2.4 GHz BAND.....	67
9.2.2.	TX ABOVE 1 GHz 802.11g MODE IN THE 2.4 GHz BAND.....	79
9.2.3.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 2.4 GHz BAND.....	86
9.3.	<i>WORST-CASE BELOW 1 GHz</i>	<i>112</i>
10.	AC POWER LINE CONDUCTED EMISSIONS	115
11.	SETUP PHOTOS	119

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
416, MAETAN 3-DONG, YEONGTONG-GU
SUWON-CITY, GYEONGGI-DO, 443-742, SOUTH KOREA

EUT DESCRIPTION: BAR PHONE WITH WLAN, 802.11B/G/N AND BLUETOOTH

MODEL: GT-I8552B

SERIAL NUMBER: FK-065-C (EMISSION) AND FK-065-D (CONDUCTION)

DATE TESTED: MARCH 13- 21, 2013.

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL CCS tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL CCS based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL CCS and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL CCS will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For UL CCS By:

Tested By:



PHILIP KIM
WiSE PROJECT MANAGER
UL CCS

DANNY VU
EMC ENGINEER
UL CCS

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.10-2009, RSS-GEN Issue 3, and RSS-210 Issue 8.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamplifier Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 1000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a bar-style cell phone featuring 802.11b/g/n WLAN, Bluetooth, GPS and 2.4 GHz mobile hotspot capability.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2412 - 2462	802.11b	16.5	44.67
2412 - 2462	802.11g	20.79	119.95
2412 - 2462	802.11n HT20	19.38	86.70

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a PCB antenna, with a maximum gain of -5 dBi.

5.4. SOFTWARE AND FIRMWARE

The firmware installed in the EUT during testing was REV.5 and the software was S5312L.

5.5. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that the Y-orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y-orientation.

Based on the baseline scan, the worst-case data rates were:

802.11b mode: 1 Mbps
802.11g mode: 6 Mbps
802.11a mode: 6 Mbps
802.11n HT20mode: MCS0

5.1. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT


Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	Samsung Electronics	GT-S5312B	FK-065-A	DoC
Headset	Samsung Electronics	GT-S5312L	FK-064-B	DoC

I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	USB	1	USB	Shielded	1.6m	N/A
2	Headset	1	Audio	Shielded	1.5m	N/A

TEST SETUP

The EUT is a stand-alone unit that was tested in the worst case orientation and configuration, where applicable, during the tests. Test software exercised the radio.

SETUP DIAGRAM FOR TESTS

6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List					
Description	Manufacturer	Model	Asset	Cal Date	Cal Due
Antenna, Horn, 18 GHz	EMCO	3115	C00872	09/20/12	09/20/13
Antenna, Horn, 26.5 GHz	ARA	MWH-1826/B	C00589	07/28/12	07/28/13
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01012	10/21/12	10/21/13
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C00749	10/21/12	10/21/13
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00558	02/21/13	02/21/14
Reject Filter, 2.4-2.5 GHz	Micro-Tronics	BRC13192	N02683	CNR	CNR
Bilog 30-2000MHz	Sunol	JB1	C01071	07/26/12	07/26/13
Power meter	HP	437B	T226	06/25/12	06/25/13
Power Sensor	HP	8481A	T233	06/26/12	06/26/13
LISN, 30 MHz	FCC	LISN-50/250-25-2	N02625	01/14/13	01/14/14
LISN, 10 kHz ~ 30 MHz	Solar	8012-50-R-24-BNC	N02481	03/07/12	03/07/14

7. MEASUREMENT METHODS

KDB 558074 Measurement Procedure PK2 is used for power and PKPSD is used for power spectral density.

Unwanted emissions within Restricted Bands are measured using traditional radiated procedures.

7.1. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS

LIMITS

None; for reporting purposes only.

PROCEDURE

KDB 789033 Zero-Span Spectrum Analyzer Method.

7.2. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS

LIMITS

None; for reporting purposes only.

PROCEDURE

KDB 789033 Zero-Span Spectrum Analyzer Method.

7.2.1. ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)
802.11b	1.00	1.00	1.000	100.0%	0.00	0.010
802.11g	2.07	2.10	0.983	98.3%	0.00	0.010
802.11n HT20	1.92	1.95	0.983	98.3%	0.00	0.010



7.2.2. MEASUREMENT METHOD FOR POWER AND PPSD


The Duty Cycle is less than 98% and consistent therefore KDB 789033 Method SA-2 is used.

**7.2.3. MEASUREMENT METHOD FOR AVERAGE SPURIOUS EMISSIONS
ABOVE 1 GHz**

The Duty Cycle is less than 98% and consistent, KDB 789033 Method AD with Power RMS Averaging and duty cycle correction is used.

7.2.4. DUTY CYCLE PLOTS





8. ANTENNA PORT TEST RESULTS

8.1. 802.11b MODE IN THE 2.4 GHz BAND

8.1.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

IC RSS-210 A8.2 (a)

The minimum 6 dB bandwidth shall be at least 500 kHz.



TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer with the RBW set between 1% and 5% of the EBW, the VBW $\geq 3 \times$ RBW, peak detector and max hold.

RESULTS

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2412	10.095	0.5
Mid	2437	10.035	0.5
High	2462	10.095	0.5

6 dB BANDWIDTH





8.1.2. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

The cable assembly insertion loss of 11.7 dB (including 11 dB pad and .7 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

RESULTS

Channel	Frequency (MHz)	Power (dBm)
Low	2412	12.80
Mid	2437	13.40
High	2462	14.00

8.1.3. OUTPUT POWER

LIMITS

FCC §15.247

IC RSS-210 A8.4

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt, based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DIRECTIONAL ANTENNA GAIN

There is only one transmitter output therefore the directional gain is equal to the antenna gain.

RESULTS



Limits


Channel	Frequency (MHz)	Directional Gain (dBi)	FCC Power Limit (dBm)	IC Power Limit (dBm)	IC EIRP Limit (dBm)	Max Power (dBm)
Low	2412	-5.00	30.00	30	36	30.00
Mid	2437	-5.00	30.00	30	36	30.00
High	2462	-5.00	30.00	30	36	30.00

Results

Channel	Frequency (MHz)	Chain 0 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Margin (dB)
Low	2412	14.98	14.98	30.00	-15.02
Mid	2437	16.10	16.10	30.00	-13.90
High	2462	16.50	16.50	30.00	-13.50

OUTPUT POWER, Chain 0





8.1.4. PSD

LIMITS

FCC §15.247

IC RSS-210 A8.2



The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


RESULTS

PSD Results

Channel	Frequency (MHz)	Chain 0 Meas (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-13.59	8.0	-21.6
Mid	2437	-13.27	8.0	-21.3
High	2462	-12.92	8.0	-20.9

PSD, Chain 0





8.1.5. OUT-OF-BAND EMISSIONS

LIMITS

FCC §15.247 (d)

IC RSS-210 A8.5


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.



TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer with RBW = 100 kHz, VBW = 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, bandedge (where measurements to the general radiated limits will not be made) and out-of-band emissions.



RESULTS


IN-BAND REFERENCE LEVEL



LOW CHANNEL BANDEDGE**HIGH CHANNEL BANDEDGE**

OUT-OF-BAND EMISSIONS





8.2. 802.11g MODE IN THE 2.4 GHz BAND

8.2.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

IC RSS-210 A8.2 (a)

The minimum 6 dB bandwidth shall be at least 500 kHz.



TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer with the RBW set between 1% and 5% of the EBW, the VBW $\geq 3 \times$ RBW, peak detector and max hold.

RESULTS

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2412	16.460	0.5
Mid	2437	16.460	0.5
High	2462	16.290	0.5

6 dB BANDWIDTH





8.2.2. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

The cable assembly insertion loss of 11.7 dB (including 11 dB pad and 0.7 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

RESULTS

Channel	Frequency (MHz)	Power (dBm)
Low	2412	10.60
Mid	2437	13.00
High	2462	12.00

8.2.3. OUTPUT POWER

LIMITS

FCC §15.247

IC RSS-210 A8.4

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt, based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DIRECTIONAL ANTENNA GAIN

There is only one transmitter output therefore the directional gain is equal to the antenna gain.

RESULTS



Limits


Channel	Frequency (MHz)	Directional Gain (dBi)	FCC Power Limit (dBm)	IC Power Limit (dBm)	IC EIRP Limit (dBm)	Max Power (dBm)
Low	2412	-5.00	30.00	30	36	30.00
Mid	2437	-5.00	30.00	30	36	30.00
High	2462	-5.00	30.00	30	36	30.00

Results

Channel	Frequency (MHz)	Chain 0 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Margin (dB)
Low	2412	18.28	18.28	30.00	-11.72
Mid	2437	20.79	20.79	30.00	-9.21
High	2462	19.57	19.57	30.00	-10.43

OUTPUT POWER, Chain 0





8.2.4. PSD

LIMITS

FCC §15.247

IC RSS-210 A8.2



The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


RESULTS

PSD Results

Channel	Frequency (MHz)	Chain 0 Meas (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-17.14	8.0	-25.1
Mid	2437	-13.96	8.0	-22.0
High	2462	-14.39	8.0	-22.4

PSD, Chain 0





8.2.5. OUT-OF-BAND EMISSIONS

LIMITS

FCC §15.247 (d)

IC RSS-210 A8.5


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.



TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer with RBW = 100 kHz, VBW = 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, bandedge (where measurements to the general radiated limits will not be made) and out-of-band emissions.



RESULTS


IN-BAND REFERENCE LEVEL



LOW CHANNEL BANDEDGE**HIGH CHANNEL BANDEDGE**

OUT-OF-BAND EMISSIONS





8.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND

8.3.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

IC RSS-210 A8.2 (a)

The minimum 6 dB bandwidth shall be at least 500 kHz.



TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer with the RBW set between 1% and 5% of the EBW, the VBW $\geq 3 \times$ RBW, peak detector and max hold.

RESULTS

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2412	17.550	0.5
Mid	2437	17.550	0.5
High	2462	17.700	0.5

6 dB BANDWIDTH





8.3.2. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

The cable assembly insertion loss of 11.7 dB (including 11 dB pad and .7 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

RESULTS

Channel	Frequency (MHz)	Power (dBm)
Low	2412	8.30
Mid	2437	11.20
High	2462	9.50

8.3.3. OUTPUT POWER

LIMITS

FCC §15.247

IC RSS-210 A8.4

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt, based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DIRECTIONAL ANTENNA GAIN

There is only one transmitter output therefore the directional gain is equal to the antenna gain.

RESULTS



Limits


Channel	Frequency (MHz)	Directional Gain (dBi)	FCC Power Limit (dBm)	IC Power Limit (dBm)	IC EIRP Limit (dBm)	Max Power (dBm)
Low	2412	-5.00	30.00	30	36	30.00
Mid	2437	-5.00	30.00	30	36	30.00
High	2462	-5.00	30.00	30	36	30.00

Results

Channel	Frequency (MHz)	Chain 0 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Margin (dB)
Low	2412	16.42	16.42	30.00	-13.58
Mid	2437	19.38	19.38	30.00	-10.62
High	2462	17.65	17.65	30.00	-12.35

OUTPUT POWER, Chain 0





8.3.4. PSD

LIMITS

FCC §15.247

IC RSS-210 A8.2



The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


RESULTS

PSD Results

Channel	Frequency (MHz)	Chain 0 Meas (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-17.51	8.0	-25.5
Mid	2437	-15.42	8.0	-23.4
High	2462	-16.66	8.0	-24.7

PSD, Chain 0





8.3.5. OUT-OF-BAND EMISSIONS

LIMITS

FCC §15.247 (d)

IC RSS-210 A8.5


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.



TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer with RBW = 100 kHz, VBW = 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, bandedge (where measurements to the general radiated limits will not be made) and out-of-band emissions.



RESULTS


IN-BAND REFERENCE LEVEL



LOW CHANNEL BANDEDGE**HIGH CHANNEL BANDEDGE**

OUT-OF-BAND EMISSIONS





9. RADIATED TEST RESULTS

9.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

IC RSS-210 Clause 2.6 (Transmitter)

IC RSS-GEN Clause 6 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 1 MHz for peak measurements and as applicable for average measurements.



The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.



The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

9.2. TRANSMITTER ABOVE 1 GHz



9.2.1. TX ABOVE 1 GHz 802.11b MODE IN THE 2.4 GHz BAND



RESTRICTED BANDEDGE (LOW CHANNEL)







AUTHORIZED BANDEDGE (HIGH CHANNEL)





HARMONICS AND SPURIOUS EMISSIONS






Low Channel


Project :13I14969															
Company Name:Samsung															
Model / Config:EUT with adapter															
Mode:b mode low ch															
Test By:Roy Zheng															

Horizontal 1000 - 18000MHz														
Test Frequency	Meter Reading	Detector	T345 Ant Factor [dB/m]	T145 Preamp Gain [dB]	Cable Factor [dB]	T160 BRF [dB]	dB(uVolt s/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Azimuth [Degs]	Height [cm]	Polarity
4823.97	34.43	MAv1	34.7	-34.9		7	0.2	41.43	54	-12.57	-	345	141	Horz
10197.35	25.03	MAv1	38	-34.7	10.6		0.6	39.53	54	-14.47	-	303	187	Horz

Mid Channel Horizontal




Mid Channel Vertical




Mid Channel

Project :13I14969															
Company Name:Samsung															
Model / Config:EUT with adapter															
Mode:b mode mid ch															
Test By:Roy Zheng															

Horizontal 1000 - 18000MHz															
Test Frequency	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	dB(uV/s/meter)	E-Fields (dBuV/m) - Avg	Margin (dB)	E-Fields (dBuV/m) - Peak	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity	
4873.96	43.64	MAv1	34.7	-34.9	7.1	0.2	50.74	54	-3.26	-	-	230	130	Horz	
9354.82	25.74	MAv1	37	-35.1	10.1	0.5	38.24	54	-15.76	-	-	127	361	Vert	







[illegible]


Horizontal 1000 - 18000MHz														
Test Frequency	Meter Reading [dBuV]	Detector	T345 Ant Factor [dB/m]	T145 Preamp Gain [dB]	Cable Factor [dB]	T160 BRF [dB]	dB(uVolt s/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Azimuth [Degs]	Height [cm]	Polarity
4923.81	30.66	MAV1	34.6	-34.9	7.1	0.2	37.66	54	-16.34	-	-	119	252	Horz


9.2.2. TX ABOVE 1 GHz 802.11g MODE IN THE 2.4 GHz BAND

RESTRICTED BANDEDGE (LOW CHANNEL)




$$\begin{aligned}
 \text{Actual Average} &= \text{Measured Average} + \text{Correction Factor} \\
 &= 43.375 \text{ dB}\mu\text{V} + 0.95 \\
 &= 44.325 \text{ dB}\mu\text{V}
 \end{aligned}$$







$$\begin{aligned}
 \text{Actual Average} &= \text{Measured Average} + \text{Correction Factor} \\
 &= 40.812 \text{ dBuV} + 0.95 \\
 &= 41.762 \text{ dBuV}
 \end{aligned}$$


AUTHORIZED BANDEGE (HIGH CHANNEL)






$$\begin{aligned}
 \text{Actual Average} &= \text{Measured Average} + \text{Correction Factor} \\
 &= 40.688 \text{ dBuV} + 0.95 \\
 &= 41.638 \text{ dBuV}
 \end{aligned}$$






$$\begin{aligned}
 \text{Actual Average} &= \text{Measured Average} + \text{Correction Factor} \\
 &= 41.496 \text{ dBuV} + 0.95 \\
 &= 42.446 \text{ dBuV}
 \end{aligned}$$

HARMONICS AND SPURIOUS EMISSIONS



Low Channel Vertical



Low Channel

Project :13I14969
Company Name:Samsung
Model / Config:EUT with adapter
Mode:g mode low ch
Test By:Roy Zheng

Horizontal 1000 - 18000MHz

Marker No.	Test Frequency (Mhz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uV/s/meter)	E-Fields (dBuV/m) - Avg	Margin (dB)	E-Fields (dBuV/m) - Peak	Margin (dB)	Height (cm)	Polarity
1	2418.436	44.61	PK	32.4	-35	4.6	0.9	0	47.51	-	-	74	-26.49	100	Horz
2	4822.133	39.65	PK	34.7	-34.9	7	0.2	0	46.65	-	-	74	-27.35	200	Horz
3	9434.174	34.67	PK	37.1	-35.1	10.1	0.5	0	47.27	-	-	74	-26.73	100	Horz

Vertical 1000 - 18000MHz

Marker No.	Test Frequency (Mhz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uV/s/meter)	E-Fields (dBuV/m) - Avg	Margin (dB)	E-Fields (dBuV/m) - Peak	Margin (dB)	Height (cm)	Polarity
4	2405.696	44.98	PK	32.3	-35	4.6	0.9	0	47.78	-	-	74	-26.22	200	Vert
5	3429.178	39.99	PK	33.2	-35	5.7	0.4	0	44.29	-	-	74	-29.71	200	Vert
6	6423.183	36.52	PK	35.9	-35	8.3	0.3	0	46.02	-	-	74	-27.98	200	Vert


Horizontal 10000 - 18000MHz

Marker No.	Test Frequency (Mhz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uV/s/meter)	E-Fields (dBuV/m) - Avg	Margin (dB)	E-Fields (dBuV/m) - Peak	Margin (dB)	Height (cm)	Polarity
7	11847.08	22.71	PK	39.1	-33.4	11.5	0.6	0	40.51	-	-	74	-33.49	200	Horz


Vertical 10000 - 18000MHz

Marker No.	Test Frequency (Mhz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uV/s/meter)	E-Fields (dBuV/m) - Avg	Margin (dB)	E-Fields (dBuV/m) - Peak	Margin (dB)	Height (cm)	Polarity
8	14809.6	22.42	PK	39.8	-32.8	13.1	0.4	0	42.92	-	-	74	-31.08	100	Vert

Mid Channel Horizontal



Mid Channel Vertical



[illegible]


Horizontal 1000 - 18000MHz															
Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor [dB/m]	T145 Preamp Gain [dB]	Cable Factor [dB]	T160 BRF [dB]	DC Corr [dB]	dB(uV/s/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Height [cm]	Polarity
1	2439.67	45.15	PK	32.4	-35	4.7	0.9	0	48.15	-	-	74	-25.85	100	Horz
2	4868.848	41.17	PK	34.7	-34.9	7.1	0.2	0	48.27	-	-	74	-25.73	100	Horz
3	7315.014	35.64	PK	35.9	-35	8.9	0.3	0	45.74	-	-	74	-28.26	100	Horz

Vertical 1000 - 18000MHz															
Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor [dB/m]	T145 Preamp Gain [dB]	Cable Factor [dB]	T160 BRF [dB]	DC Corr [dB]	dB(uV/s/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Height [cm]	Polarity
4	2431.177	45.64	PK	32.4	-35	4.7	0.9	0	48.64	-	-	74	-25.36	200	Vert
5	6291.531	36.16	PK	36	-35	8.2	0.2	0	45.56	-	-	74	-28.44	100	Vert
6	9841.869	34.63	PK	37.6	-34.9	10.4	0.4	0	48.13	-	-	74	-25.87	200	Vert


Horizontal 10000 - 18000MHz															
Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uVolt s/meter)	E-Fields (dBuV/m) - Avg	Margin (dB)	E-Fields (dBuV/m) - Peak	Margin (dB)	Height (cm)	Polarity
7	11019.49	22.9	PK	38.3	-33.9	11	0.6	0	38.9	-	-	74	-35.1	100	Horz

Vertical 10000 - 18000MHz															
Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uV/m)	E-Fields (dBuV/m) - Avg	Margin (dB)	E-Fields (dBuV/m) - Peak	Margin (dB)	Height (cm)	Polarity
8	12370.82	22.01	PK	39.2	-32.8	11.8	0.5	0	40.71	-	-	74	-33.29	200	Vert

High Channel Horizontal



High Channel Vertical



High Channel

Project :13I14969
Company Name:Samsung
Model / Config:EUT with adapter
Mode:g mode high ch
Test By:Roy Zheng

Horizontal 1000 - 18000MHz

Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uV/s/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Height (cm)	Polarity
1	2460.904	42.44	PK	32.4	-35	4.7	0.9	0	45.44	-	-	74	-28.56	200	Horz
2	4924.057	37.77	PK	34.6	-34.9	7.1	0.2	0	44.77	-	-	74	-29.23	100	Horz
3	7170.622	36.22	PK	35.8	-35	8.8	0.3	0	46.12	-	-	74	-27.88	200	Horz

Vertical 1000 - 18000MHz

Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uV/s/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Height (cm)	Polarity
4	2460.904	40.98	PK	32.4	-35	4.7	0.9	0	43.98	-	-	74	-30.02	100	Vert
5	4210.592	38.06	PK	34.1	-34.8	6.4	0.3	0	44.06	-	-	74	-29.94	100	Vert
6	9850.362	34.69	PK	37.6	-34.9	10.4	0.6	0	48.39	-	-	74	-25.61	100	Vert

Horizontal 10000 - 18000MHz


Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uV/s/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Height (cm)	Polarity
7	11559.22	22.85	PK	38.8	-33.6	11.3	0.7	0	40.05	-	-	74	-33.95	100	Horz


Vertical 10000 - 18000MHz

Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uV/s/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Height (cm)	Polarity
8	13174.41	20.78	PK	39.1	-31.8	12.2	0.5	0	40.78	-	-	74	-33.22	200	Vert


9.2.3. TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 2.4 GHz BAND


RESTRICTED BANDEDGE (LOW CHANNEL)






$$\begin{aligned}
 \text{Actual Average} &= \text{Measured Average} + \text{Correction Factor} \\
 &= 42.777 \text{ dB}\mu\text{V} + 1.58 \\
 &= 44.357 \text{ dB}\mu\text{V}
 \end{aligned}$$







$$\begin{aligned}
 \text{Actual Average} &= \text{Measured Average} + \text{Correction Factor} \\
 &= 41.481 \text{ dBuV} + 1.58 \\
 &= 43.061 \text{ dBuV}
 \end{aligned}$$


AUTHORIZED BANDEGE (HIGH CHANNEL)






$$\begin{aligned}
 \text{Actual Average} &= \text{Measured Average} + \text{Correction Factor} \\
 &= 43.069 \text{ dBuV} + 1.58 \\
 &= 44.649 \text{ dBuV}
 \end{aligned}$$






$$\begin{aligned}
 \text{Actual Average} &= \text{Measured Average} + \text{Correction Factor} \\
 &= 41.169 \text{ dBuV} + 1.58 \\
 &= 42.749 \text{ dBuV}
 \end{aligned}$$

HARMONICS AND SPURIOUS EMISSIONS



Low Channel Vertical



Low Channel

Project :13I14969
Company Name:Samsung
Model / Config:EUT with adapter
Mode:n mode low ch
Test By:Roy Zheng

Horizontal 1000 - 18000MHz

Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uV/s/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Height (cm)	Polarity
1	2409.943	44	PK	32.4	-35	4.6	0.9	0	46.9	-	-	74	-27.1	100	Horz
2	4278.541	37.82	PK	34.1	-34.9	6.5	0.3	0	43.82	-	-	74	-30.18	100	Horz
3	7709.968	35.7	PK	36.2	-35.1	9.1	0.3	0	46.2	-	-	74	-27.8	200	Horz

Vertical 1000 - 18000MHz

Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uV/s/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Height (cm)	Polarity
4	2405.696	43.52	PK	32.3	-35	4.6	0.9	0	46.32	-	-	74	-27.68	200	Vert
5	2749.688	39.96	PK	32.8	-35.1	5	0.9	0	43.56	-	-	74	-30.44	100	Vert
6	9340.744	34.87	PK	37	-35.1	10.1	0.4	0	47.27	-	-	74	-26.73	200	Vert


Horizontal 10000 - 18000MHz

Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uV/s/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Height (cm)	Polarity
7	12030.99	22.9	PK	39.2	-33.3	11.6	0.8	0	41.2	-	-	74	-32.8	100	Horz
8	17276.36	21.43	PK	41.6	-31.7	14.4	0.5	0	46.23	-	-	74	-27.77	200	Horz


Vertical 10000 - 18000MHz

Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uV/s/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Height (cm)	Polarity
9	13718.14	22.51	PK	39.1	-32	12.5	0.4	0	42.51	-	-	74	-31.49	200	Vert
10	17324.34	21.2	PK	41.7	-31.6	14.5	0.6	0	46.4	-	-	74	-27.6	100	Vert

Mid Channel Horizontal



Mid Channel Vertical





[illegible]

Horizontal 1000 - 18000MHz															
Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor [dB/m]	T145 Preamp Gain [dB]	Cable Factor [dB]	T160 BRF [dB]	DC Corr [dB]	dB(uV/s/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Height [cm]	Polarity
1	2431.177	44.16	PK	32.4	-35	4.7	0.9	0	47.16	-	-	74	-26.84	200	Horz
2	4873.095	39.7	PK	34.7	-34.9	7.1	0.2	0	46.8	-	-	74	-27.2	100	Horz
3	8992.506	35.35	PK	36.8	-35.3	9.9	0.5	0	47.25	-	-	74	-26.75	200	Horz

Vertical 1000 - 18000MHz															
Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uVolt s/meter)	E-Fields (dBuV/m) - Avg	Margin (dB)	E-Fields (dBuV/m) - Peak	Margin (dB)	Height (cm)	Polarity
4	2426.93	43.58	PK	32.4	-35	4.7	0.9	0	46.58	-	-	74	-27.42	200	Vert
5	4851.861	37.09	PK	34.7	-34.9	7.1	0.2	0	44.19	-	-	74	-29.81	200	Vert
6	8138.896	36.65	PK	36.1	-35.2	9.4	0.3	0	47.25	-	-	74	-26.75	200	Vert

High Channel Horizontal





High Channel

Project :13I14969

Company Name:Samsung

Model / Config:EUT with adapter

Mode:n mode high ch

Test By:Roy Zheng

Horizontal 1000 - 18000MHz


Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uVolts/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Height (cm)	Polarity
1	2465.151	42.63	PK	32.4	-35	4.7	0.9	0	45.63	-	-	74	-28.37	200	Horz
2	7845.866	34.48	PK	36.2	-35.1	9.2	0.3	0	45.08	-	-	74	-28.92	100	Horz
3	9472.396	34.71	PK	37.2	-35.1	10.2	0.5	0	47.51	-	-	74	-26.49	200	Horz


Vertical 1000 - 18000MHz

Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T345 Ant Factor (dB/m)	T145 Preamp Gain (dB)	Cable Factor (dB)	T160 BRF (dB)	DC Corr (dB)	dB(uVolts/meter)	E-Fields [dBuV/m] - Avg	Margin (dB)	E-Fields [dBuV/m] - Peak	Margin (dB)	Height (cm)	Polarity
4	2460.904	40.86	PK	32.4	-35	4.7	0.9	0	43.86	-	-	74	-30.14	200	Vert
5	4711.716	37.64	PK	34.7	-34.9	6.9	0.3	0	44.64	-	-	74	-29.36	200	Vert
6	8160.13	36.42	PK	36.1	-35.2	9.4	0.3	0	47.02	-	-	74	-26.98	200	Vert

9.3. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)





HORIZONTAL AND VERTICAL DATA

Project No:13I14969										
Client Name:Samsung										
Model / Device:GT-I14969										
Config / Other:Tx b mode mid ch										
Test By:Danny Vu										

Horizontal 30 - 1000MHz

Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T130 Ant Factor [dB/m]	T64 preamp/cable loss [dB]	dB(uV/s/meter)	E-Fields [dBuV/m] - QPk	Margin (dB)	Height [cm]	Polarity
1	35.9368	45.31	PK	16.7	-27.6	34.41	40	-5.59	400	Horz
2	106.3303	44.78	PK	11.8	-27	29.58	43.52	-13.94	301	Horz
3	210.7694	41.88	PK	10.4	-26.3	25.98	43.52	-17.54	301	Horz
4	245.6633	40.46	PK	11.5	-25.9	26.06	46.02	-19.96	100	Horz
5	653.7272	29.36	PK	19.9	-23.2	26.06	46.02	-19.96	400	Horz

Vertical 30 - 1000MHz

Marker No.	Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T130 Ant Factor [dB/m]	T64 preamp/cable loss [dB]	dB(uV/s/meter)	E-Fields [dBuV/m] - QPk	Margin (dB)	Height [cm]	Polarity
6	36.7849	34.67	PK	16	-27.6	23.07	40	-16.93	299	Vert
7	91.7912	35.36	PK	8	-27.1	16.26	43.52	-27.26	299	Vert
8	155.2785	31.44	PK	12.2	-26.6	17.04	43.52	-26.48	199	Vert
9	386.4502	29.91	PK	15.1	-25.3	19.71	46.02	-26.31	399	Vert
10	743.385	29.23	PK	20.7	-23.2	26.73	46.02	-19.29	399	Vert

10. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

RSS-Gen 7.2.2

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.

The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.


Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

6 WORST EMISSIONS

Project No:13I14969									
Client Name:Samsung									
Model/Device:GT-I8552B									
Test Volt/Freq:120V/60Hz									
Test By:Danny Vu									
Line-L1 .15 - 30MHz									
Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T24 IL L1.TXT (dB)	LC Cables 1&3.TXT (dB)	dB(uVolts)	CFR 47 Part 15 Class B QP	Margin (dB)	CFR 47 Part 15 Class B Avg	Margin (dB)
0.447	47.92	PK	0.1	0	48.02	56.9	-8.88	-	-
0.447	32.85	Av	0.1	0	32.95	-	-	46.9	-13.95
0.9825	50.59	PK	0.1	0.1	50.79	56	-5.21	-	-
0.9825	32.95	Av	0.1	0.1	33.15	-	-	46	-12.85
1.8015	48.98	PK	0.1	0.1	49.18	56	-6.82	-	-
1.8015	31.01	Av	0.1	0.1	31.21	-	-	46	-14.79
3.8805	48.39	PK	0.1	0.1	48.59	56	-7.41	-	-
3.8805	31.92	Av	0.1	0.1	32.12	-	-	46	-13.88
16.8945	57.08	PK	0.2	0.2	57.48	60	-2.52	-	-
16.8945	36.8	Av	0.2	0.2	37.2	-	-	50	-12.8
Line-L2 .15 - 30MHz									
Test Frequency (MHz)	Meter Reading (dBuV)	Detector	T24 IL L1.TXT (dB)	LC Cables 1&3.TXT (dB)	dB(uVolts)	CFR 47 Part 15 Class B QP	Margin (dB)	CFR 47 Part 15 Class B Avg	Margin (dB)
0.825	46.32	PK	0.1	0	46.42	56	-9.58	-	-
0.825	26.8	Av	0.1	0	26.9	-	-	46	-19.1
0.915	46.83	PK	0.1	0	46.93	56	-9.07	-	-
0.915	27.54	Av	0.1	0	27.64	-	-	46	-18.36
1.824	45.25	PK	0.1	0.1	45.45	56	-10.55	-	-
1.824	26.01	Av	0.1	0.1	26.21	-	-	46	-19.79
3.849	43.79	PK	0.1	0.1	43.99	56	-12.01	-	-
3.849	27.6	Av	0.1	0.1	27.8	-	-	46	-18.2
16.8135	45.37	PK	0.2	0.2	45.77	60	-14.23	-	-
14.4285	43.22	PK	0.2	0.2	43.62	60	-16.38	-	-
14.4285	26.88	Av	0.2	0.2	27.28	-	-	50	-22.72

LINE 1 RESULTS



LINE 2 RESULTS

