

3.5 EUT Description

The following features describe EUT represented by this report:

Item	Specification and Description
Processor	TEMUJIN(300Mhz)
Standard System memory	Embedded SDRAM 8MB size
Resolution	1200x1200dpi
Copy Quality mode	N.A
Paper Handling	Paper Tray(BIN Type) 150 Sheets
Power Rating	110~127 VAC, 4A, 50/60 Hz
Power Consumption	Power save mode : 2.8 Watts Printing mode: MAX. 270 Watts
Printer Language	SPL
PC Interfaces	Hi-Speed USB 2.0
OS compatibility	Windows 2000/XP(32/64bits)/Vista(32/64bits)/Win7(32/64bits)/2003 Server(32/64bits)/2008 Server(32/64bits)/2008 Server R2 Various Linux OS including RedHat Enterprise Linux WS 4, 5 (32/64bit), Fedora 4~12 (32/64bit), SuSE Linux 10.0, 10.1 (32bit), OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64bit), Mandriva 2005, 2006, 2007, 2008, 2009, 2009.1 (32/64bit), Ubuntu 5.04, 5.10, 6.06, 6.10, 7.04, 7.10, 8.04 8.10, 9.04, 9.10 (32/64bit), SuSE Linux Enterprise Desktop 10, 11 (32/64bit), Debian 4.0, 5.0 (32/64bit) Mac OS X 10.3~10.6
Modes of Operation	USB Printing
Intended Class for Emissions	Class B