

1.2 Detail Information related product

1.2.1 Specification

Item	Specification and Description
Print Speed	Black and White : Up to 33 PPM in A4(35 PPM in Letter)
Resolution	Printer: Up to 1200 x 1200 dpi(effective output)
First print out time	From Standby Mode : Less than 8.5 seconds From ColdBoot : Less than 25 seconds
Warm-up time	Less than 15 seconds
Power Rating	110 ~ 127 VAC, 6.5A, 50/60 Hz
Power Consumption	Printing : 600 W Power Save mode : Less than 10 W
Noise Level	Printing mode: Less than 54 dBA Standby mode : Less than 39 dBA Warm-up: Less than 50dBA
Consumable life	Black Toner Cartridge : Approx. 4,000 A4/Letter pages at 5% Coverage
Duty cycle (Max. Monthly Volume)	Print: 20,000 pages
Weight	12.7 kg (including consumables)
Package weight	3.1 kg
External dimensions (W x D x H)	400 x 435 x 284 mm(15.7 x 17.1 x 11.2 in)
Operating Environment	Temperature : 10 ~ 32 (50 ~ 90) Humidity : 20 ~ 80 % RH
Printer Language	PCL6, PostScript3, PCL5e
Memory	64MB (MAX320MB)
Interface	USB 2.0, IEEE1284, Ethernet 10/100 Base TX, WLAN
OS compatibility	- Windows 98/Me/NT4.0/2000/XP(32/64bit)/2003 Server(32/64bit) - Mac OS 8.6~9.2/10.1~10.4 - Various Linux OS including Red Hat 8~9, Fedora Core 1~4, - Mandrake 9.2~10.1, and SuSE 8.2~9.2 - NetWare 4.x, 5.x, 6.x - Unix HP-UX, Solaris, SunOS, SCO UNIX

Operating Frequency

Main Source Clock : 12 MHz, Video Clock : 12 MHz, CPU Clock : 400 MHz
SDRAM Clock : 100 MHz, USB Device Clock : 12 MHz, Network Device Clock : 25 MHz
USB Clock = 6MHz, SD Memory Clock = 100MHz, MAC Clock = 25MHz