

4.5 EUT Description

The following features describe EUT represented by this report:

Item	Specification and Description
Processor	CHORUS3-NEXT(533MHz)
Standard System memory	128MB DDR3 SDRAM
Resolution	True 600x600dpi (Up to 1,200x1,200dpi effective output)
Paper Handling	Paper Tray(standard) 250Sheets Manual Tray 50Sheet
Power Rating	110~127VAC, 6.5A, 50/60Hz
Power Consumption	Sleep mode : 2Watts Ready mode : 60Watts Printing mode: 550Watts
Printer Language	PostScript3, PCL6/5e, IBM ProPrinter, EPSON
PC Interfaces	USB2.0, NW
OS compatibility	Windows 2000/XP(32/64bits)/ Vista(32/64bits)/2003 Server(32/64bits)/2008 Server(32/64bits)/ 7(32/64bit)/2008 Server R2 Various Linux OS: Fedora Core 4, 5, 6 Fedora 7, 8, 9, 10, 11, 12 RedHat Enterprise Linux WS 4, 5 SuSE 10.0, 10.1 openSuSE 10.2, 10.3, 11.0, 11.1, 11.2 SuSE Linux Enterprise Desktop 10, 11 Debian 4.0, 5.0 Ubuntu 5.04, 5.10, 6.04, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10 Mandriva 2005LE, 2006, 2007, 2007.1, 2008, 2008.1, 2009, 2009.1
Modes of Operation	USB Printing, 1200dpi Printing, Network Printing
Intended Class for Emissions	Class B