

FCC SAR Exclusion Report

Report No. : SFACHI-WTW-P24070446

Applicant : Samsung Electronics Co., Ltd.

Address : 129, Samsung-ro Yeongtong-gu, Suwon-si Gyeonggi-do 16677, Korea

Product : Notebook

Brand : SAMSUNG

Model No. : NP960QHA

Series Model No. : NP964QHA (refer to section 2 for more details)

FCC ID : A3LNP960QHA

FCC Rule Part : CFR §2.1093

Standards : IEEE Std 1528:2013
KDB 865664 D01 v01r04, KDB 865664 D02 v01r02,
KDB 447498 D01_v06_2015.10.23_General RF Exposure Guidance

Sample Received Date : Jul. 17, 2024

Date of Evaluation : Aug. 23, 2024

Lab Address : No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location : No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City, Taiwan

FCC Accredited No. : TW0003

CERTIFICATION: The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By : Vera Huang
Vera Huang / Specialist

Approved By : Gordon Lin
Gordon Lin / Manager



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1. Summary of Maximum SAR Value	4
2. Description of Equipment Under Test	5
3. SAR Measurement Evaluation	6
3.1 Maximum Output Power	6
3.2 SAR Testing Exclusions	7
4. Information on the Testing Laboratories	9



Release Control Record

Issue No.	Reason for Change	Date Issued
SFACHI-WTW-P24070446	Initial release	Aug. 26, 2024

FCC SAR Exclusion Report

1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest Reported SAR _{10g} (W/kg)
DCD	Digitizer	Not Required

Note:

1. The SAR limit (**Head & Body: SAR_{1g} 1.6 W/kg**) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

FCC SAR Exclusion Report

2. Description of Equipment Under Test

EUT Type	Notebook
Brand Name	SAMSUNG
Model Name	NP960QHA
Series Model Name	NP964QHA
Model Difference	Refer to Note
FCC ID	A3LNP960QHA
Tx Frequency Bands	531.2-562.3kHz
Maximum Tune-up Conducted Power (Unit: dBm)	Please refer to section 3.1 of this report
Antenna Type	Coil Antenna
EUT Stage	Engineering Sample

Note:

1. All models are listed as below. The model of NP960QHA was chosen for final test.

Brand	Model name	Difference
SAMSUNG	NP960QHA	For marketing purpose
	NP964QHA	

2. S-PEN is a non-active pen.

3. The EMR (electronic-magnetic resonance) technology consists of a layer of sensors that sits behind the device's Liquid Crystal Display (LCD) screen and a layer of hardened glass. The sensors are arranged in an alternating vertical/horizontal grid pattern. Each sensor is precisely calibrated and emits a weak electromagnetic signal. Together, these signals create a magnetic field that extends about 5mm beyond the glass surface of the device. When the S-pen is close to the Liquid Crystal Display (LCD) screen, the EMR emission behavior is triggered.

4. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

5. For synchronous TER calculation, please refer to FCC ID: PD9BE201D2

FCC SAR Exclusion Report

3. SAR Measurement Evaluation

3.1 Maximum Output Power

The maximum Tune up power (Unit: mW) including tune-up tolerance is shown as below.

Mode	Frequency (MHz)	Ant. 0 Max Tune-up (mW)
Digitizer	0.5312	0.00000000223872
	0.5623	0.00000000223872

FCC SAR Exclusion Report

3.2 SAR Testing Exclusions

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

A. For the test separation distance ≤ 50 mm

$$\frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 3.0$$

- When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

• For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left(\frac{f_{(\text{MHz})}}{150} \right) \right]_{(\text{mW})}$$

• For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz

$$[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(\text{mW})}$$

B. For 100 MHz to 6 GHz and test separation distances > 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following.

- {[Power allowed at numeric threshold for 50 mm in step A]} + [(test separation distance – 50 mm) · (f(MHz)/150)] mW, for 100 MHz to 1500 MHz
- {[Power allowed at numeric threshold for 50 mm in step A]} + [(test separation distance – 50 mm) × 10] mW, for > 1500 MHz and ≤ 6 GHz

C. For frequencies below 100 MHz, the following may be considered for SAR test exclusion.

- For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step B) is multiplied by $[1 + \log(100/f(\text{MHz}))]$
- For test separation distances ≤ 50 mm, the power threshold determined by the equation in C.(1) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$
- SAR measurement procedures are not established below 100 MHz.

Mode	Frequency (MHz)	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Exclusion (mW)	Require SAR Testing?
Digitizer	0.5623	-86.5	0.00000000223872	770.81	No

Note:

- When the device output power is less than the power threshold shown in above table, the SAR testing exclusion is applied.

Summary:

Since the SAR assess for all device orientations apply SAR test exclusion per KDB 447498, SAR testing for this device is not required.

FCC SAR Exclusion Report

<Estimated SAR Calculation>

According to KDB 447498 D01, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR was estimated according to following formula to result in substantially conservative SAR values of ≤ 0.4 W/kg to determine simultaneous transmission SAR test exclusion.

$$\text{Estimated SAR} = \frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \frac{\sqrt{f_{(\text{GHz})}}}{7.5}$$

If the minimum test separation distance is < 5 mm, a distance of 5 mm is used for estimated SAR calculation. When the test separation distance is > 50 mm, the 0.4 W/kg is used for SAR-1g and the 1.0 W/kg is used for SAR-10g

Mode	Frequency (GHz)	Max. Tune-up Power (dBm)	Separation Distance (mm)	Estimated 10g SAR (W/kg)
Digitizer	0.0005623	-86.5	5	0.000000000000057

Note:

1. The separation distance is determined from the outer housing of the EUT to the user.
2. This SAR estimation formula has been considered in conjunction with the SAR Test Exclusion Thresholds to result in substantially conservative SAR values of ≤ 0.4 W/kg.
3. When standalone SAR testing is not required, an estimated SAR can be applied to determine simultaneous transmission SAR test exclusion.

FCC SAR Exclusion Report

4. Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Taiwan Huaya Lab:

Add: No. 19, Huaya 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan

Tel: +886-(0)3-318-3232

Fax: +886-(0)3-211-5834

Taiwan Linkou Lab:

Add: No. 47-2, Baodoucuokeng, Linkou Dist., New Taipei City 244, Taiwan

Tel: +886-(0)2-2605-2180

Fax: +886-(0)2-2605-2943

Taiwan Hsinchu Lab1:

Add: E-2, No. 1, Lixing 1st Rd., East Dist., Hsinchu City 300, Taiwan

Tel: +886-(0)3-666-8565

Fax: +886-(0)3-666-8323

Taiwan Hsinchu Lab2:

Add: No. 49, Ln. 206, Wende Rd., Qionglin Township, Hsinchu County 307, Taiwan

Tel: +886-(0)3-512-0595

Fax: +886-(0)3-512-0568

Taiwan Xindian Lab:

Add: B2F., No. 215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan

Tel: +886-(0)2-8914-5882

Fax: +886-(0)2-8914-5840

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The road map of all our labs can be found in our web site also.

---END---