

4.5 EUT Description

The following features describe EUT represented by this report:

Item	Specification and Description
Processor	CHORUS3-N(433Mhz)
Standard System memory	128MB DDR2 SDRAM (SCX-3405F : 64M DDR2 SDRAM)
Resolution	1200 x 1200 dpi
Copy Quality mode	Text > Scan: 300x300dpi , Printing : 600x600dpi @ ADF Scan: 600x300dpi , Printing : 600x600dpi @ Platen Text/Photo > Scan: 300x300dpi , Printing : 600x600dpi @ ADF Scan: 600x300dpi , Printing : 600x600dpi @ Platen Photo > Scan: Scan: 600x300dpi , Printing : 600x600dpi @ ADF Scan: 600x600dpi , Printing : 1200x1200dpi @ Platen
Paper Handling	150-sheet Cassette @ 80g/m ² , 10-sheet @ Special Paper
Power Rating	110-127 VAC, 5A 50/60 Hz
Power Consumption	- . Power Save mode: 2.1W - . Printing Mode : 310W - . Ready Mode : 30W - . Off Mode : 0.45W
Printer Language	SPL
PC Interfaces	High speed USB2.0, 802.11 b/g/n
OS compatibility	Windows 2000/XP(32/64bits)/Vista(32/64bits)/2003 Server(32/64bits)/2008 Server(32/64bits)/7(32/64bits)/2008 Server R2(64bits) Mac OS X 10.4 ~ 10.6 RedHat Enterprise Linux WS 4, 5 (32/64 bit) Fedora 5, 6, 7, 8, 9, 10, 11, 12, 13 (32/64 bit) SuSE Linux 10.1 (32 bit) OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64 bit) Mandriva 2007, 2008, 2009, 2009.1, 2010 (32/64 bit) Ubuntu 6.06, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10, 10.04 (32/64 bit) SuSE Linux Enterprise Desktop 10, 11 (32/64 bit) Debian 4.0, 5.0 (32/64 bit) Sun Solaris 9,10 (x86, SPARC) HP-UX 11.0, 11i v1, 11i v2, 11i v3 (PA-RISC, Itanium) IBM AIX 5.1, 5.2, 5.3, 5.4
Modes of Operation	USB Printing, Platen Scan, Platen Copy, ADF Scan, ADF Copy, Wireless FAX
Intended Class for Emissions	Class B