

3.5 EUT Description

1. The following features describe EUT represented by this report:

Item	Specification and Description
Processor	CHORUS3-N(533Mhz)
Standard System memory	128MB DDR3 SDRAM
Resolution	True 600 x 600 dpi, addressable 1200 x 1200
Copy Quality mode	Text . scan: 600x600dpi(Optical 600x300dpi)@ ADF,Printing 600x600dpi /Photo . scan: 600x600dpi(Optical 600x600dpi)@ Platen,Printing 600x600dpi Photo . scan: 600x600dpi(Optical 300x300dpi)@ ADF,Printing 600x600dpi . scan: 1200x1200dpi(Optical 600x600dpi)@ Platen,Printing 600x600dpi
Paper Handling	250-sheet Cassette @ 80g/m ² , 1-sheet Multi Purpose Tray
Power Rating	90-135 VAC, 5.5A 50/60 Hz
Power Consumption	- Average operating mode : <350W - ready mode : <50W - Power save mode : <3.0W - off mode : <0.2W
Printer Language	GDI, PCL6
PC Interfaces	High speed USB2.0, Ethernet 10/100, 802.11 b/g/n, FAX
OS compatibility	Windows 2000/XP(32/64bits)/Vista(32/64bits)/2003 Server(32/64bits)/2008 Server(32/64bits)/7(32/64bits)/2008 Server R2(64bits) Mac OS X 10.4 ~ 10.6 RedHat Enterprise Linux WS 4, 5 (32/64 bit) Fedora 5, 6, 7, 8, 9, 10, 11, 12, 13 (32/64 bit) SuSE Linux 10.1 (32 bit) OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64 bit) Mandriva 2007, 2008, 2009, 2009.1, 2010 (32/64 bit) Ubuntu 6.06, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10, 10.04 (32/64 bit) SuSE Linux Enterprise Desktop 10, 11 (32/64 bit) Debian 4.0, 5.0 (32/64 bit) Sun Solaris 9,10 (x86, SPARC) HP-UX 11.0, 11i v1, 11i v2, 11i v3 (PA-RISC, Itanium) IBM AIX 5.1, 5.2, 5.3, 5.4
Modes of Operation	USB Printing, ADF Scan, ADF Copy, USB Printing, Fax RX, Fax TX, Network Printing, Wireless
Intended Class for Emissions	Class B