

3.5 EUT Description

The following features describe EUT represented by this report:

Item	Specification	Remarks
memory	128MB (Max 384MB)	-
Resolution	Up to 1 200 dpi effective output (Printer) Up to 1 200 * 600 dpi (Optical, Scanner) Up to 4 800 * 4 800 dpi (Enhanced, Scanner) Up to 600 * 300 dpi (Copier, Text)	-
Copy/Print Speed	Up to 28 ppm(A4), 29 ppm(Letter) for Simplex Printing Up to 28 cpm(A4), 29 cpm(Letter) for Copier	-
Display	16 characters * 2 lines	-
Copy Quality mode	text, text/photo, Magazine, Photo	-
Paper Handling	Paper Tray(standard) : 250 Sheets MP Tray : 1 sheet for paper 2nd Tray : 250 sheets	-
Power Rating	110~127 VAC, 7A, 50/60 Hz	-
Power Consumption	Operation : 450 WH Standby : Less than 60 WH Power save mode : Less than 12 WH Power off mode : 0 W	-
Interfaces	Fax 33.6kbps Tx/Rx (Tel line) Ethernet 10/100 Base TX(embedded type) High Speed USB 2.0	-
OS compatibility	Windows 2000 / XP / 2003 / Vista Linux Mac OS 10.3~10.5, Universal Mac	-
Modes of Operation	Copying, USB Printing, Network Printing, FAX, SCAN to USB, Standby	-
Intended Class for Emissions	Class B	-