

3.5 EUT Description

Item	Specification	Remarks
Processor	CHORUS4(600MHz)	-
Standard System memory	128MB DDR2 SDRAM	-
Resolution	True 600x600dpi (Addressible 1200dpi support)	-
Copy Quality mode	Text : Scan 300 x 300 dpi, Print: 600 x 600 dpi (Platen, ADF) Mixed : Scan 300 x 300 dpi, Print: 600 x 600 dpi (Platen, ADF) Photo : Scan 300 x 300 dpi, Print: 600 x 600 dpi (ADF) Scan 600 x 600 dpi, Print: 1200 x 1200 dpi (Platen)	-
Paper Handling	Paper Tray(standard) 250 Sheets MP Tray 50sheets	-
Power Rating	110~127 Vac, 5A, 50/60 Hz	-
Power Consumption	Power save mode : 9 Watts Printing mode: MAX. 600 Watts	-
Printer Language	PCL6/PS3	-
PC Interfaces	USB2.0, NW, FAX	-
OS compatibility	Windows 2000/XP (32/64 bits) /Vista (32/64 bits) /2003 Server (32/64 bits) /2008 Server(32/64 bits) /7 (32/64 bits) /2008 Server R2 Various Linux OS:Fedora Core 4, 5, 6,Fedora 7, 8, 9, 10, 11, 12, RedHat Enterprise Linux WS 4, 5, SuSE 10.0, 10.1 openSuSE 10.2, 10.3, 11.0, 11.1, 11.2 SuSE Linux Enterprise Desktop 10, 11 Debian 4.0, 5.0 Ubuntu 5.04, 5.10, 6.04, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10 Mandriva 2005LE, 2006, 2007, 2007.1 2008, 2008.1, 2009, 2009.1 Mac OS 10.3 ~ 10.6	-
Modes of Operation	USB Printing, ADF Scan, ADF Copy, 1200dpi Printing, Fax RX, Fax TX, Network Printing	-
Intended Class for Emissions	Class B	-