



**FCC CFR47 PART 15 DIGITAL DEVICE**

**TEST REPORT**

**FOR**

**DVD ROM DRIVE**

**MODEL: SDR-430**

**FCC ID: A3LSDR430**

**REPORT NUMBER: 98E7557**

**ISSUE DATE: JULY 15, 1998**

*Prepared for*  
**SAMSUNG ELECTRONICS CO., LTD.**  
**416 MAETAN DONG, PALDAL GU**  
**SUWON SHI, KOREA**

*Prepared by*  
**COMPLIANCE ENGINEERING SERVICES, INC.**  
**1366 BORDEAUX DRIVE**  
**SUNNYVALE, CA 94089, USA**  
**TEL: (408) 752-8166**  
**FAX: (408) 752-8168**

**NVLAP<sup>®</sup>**  
**LAB CODE:200065-0**

| TABLE OF CONTENTS                            | PAGE |
|----------------------------------------------|------|
| 1. VERIFICATION OF COMPLIANCE .....          | 1    |
| 2. PRODUCT DESCRIPTION .....                 | 2    |
| 3. TESTED SYSTEM DETAILS.....                | 2    |
| 4. TEST FACILITY.....                        | 3    |
| 5. ACCREDITATION AND LISTING .....           | 3    |
| 6. MEASUREMENT INSTRUMENTATION .....         | 3    |
| 7. MEASURING INSTRUMENT CALIBRATION .....    | 4    |
| 8. UNITS OF MEASUREMENT.....                 | 4    |
| 9. ANTENNAS .....                            | 5    |
| 10. CLASSIFICATION OF DIGITAL DEVICE.....    | 5    |
| 11. RADIATED EMISSION LIMITS .....           | 5    |
| 12. CONDUCTED EMISSION LIMITS .....          | 6    |
| 13. CONDUCTED EMISSION TEST PROCEDURE.....   | 8    |
| 14. RADIATED EMISSION TEST PROCEDURE .....   | 8    |
| 15. AMBIENT CONDITIONS .....                 | 9    |
| 16. SYSTEM TEST CONFIGURATION .....          | 9    |
| 17. EQUIPMENT MODIFICATIONS.....             | 10   |
| 18. EUT SETUP PHOTOS .....                   | 11   |
| 19. TEST EQUIPMENT LIST .....                | 12   |
| 20. TEST RESULT SUMMARY.....                 | 13   |
| APPENDICES.....                              | 15   |
| .EXTERNAL I/O CABLE CONSTRUCTION DESCRIPTION |      |
| .CONFIGURATION BLOCK DIAGRAM                 |      |
| .EUT PHOTOGRAPHS                             |      |

## 1. VERIFICATION OF COMPLIANCE

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.  
416 MAETAN DONG, PALDAL GU  
SUWON SHI, KOREA



CONTACT PERSON: BEN KIM / MANAGER

TELEPHONE NO: 408-544-5124

MODEL NO/NAME: SDR-430

SERIAL NO: N/A DATE TESTED: JULY 15, 1998

|                                       |                                                                                                           |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------|
| TYPE OF EQUIPMENT:                    | INFORMATION TECHNOLOGY EQUIPMENT (ITE)                                                                    |
| MEASUREMENT DISTANCE:                 | (X) 3 METER ( ) 10 METER                                                                                  |
| TECHNICAL LIMIT:                      | CLASS B                                                                                                   |
| FCC RULES:                            | PART 15                                                                                                   |
| MEASUREMENT PROCEDURE                 | ANSI C63.4:92                                                                                             |
| EQUIPMENT AUTHORIZATION PROCEDURE     | CERTIFICATION                                                                                             |
| MODIFICATIONS MADE ON EUT             | <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO                                       |
| DEVIATIONS FROM MEASUREMENT PROCEDURE | <input type="checkbox"/> YES (refer to section 21 for comments)<br><input checked="" type="checkbox"/> NO |
| RADIATED EMISSION TEST RESULT         | -15.56 dB@ 166.47 MHz/VERTICAL                                                                            |
| CONDUCTED EMISSION TEST RESULT        | -14.3 dB @ 22.165 MHz/L2                                                                                  |

The above equipment was tested by Compliance Consulting Services for compliance with the requirements set forth in the FCC CFR 47, PART 15. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved By



MIKE C.I. KUO / VICE PRESIDENT  
COMPLIANCE CONSULTING SERVICES

## 2. PRODUCT DESCRIPTION

|                                                    |                     |
|----------------------------------------------------|---------------------|
| CHASSIS TYPE                                       | PLASTIC & METAL     |
| CPU SPEEDS TESTED                                  | 133 Mhz PENTIUM     |
| LIST OF EACH OSC. OR XTAL. FREQ.<br>(FREQ.>=1 MHz) | 22.5792, 20, 50 MHz |
| CHIPSET BRAND AND PART NO.                         | TOSHIBA TC9453F     |
| NUMBER OF PCB LAYERS                               | 4                   |
| BOARD REVISION NO                                  | 01                  |
| POWER REQUIREMENTS                                 | 120 V AC, 60 Hz     |
| NO. OF EXTERNAL I/O CONNECTORS                     | 1                   |

## 3. TESTED SYSTEM DETAILS

The Model names for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

### External Peripheral Devices

| Device Type | Manufacturer | Model Number      | Serial No.   | FCC ID / DoC  |
|-------------|--------------|-------------------|--------------|---------------|
| MONITOR     | SAMSUNG      | CKE5507L          | N/A          | DoC           |
| KEYBOARD    | UNISYS       | PCK-101-KBD       | 8406-056618  | EW4KPQ2479D   |
| MOUSE       | MICROSOFT    | INTELLIMOUSE      | 00768461     | C3KKZB1       |
| MODEM       | HAYES        | 4007AM            | A00840073172 | BFJ4000AM     |
| PRINTER     | HP           | 2225C             | 2511S41679   | BS46XU2225C   |
| COMPUTER    | AST          | BRAVO MS<br>P/133 | 415ASN000967 | DJKEAGLE-MS-P |
| HEADPHONE   | HP           | LT-100            | N/A          | N/A           |

#### **4. TEST FACILITY**

The open area test sites and conducted measurement facilities used to collect the radiated data are located at 561F Monterey Road, Morgan Hill, California, USA. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

#### **5. ACCREDITATION AND LISTING**

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code:200065-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission (reference no: 31040/SIT (1300B3) and 31040/SIT(1300F2))

#### **6. MEASUREMENT INSTRUMENTATION**

Radiated emissions were measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, ridged waveguide, liner horn.

EMI receivers were used for line conducted readings, spectrum analyzers with pre-selectors and quasi-peak detectors were used to perform radiated measurements. Receiving equipment (i.e., receiver, analyzer, quasi-peak adapter, pre-selector) and LISNs conform to CISPR specification for "Radio Interference Measuring Apparatus and Measurement Methods," Publication 16.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

## 7. MEASURING INSTRUMENT CALIBRATION

The measuring equipment which was utilized in performing the tests documented herein has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment which is traceable to recognized national standards.

## 8. UNITS OF MEASUREMENT

Measurements of radiated interference are reported in terms of dB(uV/m) at a specified distance. The indicated readings on the spectrum analyzer were converted to dB(uV/m) by use of appropriate conversion factors. Measurements of conducted interference are reported in terms of dB(uV).

The field strength is calculated by adding the Antenna Factor and Cable Factors, then by subtracting the Amplifier Gain from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Amplifier Gain

Assume a receiver reading of 52.5 dBuV is obtained. The Antenna Factor of 7.4dB/m and a Cable Factor of 1.1dB is added. The Amplifier Gain of 29 dB is subtracted, giving a field strength of 32 dBuV/m. The 32 dBuV/m value was mathematically converted to its corresponding level in uV/m.

$$FS = 52.5 + 7.4 + 1.1 - 29 = 32 \text{ dBuV/m}$$

$$\text{Level in uV/m} = \text{Common Antilogarithm} [(32 \text{ dBuV/m})/20] = 39.8 \text{ uV/m}$$

## 9. ANTENNAS

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 3 meters from the leading edge of the turn table.

## 10. CLASSIFICATION OF DIGITAL DEVICE

Class A includes digital devices that are marketed for use in commercial, industrial or business environments, excluding devices which are marketed for use by the general public or are intended to be used in the home.

Class B includes digital devices that are marketed for use in residential environments, notwithstanding use in commercial, business and industrial environments.

Note: The responsible party may also qualify a device intended to be marketed in a commercial, business or industrial environment as Class B device, and in fact is encouraged to do so provided the device complies with the technical specifications for a Class B digital device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B digital device, regardless of its intended use.

## 11. RADIATED EMISSION LIMITS

### FCC PART 15 CLASS A

#### MEASURING DISTANCE OF 10 METER

| FREQUENCY RANGE<br>(MHz) | FIELD STRENGTH<br>(Microvolts/m) | FIELD STRENGTH<br>(dBuV/m) |
|--------------------------|----------------------------------|----------------------------|
| 30-88                    | 90                               | 39.1                       |
| 88-216                   | 150                              | 43.5                       |
| 216-960                  | 210                              | 46.4                       |
| Above 960                | 300                              | 49.5                       |

FCC PART 15 CLASS B

| MEASURING DISTANCE OF 3 METER |                                  |                            |
|-------------------------------|----------------------------------|----------------------------|
| FREQUENCY RANGE<br>(MHz)      | FIELD STRENGTH<br>(Microvolts/m) | FIELD STRENGTH<br>(dBuV/m) |
| 30-88                         | 100                              | 40                         |
| 88-216                        | 150                              | 43.5                       |
| 216-960                       | 200                              | 46                         |
| Above 960                     | 500                              | 54                         |

**FCC RADIATED EMISSION ALTERNATIVE METHOD  
(CISPR 22/EN55022)**

Limits for radiated disturbance of Class A ITE at  
measuring distance of 10 m

| Frequency range<br>MHz                                                                                                                                       | Quasi-peak limits<br>dB(uV/m) |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
| 30 to 230                                                                                                                                                    | <b>40</b>                     |
| 230 to 1000                                                                                                                                                  | <b>47</b>                     |
| <b>NOTES</b><br>1. The lower limit shall apply at the transition frequency.<br>2. Additional provisions may be required for cases where interference occurs. |                               |

Limits for radiated disturbance of Class B ITE at  
measuring distance of 10 m

| Frequency range<br>MHz                                                                                                                                       | Quasi-peak limits<br>dB(uV/m) |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
| 30 to 230                                                                                                                                                    | <b>30</b>                     |
| 230 to 1000                                                                                                                                                  | <b>37</b>                     |
| <b>NOTES</b><br>1. The lower limit shall apply at the transition frequency.<br>2. Additional provisions may be required for cases where interference occurs. |                               |

**12. CONDUCTED EMISSION LIMITS**

FCC CLASS A

| FREQUENCY RANGE  | FIELD STRENGTH<br>(Microvolts) | FIELD STRENGTH<br>(dBuV)/QP |
|------------------|--------------------------------|-----------------------------|
| 450kHz-1.705MHz  | 1000                           | 60                          |
| 1.705mhz - 30mhz | 3000                           | 69.54                       |

FCC CLASS B

| FREQUENCY RANGE | FIELD STRENGTH<br>(Microvolts) | FIELD STRENGTH<br>(dBuV)/QP |
|-----------------|--------------------------------|-----------------------------|
| 450kHz-30MHz    | 250                            | 48                          |

**FCC CONDUCTED EMISSION ALTERNATIVE METHOD  
(CISPR 22/EN55022)**

Limits for conducted disturbance at the mains ports of  
Class A ITE

| Frequency range<br>MHz                                         | Limits<br>dB(uV) |         |
|----------------------------------------------------------------|------------------|---------|
|                                                                | Quasi-peak       | Average |
| 0.15 to 0.50                                                   | 79               | 66      |
| 0.5 to 30                                                      | 73               | 60      |
| Note- The lower limit shall apply at the transition frequency. |                  |         |

Limits of Conducted disturbance at the mains ports  
of Class B ITE

| Frequency range<br>MHz                                                                                                                                                       | Limits<br>dB(uV) |          |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|----------|
|                                                                                                                                                                              | Quasi-peak       | Average  |
| 0.15 to 0.50                                                                                                                                                                 | 66 to 56         | 56 to 46 |
| 0.50 to 5                                                                                                                                                                    | 56               | 46       |
| 5 to 30                                                                                                                                                                      | 60               | 50       |
| Note<br>1.The lower limit shall apply at the transition frequencies<br>2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz. |                  |          |

### 13. CONDUCTED EMISSION TEST PROCEDURE

The EUT is located so that the distance between the boundary of the EUT and the closest surface to the LISN is 0.8m.

EUT test configuration is according to Section 7 of ANSI C63.4/1992.

Conducted disturbance shall be measured between the phase lead and the ground, and between the neutral lead and the ground. The frequency 0.450 - 30 MHz (or 0.150 - 30 MHz in case of CISPR 22/EN55022 method) shall be investigated.

Set the EMI receiver to PEAK detector setting and sweep continuously over the frequency range to be investigated. Set resolution bandwidth to 9kHz minimum. Connect EMI receiver input cable to LINE 1 RF measurement connection on the LISN. Connect a 50ohm terminator to the unused RF connection on the LISN. For each mode of EUT operation, maximize emissions readings by manipulating cable and wire positions. Record the configuration for each EUT power cord which produces emissions closest to the limit. Repeat the same procedure for LINE 2 of each EUT power cord.

### 14. RADIATED EMISSION TEST PROCEDURE

The EUT and all other support equipment are placed on a wooden table 80 cm above the ground screen. Antenna to EUT distance is either 3 meters or 10 meters (Class B or Class A). During the test, the table is rotated 360 degrees to maximize emissions and the antenna is positioned from 1 to 4 meters above the ground screen to further maximize emissions. The antenna is polarized in both vertical and horizontal positions.

EUT test configuration is according to Section 8 of ANSI C63.4/1992.

Monitor the frequency range of interest at a fixed antenna height and EUT azimuth. Frequency span should be small enough to easily differentiate between broadcast stations and intermittent ambients. Rotate EUT 360 degrees to maximize emissions received from EUT. If emission increases by more than 1 dB, or if another emission appears that is greater by 1 dB, return to azimuth where maximum occurred and perform

additional cable manipulation to further maximize received emission.

Move antenna up and down to further maximize suspected highest amplitude signal. If emission increased by 1 dB or more, or if another emission appears that is greater by 1dB or more, return to antenna height where maximum signal was observed and manipulate cables to produce highest emissions, noting frequency and amplitude.

## 15. AMBIENT CONDITIONS

The ambient conditions at the time of final tests were as follows:

|             | Radiated Emission | Conducted Emission |
|-------------|-------------------|--------------------|
| Temperature | 35 ° C            | 23° C              |
| Humidity    | 53%               | 50%                |

## 16. SYSTEM TEST CONFIGURATION

The equipment under test was configured and operated in a manner which tended to maximize its emission characteristics in a typical application. Power and signal distribution, ground, interconnecting cabling and physical placement of equipment simulated the typical application and usage insofar as practicable.

| SOFTWARE USED DURING THE TESTS |                                                                                |
|--------------------------------|--------------------------------------------------------------------------------|
| Operating System               | N/A                                                                            |
| File Name                      | N/A                                                                            |
| Program Sequence               | Insert CD in DVD ROM Drive and press play, and then it will play continuously. |

## 17. EQUIPMENT MODIFICATIONS

To achieve compliance to CLASS B levels, the following change(s) were made during compliance testing:

NOT APPLICABLE

## 18. EUT SETUP PHOTOS



### Radiated Emission Setup Photos (Worst Emission Position)



### Conducted Emission Setup Photos (Worst Emission Position)

## 19. TEST EQUIPMENT LIST

| Equipment           | Manufacturer  | Model No.              | Serial No.  | Site | Cal Date | Due Date |
|---------------------|---------------|------------------------|-------------|------|----------|----------|
| Receiver            | H.P.          | 8546A                  | 3520A00259  | A    | 03/98    | 03/99    |
| RF Filter Section   | H.P.          | 85460A                 | 3448A00232  | A    | 03/98    | 03/99    |
| Antenna             | Chase         | CBL6112                | 2049        | A/F  | 05/98    | 05/99    |
| Antenna             | EMCO          | 3110                   | 8908-1079   | A/F  | 10/97    | 10/98    |
| Antenna             | EMCO          | 3146                   | NSN=X100    | A/F  | 10/97    | 10/98    |
| Pre-Amp             | H.P.(P2)      | 8447D                  | 2944A06265  | A/F  | 09/97    | 09/98    |
| Spectrum Analyzer   | H.P.          | 8566B                  | 3014A06685  | F    | 08/97    | 08/98    |
| Spectrum Display    | H.P.          | 85662A                 | 3026A19146  | F    | 08/97    | 08/98    |
| Quasi-peak Detector | H.P.          | 85650A                 | 3145A01654  | F    | 07/98    | 07/99    |
| Spectrum Analyzer   | H.P.          | 8568A                  | 2314A02604  | B    | 02/98    | 02/99    |
| Spectrum Display    | H.P.          | 85662A                 | 2314A04793  | B    | 02/98    | 02/99    |
| Quasi-peak Detector | H.P.          | 85650A                 | 2521A01038  | B    | 02/98    | 02/99    |
| Pre-Amp             | H.P.(P8)      | 8447D                  | 2944A06589  | B    | 09/97    | 09/98    |
| Antenna             | Eaton         | 94455-1                | 1197        | B    | 10/97    | 10/98    |
| Antenna             | Emco          | 3146                   | 2120        | B    | 10/97    | 10/98    |
| Spectrum Analyzer   | H.P.          | 8568B                  | 2732A03661  | C    | 04/98    | 04/99    |
| Spectrum Display    | H.P.          | 85662A                 | 2811A015728 | C    | 04/98    | 04/99    |
| Quasi-peak Detector | H.P.          | 85650A                 | 2811A01335  | C    | 11/97    | 11/98    |
| Pre-Amp             | H.P.(P5)      | 8447D                  | 2944A06550  | C    | 09/97    | 09/98    |
| Antenna             | Eaton         | 94455-1                | 1214        | C    | 10/97    | 10/98    |
| Antenna             | EMCO          | 3146                   | 9107-3163   | C    | 10/97    | 10/98    |
| LISN                | Fischer       | LISN2                  | N/A         | Cond | 01/98    | 01/99    |
| LISN                | Fischer       | CISPR adapter          | N/A         | Cond | 01/98    | 01/99    |
| EMI Receiver        | Rhode Schwarz | ESHS20                 | 827129/006  | Cond | 03/98    | 03/99    |
| LISN                | Fischer       | FCCLISN<br>50/250-25-2 | 114         | Cond | 08/97    | 08/98    |

## 20. TEST RESULT SUMMARY

**Preliminary Radiated Emission Tests** were performed at the 3 meter open area test site. CCS test procedure no:CCSUE2001B and the procedure listed in ANSI C63.4 /1992 section 8.3.1.1. were used. The following preliminary tests were conducted to determine the worst mode of operation and configuration.

| Preliminary Radiated Emission Test |                 |                    |                                     |
|------------------------------------|-----------------|--------------------|-------------------------------------|
| Frequency Range Investigated       |                 | 30 MHz TO 1000 MHz |                                     |
| Mode of operation                  | Date            | Data Report No.    | Worst Mode                          |
| <b>PLAY DVD MOVIE</b>              | <b>07/15/98</b> | <b>980715F1</b>    | <input checked="" type="checkbox"/> |

**Final Radiated Emission Test** was conducted by operating the worst mode as indicated above.

|                                        |                            |                             |                                  |                    |                |                             |                |
|----------------------------------------|----------------------------|-----------------------------|----------------------------------|--------------------|----------------|-----------------------------|----------------|
| OATS No:<br>F / 3 METER                |                            | Data Report No.<br>980715F1 |                                  | Date<br>07/15/98   |                | Tested By:<br>KERWIN CORPUZ |                |
| Six Highest Radiated Emission Readings |                            |                             |                                  |                    |                |                             |                |
| Frequency Range Investigated           |                            |                             |                                  | 30 MHz TO 1000 MHz |                |                             |                |
| Freq<br>(MHz)                          | Meter<br>Reading<br>(dBuV) | C.F.<br>(dB/m)              | Corrected<br>Reading<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Reading<br>Type<br>(P/Q/A)  | Polar<br>(H/V) |
| 31.37                                  | 38.8                       | -14.9                       | 23.90                            | 40.0               | -16.10         | P                           | V              |
| 50.41                                  | 41.5                       | -20.53                      | 20.97                            | 40.0               | -19.03         | P                           | V              |
| 131.52                                 | 38.9                       | -14.74                      | 24.16                            | 43.5               | -19.34         | P                           | V              |
| 149.14                                 | 38.4                       | -13.42                      | 24.98                            | 43.5               | -18.52         | P                           | V              |
| 166.47                                 | 39.9                       | -11.96                      | 27.94                            | 43.5               | -15.56         | P                           | V              |
| 213.1                                  | 39.1                       | -16.10                      | 23.0                             | 43.5               | -20.5          | P                           | V              |

C.F.(Correction Factor)=Antenna Factor+Cable Loss-Amplifier Gain

Corrected Reading = Metering Reading + C.F.

Margin=Corrected Reading - Limits

P=Peak Reading

H=Horizontal Polarization/Antenna

Q=Quasi-peak

V=Vertical Polarization/Antenna

A=Average Reading

Comments: N/A

**Preliminary Conducted Emission Tests** were performed according to CCS test procedure no:CCSUE2002B and ANSI C63.4/1992 section 7.2.3. The following preliminary tests were conducted to determine the worst mode of operation.

| Preliminary Conducted Emission Test |          |                      |                                     |
|-------------------------------------|----------|----------------------|-------------------------------------|
| Frequency Range Investigated        |          | 450 kHz TO 30 MHz    |                                     |
| Mode of operation                   | Date     | Data Report/Plot No. | Worst Mode                          |
| PLAY DVD MOVIE                      | 07/15/98 | N/A                  | <input checked="" type="checkbox"/> |

**Final Conducted Emission Test** was conducted by operating the worst mode as indicated above.

|                                         |                      |                 |                            |                   |             |                             |              |
|-----------------------------------------|----------------------|-----------------|----------------------------|-------------------|-------------|-----------------------------|--------------|
| Conducted Room                          |                      | Plot No.<br>N/A |                            | Date<br>07/15/98  |             | Tested By:<br>KERWIN CORPUZ |              |
| Six Highest Conducted Emission Readings |                      |                 |                            |                   |             |                             |              |
| Frequency Range Investigated            |                      |                 |                            | 450 kHz TO 30 MHz |             |                             |              |
| Freq (MHz)                              | Meter Reading (dBuV) | C.F. (dB)       | Corrected Reading (dBuV/m) | Limits (dBuV/m)   | Margin (dB) | Reading Type (P/Q/A)        | Line (L1/L2) |
| 2.23                                    | 31.2                 | 0               | 31.2                       | 48.0              | -16.8       | P                           | L1           |
| 2.36                                    | 31.5                 | 0               | 31.5                       | 48.0              | -16.5       | P                           | L1           |
| 6.0                                     | 31.9                 | 0               | 31.9                       | 48.0              | -16.1       | P                           | L1           |
| 0.79                                    | 31.1                 | 0               | 31.1                       | 48.0              | -16.9       | P                           | L2           |
| 6.0                                     | 31.6                 | 0               | 31.6                       | 48.0              | -16.4       | P                           | L2           |
| 22.165                                  | 33.7                 | 0               | 33.7                       | 48.0              | -14.3       | P                           | L2           |

C.F.(Correction Factor)=Insertion Loss + Cable Loss

Corrected Reading = Metering Reading + C.F.

Margin=Corrected Reading - Limits

P=Peak Reading

L1=Hot

Q=Quasi-peak

L2=Neutral

A=Average Reading

Comments: N/A

## **APPENDICES**

EXTERNAL I/O CABLE CONSTRUCTION DESCRIPTION

CONFIGURATION BLOCK DIAGRAM

EUT PHOTOGRAPHS

### External I/O Cable Construction Description

| CABLE NO: 1                  |                                     |
|------------------------------|-------------------------------------|
| I/O Port: Keyboard           | Number of I/O ports of this type: 1 |
| Number of Conductors: 6      | Connector Type: PS/2                |
| Capture Type: Push-In        | Type of Cable used: Shielded        |
| Cable Connector Type: Molded | Cable Length: 1.5 m                 |
| Bundled During Tests: No     | Data Traffic Generated: Yes         |
| Remark: N/A                  |                                     |

| CABLE NO: 2                  |                                     |
|------------------------------|-------------------------------------|
| I/O Port: Mouse              | Number of I/O ports of this type: 1 |
| Number of Conductors: 6      | Connector Type: PS/2                |
| Capture Type: Push-In        | Type of Cable used: Shielded        |
| Cable Connector Type: Molded | Cable Length: 1.8 m                 |
| Bundled During Tests: No     | Data Traffic Generated: Yes         |
| Remark: N/A                  |                                     |

| CABLE NO: 3                  |                                     |
|------------------------------|-------------------------------------|
| I/O Port: Headphone          | Number of I/O ports of this type: 1 |
| Number of Conductors: 3      | Connector Type: Stereo Plug         |
| Capture Type: Push-In        | Type of Cable used: Unshielded      |
| Cable Connector Type: Molded | Cable Length: 2.6 m                 |
| Bundled During Tests: Yes    | Data Traffic Generated: Yes         |
| Remark: N/A                  |                                     |

| CABLE NO: 4                                      |                                     |
|--------------------------------------------------|-------------------------------------|
| I/O Port: VGA                                    | Number of I/O ports of this type: 1 |
| Number of Conductors: 14                         | Connector Type: S-SUB 15            |
| Capture Type: Screw-In                           | Type of Cable used: Shielded        |
| Cable Connector Type: Molded                     | Cable Length: 1.6 m                 |
| Bundled During Tests: Yes                        | Data Traffic Generated: Yes         |
| Remark: Ferrite cores at both ends of connector. |                                     |

| CABLE NO: 5                 |                                     |
|-----------------------------|-------------------------------------|
| I/O Port: RS232             | Number of I/O ports of this type: 1 |
| Number of Conductors: 9     | Connector Type: DB9                 |
| Capture Type: Screw-In      | Type of Cable used: Shielded        |
| Cable Connector Type: Metal | Cable Length: 2.3 m                 |
| Bundled During Tests: No    | Data Traffic Generated: No          |
| Remark: N/A                 |                                     |

| CABLE NO: 6                 |                                     |
|-----------------------------|-------------------------------------|
| I/O Port: Parallel          | Number of I/O ports of this type: 1 |
| Number of Conductors: 25    | Connector Type: DB25                |
| Capture Type: Screw-In      | Type of Cable used: Shielded        |
| Cable Connector Type: Metal | Cable Length: 2.3 m                 |
| Bundled During Tests: Yes   | Data Traffic Generated: No          |
| Remark: N/A                 |                                     |

| CABLE NO: 7, 8               |                                     |
|------------------------------|-------------------------------------|
| I/O Port: AC Power           | Number of I/O ports of this type: 2 |
| Number of Conductors: 3      | Connector Type: USA Power Plug      |
| Capture Type: Push-In        | Type of Cable used: Unshielded      |
| Cable Connector Type: Molded | Cable Length: 1.8 m                 |
| Bundled During Tests: No     | Data Traffic Generated: No          |
| Remark: N/A                  |                                     |

| CABLE NO: 9                  |                                     |
|------------------------------|-------------------------------------|
| I/O Port: AC Adaptor         | Number of I/O ports of this type: 1 |
| Number of Conductors: 2      | Connector Type: USA                 |
| Capture Type: Push-In        | Type of Cable used: Unshielded      |
| Cable Connector Type: Molded | Cable Length: 2 m                   |
| Bundled During Tests: No     | Data Traffic Generated: No          |
| Remark: N/A                  |                                     |

| CABLE NO: 10                                                 |                                     |
|--------------------------------------------------------------|-------------------------------------|
| I/O Port: AC Power                                           | Number of I/O ports of this type: 1 |
| Number of Conductors: 3                                      | Connector Type: USA                 |
| Capture Type: Push-In                                        | Type of Cable used: Unshielded      |
| Cable Connector Type: Molded                                 | Cable Length: 1.8 m                 |
| Bundled During Tests: No- Radiation,<br>Yes- Line Conduction | Data Traffic Generated: No          |
| Remark: N/A                                                  |                                     |

### Configuration Block Diagram

