

ProXpress M4025DW Technical Specification

Item	Specification and Description
Processor	A1500 (600MHz)
Standard System memory	128MB DDR3 (M33****, M38**** series) 256MB DDR3 (M40**** series) Option 512MB DDR3 (except M38**D series)
Resolution	Pseudo 1200 dpi
Speed	ProXpress M33**** series 33ppm ProXpress M38**** series 38ppm ProXpress M40**** series 40ppm
Paper Handling	Paper Tray(standard) 250 Sheets SCF Tray(option) 520 Sheets MP Tray 1 Sheet (M33**ND, M38**D series) MP Tray 50 Sheets (M38**ND, M38**DW, M40**ND series)
Power Rating	110VAC ~ 127VAC, 6.5A, 50/60 Hz
Power Consumption	Power save mode : 0.9 Watts 2.1 Watts (WI-FI model) Stand by mode : 60 Watts Printing simplex : 600 Watts
Printer Language	SPL,PCL6,PS3,PCL5e, IBM Proprint, EPSON, KS, KSSM, PDF V1.7
Interfaces	USB2.0, Network, WI-FI
OS compatibility	Window XP (32/64 bit) / 2003 Server (32/64 bit) / Vista (32/64 bit) / 2008 server (32/64 bit) / 7 (32/64 bit) / 2008 Server R2 / 8 (32/64bit) Linux : RedHat Enterprise Linux WS 4, 5, 6 (32/64 bit) / Fedora 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15 (32/64 bit) / OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2, 11.3, 11.4 (32/64 bit) / Mandriva 2007, 2008, 2009, 2009.1, 2010 (32/64 bit) / Ubuntu 6.06, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10, 10.04, 10.10, 11.04 (32/64 bit) / SuSE Linux Enterprise Desktop 10, 11 (32/64 bit) / Debian 4.0, 5.0, 6.0 (32/64 bit) UNIX : Sun Solaris 9,10,11 (x86, SPARC) / HP-UX 11.0, 11i v1, 11i v2, 11i v3 (PA-RISC, Itanium) / IBM AIX 5.1, 5.2, 5.3, 5.4, 6.1, 7.1 (PowerPC) Mac OS : X10.5~10.8 Citrix Presentation Server Windows Terminal Services
Modes of Operation	USB Printing, Network Printing , WI-FI Printing
Intended Class for Emissions	Class B

■ Type of Product : Mono LASER print

■ Variant Model

ProXpress M3325ND / ProXpress M3320ND
ProXpress M3825D / ProXpress M3820D
ProXpress M3825ND / ProXpress M3820ND
ProXpress M3825DW / ProXpress M3820DW
ProXpress M4025ND / ProXpress M4020ND

■ Clock Frequency List

Main Source Clock	: 12MHz
Video Clock	: 23.689MHz (33ppm, 38ppm)
	: 19.849MHz (40ppm)
CPU Internal Clock	: 600MHz
DDR3 Clock	: 384MHz
USB Device Clock	: 12MHz
ETHERNET Clock	: 25MHz

■ Factory Address

SSDP

SAMSUNG ELECTRONICS (SHANDONG) DIGITAL PRINTING CO.,LTD.
#264209,Samsung Road,Weihi Hi-Tech IDZ Shandong Province CHINA.

신흥

Weihai Shin Heung Digital Electronics Co., Ltd.
98, Samsung Road, Weihai Hi-Tech. IDZ, Shandong Province, P.R.China