

TEST REPORT

of


FCC Part 15 Subpart B & C §15.249/ RSS-210 Issue 8, RSS-Gen Issue 3

FCC ID /IC Certification: A3LSM3PWP/649E-SM3PWP

Equipment Under Test : 2.4G Wireless Mouse
Model Name : AA-SM3PWPB
Serial No. : N/A
Applicant : SAMSUNG ELECTRONICS CO., LTD.
Manufacturer : Areson Technology Corp.
Date of Test(s) : 2011. 06. 01 ~ 2011. 06. 27
Date of Issue : 2011. 06. 27

In the configuration tested, the EUT complied with the standards specified above.

Tested By:




Grant Lee

Date

2011. 06. 27

Approved By:



Charles Kim

Date

2011. 06. 27

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Table of contents

1. General information -----	3
2. Fundamental, Spurious emission and edge band radiated emission --	6
3. Receiver Radiated Spurious Emission-----	13
4. 99% Bandwidth -----	14
5. RF Exposure evaluation -----	17

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1. General information

1.1 Testing laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

Wireless Div. 2FL, 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea 435-040

www.kr.sgs.com/ee

Telephone : +82 +31 428 5700

FAX : +82 +31 427 2371

1.2 Details of applicant

Applicant : SAMSUNG ELECTRONICS CO., LTD.

Address : 416, Maetan-3dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, KR

Contact Person : Lee, Sang Cheong

Phone No. : +82 +10 8000 0700

1.3. Description of EUT

Kind of Product	2.4G Wireless Mouse
Model Name	AA-SM3PWPB
Serial Number	N/A
Power Supply	DC 3 V (Lithium Battery)
Frequency Range	2 402 MHz ~ 2 472 MHz
Modulation Technique	GFSK
Number of Channels	79
Antenna Type	Fixed Type
Antenna Gain	-9.90 dBi
H/W version	Rev1.0
S/W version	Rev1.0

1.4 Details of modification

-N/A

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory)

8-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.kr.sgs.com/ee

1.5. Test equipment list

Equipment	Manufacturer	Model	Serial Number	Cal Due.
Signal Generator	Agilent	E4438C	MY42082477	Mar 31, 2012
Spectrum Analyzer	R & S	FSV30	100955	Apr. 01, 2012
Power Meter	Agilent	E4416A	GB4129123	Mar. 31, 2012
Power Sensor	Agilent	E9327A	US40441371	Mar. 30, 2012
Attenuator	Agilent	8495B	MY42141937	Apr. 01, 2012
High Pass Filter	Wainwright	WHK3.0/18G-10SS	344	Sep. 29, 2011
DC power Supply	Agilent	U8002A	MY48490027	Jan. 01, 2012
Preamplifier	H.P.	8447F	2944A03909	Jul. 05, 2011
Preamplifier	Agilent	8449B	3008A01932	Mar. 31, 2011
Test Receiver	R & S	ESU26	100109	Feb. 21, 2012
Bilog Antenna	SCHWARZBECK MESSELEKTRONIK	VULB9163	396	Jul. 22, 2011
Horn Antenna	Rohde & Schwarz	HF 906	100326	Oct. 08, 2011
Antenna Master	EMCO	1050	1228	N.C.R.
Turn Table	Daeil EMC	DI-1500	N/A	N.C.R.
Anechoic Chamber	SY Corporation	L × W × H (9.6 m × 6.4 m × 6.6 m)	N/A	N.C.R.
Horn Antenna	R & S	BBHA9170	BBHA9170431	Mar. 17, 2012

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1.6. Summary of test results

The EUT has been tested according to the following specifications:

APPLIED STANDARD:FCC Part15, RSS-210,RSS-Gen			
Section in FCC 15	Section in RSS-210 RSS-Gen	Test Item	Result
15.209(a) 15.249(a) 15.249(d) 15.205	A2.9(a),(b)	Fundamental, Spurious emission and edge band radiated emission	Complied
15.109(a)	RSS-Gen 6	Receiver Radiated Spurious Emission	Complied
-	A8.1(1)	99% Bandwidth	Complied
1.1307(b)(1)	RSS-Gen 5.5/ RSS-102	Maximum Permissible Exposure (Exposure of Humans to RF Fields)	Complied

1.7. Test report revision


Revision	Report number	Description
0	F690501/RF-RTL004772	Initial
1	F690501/RF-RTL004772-1	Retest fundamental strength

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


2. Fundamental, Spurious emission and edge band radiated emission

2.1. Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to 24 GHz Emissions.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.2. Test procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.4:2003

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic Chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Note :

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1 GHz.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.3. Limit

In the section 15.249(a) :

Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental ($\mu\text{V/m}$)	Field strength of harmonics ($\mu\text{V/m}$)
902 ~ 928 MHz	50	500
2 400 ~ 2 483.5 MHz	50	500
5 725 ~ 5 875 MHz	50	500
24.0 ~ 24.25 GHz	250	2 500

In the section 15.209(a) :

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Fundamental frequency (MHz)	Field strength ($\mu\text{V/m}$)	Measurement distance (m)
30 ~ 88	100*	3
88 ~ 216	150*	3
216 ~960	200*	3
Above 960	500	3

Remark:

Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

(b) In the above emission table, the tighter limit applies at the band edges.

Fundamental frequency (MHz)	Field strength ($\mu\text{V/m}$ at 3 meter)	Field strength (dB $\mu\text{V/m}$ at 3 meter)
30 ~ 88	100	40
88 ~ 216	150	43.5
216 ~960	200	46
Above 960	500	54

(e) The provisions in §§15.31, 15.33, and 15.35 for measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.4. Test result

Ambient temperature : (23 ± 2) °C
Relative humidity : 47 % R.H.

2.4.1. Below 1 GHz

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
300.024	42.00	Peak	H	13.34	-25.05	30.29	46.00	15.71
311.987	43.12	Peak	H	13.55	-25.09	31.58	46.00	14.42
347.998	45.62	Peak	H	14.69	-25.22	35.09	46.00	10.91
360.002	45.26	Peak	H	14.91	-25.29	34.88	46.00	11.12
396.013	43.76	Peak	H	15.53	-25.52	33.77	46.00	12.23
902.394	39.12	Peak	H	22.19	-24.19	37.12	46.00	8.88
Above 910.000	Not detected	-	-	-	-	-	-	-

Remark

1. To get a maximum emission level from the EUT, the EUT was moved throughout the X, Y and Z planes.(Worst case is x-plane)
2. All spurious emission at channels are almost the same below 1 GHz, so that the channel was chosen at representative in final test.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.4.2. Above 1 GHz

A. Low Channel (2 402 MHz)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 401.48	61.57	Peak	H	28.07	6.26	95.90	114.00	18.10
2 401.48	28.45	Average	H	28.07	6.26	62.78	94.00	31.22
*2 390.00	31.48	Peak	H	28.09	6.23	65.80	74.00	8.20
*2 390.00	16.29	Average	H	28.09	6.23	50.61	54.00	3.39

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4 803.98	45.98	Peak	H	32.59	-25.03	53.54	74.00	20.46
4 803.98	32.31	Average	H	32.59	-25.03	39.87	54.00	14.13
Above 4 900.00	Not detected	-	-	-	-	-	-	-

B. Middle Channel (2 432 MHz)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 431.76	60.57	Peak	H	28.01	6.28	94.86	114.00	19.14
2 431.76	27.25	Average	H	28.01	6.28	61.54	94.00	32.46

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4 864.88	45.51	Peak	H	32.82	-25.30	53.03	74.00	20.97
4 864.88	32.07	Average	H	32.82	-25.30	39.59	54.00	14.41
Above 4 900.00	Not detected	-	-	-	-	-	-	-

C. High Channel (2 472 MHz)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 471.93	59.37	Peak	H	28.05	6.33	93.75	114.00	20.25
2 471.93	28.41	Average	H	28.05	6.33	62.78	94.00	31.22
*2 483.500	29.39	Peak	H	28.09	6.36	63.83	74.00	10.17
*2 483.500	16.44	Average	H	28.09	6.36	50.88	54.00	3.12

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4 943.12	45.95	Peak	H	33.18	-24.58	54.55	74.00	19.45
4 943.12	32.04	Average	H	33.18	-24.58	40.64	54.00	13.36
Above 5 000.00	Not detected	-	-	-	-	-	-	-

Remarks ;

1. "*" means the restricted band.
2. To get a maximum emission level from the EUT, the EUT was moved throughout the X, Y and Z planes.(Worst case is x-plane)
3. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental Frequency.
4. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using peak/average detector mode.
5. Average test would be performed if the peak result were greater than the average limit.
6. Actual = Reading + AF - Amp Gain + CL

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3. Receiver Radiated spurious emissions

3.1. Test setup - Same as clause 4.1.

3.1.1. Receiver Radiated Spurious Emissions - Same as clause 4.1.1.

3.2. Limit

According to RSS-Gen(6), all spurious emissions shall comply with the limits of Table.

Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
30 - 88	3	40.0	100
88 – 216	3	43.5	150
216 – 960	3	46.0	200
Above 960	3	54.0	500

3.3. Test Procedures - Same as clause 4.3.

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.4:2003

3.3.1. Test Procedures for Radiated Spurious Emissions- Same as clause 2.3.1.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3.4. Test Results

Ambient temperature : (23 ± 2) °C
Relative humidity : 47 % R.H.

3.4.1. Spurious Radiated Emission

The frequency spectrum from 30 MHz to 1000 MHz was investigated. Emission levels are not reported much lower than the limits by over 30 dB. All reading values are peak values.

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
537.27	43.50	Peak	V	17.83	-25.78	35.55	46.00	10.45
Above 600.00	Not detected	-	-	-	-	-	-	-


Remark

1. To get a maximum emission level from the EUT, the EUT was moved throughout the X, Y and Z planes.(Worst case is x-plane)
2. All spurious emission at channels are almost the same below 1 GHz, so that the channel was chosen at representative in final test.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

4. 99 % Bandwidth

4.1. Test Setup



4.2. Limit

Limit: Not Applicable

4.3. Test Procedure

1. The 20 dB band width was measured with a spectrum analyzer connected to RF antenna connector(conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency. The analyzer center frequency was set to the EUT carrier frequency, using the analyzer. Display Line and Marker Delta functions, the 20 dB band width of the emission was determined.
2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using RBW = 30 kHz, VBW = 100 kHz, Span = 10 MHz.


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

4.4. Test Results

Ambient temperature : (23 ± 2) °C
Relative humidity : 47 % R.H.


Operation Mode	Channel	Channel Frequency (MHz)	99 % Bandwidth (MHz)
GFSK	Low	2 402	2.07
	Middle	2 432	2.11
	High	2 472	2.24

Low Channel




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Middle Channel



High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

5. RF Exposure Evaluation

5.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

According to FCC 1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational /Control Exposures				
300 – 1 500	--	--	F/300	6
1 500 – 100 000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300 – 1 500	--	--	F/1500	6
<u>1 500 – 100 000</u>	--	--	<u>1</u>	<u>30</u>

5.1.1. Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory)

8-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea, 435-040

Tel. +82 31 428 5700 / Fax. +82 31 427 2371

www.kr.sgs.com/ee

5.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

5.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

Channel	Channel Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	LIMITS (mW/cm ²)
Low	2 402	-5.86	-9.90	0.000 005	1
Middle	2 432	-6.67	-9.90	0.000 004	1
High	2 472	-8.28	-9.90	0.000 003	1

Note :

1. The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm² .

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.