



FCC CFR47 PART 15 SUBPART C

**BLUETOOTH LOW ENERGY
CERTIFICATION TEST REPORT**

FOR

GSM/WCDMA/LTE Phone + Bluetooth, DTS/UNII a/b/g/n & ANT+

MODEL NUMBER: SM-A7000

FCC ID: A3LSMA7000

REPORT NUMBER: 14I19355-E3

ISSUE DATE: NOVEMBER 13, 2014

Prepared for

**SAMSUNG ELECTRONICS CO., LTD.
129 Samsung-ro, Yeongtong-gu, Suwon-si,
Gyeonggi-do, 443-742, Korea**

Prepared by

**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	11/13/14	Initial Issue	P. Zhang

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION	6
4.3. MEASUREMENT UNCERTAINTY	6
5. EQUIPMENT UNDER TEST	7
5.1. DESCRIPTION OF EUT	7
5.2. MAXIMUM OUTPUT POWER	7
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	7
5.4. WORST-CASE CONFIGURATION AND MODE	7
5.5. DESCRIPTION OF TEST SETUP	8
6. TEST AND MEASUREMENT EQUIPMENT	10
7. SUMMARY	11
8. ANTENNA PORT TEST RESULTS	11
8.1. 6 dB BANDWIDTH	12
8.2. 99% BANDWIDTH	16
8.3. OUTPUT POWER	20
8.4. AVERAGE POWER	24
8.5. POWER SPECTRAL DENSITY	25
8.6. CONDUCTED SPURIOUS EMISSIONS	29
9. RADIATED TEST RESULTS	36
9.1. LIMITS AND PROCEDURE	36
9.2. TRANSMITTER ABOVE 1 GHz	37
9.3. WORST-CASE BELOW 1 GHz	50
10. AC POWER LINE CONDUCTED EMISSIONS	53
11. SETUP PHOTOS	56

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.

EUT DESCRIPTION: GSM/WCDMA/LTE Phone + Bluetooth, DTS/UNII a/b/g/n, & ANT+

MODEL: SM-A7000

SERIAL NUMBER: c899c6eb (RADIATED); c89fc6f6 (CONDUCTED)

DATE TESTED: NOVEMBER 7-13, 2014

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:



PENG ZHANG
CONSUMER TECHNOLOGY DIVISION
PROJECT LEADER
UL Verification Services Inc.

Tested By:



CHARLES VERGONIO
CONSUMER TECHNOLOGY DIVISION
LAB ENGINEER
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.4-2009.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
☐ Chamber A(IC: 2324B-1)	☐ Chamber D(IC: 2324B-4)
☐ Chamber B(IC: 2324B-2)	☐ Chamber E(IC: 2324B-5)
☒ Chamber C(IC: 2324B-3)	☐ Chamber F(IC: 2324B-6)
	☐ Chamber G(IC: 2324B-7)
	☐ Chamber H(IC: 2324B-8)

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/2000650.htm>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 26000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Phone + Bluetooth, DTS/UNII a/b/g/n, & ANT+.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402-2480	BLE	1.75	1.50

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of -2.32 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	SAMSUNG	EP-TA50CBC	N/A	N/A
Earphone	SAMSUNG	EHS64AVFWE	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

TEST SETUP

EUT was set in the Samsung Keysting menu mode to enable BLE communications.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Antenna, Biconolog, 30MHz-1 GHz	Sunol Sciences	JB1	C01171	02/13/15
Antenna, Horn, 18GHz	EMCO	3115	C00783	10/25/15
Antenna, Horn, 25.5 GHz	ARA	MWH-1826/B	C00980	11/14/14
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00580	01/28/15
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01052	10/22/15
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/20/14
CBT Bluetooth Tester	R & S	CBT	None	07/12/15
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/14
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/14
LISN, 30 MHz	FCC	50/250-25-2	C00626	01/14/15
Reject Filter, 2.4GHz	Micro-Tronics	BRM50702	N02684	CNR

7. SUMMARY

8.

FCC Part Section	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.247 (a)(2)	RSS-210 A8.2(a)	Occupied Band width (6dB)	>500KHz	Conducted	Pass	0.751MHz
2.1051, 15.247 (d)	RSS-210 A8.5	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-41.37dBm
15.247	RSS-210 A8.4	TX conducted output power	<30dBm		Pass	1.75dBm
15.247	RSS-210 A8.2	PSD	<8dBm		Pass	-13.71dBm
15.207 (a)	RSS-GEN 7.2.2	AC Power Line conducted emissions	Section 10	Radiated	Pass	45.26dBuV(PK)
15.205, 15.209	RSS-210 Clause 2.6, RSS-210 Clause 6	Radiated Spurious Emission	< 54dBuV/m		Pass	42.94dBuV/m

ANTENNA PORT TEST RESULTS

8.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.7750	0.5
Middle	2440	0.7510	0.5
High	2480	0.7670	0.5

6 dB BANDWIDTH PLOTS


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL



8.2. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE


Reference to KDB558074 D01 DTS Meas Guidance v03r02: The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth and to 1% of the span. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS


Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.0630
Middle	2440	1.0600
High	2480	1.0640

99% BANDWIDTH PLOTS


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL



8.3. OUTPUT POWER

LIMITS

FCC §15.247 (b)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

TEST PROCEDURE


Peak power is measured using KDB558074 D01 DTS Meas Guidance v03r02 under section 9.1.1 utilizing spectrum analyzer.

RESULTS


Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	1.150	30	-28.850
Middle	2440	1.750	30	-28.250
High	2480	1.170	30	-28.830

OUTPUT POWER PLOTS


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL



8.4. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	0.8
Middle	2440	0.5
High	2480	0.3

8.5. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247 (e)

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST PROCEDURE


Power Spectral Density was performed utilizing the "Method PKPSD (Peak PSD)" under KDB558074 D01 DTS Meas Guidance v03r02

RESULTS


Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Margin (dB)
Low	2402	-14.06	8	-22.06
Middle	2440	-14.09	8	-22.09
High	2480	-13.71	8	-21.71

POWER SPECTRAL DENSITY PLOTS


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL



8.6. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dB.

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


RESULTS

SPURIOUS EMISSIONS, LOW CHANNEL

LOW CHANNEL BANDEDGE




LOW CHANNEL SPURIOUS




SPURIOUS EMISSIONS, MID CHANNEL

MID CHANNEL REFERENCE




MID CHANNEL SPURIOUS




SPURIOUS EMISSIONS, HIGH CHANNEL

HIGH CHANNEL BANDEDGE



HIGH CHANNEL SPURIOUS



9. RADIATED TEST RESULTS

9.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4 - 2009. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and add duty cycle factor for average measurements. Duty cycle factor = $10 \log (1/x)$. For this sample: DCF = $10 \log (1/0.618) = 2.08 \text{ dB}$


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

9.2. TRANSMITTER ABOVE 1 GHz RESTRICTED BANDEDGE (LOW CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AFT119 (dB/m)	Amp/Cbl/Filt r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	2.37	42.63	PK	32	-23.1	0	51.53	-	-	74	-22.47	74	197	H
4	2.384	31.32	RMS	32.1	-23.1	2.08	42.4	54	-11.6	-	-	74	197	H
1	2.39	40.15	PK	32.1	-23.1	0	49.15	-	-	74	-24.85	74	197	H
3	2.39	30.52	RMS	32.1	-23.1	2.08	41.6	54	-12.4	-	-	74	197	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AFT119 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	2.374	42.79	PK	32	-23.1	0	51.69	-	-	74	-22.31	336	217	V
4	2.379	31.15	RMS	32.1	-23.1	2.08	42.23	54	-11.77	-	-	336	217	V
1	2.39	39.21	PK	32.1	-23.1	0	48.21	-	-	74	-25.79	336	217	V
3	2.39	30.67	RMS	32.1	-23.1	2.08	41.75	54	-12.25	-	-	336	217	V

AUTHORIZED BANDEDGE (HIGH CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AFT119 (dB/m)	Amp/Cb/Filter/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.484	40.61	PK	32.3	-22.8	0	50.11	-	-	74	-23.89	308	252	H
3	2.484	30.47	RMS	32.3	-22.8	2.08	42.05	54	-11.95	-	-	308	252	H
2	2.522	42.71	PK	32.4	-22.8	0	52.31	-	-	74	-21.69	308	252	H
4	2.531	31.06	RMS	32.4	-22.6	2.08	42.94	54	-11.06	-	-	308	252	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AFT119 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.484	38.85	PK	32.3	-22.8	0	48.35	-	-	74	-25.65	101	180	V
3	2.484	30.03	RMS	32.3	-22.8	2.08	41.61	54	-12.39	-	-	101	180	V
4	2.511	31.24	RMS	32.3	-22.8	2.08	42.82	54	-11.18	-	-	101	180	V
2	2.52	42.72	PK	32.4	-22.8	0	52.32	-	-	74	-21.68	101	180	V


HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL VERTICAL




Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fitr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 1.305	33.69	PK	30.2	-23.8	0	40.09	-	-	74	-33.91	0-360	100	H
3	* 2.257	34.01	PK	31.8	-23	0	42.81	-	-	74	-31.19	0-360	200	H
1	* 1.268	34.3	PK	29.9	-23.8	0	40.4	-	-	74	-33.6	0-360	200	V
4	* 2.27	33.56	PK	31.8	-23	0	42.36	-	-	74	-31.64	0-360	200	V
6	* 4.677	31.75	PK	34.1	-30.7	0	35.15	-	-	74	-38.85	0-360	200	H
5	* 3.655	32.26	PK	33.1	-31.2	0	34.16	-	-	74	-39.84	0-360	100	V

MID CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Ftr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.287	34.29	PK	30.1	-23.7	0	40.69	-	-	74	-33.31	0-360	200	V
2	* 1.312	34.24	PK	30.1	-23.8	0	40.54	-	-	74	-33.46	0-360	200	H
3	* 2.287	34.37	PK	31.8	-23	0	43.17	-	-	74	-30.83	0-360	100	V
4	* 2.311	33.92	PK	31.9	-23.1	0	42.72	-	-	74	-31.28	0-360	200	H
5	* 4.795	31.42	PK	34.1	-30.4	0	35.12	-	-	74	-38.88	0-360	100	H
6	8.007	31.04	PK	35.7	-28.5	0	38.24	-	-	-	-	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Ftr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
8.006	38.6	PK2	35.7	-28.5	0	45.8	-	-	-	-	360	200	V
8.008	27.54	MAV1	35.7	-28.5	0	34.74	-	-	-	-	360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK2 - KDB558074 Method: Maximum Peak


MAV1 - KDB558074 Option 1 Maximum RMS Average

HIGH CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Filtr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 1.318	33.96	PK	30	-23.8	0	40.16	-	-	74	-33.84	0-360	100	H
3	* 2.334	34.17	PK	31.9	-23.1	0	42.97	-	-	74	-31.03	0-360	200	H
1	* 1.296	34.36	PK	30.2	-23.8	0	40.76	-	-	74	-33.24	0-360	100	V
4	* 2.324	33.72	PK	31.9	-23.1	0	42.52	-	-	74	-31.48	0-360	200	V
5	* 4.248	32.65	PK	33.5	-31.3	0	34.85	-	-	74	-39.15	0-360	100	V
6	10.402	29.39	PK	37.4	-25.2	0	41.59	-	-	-	-	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Filtr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
10.403	36.67	PK2	37.4	-25.2	0	48.87	-	-	-	-	360	200	V
10.404	25.57	MAv1	37.4	-25.1	0	37.87	-	-	-	-	360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average


9.3. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)

HORIZONTAL PLOT



VERTICAL PLOT



BELOW 1 GHz TABLE

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T185 (dB/m)	Amp/Cbl (dB/m)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	30.0425	44.28	PK	21	-27.5	37.78	40	-2.22	0-360	100	V
5	32.04	36.47	PK	19.4	-27.5	28.37	40	-11.63	0-360	300	H
2	33.0175	43.87	PK	18.9	-27.5	35.27	40	-4.73	0-360	100	V
3	60.005	47.69	PK	7.1	-27.1	27.69	40	-12.31	0-360	100	V
6	106.5	38.56	PK	11.6	-26.7	23.46	43.52	-20.06	0-360	400	H
4	840.5	34.37	PK	21.7	-24.4	31.67	46.02	-14.35	0-360	100	V

10. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

RSS-Gen 7.2.2

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 [*]	56 to 46 [*]
0.5-5	56	46
5-30	60	50

^{*} Decreases with the logarithm of the frequency.


TEST PROCEDURE

ANSI C63.4 - 2009

RESULTS

6 WORST EMISSIONS


LINE 1 PLOT



LINE 1 RESULTS

Trace Markers										
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L1 (dB)	LC Cables 1&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
1	.2265	43.29	PK	.8	0	44.09	62.6	-18.51	-	-
2	.2265	18.29	Av	.8	0	19.09	-	-	52.6	-33.51
3	.303	39.39	PK	.6	0	39.99	60.2	-20.21	-	-
4	.303	20.98	Av	.6	0	21.58	-	-	50.2	-28.62
5	.5055	41.72	PK	.3	0	42.02	56	-13.98	-	-
6	.5055	33.68	Av	.3	0	33.98	-	-	46	-12.02
7	2.112	44.02	PK	.2	.1	44.32	56	-11.68	-	-
8	2.112	27.1	Av	.2	.1	27.4	-	-	46	-18.6
9	3.3675	38.79	PK	.2	.1	39.09	56	-16.91	-	-
10	3.3675	23.3	Av	.2	.1	23.6	-	-	46	-22.4
11	7.467	39.13	PK	.2	.1	39.43	60	-20.57	-	-
12	7.467	22.68	Av	.2	.1	22.98	-	-	50	-27.02
13	14.226	37.45	PK	.2	.2	37.85	60	-22.15	-	-
14	14.226	20.36	Av	.2	.2	20.76	-	-	50	-29.24

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers										
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L2 (dB)	LC Cables 2&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
15	.1635	43.96	PK	1.3	0	45.26	65.3	-20.04	-	-
16	.1635	20.7	Av	1.3	0	22	-	-	55.3	-33.3
17	.3075	42.91	PK	.6	0	43.51	60	-16.49	-	-
18	.3075	19.42	Av	.6	0	20.02	-	-	50	-29.98
19	.51	41.57	PK	.4	0	41.97	56	-14.03	-	-
20	.51	27.59	Av	.4	0	27.99	-	-	46	-18.01
21	1.023	36.1	PK	.3	0	36.4	56	-19.6	-	-
22	1.023	18.53	Av	.3	0	18.83	-	-	46	-27.17
23	6.846	33.42	PK	.2	.1	33.72	60	-26.28	-	-
24	6.846	17.94	Av	.2	.1	18.24	-	-	50	-31.76
25	15.747	34.03	PK	.3	.2	34.53	60	-25.47	-	-
26	15.747	14.36	Av	.3	.2	14.86	-	-	50	-35.14