



SAR EVALUATION REPORT

**FCC 47 CFR § 2.1093
IEEE Std 1528-2013**

For
GSM/WCDMA/LTE Phone + Bluetooth, WLAN 2.4GHz b/g/n & NFC

**Model: SM-G530F and SM-G530FQ
FCC ID: A3LSMG530F**

**Report Number: 14U18524-S1
Issue Date: 08/19/2014**

Prepared for
**SAMSUNG ELECTRONICS CO. LTD.
416 MAETAN 3-DONG, WEONGTONG-GU
SUWON CITY, GYEONGGI-DO, SOUTH KOREA, 443-742**

Prepared by
**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

REVISION HISTORY

Rev.	Issue Date	Revisions	Revised By
--	08/19/2014	Initial Issue	--

Table of Contents

1.	Attestation of Test Results	5
2.	Test Specification, Methods and Procedures.....	6
3.	Facilities and Accreditation	6
4.	SAR Measurement System & Test Equipment	7
4.1.	<i>SAR Measurement System.....</i>	7
4.2.	<i>Test Equipment.....</i>	8
5.	Measurement Uncertainty.....	9
6.	Device Under Test (DUT) Information	10
6.1.	<i>DUT Description</i>	10
6.2.	<i>Wireless Technologies.....</i>	11
6.3.	<i>Nominal and Maximum Output Power.....</i>	12
6.4.	<i>Simultaneous Transmission Condition</i>	13
6.5.	<i>General LTE SAR Test and Reporting Considerations.....</i>	14
6.6.	<i>Antenna Dimensions and Separation Distances</i>	15
7.	RF Exposure Conditions (Test Configurations)	16
7.1.	<i>Head.....</i>	16
7.2.	<i>Body-worn Accessory.....</i>	16
7.3.	<i>Wireless Router (Hotspot) and Wi-Fi Direct</i>	16
8.	Conducted Output Power Measurements.....	17
8.1.	<i>GSM850 and GSM1900.....</i>	17
8.2.	<i>W-CDMA Band V and II</i>	19
8.3.	<i>LTE Band 5.....</i>	26
8.4.	<i>Wi-Fi (2.4 GHz Band) (reference to additional KDB in footnote).....</i>	28
8.5.	<i>Bluetooth</i>	28
9.	Dielectric Property Measurements.....	29
9.1.	<i>Tissue Dielectric Parameters</i>	29
9.2.	<i>Dielectric Property Measurements Results</i>	30
10.	System Check.....	32
10.1.	<i>Reference Target SAR Values</i>	32
10.2.	<i>System Check Results</i>	32
11.	Measured and Reported (Scaled) SAR Results.....	33
11.1.	<i>GSM850.....</i>	34
11.2.	<i>GSM1900.....</i>	34

11.3.	W-CDMA Band V	34
11.4.	W-CDMA Band II.....	35
11.5.	LTE Band 5 (10MHz Bandwidth)	35
11.6.	Wi-Fi (DTS Band).....	35
11.7.	Bluetooth.....	36
11.7.1.	Standalone SAR Test Exclusion Considerations	36
11.7.2.	Estimated SAR.....	36
12.	SAR Measurement Variability.....	37
12.1.	The Highest Measured SAR Configuration in Each Frequency Band	37
12.2.	Repeated Measurement Results	37
13.	Simultaneous Transmission SAR Analysis	38
13.1.	Sum of the SAR for GSM850 & Wi-Fi & BT	38
13.2.	Sum of the SAR for GSM1900 & Wi-Fi & BT	38
13.3.	Sum of the SAR for WCDMA Band V & Wi-Fi & BT.....	39
13.4.	Sum of the SAR for WCDMA Band II & Wi-Fi & BT	39
13.5.	Sum of the SAR for LTE Band 5 & Wi-Fi & BT	40
14.	Appendixes.....	41
14.1.	Photos and Antenna Locations.....	41
14.2.	System Performance Check Plots	41
14.3.	Highest SAR Test Plots.....	41
14.4.	Calibration Certificate for E-Field Probe EX3DV4 - SN 3902	41
14.5.	Calibration Certificate for E-Field Probe EX3DV4 - SN 3929	41
14.6.	Calibration Certificate for D835V2 - SN 4d002	41
14.7.	Calibration Certificate for D1900V2- SN 5d043	41
14.8.	Calibration Certificate for D2450V2 - SN 899	41

1. Attestation of Test Results

Applicant Name	SAMSUNG ELECTRONICS CO. LTD.		
Application Purpose	☒ Original Grant ☐ Class II Permissive Change		
FCC ID	A3LSMG530F		
DUT Description	GSM/WCDMA/LTE Phone + Bluetooth, WLAN 2.4GHz b/g/n & NFC		
Exposure Category	General Population/Uncontrolled Exposure (1g SAR limit: 1.6 W/kg)		
The Highest Reported SAR	RF Exposure Conditions	Equipment Class	
		Licensed	DTS
	Head	0.363 W/kg	0.349 W/kg
	Body-worn Accessory	0.980 W/kg	0.549 W/kg
	Wireless Router (Hotspot)		
	Wi-Fi Direct	N/A	N/A
	Simultaneous Transmission	Head: 0.518 W/kg Body: 1.529 W/kg	
Applicable Standards	FCC 47 CFR § 2.1093 Published RF exposure KDB procedures IEEE Std 1528-2013		
Test Results	Pass		
Date tested	08/11/2014 – 08/13/2014		
UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report. Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government (NIST Handbook 150, Annex A). This report is written to support regulatory compliance of the applicable standards stated above.			
Approved & Released By:  Dave Weaver Program Manager UL Verification Services Inc.		Prepared By:  Tony Soares Laboratory Technician UL Verification Services Inc.	

2. Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1093, IEEE STD 1528-2003 & 2013, the following FCC Published RF exposure KDB procedures, and TCB workshop updates:

- 447498 D01 General RF Exposure Guidance v05r02
- 648474 D04 Handset SAR v01r02
- 941225 D01 SAR test for 3G devices v02
- 941225 D02 HSPA and 1x Advanced v02r02
- 941225 D03 SAR Test Reduction GSM GPRS EDGE v01
- 941225 D04 SAR for GSM E GPRS Dual Xfer Mode v01
- 941225 D05 SAR for LTE Devices v02r03
- 941225 D06 Hotspot Mode SAR v01r01
- 248227 D01 SAR Meas for 802 11abg v01r02
- 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r03
- 865664 D02 SAR Reporting v01r01
- 690783 D01 SAR Listings on Grants v01r03

3. Facilities and Accreditation

The test sites and measurement facilities used to collect data are located at


47173 Benicia Street	47266 Benicia Street
SAR Lab A	SAR Lab 1
SAR Lab B	SAR Lab 2
SAR Lab C	SAR Lab 3
SAR Lab D	SAR Lab 4
SAR Lab E	SAR Lab 5
SAR Lab F	
SAR Lab G	
SAR Lab H	

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/2000650.htm>

4. SAR Measurement System & Test Equipment

4.1. SAR Measurement System

The DASY5 system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

4.2. Test Equipment

The measuring equipment used to perform the tests documented in this report has been calibrated in accordance with the manufacturers' recommendations, and is traceable to recognized national standards.

Dielectric Property Measurements

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Network Analyzer	Agilent	ENA Series/E5071B	MY42100131	2/24/2015
Dielectronic Probe kit	SPEAG	DAK-3.5	1087	11/13/2014
Dielectronic Probe kit	SPEAG	DAK-3.5 Short	SM DAK 200 BA	N/A
Thermometer	Control Company	4242	122529163	9/19/2014
Thermometer	EXTECH	445703	CCS-200	3/24/2015

System Check

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
HP Signal Generator	HP	8665B	3546A00784	6/23/2015
Power Meter	HP	437B	3125U16345	6/16/2015
Power Meter	HP	437B	3125U09516	9/30/2014
Power Sensor	Agilent	8481A	2237A31744	10/2/2014
Power Sensor	Agilent	8481A	2349A36506	9/30/2014
Amplifier	MITEQ	AMF-4D-00400600-50-30P	1808939	N/A
Bi-directional coupler	Werlatone, Inc.	C8060-102	2710	N/A
DC Power Supply	Sorensen Ametek	XT15-4	1319A02778	N/A
HP Signal Generator	HP	8665B	3438A00633	7/10/2015
Power Meter	HP	438A	3513U04320	10/2/2014
Power Sensor	Agilent	8481A	2702A66876	9/30/2014
Power Sensor	Agilent	8481A	3318A95392	9/30/2014
Amplifier	MITEQ	AMF-4D-00400600-50-30P	1622052	N/A
Bi-directional coupler	Werlatone, Inc.	C8060-102	2711	N/A
DC Power Supply	HP	6296A	2841A-05955	N/A
E-Field Probe (SAR 1)	SPEAG	EX3DV4	3902	5/19/2015
E-Field Probe (SAR 4)	SPEAG	EX3DV4	3929	5/9/2015
Data Acquisition Electronics (SAR 1)	SPEAG	DAE3	427	1/14/2015
Data Acquisition Electronics (SAR 4)	SPEAG	DAE4	1352	9/11/2014
System Validation Dipole	SPEAG	D835V2	4d002	11/15/2014
System Validation Dipole	SPEAG	D1900V2	5d043	11/12/2014
System Validation Dipole	SPEAG	D2450V2	899	9/10/2014
Thermometer (SAR Lab 1)	EXTECH	445703	CCS-205	3/24/2015
Thermometer (SAR Lab 4)	EXTECH	445703	CCS-238	6/3/2015

Others

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Power Meter	Agilent	N1912A	MY53040015	6/29/2014
Power Sensor	Agilent	N1921A	MY52020011	5/6/2015
Base Station Simulator	R&S	CMW 500	132909-bd	6/6/2015
Base Station Simulator	R&S	CMW 500	125236-eS	5/29/2015
Base Station Simulator	R&S	CMW 500	135393-VQ	7/3/2015

5. Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2003 & 2013 is not required in SAR reports submitted for equipment approval.

6. Device Under Test (DUT) Information

6.1. DUT Description

Model: SM-G530F and SM-G530FQ	
Device Dimension	Overall (Length x Width): 130 mm x 80 mm Overall Diagonal: 155 mm Display Diagonal: 128 mm
Battery Back Cover	☐ Normal Battery Cover ☒ Normal Battery Cover with NFC ☐ Wireless Charger Battery Cover ☐ Wireless Charger Battery Cover with NFC.
Battery Options	☒ Standard – Lithium-ion battery, Rating 3.8 Vdc, 9.88Wh ☐ Extended (large capacity)
Accessory	Headset
Wireless Router (Hotspot)	Wi-Fi Hotspot mode permits the device to share its cellular data connection with other Wi-Fi-enabled devices. ☒ Mobile Hotspot (Wi-Fi 2.4 GHz) ☐ Mobile Hotspot (Wi-Fi 5 GHz)
Wi-Fi Direct	Wi-Fi Direct enabled devices transfer data directly between each other ☒ Wi-Fi Direct (Wi-Fi 2.4 GHz) ☐ Wi-Fi Direct (Wi-Fi 5 GHz)
SIM Information	☒ Single SIM ☐ Dual SIM

6.2. Wireless Technologies

Wireless technologies	Frequency bands	Operating mode	Duty Cycle used for SAR testing
GSM	850, 1900	Voice (GMSK) GPRS (GMSK) EGPRS (8PSK)	GSM Voice: 12.5%; GPRS/EGPRS: 1 Slot: 12.5%; 2 Slots: 25%, 3 Slots: 37.5%, 4 Slots: 50%,
	GPRS Multi-Slot Class: ☐ Class 8 - One Up ☐ Class 10 - Two Up ☐ Class 12 - Four Up ☒ Class 33 - Four Up Is DTM (Dual Transfer Mode) supported? ☐ Yes ☒ No		
W-CDMA (UMTS)	Band V and II	UMTS Rel. 99 (Voice & Data) HSDPA (Rel. 7 Cat. 14) DC-HSPDA (Rel. 7 Cat. 14) HSUPA (Rel. 6 Cat. 6)	100%
LTE (FDD)	Band 5	QPSK, 16QAM	100%
	Does this device SV-LTE (1xRTT-LTE)? ☐ Yes ☒ No		
Wi-Fi	2.4 GHz	802.11b 802.11g 802.11n (HT20)	100%
Bluetooth	2.4 GHz	Version 4.0 LE	32.25% (DH1), 66.68% (DH3), 77.52% (DH5)

6.3. Nominal and Maximum Output Power

Upper limit (dB): 0.5 ~ -1.5		RF Output Power (dBm)	
RF Air interface	Mode	Target	Max. tune-up tolerance limit
GSM850	Voice	32.5	33.0
	GPRS 1 slot	32.5	33.0
	GPRS 2 slots	28.5	29.0
	GPRS 3 slots	27.0	27.5
	GPRS 4 slots	25.0	25.5
	EGPRS 1 slot	27.5	28.0
	EGPRS 2 slots	26.0	26.5
	EGPRS 3 slots	23.5	24.0
	EGPRS 4 slots	22.0	22.5
GSM1900	Voice	29.5	30.0
	GPRS 1 slot	29.5	30.0
	GPRS 2 slots	26.0	26.5
	GPRS 3 slots	24.0	24.5
	GPRS 4 slots	23.0	23.5
	EGPRS 1 slot	27.0	27.5
	EGPRS 2 slots	25.5	26.0
	EGPRS 3 slots	22.5	23.0
	EGPRS 4 slots	22.0	22.5
W-CDMA Band V	R99	22.5	23.0
	HSDPA	22.5	23.0
	HSUPA	22.0	22.5
	DC-DSPA	22.0	22.5
W-CDMA Band II	R99	22.5	23.0
	HSDPA	22.5	23.0
	HSUPA	22.0	22.5
	DC-DSPA	22.0	22.5
LTE Band 5	QPSK	23.0	23.5

Upper limit (dB): 0.5		RF Output Power (dBm)	
RF Air interface	Mode	Target	Max. tune-up tolerance limit
WiFi 2.4 GHz	802.11b	17.0	17.5
	802.11g	13.0	13.5
	802.11n HT20	11.0	11.5
Bluetooth		10.0	10.5
Bluetooth LE		10.0	10.5

6.4. Simultaneous Transmission Condition


RF Exposure Condition	Capable Transmit Configurations
Head	1. GSM 850/1900 Voice + Wi-Fi 2.4GHz 2. GSM 850/1900 (GPRS/EDGE) + Wi-Fi 2.4GHz 3. WCDMA Band 2/5 + Wi-Fi 2.4GHz 4. LTE B5+ Wi-Fi 2.4GHz
Body-worn Accessory	1. GSM 850/1900 Voice + Wi-Fi 2.4GHz 2. GSM 850/1900 Voice + BT 3. GSM 850/1900 (GPRS/EDGE) + Wi-Fi 2.4GHz 4. GSM 850/1900 (GPRS/EDGE) + BT 5. WCDMA Band 2/5 + Wi-Fi 2.4GHz 6. WCDMA Band 2/5 + BT 7. LTE B5+ Wi-Fi 2.4GHz 8. LTE B5+ BT
Wireless Router (Hotspot)	1. GSM 850/1900 (GPRS/EDGE) + Wi-Fi 2.4GHz 2. WCDMA Band 2/5 + Wi-Fi 2.4GHz 3. LTE B5+ Wi-Fi 2.4GHz
Notes: 1. Only Wi-Fi 2.4GHz supports Hotspot and Wi-Fi Direct. 2. GPRS/EDGE, WCDMA and LTE support Hotspot. 3. VoIP is supported in LTE, WCDMA and GPRS. 4. Wi-Fi 2.4 GHz Radio cannot transmit simultaneously with Bluetooth Radio.	

6.5. General LTE SAR Test and Reporting Considerations

Item	Description																																																				
Frequency range, Channel Bandwidth, Numbers and Frequencies	Band 5	Frequency range: 824 - 849 MHz																																																			
		Channel Bandwidth																																																			
	20 MHz	15 MHz	10 MHz	5 MHz	3 MHz	1.4 MHz																																															
	Low			20450/ 829	20425/ 826.5	20415/ 825.5	20407/ 824.7																																														
	Mid			20525/ 836.5	20525/ 836.5	20525/ 836.5	20525/ 836.5																																														
	High			20600/ 844	20625/ 846.5	20635/ 847.5	20643/ 848.3																																														
LTE transmitter and antenna implementation	LTE has one (1) TX/RX antennas and two (2) RX antennas Refer to Appendix 14.1. Photos and Antenna Locations.																																																				
Maximum power reduction (MPR)	<table><tr><th colspan="8">Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3</th></tr><tr><th rowspan="2">Modulation</th><th colspan="6">Channel bandwidth / Transmission bandwidth (RB)</th><th rowspan="2">MPR (dB)</th></tr><tr><th>1.4 MHz</th><th>3.0 MHz</th><th>5 MHz</th><th>10 MHz</th><th>15 MHz</th><th>20 MHz</th></tr><tr><td>QPSK</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 1</td></tr><tr><td>16 QAM</td><td>≤ 5</td><td>≤ 4</td><td>≤ 8</td><td>≤ 12</td><td>≤ 16</td><td>≤ 18</td><td>≤ 1</td></tr><tr><td>16 QAM</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 2</td></tr></table> MPR Built-in by design A-MPR (additional MPR) was disabled during SAR testing							Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3								Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3																																																					
Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)																																														
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																															
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																														
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																														
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																														
Power reduction	No																																																				
Spectrum plots for RB configurations	A properly configured base station simulator was used for the SAR and power measurements; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																																				

6.6. Antenna Dimensions and Separation Distances

- ① Wi-Fi / BT Ant (TX & RX)
- ② Main Ant (TX & RX)
 - GSM 850/1900
 - WCDMA 850/1900
 - LTE Band 5



7. RF Exposure Conditions (Test Configurations)

Refer to Appendix 14.1.Photos and Antenna Locations for the specific details of the antenna-to-antenna and antenna-to-edge(s) distances.

7.1. Head

For WWAN, LTE and Wi-Fi

Test Configurations	SAR Required	Note
Left Touch	Yes	
Left Tilt (15°)	Yes	
Right Touch	Yes	
Right Tilt (15°)	Yes	

7.2. Body-worn Accessory

For WWAN and LTE

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Rear	2 mm	Yes	
Front	2 mm	Yes	

For Wi-Fi

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Rear	1 mm	Yes	
Front	1 mm	Yes	

7.3. Wireless Router (Hotspot) and Wi-Fi Direct

For WWAN and LTE

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Rear	2 mm	Yes	
Front	2 mm	Yes	
Edge 1 (Top)	125 mm	No	SAR is not required because the distance from the antenna to the edge is > 25 mm as per KDB 941225 D06 Hot Spot SAR
Edge 2 (Right)	2 mm	Yes	
Edge 3 (Bottom)	2 mm	Yes	
Edge 4 (Left)	5 mm	Yes	

For Wi-Fi

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Rear	1 mm	Yes	
Front	1 mm	Yes	
Edge 1 (Top)	25 mm	Yes	
Edge 2 (Right)	65 mm	No	SAR is not required because the distance from the antenna to the edge is > 25 mm as per KDB 941225 D06 Hot Spot SAR
Edge 3 (Bottom)	105 mm	No	SAR is not required because the distance from the antenna to the edge is > 25 mm as per KDB 941225 D06 Hot Spot SAR
Edge 4 (Left)	2 mm	Yes	

8. Conducted Output Power Measurements

8.1. GSM850 and GSM1900

GSM850 Measured Results

Band	Mode	Coding Scheme	Time Slots	Ch No.	Freq. (MHz)	Burst Pwr (dBm)	Frame Pwr (dBm)
850	GSM (Voice)	CS1	1	128	824.2	32.4	23.4
				190	836.6	33.0	24.0
				251	848.8	33.0	24.0
	GPRS (GMSK)	CS1	1	128	824.2	32.4	23.4
				190	836.6	33.0	24.0
				251	848.8	33.0	24.0
			2	128	824.2	28.5	22.5
				190	836.6	28.8	22.8
				251	848.8	28.8	22.8
			3	128	824.2	27.3	23.0
				190	836.6	27.5	23.2
				251	848.8	27.5	23.2
			4	128	824.2	25.2	22.2
				190	836.6	25.4	22.4
				251	848.8	25.5	22.5
	EGPRS (8PSK)	MCS5	1	128	824.2	27.7	18.7
				190	836.6	27.7	18.7
				251	848.8	28.0	19.0
			2	128	824.2	26.2	20.2
				190	836.6	26.3	20.3
				251	848.8	26.5	20.5
			3	128	824.2	22.3	18.0
				190	836.6	22.4	18.1
				251	848.8	22.5	18.2
			4	128	824.2	22.1	19.1
				190	836.6	22.4	19.4
				251	848.8	22.5	19.5

Notes:

The worst-case configuration and mode for SAR testing is determined to be as follows:

- Head & Body-worn Accessory: GMSK Voice Mode
- Hotspot mode: GMSK (GPRS) mode with 1 time slots, based on the output power measurements above
- SAR is not required for EGPRS (8PSK) mode because its output power is less than that of GPRS Mode

GSM1900 Measured Results

Band	Mode	Coding Scheme	Time Slots	Ch No.	Freq. (MHz)	Burst Pwr (dBm)	Frame Pwr (dBm)
1900	GSM (Voice)	CS1	1	512	1850.2	29.7	20.7
				661	1880.0	29.6	20.6
				810	1909.8	29.9	20.9
	GPRS (GMSK)	CS1	1	512	1850.2	29.7	20.7
				661	1880.0	29.6	20.6
				810	1909.8	29.9	20.9
			2	512	1850.2	26.4	20.4
				661	1880.0	26.4	20.4
				810	1909.8	26.5	20.5
			3	512	1850.2	24.3	20.0
				661	1880.0	24.3	20.0
				810	1909.8	24.4	20.1
			4	512	1850.2	23.1	20.1
				661	1880.0	23.1	20.1
				810	1909.8	23.3	20.3
	EGPRS (8PSK)	MCS5	1	512	1850.2	27.2	18.2
				661	1880.0	27.2	18.2
				810	1909.8	27.3	18.3
			2	512	1850.2	25.7	19.7
				661	1880.0	25.7	19.7
				810	1909.8	25.8	19.8
			3	512	1850.2	22.2	17.9
				661	1880.0	22.2	17.9
				810	1909.8	22.3	18.0
			4	512	1850.2	22.2	19.2
				661	1880.0	22.2	19.2
				810	1909.8	22.3	19.3

Notes:

The worst-case configuration and mode for SAR testing is determined to be as follows:

- Head & Body-worn Accessory: GMSK Voice Mode
- Hotspot mode: GMSK (GPRS) mode with 1 time slots, based on the output power measurements above
- SAR is not required for EGPRS (8PSK) mode because its output power is less than that of GPRS Mode

8.2. W-CDMA Band V and II

Release 99

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 specification. The DUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7).

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 2
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	Avg Pwr (dBm)
W-CDMA Band V	Rel 99 (RMC, 12.2 kbps)	4132	826.4	21.9
		4183	836.6	22.1
		4233	846.6	22.0
W-CDMA Band II	Rel 99 (RMC, 12.2 kbps)	9262	1852.4	22.3
		9400	1880.0	22.0
		9538	1907.6	22.3

HSDPA

The following 4 Sub-tests were completed according to Release 7 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
W-CDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm 2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
HSDPA Specific Settings	MPR (dB)	0	1	1.5	1.5
	D_{ACK}	8			
	D_{NAK}	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	$A_{hs} = \beta_{hs}/\beta_c$	30/15			

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
W-CDMA Band V	Subtest 1	4132	826.4	0	21.0
		4183	836.6	0	21.0
		4233	846.6	0	21.0
	Subtest 2	4132	826.4	0	21.0
		4183	836.6	0	21.0
		4233	846.6	0	21.1
	Subtest 3	4132	826.4	0.5	20.7
		4183	836.6	0.5	20.6
		4233	846.6	0.5	20.6
	Subtest 4	4132	826.4	0.5	20.6
		4183	836.6	0.5	20.5
		4233	846.6	0.5	20.6
W-CDMA Band II	Subtest 1	9262	1852.4	0	21.6
		9400	1880.0	0	21.3
		9538	1907.6	0	21.4
	Subtest 2	9262	1852.4	0	21.4
		9400	1880.0	0	21.4
		9538	1907.6	0	21.6
	Subtest 3	9262	1852.4	0.5	21.0
		9400	1880.0	0.5	20.9
		9538	1907.6	0.5	21.0
	Subtest 4	9262	1852.4	0.5	21.2
		9400	1880.0	0.5	20.8
		9538	1907.6	0.5	21.0

Maximum output power levels that are possible for all subtests reported.

HSPA (HSDPA & HSUPA)

The following 5 Sub-tests were completed according to Release 6 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSPA				
	Subtest	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2 kbps RMC				
	HSDPA FRC	H-Set 1				
	HSUPA Test	HSPA				
	Power Control Algorithm	Algorithm 2				Algorithm 1
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c/β_d	11/15	11/15	15/9	2/15	15/0
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	β_{ed}	1309/225	94/75	47/15 47/15	56/75	47/15
HSDPA Specific Settings	CM (dB)	1	3	2	3	1
	MPR (dB)	0	2	1	2	0
	DACK	8				0
	DNAK	8				0
	DCQI	8				0
	Ack-Nack repetition factor	3				
	CQI Feedback (Table 5.2B.4)	4ms				
HSUPA Specific Settings	CQI Repetition Factor (Table 5.2B.4)	2				
	$A_{hs} = \beta_{hs}/\beta_c$	30/15				
	E-DPDCCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E-TFCIs	5	5	2	5	1
	Reference E-TFCI	11	11	11	11	67
	Reference E-TFCI PO	4	4	4	4	18
	Reference E-TFCI	67	67	92	67	67
	Reference E-TFCI PO	18	18	18	18	18
	Reference E-TFCI	71	71	71	71	71
	Reference E-TFCI PO	23	23	23	23	23
	Reference E-TFCI	75	75	75	75	75
	Reference E-TFCI PO	26	26	26	26	26
	Reference E-TFCI	81	81	81	81	81
	Reference E-TFCI PO	27	27	27	27	27
	Maximum Channelisation Codes	2xSF2				SF4

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
W-CDMA Band V	Subtest 1	4132	826.4	0	20.5
		4183	836.6	0	20.7
		4233	846.6	0	21.2
	Subtest 2	4132	826.4	2	19.4
		4183	836.6	2	19.7
		4233	846.6	2	19.7
	Subtest 3	4132	826.4	1	19.7
		4183	836.6	1	20.0
		4233	846.6	1	19.7
	Subtest 4	4132	826.4	2	19.5
		4183	836.6	2	20.0
		4233	846.6	2	20.0
	Subtest 5	4132	826.4	0	20.9
		4183	836.6	0	21.0
		4233	846.6	0	21.0
W-CDMA Band II	Subtest 1	9262	1852.4	0	20.6
		9400	1880.0	0	20.9
		9538	1907.6	0	21.1
	Subtest 2	9262	1852.4	2	19.7
		9400	1880.0	2	19.9
		9538	1907.6	2	19.7
	Subtest 3	9262	1852.4	1	19.6
		9400	1880.0	1	19.8
		9538	1907.6	1	20.2
	Subtest 4	9262	1852.4	2	20.1
		9400	1880.0	2	20.4
		9538	1907.6	2	20.3
	Subtest 5	9262	1852.4	0	21.3
		9400	1880.0	0	21.0
		9538	1907.6	0	21.4

DC-HSDPA

The following tests were completed according to procedures in section 7.3.13 of 3GPP TS34.108 v9.5.0. A summary of these settings are illustrated below:

Downlink Physical Channels are set as per 3GPP TS34.121-1 v9.0.0 E.5.0

Table E.5.0: Levels for HSDPA connection setup

Parameter During Connection setup	Unit	Value
P-CPICH_Ec/Ior	dB	-10
P-CCPCH and SCH_Ec/Ior	dB	-12
PICH_Ec/Ior	dB	-15
HS-PDSCH	dB	off
HS-SCCH_1	dB	off
DPCH_Ec/Ior	dB	-5
OCNS_Ec/Ior	dB	-3.1

Call is set up as per 3GPP TS34.108 v9.5.0 sub clause 7.3.13

The configurations of the fixed reference channels for HSDPA RF tests are described in 3GPP TS 34.121, annex C for FDD and 3GPP TS 34.122.

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table. Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

The following 4 Sub-tests for HSDPA were completed according to Release 8 procedures in section 5.2 of 3GPP TS34.121. A summary of subtest settings are illustrated below:

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	β_d (SF)	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
HSDPA Specific Settings	MPR (dB)	0	0	0.5	0.5
	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack Repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	$A_{hs} = \beta_{hs}/\beta_c$	30/15			

Up commands are set continuously to set the UE to Max power.

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
W-CDMA Band V	Subtest 1	4132	826.4	0	20.8
		4183	836.6	0	20.7
		4233	846.6	0	21.0
	Subtest 2	4132	826.4	0	21.2
		4183	836.6	0	21.0
		4233	846.6	0	21.1
	Subtest 3	4132	826.4	0.5	20.8
		4183	836.6	0.5	20.5
		4233	846.6	0.5	20.6
	Subtest 4	4132	826.4	0.5	20.7
		4183	836.6	0.5	20.6
		4233	846.6	0.5	20.7
W-CDMA Band II	Subtest 1	9262	1852.4	0	21.2
		9400	1880.0	0	21.3
		9538	1907.6	0	21.4
	Subtest 2	9262	1852.4	0	21.4
		9400	1880.0	0	21.1
		9538	1907.6	0	21.7
	Subtest 3	9262	1852.4	0.5	20.1
		9400	1880.0	0.5	20.9
		9538	1907.6	0.5	21.0
	Subtest 4	9262	1852.4	0.5	20.8
		9400	1880.0	0.5	21.0
		9538	1907.6	0.5	21.0

8.3. LTE Band 5

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10, 15, 20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	Table 6.2.4-2
	6.6.3.3.2				
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

LTE Band 5 Measured Results

Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Meas. MPR	Avg Pwr (dBm)		
							829 MHz	836.5 MHz	844 MHz
LTE Band 5	10	QPSK	1	0	0	0	22.9	23.0	23.0
			1	25	0	0	22.9	23.0	22.9
			1	49	0	0	23.0	23.0	22.9
			25	0	1	1	21.9	21.9	21.8
			25	12	1	1	21.9	21.8	21.8
			25	25	1	1	21.9	21.9	21.9
			50	0	1	1	21.8	21.7	21.8
		16QAM	1	0	1	1	22.0	22.4	21.8
			1	25	1	1	22.0	22.4	21.7
			1	49	1	1	22.0	22.5	21.8
			25	0	2	2	21.0	20.9	20.8
			25	12	2	2	20.9	20.9	20.8
			25	25	2	2	21.0	20.9	20.9
			50	0	2	2	20.8	20.7	20.7
Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Meas. MPR	Avg Pwr (dBm)		
							826.5 MHz	836.5 MHz	846.5 MHz
LTE Band 5	5	QPSK	1	0	0	0	23.0	23.0	23.0
			1	12	0	0	23.0	23.0	22.9
			1	24	0	0	23.0	23.0	22.9
			12	0	1	1	22.0	22.0	22.0
			12	6	1	1	21.9	21.9	21.9
			12	11	1	1	21.9	21.9	22.0
			25	0	1	1	21.9	21.8	21.9
		16QAM	1	0	1	1	22.5	22.3	21.9
			1	12	1	1	22.4	22.1	21.8
			1	24	1	1	22.3	22.2	21.6
			12	0	2	2	21.0	21.0	21.0
			12	6	2	2	21.0	20.9	20.9
			12	11	2	2	21.0	21.0	21.0
			25	0	2	2	21.0	20.9	21.0
Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Meas. MPR	Avg Pwr (dBm)		
							825.5 MHz	836.5 MHz	847.5 MHz
LTE Band 5	3	QPSK	1	0	0	0	23.0	23.0	22.8
			1	7	0	0	22.9	22.9	23.0
			1	14	0	0	22.9	22.9	23.0
			8	0	1	1	22.0	21.9	21.9
			8	4	1	1	22.0	21.9	21.8
			8	7	1	1	22.0	21.9	22.0
			15	0	1	1	22.0	21.9	22.0
		16QAM	1	0	1	0	22.4	21.7	22.4
			1	7	1	0	22.4	21.8	22.3
			1	14	1	0	22.4	21.7	22.5
			8	0	2	0	20.9	20.9	20.7
			8	4	2	0	20.8	20.9	20.7
			8	7	2	0	20.8	21.0	20.8
			15	0	2	0	21.0	21.0	21.0

LTE Band 5 Measured Results (continued)

Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Meas. MPR	Avg Pwr (dBm)		
							824.7 MHz	836.5 MHz	848.3 MHz
LTE Band 5	1.4	QPSK	1	0	0	0	22.9	23.0	22.9
			1	2	0	0	22.9	22.8	22.9
			1	5	0	0	22.9	22.9	22.8
			3	0	0	0	23.0	22.9	22.9
			3	1	0	0	22.9	22.9	22.9
			3	2	0	0	22.9	22.9	22.9
			6	0	1	1	22.0	21.9	22.0
		16QAM	1	0	1	0	22.4	21.7	22.4
			1	2	1	0	22.5	21.7	22.4
			1	5	1	0	22.5	21.6	22.4
			3	0	1	0	22.0	21.9	22.2
			3	1	1	0	22.0	22.0	22.3
			3	2	1	0	22.0	21.9	22.3
			6	0	2	0	21.0	21.0	21.0

8.4. Wi-Fi (2.4 GHz Band) (reference to additional KDB in footnote)

Required Test Channels per KDB 248227 D01

Measured Results

Band (GHz)	Mode	Data Rate	Ch #	Freq. (MHz)	Avg Pwr (dBm)	SAR Test (Yes/No)
2.4 (DTS)	802.11b	1 Mbps	1	2412	16.9	Yes
			6	2437	16.5	
			11	2462	16.9	
	802.11g	6 Mbps	1	2412	12.4	No
			6	2437	13.0	
			11	2462	13.0	
	802.11n (HT20)	MCS0	1	2412	10.4	No
			6	2437	11.0	
			11	2462	11.0	

Note(s):

- Per KDB 248227 D01, SAR is not required for 802.11g/HT20 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11b channels.

Power measurements to determine worst-case data rates

Mode	Ch #	Freq. (MHz)	Data Rate	Avg Pwr (dBm)	SAR test (Yes/No)
802.11b	6	2437	1 Mbps	16.9	Yes
			2 Mbps	16.8	No
			5.5 Mbps	16.7	No
			11 Mbps	16.5	No

8.5. Bluetooth

The maximum output power is 10.5 dBm This power level qualifies for exclusion of SAR testing.

Refer to Standalone SAR Test Exclusion Considerations Section.

9. Dielectric Property Measurements

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 – 4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

9.1. Tissue Dielectric Parameters

FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00

IEEE Std 1528-2013

Refer to Table 3 of IEEE Std 1528-2013

9.2. Dielectric Property Measurements Results

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 – 4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

SAR Lab 1

Date	Freq. (MHz)	Liquid Parameters			Measured	Target	Delta (%)	Limit ±(%)
8/11/2014	Body 2450	e'	51.8800	Relative Permittivity (ϵ_r):	51.88	52.70	-1.56	5
		e"	14.9500	Conductivity (σ):	2.04	1.95	4.44	5
	Body 2410	e'	52.0000	Relative Permittivity (ϵ_r):	52.00	52.76	-1.44	5
		e"	14.8500	Conductivity (σ):	1.99	1.91	4.32	5
	Body 2475	e'	51.8100	Relative Permittivity (ϵ_r):	51.81	52.67	-1.63	5
		e"	15.0100	Conductivity (σ):	2.07	1.99	4.06	5
8/11/2014	Head 2450	e'	39.5300	Relative Permittivity (ϵ_r):	39.53	39.20	0.84	5
		e"	13.0000	Conductivity (σ):	1.77	1.80	-1.61	5
	Head 2410	e'	39.6900	Relative Permittivity (ϵ_r):	39.69	39.28	1.05	5
		e"	12.8700	Conductivity (σ):	1.72	1.76	-2.03	5
	Head 2475	e'	39.4400	Relative Permittivity (ϵ_r):	39.44	39.17	0.69	5
		e"	13.0800	Conductivity (σ):	1.80	1.83	-1.48	5

SAR Lab 4

Date	Freq. (MHz)	Liquid Parameters			Measured	Target	Delta (%)	Limit ±(%)
8/11/2014	Head 1900	e'	39.5400	Relative Permittivity (ϵ_r):	39.54	40.00	-1.15	5
		e"	13.5600	Conductivity (σ):	1.43	1.40	2.33	5
	Head 1850	e'	39.8200	Relative Permittivity (ϵ_r):	39.82	40.00	-0.45	5
		e"	13.4300	Conductivity (σ):	1.38	1.40	-1.32	5
	Head 1910	e'	39.5000	Relative Permittivity (ϵ_r):	39.50	40.00	-1.25	5
		e"	13.5800	Conductivity (σ):	1.44	1.40	3.02	5
8/11/2014	Body 1900	e'	51.2400	Relative Permittivity (ϵ_r):	51.24	53.30	-3.86	5
		e"	14.6000	Conductivity (σ):	1.54	1.52	1.48	5
	Body 1850	e'	51.4800	Relative Permittivity (ϵ_r):	51.48	53.30	-3.41	5
		e"	14.4500	Conductivity (σ):	1.49	1.52	-2.21	5
	Body 1910	e'	51.2000	Relative Permittivity (ϵ_r):	51.20	53.30	-3.94	5
		e"	14.6300	Conductivity (σ):	1.55	1.52	2.22	5
8/8/2014	Head 835	e'	41.8600	Relative Permittivity (ϵ_r):	41.86	41.50	0.87	5
		e"	19.9300	Conductivity (σ):	0.93	0.90	2.81	5
	Head 820	e'	42.0300	Relative Permittivity (ϵ_r):	42.03	41.60	1.03	5
		e"	19.9500	Conductivity (σ):	0.91	0.90	1.24	5
	Head 850	e'	41.6800	Relative Permittivity (ϵ_r):	41.68	41.50	0.43	5
		e"	19.8900	Conductivity (σ):	0.94	0.92	2.74	5
8/8/2014	Body 835	e'	53.7000	Relative Permittivity (ϵ_r):	53.70	55.20	-2.72	5
		e"	21.7600	Conductivity (σ):	1.01	0.97	4.15	5
	Body 820	e'	53.8600	Relative Permittivity (ϵ_r):	53.86	55.28	-2.56	5
		e"	21.8500	Conductivity (σ):	1.00	0.97	2.87	5
	Body 850	e'	53.5500	Relative Permittivity (ϵ_r):	53.55	55.16	-2.91	5
		e"	21.7000	Conductivity (σ):	1.03	0.99	3.90	5

SAR Lab 4 Continued

Date	Freq. (MHz)	Liquid Parameters			Measured	Target	Delta (%)	Limit ±(%)
8/12/2014	Head 835	e'	40.1500	Relative Permittivity (ϵ_r):	40.15	41.50	-3.25	5
		e''	19.0200	Conductivity (σ):	0.88	0.90	-1.88	5
	Head 820	e'	40.3200	Relative Permittivity (ϵ_r):	40.32	41.60	-3.08	5
		e''	19.0500	Conductivity (σ):	0.87	0.90	-3.33	5
	Head 850	e'	39.9700	Relative Permittivity (ϵ_r):	39.97	41.50	-3.69	5
		e''	18.9900	Conductivity (σ):	0.90	0.92	-1.91	5
8/12/2014	Body 835	e'	55.2100	Relative Permittivity (ϵ_r):	55.21	55.20	0.02	5
		e''	21.4600	Conductivity (σ):	1.00	0.97	2.72	5
	Body 820	e'	55.2800	Relative Permittivity (ϵ_r):	55.28	55.28	0.01	5
		e''	21.5000	Conductivity (σ):	0.98	0.97	1.22	5
	Body 850	e'	55.1000	Relative Permittivity (ϵ_r):	55.10	55.16	-0.10	5
		e''	21.4200	Conductivity (σ):	1.01	0.99	2.56	5

10. System Check

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are remeasured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

10.1. Reference Target SAR Values

The reference SAR values can be obtained from the calibration certificate of system validation dipoles

System Dipole	Serial No.	Cal. Date	Freq. (MHz)	Target SAR Values (W/kg)		
				1g/10g	Head	Body
D835V2	4d002	11/15/2013	835	1g	9.49	9.43
				10g	6.18	6.21
D1900V2	5d043	11/12/2013	1900	1g	40.1	39
				10g	21.1	20.8
D2450V2	899	9/10/2013	2450	1g	51.3	49.7
				10g	23.9	23.3

10.2. System Check Results

The 1-g and 10-g SAR measured with a reference dipole, using the required tissue-equivalent medium at the test frequency, must be within 10% of the manufacturer calibrated dipole SAR target.

SAR Lab 1

Date Tested	System Dipole		T.S. Liquid	Measured Results			Target (Ref. Value)	Delta $\pm 10\%$	Est./Zoom Ratio	Plot No.
	Type	Serial #		Area Scan	Zoom Scan	Normalize to 1 W				
8/11/2014	D2450V2	899	Body	1g	4.71	4.70	47.0	-5.43	0.21	
				10g	2.04	2.18	21.8	-6.44		
8/11/2014	D2450V2	899	Head	1g	5.66	5.55	55.5	8.19	1.94	1,2
				10g	2.48	2.51	25.1	5.02		

SAR Lab 4

Date Tested	System Dipole		T.S. Liquid	Measured Results			Target (Ref. Value)	Delta $\pm 10\%$	Est./Zoom Ratio	Plot No.
	Type	Serial #		Area Scan	Zoom Scan	Normalize to 1 W				
8/11/2014	D1900V2	5d043	Head	1g	4.41	4.29	42.9	6.98	2.72	3,4
				10g	2.28	2.24	22.4	6.16		
8/11/2014	D1900V2	5d043	Body	1g	4.16	4.11	41.1	5.38	1.20	
				10g	2.12	2.15	21.5	3.37		
8/8/2014	D835V2	4d002	Head	1g	1.04	1.01	10.1	6.43	2.88	
				10g	0.70	0.66	6.6	7.44		
8/8/2014	D835V2	4d002	Body	1g	1.05	1.01	10.1	7.10	3.81	
				10g	0.70	0.67	6.7	7.73		
8/12/2014	D835V2	4d002	Head	1g	1.02	1.00	10.0	5.16	2.16	
				10g	0.69	0.66	6.6	5.99		
8/12/2014	D835V2	4d002	Body	1g	1.05	1.02	10.2	8.17	2.86	5,6
				10g	0.71	0.67	6.7	8.53		

11. Measured and Reported (Scaled) SAR Results

SAR Test Reduction criteria are as follows:

KDB 447498 D01 General RF Exposure Guidance:

Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:

- ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

KDB 648474 D04 Handset SAR:

With headset attached, when the reported SAR for body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

KDB 941225 D01 SAR test for 3G devices:

Body SAR is also measured for HSPA when the maximum average output of each RF channel with HSPA active is at least $\frac{1}{4}$ dB higher than that measured without HSPA using 12.2 kbps RMC or the maximum SAR for 12.2 kbps RMC is above 75% of the SAR limit. Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 with power control algorithm 2.

KDB 941225 D05 SAR for LTE Devices:

SAR test reduction is applied using the following criteria:

- Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB, and 50% RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel.
- When the reported SAR is > 0.8 W/kg, testing for other Channels is performed at the highest output power level for 1RB, and 50% RB configuration for that channel.
- Testing for 100% RB configuration is performed at the highest output power level for 100% RB configuration across the Low, Mid and High Channel when the highest reported SAR for 1 RB and 50% RB are > 0.8 W/kg. Testing for the remaining required channels is not needed because the reported SAR for 100% RB Allocation < 1.45 W/kg.
- Testing for 16-QAM modulation is not required because the reported SAR for QPSK is < 1.45 W/Kg and its output power is not more than 0.5 dB higher than that of QPSK.
- Testing for the other channel bandwidths is not required because the reported SAR for the highest channel bandwidth is < 1.45 W/Kg and its output power is not more than 0.5 dB higher than that of the highest channel bandwidth.

KDB 248227 D01 SAR Measurements Procedures for 802.11 a/b/g Transmitters v01r02 (pg.6):

Each channel should be tested at the lowest data rate in each a-b/g mode or 4.9 GHz channel BW configuration.

When the extrapolated maximum peak SAR for the maximum output channel is ≤ 1.6 W/kg and the 1-g averaged SAR is ≤ 0.8 W/kg, testing of other channels in the "default test channels" or "required test channels" configuration is optional.

11.1. GSM850

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	Meas.	Scaled	
Head	Voice	0	Left Touch	190	836.6	33.0	33.0	0.070	0.070	0.053	0.053	1
			Left Tilt	190	836.6	33.0	33.0	0.038	0.038	0.029	0.029	
			Right Touch	190	836.6	33.0	33.0	0.054	0.054	0.042	0.042	
			Right Tilt	190	836.6	33.0	33.0	0.038	0.038	0.030	0.030	
Head VoIP	GPRS 1 Slots	0	Left Touch	190	836.6	33.0	33.0	0.076	0.076	0.056	0.056	2
			Left Tilt	190	836.6	33.0	33.0	0.040	0.040	0.031	0.031	
			Right Touch	190	836.6	33.0	33.0	0.056	0.056	0.044	0.044	
			Right Tilt	190	836.6	33.0	33.0	0.039	0.039	0.031	0.031	
Body-worn	Voice	10	Rear	190	836.6	33.0	33.0	0.151	0.151	0.095	0.095	3
			Front	190	836.6	33.0	33.0	0.104	0.104	0.071	0.071	
Body-worn(VoIP) & Hotspot	GPRS 1 Slots	10	Rear	190	836.6	33.0	33.0	0.150	0.150	0.093	0.093	4
			Front	190	836.6	33.0	33.0	0.108	0.108	0.073	0.073	
Hotspot		10	Edge 2	190	836.6	33.0	33.0	0.058	0.058	0.042	0.042	
			Edge 3	190	836.6	33.0	33.0	0.021	0.021	0.014	0.014	
			Edge 4	190	836.6	33.0	33.0	0.118	0.118	0.083	0.083	

11.2. GSM1900

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	Meas.	Scaled	
Head	Voice	0	Left Touch	661	1880.0	30.0	29.6	0.149	0.163	0.094	0.103	5
			Left Tilt	661	1880.0	30.0	29.6	0.078	0.086	0.049	0.054	
			Right Touch	661	1880.0	30.0	29.6	0.104	0.114	0.070	0.077	
			Right Tilt	661	1880.0	30.0	29.6	0.079	0.087	0.050	0.055	
Head VoIP	GPRS 1 Slots	0	Left Touch	661	1880.0	30.0	29.6	0.145	0.159	0.092	0.101	6
			Left Tilt	661	1880.0	30.0	29.6	0.072	0.079	0.045	0.049	
			Right Touch	661	1880.0	30.0	29.6	0.104	0.114	0.069	0.076	
			Right Tilt	661	1880.0	30.0	29.6	0.072	0.079	0.047	0.052	
Body-worn	Voice	10	Rear	661	1880.0	30.0	29.6	0.443	0.486	0.247	0.271	
			Front	661	1880.0	30.0	29.6	0.488	0.535	0.271	0.297	7
Body-worn(VoIP) & Hotspot	GPRS 1 Slots	10	Rear	661	1880.0	30.0	29.6	0.459	0.503	0.255	0.280	
Front			661	1880.0	30.0	29.6	0.465	0.510	0.258	0.283	8	
Edge 2			661	1880.0	30.0	29.6	0.045	0.049	0.030	0.033		
Edge 3			661	1880.0	30.0	29.6	0.302	0.331	0.176	0.193		
Edge 4			661	1880.0	30.0	29.6	0.113	0.124	0.071	0.078		
Hotspot												

11.3. W-CDMA Band V

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	Meas.	Scaled	
Head	Rel 99 RMC	0	Left Touch	4183	836.6	23.0	22.1	0.080	0.098	0.060	0.074	9
			Left Tilt	4183	836.6	23.0	22.1	0.044	0.054	0.035	0.043	
			Right Touch	4183	836.6	23.0	22.1	0.059	0.073	0.046	0.057	
			Right Tilt	4183	836.6	23.0	22.1	0.041	0.050	0.032	0.039	
Body-worn & Hotspot	Rel 99 RMC	10	Rear	4183	836.6	23.0	22.1	0.162	0.199	0.099	0.122	10
			Front	4183	836.6	23.0	22.1	0.117	0.144	0.080	0.098	
Hotspot	Rel 99 RMC	10	Edge 2	4183	836.6	23.0	22.1	0.034	0.042	0.025	0.031	
			Edge 3	4183	836.6	23.0	22.1	0.025	0.031	0.017	0.021	
			Edge 4	4183	836.6	23.0	22.1	0.085	0.105	0.060	0.074	

11.4. W-CDMA Band II

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	Meas.	Scaled	
Head	Rel 99 RMC	0	Left Touch	9400	1880.0	23.0	22.0	0.288	0.363	0.174	0.219	11
			Left Tilt	9400	1880.0	23.0	22.0	0.117	0.147	0.072	0.091	
			Right Touch	9400	1880.0	23.0	22.0	0.186	0.234	0.122	0.154	
			Right Tilt	9400	1880.0	23.0	22.0	0.150	0.189	0.092	0.116	
Body-worn & Hotspot	Rel 99 RMC	10	Rear	9262	1852.4	23.0	22.3	0.751	0.882	0.417	0.490	
				9400	1880.0	23.0	22.0	0.719	0.905	0.403	0.507	
				9538	1907.6	23.0	22.3	0.834	0.980	0.459	0.539	12
			Front	9262	1852.4	23.0	22.3	0.587	0.690	0.338	0.397	
				9400	1880.0	23.0	22.0	0.731	0.920	0.409	0.515	
				9538	1907.6	23.0	22.3	0.647	0.760	0.364	0.428	
Hotspot	Rel 99 RMC	10	Edge 2	9400	1880.0	23.0	22.0	0.079	0.099	0.051	0.064	
			Edge 3	9400	1880.0	23.0	22.0	0.552	0.695	0.319	0.402	
			Edge 4	9400	1880.0	23.0	22.0	0.206	0.259	0.126	0.159	

11.5. LTE Band 5 (10MHz Bandwidth)

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	RB Allocation	RB offset	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
								Tune-up limit	Meas.	Meas.	Scaled	Meas.	Scaled	
Head	QPSK	0	Left Touch	20525	836.5	1	49.0	23.5	23.0	0.096	0.108	0.072	0.081	13
						25	25.0	22.5	21.9	0.076	0.087	0.057	0.065	
			Left Tilt	20525	836.5	1	49.0	23.5	23.0	0.048	0.054	0.038	0.043	
						25	25.0	22.5	21.9	0.037	0.042	0.029	0.033	
			Right Touch	20525	836.5	1	49.0	23.5	23.0	0.070	0.079	0.054	0.061	
						25	25.0	22.5	21.9	0.055	0.063	0.042	0.048	
			Right Tilt	20525	836.5	1	49.0	23.5	23.0	0.043	0.048	0.034	0.038	
						25	25.0	22.5	21.9	0.036	0.041	0.029	0.033	
Body-worn & Hotspot	QPSK	10	Rear	20525	836.5	1	49.0	23.5	23.0	0.187	0.210	0.121	0.136	14
						25	25.0	22.5	21.9	0.147	0.169	0.095	0.109	
			Front	20525	836.5	1	49.0	23.5	23.0	0.145	0.163	0.096	0.108	
						25	25.0	22.5	21.9	0.114	0.131	0.076	0.087	
Hotspot	QPSK	10	Edge 2	20525	836.5	1	49.0	23.5	23.0	0.043	0.048	0.031	0.035	
						25	25.0	22.5	21.9	0.032	0.037	0.023	0.026	
			Edge 3	20525	836.5	1	49.0	23.5	23.0	0.028	0.031	0.018	0.020	
						25	25.0	22.5	21.9	0.021	0.024	0.014	0.016	
			Edge 4	20525	836.5	1	49.0	23.5	23.0	0.122	0.137	0.086	0.096	
						25	25.0	22.5	21.9	0.094	0.108	0.067	0.077	

11.6. Wi-Fi (DTS Band)

Frequency Band	RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
							Tune-up limit	Meas.	Meas.	Scaled	Meas.	Scaled	
2.4 GHz	Head	802.11b 1 Mbps	0	Left Touch	6	2437.0	17.5	16.5	0.123	0.155	0.065	0.082	
				Left Tilt	6	2437.0	17.5	16.5	0.096	0.121	0.049	0.062	
				Right Touch	6	2437.0	17.5	16.5	0.277	0.349	0.134	0.169	15
				Right Tilt	6	2437.0	17.5	16.5	0.204	0.257	0.099	0.125	
	Body-worn & Hotspot	802.11b 1 Mbps	10	Rear	6	2437.0	17.5	16.5	0.436	0.549	0.206	0.259	16
				Front	6	2437.0	17.5	16.5	0.085	0.107	0.045	0.057	
	Hotspot	802.11b 1 Mbps	10	Edge 1	6	2437.0	17.5	16.5	0.062	0.078	0.031	0.039	
				Edge 4	6	2437.0	17.5	16.5	0.274	0.345	0.127	0.160	

11.7. Bluetooth

11.7.1. Standalone SAR Test Exclusion Considerations

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$, for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Body-worn Accessory Exposure Conditions

Max. tune-up tolerance limit		Min. test separation distance (mm)	Frequency (GHz)	Result
(dBm)	(mW)			
10.5	11	10	2.480	1.8

Conclusion:

The computed value is < 3 ; therefore, Bluetooth qualifies for Standalone SAR test exclusion.

11.7.2. Estimated SAR

When the standalone SAR test exclusion is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

- $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f_{(\text{GHz})}/x}]$ W/kg for test separation distances ≤ 50 mm;
where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
- 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

Estimated SAR Result for Body-worn Accessory Conditions:

Test Configuration	Max. tune-up tolerance limit (mW)	Min. test separation distance (mm)	Frequency (GHz)	Estimated 1-g SAR (W/kg)
Rear/Front	11	10	2.480	0.231

12. SAR Measurement Variability

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz v01. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the **ratio of largest to smallest SAR** for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

12.1. The Highest Measured SAR Configuration in Each Frequency Band

Frequency Band (MHz)	Air Interface	Head (W/kg)	Body-worn Accessory (W/kg)	Wireless Router (Hotspot) (W/kg)	Repeated SAR (Yes/No)
850	GSM 850				No
	WCDMA Band V				No
	LTE Band 5		0.187		No
1900	GSM 1900				No
	WCDMA Band II		0.834		Yes
2400	Wi-Fi 802.11b/g/n		0.436		No

12.2. Repeated Measurement Results

Head

Frequency band	Test Position	Antenna	Mode	Ch #.	Freq. (MHz)	Meas. SAR (W/kg)		Largest to Smallest SAR Ratio	Note
						Original	Repeated		
W-CDMA Band II	Rear		Rel 99 RMC 12.2 kbps	9538	1907.6	0.834	0.807	1.03	1

Body-worn Accessory and Wireless Router (Hotspot)

N/A

Note(s):

1. Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.20 .

13. Simultaneous Transmission SAR Analysis

13.1. Sum of the SAR for GSM850 & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario			Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① GSM850	② Wi-Fi(DTS)	③ Bluetooth		
Head	Left Touch	① + ②	0.076	0.155		0.231	No
	Left Tilt	① + ②	0.040	0.121		0.161	No
	Right Touch	① + ②	0.056	0.349		0.405	No
	Right Tilt	① + ②	0.039	0.257		0.296	No
Body-worn Accessory & Hotspot	Rear	① + ②	0.151	0.549		0.700	No
		① + ③	0.151		0.231	0.382	No
	Front	① + ②	0.108	0.107		0.215	No
		① + ③	0.108		0.231	0.339	No
Hotspot	Edge 1	① + ②		0.078		0.078	No
	Edge 2	① + ②	0.058			0.058	No
	Edge 3	① + ②	0.021			0.021	No
	Edge 4	① + ②	0.118	0.345		0.463	No

13.2. Sum of the SAR for GSM1900 & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario			Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① GSM1900	② Wi-Fi(DTS)	③ Bluetooth		
Head	Left Touch	① + ②	0.163	0.155		0.318	No
	Left Tilt	① + ②	0.086	0.121		0.207	No
	Right Touch	① + ②	0.114	0.349		0.463	No
	Right Tilt	① + ②	0.087	0.257		0.344	No
Body-worn Accessory & Hotspot	Rear	① + ②	0.503	0.549		1.052	No
		① + ③	0.503		0.231	0.734	No
	Front	① + ②	0.535	0.107		0.642	No
		① + ③	0.535		0.231	0.766	No
Hotspot	Edge 1	① + ②		0.078		0.078	No
	Edge 2	① + ②	0.049			0.049	No
	Edge 3	① + ②	0.331			0.331	No
	Edge 4	① + ②	0.124	0.345		0.469	No

13.3. Sum of the SAR for WCDMA Band V & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario			Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① W-CDMA Band V	② Wi-Fi(DTS)	③ Bluetooth		
Head	Left Touch	① + ②	0.098	0.155		0.253	No
	Left Tilt	① + ②	0.054	0.121		0.175	No
	Right Touch	① + ②	0.073	0.349		0.422	No
	Right Tilt	① + ②	0.050	0.257		0.307	No
Body-worn Accessory & Hotspot	Rear	① + ②	0.199	0.549		0.748	No
		① + ③	0.199		0.231	0.430	No
	Front	① + ②	0.144	0.107		0.251	No
		① + ③	0.144		0.231	0.375	No
Hotspot	Edge 1	① + ②		0.078		0.078	No
	Edge 2	① + ②	0.042			0.042	No
	Edge 3	① + ②	0.031			0.031	No
	Edge 4	① + ②	0.105	0.345		0.450	No

13.4. Sum of the SAR for WCDMA Band II & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario			Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① W-CDMA Band II	② Wi-Fi(DTS)	③ Bluetooth		
Head	Left Touch	① + ②	0.363	0.155		0.518	No
	Left Tilt	① + ②	0.147	0.121		0.268	No
	Right Touch	① + ②	0.234	0.349		0.583	No
	Right Tilt	① + ②	0.189	0.257		0.446	No
Body-worn Accessory & Hotspot	Rear	① + ②	0.980	0.549		1.529	No
		① + ③	0.980		0.231	1.211	No
	Front	① + ②	0.920	0.107		1.027	No
		① + ③	0.920		0.231	1.151	No
Hotspot	Edge 1	① + ②		0.078		0.078	No
	Edge 2	① + ②	0.099			0.099	No
	Edge 3	① + ②	0.695			0.695	No
	Edge 4	① + ②	0.259	0.345		0.604	No

13.5. Sum of the SAR for LTE Band 5 & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario			Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① LTE Band 5	② Wi-Fi(DTS)	③ Bluetooth		
Head	Left Touch	① + ②	0.108	0.155		0.263	No
	Left Tilt	① + ②	0.054	0.121		0.175	No
	Right Touch	① + ②	0.079	0.349		0.428	No
	Right Tilt	① + ②	0.048	0.257		0.305	No
Body-worn Accessory & Hotspot	Rear	① + ②	0.210	0.549		0.759	No
		① + ③	0.210		0.231	0.441	No
	Front	① + ②	0.163	0.107		0.270	No
		① + ③	0.163		0.231	0.394	No
Hotspot	Edge 1	① + ②		0.078		0.078	No
	Edge 2	① + ②	0.048			0.048	No
	Edge 3	① + ②	0.031			0.031	No
	Edge 4	① + ②	0.137	0.345		0.482	No

Conclusion:

Simultaneous transmission SAR measurement (Volume Scan) is not required because either sum of the 1-g SAR is < 1.6 W/kg or the SPLSR is < 0.04 for all circumstances that require SPLSR calculation.

14. Appendixes

Refer to separated files for the following appendixes.

- 14.1. Photos and Antenna Locations**
- 14.2. System Performance Check Plots**
- 14.3. Highest SAR Test Plots**
- 14.4. Calibration Certificate for E-Field Probe EX3DV4 - SN 3902**
- 14.5. Calibration Certificate for E-Field Probe EX3DV4 - SN 3929**
- 14.6. Calibration Certificate for D835V2 - SN 4d002**
- 14.7. Calibration Certificate for D1900V2- SN 5d043**
- 14.8. Calibration Certificate for D2450V2 - SN 899**

END OF REPORT