

FCC DTS REPORT

FCC Certification

Applicant Name:
SAMSUNG Electronics Co.,Ltd.

Address:
129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do,
16677, Rep. of Korea

Date of Issue:

August 26, 2015

Test Site/Location:

HCT CO., LTD., 74, Seoicheon-ro 578beon-gil,
Majang-myeon, Icheon-si, Gyeonggi-do, Korea

Report No.: HCT-R-1508-F003-4

HCT FRN: 0005866421

FCC ID : A3LSMJ200F

APPLICANT : SAMSUNG Electronics Co.,Ltd.

FCC Model(s): SM-J200F/DS

Additional Model(s): SM-J200F, SM-J200G/DD, SM-J200GU/DS

EUT Type: Mobile Phone

Max. RF Output Power: Wi-Fi 802.11b (21.45 dBm) / Wi-Fi 802.11g (25.04 dBm) /
Wi-Fi 802.11n_20MHz BW (24.27dBm)

Frequency Range: 2412 MHz - 2462 MHz (2.4 GHz Band)

Modulation type: CCK/DSSS/OFDM


FCC Classification: Digital Transmission System(DTS)

FCC Rule Part(s): Part 15.247

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)



Report prepared by
: Kyung Soo Kang
Test Engineer of RF Team



Approved by
: Sang Jun Lee
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1508-F003	August 13, 2015	- First Approval Report
HCT-R-1508-F003-1	August 17, 2015	- Revised the Additional model name (SM-J200G/DS -> SM-J200GU/DS)
HCT-R-1508-F003-2	August 21, 2015	- Revised the ANSI version.
HCT-R-1508-F003-3	August 26, 2015	- Retested using ANSI C63.10:2013.
HCT-R-1508-F003-4	August 28, 2015	- Retested radiated emissions with plots. - Revised the peak gain of antenna.

Table of Contents

1. GENERAL INFORMATION	4
2. EUT DESCRIPTION	4
3. TEST METHODOLOGY	5
3.1 EUT CONFIGURATION	5
3.2 EUT EXERCISE	5
3.3 GENERAL TEST PROCEDURES	5
3.4 DESCRIPTION OF TEST MODES	5
4. INSTRUMENT CALIBRATION.....	6
5. FACILITIES AND ACCREDITATIONS	6
5.1 FACILITIES	6
5.2 EQUIPMENT	6
6. ANTENNA REQUIREMENTS	7
7. SUMMARY TEST OF RESULTS	8
8. TEST RESULT	9
8.1 DUTY CYCLE.....	9
8.2 6dB BANDWIDTH (802.11b/g/n)	11
8.3 OUTPUT POWER (802.11b/g/n)	15
8.4 POWER SPECTRAL DENSITY (802.11b/g/n).....	22
8.5 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS	26
8.6 RADIATED MEASUREMENT.....	39
8.6.1 RADIATED SPURIOUS EMISSIONS.....	39
8.6.2 RADIATED RESTRICTED BAND EDGES	52
8.7 POWERLINE CONDUCTED EMISSIONS	55
9. LIST OF TEST EQUIPMENT	60
9.1 LIST OF TEST EQUIPMENT(Conducted Test)	60
9.2 LIST OF TEST EQUIPMENT(Radiated Test).....	61

1. GENERAL INFORMATION

Applicant: SAMSUNG Electronics Co.,Ltd.
Address: 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID: A3LSMJ200F
EUT Type: Mobile Phone
Model name(s): SM-J200F/DS
Additional Model(s): SM-J200F, SM-J200G/DD,SM-J200GU/DS
Date(s) of Tests: July 21, 2015 ~ August 28, 2015
Place of Tests: HCT Co., Ltd.
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea
(IC Recognition No. : 5944A-3)

2. EUT DESCRIPTION

FCC Model Name	SM-J200F/DS	
FCC Additional Model Name	SM-J200F, SM-J200G/DD,SM-J200GU/DS	
EUT Type	Mobile Phone	
Power Supply	DC 3.85 V	
Battery Infomation	Model: EB-BG360BBE Type: Li-ion Battery(Standard)	
Frequency Range	TX: 2412 MHz ~ 2462 MHz RX: 2412 MHz ~ 2462 MHz	
Max. RF Output Power	Peak	Wi-Fi 802.11b(21.45 dBm) / Wi-Fi 802.11g (25.04dBm) / Wi-Fi 802.11n_20MHz BW (24.27 dBm)/
	Average	Wi-Fi 802.11b(16.49 dBm) / Wi-Fi 802.11g (14.53dBm) / Wi-Fi 802.11n_20MHz BW (12.61 dBm)/
Modulation Type	DSSS/CCK(802.11b), OFDM(802.11g, 802.11n)	
Antenna Specification	Manufacturer: PARTRON Antenna type:INTERNAL ANTENNA Peak Gain : 0.90 dBi	

3. TEST METHODOLOGY

FCC KDB 558074 D01 DTS Meas Guidance v03r03 dated June 09, 2015 entitled “Guidance for Performing Compliance Measurements on Digital Transmission Systems(DTS) and the measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) Operating Under §15.247” were used in the measurement.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 8 of ANSI C63.10. (Version: 2013)

Conducted Antenna Terminal

See Section from 9.1 to 9.2.(KDB 558074)

3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 07, 2015 (Registration Number: 90661)

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

* The antennas of this E.U.T are permanently attached.

*The E.U.T Complies with the requirement of §15.203

7. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§15.247(a)(2)	> 500 kHz	CONDUCTED	PASS
Conducted Maximum Peak Output Power	§15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge(Out of Band Emissions)	§15.247(d)	Conducted > 20 dBc		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 8.7		PASS
Radiated Spurious Emissions	§15.205, 15.209	cf. Section 8.6.1	RADIATED	PASS
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 8.6.2		PASS

8. TEST RESULT


8.1 DUTY CYCLE

■ TEST PROCEDURE

According to KDB 558074)6)b), issued 06/09/2015)

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value. Set $VBW \geq RBW$. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

■ TEST CONFIGURATION



■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0)b) in KDB 558074(issued 06/09/2015)

The largest available value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.

1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz ($\geq$ RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = T_{on} / T_{total} and Duty Cycle Factor = $10 \cdot \log(1/\text{Duty Cycle})$

Duty Cycle Factor

Mode	Data Rate	T _{on} (ms)	T _{total} (ms)	Duty Cycle	Duty Cycle Factor (dB)
b	1 Mbps	8.620	8.720	0.98853211	0.050
	2 Mbps	4.320	4.420	0.97737557	0.099
	5.5 Mbps	1.620	1.720	0.94186047	0.260
	11 Mbps	0.861	0.960	0.89687500	0.473
g	6 Mbs	1.431	1.529	0.93590582	0.288
	9 Mbs	0.960	1.062	0.90395480	0.439
	12 Mbs	0.723	0.822	0.87956204	0.557
	18 Mbs	0.492	0.594	0.82828283	0.818
	24 Mbs	0.372	0.473	0.78646934	1.043
	36 Mbs	0.256	0.356	0.71910112	1.432
	48 Mbs	0.195	0.296	0.65878378	1.813
	54 Mbs	0.180	0.280	0.64285714	1.919
n_ 20MHz BW	6.5 Mbs	1.335	1.435	0.93031359	0.314
	13 Mbs	0.690	0.790	0.87341772	0.588
	19.5 Mbs	0.472	0.573	0.82373473	0.842
	26 Mbs	0.363	0.464	0.78232759	1.066
	39 Mbs	0.254	0.355	0.71549296	1.454
	52 Mbs	0.200	0.300	0.66666667	1.761
	58.5 Mbs	0.184	0.284	0.64788732	1.885
	65 Mbs	0.168	0.269	0.62453532	2.044

Note : Duty Cycle Factor = $10 \cdot \log(1/\text{Duty Cycle})$. where, Duty Cycle = $T_{\text{on}} / T_{\text{total}}$


8.2 6dB BANDWIDTH (802.11b/g/n)

Test Requirements and limit, §15.247(a)(2)

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6dB bandwidth is 500 kHz.

■ TEST CONFIGURATION



■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Procedure 8.1 in KDB 558074, issued 06/09/2015)

RBW = 100 kHz

VBW $\geq 3 \times$ RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple

Allow the trace to stabilize

Note : We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.

■ TEST RESULTS

Conducted 6dB Bandwidth Measurements for 802.11b

802.11b Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
Frequency [MHz]	Channel No.			
2412	1	9.082	0.500	Pass
2437	6	9.073	0.500	Pass
2462	11	8.612	0.500	Pass

Conducted 6dB Bandwidth Measurements for 802.11g

802.11g Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
Frequency [MHz]	Channel No.			
2412	1	15.150	0.500	Pass
2437	6	15.150	0.500	Pass
2462	11	15.150	0.500	Pass


Conducted 6dB Bandwidth Measurements for 802.11n_20 MHz BW

802.11n Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
Frequency [MHz]	Channel No.			
2412	1	15.150	0.500	Pass
2437	6	15.140	0.500	Pass
2462	11	15.160	0.500	Pass


Note : In order to simplify the report, attached plots were only the most wide 6 dB BW channel.

■ RESULT PLOTS


6dB Bandwidth plot (802.11b-CH 1)



6dB Bandwidth plot (802.11g-CH 1)



6dB Bandwidth plot (802.11n_20 MHz BW-CH 11)




8.3 OUTPUT POWER (802.11b/g/n)

Test Requirements and limit, §15.247(b)(3)

The transmitter output is connected to the input of an RF power sensor. Measurement is made using a broadband power meter capable of making peak and average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

■ TEST CONFIGURATION(20 MHz BW)



■ TEST PROCEDURE(20 MHz BW)

- Peak Power (Procedure 9.1.2 in KDB 558074, issued 06/09/2015)
 1. Measure the peak power of the transmitter.
- Average Power (Procedure 9.2.3.1 in KDB 558074, issued 06/09/2015)
 1. Measure the duty cycle.
 2. Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
 3. Add $10 \log (1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

Note :

1. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 10.2 dB is offset for 2.4 GHz Band.

Actual value of loss for the attenuator and cable combination is below table.

Band	Frequency(MHz)	Loss(dB)
2.4 GHz	2412	10.21
	2437	10.24
	2462	10.24

(Actual value of loss for the attenuator and cable combination)

TEST RESULTS-Peak

Conducted Output Power Measurements (802.11b Mode)

802.11b Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	1 Mbps	20.32	30
		2 Mbps	20.43	30
		5.5 Mbps	20.52	30
		11 Mbps	20.49	30
2437	6	1 Mbps	21.23	30
		2 Mbps	21.27	30
		5.5 Mbps	21.37	30
		11 Mbps	21.45	30
2462	11	1 Mbps	19.70	30
		2 Mbps	19.75	30
		5.5 Mbps	19.79	30
		11 Mbps	19.76	30

Conducted Output Power Measurements (802.11g Mode)

802.11g Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	6 Mbps	24.36	30
		9 Mbps	24.39	30
		12 Mbps	24.34	30
		18 Mbps	23.99	30
		24 Mbps	24.29	30
		36 Mbps	24.40	30
		48 Mbps	24.01	30
		54 Mbps	24.21	30
2437	6	6 Mbps	25.04	30
		9 Mbps	24.84	30
		12 Mbps	24.52	30
		18 Mbps	24.41	30
		24 Mbps	24.67	30
		36 Mbps	24.62	30
		48 Mbps	24.49	30
		54 Mbps	24.44	30
2462	11	6 Mbps	24.40	30
		9 Mbps	24.11	30
		12 Mbps	23.93	30
		18 Mbps	23.78	30
		24 Mbps	23.92	30
		36 Mbps	24.03	30
		48 Mbps	23.81	30
		54 Mbps	23.79	30

Conducted Output Power Measurements (802.11n_20MHz BW Mode)

802.11n Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	6.5 Mbps	23.79	30
		13 Mbps	23.76	30
		19.5 Mbps	23.26	30
		26 Mbps	23.06	30
		39 Mbps	22.98	30
		52 Mbps	23.79	30
		58.5 Mbps	23.03	30
		65 Mbps	23.16	30
2437	6	6.5 Mbps	23.88	30
		13 Mbps	24.19	30
		19.5 Mbps	24.08	30
		26 Mbps	23.52	30
		39 Mbps	23.25	30
		52 Mbps	24.27	30
		58.5 Mbps	23.36	30
		65 Mbps	23.37	30
2462	11	6.5 Mbps	23.30	30
		13 Mbps	23.53	30
		19.5 Mbps	23.46	30
		26 Mbps	22.81	30
		39 Mbps	22.78	30
		52 Mbps	23.64	30
		58.5 Mbps	22.64	30
		65 Mbps	22.50	30

■ TEST RESULTS-Average

Conducted Output Power Measurements (802.11b Mode)

802.11b Mode		Rate (Mbps)	Measured Power(dBm)	Duty Cycle Factor (dB)	Measured Power(dBm) + Duty Cycle Factor(dB)	Limit (dBm)
Frequency [MHz]	Channel No.					
2412	1	1 Mbps	15.92	0.050	15.97	30
		2 Mbps	16.01	0.099	16.11	30
		5.5 Mbps	15.87	0.260	16.13	30
		11 Mbps	15.64	0.473	16.11	30
2437	6	1 Mbps	16.33	0.050	16.38	30
		2 Mbps	16.35	0.099	16.45	30
		5.5 Mbps	16.21	0.260	16.47	30
		11 Mbps	16.02	0.473	16.49	30
2462	11	1 Mbps	15.53	0.050	15.58	30
		2 Mbps	15.64	0.099	15.74	30
		5.5 Mbps	15.48	0.260	15.74	30
		11 Mbps	15.31	0.473	15.78	30

Conducted Output Power Measurements (802.11g Mode)

802.11g Mode		Rate (Mbps)	Measured Power(dBm)	Duty Cycle Factor (dB)	Measured Power(dBm) + Duty Cycle Factor(dB)	Limit (dBm)
Frequency [MHz]	Channel No.					
2412	1	6 Mbps	13.74	0.288	14.03	30
		9 Mbps	13.61	0.439	14.05	30
		12 Mbps	13.50	0.557	14.06	30
		18 Mbps	13.24	0.818	14.06	30
		24 Mbps	13.00	1.043	14.04	30
		36 Mbps	12.62	1.432	14.05	30
		48 Mbps	12.25	1.813	14.06	30
		54 Mbps	12.10	1.919	14.02	30
2437	6	6 Mbps	14.22	0.288	14.51	30
		9 Mbps	14.08	0.439	14.52	30
		12 Mbps	13.97	0.557	14.53	30
		18 Mbps	13.68	0.818	14.50	30
		24 Mbps	13.45	1.043	14.49	30
		36 Mbps	13.07	1.432	14.50	30
		48 Mbps	12.71	1.813	14.52	30
		54 Mbps	12.57	1.919	14.49	30
2462	11	6 Mbps	13.46	0.288	13.75	30
		9 Mbps	13.26	0.439	13.70	30
		12 Mbps	13.16	0.557	13.72	30
		18 Mbps	12.86	0.818	13.68	30
		24 Mbps	12.67	1.043	13.71	30
		36 Mbps	12.21	1.432	13.64	30
		48 Mbps	11.86	1.813	13.67	30
		54 Mbps	11.71	1.919	13.63	30

Conducted Output Power Measurements (802.11n_20MHz BW Mode)

802.11n Mode		Rate (Mbps)	Measured Power(dBm)	Duty Cycle Factor (dB)	Measured Power(dBm) + Duty Cycle Factor(dB)	Limit (dBm)
Frequency [MHz]	Channel No.					
2412	1	6.5 Mbps	11.86	0.314	12.17	30
		13 Mbps	11.62	0.588	12.21	30
		19.5 Mbps	11.33	0.842	12.17	30
		26 Mbps	11.13	1.066	12.20	30
		39 Mbps	10.75	1.454	12.20	30
		52 Mbps	10.45	1.761	12.21	30
		58.5 Mbps	10.34	1.885	12.23	30
		65 Mbps	10.12	2.044	12.16	30
2437	6	6.5 Mbps	12.22	0.314	12.53	30
		13 Mbps	11.95	0.588	12.54	30
		19.5 Mbps	11.72	0.842	12.56	30
		26 Mbps	11.54	1.066	12.61	30
		39 Mbps	11.16	1.454	12.61	30
		52 Mbps	10.83	1.761	12.59	30
		58.5 Mbps	10.67	1.885	12.56	30
		65 Mbps	10.48	2.044	12.52	30
2462	11	6.5 Mbps	11.53	0.314	11.84	30
		13 Mbps	11.21	0.588	11.80	30
		19.5 Mbps	10.97	0.842	11.81	30
		26 Mbps	10.82	1.066	11.89	30
		39 Mbps	10.44	1.454	11.89	30
		52 Mbps	10.03	1.761	11.79	30
		58.5 Mbps	9.98	1.885	11.87	30
		65 Mbps	9.81	2.044	11.85	30


8.4 POWER SPECTRAL DENSITY (802.11b/g/n)

Test Requirements and limit, §15.247(e)

The peak power spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

Minimum Standard – the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

■ TEST CONFIGURATION



■ TEST PROCEDURE

We tested according to Procedure 10.2 in KDB 558074, issued 06/09/2015

The spectrum analyzer is set to :

Set analyzer center frequency to DTS channel center frequency.

Span = 1.5 times the DTS channel bandwidth.

RBW = 3 kHz ≤ RBW ≤ 100 kHz.

VBW ≥ 3 x RBW.

Sweep = auto couple

Detector = peak

Trace Mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

■ Sample Calculation

PSD = Reading Value + ATT loss + Cable loss(1 ea)

Output Power = -5 dBm + 10 dB + 0.8 dB = 5.8 dBm

Note :

1. Spectrum reading values are not plot data. The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 10.2 dB is offset for 2.4 GHz Band.

Actual value of loss for the attenuator and cable combination is below table.

Band	Frequency(MHz)	Loss(dB)
2.4 GHz	2412	10.21
	2437	10.24
	2462	10.24

(Actual value of loss for the attenuator and cable combination)

■ TEST RESULTS


Conducted Power Density Measurements

Frequency (MHz)	Channel No.	Mode	Test Result		
			PSD (dBm)	Limit (dBm)	Pass/Fail
2412	1	802.11b	-6.360	8	Pass
2437	6		-4.180	8	Pass
2462	11		-5.116	8	Pass
2412	1	802.11g	-8.851	8	Pass
2437	6		-8.947	8	Pass
2462	11		-10.309	8	Pass
2412	1	802.11n 20MHz BW	-11.825	8	Pass
2437	6		-12.541	8	Pass
2462	11		-11.892	8	Pass


Note : In order to simplify the report, attached plots were only the highest PSD channel.

■ RESULT PLOTS


Power Spectral Density (802.11b-CH 6)



Power Spectral Density (802.11g-CH 1)




Power Spectral Density (802.11n_20MHz BW -CH 1)



8.5 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS**Test Requirements and limit, §15.247(d)**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit : 20 dBc**■ TEST CONFIGURATION****■ TEST PROCEDURE**

The transmitter output is connected to the spectrum analyzer. (Procedure 11.0 in KDB 558074, issued 06/09/2015)

RBW = 100 kHz

VBW $\geq 3 \times$ RBW

Set span to encompass the spectrum to be examined

Detector = Peak

Trace Mode = max hold

Sweep time = auto couple

Ensure that the number of measurement points $\geq$ Span/RBW

Allow trace to fully stabilize.

Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 10th harmonic range with the transmitter set to the lowest, middle, and highest channels.

Note :

1. The band edge results in plot is already including the actual values of loss for the attenuator and cable combination.

2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 10.2 dB is offset for 2.4 GHz Band. Actual value of loss for the attenuator and cable combination is below table.

Band	Frequency(MHz)	Loss(dB)
2.4 GHz	2412	10.21
	2437	10.24
	2462	10.24

(Actual value of loss for the attenuator and cable combination)

4. In case of conducted spurious emissions test, please check factors blow table.
5. In order to simplify the report, attached plots were only the worst case channel.

■ FACTORS FOR FREQUENCY

Freq(MHz)	Factor(dB)
30	9.95
100	10.01
200	10.03
300	10.04
400	10.05
500	10.04
600	10.03
700	10.09
800	10.10
900	10.08
1000	10.11
2000	10.25
2400*	10.19
2500*	10.26
3000	10.27
4000	10.22
5000	10.48
5700*	10.42
5800*	10.48
6000	10.48
7000	10.57
8000	10.45


9000	10.50
10000	10.64
11000	10.69
12000	10.75
13000	10.92
14000	11.90
15000	11.00
16000	11.03
17000	10.93
18000	10.96
19000	10.85
20000	12.11
21000	11.17
22000	10.99
23000	11.12
24000	11.10
25000	11.42

Note : 1. '*' is fundamental frequency range.


2. Factor = Cable loss + Attenuator loss

■ RESULT PLOTS


BandEdge (802.11b-CH1)




BandEdge (802.11b-CH11)




BandEdge (802.11g-CH1)




BandEdge (802.11g-CH11)



Band Edge (802.11n_20MHz-CH1)




Band Edge (802.11n_20MHz-CH11)




30 MHz ~ 1 GHz

Conducted Spurious Emission (802.11g_Ch.6_6 Mbps)




1 GHz ~ 3 GHz

Conducted Spurious Emission (802.11g_Ch.6_6 Mbps)




3 GHz ~ 5 GHz

Conducted Spurious Emission (802.11g_Ch.6_6 Mbps)




5 GHz ~ 7 GHz

Conducted Spurious Emission (802.11g_Ch.6_6 Mbps)




7 GHz ~ 9 GHz

Conducted Spurious Emission (802.11g_Ch.6_6 Mbps)




9 GHz ~ 11 GHz

Conducted Spurious Emission (802.11g_Ch.6_6 Mbps)




11 GHz ~ 13 GHz

Conducted Spurious Emission (802.11g_Ch.6_6 Mbps)




13 GHz ~ 15 GHz

Conducted Spurious Emission (802.11g_Ch.6_6 Mbps)




15 GHz ~ 17 GHz

Conducted Spurious Emission (802.11g_Ch.6_6 Mbps)




17 GHz ~ 19 GHz

Conducted Spurious Emission (802.11g_Ch.6_6 Mbps)




19 GHz ~ 21 GHz

Conducted Spurious Emission (802.11g_Ch.6_6 Mbps)




21 GHz ~ 23 GHz

Conducted Spurious Emission (802.11g_Ch.6_6 Mbps)



23 GHz ~ 25 GHz

Conducted Spurious Emission (802.11g_Ch.6_6 Mbps)




8.6 RADIATED MEASUREMENT.**8.6.1 RADIATED SPURIOUS EMISSIONS.**

Test Requirements and limit, §15.205, §15.209


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



TEST PROCEDURE USED

Method 12.1 in KDB 558074, issued 06/09/2015

Spectrum Setting

- Peak

Peak emission levels are measured by setting the instrument as follows:

RBW = cf. Table 1.

VBW $\geq 3 \times$ RBW.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweeps to continue until the trace stabilizes.

(Note that the required measurement time may be longer for low duty cycle applications).

Table 1 —RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

- Average (duty cycle $\geq 98\%$)

Set RBW = 1 MHz

Set VBW $\geq 3 \times$ RBW

Detector = RMS

Averaging type = power (i.e., RMS).

Sweep time = auto.

Trace mode = average (at least 100 traces).

- Average (duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$)

Set RBW = 1 MHz

Set VBW $\geq 3 \times$ RBW

Detector = RMS.

Averaging type = power (i.e., RMS).

Sweep time = auto.

Trace mode = average (at least 100 traces).

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.

- Average (duty cycle $< 98\%$, duty cycle variations exceed $\pm 2\%$)

Set RBW = 1 MHz

Set VBW $\geq 1/T$. (at least 100 times less than the resolution bandwidth, but no less than 10 Hz.)

Select spectrum analyzer linear display mode.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Note :

1. We are performed the RSE and radiated band edge using standard radiated method.

2. The duty cycle factor for 802.11 b/g/n

Mode	Worst Data rate (Mbps)	T _{on} (ms)	T _{total} (ms)	Duty Cycle (%)	Duty Cycle Factor (dB)	VBW(1/T) (Hz)
b	1	8.620	8.720	98.85	0.050	116
g	6	1.431	1.529	93.59	0.288	699
n_20MHz	6.5	1.335	1.435	93.03	0.314	749

TEST RESULTS

9 kHz – 30MHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	$\text{dB}\mu\text{V}$	dB /m	dB	(H/V)	$\text{dB}\mu\text{V/m}$	$\text{dB}\mu\text{V/m}$	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)
4. Limit line = specific Limits (dBuV) + Distance extrapolation factor
5. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

TEST RESULTS

Below 1 GHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	$\text{dB}_{\mu\text{V}}$	dB /m	dB	(H/V)	$\text{dB}_{\mu\text{V/m}}$	$\text{dB}_{\mu\text{V/m}}$	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Above 1 GHz

Operation Mode: 802.11 b
Transfer Rate: 1 Mbps
Operating Frequency: 2412
Channel No.: 01 Ch

Frequency [MHz]	Reading dBuV	A.F.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	53.19	-1.98	V	51.21	73.98	22.77	PK
4824	46.10	-1.98	V	44.12	53.98	9.86	AV
7236	47.25	7.60	V	54.85	73.98	19.13	PK
7236	35.79	7.60	V	43.39	53.98	10.59	AV
4824	52.12	-1.98	H	50.14	73.98	23.84	PK
4824	44.61	-1.98	H	42.63	53.98	11.35	AV
7236	46.84	7.60	H	54.44	73.98	19.54	PK
7236	35.12	7.60	H	42.72	53.98	11.26	AV

Operation Mode: 802.11 g
Transfer Rate: 6 Mbps
Operating Frequency: 2412
Channel No.: 01 Ch

Frequency [MHz]	*Reading dBuV	A.F.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	49.93	-1.98	V	47.95	73.98	26.03	PK
4824	35.64	-1.98	V	33.66	53.98	20.32	AV
7236	46.02	7.60	V	53.62	73.98	20.36	PK
7236	32.37	7.60	V	39.97	53.98	14.01	AV
4824	49.57	-1.98	H	47.59	73.98	26.39	PK
4824	35.59	-1.98	H	33.61	53.98	20.37	AV
7236	45.13	7.60	H	52.73	73.98	21.25	PK
7236	32.27	7.60	H	39.87	53.98	14.11	AV

Operation Mode: 802.11 n
Transfer Rate: 6.5 Mbps
Operating Frequency: 2412
Channel No.: 01 Ch

Frequency [MHz]	*Reading dBuV	A.F.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	49.49	-1.98	V	47.51	73.98	26.47	PK
4824	35.67	-1.98	V	33.69	53.98	20.29	AV
7236	45.78	7.60	V	53.38	73.98	20.60	PK
7236	32.38	7.60	V	39.98	53.98	14.00	AV
4824	49.08	-1.98	H	47.10	73.98	26.88	PK
4824	35.51	-1.98	H	33.53	53.98	20.45	AV
7236	45.25	7.60	H	52.85	73.98	21.13	PK
7236	32.25	7.60	H	39.85	53.98	14.13	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. The Reading values are already added value of the duty cycle factor. (802.11g/n)
5. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
6. We have done 802.11b/g/n mode and all data rate. Worst data rate is the lowest data of each mode.
7. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: 802.11 b
 Transfer Rate: 1 Mbps
 Operating Frequency: 2437
 Channel No.: 06 Ch

Frequency [MHz]	Reading dBuV	A.F.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	51.08	-1.92	V	49.16	73.98	24.82	PK
4874	42.27	-1.92	V	40.35	53.98	13.63	AV
7311	47.33	7.38	V	54.71	73.98	19.27	PK
7311	34.45	7.38	V	41.83	53.98	12.15	AV
4874	50.35	-1.92	H	48.43	73.98	25.55	PK
4874	41.17	-1.92	H	39.25	53.98	14.73	AV
7311	47.10	7.38	H	54.48	73.98	19.50	PK
7311	33.94	7.38	H	41.32	53.98	12.66	AV

Operation Mode: 802.11 g
 Transfer Rate: 6 Mbps
 Operating Frequency: 2437
 Channel No.: 06 Ch

Frequency [MHz]	Reading dBuV	A.F.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	50.11	-1.92	V	48.19	73.98	25.79	PK
4874	35.74	-1.92	V	33.82	53.98	20.16	AV
7311	46.96	7.38	V	54.34	73.98	19.64	PK
7311	32.45	7.38	V	39.83	53.98	14.15	AV
4874	49.82	-1.92	H	47.90	73.98	26.08	PK
4874	35.43	-1.92	H	33.51	53.98	20.47	AV
7311	46.58	7.38	H	53.96	73.98	20.02	PK
7311	32.38	7.38	H	39.76	53.98	14.22	AV

Operation Mode: 802.11 n
Transfer Rate: 6.5 Mbps
Operating Frequency: 2437
Channel No.: 06 Ch

Frequency [MHz]	Reading dBuV	A.F.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	50.01	-1.92	V	48.09	73.98	25.89	PK
4874	35.71	-1.92	V	33.79	53.98	20.19	AV
7311	46.45	7.38	V	53.83	73.98	20.15	PK
7311	32.49	7.38	V	39.87	53.98	14.11	AV
4874	49.68	-1.92	H	47.76	73.98	26.22	PK
4874	35.46	-1.92	H	33.54	53.98	20.44	AV
7311	46.20	7.38	H	53.58	73.98	20.40	PK
7311	32.45	7.38	H	39.83	53.98	14.15	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. The Reading values are already added value of the duty cycle factor. (802.11g/n)
5. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
6. We have done 802.11b/g/n mode and all data rate. Worst data rate is the lowest data of each mode.
7. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: 802.11 b
Transfer Rate: 1 Mbps
Operating Frequency: 2462
Channel No. 11 Ch

Frequency [MHz]	Reading dBuV	A.F.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	52.68	-1.93	V	50.75	73.98	23.23	PK
4924	45.89	-1.93	V	43.96	53.98	10.02	AV
7386	47.05	7.28	V	54.33	73.98	19.65	PK
7386	33.94	7.28	V	41.22	53.98	12.76	AV
4924	51.57	-1.93	H	49.64	73.98	24.34	PK
4924	44.36	-1.93	H	42.43	53.98	11.55	AV
7386	46.71	7.28	H	53.99	73.98	19.99	PK
7386	33.48	7.28	H	40.76	53.98	13.22	AV

Operation Mode: 802.11 g
Transfer Rate: 6 Mbps
Operating Frequency: 2462
Channel No. 11 Ch

Frequency [MHz]	Reading dBuV	A.F.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	48.52	-1.93	V	46.59	73.98	27.39	PK
4924	34.81	-1.93	V	32.88	53.98	21.10	AV
7386	45.40	7.28	V	52.68	73.98	21.30	PK
7386	31.59	7.28	V	38.87	53.98	15.11	AV
4924	48.51	-1.93	H	46.58	73.98	27.40	PK
4924	34.64	-1.93	H	32.71	53.98	21.27	AV
7386	45.19	7.28	H	52.47	73.98	21.51	PK
7386	31.49	7.28	H	38.77	53.98	15.21	AV

Operation Mode: 802.11 n
 Transfer Rate: 6.5 Mbps
 Operating Frequency: 2462
 Channel No.: 11 Ch


Frequency [MHz]	Reading dBuV	A.F.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	48.69	-1.93	V	46.76	73.98	27.22	PK
4924	34.83	-1.93	V	32.90	53.98	21.08	AV
7386	45.66	7.28	V	52.94	73.98	21.04	PK
7386	31.57	7.28	V	38.85	53.98	15.13	AV
4924	48.46	-1.93	H	46.53	73.98	27.45	PK
4924	34.62	-1.93	H	32.69	53.98	21.29	AV
7386	45.10	7.28	H	52.38	73.98	21.60	PK
7386	31.49	7.28	H	38.77	53.98	15.21	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. The Reading values are already added value of the duty cycle factor. (802.11g/n)
5. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
6. We have done 802.11b/g/n mode and all data rate. Worst data rate is the lowest data of each mode.
7. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.


RESULT PLOTS

Radiated Spurious Emissions plot – Average Reading (802.11b, Ch.1 2nd Harmonic)



Date: 28.AUG.2015 08:20:50

Radiated Spurious Emissions plot – Peak Reading (802.11b, Ch.1 2nd Harmonic)



Date: 28.AUG.2015 08:21:52

Note : Only the worst case plots for Radiated Spurious Emissions.

8.6.2 RADIATED RESTRICTED BAND EDGES

Test Requirements and limit, §15.247(d) §15.205, §15.209

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c)).

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading dBuV	A.F.+CL [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	31.18	31.47	H	62.65	73.98	11.33	PK
2390.0	15.40	31.47	H	46.87	53.98	7.11	AV
2390.0	29.04	31.47	V	60.51	73.98	13.47	PK
2390.0	14.38	31.47	V	45.85	53.98	8.13	AV
2483.5	39.00	31.46	H	70.46	73.98	3.52	PK
2483.5	17.40	31.46	H	48.86	53.98	5.12	AV
2483.5	37.11	31.46	V	68.57	73.98	5.41	PK
2483.5	16.24	31.46	V	47.70	53.98	6.28	AV

Operation Mode: 802.11b

Transfer Rate: 1 Mbps

Operating Frequency: 2412 MHz, 2462 MHz

Channel No. 01 Ch, 11 Ch

Frequency [MHz]	Reading dBuV	A.F.+CL [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	26.16	31.47	H	57.63	73.98	16.35	PK
2390.0	12.43	31.47	H	43.90	53.98	10.08	AV
2390.0	24.01	31.47	V	55.48	73.98	18.50	PK
2390.0	12.20	31.47	V	43.67	53.98	10.31	AV
2483.5	27.03	31.46	H	58.49	73.98	15.49	PK
2483.5	13.51	31.46	H	44.97	53.98	9.01	AV
2483.5	25.93	31.46	V	57.39	73.98	16.59	PK
2483.5	12.98	31.46	V	44.44	53.98	9.54	AV

Operation Mode: 802.11n_20MHz BW

Transfer Rate: 6.5 Mbps

Operating Frequency: 2412 MHz, 2462 MHz

Channel No. 01 Ch, 11 Ch


Frequency [MHz]	Reading dBuV	A.F.+CL [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	28.80	31.47	H	60.27	73.98	13.71	PK
2390.0	14.18	31.47	H	45.65	53.98	8.33	AV
2390.0	27.52	31.47	V	58.99	73.98	14.99	PK
2390.0	13.13	31.47	V	44.60	53.98	9.38	AV
2483.5	37.12	31.46	H	68.58	73.98	5.40	PK
2483.5	15.88	31.46	H	47.34	53.98	6.64	AV
2483.5	36.55	31.46	V	68.01	73.98	5.97	PK
2483.5	15.06	31.46	V	46.52	53.98	7.46	AV

Notes:

1. The Reading values are already added value of the duty cycle factor. (802.11g/n)
2. Total = Reading Value + Antenna Factor + Cable Loss
3. We have done 802.11b/g/n mode and all data rate. Worst data rate is the lowest data of each mode.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.


RESULT PLOTS

Radiated Restricted Band Edges plot – Average Reading (802.11g, Ch.11)



Date: 28.AUG.2015 06:58:11

Radiated Restricted Band Edges plot – Peak Reading (802.11g, Ch.11)



Date: 28.AUG.2015 08:30:33

Note : Only the worst case plots for Radiated Restricted Band Edges.

8.7 POWERLINE CONDUCTED EMISSIONS

Test Requirements and limit, §15.207

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.

Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

RESULT PLOTS

Conducted Emissions (Line 1)

EMI Auto Test(7)


1 / 2

HCT TEST Report

Common Information

EUT: SM-J200F/DS
Manufacturer: SAMSUNG
Test Site: SHIELD ROOM
Operating Conditions: WLAN MODE
Operator Name: KS KANG

FCC CLASS B



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
— Preview Result 2-AVG — Final Result 1-QPK — Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	45.8	9.000	Off	N	9.6	20.2	66.0
0.166000	49.2	9.000	Off	N	9.6	16.0	65.2
0.174000	47.2	9.000	Off	N	9.6	17.6	64.8
0.180000	45.6	9.000	Off	N	9.6	18.9	64.5
0.190000	42.9	9.000	Off	N	9.6	21.1	64.0
0.206000	44.0	9.000	Off	N	9.6	19.4	63.4
2.420000	32.5	9.000	Off	N	9.7	23.5	56.0
2.508000	33.4	9.000	Off	N	9.7	22.6	56.0
2.514000	34.3	9.000	Off	N	9.7	21.7	56.0
2.550000	32.5	9.000	Off	N	9.7	23.5	56.0
2.554000	32.6	9.000	Off	N	9.7	23.4	56.0
2.596000	32.3	9.000	Off	N	9.7	23.7	56.0
5.344000	30.4	9.000	Off	N	9.8	29.6	60.0
6.078000	28.2	9.000	Off	N	9.9	31.8	60.0
6.774000	28.7	9.000	Off	N	9.9	31.3	60.0
7.558000	27.4	9.000	Off	N	9.9	32.6	60.0

7/24/2015

9:12:44

EMI Auto Test(7)

2 / 2

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
8.410000	28.2	9.000	Off	N	9.9	31.8	60.0
9.026000	27.6	9.000	Off	N	9.9	32.4	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.152000	31.1	9.000	Off	N	9.6	24.8	55.9
0.166000	35.3	9.000	Off	N	9.6	19.9	55.2
0.186000	28.4	9.000	Off	N	9.6	25.8	54.2
0.190000	28.2	9.000	Off	N	9.6	25.8	54.0
0.194000	28.6	9.000	Off	N	9.6	25.3	53.9
0.204000	30.1	9.000	Off	N	9.6	23.3	53.4
2.420000	24.4	9.000	Off	N	9.7	21.6	46.0
2.506000	25.3	9.000	Off	N	9.7	20.7	46.0
2.516000	26.5	9.000	Off	N	9.7	19.5	46.0
2.550000	25.2	9.000	Off	N	9.7	20.8	46.0
2.554000	25.6	9.000	Off	N	9.7	20.4	46.0
2.666000	24.0	9.000	Off	N	9.7	22.0	46.0
5.252000	21.3	9.000	Off	N	9.8	28.7	50.0
5.548000	20.8	9.000	Off	N	9.8	29.2	50.0
5.708000	21.4	9.000	Off	N	9.8	28.6	50.0
6.774000	19.2	9.000	Off	N	9.9	30.8	50.0
8.832000	20.0	9.000	Off	N	9.9	30.0	50.0
9.074000	20.4	9.000	Off	N	9.9	29.6	50.0

7/24/2015

9:12:44

Conducted Emissions (Line 2)

EMI Auto Test(7)


1 / 2

HCT TEST Report

Common Information

EUT: SM-J200F/DS
Manufacturer: SAMSUNG
Test Site: SHIELD ROOM
Operating Conditions: WLAN MODE
Operator Name: KS KANG

FCC CLASS B



— FCCCLASS B_QP — FCCCLASS B_AV — Preview Result 1-PK*
— Preview Result 2-AVG × Final Result 1-QPK × Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.152000	42.6	9.000	Off	L1	9.6	23.3	65.9
0.164000	45.9	9.000	Off	L1	9.6	19.4	65.3
0.178000	44.2	9.000	Off	L1	9.6	20.4	64.6
0.184000	42.1	9.000	Off	L1	9.6	22.2	64.3
0.204000	41.1	9.000	Off	L1	9.6	22.3	63.4
0.218000	40.8	9.000	Off	L1	9.6	22.1	62.9
2.436000	40.9	9.000	Off	L1	9.7	15.1	56.0
2.442000	41.0	9.000	Off	L1	9.7	15.0	56.0
2.446000	40.8	9.000	Off	L1	9.7	15.2	56.0
2.528000	40.4	9.000	Off	L1	9.7	15.6	56.0
2.572000	40.0	9.000	Off	L1	9.7	16.0	56.0
2.576000	39.4	9.000	Off	L1	9.7	16.6	56.0
5.206000	37.6	9.000	Off	L1	9.8	22.4	60.0
5.272000	36.0	9.000	Off	L1	9.8	24.0	60.0
5.508000	35.8	9.000	Off	L1	9.9	24.2	60.0
22.622000	34.7	9.000	Off	L1	10.3	25.3	60.0

7/24/2015

9:23:33

EMI Auto Test(7)

2 / 2

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
23.104000	35.0	9.000	Off	L1	10.3	25.0	60.0
23.114000	34.1	9.000	Off	L1	10.3	25.9	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.152000	28.3	9.000	Off	L1	9.6	27.6	55.9
0.164000	31.8	9.000	Off	L1	9.6	23.5	55.3
0.168000	31.8	9.000	Off	L1	9.6	23.3	55.1
0.174000	31.3	9.000	Off	L1	9.6	23.5	54.8
0.202000	26.7	9.000	Off	L1	9.6	26.8	53.5
0.206000	26.8	9.000	Off	L1	9.6	26.6	53.4
2.406000	29.6	9.000	Off	L1	9.7	16.4	46.0
2.436000	31.4	9.000	Off	L1	9.7	14.6	46.0
2.442000	31.0	9.000	Off	L1	9.7	15.0	46.0
2.534000	29.9	9.000	Off	L1	9.7	16.1	46.0
2.566000	31.0	9.000	Off	L1	9.7	15.0	46.0
2.618000	29.7	9.000	Off	L1	9.8	16.3	46.0
5.204000	26.5	9.000	Off	L1	9.8	23.5	50.0
5.208000	26.5	9.000	Off	L1	9.8	23.5	50.0
5.272000	26.3	9.000	Off	L1	9.8	23.7	50.0
5.508000	25.5	9.000	Off	L1	9.9	24.5	50.0
22.622000	23.0	9.000	Off	L1	10.3	27.0	50.0
23.104000	23.2	9.000	Off	L1	10.3	26.8	50.0

7/24/2015

9:23:33

9. LIST OF TEST EQUIPMENT

9.1 LIST OF TEST EQUIPMENT(Conducted Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216/ LISN	01/13/2015	Annual	100073
Agilent	E4440A/ Spectrum Analyzer	03/18/2015	Annual	US45303008
Agilent	N9020A/ SIGNAL ANALYZER	04/29/2015	Annual	MY51110063
Agilent	N1911A/Power Meter	01/15/2015	Annual	MY45100523
Agilent	N1921A /POWER SENSOR	07/09/2015	Annual	MY45241059
Agilent	87300B/Directional Coupler	12/08/2014	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	04/30/2015	Annual	11275
ITECH	IT6720 / DC POWER SUPPLY	11/04/2014	Annual	010002156287001199
Rohde & Schwarz	CBT / BLUETOOTH TESTER	03/13/2015	Annual	100808
Agilent	8493C / Attenuator(10 dB)	07/21/2015	Annual	76649

9.2 LIST OF TEST EQUIPMENT(Radiated Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Schwarzbeck	VULB 9160/ TRILOG Antenna	10/10/2014	Biennial	3368
HD	MA240/ Antenna Position Tower	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	12
Rohde & Schwarz	SCU-18/ Signal Conditioning Unit	09/04/2014	Annual	10094
*CERNEX	CBL18265035 / POWER AMP	07/27/2015	Annual	22966
Schwarzbeck	BBHA 9120D/ Horn Antenna	12/03/2013	Biennial	9120D-1191
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	04/30/2015	Biennial	BBHA9170124
Rohde & Schwarz	FSP / Spectrum Analyzer	10/23/2014	Annual	836650/016
Wainwright Instrument	WHF3.0/18G-10EF / High Pass Filter	06/29/2015	Annual	8
Wainwright Instrument	WRCJ2400/2483.5-2370/2520-60/14SS / Band Reject Filter	06/15/2015	Annual	1
Rohde & Schwarz	CBT / BLUETOOTH TESTER	03/13/2015	Annual	100808
Rohde & Schwarz	LOOP ANTENNA	09/03/2014	Biennial	1513-175
CERNEX	CBL06185030 / POWER AMP	07/21/2015	Annual	22965
CERNEX	CBLU1183540 / POWER AMP	07/21/2015	Annual	22964
*The CERNEX POWER AMP(22966) used after calibration date(2015.07.27)				