



SAR EVALUATION REPORT

Applicant Name:

Samsung Electronics, Co. Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do 443-742, Korea

Date of Testing:

04/14/14 - 06/19/14

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

0Y1405231077.A3L

FCC ID:

A3LSMT705Y

APPLICANT:

SAMSUNG ELECTRONICS, CO. LTD.

DUT Type:

Portable Tablet

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model(s):

SM-T705Y

Equipment Class	Band & Mode	Tx Frequency	SAR	
			1 gm Head (W/kg)	1 gm Body (W/kg)
PCB	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	< 0.1	0.93
PCB	UMTS 850	826.40 - 846.60 MHz	< 0.1	0.45
PCB	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	< 0.1	0.56
PCB	UMTS 1900	1852.4 - 1907.6 MHz	0.23	0.88
PCB	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.10	0.55
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.48	1.06
DTS	Bluetooth LE	2402 - 2480 MHz	N/A	
DTS	5.8 GHz WLAN	5745 - 5825 MHz		
NII	5.2 GHz WLAN	5180 - 5240 MHz		
NII	5.3 GHz WLAN	5260 - 5320 MHz		
NII	5.5 GHz WLAN	5500 - 5700 MHz		
DSS	Bluetooth	2402 - 2480 MHz	N/A	0.27
Simultaneous SAR per KDB 690783 D01v01r02:			0.61	1.57

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.7 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



FCC ID: A3LSMT705Y		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 1 of 68

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	9
3	INTRODUCTION	10
4	DOSIMETRIC ASSESSMENT	11
5	DEFINITION OF REFERENCE POINTS	12
6	TEST CONFIGURATION POSITIONS FOR HANDSETS	13
7	RF EXPOSURE LIMITS	15
8	FCC MEASUREMENT PROCEDURES.....	16
9	RF CONDUCTED POWERS.....	20
10	SYSTEM VERIFICATION.....	37
11	SAR DATA SUMMARY	39
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	45
13	SAR MEASUREMENT VARIABILITY	63
14	EQUIPMENT LIST	64
15	MEASUREMENT UNCERTAINTIES	65
16	CONCLUSION.....	66
17	REFERENCES	67
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: SAR TEST SETUP PHOTOGRAPHS		
APPENDIX G: SENSOR TRIGGERING INFORMATION		

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet	Page 2 of 68	

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 5 (Cell)	Data	824.7 - 848.3 MHz
2.4 GHz WLAN	Data	2412 - 2462 MHz
5.8 GHz WLAN	Data	5745 - 5825 MHz
5.2 GHz WLAN	Data	5180 - 5240 MHz
5.3 GHz WLAN	Data	5260 - 5320 MHz
5.5 GHz WLAN	Data	5500 - 5700 MHz
Bluetooth	Data	2402 - 2480 MHz
ANT+	Data	2402 - 2480 MHz

1.2 Power Reduction for SAR

This device uses a sensor for SAR compliance. The sensor is activated when used in close proximity to the user's body. The sensor triggers power reduction for voice and data modes and is only applicable for tablet operations. Since the device is a full tablet size, the Body SAR was evaluated per FCC KDB Publication 616217 D04v01 for full sized tablets.

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v05.

Maximum Power:

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	33.0	33.0	31.5	30.0	28.5	27.5	26.0	24.5	23.0
	Nominal	32.5	32.5	31.0	29.5	28.0	27.0	25.5	24.0	22.5
GSM/GPRS/EDGE 1900	Maximum	29.0	29.0	28.5	27.5	26.0	27.0	25.5	24.0	22.5
	Nominal	28.5	28.5	28.0	27.0	25.5	26.5	25.0	23.5	22.0

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA Rel. 99	3GPP HSDPA Rel. 5	3GPP HSUPA Rel. 6
UMTS Band 5 (850 MHz)	Maximum	23.0	23.0	23.0
	Nominal	22.5	22.5	22.5
UMTS Band 2 (1900 MHz)	Maximum	23.5	23.5	23.5
	Nominal	23.0	23.0	23.0

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 3 of 68

Mode / Band		Modulated Average (dBm)
LTE Band 5 (Cell)	Maximum	23.0
	Nominal	22.5

Mode / Band		Modulated Average (dBm)
SISO IEEE 802.11b (2.4 GHz)	Maximum	12.5
	Nominal	12.0
SISO IEEE 802.11g (2.4 GHz)	Maximum	11.5
	Nominal	11.0
SISO & MIMO IEEE 802.11n (2.4 GHz)	Maximum	10.5
	Nominal	10.0
SISO IEEE 802.11a (5 GHz)	Maximum	8.0
	Nominal	7.5
SISO IEEE 802.11n (5 GHz)	Maximum	8.0
	Nominal	7.5
MIMO IEEE 802.11n (5.2-5.5 GHz) - 20MHz Bandwidth	Maximum	7.0
	Nominal	6.5
MIMO IEEE 802.11n (5.2-5.3 GHz) - 40MHz Bandwidth	Maximum	6.5
	Nominal	6.0
MIMO IEEE 802.11n (5.5 GHz) - 40MHz Bandwidth	Maximum	7.0
	Nominal	6.5
MIMO IEEE 802.11n (5.8 GHz)	Maximum	8.0
	Nominal	7.5
SISO IEEE 802.11ac (5 GHz)	Maximum	8.0
	Nominal	7.5
MIMO IEEE 802.11ac (5.2-5.5 GHz) - 80MHz Bandwidth	Maximum	6.5
	Nominal	6.0
MIMO IEEE 802.11ac (5.8 GHz)	Maximum	8.0
	Nominal	7.5
Bluetooth	Maximum	10.5
	Nominal	10.0
Bluetooth LE	Maximum	7.0
	Nominal	6.5

With Power Backoff (Body at 0mm):


Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	25.0	25.0	23.5	22.0	20.5	21.5	20.5	19.5	18.5
	Nominal	24.5	24.5	23.0	21.5	20.0	21.0	20.0	19.0	18.0
GSM/GPRS/EDGE 1900	Maximum	20.5	20.5	17.5	16.0	15.0	19.0	16.0	15.0	14.0
	Nominal	20.0	20.0	17.0	15.5	14.5	18.5	15.5	14.5	13.5

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA Rel. 99	3GPP HSDPA Rel. 5	3GPP HSUPA Rel. 6
UMTS Band 5 (850 MHz)	Maximum	16.0	16.0	16.0
	Nominal	15.5	15.5	15.5
UMTS Band 2 (1900 MHz)	Maximum	12.5	12.5	12.5
	Nominal	12.0	12.0	12.0

Mode / Band		Modulated Average (dBm)
LTE Band 5 (Cell)	Maximum	16.5
	Nominal	16.0

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 4 of 68

1.4 DUT Antenna Locations



Note: Exact antenna dimensions and separation distances are shown in the Technical Descriptions in the FCC Filing.

Figure 1-1
DUT Antenna Locations

Table 1-1
Body Sides for SAR Testing

Body Sides for SAR Testing						
Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	No	No	Yes	Yes	Yes
UMTS 850	Yes	No	No	Yes	Yes	No
GPRS 1900	Yes	No	No	Yes	Yes	Yes
UMTS 1900	Yes	No	No	Yes	Yes	No
LTE Band 5 (Cell)	Yes	No	No	Yes	Yes	No
2.4 GHz WLAN	Yes	No	Yes	No	Yes	No
2.4 GHz Bluetooth	Yes	No	Yes	No	Yes	No

Note: Per FCC KDB 616217 D04v01r01, Particular DUT edges were not required to be evaluated for SAR based on the SAR exclusion threshold in KDB 447498 D01v05r01. Although GPRS 1900 left edge testing was not required based on the SAR exclusion, it was additionally tested.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 5 of 68

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D05v01, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-2 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another. This device supports MIMO Tx for WLAN 802.11n/ac. Each WLAN antenna can transmit independently or together when operating with MIMO.




Figure 1-2
Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v05 3) procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body	Notes
1	GSM voice + 2.4 GHz Wi-Fi	Yes	Yes	
2	GSM voice + 5 GHz Wi-Fi	Yes	Yes	
3	GSM voice + 2.4 GHz Bluetooth	N/A	Yes	
4	UMTS + 2.4 GHz Wi-Fi	Yes	Yes	
5	UMTS + 5 GHz Wi-Fi	Yes	Yes	
6	UMTS + 2.4 GHz Bluetooth	N/A	Yes	
7	LTE + 2.4 GHz Wi-Fi	Yes	Yes	
8	LTE + 5.8 GHz Wi-Fi	N/A	Yes	WIFI Direct
9	LTE + 2.4 GHz Bluetooth	N/A	Yes	
10	GPRS/EDGE + 2.4 GHz Wi-Fi	N/A	Yes	
11	GPRS/EDGE + 5.8 GHz Wi-Fi	N/A	Yes	WIFI Direct
12	GPRS/EDGE + 2.4 GHz Bluetooth	N/A	Yes	

Notes:

- When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPDCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
- Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
- Per FCC KDB 616217 D04 4.3, when voice mode is limited to speaker mode or headset operations only for body operations, additional SAR testing for tablet voice use is not required. Therefore, voice standalone and simultaneous combinations are not evaluated for body configurations. Corresponding data modes are used for summation with Bluetooth when applicable.
- GSM/GPRS, UMTS and LTE share the same antenna and cannot transmit simultaneously.
- This device supports 2x2 MIMO Tx for WLAN 802.11n/ac. Each WLAN antenna can transmit independently or together when operating with MIMO.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 6 of 68

1.6 SAR Test Exclusions Applied

(A) WIFI/BT

Per FCC KDB 447498 D01v05, the SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, Bluetooth LE SAR was not required; $[(5/5) * \sqrt{2.440}] = 1.6 < 3.0$. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

Based on the maximum conducted power of 5GHz WLAN (rounded to the nearest mW) and the antenna to user separation distance, 5GHz WLAN SAR was not required; $[(6/5) * \sqrt{5.825}] = 2.9 < 3.0$. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

This device supports 40 MHz Bandwidths for IEEE 802.11n for 5 GHz WIFI only.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) No new 5 GHz channels

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v02.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02.

1.7 Guidance Applied

- IEEE 1528-2003
- FCC KDB Publication 941225 D01-D06 (2G/3G/4G)
- FCC KDB Publication 248227 D01v01r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v05 (General SAR Guidance)
- FCC KDB Publication 616217 D04v01 (Tablet SAR Consideration)
- FCC KDB Publication 447498 (SAR Measurements up to 6 GHz)
- October 2013 TCB Workshop Notes (GPRS/EDGE)

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 7 of 68

1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

	Head Serial Number	Body Serial Number - Reduced power	Body Serial Number - Max power
GSM/GPRS/EDGE 850	0206-1	2305-2	2305-1
UMTS 850	0206-1	0206-3	2305-1
GSM/GPRS/EDGE 1900	0206-1	0206-3	0206-1
UMTS 1900	2305-1	0206-3	2305-1
LTE Band 5 (Cell)	0206-1	0206-3	0206-2
2.4 GHz WLAN	0410-02	-	1004-1
2.4 GHz BT	-	-	1004-1

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 8 of 68

2 LTE INFORMATION

LTE Information			
FCC ID	A3LSMT705Y		
Form Factor	Portable Tablet		
Frequency Range of each LTE transmission band	LTE Band 5 (Cell) (824.7 - 848.3 MHz)		
Channel Bandwidths	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
Channel Numbers and Frequencies (MHz)	Low	Mid	High
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)	836.5 (20525)	844 (20600)
UE Category	3		
Modulations Supported in UL	QPSK, 16QAM		
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3~6.2.5? (manufacturer attestation to be provided)	YES		
A-MPR (Additional MPR) disabled for SAR Testing?	YES		

FCC ID: A3LSMT705Y		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet	Page 9 of 68	

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 10 of 68

4

DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01*

Frequency	Maximum Area Scan Resolution (mm) (Δx_{area} , Δy_{area})	Maximum Zoom Scan Resolution (mm) (Δx_{zoom} , Δy_{zoom})	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
				$\Delta z_{zoom}(n)$	$\Delta z_{zoom}(1)^*$	
≤2 GHz	≤15	≤8	≤5	≤4	≤1.5* $\Delta z_{zoom}(n-1)$	≥30
2-3 GHz	≤12	≤5	≤5	≤4	≤1.5* $\Delta z_{zoom}(n-1)$	≥30
3-4 GHz	≤12	≤5	≤4	≤3	≤1.5* $\Delta z_{zoom}(n-1)$	≥28
4-5 GHz	≤10	≤4	≤3	≤2.5	≤1.5* $\Delta z_{zoom}(n-1)$	≥25
5-6 GHz	≤10	≤4	≤2	≤2	≤1.5* $\Delta z_{zoom}(n-1)$	≥22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 11 of 68

5

DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 12 of 68

6

TEST CONFIGURATION POSITIONS FOR HANDSETS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 13 of 68




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Testing for Tablet per KDB Publication 616217 D04v01

This device can be used also in full sized tablet exposure conditions, due to its size. Per FCC KDB 616217, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR Exclusion Threshold in KDB 447498 D01v05 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

6.5 Additional Test Positions due to Proximity Sensor Considerations

This device uses a proximity sensor to reduce voice and data powers in tablet-device use conditions.

While the device's antenna is within a certain distance of the user, the proximity sensor activates and reduces the maximum output power allowed. However, the sensor is not active when the device is moved beyond the sensor triggering distance and the maximum output power is no longer limited. Therefore, an additional exposure condition is needed in the vicinity of the triggering distance to ensure SAR is compliant when the device is allowed to operate at a non-reduced output power level.

FCC KDB 616217 D04 Section 6 was used as a guideline for selecting SAR test distances for this device at these additional exposure conditions. Since the proximity sensor activation distance for the back side of the device is 16 mm, a conservative distance of 15 mm was tested for SAR on the back side at maximum power. Since the proximity sensor activation distance for the bottom edge of the device is 14 mm, a conservative distance of 13 mm was tested for SAR on the bottom edge at maximum power. Since the proximity sensor activation distance for the right edge of the device is 10 mm, a conservative distance of 9 mm was tested for SAR on the right edge at maximum power. Sensor triggering distance summary data is included in Appendix G.

The sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the sensor entirely covers the antenna.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 14 of 68

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 15 of 68

Power measurements were performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v05, When SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r02.

8.2 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01 "SAR Measurement Procedures for 3G Devices" v02, October 2007.

The device was placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test were evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device was tested throughout the SAR test at maximum output power, the SAR measurement system measures a "point SAR" at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviated by more than 5%, the SAR test and drift measurements were repeated.

8.3 SAR Measurement Conditions for UMTS

8.3.1 Output Power Verification

Maximum output power is measured on the High, Middle and Low channels for each applicable transmission band according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all "1s".

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121 (release 5), using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

8.3.2 Head SAR Measurements for Handsets

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all "1s". SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than 0.25 dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4 kbps SRB (signaling radio bearer) using the exposure configuration that resulted in the highest SAR for that RF channel in the 12.2 kbps RMC mode.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 16 of 68

8.3.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all "1s".

8.3.4 Procedures Used to Establish RF Signal for SAR HSDPA Data Devices

The following procedures are applicable to HSDPA data devices operating under 3GPP Release 5. Body exposure conditions are typically applicable to these devices, including handsets and data modems operating in various electronic devices. HSDPA operates in conjunction with UMTS and requires an active DPCCCH. The default test configuration is to measure SAR in UMTS without HSDPA, with an established radio link between the DUT and a communication test set with 12.2 kbps RMC mode configured in Test Loop Mode 1; and tested with HSDPA with FRC and a 12.2 kbps RMC using the highest SAR configuration in UMTS. SAR is selectively confirmed for other physical channel configurations according to output power, exposure conditions and device operating capabilities. Maximum output power is verified according to 3GPP TS 23.121 (Release 5) and SAR must be measured according to these maximum output conditions.

Sub-Test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$.
Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 8$ ($A_{hs} = 30/15$) with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 7$ ($A_{hs} = 24/15$) with $\beta_{hs} = 24/15 * \beta_c$.
Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Figure 8-1
Table C.10.1.4 of TS 234.121-1

8.3.5 SAR Measurements for HSUPA Data Devices

SAR for body exposure configurations are measured according to the 'Body SAR Measurements' procedures in the 'WCDMA Handsets' section of the KDB 941225 D01 FCC 3G document. In addition, Body SAR is also measured for HSPA when the maximum average output of each RF channel with HSPA active is at least ¼ dB higher of that measured without HSPA in 12.2 kbps RMC mode or the maximum SAR for 12.2 kbps RMC is above 75% of the SAR limit. Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 with power control algorithm 2, according to the highest body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP is applicable for head exposure, SAR is not required when the maximum output of each RF channel with HSPA is less than ¼ dB higher than that measured using 12.2 kbps RMC; otherwise, the same HSPA configuration used for body measurements should be used to test for head exposure.

Due to inner loop power control requirements in HSPA, a commercial communication test set should be used for the output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and EDCH configurations for HSPA should be configured according to the β values indicated below as well as other applicable procedures described in the 'WCDMA Handset' and 'Release 5 HSDPA Data Devices' sections of the FCC 3G document.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 17 of 68

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{15} (1)	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed} : 47/15 β_{ed} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{15} = \beta_{15}/\beta_c = 30/15 \Leftrightarrow \beta_{15} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{15}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: β_{ed} can not be set directly; it is set by Absolute Grant Value.

8.4 SAR Measurement Conditions for LTE

LTE modes were tested according to FCC KDB 941225 D05v02 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 was used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.4.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.4.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.4.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.4.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r01:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.

FCC ID: A3LSMT705Y	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 18 of 68

- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to ½ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is <1.45 W/kg.

8.5 SAR Testing with 802.11 Transmitters

Normal network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g/n /ac transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v01r02 for more details.

8.5.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

8.5.2 Frequency Channel Configurations [24]

For 2.4 GHz, the highest average RF output power channel between the low, mid and high channel at the lowest data rate was selected for SAR evaluation in 802.11b mode. 802.11g/n modes and higher data rates for 802.11b were additionally evaluated for SAR if the output power of the respective mode was 0.25 dB or higher than the powers of the SAR configurations tested in the 802.11b mode.

If the maximum extrapolated peak SAR of the zoom scan for the highest output channel was less than 1.6 W/kg and if the 1g averaged SAR was less than 0.8 W/kg, SAR testing was not required for the other test channels in the band.

8.5.3 MIMO SAR considerations

Per KDB 248227, SAR for MIMO was measured with both antennas transmitting simultaneously and was evaluated independently of SISO operation. For 2.4 GHz MIMO, 802.11n was evaluated. 5 GHz WLAN were excluded per FCC KDB 447498 D01v05.

FCC ID: A3LSMT705Y		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 19 of 68

9 RF CONDUCTED POWERS

9.1 GSM Conducted Powers

Table 9-1
Maximum GSM/GPRS/EDGE Average RF Conducted Powers

		Maximum Burst-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	32.57	32.49	30.86	29.42	27.98	27.42	25.93	24.27	22.75
	190	32.58	32.47	30.91	29.45	27.99	27.26	25.83	24.13	22.63
	251	32.64	32.56	31.00	29.49	28.07	27.10	25.67	23.97	22.47
GSM 1900	512	28.63	28.56	28.03	27.01	25.58	26.18	24.71	23.29	21.75
	661	28.53	28.47	27.96	26.96	25.50	26.44	24.92	23.53	22.00
	810	28.64	28.59	28.02	27.07	25.61	26.51	25.05	23.61	22.04
		Calculated Maximum Frame-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	23.54	23.46	24.84	25.16	24.97	18.39	19.91	20.01	19.74
	190	23.55	23.44	24.89	25.19	24.98	18.23	19.81	19.87	19.62
	251	23.61	23.53	24.98	25.23	25.06	18.07	19.65	19.71	19.46
GSM 1900	512	19.60	19.53	22.01	22.75	22.57	17.15	18.69	19.03	18.74
	661	19.50	19.44	21.94	22.70	22.49	17.41	18.90	19.27	18.99
	810	19.61	19.56	22.00	22.81	22.60	17.48	19.03	19.35	19.03
GSM 850	Frame	23.47	23.47	24.98	25.24	24.99	17.97	19.48	19.74	19.49
GSM 1900	Avg.Targets:	19.47	19.47	21.98	22.74	22.49	17.47	18.98	19.24	18.99

Table 9-2
Reduced GSM/GPRS/EDGE Average RF Conducted Powers
Representing Body at 0 mm

		Maximum Burst-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	24.37	24.35	22.80	21.33	19.84	20.82	19.92	18.77	17.82
	190	24.40	24.37	22.87	21.37	19.86	20.68	19.67	18.64	17.70
	251	24.35	24.29	22.81	21.32	19.83	20.52	19.45	18.56	17.44
GSM 1900	512	19.95	19.95	16.92	15.46	14.43	18.52	15.51	14.52	13.46
	661	20.01	19.94	16.95	15.48	14.41	18.53	15.40	14.48	13.36
	810	20.10	20.08	17.05	15.62	14.54	18.42	15.39	14.43	13.25

FCC ID: A3LSMT705Y		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 20 of 68

		Calculated Maximum Frame-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	15.34	15.32	16.78	17.07	16.83	11.79	13.90	14.51	14.81
	190	15.37	15.34	16.85	17.11	16.85	11.65	13.65	14.38	14.69
	251	15.32	15.26	16.79	17.06	16.82	11.49	13.43	14.30	14.43
GSM 1900	512	10.92	10.92	10.90	11.20	11.42	9.49	9.49	10.26	10.45
	661	10.98	10.91	10.93	11.22	11.40	9.50	9.38	10.22	10.35
	810	11.07	11.05	11.03	11.36	11.53	9.39	9.37	10.17	10.24
GSM 850	Frame Avg.Targets:	15.47	15.47	16.98	17.24	16.99	11.97	13.98	14.74	14.99
GSM 1900		10.97	10.97	10.98	11.24	11.49	9.47	9.48	10.24	10.49

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- Per October 2013 TCB Workshop Notes, the source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for body SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 33 (Max 4 Tx uplink slots)
EDGE Multislot class: 33 (Max 4 Tx uplink slots)
DTM Multislot Class: N/A




Figure 9-1
Power Measurement Setup

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 21 of 68

9.2 UMTS Conducted Powers

Table 9-3
Maximum UMTS Average RF Conducted Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	22.79	22.78	22.77	23.05	23.11	23.25	-
99		12.2 kbps AMR	22.50	22.54	22.53	23.04	23.08	23.23	-
6	HSDPA	Subtest 1	22.77	22.83	22.81	23.22	23.29	23.35	0
6		Subtest 2	22.55	22.58	22.56	23.28	23.35	23.36	0
6		Subtest 3	22.30	22.42	22.28	23.09	23.13	23.20	0.5
6		Subtest 4	22.03	22.08	22.07	22.84	22.90	22.99	0.5
6	HSUPA	Subtest 1	22.53	22.55	22.56	22.25	22.30	22.46	0
6		Subtest 2	20.78	20.82	20.79	21.05	21.41	21.63	2
6		Subtest 3	21.55	21.58	21.55	21.92	22.02	22.21	1
6		Subtest 4	20.85	20.84	20.80	21.65	21.49	21.82	2
6		Subtest 5	22.51	22.53	22.80	22.94	22.96	22.93	0

Table 9-4
Reduced UMTS Average RF Conducted Powers
Representing Body at 0 mm

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	15.84	15.87	15.85	12.17	12.18	12.14	-
99		12.2 kbps AMR	15.83	15.84	15.84	11.91	11.86	11.90	-
6	HSDPA	Subtest 1	15.68	15.77	15.74	12.28	12.25	12.20	0
6		Subtest 2	15.65	15.74	15.70	12.31	12.24	12.21	0
6		Subtest 3	15.70	15.81	15.71	12.27	12.19	12.12	0.5
6		Subtest 4	15.67	15.72	15.74	12.22	12.24	12.17	0.5
6	HSUPA	Subtest 1	14.77	14.79	14.83	11.26	11.31	11.33	0
6		Subtest 2	15.16	15.28	15.26	11.72	11.74	11.79	2
6		Subtest 3	14.80	14.90	14.89	11.34	11.35	11.37	1
6		Subtest 4	14.96	15.00	15.02	11.48	11.40	11.47	2
6		Subtest 5	15.73	15.75	15.72	11.93	11.92	11.94	0

UMTS SAR was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v02. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.

This device does not support DC-HSDPA.

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 1 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.




Figure 9-2
Power Measurement Setup

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 22 of 68

9.3 LTE Conducted Powers

9.3.1 LTE Band 5 (Cell)

Table 9-5
Maximum LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	836.5	20525	10	QPSK	1	0	22.36	0	0
	836.5	20525	10	QPSK	1	25	22.51	0	0
	836.5	20525	10	QPSK	1	49	22.18	0	0
	836.5	20525	10	QPSK	25	0	21.41	0-1	1
	836.5	20525	10	QPSK	25	12	21.35	0-1	1
	836.5	20525	10	QPSK	25	25	21.33	0-1	1
	836.5	20525	10	QPSK	50	0	21.38	0-1	1
	836.5	20525	10	16QAM	1	0	21.65	0-1	1
	836.5	20525	10	16QAM	1	25	21.66	0-1	1
	836.5	20525	10	16QAM	1	49	21.45	0-1	1
	836.5	20525	10	16QAM	25	0	20.41	0-2	2
	836.5	20525	10	16QAM	25	12	20.37	0-2	2
	836.5	20525	10	16QAM	25	25	20.32	0-2	2
	836.5	20525	10	16QAM	50	0	20.38	0-2	2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-6
Reduced LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth
Representing Body at 0 mm

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	836.5	20525	10	QPSK	1	0	15.51	0	0
	836.5	20525	10	QPSK	1	25	15.61	0	0
	836.5	20525	10	QPSK	1	49	15.53	0	0
	836.5	20525	10	QPSK	25	0	14.56	0-1	1
	836.5	20525	10	QPSK	25	12	14.54	0-1	1
	836.5	20525	10	QPSK	25	25	14.50	0-1	1
	836.5	20525	10	QPSK	50	0	14.53	0-1	1
	836.5	20525	10	16QAM	1	0	14.80	0-1	1
	836.5	20525	10	16QAM	1	25	14.83	0-1	1
	836.5	20525	10	16QAM	1	49	14.72	0-1	1
	836.5	20525	10	16QAM	25	0	13.71	0-2	2
	836.5	20525	10	16QAM	25	12	13.65	0-2	2
	836.5	20525	10	16QAM	25	25	13.59	0-2	2
	836.5	20525	10	16QAM	50	0	13.67	0-2	2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 23 of 68

Table 9-7
Maximum LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	826.5	20425	5	QPSK	1	0	22.59	0	0
	826.5	20425	5	QPSK	1	12	22.64	0	0
	826.5	20425	5	QPSK	1	24	22.52	0	0
	826.5	20425	5	QPSK	12	0	21.47	0-1	1
	826.5	20425	5	QPSK	12	6	21.45	0-1	1
	826.5	20425	5	QPSK	12	13	21.41	0-1	1
	826.5	20425	5	QPSK	25	0	21.43	0-1	1
	826.5	20425	5	16-QAM	1	0	21.71	0-1	1
	826.5	20425	5	16-QAM	1	12	21.76	0-1	1
	826.5	20425	5	16-QAM	1	24	21.66	0-1	1
	826.5	20425	5	16-QAM	12	0	20.49	0-2	2
	826.5	20425	5	16-QAM	12	6	20.50	0-2	2
Mid	826.5	20425	5	16-QAM	12	13	20.42	0-2	2
	826.5	20425	5	16-QAM	25	0	20.42	0-2	2
	836.5	20525	5	QPSK	1	0	22.59	0	0
	836.5	20525	5	QPSK	1	12	22.54	0	0
	836.5	20525	5	QPSK	1	24	22.47	0	0
	836.5	20525	5	QPSK	12	0	21.42	0-1	1
	836.5	20525	5	QPSK	12	6	21.40	0-1	1
	836.5	20525	5	QPSK	12	13	21.36	0-1	1
	836.5	20525	5	QPSK	25	0	21.36	0-1	1
	836.5	20525	5	16-QAM	1	0	21.68	0-1	1
	836.5	20525	5	16-QAM	1	12	21.67	0-1	1
	836.5	20525	5	16-QAM	1	24	21.56	0-1	1
High	846.5	20625	5	16-QAM	12	0	20.44	0-2	2
	846.5	20625	5	16-QAM	12	6	20.42	0-2	2
	846.5	20625	5	16-QAM	12	13	20.36	0-2	2
	846.5	20625	5	16-QAM	25	0	20.36	0-2	2
	846.5	20625	5	QPSK	1	0	22.44	0	0
	846.5	20625	5	QPSK	1	12	22.40	0	0
	846.5	20625	5	QPSK	1	24	22.38	0	0
	846.5	20625	5	QPSK	12	0	21.30	0-1	1
	846.5	20625	5	QPSK	12	6	21.25	0-1	1
	846.5	20625	5	QPSK	12	13	21.21	0-1	1
	846.5	20625	5	QPSK	25	0	21.26	0-1	1
	846.5	20625	5	16-QAM	1	0	21.62	0-1	1
	846.5	20625	5	16-QAM	1	12	21.58	0-1	1
	846.5	20625	5	16-QAM	1	24	21.52	0-1	1
	846.5	20625	5	16-QAM	12	0	20.33	0-2	2
	846.5	20625	5	16-QAM	12	6	20.28	0-2	2
	846.5	20625	5	16-QAM	12	13	20.24	0-2	2
	846.5	20625	5	16-QAM	25	0	20.26	0-2	2

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 24 of 68

Table 9-8
Reduced LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth
Representing Body at 0 mm

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	826.5	20425	5	QPSK	1	0	15.91	0	0
	826.5	20425	5	QPSK	1	12	15.87	0	0
	826.5	20425	5	QPSK	1	24	15.82	0	0
	826.5	20425	5	QPSK	12	0	14.87	0-1	1
	826.5	20425	5	QPSK	12	6	14.83	0-1	1
	826.5	20425	5	QPSK	12	13	14.79	0-1	1
	826.5	20425	5	QPSK	25	0	14.83	0-1	1
	826.5	20425	5	16-QAM	1	0	15.18	0-1	1
	826.5	20425	5	16-QAM	1	12	15.16	0-1	1
	826.5	20425	5	16-QAM	1	24	15.09	0-1	1
	826.5	20425	5	16-QAM	12	0	13.95	0-2	2
	826.5	20425	5	16-QAM	12	6	13.92	0-2	2
Mid	826.5	20425	5	16-QAM	12	13	13.84	0-2	2
	826.5	20425	5	16-QAM	25	0	13.88	0-2	2
	836.5	20525	5	QPSK	1	0	15.70	0	0
	836.5	20525	5	QPSK	1	12	15.67	0	0
	836.5	20525	5	QPSK	1	24	15.58	0	0
	836.5	20525	5	QPSK	12	0	14.66	0-1	1
	836.5	20525	5	QPSK	12	6	14.65	0-1	1
	836.5	20525	5	QPSK	12	13	14.61	0-1	1
	836.5	20525	5	QPSK	25	0	14.63	0-1	1
	836.5	20525	5	16-QAM	1	0	14.98	0-1	1
	836.5	20525	5	16-QAM	1	12	14.97	0-1	1
	836.5	20525	5	16-QAM	1	24	14.87	0-1	1
High	836.5	20525	5	16-QAM	12	0	13.74	0-2	2
	836.5	20525	5	16-QAM	12	6	13.71	0-2	2
	836.5	20525	5	16-QAM	12	13	13.66	0-2	2
	836.5	20525	5	16-QAM	25	0	13.68	0-2	2
	846.5	20625	5	QPSK	1	0	15.65	0	0
	846.5	20625	5	QPSK	1	12	15.63	0	0
	846.5	20625	5	QPSK	1	24	15.60	0	0
	846.5	20625	5	QPSK	12	0	14.61	0-1	1
	846.5	20625	5	QPSK	12	6	14.57	0-1	1
	846.5	20625	5	QPSK	12	13	14.56	0-1	1
	846.5	20625	5	QPSK	25	0	14.52	0-1	1
	846.5	20625	5	16-QAM	1	0	14.84	0-1	1
	846.5	20625	5	16-QAM	1	12	14.94	0-1	1
	846.5	20625	5	16-QAM	1	24	14.82	0-1	1
	846.5	20625	5	16-QAM	12	0	13.65	0-2	2
	846.5	20625	5	16-QAM	12	6	13.63	0-2	2
	846.5	20625	5	16-QAM	12	13	13.60	0-2	2
	846.5	20625	5	16-QAM	25	0	13.64	0-2	2

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet	Page 25 of 68	

Table 9-9
Maximum LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
825.5	20415	3	QPSK	1	0	22.47	0	0
825.5	20415	3	QPSK	1	7	22.50	0	0
825.5	20415	3	QPSK	1	14	22.45	0	0
825.5	20415	3	QPSK	8	0	21.40	0-1	1
825.5	20415	3	QPSK	8	4	21.38	0-1	1
825.5	20415	3	QPSK	8	7	21.39	0-1	1
825.5	20415	3	QPSK	15	0	21.39	0-1	1
825.5	20415	3	16-QAM	1	0	21.55	0-1	1
825.5	20415	3	16-QAM	1	7	21.66	0-1	1
825.5	20415	3	16-QAM	1	14	21.58	0-1	1
825.5	20415	3	16-QAM	8	0	20.48	0-2	2
825.5	20415	3	16-QAM	8	4	20.47	0-2	2
825.5	20415	3	16-QAM	8	7	20.48	0-2	2
825.5	20415	3	16-QAM	15	0	20.44	0-2	2
836.5	20525	3	QPSK	1	0	22.37	0	0
836.5	20525	3	QPSK	1	7	22.36	0	0
836.5	20525	3	QPSK	1	14	22.29	0	0
836.5	20525	3	QPSK	8	0	21.26	0-1	1
836.5	20525	3	QPSK	8	4	21.24	0-1	1
836.5	20525	3	QPSK	8	7	21.23	0-1	1
836.5	20525	3	QPSK	15	0	21.26	0-1	1
836.5	20525	3	16-QAM	1	0	21.45	0-1	1
836.5	20525	3	16-QAM	1	7	21.50	0-1	1
836.5	20525	3	16-QAM	1	14	21.41	0-1	1
836.5	20525	3	16-QAM	8	0	20.37	0-2	2
836.5	20525	3	16-QAM	8	4	20.34	0-2	2
836.5	20525	3	16-QAM	8	7	20.33	0-2	2
836.5	20525	3	16-QAM	15	0	20.32	0-2	2
847.5	20635	3	QPSK	1	0	22.18	0	0
847.5	20635	3	QPSK	1	7	22.17	0	0
847.5	20635	3	QPSK	1	14	22.20	0	0
847.5	20635	3	QPSK	8	0	21.14	0-1	1
847.5	20635	3	QPSK	8	4	21.12	0-1	1
847.5	20635	3	QPSK	8	7	21.11	0-1	1
847.5	20635	3	QPSK	15	0	21.14	0-1	1
847.5	20635	3	16-QAM	1	0	21.34	0-1	1
847.5	20635	3	16-QAM	1	7	21.43	0-1	1
847.5	20635	3	16-QAM	1	14	21.30	0-1	1
847.5	20635	3	16-QAM	8	0	20.27	0-2	2
847.5	20635	3	16-QAM	8	4	20.23	0-2	2
847.5	20635	3	16-QAM	8	7	20.25	0-2	2
847.5	20635	3	16-QAM	15	0	20.22	0-2	2

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet	Page 26 of 68	

Table 9-10
Reduced LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth
Representing Body at 0 mm

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	825.5	20415	3	QPSK	1	0	15.85	0	0
	825.5	20415	3	QPSK	1	7	15.84	0	0
	825.5	20415	3	QPSK	1	14	15.79	0	0
	825.5	20415	3	QPSK	8	0	14.85	0-1	1
	825.5	20415	3	QPSK	8	4	14.84	0-1	1
	825.5	20415	3	QPSK	8	7	14.83	0-1	1
	825.5	20415	3	QPSK	15	0	14.85	0-1	1
	825.5	20415	3	16-QAM	1	0	15.04	0-1	1
	825.5	20415	3	16-QAM	1	7	15.09	0-1	1
	825.5	20415	3	16-QAM	1	14	15.02	0-1	1
	825.5	20415	3	16-QAM	8	0	13.99	0-2	2
	825.5	20415	3	16-QAM	8	4	13.97	0-2	2
Mid	825.5	20415	3	16-QAM	8	7	13.98	0-2	2
	825.5	20415	3	16-QAM	15	0	13.94	0-2	2
	836.5	20525	3	QPSK	1	0	15.70	0	0
	836.5	20525	3	QPSK	1	7	15.69	0	0
	836.5	20525	3	QPSK	1	14	15.62	0	0
	836.5	20525	3	QPSK	8	0	14.70	0-1	1
	836.5	20525	3	QPSK	8	4	14.67	0-1	1
	836.5	20525	3	QPSK	8	7	14.69	0-1	1
	836.5	20525	3	QPSK	15	0	14.70	0-1	1
	836.5	20525	3	16-QAM	1	0	14.89	0-1	1
	836.5	20525	3	16-QAM	1	7	14.95	0-1	1
	836.5	20525	3	16-QAM	1	14	14.87	0-1	1
High	836.5	20525	3	16-QAM	8	0	13.83	0-2	2
	836.5	20525	3	16-QAM	8	4	13.80	0-2	2
	836.5	20525	3	16-QAM	8	7	13.81	0-2	2
	836.5	20525	3	16-QAM	15	0	13.79	0-2	2
	847.5	20635	3	QPSK	1	0	15.66	0	0
	847.5	20635	3	QPSK	1	7	15.64	0	0
	847.5	20635	3	QPSK	1	14	15.63	0	0
	847.5	20635	3	QPSK	8	0	14.65	0-1	1
	847.5	20635	3	QPSK	8	4	14.63	0-1	1
	847.5	20635	3	QPSK	8	7	14.62	0-1	1
	847.5	20635	3	QPSK	15	0	14.65	0-1	1
	847.5	20635	3	16-QAM	1	0	14.86	0-1	1
	847.5	20635	3	16-QAM	1	7	14.90	0-1	1
	847.5	20635	3	16-QAM	1	14	14.84	0-1	1
	847.5	20635	3	16-QAM	8	0	13.80	0-2	2
	847.5	20635	3	16-QAM	8	4	13.76	0-2	2
	847.5	20635	3	16-QAM	8	7	13.78	0-2	2
	847.5	20635	3	16-QAM	15	0	13.74	0-2	2

FCC ID: A3LSMT705Y		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 27 of 68

Table 9-11
Maximum LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	824.7	20407	1.4	QPSK	1	0	22.57	0	0
	824.7	20407	1.4	QPSK	1	2	22.56	0	0
	824.7	20407	1.4	QPSK	1	5	22.56	0	0
	824.7	20407	1.4	QPSK	3	0	22.61	0	0
	824.7	20407	1.4	QPSK	3	2	22.60	0	0
	824.7	20407	1.4	QPSK	3	3	22.62	0	0
	824.7	20407	1.4	QPSK	6	0	21.44	0-1	1
	824.7	20407	1.4	16-QAM	1	0	21.74	0-1	1
	824.7	20407	1.4	16-QAM	1	2	21.74	0-1	1
	824.7	20407	1.4	16-QAM	1	5	21.75	0-1	1
	824.7	20407	1.4	16-QAM	3	0	21.47	0-1	1
	824.7	20407	1.4	16-QAM	3	2	21.45	0-1	1
Mid	824.7	20407	1.4	16-QAM	3	3	21.46	0-1	1
	824.7	20407	1.4	16-QAM	6	0	20.55	0-2	2
	836.5	20525	1.4	QPSK	1	0	22.43	0	0
	836.5	20525	1.4	QPSK	1	2	22.41	0	0
	836.5	20525	1.4	QPSK	1	5	22.42	0	0
	836.5	20525	1.4	QPSK	3	0	22.48	0	0
	836.5	20525	1.4	QPSK	3	2	22.45	0	0
	836.5	20525	1.4	QPSK	3	3	22.46	0	0
	836.5	20525	1.4	QPSK	6	0	21.32	0-1	1
	836.5	20525	1.4	16-QAM	1	0	21.63	0-1	1
	836.5	20525	1.4	16-QAM	1	2	21.64	0-1	1
	836.5	20525	1.4	16-QAM	1	5	21.61	0-1	1
High	836.5	20525	1.4	16-QAM	3	0	21.36	0-1	1
	836.5	20525	1.4	16-QAM	3	2	21.33	0-1	1
	836.5	20525	1.4	16-QAM	3	3	21.35	0-1	1
	836.5	20525	1.4	16-QAM	6	0	20.45	0-2	2
	848.3	20643	1.4	QPSK	1	0	22.38	0	0
	848.3	20643	1.4	QPSK	1	2	22.37	0	0
	848.3	20643	1.4	QPSK	1	5	22.39	0	0
	848.3	20643	1.4	QPSK	3	0	22.43	0	0
	848.3	20643	1.4	QPSK	3	2	22.42	0	0
	848.3	20643	1.4	QPSK	3	3	22.44	0	0
	848.3	20643	1.4	QPSK	6	0	21.26	0-1	1
	848.3	20643	1.4	16-QAM	1	0	21.56	0-1	1
	848.3	20643	1.4	16-QAM	1	2	21.57	0-1	1
	848.3	20643	1.4	16-QAM	1	5	21.54	0-1	1
	848.3	20643	1.4	16-QAM	3	0	21.28	0-1	1
	848.3	20643	1.4	16-QAM	3	2	21.26	0-1	1
	848.3	20643	1.4	16-QAM	3	3	21.27	0-1	1
	848.3	20643	1.4	16-QAM	6	0	20.37	0-2	2

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 28 of 68

Table 9-12
Reduced LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth
Representing Body at 0 mm

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	824.7	20407	1.4	QPSK	1	0	15.96	0	0
	824.7	20407	1.4	QPSK	1	2	15.94	0	0
	824.7	20407	1.4	QPSK	1	5	15.94	0	0
	824.7	20407	1.4	QPSK	3	0	16.00	0	0
	824.7	20407	1.4	QPSK	3	2	15.97	0	0
	824.7	20407	1.4	QPSK	3	3	15.98	0	0
	824.7	20407	1.4	QPSK	6	0	14.89	0-1	1
	824.7	20407	1.4	16-QAM	1	0	15.22	0-1	1
	824.7	20407	1.4	16-QAM	1	2	15.22	0-1	1
	824.7	20407	1.4	16-QAM	1	5	15.18	0-1	1
	824.7	20407	1.4	16-QAM	3	0	14.91	0-1	1
	824.7	20407	1.4	16-QAM	3	2	14.90	0-1	1
Mid	824.7	20407	1.4	16-QAM	3	3	14.93	0-1	1
	824.7	20407	1.4	16-QAM	6	0	14.05	0-2	2
	836.5	20525	1.4	QPSK	1	0	15.76	0	0
	836.5	20525	1.4	QPSK	1	2	15.75	0	0
	836.5	20525	1.4	QPSK	1	5	15.73	0	0
	836.5	20525	1.4	QPSK	3	0	15.81	0	0
	836.5	20525	1.4	QPSK	3	2	15.80	0	0
	836.5	20525	1.4	QPSK	3	3	15.78	0	0
	836.5	20525	1.4	QPSK	6	0	14.74	0-1	1
	836.5	20525	1.4	16-QAM	1	0	15.08	0-1	1
	836.5	20525	1.4	16-QAM	1	2	15.06	0-1	1
	836.5	20525	1.4	16-QAM	1	5	15.05	0-1	1
High	836.5	20525	1.4	16-QAM	3	0	14.77	0-1	1
	836.5	20525	1.4	16-QAM	3	2	14.78	0-1	1
	836.5	20525	1.4	16-QAM	3	3	14.77	0-1	1
	836.5	20525	1.4	16-QAM	6	0	13.88	0-2	2
	848.3	20643	1.4	QPSK	1	0	15.73	0	0
	848.3	20643	1.4	QPSK	1	2	15.72	0	0
	848.3	20643	1.4	QPSK	1	5	15.74	0	0
	848.3	20643	1.4	QPSK	3	0	15.79	0	0
	848.3	20643	1.4	QPSK	3	2	15.77	0	0
	848.3	20643	1.4	QPSK	3	3	15.78	0	0
	848.3	20643	1.4	QPSK	6	0	14.71	0-1	1
	848.3	20643	1.4	16-QAM	1	0	15.03	0-1	1
	848.3	20643	1.4	16-QAM	1	2	15.00	0-1	1
	848.3	20643	1.4	16-QAM	1	5	14.99	0-1	1
	848.3	20643	1.4	16-QAM	3	0	14.71	0-1	1
	848.3	20643	1.4	16-QAM	3	2	14.73	0-1	1
	848.3	20643	1.4	16-QAM	3	3	14.73	0-1	1
	848.3	20643	1.4	16-QAM	6	0	13.85	0-2	2

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 29 of 68

9.4 WLAN Conducted Powers

Table 9-13
IEEE 802.11b Average RF Power

802.11b	Antenna	Mode	Freq [MHz]	Channel	802.11b Conducted Power [dBm]			
					Data Rate [Mbps]			
					1	2	5.5	11
	Antenna 1	802.11b	2412	1*	11.85	11.93	11.93	11.95
		802.11b	2437	6*	12.13	12.27	12.35	12.19
		802.11b	2462	11*	11.79	11.96	11.97	11.99
	Antenna 2	802.11b	2412	1*	11.88	12.10	12.11	12.12
		802.11b	2437	6*	12.35	12.44	12.41	12.42
		802.11b	2462	11*	11.30	11.68	11.64	11.66

Table 9-14
IEEE 802.11g Average RF Power

802.11g	Antenna	Mode	Freq [MHz]	Channel	802.11g Conducted Power [dBm]							
					Data Rate [Mbps]							
					6	9	12	18	24	36	48	54
	Antenna 1	802.11g	2412	1	11.12	11.12	11.13	11.12	11.39	11.33	11.44	11.25
		802.11g	2437	6	11.45	11.35	11.40	11.35	11.45	11.48	11.41	11.40
		802.11g	2462	11	11.29	11.27	11.25	11.26	11.38	11.45	11.46	11.40
	Antenna 2	802.11g	2412	1	10.33	10.29	10.34	10.37	10.61	10.61	10.51	10.60
		802.11g	2437	6	11.05	11.15	10.97	11.11	11.27	11.28	11.22	11.28
		802.11g	2462	11	10.05	10.08	10.08	10.11	10.34	10.36	10.15	10.29

Table 9-15
IEEE 802.11n Average RF Power

802.11n (2.4GHz)	Antenna	Mode	Freq [MHz]	Channel	802.11n (2.4GHz) Conducted Power [dBm]							
					Data Rate [Mbps]							
					6.5	13	19.5	26	39	52	58.5	65
	Antenna 1	802.11n	2412	1	10.22	10.20	10.19	10.44	10.49	10.39	10.39	10.46
		802.11n	2437	6	10.46	10.48	10.48	10.44	10.42	10.41	10.47	10.45
		802.11n	2462	11	10.25	10.26	10.29	10.39	10.40	10.49	10.43	10.46
	Antenna 2	802.11n	2412	1	9.00	9.01	9.05	9.28	9.26	9.21	9.27	9.30
		802.11n	2437	6	9.59	9.56	9.63	9.84	9.88	9.88	9.80	10.01
		802.11n	2462	11	8.66	8.64	8.60	8.96	8.83	8.91	8.76	8.79

Table 9-16
MIMO IEEE 802.11n Average RF Power

802.11n (2.4GHz)	Antenna	Freq [MHz]	Channel	802.11n (2.4GHz) Conducted Power [dBm]
				Data Rate [Mbps]
				13
	MIMO	2412	1*	10.19
		2437	6*	10.46
		2462	11*	9.95

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 30 of 68

Table 9-17
IEEE 802.11a Average RF Power

802.11a	Antenna	Mode	Freq [MHz]	Channel	802.11a Conducted Power [dBm]							
					Data Rate [Mbps]							
					6	9	12	18	24	36	48	54
Antenna 1	802.11a	5180	36*	7.07	6.86	6.93	6.90	7.28	7.24	7.38	7.35	
	802.11a	5200	40	7.16	6.75	6.78	6.71	7.06	7.11	7.18	7.00	
	802.11a	5220	44	7.15	6.92	6.92	6.95	7.20	7.17	7.28	7.14	
	802.11a	5240	48*	7.04	6.88	6.85	6.88	7.30	7.14	7.30	7.24	
	802.11a	5260	52*	7.21	6.79	6.84	6.90	7.17	7.08	7.19	7.05	
	802.11a	5280	56	7.12	7.03	6.99	7.10	7.39	7.27	7.39	7.17	
	802.11a	5300	60	7.19	7.18	7.18	7.10	7.40	7.39	7.41	7.31	
	802.11a	5320	64*	7.00	6.81	6.79	6.75	7.23	7.07	7.23	7.13	
	802.11a	5500	100	7.31	7.14	7.22	7.23	7.54	7.49	7.64	7.42	
	802.11a	5520	104*	7.24	7.23	7.12	7.33	7.50	7.40	7.49	7.40	
	802.11a	5540	108	7.37	7.21	7.25	7.22	7.62	7.66	7.66	7.56	
	802.11a	5560	112	7.37	7.28	7.27	7.30	7.61	7.56	7.65	7.61	
	802.11a	5580	116*	7.22	7.16	7.18	7.05	7.53	7.44	7.39	7.17	
	802.11a	5600	120	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	802.11a	5620	124	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	802.11a	5640	128	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	802.11a	5660	132	7.20	7.33	7.13	7.06	7.51	7.32	7.54	7.33	
	802.11a	5680	136*	7.28	7.25	7.22	7.30	7.26	7.26	7.53	7.45	
	802.11a	5700	140	7.42	7.18	7.08	6.96	7.41	7.25	7.36	7.21	
	802.11a	5745	149*	7.14	7.00	7.15	7.05	7.24	7.15	7.24	7.04	
	802.11a	5765	153	7.29	7.26	7.19	7.17	7.47	7.23	7.43	7.21	
	802.11a	5785	157*	7.35	7.39	7.39	7.28	7.50	7.42	7.47	7.37	
	802.11a	5805	161	7.17	7.26	7.25	7.10	7.44	7.28	7.38	7.11	
	802.11a	5825	165*	7.05	6.98	7.05	7.05	7.35	7.26	7.25	7.11	
Antenna 2	802.11a	5180	36*	7.38	7.15	7.28	7.10	7.56	7.37	7.31	7.50	
	802.11a	5200	40	7.10	7.03	7.11	7.12	7.33	7.37	7.38	7.54	
	802.11a	5220	44	7.19	7.21	7.17	7.20	7.42	7.35	7.39	7.53	
	802.11a	5240	48*	7.05	7.08	7.06	7.05	7.40	7.20	7.28	7.30	
	802.11a	5260	52*	7.21	7.05	7.00	7.01	7.41	7.36	7.36	7.42	
	802.11a	5280	56	7.01	6.93	6.99	6.95	7.45	7.37	7.34	7.36	
	802.11a	5300	60	7.08	7.08	6.95	7.06	7.35	7.29	7.10	7.27	
	802.11a	5320	64*	7.05	6.96	6.97	6.96	7.30	7.13	7.20	7.30	
	802.11a	5500	100	6.98	7.02	6.98	6.97	7.22	7.31	7.10	7.31	
	802.11a	5520	104*	6.91	6.83	6.77	6.88	7.23	7.21	7.14	7.28	
	802.11a	5540	108	7.55	7.03	6.96	7.02	7.26	7.22	7.13	7.26	
	802.11a	5560	112	7.04	7.08	7.08	7.18	7.30	7.30	7.22	7.34	
	802.11a	5580	116*	6.97	6.78	6.79	6.81	7.11	7.11	7.00	7.24	
	802.11a	5600	120	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	802.11a	5620	124	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	802.11a	5640	128	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	802.11a	5660	132	6.88	6.78	6.95	6.87	7.20	7.17	7.14	7.30	
	802.11a	5680	136*	6.85	6.92	6.95	7.05	7.10	7.13	6.98	7.06	
	802.11a	5700	140	6.99	7.00	6.86	6.99	6.96	6.98	6.93	7.07	
	802.11a	5745	149*	7.22	7.30	7.23	7.25	7.52	7.50	7.54	7.52	
	802.11a	5765	153	7.16	6.88	6.84	6.85	7.22	7.21	7.28	7.32	
	802.11a	5785	157*	7.22	7.09	7.09	7.08	7.43	7.46	7.32	7.44	
	802.11a	5805	161	7.21	7.26	7.23	7.27	7.56	7.50	7.47	7.53	
	802.11a	5825	165*	7.35	7.21	7.20	7.16	7.57	7.44	7.50	7.51	

Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

(*) – indicates default channels per KDB Publication 248227 D01v01r02. When the adjacent channels are higher in power then the default channels, these “required channels” are considered for SAR testing instead of the default channels.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 31 of 68

Table 9-18
IEEE 802.11n Average RF Power – 20 MHz Bandwidth

20MHz 802.11n (5GHz)	Antenna	Mode	Freq [MHz]	Channel	20MHz BW 802.11n (5GHz) Conducted Power [dBm]							
					Data Rate [Mbps]							
					6.5	13	19.5	26	39	52	58.5	65
Antenna 1	802.11n	5180	36	6.95	6.91	6.95	7.13	7.11	7.27	7.32	7.25	
	802.11n	5200	40	6.91	6.74	6.87	7.13	7.11	7.30	7.22	7.23	
	802.11n	5220	44	6.81	6.76	6.76	6.95	7.00	6.99	7.18	7.07	
	802.11n	5240	48	7.07	7.02	7.09	7.35	7.34	7.34	7.30	7.34	
	802.11n	5260	52	6.90	6.90	6.90	7.07	7.15	7.21	7.34	7.33	
	802.11n	5280	56	7.00	7.00	7.04	7.33	7.26	7.33	7.33	7.42	
	802.11n	5300	60	6.94	6.89	6.91	7.12	7.14	7.12	7.31	7.27	
	802.11n	5320	64	6.95	7.02	7.01	7.26	7.26	7.45	7.45	7.43	
	802.11n	5500	100	7.22	7.20	7.29	7.43	7.53	7.61	7.65	7.60	
	802.11n	5520	104	7.11	7.10	7.06	7.33	7.31	7.42	7.42	7.48	
	802.11n	5540	108	6.94	6.77	6.65	6.84	6.92	7.20	7.30	7.23	
	802.11n	5560	112	7.19	7.23	7.20	7.43	7.49	7.52	7.60	7.66	
	802.11n	5580	116	7.12	6.96	7.00	7.43	7.28	7.62	7.47	7.63	
	802.11n	5600	120	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	802.11n	5620	124	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	802.11n	5640	128	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	802.11n	5660	132	7.13	7.10	7.09	7.33	7.32	7.42	7.46	7.34	
	802.11n	5680	136	7.11	7.14	7.16	7.38	7.38	7.56	7.58	7.60	
	802.11n	5700	140	7.19	7.25	7.22	7.25	7.56	7.63	7.60	7.59	
	802.11n	5745	149	7.09	7.09	7.19	7.25	7.31	7.28	7.43	7.37	
	802.11n	5765	153	7.01	6.96	7.00	7.28	7.26	7.19	7.22	7.24	
	802.11n	5785	157	6.94	6.77	6.79	6.88	7.06	6.99	7.02	7.10	
	802.11n	5805	161	6.89	6.79	6.86	7.11	7.11	7.20	7.20	7.14	
	802.11n	5825	165	6.84	7.00	6.84	7.19	7.26	7.31	7.21	7.30	
Antenna 2	802.11n	5180	36	6.91	6.84	6.84	7.08	7.20	7.26	7.33	7.39	
	802.11n	5200	40	7.11	7.31	7.26	7.47	7.43	7.57	7.51	7.42	
	802.11n	5220	44	7.05	7.17	7.21	7.39	7.37	7.55	7.48	7.53	
	802.11n	5240	48	6.85	7.08	6.99	7.14	7.16	7.17	7.21	7.22	
	802.11n	5260	52	6.65	6.83	6.91	7.02	7.11	7.16	7.21	7.18	
	802.11n	5280	56	6.79	6.83	6.85	7.03	7.04	7.00	7.05	7.04	
	802.11n	5300	60	6.88	7.03	6.94	7.14	7.17	7.44	7.35	7.22	
	802.11n	5320	64	6.75	6.76	6.82	6.85	6.87	7.01	6.82	6.98	
	802.11n	5500	100	6.82	6.80	6.84	6.81	6.81	6.92	7.03	7.05	
	802.11n	5520	104	6.75	6.74	6.83	6.82	6.87	7.06	7.03	7.09	
	802.11n	5540	108	6.67	6.74	6.74	6.90	6.91	6.98	7.02	7.07	
	802.11n	5560	112	6.78	6.58	6.75	6.87	6.95	7.06	6.96	7.10	
	802.11n	5580	116	6.65	6.62	6.57	6.83	6.81	6.86	6.87	6.95	
	802.11n	5600	120	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	802.11n	5620	124	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	802.11n	5640	128	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	802.11n	5660	132	6.62	6.52	6.45	6.67	6.57	6.83	6.79	6.81	
	802.11n	5680	136	6.56	6.45	6.51	6.52	6.47	6.68	6.74	6.74	
	802.11n	5700	140	6.50	6.52	6.57	6.47	6.57	6.50	6.56	6.58	
	802.11n	5745	149	6.94	6.93	7.01	7.29	7.13	7.42	7.41	7.40	
	802.11n	5765	153	7.02	7.07	7.17	7.38	7.35	7.52	7.46	7.52	
	802.11n	5785	157	6.95	7.00	6.89	6.98	7.19	7.25	7.29	7.21	
	802.11n	5805	161	6.91	6.90	7.00	7.21	7.29	7.40	7.28	7.28	
	802.11n	5825	165	6.92	6.84	6.90	7.12	7.16	7.35	7.28	7.27	

FCC ID: A3LSMT705Y		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 32 of 68

Table 9-19
MIMO IEEE 802.11n Average RF Power – 20 MHz Bandwidth

20MHz 802.11n (5GHz)	Antenna	Mode	Freq [MHz]	Channel	802.11n (5GHz) Conducted Power [dBm]
					Data Rate [Mbps]
					13
MIMO		802.11n	5180	36*	6.82
		802.11n	5200	40	6.57
		802.11n	5220	44	6.34
		802.11n	5240	48*	6.04
		802.11n	5260	52*	6.02
		802.11n	5280	56	5.76
		802.11n	5300	60	5.57
		802.11n	5320	64*	5.59
		802.11n	5500	100	6.22
		802.11n	5520	104*	6.06
		802.11n	5540	108	6.17
		802.11n	5560	112	6.47
		802.11n	5580	116*	6.38
		802.11n	5600	120	N/A
		802.11n	5620	124	N/A
		802.11n	5640	128	N/A
		802.11n	5660	132	6.73
		802.11n	5680	136*	6.32
		802.11n	5700	140	6.80
		802.11n	5745	149*	7.92
		802.11n	5765	153	7.89
		802.11n	5785	157*	7.88
		802.11n	5805	161	7.90
		802.11n	5825	165*	7.97

Table 9-20
IEEE 802.11n Average RF Power – 40 MHz Bandwidth

40MHz 802.11n (5GHz)	Antenna	Mode	Freq [MHz]	Channel	40MHz BW 802.11n (5GHz) Conducted Power [dBm]							
					Data Rate [Mbps]							
					13.5	27	40.5	54	81	108	121.5	135
Antenna 1		802.11n	5190	38	6.15	6.06	6.30	6.28	6.35	6.35	6.39	6.35
		802.11n	5230	46	6.52	6.51	6.56	6.82	6.80	6.92	6.93	6.89
		802.11n	5270	54	6.39	6.30	6.56	6.58	6.62	6.54	6.53	6.43
		802.11n	5310	62	6.08	6.17	6.16	6.33	6.35	6.35	6.24	6.14
		802.11n	5510	102	6.32	6.28	6.32	6.36	6.41	6.41	6.50	6.49
		802.11n	5550	110	6.21	6.14	6.17	6.27	6.47	6.39	6.37	6.40
		802.11n	5590	118	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
		802.11n	5630	126	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
		802.11n	5670	134	6.40	6.43	6.42	6.55	6.47	6.65	6.64	6.62
		802.11n	5755	151	7.35	7.40	7.39	7.45	7.48	7.54	7.58	7.42
		802.11n	5795	159	7.31	7.36	7.40	7.43	7.50	7.54	7.55	7.55
		802.11n	5190	38	6.06	6.39	6.10	6.33	6.41	6.49	6.52	6.53
		802.11n	5230	46	6.21	6.21	6.13	6.35	6.22	6.38	6.47	6.39
		802.11n	5270	54	6.02	6.14	6.10	6.05	6.05	6.22	6.05	6.18
		802.11n	5310	62	6.05	6.14	6.08	6.22	6.26	6.40	6.44	6.43
		802.11n	5510	102	7.20	7.26	7.12	7.24	7.28	7.21	7.28	7.31
Antenna 2		802.11n	5550	110	7.11	7.12	7.19	7.11	7.23	7.25	7.23	7.28
		802.11n	5590	118	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
		802.11n	5630	126	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
		802.11n	5670	134	7.15	7.22	7.20	7.22	7.27	7.31	7.33	7.30
		802.11n	5755	151	6.05	6.12	6.13	6.10	6.11	6.18	6.40	6.20
		802.11n	5795	159	6.03	6.06	6.01	6.14	6.18	6.27	6.39	6.34

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 33 of 68

Table 9-21
MIMO IEEE 802.11n Average RF Power – 40 MHz Bandwidth

40MHz 802.11n (5GHz)	Antenna	Mode	Freq [MHz]	Channel	40MHz 802.11n (5GHz) Conducted Power [dBm]
					Data Rate [Mbps]
					27
	MIMO	802.11n	5190	38	6.31
		802.11n	5230	46	6.10
		802.11n	5270	54	5.33
		802.11n	5310	62	5.56
		802.11n	5510	102	5.55
		802.11n	5550	110	5.99
		802.11n	5590	118	N/A
		802.11n	5630	126	N/A
		802.11n	5670	134	6.95
		802.11n	5755	151	7.84
		802.11n	5795	159	7.73

Table 9-22
IEEE 802.11ac Average RF Power – 80 MHz Bandwidth

80MHz 802.11ac (5GHz)	Antenna	Mode	Freq [MHz]	Channel	80MHz BW 802.11ac (5GHz) Conducted Power [dBm]									
					Data Rate [Mbps]									
					29.3	58.5	87.8	117	175.5	234	263.3	292.5	351	390
	Antenna 1	802.11ac	5210	42	6.12	6.02	6.03	6.36	6.34	6.21	6.30	6.23	6.04	6.03
		802.11ac	5290	58	6.04	6.01	6.12	6.28	6.25	6.21	6.09	6.22	6.10	6.08
		802.11ac	5530	106	6.24	6.14	6.09	6.43	6.45	6.44	6.39	6.46	6.18	6.15
	Antenna 2	802.11ac	5775	155	6.88	6.66	6.69	7.02	7.05	7.00	7.05	7.11	6.69	7.09
		802.11ac	5210	42	6.25	6.14	6.15	6.22	6.27	6.27	6.18	6.22	6.37	6.35
		802.11ac	5290	58	6.20	6.10	6.19	6.19	6.25	6.18	6.20	6.29	6.34	6.29
		802.11ac	5530	106	6.02	6.14	6.00	6.01	6.08	6.03	6.14	6.11	6.25	6.23
		802.11ac	5775	155	6.22	6.11	6.28	6.33	6.42	6.43	6.34	6.40	6.46	6.39

Table 9-23
MIMO IEEE 802.11ac Average RF Power – 80 MHz Bandwidth

80MHz 802.11ac (5GHz)	Antenna	Mode	Freq [MHz]	Channel	80MHz 802.11ac (5GHz) Conducted Power [dBm]
					Data Rate [Mbps]
					58.5
	MIMO	802.11ac	5210	42	5.53
		802.11ac	5290	58	5.20
		802.11ac	5530	106	5.48
		802.11ac	5775	155	7.14

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 34 of 68

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012/April 2013 FCC/TCB Meeting Notes:

- For SISO 2.4 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11b were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
- For MIMO 2.4 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11n was selected for SAR evaluation.
- 5 GHz WLAN were excluded per FCC KDB 447498 D01v05.
- When the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is <1.6 W/kg and the reported 1g averaged SAR is <0.8 W/kg, SAR testing on other channels is not required. Otherwise, the other default (or corresponding required) test channels were additionally tested using the lowest data rate.
- The individual spectra for each 2x2 MIMO WIFI Antenna were summed mathematically in linear power units for the MIMO output power measurements.
- The bolded data rate and channel above were tested for SAR.




Figure 9-3
Power Measurement Setup for SISO Bandwidths < 50 MHz




Figure 9-4
Power Measurement Setup for SISO Bandwidths > 50 MHz

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 35 of 68

9.5 Bluetooth Conducted Powers

Table 9-24
Bluetooth RF Conducted Powers

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	7.20	5.253
2441	1.0	39	9.61	9.138
2480	1.0	78	8.71	7.431
2402	2.0	0	3.36	2.167
2441	2.0	39	5.97	3.957
2480	2.0	78	5.24	3.342
2402	3.0	0	3.44	2.210
2441	3.0	39	6.02	3.995
2480	3.0	78	5.28	3.372

The bolded data rate and channel above were tested for SAR.




Figure 9-5
Power Measurement Setup

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 36 of 68

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C°)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
06/03/2014	835H	20.5	820	0.910	42.149	0.899	41.578	1.22%	1.37%
			835	0.925	41.941	0.900	41.500	2.78%	1.06%
			850	0.939	41.771	0.916	41.500	2.51%	0.65%
06/03/2014	1900H	22.9	1850	1.397	40.034	1.400	40.000	-0.21%	0.08%
			1880	1.426	39.919	1.400	40.000	1.86%	-0.20%
			1910	1.459	39.793	1.400	40.000	4.21%	-0.52%
06/17/2014	1900H	23.1	1850	1.348	39.999	1.400	40.000	-3.71%	0.00%
			1880	1.383	39.843	1.400	40.000	-1.21%	-0.39%
			1910	1.419	39.776	1.400	40.000	1.36%	-0.56%
04/14/2014	2450H	23.4	2401	1.720	39.335	1.756	39.287	-2.05%	0.12%
			2450	1.773	39.159	1.800	39.200	-1.50%	-0.10%
			2499	1.828	38.982	1.853	39.138	-1.35%	-0.40%
05/29/2014	835B	21.0	820	0.989	54.949	0.969	55.258	2.06%	-0.56%
			835	1.007	54.780	0.970	55.200	3.81%	-0.76%
			850	1.023	54.601	0.988	55.154	3.54%	-1.00%
06/01/2014	835B	23.4	820	0.996	55.067	0.969	55.258	2.79%	-0.35%
			835	1.010	54.930	0.970	55.200	4.12%	-0.49%
			850	1.025	54.768	0.988	55.154	3.74%	-0.70%
06/02/2014	1900B	21.5	1850	1.477	53.220	1.520	53.300	-2.83%	-0.15%
			1880	1.510	53.112	1.520	53.300	-0.66%	-0.35%
			1910	1.543	53.005	1.520	53.300	1.51%	-0.55%
06/19/2014	1900B	21.3	1850	1.449	53.626	1.520	53.300	-4.67%	0.61%
			1880	1.481	53.465	1.520	53.300	-2.57%	0.31%
			1910	1.514	53.360	1.520	53.300	-0.39%	0.11%
04/14/2014	2450B	23.1	2401	1.962	52.784	1.903	52.765	3.10%	0.04%
			2450	2.031	52.620	1.950	52.700	4.15%	-0.15%
			2499	2.097	52.430	2.019	52.638	3.86%	-0.40%
04/21/2014	2450B	22.8	2401	1.968	51.220	1.903	52.765	3.42%	-2.93%
			2450	2.032	50.970	1.950	52.700	4.21%	-3.28%
			2499	2.100	50.831	2.019	52.638	4.01%	-3.43%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSMT705Y		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 37 of 68

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-2
System Verification Results

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
C	835	HEAD	06/03/2014	20.5	20.5	0.100	4d133	3213	0.935	9.620	9.350	-2.81%
C	1900	HEAD	06/03/2014	20.5	21.5	0.100	5d148	3213	3.990	40.700	39.900	-1.97%
K	1900	HEAD	06/17/2014	23.9	23.0	0.100	5d149	3287	3.930	40.400	39.300	-2.72%
K	2450	HEAD	04/14/2014	24.2	23.4	0.100	797	3287	5.450	51.800	54.500	5.21%
C	835	BODY	05/29/2014	22.1	21.0	0.100	4d133	3213	1.000	9.610	10.000	4.06%
I	835	BODY	06/01/2014	23.8	23.3	0.100	4d132	3209	1.000	9.310	10.000	7.41%
B	1900	BODY	06/02/2014	23.0	21.9	0.100	5d148	3288	3.810	39.300	38.100	-3.05%
B	1900	BODY	06/19/2014	23.2	21.3	0.100	5d148	3288	4.070	39.300	40.700	3.56%
G	2450	BODY	04/14/2014	24.4	23.9	0.100	797	3258	4.890	49.400	48.900	-1.01%
G	2450	BODY	04/21/2014	24.3	23.0	0.100	797	3258	4.900	49.400	49.000	-0.81%




Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 38 of 68

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

Table 11-1
GSM 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.0	32.58	0.12	Right	Cheek	0206-1	1:8.3	0.009	1.102	0.010	
836.60	190	GSM 850	GSM	33.0	32.58	0.05	Right	Tilt	0206-1	1:8.3	0.012	1.102	0.013	A1
836.60	190	GSM 850	GSM	33.0	32.58	0.12	Left	Cheek	0206-1	1:8.3	0.006	1.102	0.007	
836.60	190	GSM 850	GSM	33.0	32.58	0.17	Left	Tilt	0206-1	1:8.3	0.010	1.102	0.011	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11-2
UMTS 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	23.0	22.78	0.14	Right	Cheek	0206-1	1:1	0.014	1.052	0.015	
836.60	4183	UMTS 850	RMC	23.0	22.78	0.12	Right	Tilt	0206-1	1:1	0.017	1.052	0.018	A2
836.60	4183	UMTS 850	RMC	23.0	22.78	0.13	Left	Cheek	0206-1	1:1	0.010	1.052	0.011	
836.60	4183	UMTS 850	RMC	23.0	22.78	0.03	Left	Tilt	0206-1	1:1	0.016	1.052	0.017	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11-3
GSM 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Model/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	29.0	28.53	0.17	Right	Cheek	0206-1	1:8.3	0.044	1.114	0.049	A3
1880.00	661	GSM 1900	GSM	29.0	28.53	0.04	Right	Tilt	0206-1	1:8.3	0.023	1.114	0.026	
1880.00	661	GSM 1900	GSM	29.0	28.53	-0.03	Left	Cheek	0206-1	1:8.3	0.033	1.114	0.037	
1880.00	661	GSM 1900	GSM	29.0	28.53	0.09	Left	Tilt	0206-1	1:8.3	0.030	1.114	0.033	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11-4
UMTS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	23.5	23.11	0.00	Right	Cheek	2305-1	1:1	0.207	1.094	0.226	A4
1880.00	9400	UMTS 1900	RMC	23.5	23.11	-0.04	Right	Tilt	2305-1	1:1	0.093	1.094	0.102	
1880.00	9400	UMTS 1900	RMC	23.5	23.11	0.01	Left	Cheek	2305-1	1:1	0.127	1.094	0.139	
1880.00	9400	UMTS 1900	RMC	23.5	23.11	-0.03	Left	Tilt	2305-1	1:1	0.094	1.094	0.103	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: A3LSMT705Y		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 39 of 68

Table 11-5
LTE Band 5 (Cell) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.51	0.01	0	Right	Cheek	QPSK	1	25	0206-1	1:1	0.076	1.119	0.085	A5
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.41	0.06	1	Right	Cheek	QPSK	25	0	0206-1	1:1	0.057	1.146	0.065	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.51	0.02	0	Right	Tilt	QPSK	1	25	0206-1	1:1	0.091	1.119	0.102	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.41	0.03	1	Right	Tilt	QPSK	25	0	0206-1	1:1	0.076	1.146	0.087	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.51	0.01	0	Left	Cheek	QPSK	1	25	0206-1	1:1	0.048	1.119	0.054	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.41	0.07	1	Left	Cheek	QPSK	25	0	0206-1	1:1	0.039	1.146	0.045	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.51	0.05	0	Left	Tilt	QPSK	1	25	0206-1	1:1	0.080	1.119	0.090	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.41	0.03	1	Left	Tilt	QPSK	25	0	0206-1	1:1	0.066	1.146	0.076	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-6
DTS Head SAR

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna #	Device Serial Number	Data Rate (Mbps)	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	
2437	6	IEEE 802.11b	DSSS	12.5	12.13	0.00	Right	Cheek	Antenna 1	0410-02	1	1:1	0.117	1.089	0.127	
2437	6	IEEE 802.11b	DSSS	12.5	12.13	0.03	Right	Tilt	Antenna 1	0410-02	1	1:1	0.116	1.089	0.126	
2437	6	IEEE 802.11b	DSSS	12.5	12.13	0.21	Left	Cheek	Antenna 1	0410-02	1	1:1	0.436	1.089	0.475	
2437	6	IEEE 802.11b	DSSS	12.5	12.13	0.03	Left	Tilt	Antenna 1	0410-02	1	1:1	0.378	1.089	0.412	
2437	6	IEEE 802.11b	DSSS	12.5	12.35	0.20	Right	Cheek	Antenna 2	0410-02	1	1:1	0.032	1.035	0.033	
2437	6	IEEE 802.11b	DSSS	12.5	12.35	0.05	Right	Tilt	Antenna 2	0410-02	1	1:1	0.025	1.035	0.026	
2437	6	IEEE 802.11b	DSSS	12.5	12.35	0.20	Left	Cheek	Antenna 2	0410-02	1	1:1	0.153	1.035	0.158	
2437	6	IEEE 802.11b	DSSS	12.5	12.35	0.21	Left	Tilt	Antenna 2	0410-02	1	1:1	0.169	1.035	0.175	
2437	6	IEEE 802.11n	OFDM	10.5	10.46	0.03	Right	Cheek	MIMO	0410-02	13	1:1	0.129	1.009	0.130	
2437	6	IEEE 802.11n	OFDM	10.5	10.46	0.20	Right	Tilt	MIMO	0410-02	13	1:1	0.123	1.009	0.124	
2437	6	IEEE 802.11n	OFDM	10.5	10.46	0.08	Left	Cheek	MIMO	0410-02	13	1:1	0.449	1.009	0.453	
2437	6	IEEE 802.11n	OFDM	10.5	10.46	0.11	Left	Tilt	MIMO	0410-02	13	1:1	0.467	1.009	0.471	A6
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 40 of 68

11.2 Standalone Body SAR Data

Table 11-7
GPRS/UMTS Body SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	30.0	29.45	0.01	15 mm	2305-1	3	1:2.76	back	0.394	1.135	0.447	
836.60	190	GSM 850	GPRS	30.0	29.45	-0.04	13 mm	2305-1	3	1:2.76	bottom	0.298	1.135	0.338	
836.60	190	GSM 850	GPRS	30.0	29.45	0.02	9 mm	2305-1	3	1:2.76	right	0.207	1.135	0.235	
836.60	190	GSM 850	GPRS	30.0	29.45	0.00	0 mm	2305-1	3	1:2.76	left	0.163	1.135	0.185	
824.20	128	GSM 850	GPRS	22.0	21.33	-0.02	0 mm	2305-2	3	1:2.76	back	0.757	1.167	0.883	
836.60	190	GSM 850	GPRS	22.0	21.37	0.01	0 mm	2305-2	3	1:2.76	back	0.764	1.156	0.883	
848.80	251	GSM 850	GPRS	22.0	21.32	0.03	0 mm	2305-2	3	1:2.76	back	0.793	1.169	0.927	A7
836.60	190	GSM 850	GPRS	22.0	21.37	-0.02	0 mm	2305-2	3	1:2.76	bottom	0.321	1.156	0.371	
836.60	190	GSM 850	GPRS	22.0	21.37	0.02	0 mm	2305-2	3	1:2.76	right	0.149	1.156	0.172	
836.60	4183	UMTS 850	RMC	23.0	22.78	0.02	15 mm	2305-1	N/A	1:1	back	0.403	1.052	0.424	
836.60	4183	UMTS 850	RMC	23.0	22.78	0.05	13 mm	2305-1	N/A	1:1	bottom	0.254	1.052	0.267	
836.60	4183	UMTS 850	RMC	23.0	22.78	0.01	9 mm	2305-1	N/A	1:1	right	0.120	1.052	0.126	
836.60	4183	UMTS 850	RMC	16.0	15.87	-0.02	0 mm	0206-3	N/A	1:1	back	0.432	1.030	0.445	A8
836.60	4183	UMTS 850	RMC	16.0	15.87	-0.14	0 mm	0206-3	N/A	1:1	bottom	0.208	1.030	0.214	
836.60	4183	UMTS 850	RMC	16.0	15.87	-0.11	0 mm	0206-3	N/A	1:1	right	0.322	1.030	0.332	
1880.00	661	GSM 1900	GPRS	27.5	26.96	-0.02	15 mm	0206-1	3	1:2.76	back	0.348	1.132	0.394	
1880.00	661	GSM 1900	GPRS	27.5	26.96	0.11	13 mm	0206-1	3	1:2.76	bottom	0.230	1.132	0.260	
1880.00	661	GSM 1900	GPRS	27.5	26.96	0.08	9 mm	0206-1	3	1:2.76	right	0.180	1.132	0.204	
1880.00	661	GSM 1900	GPRS	27.5	26.96	0.00	0 mm	0206-1	3	1:2.76	left	0.089	1.132	0.101	
1880.00	661	GSM 1900	GPRS	15.0	14.41	-0.19	0 mm	0206-3	4	1:2.076	back	0.484	1.146	0.555	A9
1880.00	661	GSM 1900	GPRS	15.0	14.41	0.03	0 mm	0206-3	4	1:2.076	bottom	0.314	1.146	0.360	
1880.00	661	GSM 1900	GPRS	15.0	14.41	-0.05	0 mm	0206-3	4	1:2.076	right	0.111	1.146	0.127	
1852.40	9262	UMTS 1900	RMC	23.5	23.05	0.02	15 mm	2305-1	N/A	1:1	back	0.756	1.109	0.838	
1880.00	9400	UMTS 1900	RMC	23.5	23.11	0.00	15 mm	2305-1	N/A	1:1	back	0.784	1.094	0.858	
1907.60	9538	UMTS 1900	RMC	23.5	23.25	-0.05	15 mm	2305-1	N/A	1:1	back	0.830	1.059	0.879	A10
1880.00	9400	UMTS 1900	RMC	23.5	23.11	0.04	13 mm	2305-1	N/A	1:1	bottom	0.506	1.094	0.554	
1880.00	9400	UMTS 1900	RMC	23.5	23.11	0.03	9 mm	2305-1	N/A	1:1	right	0.407	1.094	0.445	
1880.00	9400	UMTS 1900	RMC	12.5	12.18	0.00	0 mm	0206-3	N/A	1:1	back	0.568	1.076	0.611	
1880.00	9400	UMTS 1900	RMC	12.5	12.18	0.01	0 mm	0206-3	N/A	1:1	bottom	0.377	1.076	0.406	
1880.00	9400	UMTS 1900	RMC	12.5	12.18	0.11	0 mm	0206-3	N/A	1:1	right	0.130	1.076	0.140	
1907.60	9538	UMTS 1900	RMC	23.5	23.25	0.01	15 mm	2305-1	N/A	1:1	back	0.810	1.059	0.858	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Blue entry represents variability measurement.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 41 of 68

Table 11-8
LTE Band 5 (Cell) Body SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.51	-0.04	0	0206-2	QPSK	1	25	15 mm	back	1:1	0.257	1.119	0.288	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.41	0.06	1	0206-2	QPSK	25	0	15 mm	back	1:1	0.212	1.146	0.243	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.51	-0.02	0	0206-2	QPSK	1	25	13 mm	bottom	1:1	0.336	1.119	0.376	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.41	0.01	1	0206-2	QPSK	25	0	13 mm	bottom	1:1	0.262	1.146	0.300	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.51	0.00	0	0206-2	QPSK	1	25	9 mm	right	1:1	0.237	1.119	0.265	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.41	0.04	1	0206-2	QPSK	25	0	9 mm	right	1:1	0.191	1.146	0.219	
836.50	20525	Mid	LTE Band 5 (Cell)	10	16.5	15.61	0.03	0	0206-3	QPSK	1	25	0 mm	back	1:1	0.445	1.227	0.546	A11
836.50	20525	Mid	LTE Band 5 (Cell)	10	15.5	14.56	0.02	1	0206-3	QPSK	25	0	0 mm	back	1:1	0.355	1.242	0.441	
836.50	20525	Mid	LTE Band 5 (Cell)	10	16.5	15.61	-0.01	0	0206-3	QPSK	1	25	0 mm	bottom	1:1	0.229	1.227	0.281	
836.50	20525	Mid	LTE Band 5 (Cell)	10	15.5	14.56	-0.04	1	0206-3	QPSK	25	0	0 mm	bottom	1:1	0.180	1.242	0.224	
836.50	20525	Mid	LTE Band 5 (Cell)	10	16.5	15.61	0.05	0	0206-3	QPSK	1	25	0 mm	right	1:1	0.323	1.227	0.396	
836.50	20525	Mid	LTE Band 5 (Cell)	10	15.5	14.56	0.07	1	0206-3	QPSK	25	0	0 mm	right	1:1	0.252	1.242	0.313	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak								Body 1.6 W/kg (mW/g) averaged over 1 gram											
Uncontrolled Exposure/General Population																			

Table 11-9
DTS Body SAR

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna #	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Scaled SAR (1g) (W/kg)	Plot #
MHz	Ch.															
2412	1	IEEE 802.11b	DSSS	12.5	11.85	0.00	0 mm	Antenna 1	1004-1	1	back	1:1	0.870	1.161	1.010	
2437	6	IEEE 802.11b	DSSS	12.5	12.13	0.05	0 mm	Antenna 1	1004-1	1	back	1:1	0.915	1.089	0.996	
2462	11	IEEE 802.11b	DSSS	12.5	11.79	0.08	0 mm	Antenna 1	1004-1	1	back	1:1	0.724	1.178	0.853	
2437	6	IEEE 802.11b	DSSS	12.5	12.13	0.07	0 mm	Antenna 1	1004-1	1	top	1:1	0.621	1.089	0.676	
2437	6	IEEE 802.11b	DSSS	12.5	12.13	0.18	0 mm	Antenna 1	1004-1	1	right	1:1	0.039	1.089	0.042	
2412	1	IEEE 802.11b	DSSS	12.5	11.88	0.02	0 mm	Antenna 2	1004-1	1	back	1:1	0.896	1.153	1.033	
2437	6	IEEE 802.11b	DSSS	12.5	12.35	0.20	0 mm	Antenna 2	1004-1	1	back	1:1	1.020	1.035	1.056	A12
2462	11	IEEE 802.11b	DSSS	12.5	11.30	0.12	0 mm	Antenna 2	1004-1	1	back	1:1	0.774	1.318	1.020	
2437	6	IEEE 802.11b	DSSS	12.5	12.35	0.10	0 mm	Antenna 2	1004-1	1	top	1:1	0.160	1.035	0.166	
2437	6	IEEE 802.11b	DSSS	12.5	12.35	-0.02	0 mm	Antenna 2	1004-1	1	right	1:1	0.389	1.035	0.403	
2437	6	IEEE 802.11n	OFDM	10.5	10.46	0.14	0 mm	MIMO	1004-1	13	back	1:1	0.291	1.009	0.294	
2437	6	IEEE 802.11n	OFDM	10.5	10.46	-0.05	0 mm	MIMO	1004-1	13	top	1:1	0.001	1.009	0.001	
2437	6	IEEE 802.11n	OFDM	10.5	10.46	0.03	0 mm	MIMO	1004-1	13	right	1:1	0.000	1.009	0.000	
2437	6	IEEE 802.11b	DSSS	12.5	12.35	0.12	0 mm	Antenna 2	1004-1	1	back	1:1	0.893	1.035	0.924	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram								

Blue entry represents variability measurement.

Table 11-10
Bluetooth Body SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
2441	39	Bluetooth	FHSS	10.5	9.61	-0.04	0 mm	1004-1	1	back	1:1	0.221	1.227	0.271	A13
2441	39	Bluetooth	FHSS	10.5	9.61	0.00	0 mm	1004-1	1	top	1:1	0.153	1.227	0.188	
2441	39	Bluetooth	FHSS	10.5	9.61	0.01	0 mm	1004-1	1	right	1:1	0.009	1.227	0.011	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: A3LSMT705Y		SAR EVALUATION REPORT					Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet				Page 42 of 68	

11.3 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2003, FCC KDB 616217 and FCC KDB Publication 447498 D01v05.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v05.
6. Per FCC KDB 865664 D01 v01, variability SAR tests were performed when the measured SAR results for a frequency band were greater than 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
7. Per FCC KDB 616217 D04 Section 4.3, SAR tests are required for the back surface and edges of the tablet with the tablet touching the phantom. The SAR Exclusion Threshold in FCC KDB 447498 D01v05 was applied to determine SAR test exclusion for adjacent edge configurations.
8. Head SAR testing was required for this tablet because it has a speaker/receiver and microphone positioning that allows for a held-to-ear configuration usage. Head SAR tests for main antenna were performed at max power levels for all modes.

GSM Test Notes:

1. Justification for reduced test configurations per KDB Publication 941225 D03v01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for body SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
2. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v02. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.
2. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 43 of 68

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r01. The general test procedures used for testing can be found in Section 8.4.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

WLAN Notes:

1. Justification for reduced test configurations for SISO WIFI channels per KDB Publication 248227 D01v01r02 and October 2012 FCC/TCB Meeting Notes for 2.4 GHz WIFI: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11b. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
2. For 5GHz WLAN, SAR was not required based on the maximum conducted power and the antenna to user separation distance. See section 1.6.
3. WIFI transmission was verified using an uncalibrated spectrum analyzer.
4. Since the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is >1.6 W/kg and the reported 1g averaged SAR is >0.8 W/kg, SAR testing on other default channels was required.
5. Per KDB 248227, SAR for MIMO was measured with both antennas transmitting simultaneously and was evaluated independently of SISO operation. For 2.4 GHz MIMO, 802.11n was evaluated. 5 GHz WLAN were excluded per FCC KDB Publication 447498 D01v05.
6. There is no power reduction for WLAN antenna.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 44 of 68

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v05 are applicable to handsets with built-in unlicensed transmitters such as 802.11a/b/g/n/ac and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v05 IV.C.1.iii and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤ 1.6 W/kg. When standalone SAR is not required to be measured, per FCC KDB 447498 D01v05 4.3.2 2), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

Table 12-1
Estimated SAR

Mode	Frequency	Maximum Allowed Power	Configuration	Separation Distance (Body)	Estimated SAR (Body)
	[MHz]	[dBm]		[mm]	[W/kg]
5GHz WLAN Ant. 1	5825	8.00	Head, Back Side & Top Edge Touching (*)	5	0.386
5GHz WLAN Ant. 1	5825	8.00	Right Edge, Touching	17	0.114
5GHz WLAN Ant. 2	5825	8.00	Head, Back Side & Right Edge Touching (*)	5	0.386
5GHz WLAN Ant. 2	5825	8.00	Top Edge, Touching	13	0.149
5GHz WLAN MIMO	5825	8.00	Head, and Body Touching (*)	5	0.386
Bluetooth LE	2440	7.00	Back Side & Top Edge Touching (*)	5	0.208
Bluetooth LE	2440	7.00	Right Edge, Touching	17	0.061

Note:

1. Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission.
2. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.
3. When the test separation distance was > 50 mm, an estimated SAR of 0.4 W/kg was used to determine simultaneous transmission SAR exclusion, for configurations excluded per FCC KDB Publication 447498 D01v05. When the test separation distance was < 50 mm, an estimated SAR was determined per FCC KDB Publication 447498 D01v05.
4. (*) - Per FCC KDB 447498, when the test separation distance is <5 mm, a distance of 5 mm is applied to determine estimated SAR.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 45 of 68

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant. 1 (Held to Ear)

Simult Tx	Configuration	GSM 850 SAR (W/kg)	(Ant.1) 2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	(Ant.1) 2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.010	0.127	0.137	Head SAR	Right Cheek	0.015	0.127	0.142
	Right Tilt	0.013	0.126	0.139		Right Tilt	0.018	0.126	0.144
	Left Cheek	0.007	0.475	0.482		Left Cheek	0.011	0.475	0.486
	Left Tilt	0.011	0.412	0.423		Left Tilt	0.017	0.412	0.429
Simult Tx	Configuration	GSM 1900 SAR (W/kg)	(Ant.1) 2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	(Ant.1) 2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.049	0.127	0.176	Head SAR	Right Cheek	0.226	0.127	0.353
	Right Tilt	0.026	0.126	0.152		Right Tilt	0.102	0.126	0.228
	Left Cheek	0.037	0.475	0.512		Left Cheek	0.139	0.475	0.614
	Left Tilt	0.033	0.412	0.445		Left Tilt	0.103	0.412	0.515
Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	(Ant.1) 2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)					
Head SAR	Right Cheek	0.085	0.127	0.212					
	Right Tilt	0.102	0.126	0.228					
	Left Cheek	0.054	0.475	0.529					
	Left Tilt	0.090	0.412	0.502					

Table 12-3
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant. 2 (Held to Ear)

Simult Tx	Configuration	GSM 850 SAR (W/kg)	(Ant. 2) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	(Ant. 2) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.010	0.033	0.043	Head SAR	Right Cheek	0.015	0.033	0.048
	Right Tilt	0.013	0.026	0.039		Right Tilt	0.018	0.026	0.044
	Left Cheek	0.007	0.158	0.165		Left Cheek	0.011	0.158	0.169
	Left Tilt	0.011	0.175	0.186		Left Tilt	0.017	0.175	0.192
Simult Tx	Configuration	GSM 1900 SAR (W/kg)	(Ant. 2) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	(Ant. 2) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.049	0.033	0.082	Head SAR	Right Cheek	0.226	0.033	0.259
	Right Tilt	0.026	0.026	0.052		Right Tilt	0.102	0.026	0.128
	Left Cheek	0.037	0.158	0.195		Left Cheek	0.139	0.158	0.297
	Left Tilt	0.033	0.175	0.208		Left Tilt	0.103	0.175	0.278
Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	(Ant. 2) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)					
Head SAR	Right Cheek	0.085	0.033	0.118					
	Right Tilt	0.102	0.026	0.128					
	Left Cheek	0.054	0.158	0.212					
	Left Tilt	0.090	0.175	0.265					

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet	Page 46 of 68	

Table 12-4
Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Held to Ear)

Simult Tx	Configuration	GSM 850 SAR (W/kg)	(MIMO) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	(MIMO) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.010	0.130	0.140	Head SAR	Right Cheek	0.015	0.130	0.145
	Right Tilt	0.013	0.124	0.137		Right Tilt	0.018	0.124	0.142
	Left Cheek	0.007	0.453	0.460		Left Cheek	0.011	0.453	0.464
	Left Tilt	0.011	0.471	0.482		Left Tilt	0.017	0.471	0.488
Simult Tx	Configuration	GSM 1900 SAR (W/kg)	(MIMO) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	(MIMO) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.049	0.130	0.179	Head SAR	Right Cheek	0.226	0.130	0.356
	Right Tilt	0.026	0.124	0.150		Right Tilt	0.102	0.124	0.226
	Left Cheek	0.037	0.453	0.490		Left Cheek	0.139	0.453	0.592
	Left Tilt	0.033	0.471	0.504		Left Tilt	0.103	0.471	0.574

Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	(MIMO) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.085	0.130	0.215
	Right Tilt	0.102	0.124	0.226
	Left Cheek	0.054	0.453	0.507
	Left Tilt	0.090	0.471	0.561

Table 12-5
Simultaneous Transmission Scenario with 5 GHz WLAN Ant. 1, 2 and MIMO (Held to Ear)

Simult Tx	Configuration	GSM 850 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.010	0.386	0.396	Head SAR	Right Cheek	0.015	0.386	0.401
	Right Tilt	0.013	0.386	0.399		Right Tilt	0.018	0.386	0.404
	Left Cheek	0.007	0.386	0.393		Left Cheek	0.011	0.386	0.397
	Left Tilt	0.011	0.386	0.397		Left Tilt	0.017	0.386	0.403
Simult Tx	Configuration	GSM 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.049	0.386	0.435	Head SAR	Right Cheek	0.226	0.386	0.612
	Right Tilt	0.026	0.386	0.412		Right Tilt	0.102	0.386	0.488
	Left Cheek	0.037	0.386	0.423		Left Cheek	0.139	0.386	0.525
	Left Tilt	0.033	0.386	0.419		Left Tilt	0.103	0.386	0.489

12.4 Body Simultaneous Transmission Analysis

Table 12-6
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant. 1 (Body at 0.0 cm)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	(Ant.1) 2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	(Ant.1) 2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.927	1.010	See Note 1	0.01	Body SAR	Back	0.445	1.010	1.455	N/A
	Top	0.400	0.676	1.076	N/A		Top	0.400	0.676	1.076	N/A
	Bottom	0.371	0.400	0.771	N/A		Bottom	0.214	0.400	0.614	N/A
	Right	0.172	0.042	0.214	N/A		Right	0.332	0.042	0.374	N/A
	Left	0.185	0.400	0.585	N/A		Left	0.400	0.400	0.800	N/A
Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	(Ant.1) 2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	(Ant.1) 2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.555	1.010	1.565	N/A	Body SAR	Back	0.611	1.010	See Note 1	0.01
	Top	0.400	0.676	1.076	N/A		Top	0.400	0.676	1.076	N/A
	Bottom	0.360	0.400	0.760	N/A		Bottom	0.406	0.400	0.806	N/A
	Right	0.127	0.042	0.169	N/A		Right	0.140	0.042	0.182	N/A
	Left	0.101	0.400	0.501	N/A		Left	0.400	0.400	0.800	N/A
			Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	(Ant.1) 2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR			
			Body SAR	Back	0.546	1.010	1.556	N/A			
				Top	0.400	0.676	1.076	N/A			
				Bottom	0.281	0.400	0.681	N/A			
				Right	0.396	0.042	0.438	N/A			
				Left	0.400	0.400	0.800	N/A			

Table 12-7
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant. 2 (Body at 0.0 cm)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	(Ant. 2) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	(Ant. 2) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.927	1.056	See Note 1	0.02	Body SAR	Back	0.445	1.056	1.501	N/A
	Top	0.400	0.166	0.566	N/A		Top	0.400	0.166	0.566	N/A
	Bottom	0.371	0.400	0.771	N/A		Bottom	0.214	0.400	0.614	N/A
	Right	0.172	0.403	0.575	N/A		Right	0.332	0.403	0.735	N/A
	Left	0.185	0.400	0.585	N/A		Left	0.400	0.400	0.800	N/A
Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	(Ant. 2) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	(Ant. 2) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.555	1.056	See Note 1	0.01	Body SAR	Back	0.611	1.056	See Note 1	0.01
	Top	0.400	0.166	0.566	N/A		Top	0.400	0.166	0.566	N/A
	Bottom	0.360	0.400	0.760	N/A		Bottom	0.406	0.400	0.806	N/A
	Right	0.127	0.403	0.530	N/A		Right	0.140	0.403	0.543	N/A
	Left	0.101	0.400	0.501	N/A		Left	0.400	0.400	0.800	N/A
			Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	(Ant. 2) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR			
			Body SAR	Back	0.546	1.056	See Note 1	0.01			
				Top	0.400	0.166	0.566	N/A			
				Bottom	0.281	0.400	0.681	N/A			
				Right	0.396	0.403	0.799	N/A			
Left	0.400	0.400	0.800	N/A							

FCC ID: A3LSMT705Y		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 48 of 68

Table 12-8
Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Body at 0.0 cm)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	(MIMO) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	(MIMO) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.927	0.294	1.221	N/A	Body SAR	Back	0.445	0.294	0.739	N/A
	Top	0.400	0.001	0.401	N/A		Top	0.400	0.001	0.401	N/A
	Bottom	0.371	0.400	0.771	N/A		Bottom	0.214	0.400	0.614	N/A
	Right	0.172	0.000	0.172	N/A		Right	0.332	0.000	0.332	N/A
	Left	0.185	0.400	0.585	N/A		Left	0.400	0.400	0.800	N/A
Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	(MIMO) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	(MIMO) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.555	0.294	0.849	N/A	Body SAR	Back	0.611	0.294	0.905	N/A
	Top	0.400	0.001	0.401	N/A		Top	0.400	0.001	0.401	N/A
	Bottom	0.360	0.400	0.760	N/A		Bottom	0.406	0.400	0.806	N/A
	Right	0.127	0.000	0.127	N/A		Right	0.140	0.000	0.140	N/A
	Left	0.101	0.400	0.501	N/A		Left	0.400	0.400	0.800	N/A
			Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	(MIMO) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR			
			Body SAR	Back	0.546	0.294	0.840	N/A			
				Top	0.400	0.001	0.401	N/A			
				Bottom	0.281	0.400	0.681	N/A			
				Right	0.396	0.000	0.396	N/A			
				Left	0.400	0.400	0.800	N/A			

Table 12-9
Simultaneous Transmission Scenario with 5 GHz WLAN Ant. 1 (Body at 0.0 cm)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	(Ant. 1) 5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	(Ant. 1) 5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.927	0.386	1.313	N/A	Body SAR	Back	0.445	0.386	0.831	N/A
	Top	0.400	0.386	0.786	N/A		Top	0.400	0.386	0.786	N/A
	Bottom	0.371	0.400	0.771	N/A		Bottom	0.214	0.400	0.614	N/A
	Right	0.172	0.114	0.286	N/A		Right	0.332	0.114	0.446	N/A
	Left	0.185	0.400	0.585	N/A		Left	0.400	0.400	0.800	N/A
Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	(Ant. 1) 5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	(Ant. 1) 5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.555	0.386	0.941	N/A	Body SAR	Back	0.611	0.386	0.997	N/A
	Top	0.400	0.386	0.786	N/A		Top	0.400	0.386	0.786	N/A
	Bottom	0.360	0.400	0.760	N/A		Bottom	0.406	0.400	0.806	N/A
	Right	0.127	0.114	0.241	N/A		Right	0.140	0.114	0.254	N/A
	Left	0.101	0.400	0.501	N/A		Left	0.400	0.400	0.800	N/A
			Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	(Ant. 1) 5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR			
			Body SAR	Back	0.546	0.386	0.932	N/A			
				Top	0.400	0.386	0.786	N/A			
				Bottom	0.281	0.400	0.681	N/A			
				Right	0.396	0.114	0.510	N/A			
				Left	0.400	0.400	0.800	N/A			

Table 12-10
Simultaneous Transmission Scenario with 5 GHz WLAN Ant. 2 (Body at 0.0 cm)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	(Ant.2) 5GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	(Ant.2) 5GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.927	0.386	1.313	N/A	Body SAR	Back	0.445	0.386	0.831	N/A
	Top	0.400	0.149	0.549	N/A		Top	0.400	0.149	0.549	N/A
	Bottom	0.371	0.400	0.771	N/A		Bottom	0.214	0.400	0.614	N/A
	Right	0.172	0.386	0.558	N/A		Right	0.332	0.386	0.718	N/A
	Left	0.185	0.400	0.585	N/A		Left	0.400	0.400	0.800	N/A
Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	(Ant.2) 5GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	(Ant.2) 5GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.555	0.386	0.941	N/A	Body SAR	Back	0.611	0.386	0.997	N/A
	Top	0.400	0.149	0.549	N/A		Top	0.400	0.149	0.549	N/A
	Bottom	0.360	0.400	0.760	N/A		Bottom	0.406	0.400	0.806	N/A
	Right	0.127	0.386	0.513	N/A		Right	0.140	0.386	0.526	N/A
	Left	0.101	0.400	0.501	N/A		Left	0.400	0.400	0.800	N/A
			Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	(Ant.2) 5GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR			
			Body SAR	Back	0.546	0.386	0.932	N/A			
				Top	0.400	0.149	0.549	N/A			
				Bottom	0.281	0.400	0.681	N/A			
				Right	0.396	0.386	0.782	N/A			
				Left	0.400	0.400	0.800	N/A			

Table 12-11
Simultaneous Transmission Scenario with 5 GHz WLAN MIMO (Body at 0.0 cm)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	(MIMO) 5GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	(MIMO) 5GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.927	0.386	1.313	N/A	Body SAR	Back	0.445	0.386	0.831	N/A
	Top	0.400	0.386	0.786	N/A		Top	0.400	0.386	0.786	N/A
	Bottom	0.371	0.400	0.771	N/A		Bottom	0.214	0.400	0.614	N/A
	Right	0.172	0.386	0.558	N/A		Right	0.332	0.386	0.718	N/A
	Left	0.185	0.400	0.585	N/A		Left	0.400	0.400	0.800	N/A
Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	(MIMO) 5GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	(MIMO) 5GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.555	0.386	0.941	N/A	Body SAR	Back	0.611	0.386	0.997	N/A
	Top	0.400	0.386	0.786	N/A		Top	0.400	0.386	0.786	N/A
	Bottom	0.360	0.400	0.760	N/A		Bottom	0.406	0.400	0.806	N/A
	Right	0.127	0.386	0.513	N/A		Right	0.140	0.386	0.526	N/A
	Left	0.101	0.400	0.501	N/A		Left	0.400	0.400	0.800	N/A
			Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	(MIMO) 5GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR			
			Body SAR	Back	0.546	0.386	0.932	N/A			
				Top	0.400	0.386	0.786	N/A			
				Bottom	0.281	0.400	0.681	N/A			
				Right	0.396	0.386	0.782	N/A			
				Left	0.400	0.400	0.800	N/A			

Table 12-12
Simultaneous Transmission Scenario with Bluetooth (Body at 0.0 cm)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.927	0.271	1.198	N/A	Body SAR	Back	0.445	0.271	0.716	N/A
	Top	0.400	0.208	0.608	N/A		Top	0.400	0.208	0.608	N/A
	Bottom	0.371	0.400	0.771	N/A		Bottom	0.214	0.400	0.614	N/A
	Right	0.172	0.061	0.233	N/A		Right	0.332	0.061	0.393	N/A
	Left	0.185	0.400	0.585	N/A		Left	0.400	0.400	0.800	N/A
Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.555	0.271	0.826	N/A	Body SAR	Back	0.611	0.271	0.882	N/A
	Top	0.400	0.208	0.608	N/A		Top	0.400	0.208	0.608	N/A
	Bottom	0.360	0.400	0.760	N/A		Bottom	0.406	0.400	0.806	N/A
	Right	0.127	0.061	0.188	N/A		Right	0.140	0.061	0.201	N/A
	Left	0.101	0.400	0.501	N/A		Left	0.400	0.400	0.800	N/A

Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Body SAR	Back	0.546	0.271	0.817	N/A
	Top	0.400	0.208	0.608	N/A
	Bottom	0.281	0.400	0.681	N/A
	Right	0.396	0.061	0.457	N/A
	Left	0.400	0.400	0.800	N/A

Note: Estimated Bluetooth LE SAR result for top and right edge was used in the above table to determine simultaneous transmission SAR test exclusion since it was more conservative than Bluetooth reported SAR.

Table 12-13
Simultaneous Transmission Scenario (2.4 GHz Body Back side at 1.5 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	(Ant. 1) 2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Back Side	GPRS 850	0.447	<1.010	<1.457	N/A
Back Side	UMTS 850	0.424	<1.010	<1.434	N/A
Back Side	GPRS 1900	0.394	<1.010	<1.404	N/A
Back Side	UMTS 1900	0.879	<1.010	See Note 1	<0.01
Back Side	LTE Band 5 (Cell)	0.288	<1.010	<1.298	N/A
Configuration	Mode	2G/3G/4G SAR (W/kg)	(Ant. 2) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Back Side	GPRS 850	0.447	<1.056	<1.503	N/A
Back Side	UMTS 850	0.424	<1.056	<1.480	N/A
Back Side	GPRS 1900	0.394	<1.056	<1.450	N/A
Back Side	UMTS 1900	0.879	<1.056	See Note 1	<0.02
Back Side	LTE Band 5 (Cell)	0.288	<1.056	<1.344	N/A
Configuration	Mode	2G/3G/4G SAR (W/kg)	(MIMO) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Back Side	GPRS 850	0.447	<0.294	<0.741	N/A
Back Side	UMTS 850	0.424	<0.294	<0.718	N/A
Back Side	GPRS 1900	0.394	<0.294	<0.688	N/A
Back Side	UMTS 1900	0.879	<0.294	<1.173	N/A
Back Side	LTE Band 5 (Cell)	0.288	<0.294	<0.582	N/A

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 51 of 68

Table 12-14
Simultaneous Transmission Scenario (5 GHz Body Back side at 1.5 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Back Side	GPRS 850	0.447	<0.386	<0.833	N/A
Back Side	UMTS 850	0.424	<0.386	<0.810	N/A
Back Side	GPRS 1900	0.394	<0.386	<0.780	N/A
Back Side	UMTS 1900	0.879	<0.386	<1.265	N/A
Back Side	LTE Band 5 (Cell)	0.288	<0.386	<0.674	N/A

Table 12-15
Simultaneous Transmission Scenario (Bluetooth Body Back side at 1.5 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Back Side	GPRS 850	0.447	<0.271	<0.718	N/A
Back Side	UMTS 850	0.424	<0.271	<0.695	N/A
Back Side	GPRS 1900	0.394	<0.271	<0.665	N/A
Back Side	UMTS 1900	0.879	<0.271	<1.150	N/A
Back Side	LTE Band 5 (Cell)	0.288	<0.271	<0.559	N/A

Table 12-16
Simultaneous Transmission Scenario (2.4 GHz Body Bottom Edge at 1.3 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Bottom Edge	GPRS 850	0.338	0.400	0.738	N/A
Bottom Edge	UMTS 850	0.267	0.400	0.667	N/A
Bottom Edge	GPRS 1900	0.260	0.400	0.660	N/A
Bottom Edge	UMTS 1900	0.554	0.400	0.954	N/A
Bottom Edge	LTE Band 5 (Cell)	0.376	0.400	0.776	N/A

Table 12-17
Simultaneous Transmission Scenario (5 GHz Body Bottom Edge at 1.3 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Bottom Edge	GPRS 850	0.338	0.400	0.738	N/A
Bottom Edge	UMTS 850	0.267	0.400	0.667	N/A
Bottom Edge	GPRS 1900	0.260	0.400	0.660	N/A
Bottom Edge	UMTS 1900	0.554	0.400	0.954	N/A
Bottom Edge	LTE Band 5 (Cell)	0.376	0.400	0.776	N/A

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 52 of 68

Table 12-18
Simultaneous Transmission Scenario (Bluetooth Body Bottom Edge at 1.3 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Bottom Edge	GPRS 850	0.338	0.400	0.738	N/A
Bottom Edge	UMTS 850	0.267	0.400	0.667	N/A
Bottom Edge	GPRS 1900	0.260	0.400	0.660	N/A
Bottom Edge	UMTS 1900	0.554	0.400	0.954	N/A
Bottom Edge	LTE Band 5 (Cell)	0.376	0.400	0.776	N/A

Table 12-19
Simultaneous Transmission Scenario (2.4 GHz Body Right Edge at 0.9 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	(Ant. 1) 2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Right Edge	GPRS 850	0.235	<0.042	<0.277	N/A
Right Edge	UMTS 850	0.126	<0.042	<0.168	N/A
Right Edge	GPRS 1900	0.204	<0.042	<0.246	N/A
Right Edge	UMTS 1900	0.445	<0.042	<0.487	N/A
Right Edge	LTE Band 5 (Cell)	0.265	<0.042	<0.307	N/A
Configuration	Mode	2G/3G/4G SAR (W/kg)	(Ant. 2) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Right Edge	GPRS 850	0.235	<0.403	<0.638	N/A
Right Edge	UMTS 850	0.126	<0.403	<0.529	N/A
Right Edge	GPRS 1900	0.204	<0.403	<0.607	N/A
Right Edge	UMTS 1900	0.445	<0.403	<0.848	N/A
Right Edge	LTE Band 5 (Cell)	0.265	<0.403	<0.668	N/A
Configuration	Mode	2G/3G/4G SAR (W/kg)	(MIMO) 2.4GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Right Edge	GPRS 850	0.235	<0.000	<0.235	N/A
Right Edge	UMTS 850	0.126	<0.000	<0.126	N/A
Right Edge	GPRS 1900	0.204	<0.000	<0.204	N/A
Right Edge	UMTS 1900	0.445	<0.000	<0.445	N/A
Right Edge	LTE Band 5 (Cell)	0.265	<0.000	<0.265	N/A

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 53 of 68

Table 12-20
Simultaneous Transmission Scenario (5 GHz Body Right Edge at 0.9 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	(Ant. 1) 5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Right Edge	GPRS 850	0.235	<0.114	<0.349	N/A
Right Edge	UMTS 850	0.126	<0.114	<0.240	N/A
Right Edge	GPRS 1900	0.204	<0.114	<0.318	N/A
Right Edge	UMTS 1900	0.445	<0.114	<0.559	N/A
Right Edge	LTE Band 5 (Cell)	0.265	<0.114	<0.379	N/A
Configuration	Mode	2G/3G/4G SAR (W/kg)	(Ant.2) 5GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Right Edge	GPRS 850	0.235	<0.386	<0.621	N/A
Right Edge	UMTS 850	0.126	<0.386	<0.512	N/A
Right Edge	GPRS 1900	0.204	<0.386	<0.590	N/A
Right Edge	UMTS 1900	0.445	<0.386	<0.831	N/A
Right Edge	LTE Band 5 (Cell)	0.265	<0.386	<0.651	N/A
Configuration	Mode	2G/3G/4G SAR (W/kg)	(MIMO) 5GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Right Edge	GPRS 850	0.235	<0.386	<0.621	N/A
Right Edge	UMTS 850	0.126	<0.386	<0.512	N/A
Right Edge	GPRS 1900	0.204	<0.386	<0.590	N/A
Right Edge	UMTS 1900	0.445	<0.386	<0.831	N/A
Right Edge	LTE Band 5 (Cell)	0.265	<0.386	<0.651	N/A

Table 12-21
Simultaneous Transmission Scenario (Bluetooth Body Right Edge at 0.9 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)	SPLSR
Right Edge	GPRS 850	0.235	<0.061	<0.296	N/A
Right Edge	UMTS 850	0.126	<0.061	<0.187	N/A
Right Edge	GPRS 1900	0.204	<0.061	<0.265	N/A
Right Edge	UMTS 1900	0.445	<0.061	<0.506	N/A
Right Edge	LTE Band 5 (Cell)	0.265	<0.061	<0.326	N/A

Notes:

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not higher than 0.04 per FCC KDB 447498 D01v05. See Section 12.5 for detailed SPLS ratio analysis.
2. For SAR summations for body (back side at 15mm and right edge at 9mm), WLAN and Bluetooth SAR values for 0.0 mm were used since the 0.0 mm test distance for WLAN and Bluetooth SAR values were more conservative. "<" denotes that the 0.0 mm WLAN and Bluetooth SAR values were used for summation purposes.
3. Estimated Bluetooth LE SAR result for right edge was used for Bluetooth Right Edge SAR to determine simultaneous transmission SAR test exclusion because estimated Bluetooth LE SAR was more conservative than measured Bluetooth SAR.
4. For SAR summations for body bottom edge 13 mm, estimated WLAN and Bluetooth SAR values of 0.4 W/kg was used to determine simultaneous transmission SAR exclusion, for configurations excluded per FCC KDB Publication 447498 D01v05, since the antenna separation distance is greater than 50mm.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 54 of 68

12.5 SPLSR Evaluation and Analysis

Per FCC KDB Publication 447498 D01v05, when the sum of the standalone transmitters is more than 1.6 W/kg, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. When the SAR peak to location ratio (shown below) for each pair of antennas is ≤ 0.04 , simultaneous SAR evaluation is not required. The distance between the transmitters was calculated using the following formula.

$$\text{Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2}$$

$$\text{SPLS Ratio} = \frac{(SAR_1 + SAR_2)^{1.5}}{R_i}$$

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with GPRS 850 antenna operating at limited output power with 2.4 GHz WIFI Antenna 1.

Table 12-22
Peak SAR Locations for Body Back Side at 0 mm GPRS 850 and 2.4 GHz WLAN Ant. 1

Mode/Band	x (mm)	y (mm)
GPRS 850 MHz (at 0 mm)	-70.00	-97.00
802.11b (Ant 1)	-65.60	91.80




Figure 12-1
Peak SAR Locations of 2.4 GHz WLAN Ant. 1 and GPRS 850 at 0 mm

Table 12-23
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	(a+b) ^{1.5} /D _{a-b}
GPRS 850 MHz (at 0 mm)	802.11b (Ant 1)	0.927	1.01	1.937	188.85	0.01

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet			Page 55 of 68

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with UMTS 1900 antenna operating at limited output power with 2.4 GHz WIFI Antenna 1.

Table 12-24
Peak SAR Locations for Body Back Side at 0 mm UMTS 1900 and 2.4 GHz WLAN Ant. 1

Mode/Band	x (mm)	y (mm)
UMTS 1900 MHz (at 0 mm)	-61.50	-91.50
802.11b (Ant. 1)	-65.60	91.80




Figure 12-2
Peak SAR Locations of 2.4 GHz WLAN Ant. 1 and UMTS 1900 at 0 mm

Table 12-25
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
UMTS 1900 MHz (at 0 mm)	802.11b (Ant. 1)	0.611	1.01	1.621	183.35	0.01

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 56 of 68	

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with GPRS 850 antenna operating at limited output power with 2.4 GHz WIFI Antenna 2.

Table 12-26
Peak SAR Locations for Body Back Side at 0 mm GPRS 850 and 2.4 GHz WLAN Ant. 2

Mode/Band	x (mm)	y (mm)
GPRS 850 (at 0 mm)	-70.00	-97.00
802.11b (Ant.2)	-69.80	77.20




Figure 12-3
Peak SAR Locations of 2.4 GHz WLAN Ant. 2 and GPRS 850 at 0 mm

Table 12-27
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
GPRS 850 (at 0 mm)	802.11b (Ant.2)	0.927	1.056	1.983	174.2	0.02

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 57 of 68	

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with GPRS 1900 antenna operating at limited output power with 2.4 GHz WIFI Antenna 2.

Table 12-28

Peak SAR Locations for Body Back Side at 0 mm GPRS 1900 and 2.4 GHz WLAN Ant. 2

Mode/Band	x (mm)	y (mm)
GPRS 1900 (at 0 mm)	-68.00	-89.00
802.11b (Ant. 2)	-69.80	77.20




Figure 12-4

Peak SAR Locations of 2.4 GHz WLAN Ant. 2 and GPRS 1900 at 0 mm

Table 12-29

SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
GPRS 1900 (at 0 mm)	802.11b (Ant. 2)	0.555	1.056	1.611	166.21	0.01

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 58 of 68	

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with UMTS 1900 antenna operating at limited output power with 2.4 GHz WIFI Antenna 2.

Table 12-30
Peak SAR Locations for Body Back Side at 0 mm UMTS 1900 and 2.4 GHz WLAN Ant. 2

Mode/Band	x (mm)	y (mm)
UMTS 1900 (at 0 mm)	-61.50	-91.50
802.11b (Ant. 2)	-69.80	77.20




Figure 12-5
Peak SAR Locations of 2.4 GHz WLAN Ant. 2 and UMTS 1900 at 0 mm

Table 12-31
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
UMTS 1900 (at 0 mm)	802.11b (Ant. 2)	0.611	1.056	1.667	168.9	0.01

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 0 mm with LTE B5 antenna operating at limited output power with 2.4 GHz WIFI Antenna 2.

Table 12-32
Peak SAR Locations for Body Back Side at 0 mm LTE B5 and 2.4 GHz WLAN Ant. 2

Mode/Band	x (mm)	y (mm)
LTE B5 (at 0 mm)	-75.50	-90.00
802.11b (Ant. 2)	-69.80	77.20




Figure 12-6
Peak SAR Locations of 2.4 GHz WLAN Ant. 2 and LTE B5 at 0 mm

Table 12-33
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
LTE B5 (at 0 mm)	802.11b (Ant. 2)	0.546	1.056	1.602	167.3	0.01

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 15 mm with UMTS 1900 antenna operating at maximum output power with 2.4 GHz WIFI Antenna 1.

Table 12-38

Peak SAR Locations for Body Back Side at 15 mm UMTS 1900 and 2.4 GHz WLAN Ant. 1

Mode/Band	x (mm)	y (mm)
UMTS 1900 (at 15 mm)	-62.00	-90.00
802.11b (Ant. 1)	-65.60	91.80




Figure 12-9

Peak SAR Locations of 2.4 GHz WLAN Ant. 1 and UMTS 1900 at 15 mm

Table 12-39

SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5} / D_{a-b}$
UMTS 1900 (at 15 mm)	802.11b (Ant. 1)	0.879	<1.01	<1.889	181.84	<0.01

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 61 of 68	

The sum of the standalone SAR values was above 1.6 W/kg for the Body Back side configuration at a separation distance of 15 mm with UMTS 1900 antenna operating at maximum output power with 2.4 GHz WIFI Antenna 2.

Table 12-40
Peak SAR Locations for Body Back Side at 15 mm UMTS 1900 and 2.4 GHz WLAN Ant. 2

Mode/Band	x (mm)	y (mm)
UMTS 1900 (at 15 mm)	-62.00	-90.00
802.11b (Ant. 2)	-69.80	77.20




Figure 12-10
Peak SAR Locations of 2.4 GHz WLAN Ant. 2 and UMTS 1900 at 15 mm

Table 12-41
SAR Sum to Peak Location Separation Ratio Calculation

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$
UMTS 1900 (at 15 mm)	802.11b (Ant. 2)	0.879	<1.056	<1.935	167.38	<0.02

12.6 Simultaneous Transmission Conclusion

The above numerical summed SAR and SPLSR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v05 and IEEE 1528-2013 Section 6.3.4.1.2.

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 13-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS														
Band	FREQUENCY		Mode	Service	Data Rate (Mbps)	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.						(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1900	1907.60	9538	UMTS 1900	RMC	N/A	back	15 mm	0.830	0.810	1.02	N/A	N/A	N/A	N/A
2450	2437.00	6	IEEE 802.11b Antenna 2	DSSS	1	back	0 mm	1.020	0.893	1.14	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram							

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01, the extended measurement uncertainty analysis per IEEE 1528-2003 was not required.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 63 of 68

14 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	85047A	S-Parameter Test Set	N/A	N/A	N/A	2904A00579
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	8753E	(30kHz-6GHz) Network Analyzer	7/23/2013	Annual	7/23/2014	US37390350
Agilent	8753ES	S-Parameter Network Analyzer	10/29/2013	Annual	10/29/2014	US39170122
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB46170464
Agilent	N9020A	MXA Signal Analyzer	10/29/2013	Annual	10/29/2014	US46470561
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433974
Anritsu	MA24106A	USB Power Sensor	12/18/2013	Annual	12/18/2014	1344555
Anritsu	MA24106A	USB Power Sensor	12/18/2013	Annual	12/18/2014	1344556
Anritsu	MA2411B	Pulse Power Sensor	11/14/2013	Annual	11/14/2014	1126066
Anritsu	MA2411B	Pulse Power Sensor	2/3/2014	Annual	2/3/2015	1339018
Anritsu	MA2481A	Power Sensor	10/30/2013	Annual	10/30/2014	5605
Anritsu	ML2495A	Power Meter	10/31/2013	Annual	10/31/2014	1039008
Anritsu	MT8820C	Radio Communication Analyzer	6/28/2013	Annual	6/28/2014	6201240328
Anritsu	MT8820C	Radio Communication Analyzer	12/12/2013	Annual	12/12/2014	6200901190
COMTECH	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
COMTECH	AR85729-5/5759B	Solid State Amplifier	CBT	N/A	CBT	M3W1A00-1002
Fisher Scientific	15-077-960	Digital Thermometer	12/4/2013	Biennial	12/4/2015	130764558
Fisher Scientific	S407993	Long Stem Thermometer	11/4/2013	Biennial	11/4/2015	130671801
Fisher Scientific	S407993	Long Stem Thermometer	11/4/2013	Biennial	11/4/2015	130671821
Gigatronics	80701A	(0.05-18GHz) Power Sensor	10/30/2013	Annual	10/30/2014	1833460
Gigatronics	8651A	Universal Power Meter	10/30/2013	Annual	10/30/2014	8650319
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-53W2	Attenuator (3dB)	CBT	N/A	CBT	120
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	9/23/2013	Annual	9/23/2014	109892
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	10/4/2013	Annual	10/4/2014	108798
Rohde & Schwarz	NRVD	Dual Channel Power Meter	10/12/2012	Biennial	10/12/2014	101695
Rohde & Schwarz	NRVS	Single Channel Power Meter	10/31/2013	Annual	10/31/2014	835360/0079
Rohde & Schwarz	NRV-Z32	Peak Power Sensor	10/12/2012	Biennial	10/12/2014	836019/013
Rohde & Schwarz	SME06	Signal Generator	10/30/2013	Annual	10/30/2014	832026
Seekonk	NC-100	Torque Wrench	3/18/2014	Biennial	3/18/2016	N/A
Seekonk	NC-100	Torque Wrench	3/18/2014	Biennial	3/18/2016	N/A
SPEAG	D1900V2	1900 MHz SAR Dipole	7/22/2013	Annual	7/22/2014	5d149
SPEAG	D1900V2	1900 MHz SAR Dipole	2/27/2014	Annual	2/27/2015	5d148
SPEAG	D2450V2	2450 MHz SAR Dipole	1/21/2014	Annual	1/21/2015	797
SPEAG	D835V2	835 MHz SAR Dipole	1/22/2014	Annual	1/22/2015	4d132
SPEAG	D835V2	835 MHz SAR Dipole	7/17/2013	Annual	7/17/2014	4d133
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/17/2014	Annual	3/17/2015	1364
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/14/2014	Annual	3/17/2015	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/17/2013	Annual	9/17/2014	1323
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/19/2013	Annual	11/19/2014	1408
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/26/2014	Annual	2/26/2015	665
SPEAG	DAK-3.5	Dielectric Assessment Kit	11/13/2013	Annual	11/13/2014	1091
SPEAG	ES3DV3	SAR Probe	11/20/2013	Annual	11/20/2014	3287
SPEAG	ES3DV3	SAR Probe	4/11/2014	Annual	4/11/2015	3213
SPEAG	ES3DV3	SAR Probe	2/25/2014	Annual	2/25/2015	3258
SPEAG	EX3DV4	SAR Probe	3/19/2014	Annual	3/19/2015	3209
SPEAG	EX3DV4	SAR Probe	9/23/2013	Annual	9/23/2014	3288
VWR	36934-158	Wall-Mounted Thermometer	8/8/2013	Biennial	8/8/2015	130477877

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: A3LSMT705Y		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 64 of 68

15 MEASUREMENT UNCERTAINTIES

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.0	N	1	1.0	1.0	6.0	6.0	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							RSS	12.1	11.7
Expanded Uncertainty							k=2	24.2	23.5
(95% CONFIDENCE LEVEL)									

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: A3LSMT705Y		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 65 of 68

16 CONCLUSION

16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 66 of 68

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 67 of 68

- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement procedures for IEEE 802.11a/b/g KDB Publication 248227 D01v01r02
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D02-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1405231077.A3L	Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet		Page 68 of 68

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT705Y; Type: Portable Tablet; Serial: 0206-1

Communication System: UID 0, GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 41.923$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-03-2014; Ambient Temp: 20.5°C; Tissue Temp: 20.5°C

Probe: ES3DV3 - SN3213; ConvF(6.37, 6.37, 6.37); Calibrated: 4/11/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

Mode: GSM 850, Right Head, Tilt, Mid.ch


Area Scan (12x17x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 3.671 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.0150 W/kg

SAR(1 g) = 0.012 W/kg



0 dB = 0.0124 W/kg = -19.07 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT705Y; Type: Portable Tablet; Serial: 0206-1

Communication System: UID 0, WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 41.923$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-03-2014; Ambient Temp: 20.5°C; Tissue Temp: 20.5°C

Probe: ES3DV3 - SN3213; ConvF(6.37, 6.37, 6.37); Calibrated: 4/11/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

Mode: UMTS 850, Right Head, Tilt, Mid.ch


Area Scan (12x17x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.424 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.0210 W/kg

SAR(1 g) = 0.017 W/kg



0 dB = 0.0180 W/kg = -17.45 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT705Y; Type: Portable Tablet; Serial: 0206-1

Communication System: UID 0, GSM1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.426 \text{ S/m}$; $\epsilon_r = 39.919$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-03-2014; Ambient Temp: 20.5°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3213; ConvF(4.99, 4.99, 4.99); Calibrated: 4/11/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

Mode: GSM 1900, Right Head, Cheek, Mid.ch


Area Scan (12x18x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.668 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.0610 W/kg

SAR(1 g) = 0.044 W/kg



0 dB = 0.0466 W/kg = -13.32 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT705Y; Type: Portable Tablet; Serial: 2305-1

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.383 \text{ S/m}$; $\epsilon_r = 39.843$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-17-2014; Ambient Temp: 23.9°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3287; ConvF(5.08, 5.08, 5.08); Calibrated: 11/20/2013;
Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

Mode: UMTS 1900, Right Head, Cheek, Mid.ch


Area Scan (12x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.696 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.276 W/kg

SAR(1 g) = 0.207 W/kg



0 dB = 0.230 W/kg = -6.38 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT705Y; Type: Portable Tablet; Serial: 0206-1

Communication System: UID 0, LTE BAND 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 41.924$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-03-2014; Ambient Temp: 20.5°C; Tissue Temp: 20.5°C

Probe: ES3DV3 - SN3213; ConvF(6.37, 6.37, 6.37); Calibrated: 4/11/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 5 (Cell), Right Head, Tilt, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


Area Scan (13x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.409 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.111 W/kg

SAR(1 g) = 0.091 W/kg



0 dB = 0.0949 W/kg = -10.23 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT705Y; Type: Portable Tablet; Serial: 0410-02

Communication System: UID 0, IEEE 802.11n (0); Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 1.759 \text{ S/m}$; $\epsilon_r = 39.206$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 04-14-2014; Ambient Temp: 24.2°C; Tissue Temp: 23.4°C

Probe: ES3DV3 - SN3287; ConvF(4.43, 4.43, 4.43); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: IEEE 802.11n MIMO, Left Head, Tilt, Ch 06, 13 Mbps


Area Scan (16x23x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.657 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.963 W/kg

SAR(1 g) = 0.467 W/kg



0 dB = 0.631 W/kg = -2.00 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT705Y; Type: Portable Tablet; Serial: 2305-2

Communication System: UID 0, GSM850 GPRS; 3 Tx slots; Frequency: 848.8 MHz; Duty Cycle: 1:2.76

Medium: 835 Body Medium parameters used (interpolated):

$f = 848.8 \text{ MHz}$; $\sigma = 1.022 \text{ S/m}$; $\epsilon_r = 54.615$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-29-2014; Ambient Temp: 22.1°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3213; ConvF(6.18, 6.18, 6.18); Calibrated: 4/11/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

Mode: GPRS 850, Body SAR, Back side, High.ch, 3 Tx Slots


Area Scan (11x17x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 27.583 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.74 W/kg

SAR(1 g) = 0.793 W/kg



0 dB = 0.827 W/kg = -0.82 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT705Y; Type: Portable Tablet; Serial: 0206-3

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.012 \text{ S/m}$; $\epsilon_r = 54.913$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-01-2014; Ambient Temp: 23.8°C; Tissue Temp: 23.3°C

Probe: ES3DV3 - SN3209; ConvF(6.14, 6.14, 6.14); Calibrated: 3/19/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM front; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (10x16x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.914 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.810 W/kg

SAR(1 g) = 0.432 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT705Y; Type: Portable Tablet; Serial: 0206-3

Communication System: UID 0, GSM1900 GPRS; 4 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.076

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.51 \text{ S/m}$; $\epsilon_r = 53.112$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-02-2014; Ambient Temp: 23.0°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3288; ConvF(4.82, 4.82, 4.82); Calibrated: 9/23/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM Sub Dasy B; Type: SAM 5.0; Serial: TP-1626

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

Mode: GPRS 1900, Body SAR, Back side, Mid.ch, 4 Tx Slots


Area Scan (12x18x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.896 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 1.12 W/kg

SAR(1 g) = 0.484 W/kg



0 dB = 0.516 W/kg = -2.87 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT705Y; Type: Portable Tablet; Serial: 2305-1

Communication System: UID 0, WCDMA1900; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1907.6 \text{ MHz}$; $\sigma = 1.54 \text{ S/m}$; $\epsilon_r = 53.014$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-02-2014; Ambient Temp: 23.0°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3288; ConvF(4.82, 4.82, 4.82); Calibrated: 9/23/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM Sub Dasy B; Type: SAM 5.0; Serial: TP-1626

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

Mode: UMTS 1900, Body SAR, Back side, High.ch


Area Scan (12x18x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 25.076 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.39 W/kg

SAR(1 g) = 0.830 W/kg



0 dB = 0.921 W/kg = -0.36 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT705Y; Type: Portable Tablet; Serial: 0206-3

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 1.012 \text{ S/m}$; $\epsilon_r = 54.914$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-01-2014; Ambient Temp: 23.8°C; Tissue Temp: 23.3°C

Probe: ES3DV3 - SN3209; ConvF(6.14, 6.14, 6.14); Calibrated: 3/19/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM front; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.272 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.818 W/kg

SAR(1 g) = 0.445 W/kg



0 dB = 0.492 W/kg = -3.08 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT705Y; Type: Portable Tablet; Serial: 1004-1

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 2.013 \text{ S/m}$; $\epsilon_r = 52.664$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 04-14-2014; Ambient Temp: 24.4°C; Tissue Temp: 23.9°C

Probe: ES3DV3 - SN3258; ConvF(4.14, 4.14, 4.14); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: IEEE 802.11b Antenna 2, Body SAR, Back Side, Ch 06, 1 Mbps


Area Scan (16x21x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.718 V/m; Power Drift = 0.20 dB

Peak SAR (extrapolated) = 3.35 W/kg

SAR(1 g) = 1.02 W/kg



0 dB = 1.48 W/kg = 1.70 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT705Y; Type: Portable Tablet; Serial: 1004-1

Communication System: UID 0, Bluetooth (0); Frequency: 2441 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 2.02 \text{ S/m}$; $\epsilon_r = 51.016$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 04-21-2014; Ambient Temp: 24.3°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3258; ConvF(4.14, 4.14, 4.14); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

Mode: Bluetooth, Body SAR, Back Side, Ch 39, 1 Mbps


Area Scan (14x21x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.196 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.600 W/kg

SAR(1 g) = 0.221 W/kg



0 dB = 0.307 W/kg = -5.13 dBW/kg

APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.925 \text{ S/m}$; $\epsilon_r = 41.941$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-03-2014; Ambient Temp: 20.5°C; Tissue Temp: 20.5°C

Probe: ES3DV3 - SN3213; ConvF(6.37, 6.37, 6.37); Calibrated: 4/11/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

835MHz System Verification

Area Scan (7x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.38 W/kg

SAR(1 g) = 0.935 W/kg

Deviation: -2.81%



0 dB = 1.01 W/kg = 0.04 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 5d148

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.448 \text{ S/m}$; $\epsilon_r = 39.835$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-03-2014; Ambient Temp: 20.5°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3213; ConvF(4.99, 4.99, 4.99); Calibrated: 4/11/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

1900MHz System Verification

Area Scan (5x7x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power : 20 dBm (100 mW)

Peak SAR (extrapolated) = 7.47 W/kg

SAR(1 g) = 3.99 W/kg

Deviation: -1.97%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.407 \text{ S/m}$; $\epsilon_r = 39.798$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-17-2014; Ambient Temp: 23.9°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3287; ConvF(5.08, 5.08, 5.08); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 7.16 W/kg

SAR(1 g) = 3.93 W/kg

Deviation = 2.72%



0 dB = 5.00 W/kg = 6.99 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.773 \text{ S/m}$; $\epsilon_r = 39.159$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-14-2014; Ambient Temp: 24.2°C; Tissue Temp: 23.4°C

Probe: ES3DV3 - SN3287; ConvF(4.43, 4.43, 4.43); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 11.1 W/kg

SAR(1 g) = 5.45 W/kg

Deviation = 5.21%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 1.007 \text{ S/m}$; $\epsilon_r = 54.78$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 05-29-2014; Ambient Temp: 22.1°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3213; ConvF(6.18, 6.18, 6.18); Calibrated: 4/11/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

835MHz System Verification

Area Scan (7x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.48 W/kg

SAR(1 g) = 1 W/kg

Deviation: 4.06%



0 dB = 1.07 W/kg = 0.29 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: 835MHz SAR Validation Dipole; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 1.01 \text{ S/m}$; $\epsilon_r = 54.93$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-01-2014; Ambient Temp: 23.8°C; Tissue Temp: 23.3°C

Probe: ES3DV3 - SN3209; ConvF(6.14, 6.14, 6.14); Calibrated: 3/19/2014;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM front; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

835 MHz System Verification

Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.49 W/kg

SAR(1 g) = 1 W/kg

Deviation: 7.41%



0 dB = 1.08 W/kg = 0.33 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 5d148

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.503 \text{ S/m}$; $\epsilon_r = 53.395$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-19-2014; Ambient Temp: 23.2°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3288; ConvF(4.82, 4.82, 4.82); Calibrated: 9/23/2013;

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM Sub Dasy B; Type: SAM 5.0; Serial: TP-1626

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7164)

1900MHz System Verification

Area Scan (5x7x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 6.99 W/kg

SAR(1 g) = 4.07 W/kg

Deviation = 3.56%



0 dB = 4.50 W/kg = 6.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.031 \text{ S/m}$; $\epsilon_r = 52.62$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-14-2014; Ambient Temp: 24.4°C; Tissue Temp: 23.9°C

Probe: ES3DV3 - SN3258; ConvF(4.14, 4.14, 4.14); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (7);SEMCAD X Version 14.6.10 (7164)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power = 20 dBm (100 mW)

Peak SAR (extrapolated) = 10.3 W/kg

SAR(1 g) = 4.89 W/kg

Deviation = -1.01%



0 dB = 6.40 W/kg = 8.06 dBW/kg

APPENDIX C: PROBE CALIBRATION



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **ES3-3288_Sep13/2**

CALIBRATION CERTIFICATE (Replacement of No: ES3-3288_Sep13)

Object **ES3DV3 - SN:3288**

CCV
10/4/13

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6**
Calibration procedure for dosimetric E-field probes

Calibration date: **September 23, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	04-Apr-13 (No. 217-01733)	Apr-14
Power sensor E4412A	MY41498087	04-Apr-13 (No. 217-01733)	Apr-14
Reference 3 dB Attenuator	SN: S5054 (3c)	04-Apr-13 (No. 217-01737)	Apr-14
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-13 (No. 217-01735)	Apr-14
Reference 30 dB Attenuator	SN: S5129 (30b)	04-Apr-13 (No. 217-01738)	Apr-14
Reference Probe ES3DV2	SN: 3013	28-Dec-12 (No. ES3-3013_Dec12)	Dec-13
DAE4	SN: 660	4-Sep-13 (No. DAE4-660_Sep13)	Apr-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-15
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
			Issued: October 4, 2013
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			

Probe ES3DV3

SN:3288

Manufactured: July 6, 2010
Calibrated: September 23, 2013

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3288

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.87	0.97	0.75	$\pm 10.1 \%$
DCP (mV) ^B	103.3	103.2	100.2	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	171.1	$\pm 3.5 \%$
		Y	0.0	0.0	1.0		135.0	
		Z	0.0	0.0	1.0		154.3	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3288

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	41.9	0.89	6.56	6.56	6.56	0.32	1.89	± 12.0 %
835	41.5	0.90	6.37	6.37	6.37	0.34	1.82	± 12.0 %
1750	40.1	1.37	5.67	5.67	5.67	0.56	1.51	± 12.0 %
1900	40.0	1.40	5.47	5.47	5.47	0.80	1.29	± 12.0 %
2450	39.2	1.80	4.63	4.63	4.63	0.80	1.34	± 12.0 %
2600	39.0	1.96	4.55	4.55	4.55	0.80	1.41	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3288

Calibration Parameter Determined in Body Tissue Simulating Media


f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
750	55.5	0.96	6.25	6.25	6.25	0.70	1.27	± 12.0 %
835	55.2	0.97	6.27	6.27	6.27	0.75	1.22	± 12.0 %
1750	53.4	1.49	5.10	5.10	5.10	0.59	1.46	± 12.0 %
1900	53.3	1.52	4.82	4.82	4.82	0.53	1.54	± 12.0 %
2450	52.7	1.95	4.37	4.37	4.37	0.80	1.02	± 12.0 %
2600	52.5	2.16	4.14	4.14	4.14	0.64	0.94	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$

f=600 MHz,TEM




f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ (k=2)

Dynamic Range f(SAR_{head}) (TEM cell , f = 900 MHz)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ (k=2)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: ES3DV3 - SN:3288

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-127.1
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **ES3-3287_Nov13**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3287**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6**
Calibration procedure for dosimetric E-field probes

Calibration date: **November 20, 2013**

CC
11/20/2013

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	04-Apr-13 (No. 217-01733)	Apr-14
Power sensor E4412A	MY41498087	04-Apr-13 (No. 217-01733)	Apr-14
Reference 3 dB Attenuator	SN: S5054 (3c)	04-Apr-13 (No. 217-01737)	Apr-14
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-13 (No. 217-01735)	Apr-14
Reference 30 dB Attenuator	SN: S5129 (30b)	04-Apr-13 (No. 217-01738)	Apr-14
Reference Probe ES3DV2	SN: 3013	28-Dec-12 (No. ES3-3013_Dec12)	Dec-13
DAE4	SN: 660	4-Sep-13 (No. DAE4-660_Sep13)	Sep-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-15
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

	Name	Function	Signature
Calibrated by:	Leif Klysner	Laboratory Technician	
Approved by:	Kalja Pokovic	Technical Manager	
			Issued: November 20, 2013
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Probe ES3DV3

SN:3287

Manufactured: June 7, 2010
Calibrated: November 20, 2013

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3287

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.31	1.25	1.25	$\pm 10.1 \%$
DCP (mV) ^B	102.6	102.5	100.4	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	157.3	$\pm 2.7 \%$
		Y	0.0	0.0	1.0		159.9	
		Z	0.0	0.0	1.0		152.5	
10010-CAA	SAR Validation (Square, 100ms, 10ms)	X	2.23	57.9	9.9	10.00	45.7	$\pm 1.4 \%$
		Y	2.13	57.6	9.8		46.6	
		Z	3.31	61.1	11.8		47.6	
10011-CAA	UMTS-FDD (WCDMA)	X	3.25	66.3	17.9	2.91	124.8	$\pm 0.5 \%$
		Y	3.16	65.7	17.4		127.4	
		Z	3.15	65.5	17.4		122.8	
10012-CAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	3.08	68.7	18.3	1.87	127.2	$\pm 0.7 \%$
		Y	3.03	68.2	17.9		129.4	
		Z	2.87	67.0	17.3		126.5	
10021-DAA	GSM-FDD (TDMA, GMSK)	X	15.99	90.6	25.0	9.39	99.9	$\pm 1.2 \%$
		Y	12.41	86.6	23.6		101.5	
		Z	29.18	99.9	28.5		109.2	
10023-DAA	GPRS-FDD (TDMA, GMSK, TN 0)	X	25.67	98.9	27.8	9.57	97.9	$\pm 1.7 \%$
		Y	14.20	88.5	24.3		100.6	
		Z	27.68	99.8	28.8		107.7	
10024-DAA	GPRS-FDD (TDMA, GMSK, TN 0-1)	X	42.95	99.6	24.9	6.56	124.4	$\pm 1.4 \%$
		Y	45.27	99.9	24.8		128.8	
		Z	42.64	99.6	25.5		135.7	
10027-DAA	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	27.78	91.3	21.1	4.80	136.0	$\pm 1.4 \%$
		Y	32.74	93.9	21.9		146.6	
		Z	23.93	89.5	21.1		144.8	
10028-DAA	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	59.17	99.6	22.4	3.55	142.5	$\pm 1.2 \%$
		Y	78.76	99.7	21.7		104.9	
		Z	38.06	94.2	21.4		148.8	
10032-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	93.35	99.7	19.5	1.16	108.1	$\pm 0.9 \%$
		Y	96.67	94.0	16.9		114.7	
		Z	98.17	96.2	18.2		108.9	
10039-CAA	CDMA2000 (1xRTT, RC1)	X	4.84	66.7	18.8	4.57	126.5	$\pm 0.9 \%$
		Y	4.83	66.6	18.6		134.4	
		Z	4.76	66.0	18.3		125.9	
10081-CAA	CDMA2000 (1xRTT, RC3)	X	4.00	66.2	18.5	3.97	121.9	$\pm 0.7 \%$
		Y	3.91	65.5	17.9		128.9	
		Z	3.88	65.2	17.8		120.7	

10098-CAA	UMTS-FDD (HSUPA, Subtest 2)	X	4.66	66.6	18.4	3.98	132.5	±0.7 %
		Y	4.66	66.5	18.2		141.3	
		Z	4.54	65.9	17.9		130.7	
10100-CAB	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	6.65	68.3	20.1	5.67	139.5	±1.4 %
		Y	6.69	68.3	19.9		148.9	
		Z	6.60	67.9	19.8		137.5	
10108-CAB	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	6.52	67.8	20.0	5.80	137.3	±1.4 %
		Y	6.53	67.6	19.7		147.5	
		Z	6.51	67.6	19.8		135.3	
10110-CAB	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	6.19	67.2	19.7	5.75	134.3	±1.2 %
		Y	6.24	67.3	19.6		142.9	
		Z	6.23	67.1	19.6		132.3	
10151-CAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	11.56	79.1	27.9	9.28	130.1	±3.0 %
		Y	11.01	76.8	26.2		141.9	
		Z	12.98	81.2	28.7		135.7	
10154-CAB	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	6.25	67.4	19.8	5.75	135.1	±1.2 %
		Y	6.17	66.9	19.3		143.6	
		Z	6.16	66.8	19.4		132.8	
10160-CAB	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	6.66	67.8	20.0	5.82	140.3	±1.4 %
		Y	6.72	67.9	19.9		148.8	
		Z	6.66	67.6	19.8		137.4	
10169-CAB	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	5.05	66.7	19.5	5.73	117.8	±0.9 %
		Y	4.93	66.0	18.9		125.0	
		Z	5.08	66.3	19.3		116.3	
10172-CAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	8.47	76.8	26.9	9.21	100.3	±2.2 %
		Y	8.06	74.6	25.3		107.5	
		Z	9.43	78.2	27.4		102.5	
10175-CAB	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	4.98	66.3	19.3	5.72	118.2	±0.9 %
		Y	4.96	66.1	19.0		119.9	
		Z	5.03	66.1	19.1		116.1	
10181-CAB	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	5.06	66.7	19.6	5.72	118.7	±0.9 %
		Y	4.97	66.2	19.1		120.0	
		Z	5.03	66.1	19.1		116.3	
10225-CAA	UMTS-FDD (HSPA+)	X	6.78	66.1	18.9	5.97	105.3	±1.2 %
		Y	6.68	65.7	18.6		106.8	
		Z	7.32	67.6	19.7		148.0	
10237-CAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	8.56	77.1	27.1	9.21	100.8	±1.9 %
		Y	8.33	75.8	26.1		103.8	
		Z	9.39	78.0	27.3		101.9	
10252-CAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	10.58	77.8	27.4	9.24	123.3	±2.5 %
		Y	10.48	76.9	26.5		128.1	
		Z	11.79	79.6	28.0		127.0	
10267-CAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	11.52	79.1	27.9	9.30	130.1	±2.7 %
		Y	11.24	77.7	26.9		136.0	
		Z	12.96	81.2	28.8		134.8	

10274-CAA	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	X	6.14	67.4	19.0	4.87	145.5	±1.2 %
		Y	6.19	67.4	19.0		149.2	
		Z	6.10	66.9	18.8		142.3	
10275-CAA	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	X	4.41	66.4	18.3	3.96	126.4	±0.7 %
		Y	4.43	66.3	18.2		130.4	
		Z	4.36	65.9	18.0		123.8	
10291-AAA	CDMA2000, RC3, SO55, Full Rate	X	3.57	65.9	17.9	3.46	120.0	±0.5 %
		Y	3.55	65.6	17.6		121.7	
		Z	3.50	65.1	17.5		117.2	
10292-AAA	CDMA2000, RC3, SO32, Full Rate	X	3.55	66.1	18.0	3.39	121.3	±0.5 %
		Y	3.54	66.0	17.8		123.6	
		Z	3.45	65.2	17.4		118.9	
10297-AAA	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	6.53	67.8	20.0	5.81	136.2	±1.2 %
		Y	6.48	67.5	19.6		139.3	
		Z	6.52	67.6	19.8		134.1	
10311-AAA	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	7.12	68.4	20.4	6.06	141.7	±1.4 %
		Y	7.11	68.3	20.1		145.3	
		Z	7.14	68.4	20.3		139.8	
10315-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	X	2.79	67.6	18.0	1.71	125.5	±0.5 %
		Y	2.71	66.9	17.3		128.2	
		Z	2.64	66.2	17.0		123.5	
10403-AAA	CDMA2000 (1xEV-DO, Rev. 0)	X	4.78	67.5	18.3	3.76	130.6	±0.5 %
		Y	4.77	67.5	18.2		133.8	
		Z	4.65	66.5	17.8		130.0	
10404-AAA	CDMA2000 (1xEV-DO, Rev. A)	X	4.83	68.2	18.6	3.77	129.2	±0.7 %
		Y	4.68	67.4	18.0		131.9	
		Z	4.52	66.3	17.7		128.7	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 7 and 8).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3287

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	41.9	0.89	6.52	6.52	6.52	0.47	1.46	± 12.0 %
835	41.5	0.90	6.30	6.30	6.30	0.40	1.59	± 12.0 %
1750	40.1	1.37	5.27	5.27	5.27	0.63	1.34	± 12.0 %
1900	40.0	1.40	5.08	5.08	5.08	0.62	1.37	± 12.0 %
2450	39.2	1.80	4.43	4.43	4.43	0.79	1.28	± 12.0 %
2600	39.0	1.96	4.29	4.29	4.29	0.77	1.38	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3287

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	55.5	0.96	6.09	6.09	6.09	0.55	1.37	± 12.0 %
835	55.2	0.97	6.04	6.04	6.04	0.55	1.39	± 12.0 %
1750	53.4	1.49	4.93	4.93	4.93	0.39	1.73	± 12.0 %
1900	53.3	1.52	4.67	4.67	4.67	0.38	1.75	± 12.0 %
2450	52.7	1.95	4.17	4.17	4.17	0.60	1.20	± 12.0 %
2600	52.5	2.16	4.00	4.00	4.00	0.60	1.10	± 12.0 %


^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$

f=600 MHz,TEM





f=1800 MHz,R22



Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)


Dynamic Range f(SAR_{head})

(TEM cell , f = 900 MHz)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: ES3DV3 - SN:3287**Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	-15
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **ES3-3258_Feb14**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3258**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6**
Calibration procedure for dosimetric E-field probes

CCV
 3/6/14

Calibration date: **February 25, 2014**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	04-Apr-13 (No. 217-01733)	Apr-14
Power sensor E4412A	MY41498087	04-Apr-13 (No. 217-01733)	Apr-14
Reference 3 dB Attenuator	SN: S5054 (3c)	04-Apr-13 (No. 217-01737)	Apr-14
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-13 (No. 217-01735)	Apr-14
Reference 30 dB Attenuator	SN: S5129 (30b)	04-Apr-13 (No. 217-01738)	Apr-14
Reference Probe ES3DV2	SN: 3013	30-Dec-13 (No. ES3-3013_Dec13)	Dec-14
DAE4	SN: 660	13-Dec-13 (No. DAE4-660_Dec13)	Dec-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-16
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by:	Name Israe El-Naouq	Function Laboratory Technician	Signature
Approved by:	Katja Pokovic	Technical Manager	
			Issued: February 27, 2014
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Probe ES3DV3

SN:3258

Manufactured: January 25, 2010
Calibrated: February 25, 2014

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3258

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.29	1.19	1.23	$\pm 10.1 \%$
DCP (mV) ^B	104.5	107.0	103.0	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	222.4	$\pm 3.8 \%$
		Y	0.0	0.0	1.0		202.2	
		Z	0.0	0.0	1.0		207.1	
10010- CAA	SAR Validation (Square, 100ms, 10ms)	X	5.09	65.6	14.1	10.00	44.8	$\pm 1.9 \%$
		Y	1.68	57.4	9.3		40.7	
		Z	4.01	62.4	13.0		51.1	
10011- CAB	UMTS-FDD (WCDMA)	X	3.34	67.5	18.9	2.91	131.2	$\pm 0.5 \%$
		Y	3.43	67.9	18.7		137.1	
		Z	3.42	67.8	19.0		146.0	
10012- CAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	3.40	70.9	19.8	1.87	134.2	$\pm 0.7 \%$
		Y	3.19	70.2	19.2		137.9	
		Z	3.46	70.8	19.6		149.6	
10021- DAB	GSM-FDD (TDMA, GMSK)	X	30.24	99.7	28.7	9.39	131.2	$\pm 1.4 \%$
		Y	12.91	88.5	23.9		147.5	
		Z	30.37	99.5	28.9		128.0	
10023- DAB	GPRS-FDD (TDMA, GMSK, TN 0)	X	29.88	100.0	29.0	9.57	123.0	$\pm 1.9 \%$
		Y	16.02	92.5	25.4		140.7	
		Z	30.01	100.0	29.4		125.8	
10024- DAB	GPRS-FDD (TDMA, GMSK, TN 0-1)	X	44.57	99.7	25.9	6.56	119.6	$\pm 1.7 \%$
		Y	28.97	95.3	23.2		127.6	
		Z	43.72	99.8	26.3		120.1	
10027- DAB	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	53.52	99.7	24.4	4.80	129.4	$\pm 2.2 \%$
		Y	54.55	99.9	22.9		143.3	
		Z	51.63	99.7	24.8		127.5	
10028- DAB	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	58.93	99.8	23.4	3.55	133.4	$\pm 2.2 \%$
		Y	77.54	99.7	21.3		125.3	
		Z	56.64	99.8	23.8		130.8	
10032- CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	47.03	99.5	21.3	1.16	136.3	$\pm 1.7 \%$
		Y	95.86	95.2	17.1		138.2	
		Z	39.68	100.0	22.2		132.3	
10039- CAB	CDMA2000 (1xRTT, RC1)	X	4.84	66.8	19.1	4.57	131.3	$\pm 0.9 \%$
		Y	4.75	67.0	18.9		135.2	
		Z	4.86	66.7	19.0		127.2	

10081-CAB	CDMA2000 (1xRTT, RC3)	X	4.06	66.8	19.0	3.97	148.4	±0.7 %
		Y	3.96	66.6	18.6		134.7	
		Z	4.13	66.9	19.1		143.4	
10098-CAB	UMTS-FDD (HSUPA, Subtest 2)	X	4.63	66.8	18.7	3.98	137.3	±0.7 %
		Y	4.75	67.5	18.8		148.4	
		Z	4.65	66.7	18.7		133.2	
10100-CAB	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	6.66	68.5	20.3	5.67	144.0	±1.2 %
		Y	6.27	67.1	19.3		130.6	
		Z	6.62	68.2	20.1		140.5	
10108-CAB	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	6.53	68.0	20.2	5.80	142.6	±1.4 %
		Y	6.17	66.8	19.3		129.2	
		Z	6.52	67.8	20.1		139.0	
10110-CAB	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	6.19	67.3	19.9	5.75	137.9	±1.4 %
		Y	6.12	67.3	19.6		149.5	
		Z	6.19	67.1	19.8		136.1	
10114-CAA	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	X	10.49	69.5	21.7	8.10	132.4	±2.5 %
		Y	10.23	69.1	21.3		144.3	
		Z	10.45	69.3	21.6		129.5	
10117-CAA	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	X	10.46	69.5	21.7	8.07	133.9	±2.5 %
		Y	10.26	69.2	21.3		147.4	
		Z	10.47	69.4	21.7		130.5	
10151-CAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	11.61	77.4	26.8	9.28	118.8	±3.0 %
		Y	9.89	75.2	25.7		144.9	
		Z	12.01	77.8	26.9		119.6	
10154-CAB	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	6.20	67.3	19.9	5.75	139.2	±1.2 %
		Y	5.86	66.2	19.0		128.5	
		Z	6.22	67.3	19.9		136.3	
10160-CAB	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	6.63	67.8	20.1	5.82	144.1	±1.4 %
		Y	6.31	66.8	19.3		133.1	
		Z	6.66	67.7	20.0		140.9	
10169-CAB	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	5.25	67.5	20.2	5.73	143.6	±1.2 %
		Y	4.92	66.7	19.5		131.0	
		Z	5.29	67.4	20.2		140.7	
10172-CAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	13.49	87.5	31.6	9.21	139.0	±2.7 %
		Y	7.83	75.5	26.0		124.9	
		Z	13.47	86.5	31.1		137.8	
10175-CAB	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	5.22	67.4	20.1	5.72	144.3	±1.4 %
		Y	5.08	67.5	19.9		147.9	
		Z	5.26	67.2	20.0		139.6	
10181-CAB	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	5.24	67.5	20.1	5.72	144.5	±1.2 %
		Y	5.06	67.4	19.8		147.0	
		Z	5.29	67.3	20.1		139.2	

10193-CAA	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	X	10.12	69.1	21.6	8.09	128.8	±2.2 %
		Y	9.76	68.4	21.0		132.8	
		Z	10.08	68.9	21.5		123.4	
10196-CAA	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	X	10.15	69.2	21.7	8.10	130.2	±2.2 %
		Y	9.77	68.5	21.0		134.1	
		Z	10.10	69.0	21.5		124.0	
10219-CAA	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	X	10.02	69.0	21.5	8.03	128.7	±2.2 %
		Y	9.67	68.5	21.0		133.3	
		Z	10.02	68.9	21.5		123.9	
10222-CAA	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	X	10.46	69.6	21.7	8.06	134.0	±2.2 %
		Y	10.09	68.8	21.1		139.7	
		Z	10.40	69.3	21.6		128.7	
10225-CAB	UMTS-FDD (HSPA+)	X	7.09	67.1	19.6	5.97	131.2	±1.4 %
		Y	6.98	67.2	19.4		138.0	
		Z	7.06	66.8	19.4		127.2	
10237-CAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	13.63	87.8	31.7	9.21	141.6	±3.0 %
		Y	7.85	75.5	26.0		126.5	
		Z	13.99	87.7	31.6		141.4	
10252-CAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	12.86	81.4	28.9	9.24	142.1	±3.0 %
		Y	8.91	73.4	24.8		129.9	
		Z	13.15	81.4	28.8		142.0	
10267-CAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	11.63	77.5	26.8	9.30	118.7	±3.0 %
		Y	9.62	74.3	25.2		138.4	
		Z	11.96	77.7	26.9		119.3	
10274-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	X	6.14	67.4	19.3	4.87	149.9	±0.9 %
		Y	5.90	66.9	18.7		132.8	
		Z	6.20	67.5	19.3		146.6	
10275-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	X	4.45	66.9	18.9	3.96	130.1	±0.7 %
		Y	4.50	67.2	18.8		137.9	
		Z	4.64	67.6	19.3		149.2	
10291-AAB	CDMA2000, RC3, SO55, Full Rate	X	3.79	67.5	19.2	3.46	145.3	±0.7 %
		Y	3.74	67.5	18.9		128.2	
		Z	3.78	67.3	19.1		139.1	
10292-AAB	CDMA2000, RC3, SO32, Full Rate	X	3.77	67.8	19.3	3.39	147.0	±0.5 %
		Y	3.69	67.7	18.9		130.1	
		Z	3.73	67.3	19.0		141.3	
10297-AAA	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	6.52	67.9	20.1	5.81	141.4	±1.4 %
		Y	6.41	67.6	19.7		147.4	
		Z	6.51	67.7	20.1		135.4	
10311-AAA	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	7.17	68.7	20.7	6.06	147.7	±1.4 %
		Y	6.69	67.2	19.6		128.6	
		Z	7.12	68.4	20.5		142.0	

10315-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	X	3.04	70.0	19.6	1.71	129.8	±0.5 %
		Y	3.25	71.3	19.7		136.9	
		Z	3.09	69.9	19.5		148.7	
10403-AAB	CDMA2000 (1xEV-DO, Rev. 0)	X	4.73	67.3	18.6	3.76	135.7	±0.5 %
		Y	4.93	69.1	19.0		141.5	
		Z	4.73	67.1	18.4		132.7	
10404-AAB	CDMA2000 (1xEV-DO, Rev. A)	X	4.67	67.5	18.6	3.77	134.0	±0.5 %
		Y	4.92	69.4	19.1		139.8	
		Z	4.65	67.1	18.5		130.7	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 8 and 9).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3258

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	41.9	0.89	6.53	6.53	6.53	0.40	1.60	± 12.0 %
835	41.5	0.90	6.27	6.27	6.27	0.80	1.17	± 12.0 %
1750	40.1	1.37	5.19	5.19	5.19	0.80	1.10	± 12.0 %
1900	40.0	1.40	5.04	5.04	5.04	0.68	1.27	± 12.0 %
2450	39.2	1.80	4.52	4.52	4.52	0.78	1.23	± 12.0 %
2600	39.0	1.96	4.34	4.34	4.34	0.76	1.33	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3258

Calibration Parameter Determined in Body Tissue Simulating Media


f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	55.5	0.96	6.15	6.15	6.15	0.61	1.32	± 12.0 %
835	55.2	0.97	6.11	6.11	6.11	0.80	1.15	± 12.0 %
1750	53.4	1.49	4.83	4.83	4.83	0.47	1.74	± 12.0 %
1900	53.3	1.52	4.61	4.61	4.61	0.55	1.59	± 12.0 %
2450	52.7	1.95	4.14	4.14	4.14	0.80	1.11	± 12.0 %
2600	52.5	2.16	3.91	3.91	3.91	0.80	1.00	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.


Frequency Response of E-Field
(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM




f=1800 MHz,R22



Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)


Dynamic Range f(SAR_{head})

(TEM cell , f_{eval}= 1900 MHz)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ (k=2)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, ϑ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: ES3DV3 - SN:3258

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-123.1
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client **PC Test**

Certificate No: **ES3-3213_Apr14**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3213**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6
Calibration procedure for dosimetric E-field probes**

CCV
5/7/14

Calibration date: **April 11, 2014**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	03-Apr-14 (No. 217-01911)	Apr-15
Power sensor E4412A	MY41498087	03-Apr-14 (No. 217-01911)	Apr-15
Reference 3 dB Attenuator	SN: S5054 (3c)	03-Apr-14 (No. 217-01915)	Apr-15
Reference 20 dB Attenuator	SN: S5277 (20x)	03-Apr-14 (No. 217-01919)	Apr-15
Reference 30 dB Attenuator	SN: S5129 (30b)	03-Apr-14 (No. 217-01920)	Apr-15
Reference Probe ES3DV2	SN: 3013	30-Dec-13 (No. ES3-3013_Dec13)	Dec-14
DAE4	SN: 660	13-Dec-13 (No. DAE4-660_Dec13)	Dec-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-16
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by:	Name Leif Klysner	Function Laboratory Technician	Signature
Approved by:	Katja Pokovic	Technical Manager	
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			Issued: April 14, 2014



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Probe ES3DV3

SN:3213

Manufactured: October 14, 2008
Calibrated: April 11, 2014

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3213

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.47	1.36	1.32	$\pm 10.1 \%$
DCP (mV) ^B	102.9	101.6	102.7	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	197.4	$\pm 3.8 \%$
		Y	0.0	0.0	1.0		219.1	
		Z	0.0	0.0	1.0		195.3	
10010- CAA	SAR Validation (Square, 100ms, 10ms)	X	5.05	68.5	14.4	10.00	41.4	$\pm 0.9 \%$
		Y	9.83	75.4	16.6		39.8	
		Z	10.63	76.7	17.0		40.3	
10011- CAB	UMTS-FDD (WCDMA)	X	3.25	67.1	18.8	2.91	135.4	$\pm 0.5 \%$
		Y	3.21	66.6	18.4		131.4	
		Z	3.43	68.3	19.4		133.5	
10012- CAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	3.39	71.8	20.4	1.87	137.8	$\pm 0.7 \%$
		Y	2.98	69.1	19.1		133.1	
		Z	3.26	71.3	20.3		133.8	
10021- DAB	GSM-FDD (TDMA, GMSK)	X	22.08	99.1	27.6	9.39	143.1	$\pm 2.2 \%$
		Y	21.57	99.6	28.2		141.4	
		Z	13.61	90.9	24.9		137.1	
10023- DAB	GPRS-FDD (TDMA, GMSK, TN 0)	X	16.13	94.0	26.2	9.57	133.8	$\pm 1.9 \%$
		Y	22.39	99.7	28.1		137.8	
		Z	18.99	97.5	27.4		129.2	
10024- DAB	GPRS-FDD (TDMA, GMSK, TN 0-1)	X	21.23	93.4	23.4	6.56	148.9	$\pm 1.9 \%$
		Y	33.62	99.9	25.4		148.5	
		Z	32.72	99.7	25.1		141.6	
10027- DAB	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	49.20	99.7	23.0	4.80	138.6	$\pm 2.5 \%$
		Y	40.22	99.8	23.9		134.7	
		Z	43.82	99.8	23.4		131.9	
10028- DAB	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	50.05	99.8	22.4	3.55	146.5	$\pm 2.2 \%$
		Y	51.41	99.6	22.3		144.4	
		Z	46.36	99.5	22.4		140.0	
10032- CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	40.43	99.5	20.4	1.16	135.1	$\pm 1.7 \%$
		Y	24.55	99.5	21.7		133.5	
		Z	32.87	99.9	21.0		131.0	
10039- CAB	CDMA2000 (1xRTT, RC1)	X	4.69	66.6	19.0	4.57	133.4	$\pm 0.9 \%$
		Y	4.76	66.9	19.3		133.2	
		Z	4.71	66.8	19.2		130.1	

10081-CAB	CDMA2000 (1xRTT, RC3)	X	3.87	66.1	18.6	3.97	129.0	±0.7 %
		Y	3.89	66.1	18.7		129.6	
		Z	3.97	66.6	19.0		146.7	
10098-CAB	UMTS-FDD (HSUPA, Subtest 2)	X	4.59	66.8	18.8	3.98	141.1	±0.7 %
		Y	4.64	67.0	19.0		140.0	
		Z	4.67	67.2	19.1		138.5	
10100-CAB	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	6.52	68.0	20.1	5.67	147.5	±1.4 %
		Y	6.61	68.3	20.4		148.5	
		Z	6.51	68.0	20.1		145.4	
10108-CAB	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	6.39	67.5	19.9	5.80	145.2	±1.4 %
		Y	6.44	67.8	20.2		145.8	
		Z	6.41	67.7	20.1		145.5	
10110-CAB	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	6.02	66.7	19.5	5.75	141.3	±1.4 %
		Y	6.10	67.2	20.0		141.0	
		Z	6.05	67.0	19.8		141.2	
10114-CAA	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	X	10.19	68.9	21.4	8.10	135.6	±2.2 %
		Y	10.43	69.6	21.9		135.7	
		Z	10.21	69.0	21.5		134.5	
10117-CAA	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	X	10.17	68.9	21.3	8.07	137.7	±2.5 %
		Y	10.45	69.6	21.9		137.2	
		Z	10.22	69.1	21.5		136.9	
10151-CAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	9.70	74.8	25.8	9.28	133.6	±3.0 %
		Y	9.81	75.7	26.7		130.1	
		Z	9.49	74.4	25.7		131.6	
10154-CAB	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	6.07	67.0	19.7	5.75	142.9	±1.4 %
		Y	6.19	67.6	20.2		145.4	
		Z	6.06	67.0	19.8		141.7	
10160-CAB	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	6.50	67.5	19.9	5.82	148.5	±1.4 %
		Y	6.35	67.0	19.7		127.0	
		Z	6.52	67.6	20.0		147.9	
10169-CAB	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	5.00	66.8	19.8	5.73	145.4	±1.4 %
		Y	5.13	67.5	20.4		148.9	
		Z	5.06	67.3	20.2		144.8	
10172-CAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	9.02	79.7	28.5	9.21	148.9	±3.0 %
		Y	8.14	77.1	27.6		125.0	
		Z	8.82	79.5	28.6		147.1	
10175-CAB	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	5.05	67.2	20.0	5.72	146.2	±1.4 %
		Y	5.14	67.6	20.4		145.9	
		Z	5.00	67.1	20.1		140.8	
10181-CAB	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	5.07	67.2	20.0	5.72	149.7	±1.4 %
		Y	5.15	67.6	20.4		146.0	
		Z	5.00	67.0	20.0		141.0	

10193-CAA	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	X	9.92	68.8	21.4	8.09	135.2	±2.2 %
		Y	10.06	69.3	21.8		130.6	
		Z	9.78	68.4	21.2		126.9	
10196-CAA	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	X	9.93	68.9	21.4	8.10	136.4	±2.2 %
		Y	10.06	69.3	21.9		131.1	
		Z	9.84	68.7	21.4		128.8	
10219-CAA	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	X	9.81	68.8	21.4	8.03	135.3	±2.2 %
		Y	9.95	69.3	21.8		130.1	
		Z	9.71	68.5	21.2		127.4	
10222-CAA	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	X	10.24	69.1	21.5	8.06	141.2	±2.2 %
		Y	10.45	69.7	22.0		136.8	
		Z	10.13	68.9	21.4		133.6	
10225-CAB	UMTS-FDD (HSPA+)	X	6.95	66.9	19.5	5.97	137.9	±1.4 %
		Y	7.03	67.2	19.8		133.2	
		Z	6.92	66.9	19.5		130.6	
10237-CAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	8.08	76.6	27.0	9.21	127.8	±3.0 %
		Y	10.15	84.0	31.2		149.6	
		Z	8.67	79.0	28.3		145.4	
10252-CAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	8.92	73.6	25.3	9.24	126.0	±3.5 %
		Y	9.19	75.1	26.5		124.0	
		Z	9.66	76.2	26.8		149.1	
10267-CAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	9.59	74.5	25.7	9.30	131.9	±3.0 %
		Y	9.87	75.8	26.8		130.6	
		Z	9.36	73.9	25.5		127.8	
10274-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	X	5.84	66.6	18.8	4.87	128.6	±0.9 %
		Y	5.87	66.7	19.0		128.8	
		Z	6.08	67.6	19.4		149.9	
10275-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	X	4.35	66.6	18.8	3.96	134.0	±0.9 %
		Y	4.46	67.0	19.1		138.5	
		Z	4.39	66.8	19.0		129.4	
10291-AAB	CDMA2000, RC3, SO55, Full Rate	X	3.72	67.5	19.2	3.46	149.2	±0.7 %
		Y	3.66	67.1	19.1		129.6	
		Z	3.72	67.6	19.3		143.2	
10292-AAB	CDMA2000, RC3, SO32, Full Rate	X	3.54	66.9	18.8	3.39	128.3	±0.5 %
		Y	3.61	67.2	19.1		130.4	
		Z	3.69	67.8	19.4		146.2	
10297-AAA	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	6.38	67.4	19.9	5.81	145.8	±1.4 %
		Y	6.50	68.0	20.4		148.6	
		Z	6.35	67.4	19.9		140.8	
10311-AAA	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	6.70	67.2	19.7	6.06	127.8	±1.4 %
		Y	6.85	67.7	20.3		130.2	
		Z	6.98	68.2	20.4		147.9	

10315-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	X	2.82	69.1	19.2	1.71	135.1	±0.7 %
		Y	2.92	69.5	19.6		136.9	
		Z	3.22	71.8	20.6		130.9	
10403-AAB	CDMA2000 (1xEV-DO, Rev. 0)	X	4.77	68.3	18.9	3.76	140.0	±0.5 %
		Y	4.80	68.4	19.1		141.4	
		Z	4.86	68.9	19.3		134.8	
10404-AAB	CDMA2000 (1xEV-DO, Rev. A)	X	4.61	68.0	18.8	3.77	138.2	±0.7 %
		Y	4.67	68.2	19.0		139.3	
		Z	4.69	68.5	19.1		133.9	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 8 and 9).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3213

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	41.9	0.89	6.58	6.58	6.58	0.34	1.79	± 12.0 %
835	41.5	0.90	6.37	6.37	6.37	0.29	1.94	± 12.0 %
1750	40.1	1.37	5.18	5.18	5.18	0.79	1.17	± 12.0 %
1900	40.0	1.40	4.99	4.99	4.99	0.57	1.36	± 12.0 %
2450	39.2	1.80	4.40	4.40	4.40	0.78	1.28	± 12.0 %
2600	39.0	1.96	4.25	4.25	4.25	0.77	1.23	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3213

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	55.5	0.96	6.21	6.21	6.21	0.77	1.19	± 12.0 %
835	55.2	0.97	6.18	6.18	6.18	0.54	1.37	± 12.0 %
1750	53.4	1.49	4.89	4.89	4.89	0.73	1.27	± 12.0 %
1900	53.3	1.52	4.68	4.68	4.68	0.47	1.70	± 12.0 %
2450	52.7	1.95	4.26	4.26	4.26	0.70	1.16	± 12.0 %
2600	52.5	2.16	4.05	4.05	4.05	0.67	1.00	± 12.0 %


^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$

f=600 MHz,TEM





f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f_{\text{eval}} = 1900 \text{ MHz}$)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



Uncertainty of Spherical Isotropy Assessment: $\pm 2.6\%$ ($k=2$)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3213

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-68.3
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **ES3-3209_Mar14**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3209**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6**
Calibration procedure for dosimetric E-field probes

CCV
 3/27/14

Calibration date: **March 19, 2014**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	04-Apr-13 (No. 217-01733)	Apr-14
Power sensor E4412A	MY41498087	04-Apr-13 (No. 217-01733)	Apr-14
Reference 3 dB Attenuator	SN: S5054 (3c)	04-Apr-13 (No. 217-01737)	Apr-14
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-13 (No. 217-01735)	Apr-14
Reference 30 dB Attenuator	SN: S5129 (30b)	04-Apr-13 (No. 217-01738)	Apr-14
Reference Probe ES3DV2	SN: 3013	30-Dec-13 (No. ES3-3013_Dec13)	Dec-14
DAE4	SN: 660	13-Dec-13 (No. DAE4-660_Dec13)	Dec-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-16
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by:	Name Claudio Leubler	Function Laboratory Technician	Signature
Approved by:	Katja Pokovic	Technical Manager	
Issued: March 20, 2014			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Probe ES3DV3

SN:3209

Manufactured: October 14, 2008
Calibrated: March 19, 2014

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3209

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V/m})^2$) ^A	1.35	1.32	1.13	$\pm 10.1 \%$
DCP (mV) ^B	101.5	101.0	102.5	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^F (k=2)
0	CW	X	0.0	0.0	1.0	0.00	188.4	$\pm 3.8 \%$
		Y	0.0	0.0	1.0		180.7	
		Z	0.0	0.0	1.0		200.1	
10010-CAA	SAR Validation (Square, 100ms, 10ms)	X	2.80	64.7	12.3	10.00	43.2	$\pm 1.4 \%$
		Y	3.12	65.6	13.1		41.9	
		Z	2.67	64.0	11.7		39.4	
10011-CAB	UMTS-FDD (WCDMA)	X	3.39	67.7	19.0	2.91	149.2	$\pm 0.5 \%$
		Y	3.38	67.7	19.0		146.1	
		Z	3.35	67.6	18.7		136.1	
10012-CAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	3.01	69.8	19.4	1.87	149.4	$\pm 0.7 \%$
		Y	3.06	70.1	19.6		147.1	
		Z	2.98	69.7	19.2		136.4	
10021-DAB	GSM-FDD (TDMA, GMSK)	X	5.47	79.6	20.4	9.39	146.9	$\pm 1.7 \%$
		Y	7.76	84.9	22.9		134.2	
		Z	4.34	75.3	18.5		134.2	
10023-DAB	GPRS-FDD (TDMA, GMSK, TN 0)	X	6.66	82.9	21.6	9.57	139.8	$\pm 2.5 \%$
		Y	9.36	88.2	24.2		131.5	
		Z	4.67	76.1	18.8		144.8	
10024-DAB	GPRS-FDD (TDMA, GMSK, TN 0-1)	X	5.89	79.1	17.9	6.56	141.2	$\pm 1.9 \%$
		Y	27.58	99.6	24.8		145.8	
		Z	5.42	77.8	17.4		129.3	
10027-DAB	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	9.68	85.3	19.0	4.80	136.9	$\pm 2.2 \%$
		Y	36.47	100.0	23.3		139.2	
		Z	31.63	96.5	21.4		149.2	
10028-DAB	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	40.09	99.7	21.7	3.55	125.9	$\pm 1.9 \%$
		Y	47.92	99.6	21.7		127.6	
		Z	61.98	99.9	20.8		136.2	
10032-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	99.32	95.7	16.5	1.16	145.1	$\pm 1.7 \%$
		Y	55.30	99.5	19.3		145.6	
		Z	0.54	60.4	5.7		132.7	
10039-CAB	CDMA2000 (1xRTT, RC1)	X	4.77	67.1	19.2	4.57	145.6	$\pm 0.9 \%$
		Y	4.85	67.5	19.5		147.8	
		Z	4.67	66.7	18.9		133.4	

10081-CAB	CDMA2000 (1xRTT, RC3)	X	3.93	66.4	18.8	3.97	140.9	±0.7 %
		Y	4.02	66.9	19.1		146.0	
		Z	3.86	66.1	18.5		129.1	
10098-CAB	UMTS-FDD (HSUPA, Subtest 2)	X	4.56	66.6	18.6	3.98	132.8	±0.7 %
		Y	4.58	66.7	18.7		135.9	
		Z	4.63	67.0	18.7		143.0	
10100-CAB	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	6.42	67.5	19.8	5.67	139.3	±1.4 %
		Y	6.49	67.9	20.1		143.0	
		Z	6.18	66.7	19.3		126.9	
10108-CAB	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	6.28	67.1	19.7	5.80	136.9	±1.4 %
		Y	6.35	67.5	20.0		140.4	
		Z	6.36	67.5	19.8		147.1	
10110-CAB	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	5.94	66.5	19.4	5.75	134.0	±1.4 %
		Y	6.01	66.9	19.8		136.4	
		Z	5.99	66.8	19.5		143.6	
10114-CAA	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	X	10.02	68.5	21.1	8.10	127.2	±2.2 %
		Y	10.31	69.3	21.8		130.2	
		Z	10.12	68.8	21.2		139.0	
10117-CAA	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	X	10.03	68.5	21.1	8.07	129.2	±2.2 %
		Y	10.31	69.3	21.7		131.2	
		Z	10.15	68.9	21.3		141.0	
10151-CAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	8.54	72.4	24.8	9.28	139.6	±3.0 %
		Y	9.29	75.2	26.7		144.1	
		Z	8.55	72.5	24.7		149.7	
10154-CAB	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	5.94	66.5	19.4	5.75	134.7	±1.4 %
		Y	6.00	66.9	19.7		136.7	
		Z	6.01	66.9	19.5		143.3	
10160-CAB	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	6.40	67.1	19.7	5.82	139.9	±1.7 %
		Y	6.48	67.5	20.0		142.9	
		Z	6.43	67.3	19.7		148.7	
10169-CAB	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	4.90	66.8	19.8	5.73	136.1	±1.4 %
		Y	5.03	67.2	20.2		141.1	
		Z	5.08	67.3	20.0		148.1	
10172-CAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	6.56	72.5	25.2	9.21	125.7	±2.5 %
		Y	7.28	75.4	27.1		128.8	
		Z	6.78	73.0	25.2		138.3	
10175-CAB	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	4.86	66.6	19.7	5.72	133.7	±1.4 %
		Y	4.97	66.9	20.0		136.3	
		Z	5.04	67.2	19.9		145.7	
10181-CAB	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	4.88	66.7	19.7	5.72	133.3	±1.4 %
		Y	4.99	67.0	20.0		136.5	
		Z	5.06	67.3	19.9		145.7	

10193-CAA	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	X	10.05	69.2	21.7	8.09	146.7	±2.5 %
		Y	10.20	69.8	22.1		146.9	
		Z	9.76	68.5	21.1		132.1	
10196-CAA	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	X	10.05	69.2	21.7	8.10	148.5	±2.2 %
		Y	10.21	69.9	22.2		148.0	
		Z	9.75	68.5	21.2		133.6	
10219-CAA	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	X	9.96	69.2	21.6	8.03	148.9	±2.5 %
		Y	10.09	69.7	22.1		147.4	
		Z	9.67	68.5	21.1		133.4	
10222-CAA	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	X	10.00	68.5	21.1	8.06	127.8	±2.2 %
		Y	10.21	69.1	21.6		127.3	
		Z	10.11	68.9	21.2		140.4	
10225-CAB	UMTS-FDD (HSPA+)	X	6.81	66.5	19.3	5.97	125.8	±1.4 %
		Y	7.07	67.5	19.9		149.0	
		Z	6.92	67.0	19.4		136.8	
10237-CAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	6.62	72.8	25.3	9.21	128.5	±2.2 %
		Y	7.33	75.7	27.2		129.5	
		Z	6.87	73.4	25.5		141.8	
10252-CAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	7.92	71.5	24.4	9.24	131.3	±3.0 %
		Y	8.35	73.3	25.7		131.3	
		Z	7.94	71.6	24.3		140.2	
10267-CAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	8.52	72.3	24.8	9.30	138.8	±3.0 %
		Y	9.10	74.5	26.3		139.5	
		Z	8.53	72.3	24.6		149.4	
10274-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	X	5.98	67.1	19.1	4.87	144.4	±0.9 %
		Y	5.99	67.3	19.2		144.0	
		Z	5.80	66.6	18.7		131.0	
10275-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	X	4.51	67.2	19.0	3.96	148.6	±0.7 %
		Y	4.30	66.3	18.6		127.3	
		Z	4.40	66.9	18.7		135.9	
10291-AAB	CDMA2000, RC3, SO55, Full Rate	X	3.61	66.9	18.8	3.46	138.3	±0.7 %
		Y	3.67	67.2	19.0		140.5	
		Z	3.62	67.0	18.7		128.8	
10292-AAB	CDMA2000, RC3, SO32, Full Rate	X	3.59	67.1	18.9	3.39	141.5	±0.7 %
		Y	3.59	67.1	18.9		142.0	
		Z	3.59	67.2	18.8		130.8	
10297-AAA	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	6.27	67.0	19.7	5.81	135.3	±1.7 %
		Y	6.31	67.3	19.9		136.0	
		Z	6.36	67.4	19.8		147.2	
10311-AAA	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	6.91	67.9	20.2	6.06	141.9	±1.7 %
		Y	6.94	68.1	20.4		142.7	
		Z	6.68	67.1	19.7		130.3	

10315-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	X	2.94	69.9	19.6	1.71	148.6	±0.5 %
		Y	2.81	68.8	19.0		148.8	
		Z	2.92	69.7	19.2		138.1	
10403-AAB	CDMA2000 (1xEV-DO, Rev. 0)	X	4.76	68.7	19.1	3.76	128.0	±0.5 %
		Y	4.71	68.2	18.9		129.2	
		Z	4.85	68.8	19.0		141.9	
10404-AAB	CDMA2000 (1xEV-DO, Rev. A)	X	4.64	68.5	19.0	3.77	126.3	±0.7 %
		Y	4.60	68.2	18.9		127.9	
		Z	4.74	68.8	19.0		140.6	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 8 and 9).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3209

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	41.9	0.89	6.43	6.43	6.43	0.29	2.01	± 12.0 %
835	41.5	0.90	6.23	6.23	6.23	0.34	1.70	± 12.0 %
1750	40.1	1.37	5.24	5.24	5.24	0.80	1.13	± 12.0 %
1900	40.0	1.40	5.13	5.13	5.13	0.46	1.49	± 12.0 %
2450	39.2	1.80	4.54	4.54	4.54	0.63	1.38	± 12.0 %
2600	39.0	1.96	4.38	4.38	4.38	0.76	1.28	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3209

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	55.5	0.96	6.16	6.16	6.16	0.26	2.23	± 12.0 %
835	55.2	0.97	6.14	6.14	6.14	0.80	1.13	± 12.0 %
1750	53.4	1.49	4.85	4.85	4.85	0.59	1.42	± 12.0 %
1900	53.3	1.52	4.68	4.68	4.68	0.52	1.59	± 12.0 %
2450	52.7	1.95	4.20	4.20	4.20	0.73	1.08	± 12.0 %
2600	52.5	2.16	4.04	4.04	4.04	0.80	1.00	± 12.0 %


^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$

f=600 MHz,TEM





f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ (k=2)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f_{\text{eval}} = 1900 \text{ MHz}$)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ , θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: ES3DV3 - SN:3209

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-38.3
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D835V2-4d133_Jul13**

CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d133**

Calibration procedure(s) **QA CAL-05.v9
Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **July 17, 2013**

✓
KOK
8/12/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	01-Nov-12 (No. 217-01640)	Oct-13
Power sensor HP 8481A	US37292783	01-Nov-12 (No. 217-01640)	Oct-13
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-13 (No. 217-01736)	Apr-14
Type-N mismatch combination	SN: 5047.3 / 06327	04-Apr-13 (No. 217-01739)	Apr-14
Reference Probe ES3DV3	SN: 3205	28-Dec-12 (No. ES3-3205_Dec12)	Dec-13
DAE4	SN: 601	25-Apr-13 (No. DAE4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

	Name	Function	Signature
Calibrated by:	Leif Klysner	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: July 18, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	41.8 $\pm$ 6 %	0.92 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.44 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	9.62 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.59 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	6.28 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	54.9 $\pm$ 6 %	1.00 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.46 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	9.61 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.62 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	6.36 W/kg $\pm$ 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	52.0 Ω - 1.8 j Ω
Return Loss	- 31.8 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	48.2 Ω - 3.6 j Ω
Return Loss	- 27.7 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.395 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	July 22, 2011

DASY5 Validation Report for Head TSL

Date: 17.07.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d133

Communication System: UID 0 - CW ; Frequency: 835 MHz

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.92 \text{ S/m}$; $\epsilon_r = 41.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.05, 6.05, 6.05); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 57.188 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.66 W/kg

SAR(1 g) = 2.44 W/kg; SAR(10 g) = 1.59 W/kg

Maximum value of SAR (measured) = 2.84 W/kg




0 dB = 2.84 W/kg = 4.53 dBW/kg

Impedance Measurement Plot for Head TSL


18 Jul 2013 09:49:17
[CH1] S11 1 U FS 1: 51.957 $\angle$ -1.7539 $\angle$ 108.67 pF 835.000 000 MHz

*
De1
CA
Avg
16
H1d



CH2 S11 L00 5 dB/REF -20 dB 1:-31.772 dB 835.000 000 MHz

CA
Avg
16
H1d



DASY5 Validation Report for Body TSL

Date: 17.07.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d133

Communication System: UID 0 - CW ; Frequency: 835 MHz

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 1 \text{ S/m}$; $\epsilon_r = 54.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.04, 6.04, 6.04); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 55.351 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.59 W/kg

SAR(1 g) = 2.46 W/kg; SAR(10 g) = 1.62 W/kg

Maximum value of SAR (measured) = 2.86 W/kg




0 dB = 2.86 W/kg = 4.56 dBW/kg

Impedance Measurement Plot for Body TSL

18 Jul 2013 09:11:04
 [CH1] S11 1 U FS 1: 48.184 Ω -3.6035 Ω 52.894 pF 835.000 000 MHz

*
 Del
 CA



Avg
 16


H1d

CH2 S11 LOG 5 dB/REF -20 dB 1: -27.734 dB 835.000 000 MHz

CA

Avg
 16

H1d





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **D835V2-4d132_Jan14**

CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d132**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **January 22, 2014**

CC
21/14 ✓

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-13 (No. 217-01736)	Apr-14
Type-N mismatch combination	SN: 5047.3 / 06327	04-Apr-13 (No. 217-01739)	Apr-14
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	25-Apr-13 (No. DAE4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by: **Jeton Kastrati** Function: **Laboratory Technician** Signature:

Approved by: **Katja Pokovic** Technical Manager Signature:

Issued: January 22, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	40.6 $\pm$ 6 %	0.93 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.37 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	9.20 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.54 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	6.02 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	53.6 $\pm$ 6 %	1.01 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.41 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	9.31 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.56 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	6.08 W/kg $\pm$ 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	51.9 Ω - 1.4 j Ω
Return Loss	- 32.9 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	47.0 Ω - 2.9 j Ω
Return Loss	- 27.4 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.389 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	July 22, 2011

DASY5 Validation Report for Head TSL

Date: 22.01.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d132

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used: $f = 835$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.22, 6.22, 6.22); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 58.681 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 3.56 W/kg

SAR(1 g) = 2.37 W/kg; SAR(10 g) = 1.54 W/kg

Maximum value of SAR (measured) = 2.77 W/kg



Impedance Measurement Plot for Head TSL

22 Jan 2014 12:03:00
 CH1 S11 1 U FS 1: 51.861 $\angle$ -1.3574 $\angle$ 140.42 pF 835.000 000 MHz


*

De1

CA

Avg
16

H1d




CH2 S11 LOG 5 dB/REF -20 dB 1: -32.916 dB 835.000 000 MHz

CA

Avg
16

H1d



DASY5 Validation Report for Body TSL

Date: 20.01.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d132

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 1.007 \text{ S/m}$; $\epsilon_r = 53.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.09, 6.09, 6.09); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 54.687 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 3.57 W/kg

SAR(1 g) = 2.41 W/kg; SAR(10 g) = 1.56 W/kg

Maximum value of SAR (measured) = 2.79 W/kg




0 dB = 2.79 W/kg = 4.46 dBW/kg

Impedance Measurement Plot for Body TSL


20 Jan 2014 10:35:09
 [CH1] S11 1 U FS 2: 46.990 Ω -2.8711 Ω 66.388 pF 835.000 000 MHz

*
 De1
 CA
 Avg
 16
 H1d



CH2 S11 LOG 5 dB/REF -20 dB 21-27.356 dB 835.000 000 MHz

CA
 Avg
 16
 H1d





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **D1900V2-5d148_Feb14**

CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d148**

Calibration procedure(s) **QA CAL-05.v9**
 Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **February 27, 2014**

CCV
3/1/2014

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-13 (No. 217-01736)	Apr-14
Type-N mismatch combination	SN: 5047.3 / 06327	04-Apr-13 (No. 217-01739)	Apr-14
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	25-Apr-13 (No. DAE4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by: **Jeton Kastrati** Name
 Laboratory Technician Function

Approved by: **Katja Pokovic** Name
 Technical Manager Function

Signature

Issued: February 27, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	38.9 $\pm$ 6 %	1.39 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	10.2 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	40.7 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	5.31 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	21.2 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.3	1.52 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	52.8 $\pm$ 6 %	1.49 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	9.73 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	39.3 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.15 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	20.7 W/kg $\pm$ 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	$52.5 \Omega + 5.5 j\Omega$
Return Loss	- 24.6 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	$48.0 \Omega + 6.7 j\Omega$
Return Loss	- 23.0 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.197 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	March 11, 2011

DASY5 Validation Report for Head TSL

Date: 27.02.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d148

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.39$ S/m; $\epsilon_r = 38.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(5.06, 5.06, 5.06); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 98.796 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 18.9 W/kg

SAR(1 g) = 10.2 W/kg; SAR(10 g) = 5.31 W/kg

Maximum value of SAR (measured) = 12.8 W/kg




0 dB = 12.8 W/kg = 11.07 dBW/kg

Impedance Measurement Plot for Head TSL

27 Feb 2014 09:42:31
 [CH1] S11 1 U FS 4: 52.533 Δ 5.5234 Δ 462.67 pH 1 900.000 000 MHz


*
 De1
 CA



AVG
 16
 H1d

CH2 S11 LOG 5 dB/REF -20 dB 4:-24.552 dB 1 900.000 000 MHz

CA
 AVG
 16
 H1d



START 1 700.000 000 MHz

STOP 2 100.000 000 MHz

DASY5 Validation Report for Body TSL

Date: 27.02.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d148

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.49$ S/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.76, 4.76, 4.76); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.520 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 17.0 W/kg

SAR(1 g) = 9.73 W/kg; SAR(10 g) = 5.15 W/kg

Maximum value of SAR (measured) = 12.2 W/kg




0 dB = 12.2 W/kg = 10.86 dBW/kg

Impedance Measurement Plot for Body TSL


CH1 S11 1 U FS 4: 47.971 Ω 6.6777 Ω 559.37 pF 1 900.000 000 MHz 27 Feb 2014 09:42:04

*
De1
CA
Avg
16
H1d



CH2 S11 LOG 5 dB/REF -20 dB 4:-22.970 dB 1 900.000 000 MHz

CA
Avg
16
H1d





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D2450V2-797_Jan14**

CALIBRATION CERTIFICATE

Object **D2450V2 - SN: 797**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **January 21, 2014**

CC ✓
2/5/14

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-13 (No. 217-01736)	Apr-14
Type-N mismatch combination	SN: 5047.3 / 06327	04-Apr-13 (No. 217-01739)	Apr-14
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	25-Apr-13 (No. DAE4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

	Name	Function	Signature
Calibrated by:	Israe El-Naouq	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: January 21, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	38.7 $\pm$ 6 %	1.86 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.2 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	51.8 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.13 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.3 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	51.3 $\pm$ 6 %	2.04 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	12.7 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	49.4 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.86 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	23.1 W/kg $\pm$ 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	$53.5 \Omega + 3.2 j\Omega$
Return Loss	- 26.7 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	$50.0 \Omega + 4.9 j\Omega$
Return Loss	- 26.2 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.151 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	January 24, 2006

DASY5 Validation Report for Head TSL

Date: 21.01.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 797

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.86$ S/m; $\epsilon_r = 38.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.53, 4.53, 4.53); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 99.151 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 27.5 W/kg

SAR(1 g) = 13.2 W/kg; SAR(10 g) = 6.13 W/kg

Maximum value of SAR (measured) = 16.9 W/kg



0 dB = 16.9 W/kg = 12.28 dBW/kg


Impedance Measurement Plot for Head TSL

21 Jan 2014 11:31:52
 [CH1] S11 1 U FS 2: 53.512 $\angle$ 3.2285 $\angle$ 209.73 pH 2 450.000 000 MHz

*
 Del
 CA

Avg
 16

H1d




CH2 S11 LOG 5 dB/REF -20 dB 2:-26.730 dB 2 450.000 000 MHz

CA

Avg
 16

H1d



DASY5 Validation Report for Body TSL

Date: 21.01.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 797

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 2.04$ S/m; $\epsilon_r = 51.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.35, 4.35, 4.35); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 93.709 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 26.4 W/kg

SAR(1 g) = 12.7 W/kg; SAR(10 g) = 5.86 W/kg

Maximum value of SAR (measured) = 16.8 W/kg




0 dB = 16.8 W/kg = 12.25 dBW/kg

Impedance Measurement Plot for Body TSL

21 Jan 2014 11:31:29
CH1 S11 1 U FS 2: 49.994 Ω 4.9258 Ω 319.98 μH 2 450.000 000 MHz


*
Del
CA



Avg
16
H1d

CH2 S11 LOG 5 dB/REF -20 dB 2:-26.162 dB 2 450.000 000 MHz

CA
Avg
16
H1d



START 2 250.000 000 MHz STOP 2 450.000 000 MHz



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D1900V2-5d149_Jul13**

CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d149**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **July 22, 2013**

✓
 KOK
 8/19/13

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	01-Nov-12 (No. 217-01640)	Oct-13
Power sensor HP 8481A	US37292783	01-Nov-12 (No. 217-01640)	Oct-13
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-13 (No. 217-01736)	Apr-14
Type-N mismatch combination	SN: 5047.3 / 06327	04-Apr-13 (No. 217-01739)	Apr-14
Reference Probe ES3DV3	SN: 3205	28-Dec-12 (No. ES3-3205_Dec12)	Dec-13
DAE4	SN: 601	25-Apr-13 (No. DAE4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

	Name	Function	Signature
Calibrated by:	Jeton Kastrali	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: July 22, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- d) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	38.9 $\pm$ 6 %	1.36 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.99 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	40.4 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	5.28 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	21.3 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.3	1.52 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	53.4 $\pm$ 6 %	1.49 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	10.0 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	40.5 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.36 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.6 W/kg $\pm$ 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	$52.9 \Omega + 6.0 j\Omega$
Return Loss	- 23.8 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	$48.5 \Omega + 6.4 j\Omega$
Return Loss	- 23.5 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.196 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	March 11, 2011

DASY5 Validation Report for Head TSL

Date: 22.07.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d149

Communication System: UID 0 - CW ; Frequency: 1900 MHz

Medium parameters used: $f = 1900 \text{ MHz}$; $\sigma = 1.36 \text{ S/m}$; $\epsilon_r = 38.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.98, 4.98, 4.98); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:



Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 96.173 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 18.0 W/kg

SAR(1 g) = 9.99 W/kg; SAR(10 g) = 5.28 W/kg

Maximum value of SAR (measured) = 12.4 W/kg



0 dB = 12.4 W/kg = 10.93 dBW/kg


Impedance Measurement Plot for Head TSL

22 Jul 2013 11:59:34
 CH1 S11 1 U FS 1: 52.941 Ω 6.0059 Ω 503.09 μH 1 900.000 000 MHz

*
 Del
 CA

Avg
 16

H1d




CH2 S11 LOG 5 dB/REF -20 dB 1:-23.758 dB 1 900.000 000 MHz

CA

Avg
 16

H1d



DASY5 Validation Report for Body TSL

Date: 22.07.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d149

Communication System: UID 0 - CW ; Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.49$ S/m; $\epsilon_r = 53.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.6, 4.6, 4.6); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.173 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 17.0 W/kg

SAR(1 g) = 10 W/kg; SAR(10 g) = 5.36 W/kg

Maximum value of SAR (measured) = 12.6 W/kg




0 dB = 12.6 W/kg = 11.00 dBW/kg

Impedance Measurement Plot for Body TSL

22 Jul 2013 11:32:14
 CH1 S11 1 U FS 1: 48.525 Δ 6.3906 Δ 535.32 pH 1 900.000 000 MHz

*
 Del
 CA




Avg
 16

H1d

CH2 S11 LOG 5 dB/REF -20 dB 1: -23.547 dB 1 900.000 000 MHz

CA



Avg
 16

H1d

START 1 700.000 000 MHz

STOP 2 100.000 000 MHz

APPENDIX D: SAR TISSUE SPECIFICATIONS

Measurement Procedure for Tissue verification:

- 1) The network analyzer and probe system was configured and calibrated.
- 2) The probe was immersed in the tissue. The tissue was placed in a nonmetallic container. Trapped air bubbles beneath the flange were minimized by placing the probe at a slight angle.
- 3) The complex admittance with respect to the probe aperture was measured
- 4) The complex relative permittivity ϵ can be calculated from the below equation (Pournaropoulos and Misra):

$$Y = \frac{j2\omega\epsilon_r\epsilon_0}{[\ln(b/a)]^2} \int_a^b \int_a^b \int_0^\pi \cos\phi' \frac{\exp[-j\omega r(\mu_0\epsilon_r'\epsilon_0)^{1/2}]}{r} d\phi' d\rho' d\rho$$

where Y is the admittance of the probe in contact with the sample, the primed and unprimed coordinates refer to source and observation points, respectively, $r^2 = \rho^2 + \rho'^2 - 2\rho\rho'\cos\phi'$, ω is the angular frequency, and $j = \sqrt{-1}$.

Table D-I
Composition of the Tissue Equivalent Matter

Frequency (MHz)	835	835	1900	1900	2450	2450
Tissue	Head	Body	Head	Body	Head	Body
Ingredients (% by weight)						
Bactericide	0.1	0.1			See Page 2	
DGBE			44.92	29.44		26.7
HEC	1	1				
NaCl	1.45	0.94	0.18	0.39		0.1
Sucrose	57	44.9				
Water	40.45	53.06	54.9	70.17		73.2

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet			APPENDIX D: Page 1 of 2

2 Composition / Information on ingredients

The Item is composed of the following ingredients:

H ₂ O	Water, 52 – 75%
C ₈ H ₁₈ O ₃	Diethylene glycol monobutyl ether (DGBE), 25 – 48% (CAS-No. 112-34-5, EC-No. 203-961-6, EC-index-No. 603-096-00-8) Relevant for safety; Refer to the respective Safety Data Sheet*.
NaCl	Sodium Chloride, <1.0%

Figure D-1

Composition of 2.4 GHz Head Tissue Equivalent Matter

Note: 2.4 GHz head liquid recipes are proprietary SPEAG. Since the composition is approximate to the actual liquids utilized, the manufacturer tissue-equivalent liquid data sheets are provided below.

Measurement Certificate / Material Test

Item Name	Head Tissue Simulating Liquid (HSL2450V2)
Product No.	SL AAH 245 BA (Charge: 130212-2)
Manufacturer	SPEAG

Measurement Method

TSL dielectric parameters measured using calibrated OCP probe.

Setup Validation

Validation results were within $\pm 2.5\%$ towards the target values of Methanol.

Target Parameters

Target parameters as defined in the IEEE 1528 and IEC 62209 compliance standards.

Test Condition

Ambient	Environment temperatur (22 ± 3)°C and humidity < 70%.
TSL Temperature	23°C
Test Date	13-Feb-13
Operator	DI

Additional Information

TSL Density	0.988 g/cm ³
TSL Heat-capacity	3.680 kJ/(kg*K)

f [MHz]	Measured			Target			Diff. to Target [%]	
	HP-e*	HP-e*	sigma	eps	sigma	delta-eps	delta-sigma	
1900	40.4	11.94	1.26	40.0	1.40	1.0	-9.9	
1925	40.3	12.02	1.29	40.0	1.40	0.7	-8.0	
1950	40.2	12.11	1.31	40.0	1.40	0.5	-6.2	
1975	40.1	12.20	1.34	40.0	1.40	0.2	-4.2	
2000	40.0	12.29	1.37	40.0	1.40	-0.1	-2.3	
2025	39.9	12.39	1.40	40.0	1.42	-0.2	-1.9	
2050	39.8	12.49	1.42	39.9	1.44	-0.4	-1.4	
2075	39.6	12.57	1.45	39.9	1.47	-0.6	-1.1	
2100	39.5	12.65	1.48	39.8	1.49	-0.7	-0.7	
2125	39.4	12.74	1.51	39.8	1.51	-0.9	-0.4	
2150	39.3	12.82	1.53	39.7	1.53	-1.0	0.0	
2175	39.2	12.89	1.56	39.7	1.56	-1.2	0.3	
2200	39.1	12.97	1.59	39.6	1.58	-1.3	0.6	
2225	39.0	13.04	1.61	39.6	1.60	-1.5	0.9	
2250	38.9	13.11	1.64	39.6	1.62	-1.7	1.2	
2275	38.8	13.20	1.67	39.5	1.64	-1.8	1.6	
2300	38.7	13.28	1.70	39.5	1.67	-2.0	2.0	
2325	38.6	13.35	1.73	39.4	1.69	-2.1	2.3	
2350	38.5	13.42	1.75	39.4	1.71	-2.3	2.6	
2375	38.4	13.50	1.78	39.3	1.73	-2.4	2.9	
2400	38.3	13.58	1.81	39.3	1.76	-2.6	3.3	
2425	38.2	13.65	1.84	39.2	1.78	-2.7	3.6	
2450	38.1	13.73	1.87	39.2	1.80	-2.9	4.0	
2475	38.0	13.79	1.90	39.2	1.83	-3.1	3.9	
2500	37.9	13.85	1.93	39.1	1.85	-3.3	3.9	
2525	37.8	13.94	1.96	39.1	1.88	-3.4	4.0	
2550	37.7	14.02	1.99	39.1	1.91	-3.6	4.2	
2575	37.6	14.09	2.02	39.0	1.94	-3.8	4.3	
2600	37.5	14.17	2.05	39.0	1.96	-4.0	4.4	
2625	37.4	14.23	2.08	39.0	1.99	-4.2	4.4	
2650	37.3	14.29	2.11	38.9	2.02	-4.3	4.4	
2675	37.1	14.36	2.14	38.9	2.05	-4.5	4.5	
2700	37.0	14.43	2.17	38.9	2.07	-4.8	4.6	





Figure D-2

2.4 GHz Head Tissue Equivalent Matter

FCC ID: A3LSMT705Y	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet			APPENDIX D: Page 2 of 2

APPENDIX E: SAR SYSTEM VALIDATION

Per FCC KDB 865664 D02v01, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB 865664 D01 v01 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

Table E-I
SAR System Validation Summary

SAR SYSTEM #	FREQ. [MHz]	DATE	PROBE SN	PROBE TYPE	PROBE CAL. POINT		COND.	PERM.	CW VALIDATION			MOD. VALIDATION		
							(σ)	(ϵ_r)	SENSI- TIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
C	835	5/12/2014	3213	ES3DV3	835	Head	0.895	40.43	PASS	PASS	PASS	GMSK	PASS	N/A
C	1900	5/13/2014	3213	ES3DV3	1900	Head	1.446	39.46	PASS	PASS	PASS	GMSK	PASS	N/A
K	1900	6/16/2014	3287	ES3DV4	1900	Head	1.383	39.84	PASS	PASS	PASS	GMSK	PASS	N/A
K	2450	2/8/2014	3287	ES3DV3	2450	Head	1.832	38.03	PASS	PASS	PASS	OFDM	N/A	PASS
C	835	5/12/2014	3213	ES3DV3	835	Body	0.969	53.52	PASS	PASS	PASS	GMSK	PASS	N/A
I	835	5/7/2014	3209	ES3DV3	835	Body	1.006	53.96	PASS	PASS	PASS	GMSK	PASS	N/A
B	1900	11/4/2013	3288	ES3DV3	1900	Body	1.576	51.35	PASS	PASS	PASS	GMSK	PASS	N/A
G	2450	3/5/2014	3258	ES3DV3	2450	Body	2.044	51.30	PASS	PASS	PASS	OFDM	N/A	PASS

NOTE: While the probes have been calibrated for both CW and modulated signals, all measurements were performed using communication systems calibrated for CW signals only. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to KDB 865664.

FCC ID: A3LSMT705Y		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 04/14/14 - 06/19/14	DUT Type: Portable Tablet			APPENDIX E: Page 1 of 1

APPENDIX G: SENSOR TRIGGERING DATA SUMMARY

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 04/14/2014 – 06/19/2014	DUT Type: Portable Tablet			APPENDIX G: Page 1 of 5

A3LSMT705Y Sensor Triggering Data Summary

Per FCC KDB Publication 616217 D04v01, this device was tested by the manufacturer to determine the proximity sensor triggering distances for the back and top edge of the device. The measured output power within ± 5 mm of the triggering points (or until touching the phantom) is included for back side and each applicable edge.

To ensure all production units are compliant it is necessary to test SAR at a distance 1 mm less than the smallest distance from the device and SAR phantom (determined from these triggering tests according to the KDB 616217 D04v01) with the device at maximum output power without power reduction. These SAR Tests are included in addition to the SAR tests for the device touching the SAR phantom, with reduced power.

The operational description contains information explaining how this device remains compliant in the event of a sensor malfunction.

FCC ID: A3LSMT705Y	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Test Dates: 04/14/2014 – 06/19/2014	DUT Type: Portable Tablet	APPENDIX G: Page 2 of 5

Back Side

Moving device toward the phantom:

KDB 616217 6.2.6 Measured Power [dBm]											
Distance[mm]	21	20	19	18	17	16	15	14	13	12	11
GSM850	32.47	32.45	32.66	32.50	32.30	24.36	24.41	24.42	24.73	24.71	24.39
GSM1900	28.59	28.57	28.67	28.59	28.70	19.99	20.12	19.97	20.06	19.97	20.07
GPRS850 1Tx	32.55	32.55	32.62	32.59	32.48	24.41	24.44	24.44	24.62	24.53	24.45
GPRS850 2Tx	30.81	30.94	31.12	30.97	31.06	23.18	22.89	22.99	23.03	23.22	23.20
GPRS850 3Tx	29.44	29.46	29.26	29.44	29.37	21.43	21.33	21.35	21.28	21.36	21.44
GPRS850 4Tx	27.78	28.18	27.78	28.04	28.15	19.88	19.76	19.95	20.07	19.78	20.05
GPRS1900 1Tx	28.51	28.70	28.61	28.43	28.54	19.76	20.06	20.24	20.02	19.99	20.10
GPRS1900 2Tx	28.19	27.76	28.12	27.88	27.85	17.12	17.21	17.15	17.06	17.08	16.93
GPRS1900 3Tx	27.10	26.96	27.16	26.90	27.19	15.41	15.64	15.55	15.49	15.27	15.28
GPRS1900 4Tx	25.61	25.40	25.63	25.54	25.56	14.73	14.32	14.46	14.50	14.69	14.38
EDGE850 1Tx	26.98	27.09	26.85	27.20	26.77	20.85	20.89	21.08	21.01	20.81	20.81
EDGE850 2Tx	25.30	25.57	25.55	25.49	25.44	20.11	19.76	20.15	19.76	19.88	19.79
EDGE850 3Tx	24.22	23.99	23.94	24.09	24.13	19.20	19.14	19.08	18.87	19.13	18.93
EDGE850 4Tx	22.66	22.53	22.61	22.49	22.41	17.96	18.19	17.91	18.04	17.97	17.83
EDGE1900 1Tx	26.30	26.69	26.47	26.58	26.40	18.26	18.61	18.34	18.43	18.62	18.29
EDGE1900 2Tx	24.89	24.87	24.98	25.15	24.94	15.38	15.73	15.63	15.46	15.26	15.68
EDGE1900 3Tx	23.29	23.57	23.54	23.33	23.54	14.67	14.58	14.33	14.29	14.60	14.30
EDGE1900 4Tx	21.88	22.15	21.81	22.04	21.95	13.37	13.62	13.67	13.26	13.51	13.46
WCDMA850	22.33	22.49	22.69	22.57	22.26	15.27	15.56	15.65	15.60	15.32	15.46
WCDMA1900	22.66	22.36	22.64	22.50	22.51	11.48	11.37	11.42	11.68	11.71	11.55
LTE B5	22.30	22.35	22.43	22.36	22.64	16.12	16.13	15.96	15.95	15.93	16.17

Moving device away from the phantom:

KDB 616217 6.2.8 Measured Power [dBm]											
Distance[mm]	21	20	19	18	17	16	15	14	13	12	11
GSM850	32.58	32.39	32.53	32.41	32.33	24.60	24.25	24.45	24.63	24.71	24.71
GSM1900	28.55	28.62	28.30	28.48	28.39	19.95	20.15	19.76	20.07	19.80	20.13
GPRS850 1Tx	32.66	32.65	32.30	32.48	32.26	24.75	24.32	24.66	24.30	24.50	24.63
GPRS850 2Tx	30.95	30.85	30.90	31.22	31.03	22.97	23.13	22.97	23.10	22.90	23.09
GPRS850 3Tx	29.40	29.28	29.38	29.47	29.32	21.51	21.42	21.29	21.56	21.56	21.38
GPRS850 4Tx	27.93	28.07	27.78	28.10	27.92	19.81	19.91	20.10	20.09	20.25	19.92
GPRS1900 1Tx	28.67	28.64	28.72	28.74	28.72	20.23	19.79	19.86	20.16	20.06	19.88
GPRS1900 2Tx	27.81	28.15	28.04	28.24	27.96	17.10	16.95	17.11	17.14	17.22	16.78
GPRS1900 3Tx	27.20	26.78	26.90	27.24	27.09	15.30	15.51	15.48	15.50	15.67	15.44
GPRS1900 4Tx	25.49	25.36	25.70	25.27	25.60	14.28	14.31	14.57	14.39	14.58	14.43
EDGE850 1Tx	27.07	27.22	26.77	27.19	26.85	20.84	21.21	20.86	20.95	20.91	20.89
EDGE850 2Tx	25.44	25.68	25.41	25.65	25.62	19.92	20.22	19.87	20.01	20.00	20.14
EDGE850 3Tx	24.21	24.25	23.98	24.14	24.23	18.91	19.09	19.18	19.14	19.16	19.06
EDGE850 4Tx	22.73	22.28	22.64	22.33	22.75	18.20	17.96	17.84	17.75	17.77	18.05
EDGE1900 1Tx	26.58	26.62	26.41	26.64	26.37	18.37	18.29	18.55	18.66	18.56	18.64
EDGE1900 2Tx	25.20	25.07	24.81	24.76	25.10	15.61	15.50	15.68	15.55	15.74	15.50
EDGE1900 3Tx	23.63	23.62	23.32	23.48	23.51	14.42	14.47	14.56	14.28	14.32	14.52
EDGE1900 4Tx	22.24	22.16	22.14	22.12	22.16	13.65	13.57	13.69	13.57	13.67	13.26
WCDMA850	22.34	22.31	22.53	22.63	22.57	15.33	15.71	15.36	15.59	15.27	15.75
WCDMA1900	22.48	22.70	22.73	22.32	22.25	11.66	11.26	11.67	11.66	11.26	11.46
LTE B5	22.48	22.34	22.71	22.25	22.59	16.15	15.84	15.98	15.84	16.07	15.89

Based on the most conservative measured triggering distance of 16 mm, additional SAR measurements were required at 15 mm from the back side.

FCC ID: A3LSMT705Y	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 04/14/2014 – 06/19/2014	DUT Type: Portable Tablet			APPENDIX G: Page 3 of 5

Bottom Edge

Moving device toward the phantom:

KDB 616217 6.2.6 Measured Power [dBm]											
Distance[mm]	19	18	17	16	15	14	13	12	11	10	9
GSM850	32.73	32.51	32.43	32.59	32.46	24.39	24.25	24.25	24.75	24.30	24.27
GSM1900	28.48	28.41	28.28	28.55	28.33	19.82	19.79	20.08	19.89	20.24	19.99
GPRS850 1Tx	32.52	32.52	32.48	32.27	32.74	24.54	24.46	24.71	24.73	24.26	24.47
GPRS850 2Tx	31.03	31.06	31.17	31.16	30.86	22.85	22.80	23.23	23.25	23.09	23.08
GPRS850 3Tx	29.58	29.47	29.37	29.63	29.69	21.72	21.63	21.52	21.63	21.72	21.43
GPRS850 4Tx	28.09	28.19	27.91	28.14	28.08	19.85	19.95	19.97	20.23	20.16	20.22
GPRS1900 1Tx	28.27	28.59	28.32	28.61	28.66	19.88	20.15	19.90	20.17	19.85	20.08
GPRS1900 2Tx	28.12	28.24	28.17	27.92	28.03	17.20	16.83	16.89	17.06	17.23	17.09
GPRS1900 3Tx	27.18	26.81	26.96	27.05	26.95	15.39	15.44	15.51	15.65	15.31	15.62
GPRS1900 4Tx	25.46	25.46	25.42	25.74	25.66	14.28	14.37	14.31	14.75	14.38	14.60
EDGE850 1Tx	27.11	26.80	27.20	26.97	26.92	20.85	20.75	21.04	21.08	20.96	20.79
EDGE850 2Tx	25.69	25.70	25.26	25.31	25.37	19.92	19.85	19.90	20.06	20.05	19.95
EDGE850 3Tx	24.17	24.24	23.94	24.07	23.89	18.97	19.14	19.11	18.96	19.04	19.10
EDGE850 4Tx	22.49	22.56	22.44	22.71	22.49	18.23	17.92	18.00	17.95	18.24	17.80
EDGE1900 1Tx	26.36	26.50	26.52	26.53	26.53	18.45	18.71	18.69	18.55	18.72	18.59
EDGE1900 2Tx	24.94	25.14	24.97	25.24	25.07	15.26	15.36	15.50	15.60	15.26	15.70
EDGE1900 3Tx	23.36	23.55	23.67	23.75	23.72	14.51	14.73	14.52	14.60	14.31	14.55
EDGE1900 4Tx	22.20	21.87	21.97	22.05	22.12	13.71	13.56	13.65	13.52	13.62	13.57
WCDMA850	22.69	22.70	22.60	22.45	22.52	15.43	15.59	15.44	15.40	15.39	15.35
WCDMA1900	22.63	22.37	22.47	22.60	22.51	11.34	11.55	11.28	11.40	11.58	11.56
LTE B5	22.65	22.67	22.69	22.70	22.29	16.01	15.85	15.80	15.83	15.87	15.81

Moving device away from the phantom:

KDB 616217 6.2.8 Measured Power [dBm]											
Distance[mm]	19	18	17	16	15	14	13	12	11	10	9
GSM850	32.33	32.72	32.35	32.29	32.42	24.33	24.31	24.73	24.41	24.49	24.34
GSM1900	28.52	28.48	28.72	28.25	28.58	19.86	19.76	19.97	20.14	20.00	19.96
GPRS850 1Tx	32.28	32.55	32.43	32.39	32.44	24.53	24.74	24.51	24.74	24.57	24.48
GPRS850 2Tx	31.20	30.75	31.19	30.84	30.95	23.16	23.11	23.14	22.98	23.15	23.15
GPRS850 3Tx	29.68	29.49	29.57	29.25	29.48	21.54	21.43	21.71	21.29	21.70	21.38
GPRS850 4Tx	28.22	28.11	28.18	27.75	27.93	19.88	20.07	20.14	20.04	19.81	20.16
GPRS1900 1Tx	28.58	28.65	28.74	28.26	28.38	20.19	20.21	19.87	19.86	19.99	20.22
GPRS1900 2Tx	28.03	27.78	28.24	27.86	27.79	16.76	17.19	16.91	16.87	17.11	17.00
GPRS1900 3Tx	27.03	26.84	27.08	27.22	27.10	15.63	15.30	15.71	15.74	15.72	15.40
GPRS1900 4Tx	25.42	25.43	25.59	25.62	25.40	14.28	14.44	14.62	14.36	14.44	14.46
EDGE850 1Tx	27.16	26.88	27.08	27.05	26.79	21.00	21.09	21.23	21.05	21.11	20.85
EDGE850 2Tx	25.49	25.64	25.44	25.30	25.28	19.77	19.81	20.14	19.76	20.23	20.08
EDGE850 3Tx	23.93	24.18	24.16	24.05	23.77	19.22	19.12	18.94	19.04	18.95	18.80
EDGE850 4Tx	22.74	22.37	22.57	22.51	22.59	17.88	17.87	17.99	18.02	18.03	18.04
EDGE1900 1Tx	26.57	26.32	26.42	26.31	26.27	18.57	18.41	18.31	18.67	18.60	18.74
EDGE1900 2Tx	24.84	24.80	24.81	24.98	24.80	15.40	15.66	15.51	15.27	15.75	15.53
EDGE1900 3Tx	23.47	23.36	23.40	23.47	23.67	14.70	14.67	14.52	14.71	14.51	14.44
EDGE1900 4Tx	21.81	22.12	21.86	21.88	22.01	13.65	13.35	13.71	13.60	13.45	13.73
WCDMA850	22.56	22.42	22.52	22.30	22.30	15.35	15.52	15.46	15.31	15.72	15.26
WCDMA1900	22.39	22.58	22.53	22.29	22.26	11.32	11.59	11.31	11.44	11.34	11.55
LTE B5	22.41	22.56	22.47	22.33	22.35	16.00	15.88	15.81	15.95	16.03	16.15

Based on the most conservative measured triggering distance of 14 mm, additional SAR measurements were required at 13 mm from the bottom edge

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 04/14/2014 – 06/19/2014	DUT Type: Portable Tablet			APPENDIX G: Page 4 of 5

Right Edge

Moving device toward the phantom:

KDB 616217 6.2.6 Measured Power [dBm]											
Distance[mm]	15	16	13	12	11	10	9	8	7	6	5
GSM850	32.60	32.68	32.74	32.50	32.33	24.40	24.48	24.73	24.73	24.65	24.37
GSM1900	28.60	28.57	28.41	28.51	28.26	19.94	19.77	19.92	20.23	20.23	20.08
GPRS850 1Tx	32.43	32.71	32.48	32.60	32.72	24.45	24.59	24.70	24.56	24.58	24.59
GPRS850 2Tx	31.21	30.87	31.06	31.04	30.94	22.87	23.18	23.04	22.97	23.07	23.06
GPRS850 3Tx	29.40	29.61	29.27	29.53	29.32	21.28	21.36	21.59	21.41	21.45	21.44
GPRS850 4Tx	27.81	27.77	28.15	27.85	28.15	19.81	19.99	19.82	20.18	19.88	19.87
GPRS1900 1Tx	28.70	28.49	28.48	28.57	28.70	19.85	20.24	19.82	20.19	20.19	20.25
GPRS1900 2Tx	27.89	28.07	27.88	28.24	27.86	17.05	17.13	16.78	16.84	17.14	16.87
GPRS1900 3Tx	26.83	27.08	26.81	26.76	26.85	15.39	15.39	15.43	15.61	15.39	15.75
GPRS1900 4Tx	25.66	25.48	25.72	25.35	25.30	14.29	14.75	14.43	14.68	14.59	14.62
EDGE850 1Tx	27.02	27.07	26.98	27.03	27.21	21.14	21.18	20.81	21.09	21.19	20.89
EDGE850 2Tx	25.54	25.69	25.49	25.74	25.74	20.12	19.98	19.91	19.90	19.76	20.11
EDGE850 3Tx	24.09	23.77	24.05	23.99	24.00	19.16	19.03	18.91	19.23	18.77	18.98
EDGE850 4Tx	22.40	22.65	22.34	22.55	22.39	17.79	17.92	17.96	17.80	18.20	18.00
EDGE1900 1Tx	26.59	26.70	26.32	26.51	26.59	18.41	18.49	18.37	18.49	18.70	18.32
EDGE1900 2Tx	25.14	24.96	25.14	25.12	24.81	15.37	15.55	15.40	15.62	15.70	15.53
EDGE1900 3Tx	23.47	23.69	23.43	23.42	23.61	14.72	14.66	14.43	14.56	14.64	14.61
EDGE1900 4Tx	21.96	22.05	21.91	21.88	22.08	13.28	13.53	13.43	13.63	13.61	13.60
WCDMA850	22.46	22.70	22.63	22.52	22.25	15.61	15.34	15.53	15.65	15.56	15.33
WCDMA1900	22.44	22.65	22.38	22.49	22.55	11.44	11.41	11.64	11.56	11.60	11.54
LTE B5	22.57	22.49	22.39	22.59	22.46	16.01	16.13	16.03	16.16	16.06	15.78

Moving device away from the phantom:

KDB 616217 6.2.8 Measured Power [dBm]											
Distance[mm]	15	14	13	12	11	10	9	8	7	6	5
GSM850	32.43	32.34	32.44	32.53	32.36	24.65	24.41	24.34	24.25	24.30	24.63
GSM1900	28.59	28.56	28.66	28.33	28.67	20.06	19.88	19.87	20.25	19.99	20.4
GPRS850 1Tx	32.30	32.49	32.70	32.47	32.44	24.55	24.46	24.58	24.70	24.59	24.95
GPRS850 2Tx	31.09	31.05	31.01	31.21	30.80	23.06	22.95	22.92	22.79	22.76	23.3
GPRS850 3Tx	29.47	29.42	29.54	29.53	29.66	21.26	21.35	21.53	21.47	21.56	21.71
GPRS850 4Tx	28.13	28.13	28.00	27.89	28.12	20.02	19.87	20.19	20.08	19.88	20.15
GPRS1900 1Tx	28.72	28.51	28.47	28.51	28.60	20.21	19.77	20.04	19.79	19.77	20.22
GPRS1900 2Tx	28.16	28.04	27.96	28.19	28.01	16.86	16.96	16.83	16.76	17.02	17.4
GPRS1900 3Tx	26.92	27.12	26.83	26.76	27.17	15.59	15.51	15.57	15.43	15.51	15.85
GPRS1900 4Tx	25.58	25.56	25.47	25.44	25.71	14.66	14.26	14.68	14.46	14.69	14.7
EDGE850 1Tx	27.17	26.88	27.21	26.83	26.82	21.21	20.76	21.22	20.94	21.24	21.38
EDGE850 2Tx	25.44	25.48	25.70	25.61	25.60	19.86	20.08	20.05	20.15	19.94	20.18
EDGE850 3Tx	24.18	23.83	24.09	23.82	24.18	19.19	18.95	18.82	19.19	19.01	19.27
EDGE850 4Tx	22.52	22.34	22.59	22.50	22.41	18.11	17.92	17.99	18.07	18.01	18.1
EDGE1900 1Tx	26.48	26.70	26.60	26.67	26.67	18.59	18.71	18.35	18.65	18.44	18.62
EDGE1900 2Tx	25.02	24.77	24.94	24.82	25.21	15.56	15.60	15.43	15.26	15.54	15.63
EDGE1900 3Tx	23.71	23.37	23.29	23.59	23.29	14.58	14.33	14.30	14.37	14.54	14.77
EDGE1900 4Tx	21.91	21.90	21.98	21.95	21.79	13.63	13.36	13.43	13.34	13.53	13.72
WCDMA850	22.36	22.50	22.71	22.74	22.26	15.35	15.39	15.44	15.37	15.49	15.84
WCDMA1900	22.27	22.47	22.34	22.55	22.49	11.49	11.72	11.40	11.51	11.33	12.28
LTE B5	22.41	22.58	22.73	22.61	22.27	15.80	16.12	15.81	15.82	15.85	16.37

Based on the most conservative measured triggering distance of 10 mm, additional SAR measurements were required at 9 mm from the right edge

FCC ID: A3LSMT705Y	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 04/14/2014 – 06/19/2014	DUT Type: Portable Tablet			APPENDIX G: Page 5 of 5