


# EMC TEST REPORT

|                                                                                                                                                                             |                                |                                                                                                                                                                                                                                                                                                    |   |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|
| <b>Project No.</b>                                                                                                                                                          | LBE20200608                    | <b>Issue No.</b>                                                                                                                                                                                                                                                                                   | 0 |
| <b>Applicant</b>                                                                                                                                                            | <b>Name of organization</b>    | Samsung Electronics Co., Ltd.                                                                                                                                                                                                                                                                      |   |
|                                                                                                                                                                             | <b>Address</b>                 | (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea                                                                                                                                                                                                       |   |
|                                                                                                                                                                             | <b>Date of receipt</b>         | June 4, 2020                                                                                                                                                                                                                                                                                       |   |
| <b>EUT</b>                                                                                                                                                                  | <b>Type of device</b>          | <input checked="" type="checkbox"/> All other Receivers subject to part15<br><input checked="" type="checkbox"/> Class B Personal Computers and peripherals<br><input checked="" type="checkbox"/> Other Class B digital devices and peripherals<br><input type="checkbox"/> FM Broadcast Receiver |   |
|                                                                                                                                                                             | <b>Equipment authorization</b> | <input checked="" type="checkbox"/> Certification <input type="checkbox"/> Supplier's Declaration of Conformity                                                                                                                                                                                    |   |
|                                                                                                                                                                             | <b>FCC ID</b>                  | A3LSMT975                                                                                                                                                                                                                                                                                          |   |
|                                                                                                                                                                             | <b>Kind of product</b>         | Portable Device                                                                                                                                                                                                                                                                                    |   |
|                                                                                                                                                                             | <b>Model No.</b>               | SM-T975                                                                                                                                                                                                                                                                                            |   |
|                                                                                                                                                                             | <b>Variant Model No.</b>       | Refer to clause 4.6                                                                                                                                                                                                                                                                                |   |
|                                                                                                                                                                             | <b>Manufacturer</b>            | Samsung Electronics Vietnam Thai Nguyen Co., Ltd.<br>Yen Binh I industrial Park, Pho Yen District,<br>Thai Nguyen Province, Vietnam                                                                                                                                                                |   |
| <b>Applied Standards</b>                                                                                                                                                    |                                | 47 CFR Part 15, Subpart B, Class B / ANSI C63.4-2014                                                                                                                                                                                                                                               |   |
| <b>Test Period</b>                                                                                                                                                          |                                | June 12, 2020 ~ June 17, 2020                                                                                                                                                                                                                                                                      |   |
| <b>Issue date</b>                                                                                                                                                           |                                | June 18, 2020                                                                                                                                                                                                                                                                                      |   |
| <b>Test result : Complied</b><br><br>The equipment under test has found to be compliant with the applied standards.<br>(Refer to the attached test result for more detail.) |                                |                                                                                                                                                                                                                                                                                                    |   |
| <b>Tested by</b> : Eun-Kyung Oh<br>                                                      |                                | <b>Reviewed by</b> : Sun-Ho Kim<br>                                                                                                                                                                            |   |
| The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from Global CS Center.      |                                |                                                                                                                                                                                                                                                                                                    |   |
| <b>Samsung Electronics Co Ltd, Global CS Center</b><br>(Maetan dong) 129, Samsung-ro, Yeongtong-Gu, Suwon-Si, Gyeonggi-Do 16677, Korea                                      |                                |                                                                                                                                                                                                                                                                                                    |   |

# Table of contents

## 1. Report Information

|                            |   |
|----------------------------|---|
| 1.1 Revision history ..... | 3 |
|----------------------------|---|

## 2. Summary of test results

|                    |   |
|--------------------|---|
| 2.1 Emission ..... | 3 |
|--------------------|---|

## 3. General Information

|                         |   |
|-------------------------|---|
| 3.1 Test facility ..... | 3 |
|-------------------------|---|

## 4. Test Configuration

|                                            |    |
|--------------------------------------------|----|
| 4.1 Test Peripherals .....                 | 4  |
| 4.2 EUT operating mode .....               | 5  |
| 4.3 Details of Sampling .....              | 5  |
| 4.4 Used cable description .....           | 6  |
| 4.5 Test arrangement .....                 | 7  |
| 4.6 EUT Description .....                  | 10 |
| 4.7 EUT Frequencies .....                  | 10 |
| 4.8 Test configuration and condition ..... | 11 |
| 4.9 Measurement uncertainty .....          | 11 |

## 5. Result of individual tests

|                                 |    |
|---------------------------------|----|
| 5.1 Conducted disturbance ..... | 12 |
| 5.2 Radiated disturbance .....  | 17 |

# 1. Report Information

## 1.1 Revision history

| No.     | Date of Issue | Revised detailed information                                  |
|---------|---------------|---------------------------------------------------------------|
| Issue 0 | 18 June 2020  | There are no revisions and this version is basic test report. |

※ Remark

Compliance with Part 15B requirements for the receiver part of the licensed transmitter (equipment code CXX) is covered by other test report.

# 2. Summary of test results

## 2.1 Emission

The EUT has been tested according to the following specifications:

| Applied                             | Test type                             | Applied standard                                        | Result   |
|-------------------------------------|---------------------------------------|---------------------------------------------------------|----------|
| <input checked="" type="checkbox"/> | Conducted Disturbance<br>(Mains port) | 47 CFR Part 15 Subpart B / ANSI C63.4-2014<br>(Class B) | Complied |
| <input checked="" type="checkbox"/> | Radiated Disturbance                  |                                                         | Complied |

# 3. General Information

## 3.1 Test facility

The Global CS Center is located on Samsung Electronics Co., Ltd. at (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea. All testing are performed in Semi-anechoic chambers conforming to the site attenuation characteristics defined by ANSI C63.4, CISPR 32, CISPR 16-1-4 and Shielded rooms. And all antennas are properly calibrated using ANSI C63.5:2017.

The Global CS Center is an ISO/IEC 17025 accredited testing laboratory by the National Radio Research Agency with designation No. KR0004. for EMC testing.

## 4. Test Setup configuration

### 4.1 Test Peripherals

The cables used for these peripherals are either permanently attached by the peripheral manufacturer or coupled with an assigned cable as defined below.

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

| Mark | Description           | Model No.    | Serial No.                  | Manufacturer / Trademark | FCC ID     |
|------|-----------------------|--------------|-----------------------------|--------------------------|------------|
| A    | Portable Device       | SM-T975      | -                           | SAMSUNG                  | A3LSMT975  |
| B    | Battery               | EB-BT975ABY  | -                           | SDI                      | -          |
| C    | Headset               | GHSS028-K7   | -                           | GLONIC                   | -          |
| D    | Data Cable            | EP-DT725BBE  | -                           | RFTECH                   | -          |
| E    | Micro SD Card         | 64GB         | -                           | SAMSUNG                  | -          |
| F    | Laptop Computer       | Latitude5580 | 1CHRYM2                     | Dell                     | DoC        |
|      |                       | Latitude5580 | D3HRYM2                     | Dell                     | DoC        |
| G    | Laptop AC Adapter     | LA65NM130    | 5D77                        | Dell                     | DoC        |
|      |                       | LA65NM130    | 5B3C                        | Dell                     | DoC        |
| H    | Mouse                 | AA-SM7PCPB   | CNBA5903634ADV8<br>J31O3050 | SAMSUNG                  | DoC        |
|      |                       | SNJ-B138     | Z5F8353                     | SAMSUNG                  | DoC        |
| I    | Router                | DIR-806A     | RF0F1D8011501               | D-Link                   | DoC        |
|      |                       |              | RF0F1D8011504               | D-Link                   | DoC        |
| J    | Travel Adapter        | EP-TA200     | R37N4AA0042DK3              | SOLUEM                   | -          |
| K    | DP Monitor            | 27UD88       | 711NTQD8H004                | LG                       | DoC        |
| L    | DP Monitor AC Adapter | LCAP31       | EH8NN62949005506<br>2       | LG                       | DoC        |
| M    | DP Cable              | JCA141       | BW2K1709000770              | J5CREATE                 | DoC        |
| N    | Keyboard              | EF-DT970     | -                           | SAMSUNG                  | -          |
| O    | S-Pen                 | EJ-PT870     | -                           | WACOM                    | A3LEJPT870 |

This tablet device does not contain the minimum number of ports required for personal computer testing per ANSI C63.4, but the EUT is attached to a computer through its only available port, which represents worst case emissions. All other aspects of C63.4 testing requirements were maintained.

## 4.2 EUT operating mode

To achieve compliance applied standard specification including CXX, JAB and JBP requirement, the following mode(s) were made during compliance testing:

### 4.2.1 Conducted Emission

| No. | Operating mode                                                                    |
|-----|-----------------------------------------------------------------------------------|
| 1   | Camera (rear) + Charging (w/ TA) + Cellular receiver (LTE FDD26 Center Frequency) |
| 2   | Camera (front) + Charging (w/ TA)                                                 |
| 3   | Video + Audio playback from internal memory data + Charging (w/ TA)               |
| 4   | USB Data Communication with PC (from internal memory data)                        |

### 4.2.2 Radiated Emission

| No. | Operating mode                                                                             |
|-----|--------------------------------------------------------------------------------------------|
| 1   | Camera (rear) + Charging (w/ TA)                                                           |
| 2   | Camera (front)                                                                             |
| 3   | Video + Audio playback from internal memory data (w/ Headset)                              |
| 4   | Video + Audio playback from internal memory data + Display out (w/ USB to Direct DP cable) |
| 5   | USB Data Communication with PC (from external memory data)                                 |

## 4.3 Details of Sampling

Customer selected, single unit.


#### 4.4 Used cable description

The EUT is configured, installed, arranged and operated in a manner consistent with typical applications. Interface cables/loads/devices are connected to at least one of each type of interface port of the EUT, and where practical, each cable shall be terminated in a device typical of actual usage. The type(s) of interconnecting cables to be used and the interface port (of the EUT) to which these were connected:


| No. | Connected cable | Length [m] | Shielded [Y/N] | Note                                                        |
|-----|-----------------|------------|----------------|-------------------------------------------------------------|
| 1   | Data Cable      | 1.0        | Y              | From EUT to Laptop Computer /<br>From EUT to Travel Adapter |
| 2   | Headset         | 1.2        | N              | For EUT                                                     |
| 3   | Power           | 1.8        | N              | From Laptop Computer to AC Adapter                          |
| 4   | Power           | 1.5        | N              | For Laptop AC Adapter                                       |
| 5   | LAN             | 1.5        | N              | From Laptop Computer to Router                              |
| 6   | USB             | 0.8        | Y              | From Laptop Computer to Router for DC Power                 |
| 7   | USB             | 1.8        | Y              | From Laptop Computer to Mouse                               |
| 8   | DP Cable        | 1.1        | Y              | From DP Monitor to EUT                                      |
| 9   | Power           | 1.2        | N              | From DP Monitor to DP Monitor AC Adapter                    |
| 10  | Power           | 1.8        | N              | For DP Monitor AC Adapter                                   |

## 4.5 Test arrangement

### 4.5.1 Conducted Emission




[ Mode 1 - 3 ]




[ Mode 4 ]

## 4.5.2 Radiated Emission




[ Mode 1 ]




[ Mode 2 - 3 ]





[ Mode 4 ]



[ Mode 5 ]

## 4.6 EUT Description

The EUT is a tablet type Portable Device which can operate on GSM850/900/1800/1900, WCDMA FDD1/2/4/5/8, LTE FDD1/2/3/4/5/7/8/12/13/20/25/26/28/66, LTE TDD38/40/41 bands and incorporates a Bluetooth, Wi-Fi, Camera, GNSS, DP, Pogo pin, S-Pen and Audio and Video.

### 4.6.1 The variant models

- None

## 4.7 EUT Frequencies

| The highest frequencies<br>(Generated and used) | Frequency [ MHz ] |
|-------------------------------------------------|-------------------|
| Wi-Fi                                           | 5 825             |

## 4.8 Test configuration and condition

The system was configured for testing in a typical fashion that a customer would normally use. Cables were attached to each of the available I/O Ports. Where applicable, peripherals were attached to the I/O cables. All the external I/O ports are exercised, as well as internal and the external SD card, by writing and reading arbitrary data or charging with TA.

The EUT was investigated in three orientations and the worst case orientation is reported.

RX mode(850MHz) testing was performed with the LTE FDD26 RX Test mode at center frequency. All licensed communication (850MHz) RX mode, GSM/WCDMA/LTE, test results are not significantly different.

The video and audio were repetitively played with the earphone connected.

The video and audio were played on monitor through display out function using direct DP cable.

The camera of the EUT was operated continuously.

Power source for the EUT operating was supplied by CVCF made by the Pacific Corp.

**- Test Voltage : AC 120 V, 60 Hz**

## 4.9 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus: (According to CISPR 16-4-2 and UKAS M3003)

### 4.9.1 Emission

| Test type                             |            | Measurement uncertainty<br>(C.L. approximately 95 %, $k = 2$ ) |
|---------------------------------------|------------|----------------------------------------------------------------|
| Conducted disturbance                 | AC Mains   | 2.83 dB                                                        |
| Radiated Disturbance<br>(Below 1 GHz) | Horizontal | 4.08 dB                                                        |
|                                       | Vertical   | 4.58 dB                                                        |
| Radiated Disturbance<br>(Above 1 GHz) | Horizontal | 5.21 dB                                                        |
|                                       | Vertical   | 5.22 dB                                                        |

#### \* Remark

- 1) The values for uncertainty of conducted and radiated emissions are less than the Corresponding values of  $U_{CISPR}$  given in CISPR 55016-4-2. Therefore no adjustment of measurement results is necessary when comparing them with the relevant limits.

## 5. Results of individual test

### 5.1 Conducted disturbance

The EUT is connected to a LISN via travel adapter. If the EUT is connected to the Laptop Computer USB port, the Laptop AC adapter is connected to a LISN.

Both conducted lines are measured in Quasi-Peak and CISPR-Average mode, including the worst-case data points for each tested configuration. The EUT measured in accordance with the methods described in standards.

#### Limits for conducted disturbance at the mains ports of Class B ITE

| Frequency range Limits<br>[ MHz ] | Resolution Bandwidth<br>[ kHz ] | Limits [ dB(μV) ] |          |
|-----------------------------------|---------------------------------|-------------------|----------|
|                                   |                                 | Quasi-peak        | Average  |
| 0,15 to 0,50                      | 9                               | 66 to 56          | 56 to 46 |
| 0,50 to 5                         | 9                               | 56                | 46       |
| 5 to 30                           | 9                               | 60                | 50       |

NOTE 1 The lower limit shall apply at the transition frequency.  
NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

#### 5.1.1 Test instrumentation


| EMC No. | Test Instrument   | Model name | Manufacturer | Serial No.  | Next Calibration |                  |
|---------|-------------------|------------|--------------|-------------|------------------|------------------|
|         |                   |            |              |             | Date             | Interval (Month) |
| E5I-007 | LTE Communicator  | CMW500     | R&S          | 132729      | 2021-03-27       | 12               |
| E5I-017 | EMI Test Receiver | ESU8       | R&S          | 100483      | 2021-01-20       | 12               |
| E5I-127 | LISN              | ENV216     | R&S          | 102061      | 2020-08-01       | 12               |
| -       | Test software     | EMC32      | R&S          | Ver 9.26.01 | -                | -                |

#### 5.1.2 Temperature and humidity condition

|                   |                      |                     |                             |
|-------------------|----------------------|---------------------|-----------------------------|
| Test date         | 2020-06-17           | Test engineer       | Eun-Kyung Oh                |
| Climate condition | Ambient temperature  | (20.0 ± 0.5) °C     | Limit (15.0 to 35.0) °C     |
|                   | Relative humidity    | (57.1 ± 0.5) % R.H. | Limit (25.0 to 75.0) % R.H. |
|                   | Atmospheric pressure | (100.2 ± 0.5) kPa   | Limit (86.0 to 106.0) kPa   |
| Test place        | Shield Room (SR8)    |                     |                             |

### 5.1.3 Test results

#### ☐ Operating Mode 1: AC Mains



QP / CAV final measurement results table:

| Frequency (MHz) | QP (dBμV) | CAV (dBμV) | Limit (dBμV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|-----------|------------|--------------|-------------|------|------------|
| 0.634           | 38.46     | ---        | 56.00        | 17.54       | L1   | 10.0       |
| 0.638           | ---       | 26.18      | 46.00        | 19.82       | L1   | 10.0       |
| 0.713           | 38.85     | ---        | 56.00        | 17.15       | L1   | 10.0       |
| 0.719           | ---       | 36.17      | 46.00        | 9.83        | L1   | 10.0       |
| 0.960           | ---       | 28.77      | 46.00        | 17.23       | L1   | 9.9        |
| 0.965           | 35.67     | ---        | 56.00        | 20.33       | L1   | 9.9        |
| 3.568           | 39.81     | ---        | 56.00        | 16.19       | L1   | 9.9        |
| 3.615           | ---       | 27.95      | 46.00        | 18.05       | L1   | 9.9        |
| 3.926           | ---       | 28.21      | 46.00        | 17.79       | L1   | 9.9        |
| 4.126           | 43.91     | ---        | 56.00        | 12.09       | L1   | 9.9        |
| 13.164          | ---       | 30.91      | 50.00        | 19.09       | N    | 10.4       |
| 13.166          | 46.16     | ---        | 60.00        | 13.84       | N    | 10.4       |


Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)

Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

## □ Operating Mode 2: AC Mains



QP / CAV final measurement results table:

| Frequency (MHz) | QP (dBμV) | CAV (dBμV) | Limit (dBμV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|-----------|------------|--------------|-------------|------|------------|
| 0.632           | 36.33     | ---        | 56.00        | 19.67       | L1   | 10.0       |
| 0.638           | ---       | 34.69      | 46.00        | 11.31       | L1   | 10.0       |
| 0.713           | 38.63     | ---        | 56.00        | 17.37       | L1   | 10.0       |
| 0.717           | ---       | 35.66      | 46.00        | 10.34       | L1   | 10.0       |
| 0.958           | ---       | 28.58      | 46.00        | 17.42       | L1   | 9.9        |
| 0.962           | 33.37     | ---        | 56.00        | 22.63       | L1   | 9.9        |
| 3.608           | ---       | 27.71      | 46.00        | 18.29       | L1   | 9.9        |
| 3.642           | 40.42     | ---        | 56.00        | 15.58       | L1   | 9.9        |
| 3.917           | ---       | 28.04      | 46.00        | 17.96       | L1   | 9.9        |
| 4.119           | 42.01     | ---        | 56.00        | 13.99       | L1   | 9.9        |
| 12.824          | 45.40     | ---        | 60.00        | 14.60       | N    | 10.4       |
| 13.067          | ---       | 28.90      | 50.00        | 21.10       | N    | 10.4       |


Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)

Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

### □ Operating Mode 3: AC Mains



QP / CAV final measurement results table:

| Frequency (MHz) | QP (dBμV) | CAV (dBμV) | Limit (dBμV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|-----------|------------|--------------|-------------|------|------------|
| 0.229           | ---       | 28.63      | 52.50        | 23.87       | L1   | 9.8        |
| 0.231           | 41.62     | ---        | 62.41        | 20.79       | L1   | 9.8        |
| 0.677           | 36.57     | ---        | 56.00        | 19.43       | L1   | 10.0       |
| 0.677           | ---       | 30.64      | 46.00        | 15.36       | L1   | 10.0       |
| 3.566           | 39.18     | ---        | 56.00        | 16.82       | N    | 10.0       |
| 3.629           | ---       | 29.95      | 46.00        | 16.05       | L1   | 9.9        |
| 4.493           | ---       | 34.86      | 46.00        | 11.14       | L1   | 9.9        |
| 4.646           | 46.11     | ---        | 56.00        | 9.89        | L1   | 9.9        |
| 9.211           | ---       | 33.77      | 50.00        | 16.23       | L1   | 10.0       |
| 9.456           | 46.05     | ---        | 60.00        | 13.95       | L1   | 10.0       |
| 13.621          | 51.84     | ---        | 60.00        | 8.16        | L1   | 10.2       |
| 13.796          | ---       | 37.07      | 50.00        | 12.93       | N    | 10.4       |


Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)

Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

# ☐ Operating Mode 4: AC Mains



QP / CAV final measurement results table:

| Frequency (MHz) | QP (dB $\mu$ V) | CAV (dB $\mu$ V) | Limit (dB $\mu$ V) | Margin (dB) | Line | Corr. (dB) |
|-----------------|-----------------|------------------|--------------------|-------------|------|------------|
| 0.150           | ---             | 38.78            | 56.00              | 17.22       | N    | 9.8        |
| 0.155           | 51.66           | ---              | 65.75              | 14.09       | L1   | 9.9        |
| 0.503           | ---             | 28.05            | 46.00              | 17.95       | L1   | 10.1       |
| 0.510           | 38.39           | ---              | 56.00              | 17.61       | L1   | 10.1       |
| 1.421           | ---             | 19.61            | 46.00              | 26.39       | N    | 9.9        |
| 1.433           | 25.99           | ---              | 56.00              | 30.01       | N    | 9.9        |
| 3.491           | ---             | 22.89            | 46.00              | 23.11       | N    | 9.8        |
| 3.539           | 32.12           | ---              | 56.00              | 23.88       | L1   | 9.8        |
| 3.710           | ---             | 24.26            | 46.00              | 21.74       | N    | 9.8        |
| 3.865           | 33.93           | ---              | 56.00              | 22.07       | N    | 9.8        |
| 9.699           | ---             | 27.18            | 50.00              | 22.82       | L1   | 9.8        |
| 9.746           | 32.77           | ---              | 60.00              | 27.23       | L1   | 9.8        |

Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)

Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor



## 5.2 Radiated disturbance

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin.

Peak measurements were made over the changeable frequency range 30 MHz to 1 GHz at a measurement distance of 10 m for the following antenna and turntable arrangements:

| Antenna Height<br>[ cm ] | Antenna Polarisation | Resolution<br>Bandwidth<br>[ kHz ] | Video<br>Bandwidth<br>[ kHz ] | Turntable position<br>[ degrees ] |
|--------------------------|----------------------|------------------------------------|-------------------------------|-----------------------------------|
| 100 ~ 400                | Horizontal, Vertical | 120                                | 300                           | Continuous                        |

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using quasi-peak detector.

Peak/CISPR-Average measurements were made over the changeable frequency range 1 GHz to 40 GHz or 5th harmonics of the highest frequency generated or used in the device or on which the device operates or tunes at a measurement distance of 3 m for the following antenna and turntable arrangements. The measurements above 1 GHz were performed with the bore-sighting antenna aimed at the EUT.

| Antenna Height<br>[ cm ] | Antenna Polarisation | Resolution<br>Bandwidth<br>[ MHz ] | Video<br>Bandwidth<br>[ MHz ] | Turntable position |
|--------------------------|----------------------|------------------------------------|-------------------------------|--------------------|
| 100 ~ 400                | Horizontal, Vertical | 1                                  | 3                             | Continuous         |

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using peak and CISPR-average detectors.

**Limits for radiated disturbance of Class B ITE at a measuring distance of 3 m and 10 m**

| Frequency range Limits<br>[ MHz ] | Field Strength          |                               |                                |
|-----------------------------------|-------------------------|-------------------------------|--------------------------------|
|                                   | 3 m [ $\mu\text{V/m}$ ] | 3 m [ dB( $\mu\text{V/m}$ ) ] | 10 m [ dB( $\mu\text{V/m}$ ) ] |
| 30 to 88                          | 100                     | 40.0                          | 29.5                           |
| 88 to 216                         | 150                     | 43.5                          | 33.0                           |
| 216 to 960                        | 200                     | 46.0                          | 35.5                           |
| Above 960                         | 500                     | 54.0                          | 43.5                           |

Note) Distance correction formula from  $D_1(3\text{m})$  to  $D_2(10\text{m})$   
: Limit at  $D_2 = \text{Limit at } D_1 + 20\text{Log}(D_1 / D_2)$

Results checked manually; and points close to the limit line were re-measured.

### 5.2.1 Test instrumentation

| EMC No. | Test Instrument          | Model name | Manufacturer | Serial No.  | Next Calibration |                  |
|---------|--------------------------|------------|--------------|-------------|------------------|------------------|
|         |                          |            |              |             | Date             | Interval (Month) |
| E5I-021 | EMI Test Receiver        | ESU40      | R&S          | 100376      | 2021-01-31       | 12               |
| E5I-018 | EMI Test Receiver        | ESU8       | R&S          | 100484      | 2021-05-22       | 12               |
| E5I-036 | Horn Antenna             | HF907      | R&S          | 100507      | 2022-04-23       | 24               |
| E5I-039 | Signal Conditioning Unit | SCU-18     | R&S          | 10211       | 2021-01-23       | 12               |
| E5I-037 | WideBand Horn Antenna    | WBH 18-40K | R&S          | 11201       | 2021-01-31       | 24               |
| E5I-042 | Signal Conditioning Unit | SCU-40A    | R&S          | 10004       | 2020-09-11       | 12               |
| E5I-069 | BiLog Antenna            | CBL6112D   | TESEQ        | 35382       | 2021-08-30       | 24               |
| E5I-071 | BiLog Antenna            | CBL6112D   | TESEQ        | 35384       | 2021-08-30       | 24               |
| E5I-093 | Preamplifier             | 310N       | SONOMA       | 273122      | 2021-01-23       | 12               |
| E5I-094 | Preamplifier             | 310N       | SONOMA       | 282363      | 2021-01-23       | 12               |
| -       | Test software            | EP7RE      | TOYO         | Ver 5.8.2   | -                | -                |
| -       | Test software            | EMC32      | R&S          | Ver 9.25.00 | -                | -                |


### 5.2.2 Temperature and humidity condition

|                          |                              |                      |                             |
|--------------------------|------------------------------|----------------------|-----------------------------|
| <b>Test date</b>         | 2020-06-12                   | <b>Test engineer</b> | Eun-Kyung Oh                |
| <b>Climate condition</b> | Ambient temperature          | (23.2 ± 0.5) °C      | Limit (15.0 to 35.0) °C     |
|                          | Relative humidity            | (61.7 ± 0.5) % R.H.  | Limit (25.0 to 75.0) % R.H. |
|                          | Atmospheric pressure         | (101.0 ± 0.5) kPa    | Limit (86.0 to 106.0) kPa   |
| <b>Test place</b>        | Semi-Anechoic Chamber (SAC4) |                      |                             |

### 5.2.3 Test results

#### ☐ Operating Mode 1

#### - Frequencies below 1 GHz



#### Final Result

| No. | Frequency [MHz] | (P) | Reading QP [dB(uV)] | c.f [dB(1/m)] | Result QP [dB(uV/m)] | Limit QP [dB(uV/m)] | Margin QP [dB] | Height [cm] | Angle [deg] | System |
|-----|-----------------|-----|---------------------|---------------|----------------------|---------------------|----------------|-------------|-------------|--------|
| 1   | 30.704          | H   | 23.0                | -7.0          | 16.0                 | 29.5                | 13.5           | 176         | 23          | 1      |
| 2   | 32.414          | H   | 23.1                | -8.1          | 15.0                 | 29.5                | 14.5           | 324         | 323         | 1      |
| 3   | 40.523          | H   | 23.1                | -12.8         | 10.3                 | 29.5                | 19.2           | 270         | 284         | 1      |
| 4   | 79.552          | V   | 30.3                | -17.0         | 13.3                 | 29.5                | 16.2           | 188         | 255         | 2      |
| 5   | 970.524         | V   | 18.7                | 2.0           | 20.7                 | 43.5                | 22.8           | 275         | 339         | 2      |
| 6   | 991.984         | H   | 19.9                | 0.9           | 20.8                 | 43.5                | 22.7           | 125         | 357         | 1      |

Note1) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

## - Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters


Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 2

## - Frequencies below 1 GHz



## Final Result

| No. | Frequency [MHz] | (P) | Reading QP [dB(uV)] | c.f [dB(1/m)] | Result QP [dB(uV/m)] | Limit QP [dB(uV/m)] | Margin QP [dB] | Height [cm] | Angle [deg] | System |
|-----|-----------------|-----|---------------------|---------------|----------------------|---------------------|----------------|-------------|-------------|--------|
| 1   | 30.728          | H   | 23.0                | -7.0          | 16.0                 | 29.5                | 13.5           | 390         | 0           | 1      |
| 2   | 37.639          | H   | 22.4                | -11.2         | 11.2                 | 29.5                | 18.3           | 104         | 235         | 1      |
| 3   | 696.026         | H   | 33.4                | -3.9          | 29.5                 | 35.5                | 6.0            | 113         | 16          | 1      |
| 4   | 816.064         | H   | 31.3                | -2.0          | 29.3                 | 35.5                | 6.2            | 100         | 21          | 1      |
| 5   | 828.068         | H   | 29.7                | -2.0          | 27.7                 | 35.5                | 7.8            | 100         | 27          | 1      |
| 6   | 991.270         | V   | 18.4                | 2.6           | 21.0                 | 43.5                | 22.5           | 364         | 74          | 2      |

Note1) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

## - Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters


Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 3

## - Frequencies below 1 GHz



## Final Result

| No. | Frequency [MHz] | (P) | Reading QP [dB(uV)] | c.f [dB(1/m)] | Result QP [dB(uV/m)] | Limit QP [dB(uV/m)] | Margin QP [dB] | Height [cm] | Angle [deg] | System |
|-----|-----------------|-----|---------------------|---------------|----------------------|---------------------|----------------|-------------|-------------|--------|
| 1   | 30.000          | H   | 22.9                | -6.6          | 16.3                 | 29.5                | 13.2           | 104         | 272         | 1      |
| 2   | 30.000          | V   | 21.4                | -6.1          | 15.3                 | 29.5                | 14.2           | 100         | 69          | 2      |
| 3   | 142.156         | H   | 22.0                | -13.6         | 8.4                  | 33.0                | 24.6           | 134         | 22          | 1      |
| 4   | 873.294         | H   | 21.0                | -1.2          | 19.8                 | 35.5                | 15.7           | 127         | 193         | 1      |
| 5   | 943.255         | H   | 20.4                | -0.2          | 20.2                 | 35.5                | 15.3           | 179         | 181         | 1      |
| 6   | 998.424         | V   | 18.2                | 2.8           | 21.0                 | 43.5                | 22.5           | 182         | 341         | 2      |

Note1) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

## - Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor



☐ Operating Mode 4**- Frequencies below 1 GHz**

## Final Result

| No. | Frequency [MHz] | (P) | Reading QP [dB(uV)] | c.f [dB(1/m)] | Result QP [dB(uV/m)] | Limit QP [dB(uV/m)] | Margin QP [dB] | Height [cm] | Angle [deg] | System |
|-----|-----------------|-----|---------------------|---------------|----------------------|---------------------|----------------|-------------|-------------|--------|
| 1   | 30.694          | V   | 22.2                | -6.5          | 15.7                 | 29.5                | 13.8           | 106         | 353         | 2      |
| 2   | 375.340         | H   | 40.6                | -8.7          | 31.9                 | 35.5                | 3.6            | 194         | 153         | 1      |
| 3   | 397.407         | H   | 35.7                | -8.1          | 27.6                 | 35.5                | 7.9            | 173         | 154         | 1      |
| 4   | 486.865         | H   | 33.9                | -6.0          | 27.9                 | 35.5                | 7.6            | 195         | 206         | 1      |
| 5   | 500.918         | H   | 32.7                | -5.8          | 26.9                 | 35.5                | 8.6            | 225         | 209         | 1      |
| 6   | 861.025         | H   | 29.6                | -1.5          | 28.1                 | 35.5                | 7.4            | 101         | 241         | 1      |


Note1) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

**- Frequencies above 1 GHz**

| Frequency (MHz) | PK (dBμV) | CAV (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|-----------|--------------|----------------|-------------|-------------|-----|---------------|------------|
| 1 074.800       | ---       | 37.41        | 54.00          | 16.59       | 100.2       | H   | 169.0         | 7.1        |
| 1 075.600       | 48.08     | ---          | 74.00          | 25.92       | 101.0       | H   | 169.0         | 7.1        |
| 1 203.600       | 44.81     | ---          | 74.00          | 29.19       | 103.5       | H   | 251.0         | 7.3        |
| 1 215.600       | ---       | 34.67        | 54.00          | 19.33       | 104.3       | H   | 256.0         | 7.3        |
| 2 408.800       | 56.09     | ---          | 74.00          | 17.91       | 102.1       | H   | 231.0         | 13.8       |
| 2 408.800       | ---       | 46.93        | 54.00          | 7.07        | 103.0       | H   | 231.0         | 13.8       |
| 2 974.000       | ---       | 33.76        | 54.00          | 20.24       | 106.6       | V   | 266.0         | 16.8       |
| 2 995.200       | 44.33     | ---          | 74.00          | 29.67       | 107.2       | V   | 246.0         | 17.0       |
| 5 400.000       | ---       | 42.68        | 54.00          | 11.32       | 106.2       | H   | 124.0         | 7.3        |
| 5 400.000       | 44.92     | ---          | 74.00          | 29.08       | 106.8       | H   | 124.0         | 7.3        |
| 17 840.500      | ---       | 44.22        | 54.00          | 9.78        | 109.4       | H   | 226.0         | 35.4       |
| 17 843.000      | 50.05     | ---          | 74.00          | 23.95       | 109.9       | H   | 163.0         | 35.3       |

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters


Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 5

## - Frequencies below 1 GHz



## Final Result

| No. | Frequency [MHz] | (P) | Reading QP [dB(uV)] | c.f [dB(1/m)] | Result QP [dB(uV/m)] | Limit QP [dB(uV/m)] | Margin QP [dB] | Height [cm] | Angle [deg] | System |
|-----|-----------------|-----|---------------------|---------------|----------------------|---------------------|----------------|-------------|-------------|--------|
| 1   | 30.849          | V   | 21.7                | -6.5          | 15.2                 | 29.5                | 14.3           | 100         | 114         | 2      |
| 2   | 30.849          | H   | 23.1                | -7.1          | 16.0                 | 29.5                | 13.5           | 191         | 359         | 1      |
| 3   | 169.923         | V   | 33.3                | -13.5         | 19.8                 | 33.0                | 13.2           | 105         | 186         | 2      |
| 4   | 174.045         | V   | 38.0                | -13.6         | 24.4                 | 33.0                | 8.6            | 105         | 178         | 2      |
| 5   | 268.256         | V   | 33.5                | -9.2          | 24.3                 | 35.5                | 11.2           | 105         | 149         | 2      |
| 6   | 957.562         | V   | 18.9                | 1.7           | 20.6                 | 35.5                | 14.9           | 308         | 253         | 2      |


Note1) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

**- Frequencies above 1 GHz**

| Frequency (MHz) | PK (dBμV) | CAV (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|-----------|--------------|----------------|-------------|-------------|-----|---------------|------------|
| 1 386.800       | ---       | 27.60        | 54.00          | 26.40       | 102.1       | V   | 343.0         | 8.8        |
| 1 411.200       | 39.70     | ---          | 74.00          | 34.30       | 101.7       | V   | 343.0         | 9.0        |
| 2 126.400       | 50.75     | ---          | 74.00          | 23.25       | 105.5       | V   | 22.0          | 13.0       |
| 2 144.400       | 37.12     | ---          | 74.00          | 36.88       | 106.4       | H   | 231.0         | 12.9       |
| 2 431.600       | ---       | 31.74        | 54.00          | 22.26       | 103.1       | H   | 166.0         | 14.0       |
| 2 460.000       | 45.93     | ---          | 74.00          | 28.07       | 104.7       | H   | 53.0          | 14.2       |
| 10 027.500      | ---       | 37.84        | 54.00          | 16.16       | 103.8       | H   | 333.0         | 19.8       |
| 10 100.000      | 44.12     | ---          | 74.00          | 29.88       | 103.1       | V   | 147.0         | 19.8       |
| 14 480.000      | ---       | 41.33        | 54.00          | 12.67       | 106.2       | V   | 264.0         | 28.6       |
| 14 630.000      | 47.53     | ---          | 74.00          | 26.47       | 106.9       | V   | 58.0          | 29.7       |
| 17 818.000      | ---       | 45.15        | 54.00          | 8.85        | 108.4       | V   | 307.0         | 35.8       |
| 17 854.000      | 50.17     | ---          | 74.00          | 23.83       | 108.2       | H   | 194.0         | 35.1       |

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor