



PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

http://www.pctestlab.com



MEASUREMENT REPORT

FCC Part 22, 24 & 27

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Yeongtong-gu
Suwon-city, Gyeonggi-do, 443-803
Republic of Korea

Date of Testing:

6/26 - 7/2/2013

Test Site/Location:

PCTEST Lab., Columbia, MD, USA

Test Report Serial No.:

0Y1306201050.A3L

FCC ID:**A3LSMV100T****APPLICANT:****SAMSUNG ELECTRONICS CO., LTD.****Application Type:**

Certification

Model(s):

SM-V100T

EUT Type:

Portable Wireless Router

FCC Classification:

PCS Licensed Transmitter (PCB)

FCC Rule Part(s):

§2 §22(H) §24(E) §27(L)

Test Procedure(s):

ANSI/TIA-603-C-2004, KDB 971168 v02r01


Test Device Serial No.:

identical prototype [S/N: FK-174-C]

Mode	Tx Frequency (MHz)	Emission Designator	ERP/EIRP	
			Max. Power (W)	Max. Power (dBm)
GSM850	824.2 - 848.8	241KGXW	0.310	24.92
EDGE850	824.2 - 848.8	247KG7W	0.110	20.40
GSM1900	1850.2 - 1909.8	244KGXW	1.650	32.17
EDGE1900	1850.2 - 1909.8	244KG7W	0.782	28.93
WCDMA850	826.4 - 846.6	4M15F9W	0.060	17.75
WCDMA1700	1712.4 - 1752.5	4M15F9W	0.360	25.56
WCDMA1900	1852.4 - 1907.6	4M15F9W	0.691	28.39

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortanez
President




FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 1 of 71

TABLE OF CONTENTS


FCC PART 22, 24 & 27 MEASUREMENT REPORT	3
1.0 INTRODUCTION	4
1.1 SCOPE	4
1.2 TESTING FACILITY	4
2.0 PRODUCT INFORMATION	5
2.1 EQUIPMENT DESCRIPTION	5
2.2 DEVICE CAPABILITIES	5
2.3 TEST CONFIGURATION	5
2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS	5
3.0 DESCRIPTION OF TESTS	6
3.1 EVALUATION PROCEDURE	6
3.2 CELLULAR - BASE FREQUENCY BLOCKS	6
3.3 CELLULAR - MOBILE FREQUENCY BLOCKS	6
3.4 PCS - BASE FREQUENCY BLOCKS	6
3.5 PCS - MOBILE FREQUENCY BLOCKS	7
3.6 AWS - BASE FREQUENCY BLOCKS	7
3.7 AWS - MOBILE FREQUENCY BLOCKS	7
3.8 RADIATED MEASUREMENTS	8
4.0 TEST EQUIPMENT CALIBRATION DATA	9
5.0 SAMPLE CALCULATIONS	10
6.0 TEST RESULTS	11
6.1 SUMMARY	11
6.2 OCCUPIED BANDWIDTH	12
6.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	17
6.4 BAND EDGE EMISSIONS AT ANTENNA TERMINAL	35
6.5 PEAK-AVERAGE RATIO	43
6.6 RADIATED POWER (ERP/EIRP)	46
6.7 RADIATED SPURIOUS EMISSIONS MEASUREMENTS	50
6.8 FREQUENCY STABILITY / TEMPERATURE VARIATION	60
7.0 CONCLUSION	71

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 2 of 71



MEASUREMENT REPORT

FCC Part 22, 24 & 27




§2.1033 General Information

APPLICANT: Samsung Electronics Co., Ltd.
APPLICANT ADDRESS: 129, Samsung-ro, Yeongtong-gu
 Suwon-city, Gyeonggi-do, 443-803, Republic of Korea
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA
FCC RULE PART(S): §2 §22(H) §24(E) §27(L)
BASE MODEL: SM-V100T
FCC ID: A3LSMV100T
FCC CLASSIFICATION: PCS Licensed Transmitter (PCB)
MODE: GSM / EDGE / WCDMA
FREQUENCY TOLERANCE: $\pm 0.00025\%$ (2.5 ppm)
Test Device Serial No.: FK-174-C ☐ Production ☒ Pre-Production ☐ Engineering
DATE(S) OF TEST: 6/26 - 7/2/2013
TEST REPORT S/N: 0Y1306201050.A3L

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 3 of 71

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on February 15, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: OY1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 4 of 71

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Wireless Router FCC ID: A3LSMV100T**. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Band 4 and 17 LTE, 802.11a/b/g/n/ac WLAN

2.3 Test Configuration

The Samsung Portable Wireless Router FCC ID: A3LSMV100T was tested per the guidance of ANSI/TIA-603-C-2004 and KDB 971168 v02r01. See Section 6.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 5 of 71

3.0 DESCRIPTION OF TESTS


3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-C-2004) and “Measurement Guidance for Certification of Licensed Digital Transmitters” (KDB 971168 v02r01) were used in the measurement of the **Samsung Portable Wireless Router FCC ID: A3LSMV100T**.

Deviation from Measurement Procedure.....None

3.2 Cellular - Base Frequency Blocks

§22.905



BLOCK 1: 869 – 880 MHz (A* Low + A)


BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B*)

3.3 Cellular - Mobile Frequency Blocks

§22.905



BLOCK 1: 824 – 835 MHz (A* Low + A)


BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B*)

3.4 PCS - Base Frequency Blocks

§24.229



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)

BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 5: 1970 – 1975 MHz (F)


BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router	Page 6 of 71

3.5 PCS - Mobile Frequency Blocks

§24.229



BLOCK 1: 1850 – 1865 MHz (A)

BLOCK 4: 1885 – 1890 MHz (E)

BLOCK 2: 1865 – 1870 MHz (D)


BLOCK 5: 1890 – 1895 MHz (F)

BLOCK 3: 1870 – 1885 MHz (B)

BLOCK 6: 1895 – 1910 MHz (C)

3.6 AWS - Base Frequency Blocks

§27.5(h)



BLOCK 1: 2110 – 2120 MHz (A)

BLOCK 4: 2135 – 2140 MHz (D)

BLOCK 2: 2120 – 2130 MHz (B)


BLOCK 5: 2140 – 2145 MHz (E)

BLOCK 3: 2130 – 2135 MHz (C)

BLOCK 6: 2145 – 2155 MHz (E)

3.7 AWS - Mobile Frequency Blocks

§27.5(h)



BLOCK 1: 1710 – 1720 MHz (A)

BLOCK 4: 1735 – 1740 MHz (D)

BLOCK 2: 1720 – 1730 MHz (B)

BLOCK 5: 1740 – 1745 MHz (E)

BLOCK 3: 1730 – 1735 MHz (C)

BLOCK 6: 1745 – 1755 MHz (F)

3.8 Radiated Measurements

§2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a) §27.50(d)(10) §27.53(h) RSS-132(4.4) RSS-132(4.5.1) RSS-133(6.4) RSS-133(6.5.1) RSS-139(6.5.2)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. For the EUT positioning, "H" is defined with the EUT lying flat on the test surface, "H2" is defined with the EUT standing up on its side, and "V" is defined with the EUT standing upright.

Per the guidance of ANSI/TIA-603-C-2004, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

Radiated power levels are investigated with the receive antenna vertically polarized while radiated spurious emissions levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/TIA-603-C-2004.

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 8 of 71

4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx1	Licensed Transmitter Cable Set	1/17/2013	Annual	1/17/2014	N/A
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	3/29/2013	Annual	3/29/2014	N/A
Agilent	8447D	Broadband Amplifier	5/31/2013	Annual	5/31/2014	2443A01900
Agilent	E8267C	Vector Signal Generator	10/10/2011	Biennial	10/10/2013	US42340152
Agilent	N9020A	MXA Signal Analyzer	10/9/2012	Annual	10/9/2013	US46470561
Espec	ESX-2CA	Environmental Chamber	4/16/2013	Annual	4/16/2014	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	7/22/2011	Biennial	7/22/2013	125518
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	11/7/2012	Biennial	11/7/2014	128338
Mini-Circuits	VHF-1200+	High Pass Filter	1/17/2013	Annual	1/17/2014	30923
Mini-Circuits	VHF-3100+	High Pass Filter	1/17/2013	Annual	1/17/2014	30841
Rohde & Schwarz	CMU200	Base Station Simulator	N/A	N/A	N/A	836536/0005
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	5/31/2013	Annual	5/31/2014	100071
Rohde & Schwarz	ESU26	EMI Test Receiver	2/25/2013	Annual	2/25/2014	100342
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	11/14/2011	Biennial	11/14/2013	9105-2404
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/26/2012	Biennial	1/26/2014	A051107

Table 4-1. Test Equipment

Notes:

1. For equipment listed above that has a calibration due date that falls within the test date range, care was taken to ensure that this equipment was utilized prior to the calibration due date.
2. Equipment used for signaling with a calibration date of "N/A" shown in this list was only used for maintaining a link between the piece of equipment and the EUT. This equipment was not used to make direct calibrated measurements.

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 9 of 71

5.0 SAMPLE CALCULATIONS

GSM Emission Designator

Emission Designator = 250KGXW

GSM BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M16F9W

WCDMA BW = 4.16 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm - (-24.80) = 50.3 dBc.

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 10 of 71

6.0 TEST RESULTS

6.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMV100T
 FCC Classification: PCS Licensed Transmitter (PCB)
 Mode(s): GSM / EDGE / WCDMA

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)					
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 6.2
2.1051 22.917(a) 24.238(a) 27.53(h)	Conducted Band Edge / Spurious Emissions	> 43 + log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Sections 6.3, 6.4
24.232(d) 27.50(d.5)	Peak-Average Ratio	< 13 dB		PASS	Section 6.5
2.1046	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
2.1055 22.355 24.235 27.54	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24, 27)		PASS	Section 6.8
22.913(a.2)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 6.6
24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 6.6
27.50(d.4)	Equivalent Isotropic Radiated Power (Band 4)	< 1 Watts max. EIRP		PASS	Section 6.6
2.1053 22.917(a) 24.238(a) 27.53(h)	Radiated Spurious Emissions	> 43 + log ₁₀ (P[Watts]) for all out-of-band emissions		PASS	Section 6.7

Table 6-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation", Version 2.0.

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router	Page 11 of 71	

6.2 Occupied Bandwidth

§2.1049 RSS-Gen(4.6.1) RSS-133(2.3) RSS-139(2.3)

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 v02r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 6-1. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 12 of 71




Plot 6-1. Occupied Bandwidth Plot (Cellular GSM Mode – Ch. 190)




Plot 6-2. Occupied Bandwidth Plot (EDGE850 Mode – Ch. 190)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 13 of 71




Plot 6-3. Occupied Bandwidth Plot (PCS GSM Mode – Ch. 661)




Plot 6-4. Occupied Bandwidth Plot (EDGE1900 Mode – Ch. 661)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 14 of 71




Plot 6-5. Occupied Bandwidth Plot (Cellular WCDMA Mode – Ch. 4183)



Plot 6-6. Occupied Bandwidth Plot (AWS WCDMA Mode – Ch. 1412)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 15 of 71



Plot 6-7. Occupied Bandwidth Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 16 of 71

6.3 Spurious and Harmonic Emissions at Antenna Terminal §2.1051 §22.917(a) §24.238(a) §27.53(h) RSS-132(4.5.1) RSS-133(6.5.1) RSS-139(6.5.1)

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 v02r01 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into at least two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = RMS
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 6-2. Test Instrument & Measurement Setup


Test Notes

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22 and 1 MHz or greater for Part 24, Part 27. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 17 of 71




Plot 6-8. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)




Plot 6-9. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)

FCC ID: A3LSMV100T	 FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router	Page 18 of 71





Plot 6-10. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)






Plot 6-11. Conducted Spurious Plot (Cellular GSM Mode – Ch. 190)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 19 of 71




FCC ID: A3LSMV100T	 FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router	Page 21 of 71







Plot 6-18. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)




Plot 6-19. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)


FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 23 of 71









Plot 6-24. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 6-25. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)


FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 26 of 71









Plot 6-32. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1412)




Plot 6-33. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1862)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 30 of 71






Plot 6-36. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)




Plot 6-37. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 32 of 71



Plot 6-38. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)



Plot 6-39. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 33 of 71

6.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(h) RSS-132(4.5.1) RSS-133(6.5.1) RSS-139(6.5.1)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 v02r01 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW $\geq 1\%$ of the emission bandwidth
4. VBW $\geq 3 \times$ RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times$ Span/RBW
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 6-3. Test Instrument & Measurement Setup


Test Notes

Per 22.917(b), 24.238(b), and 27.53(h)(3), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit.

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 35 of 71




Plot 6-41. Band Edge Plot (Cellular GSM Mode – Ch. 128)




Plot 6-42. Band Edge Plot (Cellular GSM Mode – Ch. 251)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 36 of 71




Plot 6-43. Band Edge Plot (PCS GSM Mode – Ch. 512)



Plot 6-44. Band Edge Plot (PCS GSM Mode – Ch. 810)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 37 of 71




Plot 6-45. Band Edge Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 6-46. Band Edge Plot (Cellular WCDMA Mode – Ch. 4233)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 38 of 71




Plot 6-47. Band Edge Plot (AWS WCDMA Mode – Ch. 1312)




Plot 6-48. 4MHz Span Plot (AWS WCDMA Mode – Ch. 1312)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 39 of 71




Plot 6-49. Band Edge Plot (AWS WCDMA Mode – Ch. 1862)




Plot 6-50. 4MHz Span Plot (AWS WCDMA Mode – Ch. 1862)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 40 of 71




Plot 6-51. Band Edge Plot (PCS WCDMA Mode – Ch. 9262)



Plot 6-52. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9262)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 41 of 71



Plot 6-53. Band Edge Plot (PCS WCDMA Mode – Ch. 9538)



Plot 6-54. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 42 of 71

6.5 Peak-Average Ratio

§24.232(d) §27.50(d.5) RSS-132(5.4) RSS-133(6.4) RSS-139(6.4)

Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

Test Procedure Used

KDB 971168 v02r01 – Section 5.7.1

Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 6-4. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 43 of 71




Plot 6-55. Peak-Average Ratio Plot (PCS GSM Mode – Ch. 661)




Plot 6-56. Peak-Average Ratio Plot (EDGE1900 Mode – Ch. 661)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 44 of 71



Plot 6-57. Peak-Average Ratio Plot (AWS WCDMA Mode – Ch. 1412)



Plot 6-58. Peak-Average Ratio Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 45 of 71

6.6 Radiated Power (ERP/EIRP)

§22.913(a)(2) RSS-132(4.4) [SRSP-503(5.1.3)]

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 v02r01 – Section 5.2.1

ANSI/TIA-603-C-2004 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer's "time domain power" measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $\geq 2 \times$ span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the "gating" function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 46 of 71

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-5. Test Instrument & Measurement Setup

Test Notes

- 1) This device was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, HSUPA, and GSM/GPRS/EDGE capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This unit was tested with its standard battery.
- 4) The worst case test configuration was found in the EUT in the H2 positioning for cellular WCDMA and V positioning for all other modes tested. The data reported in the tables below was measured in this test setup.

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 47 of 71

Frequency [MHz]	Mode	Battery Type	Substitute Level [dBm]	Antenna Gain [dBd]	EUT Pol [H/V]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
824.20	GSM850	Standard	26.07	-1.15	V	24.92	0.310	38.45	-13.53
836.60	GSM850	Standard	23.58	-1.15	V	22.43	0.175	38.45	-16.02
848.80	GSM850	Standard	21.57	-1.15	V	20.42	0.110	38.45	-18.03
824.20	EDGE850	Standard	21.55	-1.15	V	20.40	0.110	38.45	-18.05

Table 6-2. ERP (Cellular GSM)

Frequency [MHz]	Mode	Battery Type	Substitute Level [dBm]	Antenna Gain [dBd]	EUT Pol [H/V]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
826.40	WCDMA850	Standard	18.90	-1.15	H2	17.75	0.060	38.45	-20.70
836.60	WCDMA850	Standard	16.61	-1.15	H2	15.46	0.035	38.45	-22.99
846.60	WCDMA850	Standard	16.22	-1.15	H2	15.07	0.032	38.45	-23.38

Table 6-4. ERP (Cellular WCDMA)

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)						Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router						Page 48 of 71

Frequency [MHz]	Mode	Battery Type	Substitute Level [dBm]	Antenna Gain [dBi]	EUT Pol [H/V]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1712.40	WCDMA1700	Standard	15.36	9.89	V	25.25	0.335	30.00	-4.75
1732.50	WCDMA1700	Standard	15.71	9.85	V	25.56	0.360	30.00	-4.44
1752.50	WCDMA1700	Standard	14.73	9.81	V	24.54	0.284	30.00	-5.46

Table 6-3. EIRP (AWS WCDMA)

Frequency [MHz]	Mode	Battery Type	Substitute Level [dBm]	Antenna Gain [dBi]	EUT Pol [H/V]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1850.20	GSM1900	Standard	22.15	7.97	V	30.12	1.029	33.01	-2.89
1880.00	GSM1900	Standard	24.15	8.02	V	32.17	1.650	33.01	-0.84
1909.80	GSM1900	Standard	21.98	8.11	V	30.09	1.020	33.01	-2.92
1880.00	EDGE1900	Standard	20.70	8.23	V	28.93	0.782	33.01	-4.08

Table 6-4. EIRP (PCS GSM)

Frequency [MHz]	Mode	Battery Type	Substitute Level [dBm]	Antenna Gain [dBi]	EUT Pol [H/V]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1852.40	WCDMA1900	Standard	18.80	9.59	V	28.39	0.691	33.01	-4.62
1880.00	WCDMA1900	Standard	16.64	9.53	V	26.17	0.414	33.01	-6.84
1907.60	WCDMA1900	Standard	17.96	9.48	V	27.44	0.554	33.01	-5.57

Table 6-4. EIRP (PCS WCDMA)

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)							Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router							Page 49 of 71

6.7 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a) RSS-132(4.5.1)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 v02r01 – Section 5.8

ANSI/TIA-603-C-2004 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-6. Test Instrument & Measurement Setup

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 50 of 71

Test Notes

- 1) This device was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, HSUPA, and GSM/GPRS/EDGE capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This unit was tested with its standard battery.
- 4) The worst case test configuration was found in the EUT in the H positioning. The data reported in the tables below was measured in this test setup.
- 5) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
- 6) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 7) Peak levels at -125dBm represent the analyzer noise floor and signify that no emission was detected.

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 51 of 71

OPERATING FREQUENCY: 824.20 MHz
 CHANNEL: 128
 MEASURED OUTPUT POWER: 24.92 dBm = 0.310 W
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.92 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
1648.40	-54.77	2.60	-52.17	H	77.1
2472.60	-49.02	2.90	-46.13	H	71.0
3296.80	-54.95	5.44	-49.51	H	74.4
4121.00	-52.06	7.05	-45.01	H	69.9
4945.20	-54.21	7.86	-46.34	H	71.3

Table 6-5. Radiated Spurious Data (Cellular GSM Mode – Ch. 128)

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 190
 MEASURED OUTPUT POWER: 22.43 dBm = 0.175 W
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 35.43 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
1673.20	-50.78	2.34	-48.44	H	70.9
2509.80	-47.91	2.84	-45.07	H	67.5
3346.40	-54.18	5.64	-48.54	H	71.0
4183.00	-55.35	7.15	-48.21	H	70.6
5019.60	-54.41	7.97	-46.45	H	68.9

Table 6-6. Radiated Spurious Data (Cellular GSM Mode – Ch. 190)

OPERATING FREQUENCY: 848.80 MHz
 CHANNEL: 251
 MEASURED OUTPUT POWER: 20.42 dBm = 0.110 W
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 33.42 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
1697.60	-47.61	2.08	-45.53	H	66.0
2546.40	-50.20	3.17	-47.03	H	67.4
3395.20	-55.96	5.84	-50.12	H	70.5
4244.00	-55.28	7.24	-48.04	H	68.5
5092.80	-55.04	8.03	-47.02	H	67.4

Table 6-7. Radiated Spurious Data (Cellular GSM Mode – Ch. 251)

OPERATING FREQUENCY: 826.40 MHz
 CHANNEL: 4132
 MEASURED OUTPUT POWER: 17.75 dBm = 0.060 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 30.75 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
1652.80	-57.17	6.32	-50.85	H	68.6
2479.20	-53.02	6.58	-46.43	H	64.2
3305.60	-53.10	6.99	-46.11	H	63.9
4132.00	-52.55	7.67	-44.88	H	62.6
4958.40	-53.48	9.07	-44.42	H	62.2

Table 6-8. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 53 of 71

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 4183
 MEASURED OUTPUT POWER: 15.46 dBm = 0.035 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 28.46 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
1673.20	-53.38	6.21	-47.17	H	62.6
2509.80	-53.18	6.56	-46.62	H	62.1
3346.40	-52.79	7.13	-45.66	H	61.1
4183.00	-53.02	7.94	-45.08	H	60.5
5019.60	-52.96	8.99	-43.97	H	59.4

Table 6-9. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4183)

OPERATING FREQUENCY: 846.60 MHz
 CHANNEL: 4233
 MEASURED OUTPUT POWER: 15.07 dBm = 0.032 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 28.07 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
1693.20	-51.76	6.06	-45.71	H	60.8
2539.80	-54.49	6.69	-47.80	H	62.9
3386.40	-53.19	7.32	-45.87	H	60.9
4233.00	-54.06	8.23	-45.83	H	60.9
5079.60	-53.10	8.86	-44.24	H	59.3

Table 6-10. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)

OPERATING FREQUENCY: 1712.40 MHz
 CHANNEL: 1312
 MEASURED OUTPUT POWER: 25.25 dBm = 0.335 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 38.25 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
3424.80	-47.97	9.57	-38.40	H	63.6
5137.20	-52.58	10.95	-41.62	H	66.9
6849.60	-49.01	10.78	-38.23	H	63.5
8562.00	-45.26	11.23	-34.03	H	59.3
10274.40	-45.62	12.52	-33.11	H	58.4

Table 6-11. Radiated Spurious Data (AWS WCDMA Mode – Ch. 9262)

OPERATING FREQUENCY: 1732.50 MHz
 CHANNEL: 1412
 MEASURED OUTPUT POWER: 25.56 dBm = 0.360 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 38.56 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
3465.00	-50.03	9.63	-40.40	H	66.0
5197.50	-49.03	10.93	-38.10	H	63.7
6930.00	-48.62	10.88	-37.74	H	63.3
8662.50	-45.80	11.44	-34.35	H	59.9
10395.00	-45.08	12.58	-32.51	H	58.1

Table 6-12. Radiated Spurious Data (AWS WCDMA Mode – Ch. 9400)

OPERATING FREQUENCY: 1752.50 MHz
 CHANNEL: 1862
 MEASURED OUTPUT POWER: 24.54 dBm = 0.284 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.54 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
3505.00	-49.68	9.71	-39.97	H	64.5
5257.50	-50.80	11.00	-39.80	H	64.3
7010.00	-49.14	11.06	-38.08	H	62.6
8762.50	-45.70	11.61	-34.08	H	58.6
10515.00	-43.87	12.62	-31.25	H	55.8

Table 6-13. Radiated Spurious Data (AWS WCDMA Mode – Ch. 9538)

OPERATING FREQUENCY: 1850.20 MHz
 CHANNEL: 512
 MEASURED OUTPUT POWER: 30.12 dBm = 1.029 W
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 43.12 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
3700.40	-46.87	8.40	-38.47	H	68.6
5550.60	-49.00	10.62	-38.38	H	68.5
7400.80	-54.20	11.82	-42.38	H	72.5
9251.00	-44.96	13.30	-31.66	H	61.8
11101.20	-50.23	13.50	-36.73	H	66.9

Table 6-14. Radiated Spurious Data (PCS GSM Mode – Ch. 512)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 661
 MEASURED OUTPUT POWER: 32.17 dBm = 1.650 W
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 45.17 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
3760.00	-37.36	8.42	-28.93	H	61.1
5640.00	-51.27	10.66	-40.61	H	72.8
7520.00	-53.01	11.92	-41.08	H	73.3
9400.00	-45.77	13.24	-32.53	H	64.7
11280.00	-50.41	13.49	-36.92	H	69.1

Table 6-15. Radiated Spurious Data (PCS GSM Mode – Ch. 661)

OPERATING FREQUENCY: 1909.80 MHz
 CHANNEL: 810
 MEASURED OUTPUT POWER: 30.09 dBm = 1.020 W
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 43.09 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
3819.60	-35.79	8.57	-27.22	H	57.3
5729.40	-56.49	10.69	-45.80	H	75.9
7639.20	-51.31	12.07	-39.25	H	69.3
9549.00	-46.72	13.20	-33.52	H	63.6
11458.80	-51.49	13.42	-38.07	H	68.2

Table 6-16. Radiated Spurious Data (PCS GSM Mode – Ch. 810)

OPERATING FREQUENCY: 1852.40 MHz
 CHANNEL: 9262
 MEASURED OUTPUT POWER: 28.39 dBm = 0.691 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 41.39 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
3704.80	-42.39	9.91	-32.48	H	60.9
5557.20	-44.11	11.12	-32.99	H	61.4
7409.60	-47.54	10.76	-36.78	H	65.2
9262.00	-46.42	12.31	-34.12	H	62.5
11114.40	-43.22	12.90	-30.33	H	58.7

Table 6-17. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9262)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 9400
 MEASURED OUTPUT POWER: 26.17 dBm = 0.414 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 39.17 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
3760.00	-45.34	9.70	-35.64	H	61.8
5640.00	-47.74	11.25	-36.49	H	62.7
7520.00	-47.46	10.99	-36.47	H	62.6
9400.00	-45.47	12.26	-33.22	H	59.4
11280.00	-43.16	12.95	-30.21	H	56.4

Table 6-18. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 58 of 71

OPERATING FREQUENCY: 1907.60 MHz
 CHANNEL: 9538
 MEASURED OUTPUT POWER: 27.44 dBm = 0.554 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 40.44 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	EUT POL (H/V)	(dBc)
3815.20	-35.10	9.49	-25.61	H	53.0
5722.80	-46.82	11.29	-35.53	H	63.0
7630.40	-47.75	11.21	-36.54	H	64.0
9538.00	-44.48	12.32	-32.15	H	59.6
11445.60	-43.02	13.10	-29.92	H	57.4

Table 6-19. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 59 of 71

6.8 Frequency Stability / Temperature Variation

§2.1055 §22.355 §24.229 §24.235 §27.54 RSS-132(4.3) RSS-133(6.3) RSS-139(6.3)

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-C-2004. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24 and Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI/TIA-603-C-2004

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 60 of 71

Frequency Stability / Temperature Variation (Cont'd)

\$2.1055 \$22.355 \$24.229 \$24.235 \$27.54 RSS-132(4.3) RSS-133(6.3) RSS-139(6.3)

OPERATING FREQUENCY: 836,600,000 Hz

CHANNEL: 190

REFERENCE VOLTAGE: 3.8 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (° C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	836,599,991	-9	-0.0000010
100 %		- 30	836,599,992	-8	-0.0000010
100 %		- 20	836,599,993	-7	-0.0000009
100 %		- 10	836,599,993	-7	-0.0000009
100 %		0	836,599,987	-13	-0.0000016
100 %		+ 10	836,599,983	-17	-0.0000020
100 %		+ 20	836,599,981	-19	-0.0000022
100 %		+ 30	836,599,986	-14	-0.0000017
100 %		+ 40	836,599,997	-3	-0.0000004
100 %		+ 50	836,599,981	-19	-0.0000023
115 %	4.37	+ 20	836,599,989	-11	-0.0000013
BATT. ENDPOINT	3.40	+ 20	836,599,997	-3	-0.0000004

Table 6-20. Frequency Stability Data (Cellular GSM Mode – Ch. 190)

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router			Page 61 of 71

Frequency Stability / Temperature Variation (Cont'd)

§2.1055 §22.355 RSS-132(4.3)




Figure 6-7. Frequency Stability Graph (Cellular GSM Mode – Ch. 190)

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 62 of 71

Frequency Stability / Temperature Variation (Cont'd)

§2.1055 §22.355 RSS-132(4.3)

OPERATING FREQUENCY: 836,600,000 Hz

CHANNEL: 4183

REFERENCE VOLTAGE: 3.8 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (° C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	836,599,994	-6	-0.0000007
100 %		- 30	836,599,998	-2	-0.0000003
100 %		- 20	836,599,997	-3	-0.0000004
100 %		- 10	836,599,996	-4	-0.0000005
100 %		0	836,599,992	-8	-0.0000010
100 %		+ 10	836,599,997	-3	-0.0000004
100 %		+ 20	836,599,988	-12	-0.0000014
100 %		+ 30	836,599,984	-16	-0.0000019
100 %		+ 40	836,599,989	-11	-0.0000014
100 %		+ 50	836,599,991	-9	-0.0000011
115 %	4.37	+ 20	836,599,982	-18	-0.0000022
BATT. ENDPOINT	3.40	+ 20	836,599,983	-17	-0.0000020

Table 6-21. Frequency Stability Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router			Page 63 of 71

Frequency Stability / Temperature Variation (Cont'd)

§2.1055 §22.355 RSS-132(4.3)




Figure 6-8. Frequency Stability Graph (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 64 of 71

Frequency Stability / Temperature Variation (Cont'd)

§2.1055 §27.54 RSS-139(6.3)

OPERATING FREQUENCY: 1,732,500,000 Hz

CHANNEL: 1412

REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (° C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,732,499,997	-3	-0.0000002
100 %		- 30	1,732,499,983	-17	-0.0000010
100 %		- 20	1,732,499,992	-8	-0.0000005
100 %		- 10	1,732,499,986	-14	-0.0000008
100 %		0	1,732,499,983	-17	-0.0000010
100 %		+ 10	1,732,499,995	-5	-0.0000003
100 %		+ 20	1,732,499,994	-6	-0.0000003
100 %		+ 30	1,732,499,990	-10	-0.0000006
100 %		+ 40	1,732,499,981	-19	-0.0000011
100 %		+ 50	1,732,499,996	-4	-0.0000002
115 %	4.37	+ 20	1,732,499,983	-17	-0.0000010
BATT. ENDPOINT	3.40	+ 20	1,732,500,000	0	0.0000000

Table 6-22. Frequency Stability Data (AWS WCDMA Mode – Ch. 1413)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 65 of 71

Frequency Stability / Temperature Variation (Cont'd)

§2.1055 §27.54 RSS-139(6.3)




Figure 6-9. Frequency Stability Graph (AWS WCDMA Mode – Ch. 1413)

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 66 of 71

Frequency Stability / Temperature Variation (Cont'd)

§2.1055 §24.235 RSS-139(6.3)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 661

REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (° C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,879,999,983	-17	-0.0000009
100 %		- 30	1,879,999,994	-6	-0.0000003
100 %		- 20	1,879,999,991	-9	-0.0000005
100 %		- 10	1,879,999,991	-9	-0.0000005
100 %		0	1,879,999,994	-6	-0.0000003
100 %		+ 10	1,879,999,994	-6	-0.0000003
100 %		+ 20	1,879,999,987	-13	-0.0000007
100 %		+ 30	1,879,999,999	-1	0.0000000
100 %		+ 40	1,879,999,995	-5	-0.0000003
100 %		+ 50	1,879,999,992	-8	-0.0000004
115 %	4.37	+ 20	1,879,999,999	-1	-0.0000001
BATT. ENDPOINT	3.40	+ 20	1,879,999,984	-16	-0.0000008

Table 6-23. Frequency Stability Data (PCS GSM Mode – Ch. 661)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 67 of 71

Frequency Stability / Temperature Variation (Cont'd)

§2.1055 §24.235 RSS-139(6.3)




Figure 6-10. Frequency Stability Graph (PCS GSM Mode – Ch. 661)

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 68 of 71

Frequency Stability / Temperature Variation (Cont'd)

§2.1055 §24.235 RSS-139(6.3)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 9400

REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (° C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,879,999,990	-10	-0.0000005
100 %		- 30	1,879,999,983	-17	-0.0000009
100 %		- 20	1,879,999,983	-17	-0.0000009
100 %		- 10	1,879,999,983	-17	-0.0000009
100 %		0	1,879,999,988	-12	-0.0000006
100 %		+ 10	1,879,999,996	-4	-0.0000002
100 %		+ 20	1,879,999,990	-10	-0.0000005
100 %		+ 30	1,879,999,997	-3	-0.0000002
100 %		+ 40	1,879,999,986	-14	-0.0000007
100 %		+ 50	1,879,999,981	-19	-0.0000010
115 %	4.37	+ 20	1,879,999,991	-9	-0.0000005
BATT. ENDPOINT	3.40	+ 20	1,879,999,989	-11	-0.0000006

Table 6-24. Frequency Stability Data (PCS WCDMA Mode – Ch. 9400)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router	Page 69 of 71	

Frequency Stability / Temperature Variation (Cont'd)

§2.1055 §24.235 RSS-139(6.3)




Figure 6-11. Frequency Stability Graph (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMV100T	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 70 of 71

7.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Wireless Router FCC ID: A3LSMV100T** complies with all the requirements of Parts 2, 22, 24, 27 of the FCC rules.

FCC ID: A3LSMV100T		FCC Pt. 22, 24 & 27 GSM / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1306201050.A3L	Test Dates: 6/26 - 7/2/2013	EUT Type: Portable Wireless Router		Page 71 of 71