



SAMSUNG ELECTRONICS Co., Ltd.,
Regulatory Compliance Team
IT R&D Center

416, Maetan-3dong,
Yeongtong-gu, Suwon-si,
Gyeonggi-do, Korea 442-742

TEST REPORT ON SAR

Model Tested:	SPH-A800
FCC ID (Requested):	A3LSPHA800
Job No:	FB-070
Report No:	FB-070-S1
Date issued:	Dec. 31, 2004

– Abstract –

This document reports on SAR Tests carried out in accordance with FCC/OET Bulletin 65, Supplement C(July 2001).

Prepared By		Date	2005.01.03
	EH JUNG – Test Engineer		
Checked By		Date	2005.01.03
	JH CHOI - Manager		
Authorized By		Date	2005.01.03
	JK CHOI – Senior Manager		



Contents

1. General Information.....	3
2. Description of Device.....	3
3. Description of Test Equipment.....	4
3.1 SAR Measurement Setup.....	4
3.2 DASY4 E-Field Probe.....	5
3.3 SAM Phantom.....	6
3.4 Brain & Muscle Simulating Mixture Characterization.....	7
3.5 Device Holder for transmitters.....	8
3.6 Validation Dipole.....	8
3.7 Equipment Calibration.....	9
4. SAR Measurement Procedure.....	10
5. Description of test position.....	11
5.1 SAM Phantom Shape.....	11
5.2 Cheek/Touch Position.....	11
5.3 Ear/Tilt 15° Position.....	13
5.4 Body/Leather Configuration.....	14
6. Measurement Uncertainty.....	16
7. System Verification.....	18
7.1 Tissue Verification.....	18
7.2 Test System Validation.....	18
8. SAR Measurement Results.....	19
8.1 Measurement Results(AMPS Right Head SAR-Touch).....	20
8.2 Measurement Results(AMPS Right Head SAR-Tilt).....	21
8.3 Measurement Results(AMPS Left Head SAR-Touch).....	22
8.4 Measurement Results(AMPS Left Head SAR-Tilt).....	23
8.5 Measurement Results(CELLULAR CDMA Right Head SAR-Touch).....	24
8.6 Measurement Results(CELLULAR CDMA Right Head SAR-Tilt).....	25
8.7 Measurement Results(CELLULAR CDMA Left Head SAR-Touch).....	26
8.8 Measurement Results(CELLULAR CDMA Left Head SAR-Tilt).....	27
8.9 Measurement Results(PCS CDMA Right Head SAR-Touch).....	28
8.10 Measurement Results(PCS CDMA Right Head SAR-Tilt).....	29
8.11 Measurement Results(PCS CDMA Left Head SAR-Touch).....	30
8.12 Measurement Results(PCS CDMA Left Head SAR-Tilt).....	31
8.13 Measurement Results(AMPS Body SAR w/o holster).....	32
8.14 Measurement Results(CELLULAR CDMA Body SAR w/o Holster).....	33
8.15 Measurement Results(PCS CDMA Body SAR w/o Holster).....	34
9. Conclusion.....	35
10. Reference.....	36



1. GENERAL INFORMATION

Test Sample : Tri-Mode Dual-Band Analog/ PCS Phone (AMPS/CDMA)
Model Number : SPH-A800
Serial Number : Identical prototype (S/N : # FB-070-A)

Manufacturer : SAMSUNG ELECTRONICS Co., Ltd.
Contact : HK KIM, Engineer

Phone : +82-31-279-8466
Fax : +82-31-279-6323
Test Standard : §2.1093; FCC/OET Bulletin 65, Supplement C(July 2001)
FCC Classification : Licensed Portable Transmitter Held to Ear (PCE)
Test Dates : Dec. 20, 2004 ~ Dec. 23, 2004
Tested for : FCC/TCB Certification

2. DESCRIPTION OF DEVICE

Tx Freq. Range : 824.04–848.97 MHz (AMPS)
824.70–848.31 MHz (CDMA)
1851.25–1908.75 MHz (PCS CDMA)

Rx Freq. Range : 869.04–893.97 MHz (AMPS)
869.70–893.31 MHz (CDMA)
1931.25–1988.75 MHz (PCS CDMA)

Max. RF Output Power : 0.468 W ERP AMPS (26.70dBm)
0.433 W ERP CDMA (26.36dBm)
0.592 W EIRP PCS (27.72dBm)

Antenna Manufacturer : PARTRON
Model No.: SPH-A800

Antenna Dimensions : Length = [Intenna]

System Electronics

The DAE4(or DAE3) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

3.2 E-field Probe



The SAR measurement were conducted with the dosimetric probe ET3DV6, designed in the classical triangular configuration (see Fig.3.3) and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip (see Fig.3.4). It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving

Figure 3.2 DAE System fibers. This reflection increases first during the approach, reaches a maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach and looks for the maximum using a 2nd order fitting (see Fig.3.2). The approach is stopped at reaching the maximum.

Probe Specifications

Construction	Symmetrical design with triangular core
	Built-in optical fiber for surface detection system
	Built-in shielding against static charges
	PEEK enclosure material (resistant to organic solvents, e.g., glycoether)



Calibration In air from 10 MHz to 2.5 GHz
 In brain and muscle simulating liquid at 1900 MHz (accuracy $\pm 9.5\%$; $k=2$)

Frequency 10 MHz to 3 GHz; Linearity : ± 0.2 dB (30 MHz to 3 GHz)

Directivity ± 0.2 dB in HSL (rotation around probe axis)
 ± 0.4 dB in HSL (rotation normal to probe axis)

Dynamic 5 μ W/g to > 100mW/g; Linearity: ± 0.2 dB
 Range




Figure 3.3 Triangular Probe Configuration

Dimensions Overall length: 330mm
 Tip length: 16mm
 Body diameter: 12mm
 Tip diameter: 6.8mm
 Distance from probe tip to dipole centers: 2.7mm



Figure 3.4 Probe Thick-Film Technique

Application General dosimetry up to 3 GHz
 Compliance tests of mobile phones
 Fast automatic scanning in arbitrary phantoms

Optical ± 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces
 Surface
 Detection

3.3 SAM Phantom

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid.



Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. (See Figure 3.5)



Figure 3.5 SAM Twin Phantom

Phantom Specification

Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-2003, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid.
Shell Thickness	2 ± 0.2 mm
Filling Volume	Approx. 25 liters
Dimensions	Height: 810 mm; Length: 1000 mm; Width: 500 mm

3.4 Brain & Muscle Simulating Mixture Characterization

The brain and muscle mixtures consist of a viscous gel using hydroxethylcellulose (HEC) gelling agent and saline solution (see Table 3.1). Preservation with a bactericide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations.




Figure 3.6 Simulated Tissue

Table 3.1 Composition of the Brain & Muscle Tissue Equivalent Matter

INGREDIENTS	835MHz Brain	835MHz Muscle	1900MHz Brain	1900MHz Muscle
WATER	51.07%	65.45%	54.88%	69.91%
SUGAR	47.31%	34.31%	-	-
SALT	1.150%	0.620%	0.210%	0.130%
DGBE	-	-	44.91%	29.96%
BACTERIACIDE	0.240%	0.100%	-	-
HEC	0.230%	-	-	-
Dielectric Constant Target	41.50	55.20	40.00	53.30
Conductivity Target (S/m)	0.900	0.970	1.400	1.520

3.5 Device Holder for Transmitters

In combination with the Twin SAM Phantom V4.0, the Mounting Device (see Fig. 3.7) enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear



opening. The devices can be easily, accurately and repeatedly be positioned according to the FCC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

*Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produced infinite number of configuration. To produce worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.

Figure 3.7 Device Holder

3.6 Validation Dipole

The reference dipole should have a return loss better than -20 dB (measured in the setup) at the resonant frequency to reduce the uncertainty in the power measurement.

Frequency	835, 1900 MHz
Return Loss	< -20 dB at specified validation position
Dimensions	D835V2: dipole length: 161 mm; overall height: 330 mm D1900V2: dipole length: 68 mm; overall height: 300 mm



3.7 Equipment Calibration

Table 3.1 Test Equipment Calibration

Type	Calibration Due Date	Asset Number
Stäubli Robot RX90BL	Not Required	SWR-S045
SPEAG DAE3	2005-08-23	SWR-S024
SPEAG E-Field Probe ET3DV6	2005-04-27	SWR-S023
SPEAG SAM Twin Phantom V4.0	Not Required	SWR-S045-b
SPEAG SAM Twin Phantom V4.0	Not Required	SWR-S045-c
SPEAG Validation Dipole D835V2	2005-11-18	SWR-S026
SPEAG Validation Dipole D1900V2	2006-11-18	SWR-S029
NRVD Power Meter	2005-03-10	SWR-S004
NRVD Power Meter	2005-03-10	SWR-S005
E4421B Signal Generator	2005-11-11	SWR-S038
BBS3Q7ECK Power Amp.	2005-01-14	SWR-S056
HP-8753ES Network Analyzer	2005-05-24	SWR-S006
HP85070C Dielectric Probe Kit	Not Required	SWR-S002
DASY4 S/W (ver 4.4)	Not Required	SWR-S045-a
NRV-Z53 Power Sensor	2005-03-10	SWR-S076
NRV-Z55 Power Sensor	2005-03-12	SWR-S009
NRV-Z55 Power Sensor	2005-10-21	SWR-S010

NOTE:

The E-field probe was calibrated by SPEAG, by temperature measurement procedure. Dipole Validation measurement is performed by Samsung Lab. before each test. (see § 7.2) The brain simulating material is calibrated by Samsung using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain-equivalent material. (see § 7.1)



4. SAR MEASUREMENT PROCEDURE

The evaluation was performed using the following procedure.

STEP 1

The SAR measurement was taken at a selected spatial reference point to monitor power variations during testing. This fixed location point was measured and used as a reference value.

STEP 2

The SAR distribution at the exposed side of the head was measured at a distance of 3.9mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 20mm x 20mm. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation.

STEP 3

Around this point, a volume of 30mm x 30mm x 34mm (fine resolution volume scan, zoom scan) was assessed by measuring 5 x 5 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

The data at the surface was extrapolated, since the center of the dipoles is 2.7mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

STEP 4

The SAR value at the same location as in step 1 was again measured. (If the value changed by more than 5%, the evaluation is repeated.)

5. DESCRIPTION OF TEST POSITION

5.1 SAM Phantom Shape

Figure 5.1 shows the front, back and side views of SAM. The point “M” is the reference point for the center of mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERPs are 15 mm posterior to the entrance to ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5.2.



Figure 5.1 Front, back and side view of SAM

The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front) perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 5.3). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines should be marked on the external phantom shell to facilitate handset positioning. Posterior to the N-F line, the thickness of the phantom shell with the shape of an ear is a flat surface 6 mm thick at the ERPs.




Figure 5.2 Close up side view

5.2 Cheek/Touch Position

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (see Fig. 5.4). The “test device reference point” was then located at the same level as the center of

the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its tip and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point



Figure 5.3 Side view of the phantom showing relevant markings



Figure 5.4 Handset vertical and horizontal reference lines

Step 1

The test device was positioned with the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 5.5), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom



Figure 5.5 Front, Side and Top View of Cheek/Touch Position

Step 2

The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the ear.

Step 3

While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the plane normal to MB-NF including the line MB (reference plane).

Step 4

Rotate the handset around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.

Step 5

While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, the handset was rotated about the line NF until any point on the handset made contact with a phantom point below the ear (cheek). See Figure 5.2.

5.3 EAR/Tilt 15° Position

With the test device aligned in the “Cheek/Touch Position”:

Step 1

Repeat steps 1 to 5 of 5.2 to place the device in the “Cheek/Touch Position”



Figure 5.6 Front, side and Top View of Ear/Tilt 15° Position

Step 2

While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degree.

Step 3

The phone was then rotated around the horizontal line by 15 degree.

Step 4

While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the phone touches the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. The tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head.

5.4 Body Holster/Belt Clip Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 5.7). A device with a headset output is tested with a headset connected to the device. Body dielectric parameters are used.



Figure 5.7 Body Belt Clip and Holster Configurations

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are supplied with the device, the device is tested with each accessory that contains unique metallic component. If multiple accessory share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.



Body-worn accessories may not always be supplied or available as options for some Devices intended to be authorized for body-worn use. In this case, a test configuration where a separation distance between the back of the device and the flat phantom is used.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessory(ies), including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

In all cases SAR measurements are performed to investigate the worst-case positioning. Worst-case positioning is then documented and used to perform Body SAR testing.

In order for users to be aware of the body-worn operating requirements for meeting RF exposure compliance, operating instructions and cautions statements must be included in the user's manual.



6. MEASUREMENT UNCERTAINTY

Table 6.1 Uncertainty Budget (835MHz)

Error Description	Uncertainty Value($\pm\%$)	Probability Distribution	Divisor	C_i	Standard uncertainty	v_i^2 or v_{eff}
Measurement System						
Probe Calibration	4.85	Normal	1.000	1	4.85	∞
Axial Isotropy	4.70	rectangular	1.732	0.7	1.90	∞
Hemispherical Isotropy	9.60	rectangular	1.732	0.7	3.88	∞
Linearity	4.70	rectangular	1.732	1	2.71	∞
System Detection Limits	0.25	rectangular	1.732	1	0.14	∞
Boundary effects	1.00	rectangular	1.732	1	0.58	∞
Readout electronics	1.00	Normal	1.000	1	1.00	∞
Response time	0.80	rectangular	1.732	1	0.46	∞
RF ambient conditions	3.00	rectangular	1.732	1	1.73	∞
Integration time	0.00	rectangular	1.732	1	0.00	∞
Mechanical constrains of robot	1.43	rectangular	1.732	1	0.83	∞
Probe positioning	2.86	rectangular	1.732	1	1.65	∞
Extrapolation and integration	1.00	rectangular	1.732	1	0.58	∞
Test Sample Related						
Test Sample positioning	1.21	Normal	1.000	1	1.21	11
Device holded uncertainty	3.33	Normal	1.000	1	3.33	∞
Power Drift	5.00	Rectangular	1.732	1	2.89	∞
Phantom and Setup						
Phantom uncertainty	4.00	Rectangular	1.732	1	2.31	∞
Liquid conductivity (deviation from target)	5.00	Rectangular	1.732	0.64	1.85	∞
Liquid conductivity (measurement error)	2.78	Normal	1.000	0.64	1.78	∞
Liquid permittivity (deviation from target)	5.00	Rectangular	1.732	0.6	1.73	∞
Liquid permittivity (measurement error)	2.75	Normal	1000	0.6	1.65	∞
Combined Standard Uncertainty		Normal			9.82	48430
Extended Standard Uncertainty(K=2.00)					19.63	48430



Table 6.2 Uncertainty Budget (1900MHz)

Error Description	Uncertainty Value($\pm\%$)	Probability Distribution	Divisor	C_i	Standard uncertainty	v_i^2 or v_{eff}
Measurement System						
Probe Calibration	4.85	Normal	1.000	1	4.85	∞
Axial Isotropy	4.70	rectangular	1.732	0.7	1.90	∞
Hemispherical Isotropy	9.60	rectangular	1.732	0.7	3.88	∞
Linearity	4.70	rectangular	1.732	1	2.71	∞
System Detection Limits	0.25	rectangular	1.732	1	0.14	∞
Boundary effects	1.00	rectangular	1.732	1	0.58	∞
Readout electronics	1.00	Normal	1.000	1	1.00	∞
Response time	0.80	rectangular	1.732	1	0.46	∞
RF ambient conditions	3.00	rectangular	1.732	1	1.73	∞
Integration time	0.00	rectangular	1.732	1	0.00	∞
Mechanical constrains of robot	1.43	rectangular	1.732	1	0.83	∞
Probe positioning	2.86	rectangular	1.732	1	1.65	∞
Extrapolation and integration	1.00	rectangular	1.732	1	0.58	∞
Test Sample Related						
Test Sample positioning	1.21	Normal	1.000	1	1.21	11
Device holded uncertainty	3.33	Normal	1.000	1	3.33	∞
Power Drift	5.00	Rectangular	1.732	1	2.89	∞
Phantom and Setup						
Phantom uncertainty	4.00	Rectangular	1.732	1	2.31	∞
Liquid conductivity (deviation from target)	5.00	Rectangular	1.732	0.64	1.85	∞
Liquid conductivity (measurement error)	2.50	Normal	1.000	0.64	1.60	∞
Liquid permittivity (deviation from target)	5.00	Rectangular	1.732	0.6	1.73	∞
Liquid permittivity (measurement error)	2.42	Normal	1000	0.6	1.45	∞
Combined Standard Uncertainty		Normal			9.75	13474
Extended Standard Uncertainty(K=2.00)					19.51	13474

7. SYSTEM VERIFICATION

7.1 Tissue Verification

Table 7.1 MEASURED TISSUE PARAMETERS

	835MHz Brain				835MHz Muscle		1900MHz Brain		1900MHz Muscle	
	Target	Measured	Target	Measured	Target	Measured	Target	Measured	Target	Measured
Date		Dec.20, 2004	-	Dec.21, 2004	-	Dec.23, 2004	-	Dec.22, 2004	-	Dec.22, 2004
Liquid Temperature(°C)		20.9	-	21.0	-	21.4	-	21.1	-	20.8
Dielectric Constant: ϵ'	41.5	41.4	41.5	41.3	55.2	53.8	40.0	38.5	53.3	52.0
Conductivity: σ	0.90	0.89	0.90	0.89	0.97	0.95	1.40	1.40	1.52	1.54

The measured value must be within $\pm 5\%$ of the target value.

7.2 Test System Validation

Prior to assessment, the system is verified to the $\pm 10\%$ of the specification at 835MHz and 1900MHz by using the system validation kit(s). (see Appendix F, Graphic Plot Attached)

Table 7.2 System Validation Results

System Validation Kit	Tissue	Targeted SAR _{1g} (mW/g)	Measured SAR _{1g} (mW/g)	Deviation (%)	Date	Liquid Temperature(°C)
D-835V2 S/N: 451	835MHz Brain	2.375	2.45	3.16	Dec.20, 2004	21.5
D-835V2 S/N: 451	835MHz Brain	2.375	2.49	4.84	Dec.21, 2004	21.0
D-1900V2 S/N: 548	1900MHz Brain	9.925	10.2	2.77	Dec.22, 2004	21.3




Figure 7.1 Dipole Validation Test Setup

8. SAR MEASUREMENT RESULTS

Procedures Used To Establish Test Signal

The handset was placed into simulated call mode (AMPS, Cellular CDMA & PCS CDMA modes) using manufacturers test codes. Such test signals offer a consistent means for testing SAR and are recommended for evaluating SAR. When test modes are not available or inappropriate for testing a handset, the actual transmission is activated through a base station simulator or similar equipment. See data pages for actual procedure used in measurement.

Device Test Conditions

The handset is battery operated. Each SAR measurement was taken with a fully charged battery. In order to verify that the device was tested at full power, conducted output power measurements were performed before and after each SAR measurement to confirm the output power. If a conducted power deviation of more than 5% occurred, the test was repeated.

EUT Handset Reference Points




Figure 8.1 Handset Reference Points



8.1 MEASUREMENT RESULTS (AMPS Right Head SAR – Touch)

Date of Test :	Dec. 20, 2004		
Mixture Type:	835MHz Brain	Tissue Depth:	15.5 cm
Dielectric Constant:	41.4	Liquid Tissue Temp.:	21.6
Conductivity:	0.89	Ambient Temp:	22.5

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
824.04	991	AMPS	26.01	26.01	Standard	Cheek / Touch	Intenna	Down	0.794
836.49	383	AMPS	26.03	26.027	Standard	Cheek / Touch	Intenna	Down	0.758
848.97	799	AMPS	26.04	25.84	Standard	Cheek / Touch	Intenna	Down	1.3
824.04	991	AMPS	26.05	26.05	Standard	Cheek / Touch	Intenna	Up	0.645
836.49	383	AMPS	26.07	26.07	Standard	Cheek / Touch	Intenna	Up	0.599
848.97	799	AMPS	26.05	25.95	Standard	Cheek / Touch	Intenna	Up	1.12
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Brain 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
4. SAR Measurement System ☒ DASY4
5. Phantom Configuration ☐ Left Head ☐ Flat Phantom ☒ Right Head
6. SAR Configuration ☒ Head ☐ Body ☐ Hand
7. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
8. Battery Option ☒ Standard ☐ Extended ☐ Slim



Figure 8.2 Right Head SAR Test Setup
-- Cheek / Touch Position--



8.2 MEASUREMENT RESULTS (AMPS Right Head SAR – Tilt)

Date of Test :	Dec. 20, 2004		
Mixture Type:	835MHz Brain	Tissue Depth:	15.5 cm
Dielectric Constant:	41.4	Liquid Tissue Temp.:	21.6
Conductivity:	0.89	Ambient Temp:	22.5

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
824.04	991	AMPS	26.04	25.94	Standard	Ear/Tilt 15°	Intenna	Down	0.593
836.49	383	AMPS	26.05	25.95	Standard	Ear/Tilt 15°	Intenna	Down	0.520
848.97	799	AMPS	26.03	26.03	Standard	Ear/Tilt 15°	Intenna	Down	0.874
824.04	991	AMPS	26.06	25.86	Standard	Ear/Tilt 15°	Intenna	Up	0.281
836.49	383	AMPS	26.03	26.03	Standard	Ear/Tilt 15°	Intenna	Up	0.240
848.97	799	AMPS	26.07	25.97	Standard	Ear/Tilt 15°	Intenna	Up	0.495
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Brain 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
4. SAR Measurement System ☒ DASY4
5. Phantom Configuration ☐ Left Head ☐ Flat Phantom ☒ Right Head
6. SAR Configuration ☒ Head ☐ Body ☐ Hand
7. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
8. Battery Option ☒ Standard ☐ Extended ☐ Slim



Figure 8.3 Right Head SAR Test Setup
-- Ear / Tilt 15° Position --



8.3 MEASUREMENT RESULTS (AMPS Left Head SAR – Touch)

Date of Test :	Dec. 20, 2004		
Mixture Type:	835MHz Brain	Tissue Depth:	15.5 cm
Dielectric Constant:	41.4	Liquid Tissue Temp.:	21.6
Conductivity:	0.89	Ambient Temp:	22.5

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
824.04	991	AMPS	26.01	26.11	Standard	Cheek / Touch	Intenna	Down	0.803
836.49	383	AMPS	26.05	26.05	Standard	Cheek / Touch	Intenna	Down	0.864
848.97	799	AMPS	26.06	25.96	Standard	Cheek / Touch	Intenna	Down	1.42
824.04	991	AMPS	26.04	25.94	Standard	Cheek / Touch	Intenna	Up	0.586
836.49	383	AMPS	26.05	26.05	Standard	Cheek / Touch	Intenna	Up	0.587
848.97	799	AMPS	26.07	25.97	Standard	Cheek / Touch	Intenna	Up	1.01
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Brain 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
4. SAR Measurement System ☒ DASY4
5. Phantom Configuration ☒ Left Head ☐ Flat Phantom ☐ Right Head
6. SAR Configuration ☒ Head ☐ Body ☐ Hand
7. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
8. Battery Option ☒ Standard ☐ Extended ☐ Slim



**Figure 8.4 Left Head SAR Test Setup
-- Cheek / Touch Position--**



8.4 MEASUREMENT RESULTS (AMPS Left Head SAR – Tilt)

Date of Test :	Dec. 20, 2004		
Mixture Type:	835MHz Brain	Tissue Depth:	15.5 cm
Dielectric Constant:	41.4	Liquid Tissue Temp.:	21.6
Conductivity:	0.89	Ambient Temp:	22.5

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
824.04	991	AMPS	26.02	25.92	Standard	Ear/Tilt 15°	Intenna	Down	0.641
836.49	383	AMPS	26.04	25.94	Standard	Ear/Tilt 15°	Intenna	Down	0.619
848.97	799	AMPS	26.05	25.95	Standard	Ear/Tilt 15°	Intenna	Down	0.937
824.04	991	AMPS	26.08	25.88	Standard	Ear/Tilt 15°	Intenna	Up	0.239
836.49	383	AMPS	26.05	25.95	Standard	Ear/Tilt 15°	Intenna	Up	0.229
848.97	799	AMPS	26.07	25.87	Standard	Ear/Tilt 15°	Intenna	Up	0.408
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Brain 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
- SAR Measurement System ☒ DASY4
 - Phantom Configuration ☒ Left Head ☐ Flat Phantom ☐ Right Head
 - SAR Configuration ☒ Head ☐ Body ☐ Hand
 - Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
 - Battery Option ☒ Standard ☐ Extended ☐ Slim



Figure 8.5 Left Head SAR Test Setup

-- Ear / Tilt 15° Position --



8.5 MEASUREMENT RESULTS (CELLULAR CDMA Right Head SAR – Touch)

Date of Test :	Dec. 21, 2004		
Mixture Type:	835MHz Brain	Tissue Depth:	15.5cm
Dielectric Constant:	41.3	Liquid Tissue Temp.:	21.0
Conductivity:	0.89	Ambient Temp:	22.4

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
824.70	1013	CDMA	25.02	24.92	Standard	Cheek / Touch	Intenna	Down	0.705
835.89	0363	CDMA	25.06	25.06	Standard	Cheek / Touch	Intenna	Down	0.657
848.31	0777	CDMA	25.05	24.95	Standard	Cheek / Touch	Intenna	Down	1.03
824.70	1013	CDMA	25.04	24.94	Standard	Cheek / Touch	Intenna	Up	0.540
835.89	0363	CDMA	25.06	25.06	Standard	Cheek / Touch	Intenna	Up	0.555
848.31	0777	CDMA	25.07	25.07	Standard	Cheek / Touch	Intenna	Up	0.767
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Brain 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
- SAR Measurement System ☒ DASY4
 - Phantom Configuration ☐ Left Head ☐ Flat Phantom ☒ Right Head
 - SAR Configuration ☒ Head ☐ Body ☐ Hand
 - Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
 - Battery Option ☒ Standard ☐ Extended ☐ Slim



Figure 8.6 Right Head SAR Test Setup
-- Cheek / Touch Position--



8.6 MEASUREMENT RESULTS (CELLULAR CDMA Right Head SAR – Tilt)

Date of Test :	Dec. 21, 2004		
Mixture Type:	835MHz Brain	Tissue Depth:	15.5cm
Dielectric Constant:	41.3	Liquid Tissue Temp.:	21.0
Conductivity:	0.89	Ambient Temp:	22.4

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
824.70	1013	CDMA	25.04	24.94	Standard	Cheek / Touch	Intenna	Down	0.527
835.89	0363	CDMA	25.06	24.96	Standard	Cheek / Touch	Intenna	Down	0.448
848.31	0777	CDMA	25.06	24.86	Standard	Cheek / Touch	Intenna	Down	0.722
824.70	1013	CDMA	25.03	24.83	Standard	Cheek / Touch	Intenna	Up	0.218
835.89	0363	CDMA	25.07	25.17	Standard	Cheek / Touch	Intenna	Up	0.207
848.31	0777	CDMA	25.03	24.93	Standard	Cheek / Touch	Intenna	Up	0.322
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Brain 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
4. SAR Measurement System ☒ DASY4
5. Phantom Configuration ☐ Left Head ☐ Flat Phantom ☒ Right Head
6. SAR Configuration ☒ Head ☐ Body ☐ Hand
7. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
8. Battery Option ☒ Standard ☐ Extended ☐ Slim



Figure 8.7 Right Head SAR Test Setup
-- Ear / Tilt 15° Position --



8.7 MEASUREMENT RESULTS (CELLULAR CDMA Left Head SAR – Touch)

Date of Test :	Dec. 21, 2004		
Mixture Type:	835MHz Brain	Tissue Depth:	15.5cm
Dielectric Constant:	41.3	Liquid Tissue Temp.:	21.0
Conductivity:	0.89	Ambient Temp:	22.4

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
824.70	1013	CDMA	25.02	25.02	Standard	Cheek / Touch	Intenna	Down	0.686
835.89	0363	CDMA	25.04	24.84	Standard	Cheek / Touch	Intenna	Down	0.787
848.31	0777	CDMA	25.05	24.85	Standard	Cheek / Touch	Intenna	Down	1.13
824.70	1013	CDMA	25.03	25.03	Standard	Cheek / Touch	Intenna	Up	0.499
835.89	0363	CDMA	25.02	24.92	Standard	Cheek / Touch	Intenna	Up	0.556
848.31	0777	CDMA	25.07	24.97	Standard	Cheek / Touch	Intenna	Up	0.746
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Brain 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
- SAR Measurement System ☒ DASY4
 - Phantom Configuration ☒ Left Head ☐ Flat Phantom ☐ Right Head
 - SAR Configuration ☒ Head ☐ Body ☐ Hand
 - Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
 - Battery Option ☒ Standard ☐ Extended ☐ Slim



**Figure 8.8 Left Head SAR Test Setup
-- Cheek / Touch Position--**



8.8 MEASUREMENT RESULTS (CELLULAR CDMA Left Head SAR – Tilt)

Date of Test :	Dec. 21, 2004		
Mixture Type:	835MHz Brain	Tissue Depth:	15.5cm
Dielectric Constant:	41.3	Liquid Tissue Temp.:	21.0
Conductivity:	0.89	Ambient Temp:	22.4

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
824.70	1013	CDMA	25.04	24.94	Standard	Ear/Tilt 15°	Intenna	Down	0.523
835.89	0363	CDMA	25.03	25.03	Standard	Ear/Tilt 15°	Intenna	Down	0.565
848.31	0777	CDMA	25.05	24.95	Standard	Ear/Tilt 15°	Intenna	Down	0.747
824.70	1013	CDMA	25.06	24.96	Standard	Ear/Tilt 15°	Intenna	Up	0.204
835.89	0363	CDMA	25.03	24.93	Standard	Ear/Tilt 15°	Intenna	Up	0.233
848.31	0777	CDMA	25.07	24.97	Standard	Ear/Tilt 15°	Intenna	Up	0.272
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Brain 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
- SAR Measurement System ☒ DASY4
 - Phantom Configuration ☒ Left Head ☐ Flat Phantom ☐ Right Head
 - SAR Configuration ☒ Head ☐ Body ☐ Hand
 - Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
 - Battery Option ☒ Standard ☐ Extended ☐ Slim



Figure 8.9 Left Head SAR Test Setup
-- Ear / Tilt 15° Position --



8.9 MEASUREMENT RESULTS (PCS CDMA Right Head SAR – Touch)

Date of Test :	Dec. 22, 2004		
Mixture Type:	1900MHz Brain	Tissue Depth:	15.0 cm
Dielectric Constant:	38.5	Liquid Tissue Temp.:	21.3
Conductivity:	1.40	Ambient Temp:	22.8

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
1851.25	0025	CDMA	25.02	24.82	Standard	Cheek / Touch	Intenna	Down	0.366
1880.00	0600	CDMA	25.03	25.03	Standard	Cheek / Touch	Intenna	Down	0.457
1908.75	1175	CDMA	25.08	25.0797	Standard	Cheek / Touch	Intenna	Down	0.471
1851.25	0025	CDMA	25.07	24.97	Standard	Cheek / Touch	Intenna	Up	0.294
1880.00	0600	CDMA	25.04	25.04	Standard	Cheek / Touch	Intenna	Up	0.311
1908.75	1175	CDMA	25.01	24.91	Standard	Cheek / Touch	Intenna	Up	0.275
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Brain 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
4. SAR Measurement System ☒ DASY4
5. Phantom Configuration ☐ Left Head ☐ Flat Phantom ☒ Right Head
6. SAR Configuration ☒ Head ☐ Body ☐ Hand
7. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
8. Battery Option ☒ Standard ☐ Extended ☐ Slim



Figure 8.10 Right Head SAR Test Setup
-- Cheek / Touch Position--



8.10 MEASUREMENT RESULTS (PCS CDMA Right Head SAR – Tilt)

Date of Test :	Dec. 22, 2004		
Mixture Type:	1900MHz Brain	Tissue Depth:	15.0 cm
Dielectric Constant:	38.5	Liquid Tissue Temp.:	21.3
Conductivity:	1.40	Ambient Temp:	22.8

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
1851.25	0025	CDMA	25.02	24.92	Standard	Cheek / Touch	Intenna	Down	0.406
1880.00	0600	CDMA	25.08	24.88	Standard	Cheek / Touch	Intenna	Down	0.465
1908.75	1175	CDMA	25.07	24.97	Standard	Cheek / Touch	Intenna	Down	0.480
1851.25	0025	CDMA	25.06	25.057	Standard	Cheek / Touch	Intenna	Up	0.286
1880.00	0600	CDMA	25.08	24.98	Standard	Cheek / Touch	Intenna	Up	0.315
1908.75	1175	CDMA	25.09	24.99	Standard	Cheek / Touch	Intenna	Up	0.263
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Brain 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
4. SAR Measurement System ☒ DASY4
5. Phantom Configuration ☐ Left Head ☐ Flat Phantom ☒ Right Head
6. SAR Configuration ☒ Head ☐ Body ☐ Hand
7. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
8. Battery Option ☒ Standard ☐ Extended ☐ Slim



Figure 8.11 Right Head SAR Test Setup
-- Ear/Tilt 15° Position--



8.11 MEASUREMENT RESULTS (PCS CDMA Left Head SAR – Touch)

Date of Test :	Dec. 22, 2004		
Mixture Type:	1900MHz Brain	Tissue Depth:	15.0 cm
Dielectric Constant:	38.5	Liquid Tissue Temp.:	21.3
Conductivity:	1.40	Ambient Temp:	22.8

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
1851.25	0025	CDMA	25.02	24.92	Standard	Cheek / Touch	Intenna	Down	0.507
1880.00	0600	CDMA	25.04	24.94	Standard	Cheek / Touch	Intenna	Down	0.583
1908.75	1175	CDMA	25.08	24.98	Standard	Cheek / Touch	Intenna	Down	0.668
1851.25	0025	CDMA	25.05	24.95	Standard	Cheek / Touch	Intenna	Up	0.359
1880.00	0600	CDMA	25.04	24.94	Standard	Cheek / Touch	Intenna	Up	0.330
1908.75	1175	CDMA	25.06	25.06	Standard	Cheek / Touch	Intenna	Up	0.362
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Brain 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
4. SAR Measurement System ☒ DASY4
5. Phantom Configuration ☒ Left Head ☐ Flat Phantom ☐ Right Head
6. SAR Configuration ☒ Head ☐ Body ☐ Hand
7. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
8. Battery Option ☒ Standard ☐ Extended ☐ Slim



**Figure 8.12 Left Head SAR Test Setup
-- Cheek / Touch Position--**



8.12 MEASUREMENT RESULTS (PCS CDMA Left Head SAR – Tilt)

Date of Test :	Dec. 22, 2004		
Mixture Type:	1900MHz Brain	Tissue Depth:	15.0 cm
Dielectric Constant:	38.5	Liquid Tissue Temp.:	21.3
Conductivity:	1.40	Ambient Temp:	22.8

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
1851.25	0025	CDMA	25.01	25.01	Standard	Cheek / Touch	Intenna	Down	0.510
1880.00	0600	CDMA	25.02	24.82	Standard	Cheek / Touch	Intenna	Down	0.590
1908.75	1175	CDMA	25.08	24.88	Standard	Cheek / Touch	Intenna	Down	0.645
1851.25	0025	CDMA	25.05	24.85	Standard	Cheek / Touch	Intenna	Up	0.404
1880.00	0600	CDMA	25.06	25.16	Standard	Cheek / Touch	Intenna	Up	0.409
1908.75	1175	CDMA	25.07	24.97	Standard	Cheek / Touch	Intenna	Up	0.377
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Brain 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
- SAR Measurement System ☒ DASY4
 - Phantom Configuration ☒ Left Head ☐ Flat Phantom ☐ Right Head
 - SAR Configuration ☒ Head ☐ Body ☐ Hand
 - Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
 - Battery Option ☒ Standard ☐ Extended ☐ Slim



Figure 8.13 Left Head SAR Test Setup
-- Ear/Tilt 15° Position--



8.13 MEASUREMENT RESULTS (AMPS Body SAR without Holster)

Date of Test :	Dec. 23, 2004		
Mixture Type:	835MHz Muscle	Tissue Depth:	15.4 cm
Dielectric Constant:	53.8	Liquid Tissue Temp.:	21.4
Conductivity:	0.95	Ambient Temp:	22.4

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
824.04	991	AMPS	26.02	25.92	Standard	1.5cm[w/o Holster]	Intenna	Down	0.848
836.49	383	AMPS	26.05	26.05	Standard	1.5cm[w/o Holster]	Intenna	Down	0.668
848.97	799	AMPS	26.08	26.08	Standard	1.5cm[w/o Holster]	Intenna	Down	0.621
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Muscle 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
- SAR Measurement System ☒ DASY4
 - Phantom Configuration ☐ Left Head ☒ Flat Phantom ☐ Right Head
 - SAR Configuration ☐ Head ☒ Body ☐ Hand
 - Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
 - Test Configuration ☐ With Holster ☒ Without Holster
 - Battery Option ☒ Standard ☐ Extended ☐ Slim
- Both sides of the phone were tested and the worst-case side is reported.



Figure 8.14 Body SAR Test Setup
-- without Holster--



8.14 MEASUREMENT RESULTS (CDMA Body SAR without Holster)

Date of Test :	Dec. 23, 2004		
Mixture Type:	835MHz Muscle	Tissue Depth:	15.4 cm
Dielectric Constant:	53.8	Liquid Tissue Temp.:	21.4
Conductivity:	0.95	Ambient Temp:	22.4

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
824.70	1013	CDMA	25.05	25.05	Standard	1.5cm[w/o Holster]	Intenna	Down	0.650
835.89	0363	CDMA	25.06	25.06	Standard	1.5cm[w/o Holster]	Intenna	Down	0.556
848.31	0777	CDMA	25.08	25.08	Standard	1.5cm[w/o Holster]	Intenna	Down	0.499
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Muscle 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
- SAR Measurement System ☒ DASY4
 - Phantom Configuration ☐ Left Head ☒ Flat Phantom ☐ Right Head
 - SAR Configuration ☐ Head ☒ Body ☐ Hand
 - Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
 - Test Configuration ☐ With Holster ☒ Without Holster
 - Battery Option ☒ Standard ☐ Extended ☐ Slim
- Both sides of the phone were tested and the worst-case side is reported.



Figure 8.15 Body SAR Test Setup
-- without Holster--



8.15 MEASUREMENT RESULTS (PCS CDMA Body SAR without Holster)

Date of Test :	Dec. 22, 2004		
Mixture Type:	1900MHz Muscle	Tissue Depth:	15.5 cm
Dielectric Constant:	52.0	Liquid Tissue Temp.:	21.5
Conductivity:	1.54	Ambient Temp:	22.1

FREQUENCY		Modulation	Begin/End POWER*			Device Test Position	Antenna Position	Slide Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery				
1851.25	0025	CDMA	25.02	24.82	Standard	1.5cm[w/o Holster]	Intenna	Down	0.819
1880.00	0600	CDMA	25.04	24.94	Standard	1.5cm[w/o Holster]	Intenna	Down	0.753
1908.75	1175	CDMA	25.08	24.88	Standard	1.5cm[w/o Holster]	Intenna	Down	0.800
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						Muscle 1.6W/kg (mW/g) averaged over 1 gram			

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and the worst-case results are reported.
 - Battery is fully charged for all readings.
- *Power Measured ☒ Conducted
- SAR Measurement System ☒ DASY4
 - Phantom Configuration ☐ Left Head ☒ Flat Phantom ☐ Right Head
 - SAR Configuration ☐ Head ☒ Body ☐ Hand
 - Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
 - Test Configuration ☐ With Holster ☒ Without Holster
 - Battery Option ☒ Standard ☐ Extended ☐ Slim
- Both sides of the phone were tested and the worst-case side is reported.



Figure 8.16 Body SAR Test Setup
-- without Holster--



9. CONCLUSION

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the FCC. These measurements are taken to simulate the RF effects exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The test results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because innumerable factors may interact to determine the specific biological outcome of an exposure to electromagnetic fields, any protection guide shall consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables.



10. REFERENCES

- [1] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-2003 (Draft 6.1 – July 2001), *IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques..*
- [2] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), *Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields*, July 2001.
- [3] ANSI/IEEE C95.3 – 1991, *IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields – RF and Microwave*, New York: IEEE, 1992.
- [4] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.
- [5] ANSI/IEEE C95.1 – 1991, *American National Standard Safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz*, New York: IEEE, Aug. 1992.
- [6] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [7] NCRP, National Council on Radiation Protection and Measurements, *Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields*, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [8] T. Schmid, O. Egger, N. Kuster, *Automated E-field scanning system for dosimetric assessments*, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [9] K. Pokovic, T.Schmid, N. Kuster, *Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies*, ICECOM97, Oct. 1997, pp. 120-124.
- [10] G.Hartsgrove, A. raszewski, A. Surowiec, *Simulated Biological Materials for Electromagnetic Radiation Absorption Studies*, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36
- [11] Q. Balzano, O. Garay, T. Manning Jr., *Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones*, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [12] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, *Numerical Recipes in C*, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [13] K. Pokovic, T.Schmid, N. Kuster, *E-field Probe with improved isotropy in brain simulating liquids*, Proceedings of the ELMAR, Zadar, June 23-25, 1996, pp. 172-175.
- [14] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [15] V. Hombach, K.Meier, M. Burkhardt, E. Kuhn, N. Kuster, *The Dependence of EM Energy Absorption upon Human Head Modeling at 900MHz*, IEEE Transaction on Microwave Theory and Techniques, vol 44 no. 10, Oct. 1996, pp. 1865-1873.
- [16] N. Kuster and Q. Balzano, *Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz*, IEEE Transaction on Vehicular Technology, vol. 41, no.1, Feb.1992, pp. 17-23.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp.645-652.

APPENDIX A

SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. A.1) .

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

Figure A.1 SAR Mathematical Equation

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \sigma E^2 / \rho$$

Where :

- σ = conductivity of the tissue-simulant material (S/m)
- ρ = mass density of the tissue-simulant material (kg/m³)
- E = Total RMS electric field strength (V/m)

Note: The primary factors that control rate or energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.

APPENDIX B

Probe Calibration Process

Dosimetric Assessment Procedure

Each probe is calibrated according to a dosimetric assessment procedure described in **K. Pokovic, T.Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124** with an accuracy better than +/-10%. The spherical isotropy was evaluated with the procedure described in **K. Pokovic, T.Schmid, N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, June 23-25, 1996, pp. 172-175** and found to be better than +/-0.25dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe is tested.

Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz (see Fig. B.1), and in a waveguide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

Temperature Assessment

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe (see Fig. B.2).

$$SAR = C \frac{\Delta T}{\Delta t}$$

$$SAR = \frac{|E|^2 \cdot \sigma}{p}$$

where:

Δt = exposure time (30 seconds)

C = heat capacity of tissue (brain or muscle).

ΔT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T / \Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. Now it's possible to quantify the electric field in the simulated tissue by equating the thermally derived SAR to the E-field;

where:

σ = simulated tissue conductivity

p = Tissue density (1.25 g/cm³ for brain tissue)




Figure B.1. E-Field and Temperature measurements at 900MHz




Figure B.2. E-Field and temperature measurements at 1.9GHz

APPENDIX C

ANSI/IEEE C95.1 – 1992 RF EXPOSURE LIMITS

Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is the exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table C.1 Safety Limits for Partial Body Exposure

	UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)
SPATIAL PEAK SAR ¹ Brain	1.60	8.00
SPATIAL PEAK SAR ² Whole Body	0.08	0.40
SPATIAL PEAK SAR ³ Hands, Feet, Ankles, Wrists	4.00	20.00

¹ The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as tissue volume in the shape of a cube) and over the appropriate averaging time.

² The Spatial Average value of the SAR averaged over the whole body.

³ The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.