

MPE Calculations(WLAN: 802.11b)

- Frequency range : 2412 MHz ~ 2462 MHz
- Maximum RF output power : 16.29 dBm
- Maximum antenna peak gain : 1.95 dBi

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

$\begin{aligned} \text{EIRP} &= P + G \\ &= 16.29 \text{ dBm} + 1.95 \text{ dBi} \\ &= 18.24 \text{ dBm} \end{aligned}$	- Note P = Power input to the antenna(dBm) G = Power gain of the antenna(dBi)
---	---

- Power density at the specific separation

$\begin{aligned} S &= P G / (4 R^2 \pi) \\ &= 42.560 \times 1.567 / (4 \times 20^2 \times \pi) \\ &= 0.01327 \text{ mW/cm}^2 \end{aligned}$	- Note S = Maximum power dencity(mW/cm²) P = Power input to the antenna(mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna(20cm)
---	---

Conclusion : The exposure condition of this device is compliant with FCC rules.

The maximum permissible exposure(MPE) of the general population/Uncontrolled for this device is 1.0 mW/cm².
The power desity at 20cm does not exceed the 1.0mW/cm².

MPE Calculations(WLAN: 802.11g)

- Frequency range : 2412 MHz ~ 2462 MHz
- Maximum RF output power : 23.55 dBm
- Maximum antenna peak gain : 1.95 dBi

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

$\begin{aligned} \text{EIRP} &= P + G \\ &= 23.55 \text{ dBm} + 1.95 \text{ dBi} \\ &= 25.5 \text{ dBm} \end{aligned}$	- Note P = Power input to the antenna(dBm) G = Power gain of the antenna(dBi)
--	---

- Power density at the specific separation

$\begin{aligned} S &= P G / (4 R^2 \pi) \\ &= 226.46 \times 1.567 / (4 \times 20^2 \times \pi) \\ &= 0.07059 \text{ mW/cm}^2 \end{aligned}$	- Note S = Maximum power dencity(mW/cm²) P = Power input to the antenna(mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna(20cm)
---	---

Conclusion : The exposure condition of this device is compliant with FCC rules.

The maximum permissible exposure(MPE) of the general population/Uncontrolled for this device is 1.0 mW/cm².
The power desity at 20cm does not exceed the 1.0mW/cm².

MPE Calculations(WLAN: 802.11n)

- Frequency range : 2412 MHz ~ 2462 MHz
- Maximum RF output power : 22.58 dBm
- Maximum antenna peak gain : 1.95 dBi

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

▪ EIRP = P + G = 22.58 dBm + 1.95 dBi = 24.53 dBm	- Note P = Power input to the antenna(dBm) G = Power gain of the antenna(dBi)
---	---

- Power density at the specific separation

▪ S = P G / (4 R² π) = 181.13 X 1.567 / (4 X 20² X π) = 0.05646 mW/cm²	- Note S = Maximum power dencity(mW/cm²) P = Power input to the antenna(mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna(20cm)
---	---

Conclusion : The exposure condition of this device is compliant with FCC rules.

The maximum permissible exposure(MPE) of the general population/Uncontrolled for this device is 1.0 mW/cm².
The power desity at 20cm does not exceed the 1.0mW/cm².