



FCC EVALUATION REPORT FOR CERTIFICATION

Manufacturer : LG Electronics Inc.

642, Jinpyung-Dong, Gumi-Si

Gyeongsangbuk-Do, 730-360, Korea

Attn: Mr. Sang-Wook Lee, Chief research engineer

Date of Issue : December 24, 2007

Test Report No. : GETEC-E3-07-096

Test Site : Gumi College EMC Center
(Registration No.: 100749)

FCC ID.: BEJ19LG30UA

Applicant.: LG Electronics Inc.

Rule Part(s)	: FCC Part 15 Subpart B
Equipment Class	: Class B computing device peripheral (JBP)
EUT Type	: LCD TV/Monitor
Type of Authority	: Certification
Model No.	: 19LG30-UA
Trade name	: LG

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003 / Canadian standard ICES-003

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by,

Jae-Hoon Jeong, Senior Engineer
GUMI College EMC center

Reviewed by,

Tae-Sig Park, Technical Manager
GUMI College EMC center

CONTENTS

1. GENERAL INFORMATION	3
2. INTRODUCTION	4
3. PRODUCT INFORMATION	5
3.1 DESCRIPTION OF EUT.....	5
3.2 SUPPORT EQUIPMENT / CABLES USED	6
3.3 MODIFICATION ITEM(S)	7
4. DESCRIPTION OF TESTS	8
4.1 TEST CONDITION	8
4.2 CONDUCTED EMISSION	9
4.3 RADIATED EMISSION	10
5. CONDUCTED EMISSION.....	11
5.1 OPERATING ENVIRONMENT	11
5.2 TEST SET-UP.....	11
5.3 MEASUREMENT UNCERTAINTY	11
5.4 LIMIT	12
5.5 TEST EQUIPMENT USED	12
5.6 TEST DATA FOR POWER LINE CONDUCTED EMISSION	13
6. RADIATED EMISSION	17
6.1 OPERATING ENVIRONMENT	17
6.2 TEST SET-UP.....	17
6.3 MEASUREMENT UNCERTAINTY	17
6.4 LIMIT	18
6.5 TEST EQUIPMENT USED	18
6.6 TEST DATA FOR RADIATED EMISSION	19
7. SAMPLE CALCULATIONS.....	22
7.1 EXAMPLE 1 :	22
7.2 EXAMPLE 2 :	22
8. RECOMMENDATION & CONCLUSION.....	23
APPENDIX A – ATTESTATION STATEMENT	
APPENDIX B – PLOTS OF CONDUCTED EMISSIONS	
APPENDIX C – ID SAMPLE LABEL & LOCATION	
APPENDIX D – BLOCK DIAGRAM	
APPENDIX E – TEST SET-UP PHOTOGRAPHS	
APPENDIX F – EXTERNAL PHOTOGRAPHS	
APPENDIX G –INTERNAL PHOTOGRAPHS	
APPENDIX H – USER’S MANUAL	

Scope: Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and / or unintentional radiators for compliance with technical rules and regulations of the Federal Communications Commission.

1. General Information

Applicant: LG Electronics Inc.

Applicant Address: 642, Jinpyung-Dong, Gumi-Si, Gyeongsangbuk-do, Korea

Manufacturer: LG Electronics Inc.

Manufacturer Address: 642, Jinpyung-Dong, Gumi-Si, Gyeongsangbuk-do, Korea

Contact Person: Mr. Sang -Wook Lee, Chief research engineer

Tel No.: +82-54-470-5640

- **FCC ID** BEJ19LG30UA
- **EUT Type** LCD TV/Monitor
- **Model No.** 19LG30-UA
- **Trade Name** LG
- **Serial No.** Proto type
- **Rule Part(s)** FCC Part 15 Subpart B
- **Type of Authority** Certification
- **Test Procedure(s)** ANSI C63.4 (2003) / Canadian standard ICES-003
- **Dates of Test** December 19 ~ 20, 2007
- **Place of Test** **Gumi College EMC Center** (FCC Registration No.: 100749)
407, Bugok-Dong, Gumi-si, Gyeongsangbuk-Do, Korea
- **Test Report No.** GETEC-E3-07-096
- **Dates of Issue** December 24, 2007

2. Introduction

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Nose Emissions From Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ASNI C63.4-2003) was used in determining radiated and conducted emissions emanating from **LG Electronics Inc. LCD TV/Monitor (Model No.: 19LG30-UA)**

These measurement tests were conducted at **Gumi College EMC Center**.

The site address is 407, Bugok-Dong, Gumi-si, Gyeongsangbuk-Do, Korea

This test site is one of the highest point of Gumi 1 college at about 200 kilometers away from Seoul city and 40 kilometers away from Daegu city. It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 on October 19, 1992



Fig 1. The map above shows the Gumi College in vicinity area.

3. Product Information

3.1 Description of EUT

The Equipment Under Test (EUT) is the **LG Electronics Inc. LCD TV/Monitor (Model No.: 19LG30-UA)**
FCC ID.: BEJ19LG30-UA

MODELS		19LG30 (19LG30-UA)	22LG30 (22LG30-UA)
Dimensions (Width x Height x Depth)	Including stand	18.1 x 15.4 x 7.4 inches 458.8 x 391.0 x 189.2 mm	20.6 x 17.0 x 7.4 inches 522.2 x 432.4 x 189.2 mm
	Excluding stand	18.1 x 13.6 x 2.7 inches 458.8 x 344.5 x 69.0 mm	20.6 x 15.1 x 2.7 inches 522.2 x 383.3 x 69.0 mm
Weight	including stand	11.5 pounds / 5.2 kg	12.8 pounds / 5.8 kg
	excluding stand	10.1 pounds / 4.6 kg	11.5 pounds / 5.2 kg
Power requirement Television System Program Coverage External Antenna Impedance		AC100-240V ~ 50/60Hz NTSC-M, ATSC, 64 & 256 QAM VHF 2-13, UHF 14-69, CATV 1-135, DTV 2-69, CADTV 1-135 75 ohm	
Environment condition	Operating Temperature Operating Humidity	32 ~ 104°F (0 ~ 40°C) Less than 80%	
	Storage Temperature Storage Humidity	-4 ~ 140°F (-20 ~ 60°C) Less than 85%	

3.2 Support Equipment / Cables used**3.2.1 Used Support Equipment**

Description	Manufacturer	Model No.	S/N & FCC ID
PC	Hewlett Packard	D530	S/N: CNG34800PY FCC ID: DoC
Video card	ATI	ATI RV360	S/N: SN0402017176 FCC ID: DoC
Printer	Hewlett Packard	970CXI	S/N: MY9B01F1FG FCC ID: DoC
Serial Mouse	LOGITECH	M-S69	S/N: 334684-108 FCC ID: JNZ211443
Key-board	MRCROSOFT	X05-92626	S/N: 9262600296169 FCC ID: DoC
Joystick	Microsoft	X05-92626	S/N: 9262600296169 FCC ID: DoC
DVD player	LG Electronics Inc.	LC-954	S/N: 3850R-Z674K FCC ID: DoC
Headset	Gowoonsori	GW-500M	S/N: N/A FCC ID: DoC
TV signal generator	FLUKE	54200	S/N: 831011 FCC ID: DoC

See “Appendix E – Test Setup Photographs” for actual system test set-up

3.2.2 Used Cable(s)

Cable No.	Condition	Description
Power cable	Connected to the EUT	1.8m unshielded
Video cable(D-sub)	Connected to the EUT and PC	1.8m shielded with two ferrite cores.
Video cable(HDMI)	Connected to the EUT and PC	1.8m shielded
PC sound cable	Connected to the EUT and PC	1.8m shielded
Component cable	Connected to the EUT and DVD Player	3.0m shielded
Component sound cable	Connected to the EUT and DVD Player	3.0m shielded
AV in cable	Connected to the EUT and DVD Player	1.8m shielded
ANT cable	Connected to the EUT and TV signal generator	10m shielded
Headset cable	Connected to the EUT	1.25m shielded

3.3 Modification Item(s)

- None

4. Description of tests

4.1 Test Condition

The EUT was installed, arranged and operated in a manner that is most representative of equipment as typically used. The measurements were carried out while varying operating modes and cable positions within typically arrangement to determine maximum emission level.

The representative and worst test mode(s) were noted in the test report.

- Test Voltage / Frequency : AC 120V / 60Hz
- Test Mode(s)
 - . Monitor mode
 - . Radiated emission : 1680*1050/ 60Hz (Analog), 1680*1050/ 60Hz (HDMI)
 - . Conducted emission: 1680*1050/ 60Hz (Analog), 1680*1050/ 60Hz (HDMI)
1024*768/ 60Hz (Analog), 800*600/ 60Hz (Analog)
- Operating test pattern
 - . "H" character scrolling mode (Font size: 10)
 - . Black background white character
 - . Brightness and contrast was adjusted as maximum level
 - . 1 kHz sound tone with winamp player

4.2 Conducted Emission

The Line conducted emission test facility is inside a 4×8×2.5 meter shielded enclosure.

The EUT was placed on a non-conducting 1.0 by 1.5 meter table, which is 0.8 meters in height and 0.4 meters away from the vertical wall of the shielded enclosure.

The EUT is powered from the Rohde & Schwarz LISN (ESH2-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH3-Z5). Powers to the LISN are filtered by high-current high insertion loss power line filter.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

The RF output of the LISN was connected to the EMI test receiver (Rohde & Schwarz, ESCS30).

The EMI test receiver was scanned from 150 kHz to 30MHz with 20msec sweep time to determine the frequency producing the maximum EME from the EUT. The frequency producing the maximum level was re-examined using Quasi-Peak mode of the EMI test receiver.

The bandwidth of Quasi-peak mode was set to 9 kHz. Each emission was maximized consistent with typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum diagram emission. Excess cable lengths were bundled at center with 30 – 40 centi-meters.

Each EME reported was calibrated using the R/S signal generator




Fig 2. Impedance of LISN

4.3 Radiated Emission

Preliminary measurements were conducted 3m semi anechoic chamber using broadband antennas to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The technology configuration, mode of operation and turntable azimuth with respect to antenna was note for each frequency found.

The spectrum was scanned from 30 to 1000MHz using bicornical log antenna (Schwarzbeck, VULB9160). Above 1GHz, horn antenna (Schwarzbeck, BBHA9120D) was used.

Final measurements were made outdoors at 3m/10m-test range.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was re-examined and investigated using EMI test receiver. The detector function was set to CISPR quasi-peak mode average mode and the bandwidth of the receiver was set to 120 kHz or 1MHz depending on the frequency or type of signal.

The EUT, support equipment and interconnecting cables were reconfigured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8m high non-metallic 1.0×1.5 meter table.

The turntable containing the test sample was rotated; the antenna height was varied 1 to 4 meter and stopped at the azimuth or height producing the maximum emission.

Each EME reported was calibrated using the R/S signal generator




Fig 3. Dimensions of Open Site Test Area

5. Conducted Emission

5.1 Operating environment

Temperature : 23 °C
Relative humidity : 41 %

5.2 Test set-up

The conducted emission measurements were performed in the shielded room.

The EUT was placed on wooden table, 0.8m heights above the floor, 0.4m from the reference ground plane (GRP) wall and 0.8m from AMN.

AMN is bonded on horizontal reference ground plane.

The ground plane, which was electrically bonded to the shield room, ground system and all power lines entering the shield room, were filtered.

5.3 Measurement uncertainty

The measurement uncertainty was calculated in accordance with ISO "Guide to the expression of uncertainty in measurement".

The measurement uncertainty was given with a confidence of 95%.

Contribution	Probability Distribution	Uncertainty (±dB)	
		Power Port	Communication port
Receiver specification	Rectangular	0.50	0.50
LISN coupling specification	Rectangular	1.50	
ISN coupling specification	Rectangular		1.50
Mismatch LISN VRC : $\Gamma_l =$ 0.20 ISN VRC : $\Gamma_l =$ 0.20 ATT VRC(IN) : $\Gamma_g =$ 0.03 Uncertainty limits $20\log(1 \pm \Gamma_l \Gamma_g)$	U-shaped	0.05 -0.05	0.05 -0.05
Mismatch Receiver VRC : $\Gamma_l =$ 0.09 ATT VRC : $\Gamma_g =$ 0.11 Uncertainty limits $20\log(1 \pm \Gamma_l \Gamma_g)$	U-shaped	0.09 -0.09	0.09 -0.09
System repeatability	Std Deviation	0.55	0.55
Cable and input attenuator calibration	Normal (k=2)	0.08	0.08
Repeatability of EUT			
Combined standard uncertainty $U_c(y)$	Normal	1.07 -1.07	1.07 -1.07
Extended uncertainty U	Normal (k=2)	2.15 -2.15	2.15 -2.15

5.4 Limit

RFI Conducted	FCC Limit(dB) Class B	
Freq. Range	Quasi-Peak	Average
150kHz – 0.5MHz	66 – 56*	56 – 46*
0.5MHz – 5MHz	56	46
5MHz – 30MHz	60	50
*Limits decreases linearly with the logarithm of frequency.		

5.5 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Due to calibration
■ - ESCS30	Rohde & Schwarz	EMI test receiver	839809/003	12. 14. 2008
■ - ESH3-Z5	Rohde & Schwarz	Artificial mains network	838979/020	12. 13. 2008
■ - ESH2-Z5	Rohde & Schwarz	Artificial mains network	829991/009	12. 13. 2008

5.6 Test data for power line conducted emission

- Test Date : December 19, 2007
 -. Resolution bandwidth : 9 kHz
 -. Frequency range : 0.15MHz ~ 30MHz

◆ Test resolution: 1680*1050/60Hz (Analog)

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.154	0.09	-0.15	N	65.78	50.8	50.74	55.78	35.6	35.54	15.04	20.24
0.182	0.10	-0.20	N	64.39	47.2	47.11	54.39	29.4	29.31	17.29	25.09
0.278	0.11	-0.19	N	60.88	38.6	38.53	50.88	35.4	35.33	22.35	15.55
0.366	0.13	-0.14	L1	58.59	33.4	33.39	48.59	33.2	33.19	25.20	15.40
0.458	0.12	-0.15	N	56.73	30.4	30.37	46.73	26.0	25.97	26.36	20.76
0.674	0.14	-0.23	L1	56.00	27.9	27.81	46.00	24.2	24.11	28.19	21.89
0.758	0.14	-0.23	L1	56.00	31.7	31.61	46.00	27.4	27.31	24.39	18.69
0.994	0.13	-0.23	N	56.00	24.3	24.20	46.00	20.0	19.90	31.80	26.10
1.738	0.10	-0.30	N	56.00	30.0	29.80	46.00	27.5	27.30	26.20	18.70
2.774	0.09	-0.18	N	56.00	23.8	23.71	46.00	19.7	19.61	32.29	26.39
4.014	0.18	-0.14	L1	56.00	25.0	25.04	46.00	22.5	22.54	30.96	23.46
7.850	0.22	-0.01	L1	60.00	27.5	27.71	50.00	22.2	22.41	32.29	27.59
13.642	0.09	0.10	N	60.00	20.3	20.49	50.00	20.1	20.29	39.51	29.71

*Comment : Pol : L1 (Live), N(Neut)
 Insertion Loss : Insertion Loss of LISN
 Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

◆ Test resolution: 1680*1050/60Hz (HDMI)

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.150	0.11	-0.14	L1	66.00	51.2	51.17	56.00	35.6	35.57	14.83	20.43
0.182	0.10	-0.20	N	64.39	46.5	46.41	54.39	31.1	31.01	17.99	23.39
0.258	0.12	-0.20	L1	61.50	40.4	40.33	51.50	35.0	34.93	21.17	16.57
0.366	0.13	-0.14	L1	58.59	33.4	33.39	48.59	33.3	33.29	25.20	15.30
0.458	0.14	-0.15	L1	56.73	30.4	30.39	46.73	25.6	25.59	26.34	21.14
0.674	0.14	-0.23	L1	56.00	27.9	27.81	46.00	24.1	24.01	28.19	21.99
0.782	0.13	-0.23	N	56.00	30.9	30.80	46.00	23.9	23.80	25.20	22.20
1.218	0.14	-0.25	L1	56.00	27.1	26.99	46.00	24.1	23.99	29.01	22.01
1.878	0.09	-0.31	N	56.00	27.7	27.49	46.00	22.5	22.29	28.51	23.71
2.238	0.09	-0.28	N	56.00	39.3	39.11	46.00	27.0	26.81	16.89	19.19
3.246	0.17	-0.14	L1	56.00	20.1	20.13	46.00	19.8	19.83	35.87	26.17
12.026	0.09	0.00	N	60.00	14.5	14.59	50.00	14.4	14.49	45.41	35.51
16.058	0.50	0.00	L1	60.00	27.1	27.60	50.00	26.2	26.70	32.40	23.30

*Comment : Pol : L1 (Live), N(Neut)

Insertion Loss : Insertion Loss of LISN

Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

◆ Test resolution: 1024*768/60Hz (Analog)

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.150	0.09	-0.14	N	66.00	51.1	51.05	56.00	35.4	35.35	14.95	20.65
0.182	0.12	-0.20	L1	64.39	47.2	47.12	54.39	31.6	31.52	17.28	22.88
0.258	0.12	-0.20	L1	61.50	40.8	40.73	51.50	36.6	36.53	20.77	14.97
0.322	0.11	-0.16	N	59.66	35.5	35.45	49.66	34.2	34.15	24.20	15.50
0.410	0.12	-0.13	N	57.65	31.3	31.29	47.65	19.9	19.89	26.36	27.76
0.462	0.14	-0.15	L1	56.66	30.9	30.88	46.66	26.8	26.78	25.77	19.87
0.562	0.14	-0.21	L1	56.00	26.5	26.43	46.00	13.5	13.43	29.57	32.57
0.782	0.14	-0.23	L1	56.00	31.5	31.41	46.00	25.6	25.51	24.59	20.49
0.926	0.14	-0.23	L1	56.00	25.2	25.11	46.00	22.1	22.01	30.89	23.99
1.646	0.15	-0.29	L1	56.00	26.5	26.36	46.00	13.3	13.16	29.64	32.84
4.934	0.09	-0.16	N	56.00	20.2	20.13	46.00	14.6	14.53	35.87	31.47
13.742	0.38	0.10	L1	60.00	13.7	14.18	50.00	13.5	13.98	45.82	36.02
23.122	0.89	0.06	L1	60.00	17.0	17.94	50.00	11.8	12.74	42.06	37.26

*Comment : Pol : L1 (Live), N(Neut)

Insertion Loss : Insertion Loss of LISN

Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

◆ Test resolution: 640*480/60Hz (Analog)

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.150	0.11	-0.14	L1	66.00	51.5	51.47	56.00	35.6	35.57	14.53	20.43
0.182	0.10	-0.20	N	64.39	47.1	47.01	54.39	31.2	31.11	17.39	23.29
0.322	0.13	-0.16	L1	59.66	36.0	35.97	49.66	34.1	34.07	23.69	15.59
0.366	0.13	-0.14	L1	58.59	33.5	33.49	48.59	20.5	20.49	25.10	28.10
0.530	0.12	-0.19	N	56.00	26.8	26.73	46.00	23.0	22.93	29.27	23.07
0.662	0.14	-0.23	L1	56.00	26.7	26.61	46.00	24.2	24.11	29.39	21.89
0.782	0.13	-0.23	N	56.00	31.4	31.30	46.00	24.9	24.80	24.70	21.20
1.030	0.13	-0.23	N	56.00	23.0	22.90	46.00	9.0	8.90	33.10	37.10
1.378	0.14	-0.26	L1	56.00	27.3	27.18	46.00	23.7	23.58	28.82	22.42
1.974	0.09	-0.32	N	56.00	26.7	26.47	46.00	16.8	16.57	29.53	29.43
2.302	0.09	-0.27	N	56.00	28.5	28.32	46.00	15.7	15.52	27.68	30.48
23.662	0.90	0.02	L1	60.00	16.8	17.73	50.00	11.3	12.23	42.27	37.77

*Comment : Pol : L1 (Live), N(Neut)
Insertion Loss : Insertion Loss of LISN
Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

6. Radiated Emission

6.1 Operating environment

Temperature : 13°C
Relative humidity : 42 %

6.2 Test set-up

A preliminary scan with peak mode was performed in the semi anechoic chamber and found frequency for open area test site.

The formal radiated emission was measured at 3m/10m-distance open area test site.

The EUT was placed on a non-conductive turntable approximately 0.8 meters above the ground plane.

The turntable with EUT was rotated 360°, and the antenna was varied in height between 1.0 and 4.0 meters in order to determine the maximum emission levels.

This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

6.3 Measurement uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement”.

The measurement uncertainty was given with a confidence of 95%.

Contribution	Probability Distribution	Uncertainty (dB)			
		Biconical Ant.		Log-periodic Ant.	
		3m	10m	3m	10m
Ambient signal					
Antenna factor calibration	Normal (k=2)	0.50	0.50	0.50	0.50
Receiver specification	Rectangular	0.50	0.50	0.50	0.50
Antenna directivity	Rectangular	0.25	0.00	1.50	0.25
Antenna phase center variation	Rectangular	0.00	0.00	1.00	0.20
Antenna factor frequency interpolation	Rectangular	0.25	0.25	0.25	0.25
Measure distance variation	Rectangular	0.60	0.40	0.60	0.40
Site imperfections	Rectangular	-2.00	-2.40	2.50	2.40
Mismatch Receiver VRC : $\Gamma_l = 0.09$ Antenna VRC : $\Gamma_g = 0.43$ (Bi) 0.23 (Lp) Uncertainty limits $20\log(1 \pm \Gamma_l \Gamma_g)$	U-shaped	0.33 -0.35	0.33 -0.35	0.18 -0.18	0.18 -0.18
System repeatability	Std Deviation	0.82	0.82	0.79	0.79
Cable loss calibration	Normal (k=2)	0.09	0.09	0.09	0.09
Combined standard uncertainty $U_c(y)$	Normal	1.54 -1.54	1.70 -1.70	2.03 -2.03	1.68 -1.68
Extended uncertainty U	Normal (k=2)	3.09 -3.09	3.39 -3.40	4.05 -4.05	3.36 -3.36

6.4 Limit

Frequency (MHz)	FCC Limit @ 3m. dB μ V/m	CISPR Limit @ 10m. dB μ V/m
30 – 88	40.0	30.0
88 – 216	43.5	30.0
216 – 230	46.0	30.0
230 – 960	46.0	37.0
960 – 1000	54.0	37.0
> 1000	54.0	No Specified limit

6.5 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESI	Rohde & Schwarz	EMI test receiver	830482/010	12. 14. 2008
■ - HK116	Rohde & Schwarz	Biconical ANT	826861/018	12. 11. 2009
■ - HL223	Rohde & Schwarz	Log-periodic antenna	829228/011	12. 11. 2009
■ - HD100	HD GmbH	Position Controller	100/692/01	N/A
■ - DS415S	HD GmbH	Turntable	415/657/01	N/A
■ - MA240	HD GmbH	Antenna Mast	240/565/01	N/A
■ - BBHA9120D	Schwarzbeck	Horn ANT	597	04. 01. 2008
■ - AFS44-00101800-25-10P-44	MITEQ	Preamplifier	1258943	N/A


6.6 Test data for radiated emission

- Test Date : December 20, 2007
- Resolution bandwidth : 120 kHz / 1MHz
- Frequency range : 30MHz ~ 2000MHz
- Measurement distance : 3m

◆ Operating Condition: 1680*1050/60Hz (Analog)

Detector mode: Quasi- peak detector mode

Frequency (MHz)	Measurement Level				Limit (dBuV/m)	Margin (dBuV/m)	Positioning System		
	Reading	Antenna	Cable	Test Result			Pol.	Height	Angle
	Value(dBuV)	Factor(dB)	Loss(dB)	(dBuV/m)			(H/V)	(cm)	(deg)
86.77	14.0	8.65	2.54	25.2	40.0	14.8	V	110	355
114.02	18.9	10.62	2.84	32.3	43.5	11.2	V	109	263
121.16	21.1	11.10	2.92	35.1	43.5	8.4	V	100	280
147.47	17.4	12.23	3.34	32.9	43.5	10.6	V	122	301
192.35	14.3	13.58	3.79	31.7	43.5	11.8	V	119	277
206.66	13.9	14.04	3.98	31.9	43.5	11.6	V	105	266
270.77	20.2	17.04	4.75	42.0	46.0	4.0	H	100	176
743.87	10.1	20.94	8.16	39.2	46.0	6.8	V	200	0




< Fig 4. Radiated emission result (30MHz ~ 1000MHz)>

◆ Operating Condition: 1680*1050/60Hz (HDMI)

Detector mode: Quasi- peak detector mode

Frequency (MHz)	Measurement Level				Limit (dBuV/m)	Margin (dBuV/m)	Positioning System		
	Reading	Antenna	Cable	Test Result			Pol.	Height	Angle
	Value(dBuV)	Factor(dB)	Loss(dB)	(dBuV/m)			(H/V)	(cm)	(deg)
85.33	15.2	8.56	2.51	26.3	40.0	13.7	V	101	15
106.88	20.1	10.12	2.77	33.0	43.5	10.5	V	113	266
121.16	20.7	11.10	2.92	34.8	43.5	8.7	V	109	282
199.51	13.8	13.78	3.89	31.5	43.5	12.0	V	101	255
270.79	20.2	17.04	4.75	42.0	46.0	4.0	H	100	160
736.75	6.6	20.90	8.12	35.6	46.0	10.4	V	195	353
972.39	7.8	22.85	9.61	40.2	54.0	13.8	H	183	107




< Fig 5. Radiated emission result (30MHz ~ 1000MHz)>

◆ Operating Condition: 1680*1050/60Hz (Analog)

Detector mode: Peak detector mode / Average detector mode

Frequency (MHz)	Measurement Level						Limit (dBuV/m)		Margin (dBuV/m)		Positioning System		
	Reading Value (dBuV/m)		AF	AMP / CL	Test Result (dBuV/m)						Pol.	Height	Angle
	Peak	Average	(dB)	(dB)	Peak	Average	Peak	Average	Peak	Average	(H/V)	(cm)	(deg)
1097.21	58.6	44.3	25.0	-40.9	42.8	28.5	74.0	54.0	31.2	25.5	H	108	188
1299.22	62.0	46.7	25.4	-40.1	47.3	32.0	74.0	54.0	26.7	22.0	V	192	162
1415.21	59.5	42.4	25.6	-39.9	45.2	28.1	74.0	54.0	28.8	25.9	H	112	190
1548.01	57.5	41.5	25.8	-39.6	43.7	27.7	74.0	54.0	30.3	26.3	V	107	201
1798.01	57.1	41.6	26.0	-38.9	44.2	28.7	74.0	54.0	29.8	25.3	V	199	180




*Comment :AMP/CL : Cable loss + AMP gain

< Fig 6. Radiated emission result (1000MHz ~ 2000MHz)>

◆ Operating Condition: 1680*1050/60Hz (HDMI)

Detector mode: Peak detector mode / Average detector mode

Frequency (MHz)	Measurement Level						Limit (dBuV/m)		Margin (dBuV/m)		Positioning System		
	Reading Value (dBuV/m)		AF	AMP / CL	Test Result (dBuV/m)						Pol.	Height	Angle
	Peak	Average	(dB)	(dB)	Peak	Average	Peak	Average	Peak	Average	(H/V)	(cm)	(deg)
1080.01	65.0	61.6	25.0	-40.8	49.2	45.8	74.0	54.0	24.8	8.2	H	110	183
1404.41	62.4	49.0	25.6	-39.8	48.2	34.8	74.0	54.0	25.8	19.2	V	111	175
1620.02	64.7	55.3	25.9	-39.3	51.3	41.9	74.0	54.0	22.7	12.1	V	105	266
1835.98	63.3	52.5	26.1	-38.8	50.5	39.7	74.0	54.0	23.5	14.3	V	100	156



*Comment :AMP/CL : Cable loss + AMP gain

< Fig 7. Radiated emission result (1000MHz ~ 2000MHz)>

7. Sample Calculations

$$\begin{aligned} \text{dB}\mu\text{V} &= 20 \text{ Log}_{10}(\mu\text{V}/\text{m}) \\ \text{dB}\mu\text{V} &= \text{dBm} + 107 \\ \mu\text{V} &= 10^{(\text{dB}\mu\text{V}/20)} \end{aligned}$$

7.1 Example 1 :

■ 20.3 MHz

Class B Limit	=	250 μV	=	48 $\text{dB}\mu\text{V}$
Reading	=	- 67.8 dBm (Calibrated level)		
Convert to $\text{dB}\mu\text{V}$	=	- 67.8 $\text{dBm} + 107$	=	39.2 $\text{dB}\mu\text{V}$
$10^{(39.2\text{dB}\mu\text{V}/20)}$	=	91.2 μV		
Margin	=	39.2 – 48	=	-8.8
	=	8.8 dB below Limit		

7.2 Example 2 :

■ 66.7 MHz

Class B Limit	=	100 $\mu\text{V}/\text{m}$	=	40.0 $\text{dB}\mu\text{V}/\text{m}$
Reading	=	- 76.0 dBm (Calibrated level)		
Convert to $\text{dB}\mu\text{V}/\text{m}$	=	- 76.0 $\text{dBm} + 107$	=	31.0 $\text{dB}\mu\text{V}/\text{m}$
Antenna Factor + Cable Loss	=	5.8 dB		
Total	=	36.8 $\text{dB}\mu\text{V}/\text{m}$		
Margin	=	36.8 – 40.0	=	-3.2
	=	3.2 dB below Limit		

8. Recommendation & conclusion

The data collected shows that the **LG Electronics Inc. LCD TV/Monitor (Model No.: 19LG30-UA)** was complies with §15.107 and 15.109 of the FCC Rules.