

EMC TEST REPORT

Test item : LED LCD TV Monitor
Model No. : 42LT560C-UA
Order No. : 1202-00162
Date of receipt : 2012-02-06
Test duration : 2012-02-08 ~ 2012-02-11
Use of report : FCC CoC Marking
Date of Issue : 2012-02-16

Applicant : LG Electronics Inc.

9-1, Cheongho-ri, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea

Test laboratory : Digital EMC Co., Ltd.

683-3, Yubang-Dong, Cheoin-Gu, Yongin-Si, Gyeonggi-Do, 449-080, Korea

Test specification : ANSI C 63.4:2003
FCC Part 15 Subpart B
(Type of Device : Class B Personal Computers
and Peripherals (JBP))

Test environment : Temperature : (18 ~ 19) °C,
Humidity : (29 ~ 37) % R.H.

Test result : ☒ Comply ☐ Not Comply

The test results presented in this test report are limited only to the sample supplied by applicant and
the use of this test report is inhibited other than its purpose.


This test report shall not be reproduced except in full, without the written approval of DIGITAL EMC CO., LTD.

Tested by:



Assistant Manager
D.H.EUN

Reviewed by:



General Manager
C.H.LEE

The above test report is the accredited test results by Korea Laboratory Accreditation Scheme,
which signed the ILAC-MRA.

PRESIDENT OF DIGITAL EMC CO., LTD.

CONTENTS

1. General Remarks	3
2. Test Laboratory	3
3. General Information of EUT	4
4. Test Summary	5
4.1 Applied standards and test results	5
4.2 Test environment and conditions	5
4.3 Test result Summary	5
5. Test Set-up and operation mode	6
5.1 Principle of Configuration Selection.....	6
5.2 Test Operation Mode	6
5.3 Support Equipment Used.....	7
6. Test Results : Emission	8
6.1 Conducted Disturbance	8
6.2 Radiated Disturbance	15
Appendix 1.....	35
List of Test and Measurement Instruments	35

1. General Remarks

This report contains the result of tests performed by:

DIGITAL EMC CO., LTD.

Address : 683-3, Yubang-Dong, Cheoin-Gu, Yongin-Si, Gyeonggi-Do, 449-080, Korea

<http://www.digitalemcc.com>

Tel: +82-31-321-2664 Fax: +82-31-321-1664

2. Test Laboratory

Digital EMC Co., Ltd. Has been accredited / filed / authorized by the agencies listed in the following table;

Certificate	Nation	Agency	Code	Mark
Accreditation	Korea	KOLAS	393	ISO/IEC 17025
Site Filing	USA	FCC	101842 678747	Test Facility list & NSA Data
	Canada	IC	5740A-1 5740A-2	Test Facility list & NSA Data
	Japan	VCCI	C-1427 R-1364, R-3385 T-1442, G-338	Test Facility list & NSA Data
Certification	Korea	KC	KR0034	Test Facility list & NSA Data
	Germany	TUV	ROK1124C	ISO/IEC 17025

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the "General requirements for the competent of calibration and testing laboratory".

3. General Information of EUT

Model No.	42LT560C-UA
EUT Type	LED LCD TV Monitor
Serial No	NONE
FCC ID	BEJ42LT560CUA
Type of Sample Tested	Pre-Production
High Frequency	667 MHz
Rating	AC100-240 V~, 50/60 Hz, 1.0 A
Supplied Power for Test	AC120 V, 60 Hz
Applicant	LG Electronics Inc. 19-1, Cheongho-ri, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea
Manufacturer	LG Electronics Inc. 19-1, Cheongho-ri, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea

Resolution	Horizontal Frequency (KHz)	Vertical Frequency (Hz)
720x400	31.469	70.08
640x480	31.469	59.94
800x600	37.879	60.31
1024x768	48.363	60.00
1360x768	47.712	60.015
1280x1024	63.981	60.020
1920x1080	67.5	60.00

4. Test Summary

4.1 Applied standards and test results

Test Items	Applied Standards	Results
Conducted Disturbance	ANSI C63.4:2003	C
Radiated Disturbance	ANSI C63.4:2003	C
C=Comply N/C=Not Comply N/T=Not Tested N/A=Not Applicable		

The data in this test report are traceable to the national or international standards.

4.2 Test environment and conditions

Test Items	Test date (MM-DD)	Temp (°C)	Humidity (% R.H.)	Pressure (hPa)
Conducted Disturbance	02-08	19	37	-
Radiated Disturbance	02-11	18	29	

4.3 Test result Summary

(1) Conducted Emission(HDMI MODE)

Frequency [MHz]	Phase	Result [dB μ V]	Detector	Limit [dB μ V]	Margin [dB]
0.15293	L1	62.7	Quasi-Peak	65.8	3.1

(2) Radiated Emission(HDMI MODE)

Frequency [MHz]	Pol.	Result [dB(μ V/m)]	Detector	Limit [dB(μ V/m)]	Margin [dB]
929.260	V	42.7	Quasi-Peak	46.0	3.3

5. Test Set-up and operation mode

5.1 Principle of Configuration Selection

Emission : The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

5.2 Test Operation Mode

- DSUB MODE – Resolution : 1920 x 1080 Resolution (Worst Case)
- HDMI MODE – Resolution : 1920 x 1080 Resolution (Worst Case)
- USB MODE

EUT is the following operational conditions apply:

- a) Set the contrast control to maximum.
- b) Set the brightness control to maximum or at raster extinction if raster extinction occurs at less than maximum brightness.
- c) For color monitors, use white letters on a black background to represent all colors.
- d) Select the worse case of positive or negative video if both alternatives are available.
- e) Set character size and number of characters per line so that the typical maximum number of characters per screen is displayed.
- f) For a monitor that has no graphics capabilities, regardless of the video card used, a pattern consisting of random text shall be displayed. For a monitor with graphics capability, even though another videocard may be needed to accomplish a graphic display, a screen pattern consisting of lines of scrolling H's should be displayed. For a monitor that has no text capabilities, use a typical display. That pattern should be used for the remainder of the tests.

5.3 Support Equipment Used

Unit	Model No.	Serial No.	Manufacturer	CABLE				Backshell	FCC ID
				Connect type	Length (m)	ferrite core	shield		
PC	VOSTRO 430	9K77SBX	DELL	POWER	1.8	Not use	Non-shield	Plastic	DOC
				HDMI	1.8	Not use	Shield		
				DSUB	1.6	Use	Shield		
				STEREO	1.8	Not use	Non-shield		
				PS/2	1.6	Not use	Non-shield		
				PS/2	1.8	Not use	Non-shield		
KEYBOARD	SKG-210PB	TAKSB24503Y	MONITEREY INTERNATIONAL CORP	PS/2	1.6	Not use	Non-shield	Plastic	DOC
MOUSE	SML-510PB	TAKS903519Z	MONITEREY INTERNATIONAL CORP	PS/2	1.8	Not use	Non-shield	Plastic	DOC
CD/DVD PLAYER	DVP-NS92V	2000407	SONY EMCS	POWER AV	1.8 1.6	Not use	Non-shield	Plastic	DOC
USB MEMORY	JEWELRY	N/A	AXXEN	USB	-	-	-	-	DOC

6. Test Results : Emission

6.1 Conducted Disturbance

6.1.1 Measurement Procedure

In the range of 0.15MHz to 30MHz, the conducted disturbance was measured and set-up was made accordance with **ANSI C63.4**.

If the EUT is table top equipment, it was placed on a wooden table with a height of 0.8m above the reference ground plane and 0.4m from the conducting wall of the shielded room.

Also if the EUT is floor-standing equipment, it was placed on a non-conducted support with a height up to 0.15m above the reference ground plane.

Connect the EUT's power source lines to the appropriate power mains / peripherals through the LISN. All the other peripherals are connected to the 2nd LISN, if any.

Unused measuring port of the LISN was resistively terminated by 50 ohm terminator.

The measuring port of the LISN for EUT was connected to spectrum analyzer.

Using conducted emission test software, the emissions were scanned with peak detector mode.

After scanning over the frequency range, suspected emissions were selected to perform final measurement. When performing final measurement, the receiver was used which has Quasi-Peak detector and Average detector.

By varying the configuration of the test sample and the cable routing it was attempted to maximize the emission.

For further description of the configuration refer to the picture of the test set-up.

6.1.2 Limit for Conducted Disturbance

(1) Conducted disturbance at mains ports.

Frequency range (MHz)	Limits dB(μV)			
	Quasi-peak		Average	
	Class A	Class B	Class A	Class B
0.15 to 0.50	79	66 to 56	66	56 to 46
0.50 to 5	73	56	60	46
5 to 30		60		50
Note 1 The lower limit shall apply at the transition frequencies.				
Note 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.				

Test Result

< DSUB MODE >



Results of Conducted Emission



Digital EMC
 Date : 2012-02-08

Model No. : 42LT560C-UA
 Type :
 Serial No. :
 Test Condition : DSUB

Reference No. :
 Power Supply : 120V 60Hz
 Temp/Humi. : 19°C 37 % R.H.
 Operator :

Memo :

LIMIT : CISPR22_B QP
 CISPR22_B AV



Results of Conducted Emission

Digital EMC
Date : 2012-02-08

Model No. : 42LT560C-UA
Type :
Serial No. :
Test Condition : DSUB

Reference No. :
Power Supply : 120V 60Hz
Temp/Humi. : 19°C 37 % R.H.
Operator :

Memo :

LIMIT : CISPR22_B QP
CISPR22_B AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.15006	62.4	50.8	0.3	62.7	51.1	66.0	56.0	3.3	4.9	N
2	0.22239	36.8	35.5	0.2	37.0	35.7	62.7	52.7	25.7	17.0	N
3	0.29935	31.9	25.4	0.2	32.1	25.6	60.3	50.3	28.2	24.7	N
4	0.38543	33.1	25.2	0.3	33.4	25.5	58.2	48.2	24.8	22.7	N
5	0.43911	33.5	29.9	0.2	33.7	30.1	57.1	47.1	23.4	17.0	N
6	0.58321	26.3	17.7	0.2	26.5	17.9	56.0	46.0	29.5	28.1	N
7	13.06200	21.0	13.6	0.9	21.9	14.5	60.0	50.0	38.1	35.5	N
8	15.64550	27.7	8.4	1.0	28.7	9.4	60.0	50.0	31.3	40.6	N
9	0.15000	62.1	51.4	0.3	62.4	51.7	66.0	56.0	3.6	4.3	L1
10	0.22304	37.8	35.9	0.2	38.0	36.1	62.7	52.7	24.7	16.6	L1
11	0.30000	36.9	30.5	0.2	37.1	30.7	60.2	50.2	23.1	19.5	L1
12	0.38485	35.9	27.2	0.3	36.2	27.5	58.2	48.2	22.0	20.7	L1
13	0.43755	33.7	29.5	0.2	33.9	29.7	57.1	47.1	23.2	17.4	L1
14	0.58350	26.4	18.0	0.2	26.6	18.2	56.0	46.0	29.4	27.8	L1
15	13.08700	19.7	12.4	0.9	20.6	13.3	60.0	50.0	39.4	36.7	L1
16	15.87650	27.5	7.8	1.0	28.5	8.8	60.0	50.0	31.5	41.2	L1

< HDMI MODE >



Results of Conducted Emission



Digital EMC
Date : 2012-02-08

Model No. : 42LT560C-UA
Type :
Serial No. :
Test Condition : HDMI

Reference No. :
Power Supply : 120V 60Hz
Temp/Humi. : 19°C 37 % R.H.
Operator :

Memo :

LIMIT : CISPR22_B QP
CISPR22_B AV



Results of Conducted Emission

Digital EMC
 Date : 2012-02-08

Model No.	: 42LT560C-UA	Reference No.	:
Type	:	Power Supply	: 120V 60Hz
Serial No.	:	Temp/Humi.	: 19°C 37 % R.H.
Test Condition	: HDMI	Operator	:
Memo	:		

LIMIT : CISPR22_B QP
 CISPR22_B AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.15285	62.1	48.2	0.3	62.4	48.5	65.8	55.8	3.4	7.3	N
2	0.39693	32.4	24.0	0.3	32.7	24.3	57.9	47.9	25.2	23.6	N
3	0.43684	32.3	28.0	0.2	32.5	28.2	57.1	47.1	24.6	18.9	N
4	0.59633	25.0	14.3	0.2	25.2	14.5	56.0	46.0	30.8	31.5	N
5	15.83300	26.6	7.7	1.0	27.6	8.7	60.0	50.0	32.4	41.3	N
6	0.15293	62.4	48.7	0.3	62.7	49.0	65.8	55.8	3.1	6.8	L1
7	0.30490	36.6	27.8	0.2	36.8	28.0	60.1	50.1	23.3	22.1	L1
8	0.39274	35.0	26.4	0.3	35.3	26.7	58.0	48.0	22.7	21.3	L1
9	0.43643	33.3	28.5	0.2	33.5	28.7	57.1	47.1	23.6	18.4	L1
10	0.59586	25.7	15.6	0.2	25.9	15.8	56.0	46.0	30.1	30.2	L1
11	15.83150	26.6	8.4	1.0	27.6	9.4	60.0	50.0	32.4	40.6	L1

< USB MODE >



Results of Conducted Emission



Digital EMC
 Date : 2012-02-08

Model No. : 42LT560C-UA
 Type :
 Serial No. :
 Test Condition : USB

Reference No. :
 Power Supply : 120V 60Hz
 Temp/Humi. : 19°C 37 % R.H.
 Operator :

Memo :

LIMIT : CISPR22_B QP
 CISPR22_B AV



Results of Conducted Emission

Digital EMC
 Date : 2012-02-08

Model No. : 42LT560C-UA
 Type :
 Serial No. :
 Test Condition : USB

Reference No. :
 Power Supply : 120V 60Hz
 Temp/Humi. : 19°C 37 % R.H.
 Operator :

Memo :

LIMIT : CISPR22_B QP
 CISPR22_B AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.15102	62.3	49.3	0.3	62.6	49.6	65.9	55.9	3.3	6.3	N
2	0.33209	29.4	23.9	0.2	29.6	24.1	59.4	49.4	29.8	25.3	N
3	0.38536	32.7	24.8	0.3	33.0	25.1	58.2	48.2	25.2	23.1	N
4	0.59624	24.3	13.8	0.2	24.5	14.0	56.0	46.0	31.5	32.0	N
5	15.83000	27.9	8.7	1.0	28.9	9.7	60.0	50.0	31.1	40.3	N
6	0.15213	62.2	47.6	0.3	62.5	47.9	65.9	55.9	3.4	8.0	L1
7	0.30050	36.6	30.1	0.2	36.8	30.3	60.2	50.2	23.4	19.9	L1
8	0.38491	35.1	26.6	0.3	35.4	26.9	58.2	48.2	22.8	21.3	L1
9	0.59519	25.9	15.6	0.2	26.1	15.8	56.0	46.0	29.9	30.2	L1
10	13.29550	16.1	8.7	0.9	17.0	9.6	60.0	50.0	43.0	40.4	L1
11	15.87450	27.1	7.0	1.0	28.1	8.0	60.0	50.0	31.9	42.0	L1

6.2 Radiated Disturbance

6.2.1 Measurement Procedure

The radiated disturbance was measured and set-up was made accordance with **ANSI C63.4**.

If the EUT is tabletop equipment, it was placed on a wooden table with a height of 0.8m above the reference ground plane and 3m away from the interference receiving antenna in the **10m semi-anechoic chamber**.

Also if the EUT is floor-standing equipment, it was placed on a non-conducted support with a height up to 0.15m above the reference ground plane.

Rotate the EUT from 0° to 360° and position the receiving antenna at heights from 1 to 4m above the reference ground plane continuously to determine associated with higher emission levels and record them.

The measurement was made in both the vertical and horizontal polarization, and the maximum value is presented in the report.

For below 1GHz frequency range, Quasi-Peak detector with 120kHz RBW was used.

Also Peak and Average detector with 1MHz RBW were used for above 1GHz frequency range.

For further description of the configuration refer to the picture of the test set-up.

6.2.2 Limit for Radiated Disturbance

- The test frequency range of Radiated Disturbance measurements are listed below.

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

(1) Limit for Radiated Emission below 1000MHz

Frequency range (MHz)	Class A Equipment (10m distance)	Class B Equipment (3m distance)
	Quasi-peak (dB μ V/m)	Quasi-peak (dB μ V/m)
30 to 88	39.1	40
88 to 216	43.5	43.5
216 to 960	46.4	46
960 to 1000	49.5	54

Note 1 The lower limit shall apply at the transition frequency.

Note 2 Additional provisions may be required for cases where interference occurs.

Note 3 According to 15.109(g), as an alternative to the radiated emission limit shown above, digital devices may be shown to comply with the standards(CISPR), Pub. 22 shown as below.

Frequency range (MHz)	Class A Equipment (10m distance)	Class B Equipment (10m distance)
	Quasi-peak (dB μ V/m)	Quasi-peak (dB μ V/m)
30 to 230	40	30
230 to 1000	47	37

(2) Limits for Radiated Emission above 1000MHz at a measuring distance of 3m

Frequency (GHz)	Class A Equipment		Class B Equipment	
	Peak (dB μ V/m)	Average (dB μ V/m)	Peak (dB μ V/m)	Average (dB μ V/m)
1 to 40	80	60	74	54

Test Result

< DSUB MODE_30 MHz ~ 1 GHz >

RADIATED EMISSION


Date : 2012-02-11

Model Name : 42LT560C-UA
 Model No. :
 Serial No. :
 Test Condition : DSUB

Reference No. :
 Power Supply : 120V 60Hz
 Temp/Humi : 18 °C 29 % R.H.
 Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m)
 MARGIN: 3 dB



RADIATED EMISSION

Date : 2012-02-11

Model Name : 42LT560C-UA	Reference No. :
Model No. :	Power Supply : 120V 60Hz
Serial No. :	Temp/Humi : 18 °C 29 % R.H.
Test Condition : DSUB	Operator :

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m)
 MARGIN: 3 dB

No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	76.221	41.0	6.9	1.3	22.8	26.4	40.0	13.6	400	331
2	148.141	45.2	10.5	1.7	23.1	34.3	43.5	9.2	100	358
3	195.380	49.9	9.7	2.0	23.3	38.3	43.5	5.2	100	302
4	256.500	43.0	13.2	2.4	23.6	35.0	46.0	11.0	100	232
5	594.000	38.0	18.7	3.9	24.7	35.9	46.0	10.1	201	0
6	645.200	39.7	18.8	4.0	24.5	38.0	46.0	8.0	100	213
7	743.510	38.1	19.5	4.4	24.0	38.0	46.0	8.0	100	154
8	921.974	34.1	20.7	4.9	23.0	36.7	46.0	9.3	182	237
----- Vertical -----										
9	33.974	31.6	16.9	0.9	23.1	26.3	40.0	13.7	299	0
10	108.000	46.0	11.1	1.5	22.8	35.8	43.5	7.7	100	352
11	148.496	48.1	10.5	1.7	23.1	37.2	43.5	6.3	100	349
12	197.189	48.4	9.7	2.0	23.3	36.8	43.5	6.7	100	358
13	930.051	38.7	20.8	4.9	23.0	41.4	46.0	4.6	100	358

< DSUB MODE_1 GHz ~ 6 GHz_Peak >

RADIATED EMISSION



Date : 2012-02-11

Model Name : 42LT560C-UA
Model No. :
Serial No. :
Test Condition : DSUB

Reference No. :
Power Supply : 120V 60Hz
Temp/Humi : 18 'C 29 % R.H.
Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Peak)
FCC Part15 Subpart.B Class B (3m) - 18G(Avg)



RADIATED EMISSION

Date : 2012-02-11

Model Name	: 42LT560C-UA	Reference No.	:
Model No.	:	Power Supply	: 120V 60Hz
Serial No.	:	Temp/Humi	: 18 °C 29 % R.H.
Test Condition	: DSUB	Operator	:

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Peak)
 FCC Part15 Subpart B Class B (3m) - 18G(Avg)

No.	FREQ [MHz]	READING PEAK [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1440.705	60.9	25.0	5.8	41.6	50.1	74.0	23.9	100	203
2	1777.243	61.3	25.2	6.5	41.8	51.2	74.0	22.8	100	1
3	1945.512	59.6	25.2	6.9	41.7	50.0	74.0	24	100	172
4	2081.731	58.2	25.5	7.1	41.7	49.1	74.0	24.9	100	156
5	3235.594	54.0	29.0	9.1	41.8	50.3	74.0	23.7	100	185
----- Vertical -----										
6	1753.205	65.3	25.2	6.5	41.7	55.3	74.0	18.7	100	195
7	1809.295	60.8	25.2	6.6	41.8	50.8	74.0	23.2	100	358
8	1857.371	61.6	25.2	6.7	41.7	51.8	74.0	22.2	100	154
9	1937.500	61.2	25.2	6.9	41.7	51.6	74.0	22.4	100	358
10	2145.834	62.9	25.8	7.2	41.7	54.2	74.0	19.8	100	196
11	2971.167	56.8	28.7	8.7	41.9	52.3	74.0	21.7	100	198
12	3091.361	56.6	28.9	8.9	41.8	52.6	74.0	21.4	100	358
13	3235.594	54.2	29.0	9.1	41.8	50.5	74.0	23.5	100	358

< DSUB MODE_1 GHz ~ 6 GHz_Average >

RADIATED EMISSION


Date : 2012-02-11

Model Name : 42LT560C-UA
Model No. :
Serial No. :
Test Condition : DSUB

Reference No. :
Power Supply : 120V 60Hz
Temp/Humi : 18 °C 29 % R.H.
Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
FCC Part15 Subpart.B Class B (3m) - 18G(Peak)



RADIATED EMISSION

Date : 2012-02-11

Model Name	: 42LT560C-UA	Reference No.	:
Model No.	:	Power Supply	: 120V 60Hz
Serial No.	:	Temp/Humi	: 18 °C 29 % R.H.
Test Condition	: DSUB	Operator	:

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Avg)
 FCC Part15 Subpart B Class B (3m) - 18G(Peak)

No.	FREQ [MHz]	READING AV [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1449.500	40.6	25.0	5.8	41.6	29.8	54.0	24.2	100	203
2	1777.243	40.6	25.2	6.5	41.8	30.5	54.0	23.5	100	198
3	1941.070	40.6	25.2	6.9	41.7	31.0	54.0	23.0	100	172
4	2081.731	44.1	25.5	7.1	41.7	35.0	54.0	19.0	100	156
5	3235.594	38.9	29.0	9.1	41.8	35.2	54.0	18.8	100	185
----- Vertical -----										
6	1762.205	43.4	25.2	6.5	41.7	33.4	54.0	20.6	100	195
7	1857.371	41.0	25.2	6.7	41.7	31.2	54.0	22.8	100	154
8	1957.300	41.4	25.2	6.9	41.7	31.8	54.0	22.2	100	358
9	2139.834	40.9	25.8	7.2	41.7	32.2	54.0	21.8	100	196
10	2988.000	39.2	28.8	8.7	41.9	34.8	54.0	19.2	100	198
11	3102.000	39.4	28.9	8.9	41.8	35.4	54.0	18.6	100	358

< HDMI MODE_30 MHz ~ 1 GHz >

RADIATED EMISSION


Date : 2012-02-11

Model Name : 42LT560C-UA
Model No. :
Serial No. :
Test Condition : HDMI

Reference No. :
Power Supply : 120V 60Hz
Temp/Humi : 18 'C 29 % R.H.
Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m)
MARGIN: 3 dB



RADIATED EMISSION

Date : 2012-02-11

Model Name	: 42LT560C-UA	Reference No.	:
Model No.	:	Power Supply	: 120V 60Hz
Serial No.	:	Temp/Humi	: 18 °C 29 % R.H.
Test Condition	: HDMI	Operator	:

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m)
 MARGIN: 3 dB

No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	75.080	41.9	6.8	1.3	22.8	27.2	40.0	12.8	254	179
2	148.501	43.0	10.5	1.7	23.1	32.1	43.5	11.4	132	329
3	200.698	50.6	9.7	2.1	23.4	39.0	43.5	4.5	100	1
4	256.500	43.0	13.2	2.4	23.6	35.0	46.0	11.0	100	239
5	933.160	34.4	20.8	4.9	23.0	37.1	46.0	8.9	100	256
----- Vertical -----										
6	33.109	28.3	17.0	0.9	23.1	23.1	40.0	16.9	100	138
7	107.724	45.0	11.1	1.5	22.8	34.8	43.5	8.7	100	340
8	148.141	46.7	10.5	1.7	23.1	35.8	43.5	7.7	100	347
9	199.522	48.3	9.7	2.0	23.3	36.7	43.5	6.8	100	358
10	929.260	40.0	20.8	4.9	23.0	42.7	46.0	3.3	168	36

< HDMI MODE_1 GHz ~ 6 GHz_Peak >

RADIATED EMISSION


Date : 2012-02-11

Model Name : 42LT560C-UA
 Model No. :
 Serial No. :
 Test Condition : HDMI

Reference No. :
 Power Supply : 120V 60Hz
 Temp/Humi : 18 'C 29 % R.H.
 Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Peak)
 FCC Part15 Subpart.B Class B (3m) - 18G(Avg)



RADIATED EMISSION

Date : 2012-02-11

Model Name : 42LT560C-UA	Reference No. :
Model No. :	Power Supply : 120V 60Hz
Serial No. :	Temp/Humi : 18 °C 29 % R.H.
Test Condition : HDMI	Operator :

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Peak)
 FCC Part15 Subpart B Class B (3m) - 18G(Avg)

No.	FREQ [MHz]	READING PEAK [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1440.705	62.2	25.0	5.8	41.6	51.4	74.0	22.6	100	1
2	1753.205	62.6	25.2	6.5	41.7	52.6	74.0	21.4	100	132
3	2137.822	58.3	25.8	7.2	41.7	49.6	74.0	24.4	100	210
4	3435.918	53.7	29.1	9.4	42.0	50.2	74.0	23.8	100	1
----- Vertical -----										
5	1000.000	63.5	23.6	4.8	41.8	50.1	74.0	23.9	100	358
6	1745.192	67.7	25.2	6.5	41.7	57.7	74.0	16.3	100	195
7	1865.384	60.0	25.2	6.7	41.7	50.2	74.0	23.8	100	157
8	2145.834	63.8	25.8	7.2	41.7	55.1	74.0	18.9	100	197
9	3011.232	56.7	28.8	8.8	41.9	52.4	74.0	21.6	100	199

< HDMI MODE_1 GHz ~ 6 GHz_Average >

RADIATED EMISSION


Date : 2012-02-11

Model Name : 42LT560C-UA
Model No. :
Serial No. :
Test Condition : HDMI

Reference No. :
Power Supply : 120V 60Hz
Temp/Humi : 18 'C 29 % R.H.
Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
FCC Part15 Subpart.B Class B (3m) - 18G(Peak)



RADIATED EMISSION

Date : 2012-02-11

Model Name : 42LT560C-UA	Reference No. :
Model No. :	Power Supply : 120V 60Hz
Serial No. :	Temp/Humi : 18 °C 29 % R.H.
Test Condition : HDMI	Operator :

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Avg)
 FCC Part15 Subpart B Class B (3m) - 18G(Peak)

No.	FREQ [MHz]	READING AV [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1448.000	40.5	25.0	5.8	41.6	29.7	54.0	24.3	100	1
2	1753.205	41.4	25.2	6.5	41.7	31.4	54.0	22.6	100	132
3	2137.822	39.7	25.8	7.2	41.7	31.0	54.0	23.0	100	210
4	3435.918	38.1	29.1	9.4	42.0	34.6	54.0	19.4	100	1
----- Vertical -----										
5	1000.000	45.2	23.6	4.8	41.8	31.8	54.0	22.2	100	358
6	1746.000	45.3	25.2	6.5	41.7	35.3	54.0	18.7	100	195
7	1865.384	42.1	25.2	6.7	41.7	32.3	54.0	21.7	100	157
8	2145.834	41.9	25.8	7.2	41.7	33.2	54.0	20.8	100	197
9	2996.602	39.0	28.8	8.8	41.9	34.7	54.0	19.3	100	199

< USB MODE_30 MHz ~ 1 GHz >

RADIATED EMISSION


Date : 2012-02-11

Model Name : 42LT560C-UA
 Model No. :
 Serial No. :
 Test Condition : USB

Reference No. :
 Power Supply : 120V 60Hz
 Temp/Humi : 18 'C 29 % R.H.
 Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m)
 MARGIN: 3 dB



RADIATED EMISSION

Date : 2012-02-11

Model Name : 42LT560C-UA
 Model No. :
 Serial No. :
 Test Condition : USB

Reference No. :
 Power Supply : 120V 60Hz
 Temp/Humi : 18 °C 29 % R.H.
 Operator :

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m)
 MARGIN: 3 dB

No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	75.080	41.4	6.8	1.3	22.8	26.7	40.0	13.3	400	358
2	197.211	50.8	9.7	2.0	23.3	39.2	43.5	4.3	100	131
3	960.000	39.0	21.0	4.9	23.0	41.9	46.0	4.1	100	227
----- Vertical -----										
4	145.032	43.1	10.7	1.7	23.0	32.5	43.5	11.0	100	3
5	194.776	48.9	9.7	2.0	23.3	37.3	43.5	6.2	100	33
6	375.095	36.6	15.4	2.9	24.3	30.6	46.0	15.4	100	189

< USB MODE_1 GHz ~ 6 GHz_Peak >

RADIATED EMISSION



Date : 2012-02-11

Model Name : 42LT560C-UA
Model No. :
Serial No. :
Test Condition : USB

Reference No. :
Power Supply : 120V 60Hz
Temp/Humi : 18 'C 29 % R.H.
Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Peak)
FCC Part15 Subpart.B Class B (3m) - 18G(Avg)



RADIATED EMISSION

Date : 2012-02-11

Model Name : 42LT560C-UA	Reference No. :
Model No. :	Power Supply : 120V 60Hz
Serial No. :	Temp/Humi : 18 °C 29 % R.H.
Test Condition : USB	Operator :

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Peak)
 FCC Part15 Subpart B Class B (3m) - 18G(Avg)

No.	FREQ [MHz]	READING PEAK [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1024.038	60.3	23.7	4.9	41.8	47.1	74.0	26.9	100	188
2	1440.705	60.6	25.0	5.8	41.6	49.8	74.0	24.2	100	1
3	2081.731	56.9	25.5	7.1	41.7	47.8	74.0	26.2	100	1
----- Vertical -----										
4	1024.038	62.9	23.7	4.9	41.8	49.7	74.0	24.3	100	358
5	2169.873	56.1	25.9	7.3	41.7	47.6	74.0	26.4	100	358

< USB MODE_1 GHz ~ 6 GHz_Average >

RADIATED EMISSION


Date : 2012-02-11

Model Name : 42LT560C-UA
Model No. :
Serial No. :
Test Condition : USB

Reference No. :
Power Supply : 120V 60Hz
Temp/Humi : 18 'C 29 % R.H.
Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
FCC Part15 Subpart.B Class B (3m) - 18G(Peak)



RADIATED EMISSION

Date : 2012-02-11

Model Name	: 42LT560C-UA	Reference No.	:
Model No.	:	Power Supply	: 120V 60Hz
Serial No.	:	Temp/Humi	: 18 °C 29 % R.H.
Test Condition	: USB	Operator	:

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Avg)
 FCC Part15 Subpart B Class B (3m) - 18G(Peak)

No.	FREQ [MHz]	READING AV [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1033.647	41.1	23.7	4.9	41.8	27.9	54.0	26.1	100	188
2	1439.442	40.1	25.0	5.8	41.6	29.3	54.0	24.7	100	1
3	2078.000	39.1	25.5	7.1	41.7	30.0	54.0	24.0	100	1
----- Vertical -----										
4	1039.000	44.0	23.7	4.9	41.8	30.8	54.0	23.2	100	122
5	2169.873	39.2	25.9	7.3	41.7	30.7	54.0	23.3	100	358

Appendix 1

List of Test and Measurement Instruments

1. Conducted Disturbance

Name of Instrument	Model No.	Manufacturer	Serial No.	Cal. Date	Next Cal. Date
☐ SPECTRUM ANALYZER	8591E	H/P	3649A05889	2011.03.07	2012.03.07
☐ RFI/FIELD INTENSITY METER	KNM-2402	KYORITSU	4N-170-3	2011.07.02	2012.07.02
☐ LISN	KNW-407	KYORITSU	8-317-8	2012.01.09	2013.01.09
☐ LISN	KNW-242	KYORITSU	8-654-15	2011.07.01	2012.07.01
☐ 50 OHM TERMINATOR	CT-01	TME	N/A	2012.01.09	2013.01.09
☒ EMI TEST RECEIVER	ESCI	ROHDE & SCHWARZ	100364	2011.03.08	2012.03.08
☒ LISN	ESH2-Z5	ROHDE & SCHWARZ	828739/006	2011.09.30	2012.09.30
☒ LISN	LISN1600	TTI	197204	2011.07.02	2012.07.02
☒ 50 OHM TERMINATOR	CT-01	TME	N/A	2012.01.09	2013.01.09

2. Radiated Disturbance

Name of Instrument	Model No.	Manufacturer	Serial No.	Cal. Date	Next Cal. Date
☒ EMI TEST RECEIVER	ESU	ROHDE & SCHWARZ	100014	2012.01.09	2013.01.09
☒ BILOG ANTENNA	CBL6112B	SCHAFFNER	2737	2010.07.14	2012.07.14
☒ HORN ANTENNA	BBHA9120A	SCHWARZBECK	322	2010.04.13	2012.04.13
☒ AMPLIFIER	8447E	H/P	2945A02865	2012.01.09	2013.01.09
☒ AMPLIFIER	MLA-00108-B02-36	TSJ	1518831	2012.01.09	2013.01.09
☐ SPECTRUM ANALYZER	E4411B	AGILENT	US41062735	2011.07.01	2012.07.01
☐ AMPLIFIER	8447D	AGILENT	2443A03690	2011.07.01	2012.07.01
☐ BILOG ANTENNA	VULB9160	SCHAFFNER	3151	2010.08.25	2012.08.25
☐ EMI TEST RECEIVER	ESCI	ROHDE & SCHWARZ	100364	2011.03.08	2012.03.08
☐ BICONICAL ANT.	VHA 9103	SCHWARZBECK	91032789	2010.11.29	2012.11.29
☐ LOG-PERIODIC ANT.	UHALP 9108A	SCHWARZBECK	590	2010.07.07	2012.07.07
☐ BICONICAL ANT.	VHA 9103	SCHWARZBECK	91031946	2010.12.21	2012.12.21
☐ LOG-PERIODIC ANT.	UHALP 9108-A1	SCHWARZBECK	1098	2010.11.29	2012.11.29
☐ AMPLIFIER	MLA-100K01-B01-26	TSJ	1252741	2011.03.07	2012.03.07