

	ESTECH Co., Ltd. Rm 1015, World Venture Center II, 426-5 Gasan-dong, Guncheon-gu, Seoul, 158-803, Korea	    	Electromagnetic Interference Test Report
---	---	--	---

Test Report for FCC

Report Number		ESTF150608-005			
Applicant	Company name	LG Electronics USA			
	Address	1000 Sylvan Avenue Englewood Cliffs, NJ 07632			
	Telephone	847-941-8373			
Product	Product name	PLASMA MONITOR			
	Basic Model	42PC3DVU-UE	Manufacturer	LG Electronics Inc.	
	Additional Models	42PC3D-UE, Z42PC3DU,Z42PC3D	Country of origin	KOREA	
Test date	2006-8-8~2006-8-9		Date of issue	14-Aug-06	
Testing location	ESTECH. Co., Ltd. 97-1 Hoiuk-Ri Majang-Myon, Icheon-city, KyungKi-Do, Korea				
Standard	FCC PART 15 2006 , ANSI C 63.4 2003 , ICES-003				
Test item	☒ Conducted Emission	☐ Class A	☒ Class B	Test result	OK
	☒ Radiated Emission	☐ Class A	☒ Class B	Test result	OK
Measurement facility registration number		94696			
Tested by	Engineer J.H.Kim  (Signature)				
Reviewed by	Manager Engineer J.M.Yang  (Signature)				
Abbreviation	OK, Pass = Passed, Fail = Failed, N/A = not applicable				
* Note - Basic Model : 42PC3DVU-UE Additional Models : 42PC3D-UE,Z42PC3DU,Z42PC3D - Basic Model and Addition Models are same product,only model name is different. - This test report is not permitted to copy partly without our permission - This test result is dependent on only equipment to be used - This test result based on a single evaluation of one sample of the above mentioned					

Contents

1. Laboratory Information	3
2. Description of EUT	4
3. Test Standards	5
4. Measurement condition	6
5. Measurement of radiated emission	8
5.1 Measurement equipment	8
5.2 Environmental conditions	8
5.3 Test data	9
5.4 Test data	10
6. Measurement of conducted emission	11
6.1 Measurement equipment	11
6.2 Environmental conditions	11
6.3 Test data	12
7. Photographs of test setup	13
8. Photographs of EUT	15

Appendix 1. Spectral diagram

1. Laboratory Information

1.1 General

This EUT (Equipment Under Test) has been shown to be capable of compliance with the applicable technical standards and is tested in accordance with the measurement procedures as indicated in this report. ESTECH Lab attests to accuracy of test data. All measurement reported herein were performed by ESTECH Co., Ltd.

ESTECH Lab assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

1.2 Test Lab.

Corporation Name : ESTECH Co. Ltd

Head Office : Rm 1015, World Venture Center II, 426-5, Gasan-dong, Geumcheon-gu, Seoul, Korea
(Safety & Telecom. Test Lab)

EMC Test Lab : 58-1 Osan-Ri, GaNam-Myon, YeoJoo-Gun, KyungKi-Do, Korea
97-1 Hoiuk-Ri Majang-Myon, Icheon-city, KyungKi-Do, Korea

1.3 Official Qualification(s)

MIC : Granted Accreditation from Ministry of Information & Communication for EMC, Safety and Telecommunication

KOLAS : Accredited Lab By Korea Laboratory Accreditation Schema base on CENELEC requirements

FCC : Filed Laboratory at Federal Communications Commission

VCCI : Granted Accreditation from Voluntary Control Council for Interference from ITE

2. Description of EUT

2.1 Summary of Equipment Under Test

NONE : PLASMA MONITOR
 Model Number : 42PC3DVU-UE
 Serial Number : NONE
 Manufacturer : LG Electronics Inc.
 Country of origin : KOREA
 Rating : INPUT:AC120V / 60Hz
 Receipt Date : 2006-08-08

2.2 General descriptions of EUT

**Supported Display Resolution
(RGB-PC, HDMI1/DVI, HDMI2 Mode)**

Resolution	Horizontal Frequency (kHz)	Vertical Frequency (Hz)	Resolution	Horizontal Frequency (kHz)	Vertical Frequency (Hz)
640x350	31.468	70.08	1280x768	47.776	59.87
640x480	31.469	59.94	1360x768	47.720	59.80
720x400	31.469	70.08	1366x768	47.130	59.65
* 720x480	31.469	59.94	*1920x1080i	33.716	59.94
	31.500	60.00		33.750	60.00
800x600	37.879	60.31	*1920x1080p	27.000	24.00
1024x768	48.363	60.00		33.750	30.00
*1280x720	44.955	59.94	* This format is only for HDMI-DTV input.		
	45.000	60.00			

• 42PC3DVU is not supported to 1280x768, 1360x768, 1366x768, 1920x1080P.

60PC1D (60PC1D-UE)	Dimensions (Width x Height x Depth)	with stand	60.8 x 40.8 x 16.0 inches 1544.0 x 1035.5 x 408.2 mm
		without stand	60.8 x 38.4 x 4.7 inches 1544.0 x 977.0 x 119.2 mm
	Weight	with stand	163 pounds / 74.0 kg
		without stand	137.3 pounds / 62.26 kg
42PC3DU (42PC3DU-UE)	Dimensions (Width x Height x Depth)	with stand	44.4 x 29.5x 15.0 inches 1129.0 x 748.5 x 380.0 mm
		without stand	44.4 x 27.4 x 4.1 inches 1129.0 x 695 x 103.7 mm
	Weight	with stand	64.4 pounds / 29.2 kg
		without stand	55.8 pounds / 25.3 kg
42PC3DVU (42PC3DVU-UE)	Dimensions (Width x Height x Depth)	with stand	44.4 x 29.5x 15.0 inches 1129.0 x 748.5 x 380.0 mm
		without stand	44.4 x 27.4 x 4.1 inches 1129.0 x 695 x 103.7 mm
	Weight	with stand	62.6 pounds / 28.4 kg
		without stand	54.0 pounds / 24.5 kg
50PC3DU (50PC3DU-UE)	Dimensions (Width x Height x Depth)	with stand	51.3 x 34.3 x 14.0 inches 1302.6 x 872.0 x 355.8 mm
		without stand	51.3 x 31.9 x 4.2 inches 1302.6 x 810.0 x 107.7 mm
	Weight	with stand	114.4 pounds / 51.9 kg
		without stand	95.0 pounds / 43.1 kg
Power requirement Television System Program Coverage			AC100-240V ~ 50/60Hz NTSC-M, ATSC, 64 & 256 QAM VHF 2 ~ 13, UHF 14 ~ 69, CATV 1 ~ 135, CDTV 1 ~ 135, DTV 2 ~ 69
External Antenna Impedance			75 Ω
Environmental condition	Operating Temperature		32 ~ 104°F (0 ~ 40°C)
	Operating Humidity		Less than 80%
	Storage Temperature		-4 ~ 140°F (-20 ~ 60°C)
	Storage Humidity		Less than 85%

Using Freq. : 4MHz, 50MHz, 24MHz. 14.3MHz, 54MHz

3. Test Standards

Test Standard : FCC PART 15 (2006) & ICES-003

This Standard sets out the regulations under which an intentional, unintentional, or incidental radiator may be operated without an individual license. It also contains the technical specifications, administrative requirements and other conditions relating to the marketing of Part 15 devices.

Test Method : ANSI C 63.4 (2003)


This standard sets forth uniform methods of measurement of radio-frequency (RF) signals and noise emitted from both unintentional and intentional emitters of RF energy in the frequency range 9 kHz to 40 GHz. Methods for the measurement of radiated and AC power-line conducted radio noise are covered and may be applied to any such equipment unless otherwise specified by individual equipment requirements. These methods cover measurement of certain devices that deliberately radiate energy, such as intentional emitters, but does not cover licensed transmitters. This standard is not intended for certification/approval of avionic equipment or for industrial, scientific, and medical (ISM) equipment. These methods apply to the measurement of individual units or systems comprised of multiple units.

4. Measurement Condition

4.1 EUT Operation.

- * The EUT was in the following operation mode during all testing
- * The operational conditions of the EUT was determined by the manufacturer according to the typical use of the EUT with respect to the expected highest level of emission
- * After setting as test arrangement diagram, we tested the EUT under continuous displaying "H" character and playing Audio out /Video

4.2 Configuration and Peripherals



4.3 EUT and Support equipment

Equipment Name	Model Name	S/N	Manufacturer	Remark (FCC ID)
PLASMA MONITOR	42PC3DVU-UE	PC3D-UE, Z42PC3DU,Z42PC3	LG Electronics Inc.	EUT
PC	DCSM	85RFJ1S	Dell Asia Pacific sdn	-
PRINTER	C6414J	TH18M149P2	Hewlett packed	-
ADAPTER	C6409-60152	C1H14B	YKOGAWA	-
KEYBOARD	SKG-220C	TAKL217007P	MONTEREY INTERANTIONAL CORP	-
MOUSE	M-BE58	HCA32000098	Logitech	-

4.4 Cable Connecting

Start Equipment		End Equipment		Cable Standard		Remark
Name	I/O port	Name	I/O port	Length	Shielded	
PLASMA MONITOR	RGB	PC	RGB	2	Y	
PLASMA MONITOR	DVI	PC	DVI	2	Y	
PLASMA MONITOR	S-VIDEO	-	-	2	Y	
PLASMA MONITOR	LINE IN	-	LINE OUT	2	N	
PLASMA MONITOR	S-VIDEO	-	-	2	Y	
PLASMA MONITOR	COMPONENT1 -5PORT	-	-	2	N	
PLASMA MONITOR	COMPONENT2 -5PORT	-	-	2	N	
PLASMA MONITOR	AV IN1-3PORT	-	-	2	N	
PLASMA MONITOR	AV IN2-3PORT	-	-	2	N	
PLASMA MONITOR	AVOUT-3PORT	-	-	2	N	
PLASMA MONITOR	ANT	-	-	2	N	
PC	USB	KEYBOARD	USB	2	Y	
PC	USB	MOUSE	USB	2	Y	
PC	USB	PRINTER	USB	2	Y	
PRINTER	POWER	-	-	2	N	

5. Measurement of radiated disturbance

Above 30 MHz Electric Field strength was measured in accordance with FCC Part 15 (2006) & ICES-003. The test setup was made according to ANSI C 63.4 (2003) on an open test site, which allows a 3m distance measurement. The EUT was placed in the center of wooden turntable. The height of this table was 0.8m. The measurement was conducted with both horizontal and vertical antenna polarization. The turntable has fully rotated. For further description of the configuration refer to the picture of the test setup.

5.1 Measurement equipments

Equipment Name	Type	Manufacturer	Serial No.	Next Calibration date
TEST Receive	ESVS10	Rohde & Schwarz	838562/002	2007. 1. 23
Spectrum Analyzer	R3262C	ADVANTEST	61720116	2007. 4. 19
LogBicon Antenna	VULB 9160	Schwarzbeck	3142	2007. 5. 03
Anokufuer	310N	Sonoma Instrument	185723	2006. 9 . 23
Turn Table	2087	EMCO	2129	—
Antenna Mast	2070-01	EMCO	9702-203	—
ANT Mast Controller	2090	EMCO	1535	—
Turn Table Controller	2090	EMCO	1535	—

5.2 Environmental Condition

Test Place : Open site(3m)
 Temperature (°C) : 32 °C
 Humidity (%) : 49 %

5.3 Test data

Test Date : 9-Aug-06

Measurement Distance : 3 m

Frequency (MHz)	Reading (dB μ V)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dB μ V/m)	Result (dB μ V/m)	Margin (dB)
37.62	19.40	V	1.0	12.42	0.9	40.0	32.76	-7.24
53.38	16.60	V	1.0	12.60	1.0	40.0	30.25	-9.75
110.41	13.10	V	1.0	11.08	1.6	43.5	25.78	-17.72
120.41	12.20	H	1.9	12.04	1.7	43.5	25.92	-17.58
149.28	9.10	V	1.0	13.45	1.9	43.5	24.44	-19.06
168.00	11.60	H	1.5	13.95	2.0	43.5	27.56	-15.94
220.77	16.40	H	1.4	10.78	2.3	46.0	29.48	-16.52
250.19	12.50	H	1.2	11.92	2.4	46.0	26.80	-19.20
300.00	9.40	V	1.0	13.19	2.7	46.0	25.29	-20.71
350.00	12.00	H	1.0	14.30	2.9	46.0	29.18	-16.82
400.00	14.70	H	1.0	15.32	3.2	46.0	33.17	-12.83
500.25	13.20	H	1.0	17.06	3.6	46.0	33.81	-12.19
600.00	6.50	H	1.0	19.16	4.0	46.0	29.61	-16.39
700.00	6.60	H	1.0	20.14	4.3	46.0	31.02	-14.98
800.00	12.00	V	1.0	21.76	4.7	46.0	38.46	-7.54
Remark	H : Horizontal, V : Vertical TEST MODE ; Resolution 1024 * 768 (60Hz) at RGB mode (Worse Case)							

5.4 Test data

Test Date : 9-Aug-06

Measurement Distance : 3 m

Frequency (MHz)	Reading (dB μ V)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dB μ V/m)	Result (dB μ V/m)	Margin (dB)
35.61	20.10	V	1.0	12.41	0.9	40.0	33.43	-6.57
54.02	18.10	V	1.0	12.61	1.1	40.0	31.76	-8.24
108.81	13.00	V	1.0	10.39	1.5	43.5	24.91	-18.59
120.40	12.20	H	2.0	12.04	1.7	43.5	25.92	-17.58
150.11	8.90	H	1.6	13.90	1.9	43.5	24.68	-18.82
168.00	14.10	V	1.0	13.95	2.0	43.5	30.06	-13.44
220.11	17.20	H	1.2	10.76	2.3	46.0	30.26	-15.74
270.00	18.80	H	1.1	12.47	2.5	46.0	33.77	-12.23
300.00	8.90	V	1.0	13.19	2.7	46.0	24.79	-21.21
350.00	12.00	H	1.0	14.30	2.9	46.0	29.18	-16.82
400.00	13.10	H	1.0	15.32	3.2	46.0	31.57	-14.43
565.41	10.00	V	1.0	18.29	3.8	46.0	32.07	-13.93
600.00	10.10	H	1.0	19.16	4.0	46.0	33.21	-12.79
784.01	8.10	H	1.0	21.64	4.6	46.0	34.36	-11.64
800.00	11.00	V	1.0	21.76	4.7	46.0	37.46	-8.54
Remark	H : Horizontal, V : Vertical TEST MODE ; Resolution 1024 * 768 (75Hz) at DVI mode (Worse Case)							

6. Measurement of conducted disturbance

The continuous disturbance voltage of AC Mains in the frequency from 0.15 to 30 MHz was measured in accordance to FCC Part 15 (2006) & ICES-003. The test setup was made according to ANSI C 63.4 (2003) in a shielded. The EUT was placed on a non-conductive table at least 80 above the ground plan. A grounded vertical reference plane was positioned in a distance of 40cm from the EUT. The distance from the EUT to other metal surfaces was at least 0.8m. The EUT was only earthen by its power cord through the line impedance stabilizing network. The power cord has been bundled to a length of 1.0m.. The test receiver with Quasi Peak detector complies with CISPR 16.

6.1 Measurement equipments

Equipment Name	Type	Manufacturer	Serial No.	Next Calibration date
LISN	NNLA8120A	Schwarzbeck	8120161	2007. 2. 27
LISN	ESH3-Z5	Schwarzbeck	838979/010	2007. 2. 27
TEST Receive	ESP17	Rohde & Schwarz	100185	2006. 8. 22
Pulse Limiter	ESH3Z2	Rohde & Schwarz	NONE	2007. 6. 15

6.2 Environmental Condition

Test Place : Shield Room
 Temperature (°C) : 22 °C
 Humidity (%) : 49 %

6.3 Test data

Test Date : 8-Aug-06

Measurement Distance : 3 m

Frequency (MHz)	Correction Factor		Line (H/N)	Quasi-peak Value			Average Value		
	Lisn (dB)	Cable (dB)		Limit (dB μ V)	Reading (dB μ V)	Result (dB μ V)	Limit (dB μ V)	Reading (dB μ V)	Result (dB)
0.15	0.07	0.0	H	66.00	45.00	45.07	56.00	—	—
0.19	0.07	0.0	H	64.08	47.69	47.79	54.08	43.51	43.61
0.20	0.07	0.0	H	63.69	37.70	37.80	53.69	29.97	30.07
0.24	0.07	0.1	N	62.06	38.68	38.81	52.06	36.87	37.00
0.28	0.07	0.1	H	60.70	42.64	42.80	50.70	37.24	37.40
0.29	0.07	0.1	N	60.67	41.38	41.54	50.67	36.32	36.48
0.30	0.07	0.1	N	60.30	35.13	35.30	50.30	32.96	33.13
0.38	0.07	0.1	H	58.37	39.59	39.80	48.37	36.61	36.82
0.47	0.07	0.2	H	56.50	39.61	39.87	46.50	38.47	38.73
0.56	0.07	0.2	H	56.00	36.75	37.02	46.00	35.18	35.45
0.57	0.07	0.2	N	56.00	38.12	38.39	46.00	36.19	36.46
0.66	0.08	0.2	N	56.00	38.78	39.06	46.00	36.04	36.32
0.76	0.09	0.2	N	56.00	39.65	39.94	46.00	33.75	34.04
1.24	0.09	0.2	N	56.00	37.16	37.48	46.00	28.75	29.07
1.30	0.10	0.2	N	56.00	36.21	36.54	46.00	28.12	28.45
1.52	0.10	0.3	N	56.00	38.69	39.04	46.00	—	—
12.43	0.48	0.7	N	60.00	34.97	36.15	50.00	21.82	23.00
Remark	H : Hot Line, N : Neutral Line								

7. Photographs of test setup

7.1 Setup for Radiated Test : 30 ~ 1000 MHz

[Front]




[Rear]



7.2 Setup for Conducted Test : 0.15 ~ 30 MHz

[Front]



[Rear]



8. Photographs of EUT


[Front]



[Rear]



Appendix 1. Spectral diagram



Comment: 42PC3DU-UE (DVI) HOT
Date: 8.AUG.2006 19:07:43

*NEUTRAL




ESTECH

RBW 9 kHz

MT 1 s

PREAMP OFF

Att 10 dB



Comment: 42PC3DU-UE (DVI) NEUTRAL

Date: 8.AUG.2006 19:14:36