

FCC EVALUATION REPORT FOR CERTIFICATION

Applicant : LG Electronics Inc.

19-1, Cheongho-ri, Jinwi-myeon,

Pyeongteak-si, Gyeonggi-do, Korea.

Attn: Mr. Sang-Wook Lee, Chief research engineer

Date of Issue : December 21, 2009

Order Number: GETEC-C1-09-265

Test Report Number: GETEC-E3-09-159

Test Site: Gumi College EMC Center

FCC Registration Number: (100749, 443957)

FCC ID.: BEJ47LE7500UC

Applicant: LG Electronics Inc.

Rule Part(s)	: FCC Part 15 Subpart B
Equipment Class	: Class B computing device peripheral (JBP)
EUT Type	: LED LCD TV/Monitor
Type of Authority	: Certification
Model Name	: 47LE7500-UC, 47LE5400-UC, 47LE5500-UA
Trade Name	: LG

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003 / Canadian standard ICES-003

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by,

Reviewed by,


Hyoungh Seop Kim, Associate Engineer
GUMI College EMC center


Jae-Hoon Jeong, Senior Engineer
GUMI College EMC center



CONTENTS

1. GENERAL INFORMATION	3
2. INTRODUCTION	4
3. PRODUCT INFORMATION	5
3.1 DESCRIPTION OF EUT.....	5
3.2 SUPPORT EQUIPMENT / CABLES USED	6
3.3 MODIFICATION ITEM(S).....	7
4. DESCRIPTION OF TESTS.....	8
4.1 TEST CONDITION.....	8
4.2 CONDUCTED EMISSION	9
4.3 RADIATED EMISSION.....	10
5. CONDUCTED EMISSION.....	11
5.1 OPERATING ENVIRONMENT	11
5.2 TEST SET-UP	11
5.3 MEASUREMENT UNCERTAINTY.....	11
5.4 LIMIT	12
5.5 TEST EQUIPMENT USED.....	12
5.6 TEST DATA FOR CONDUCTED EMISSION	12
6. RADIATED EMISSION	23
6.1 OPERATING ENVIRONMENT	23
6.2 TEST SET-UP	23
6.3 MEASUREMENT UNCERTAINTY.....	23
6.4 LIMIT	24
6.5 TEST EQUIPMENT USED.....	24
6.6 TEST DATA FOR RADIATED EMISSION.....	24
7. SAMPLE CALCULATIONS.....	31
7.1 EXAMPLE 1 :	31
7.2 EXAMPLE 2 :	31
8. RECOMMENDATION & CONCLUSION.....	32
 APPENDIX A – ATTESTATION STATEMENT	
APPENDIX B – ID SAMPLE LABEL & LOCATION	
APPENDIX C – BLOCK DIAGRAM	
APPENDIX D – TEST SET-UP PHOTOGRAPHS	
APPENDIX E – EXTERNAL PHOTOGRAPHS	
APPENDIX F – INTERNAL PHOTOGRAPHS	
APPENDIX G – USER’S MANUAL	



Scope: Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and / or unintentional radiators for compliance with technical rules and regulations of the Federal Communications Commission.

1. General Information

Applicant: LG Electronics Inc.

Applicant Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Manufacturer: LG Electronics Inc.

Manufacturer Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Contact Person: Mr. Sang-Wook Lee, Chief research engineer

Tel Number: +82-31-610-9623

- **FCC ID.** BEJ47LE7500UC
- **EUT Type** LED LCD TV/Monitor
- **Model Name** 47LE7500-UC, 47LE5400-UC, 47LE5500-UA
- **Trade Name** LG
- **Serial Number** Prototype
- **Rule Part(s)** FCC Part 15 Subpart B
- **Type of Authority** Certification
- **Test Procedure(s)** ANSI C63.4 (2003) / Canadian standard ICES-003
- **Dates of Test** December 15 ~ 16, 2009
- **Place of Test** **Gumi College EMC Center** (FCC Registration Number: 100749, 443957)
407, Bugok-dong, Gumi-si, Gyeongbuk, Korea.
- **Test Report Number** GETEC-E3-09-159
- **Dates of Issue** December 21, 2009




2. Introduction

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Nose Emissions From Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ASNI C63.4-2003) was used in determining radiated and conducted emissions emanating from **LG Electronics Inc. LED LCD TV/Monitor (Model Name: 47LE7500-UC, 47LE5400-UC, 47LE5500-UA)**

These measurement tests were conducted at **Gumi College EMC Center**.

The site address is 407, Bugok-dong, Gumi-si, Gyeongbuk, Korea.

This test site is one of the highest point of Gumi 1 college at about 200 km away from Seoul city and 40 km away from Daegu city. It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 (2003)



GUMI COLLEGE EMC CENTER
407, Bugok-dong, Gumi-si,
Gyeongbuk 730-711, Korea.
Tel: +82-54-440-1195
Fax: +82-54-440-1199

Fig 1. The map above shows the Gumi College in vicinity area.



3. Product Information

3.1 Description of EUT

The Equipment under Test (EUT) is the **LG Electronics Inc. LED LCD TV/Monitor (Model Name: 47LE7500-UC, 47LE5400-UC, 47LE5500-UA) FCC ID.: BEJ47LE7500UC**

MODELS		42LE7500 (42LE7500-UC)	47LE7500 (47LE7500-UC)
Dimensions (Width x Height x Depth)	With stand	1018.2 x 693.5 x 269.8 mm (40.0 x 27.3 x 10.6 inches)	1128.6 x 758.9 x 284.4 mm (44.4 x 29.8 x 11.1 inches)
	Without stand	1018.2 x 630.7 x 29.3 mm (40.0 x 24.8 x 1.1 inches)	1128.6 x 693.3 x 29.8 mm (44.4 x 27.2 x 1.1 inches)
Weight	With stand	21.9 kg (48.2 lbs)	26.2 kg (57.7 lbs)
	Without stand	19.1 kg (42.1 lbs)	23.0 kg (50.7 lbs)
Power requirement		AC120V ~ 50/60Hz	
Television System		NTSC-M, ATSC, 64 & 256 QAM	
Program Coverage		VHF 2-13, UHF 14-69, CATV 1-135, DTV 2-69, CADTV 1-135	
External Antenna Impedance		75 ohm	
Environment condition	Operating Temperature	32 ~ 104°F (0 ~ 40°C)	
	Operating Humidity	Less than 80%	
	Storage Temperature	-4 ~ 140°F (-20 ~ 60°C)	
	Storage Humidity	Less than 85%	

Maximum Frequency range : 667 MHz



3.2 Support Equipment / Cables used

3.2.1 Used Support Equipment

Description	Manufacturer	Model Name	S/N & FCC ID
PC	Hewlett Packard	D530	S/N: CNG34800PY FCC ID: DoC
Video card	ATI	ARI RV360(9600)	S/N: SN0402017176 FCC ID: DoC
Keyboard	COMPAQ	166516-AD6	S/N: B13BBOR391006D FCC ID: AQ6-23K15
PS2 mouse	LOGITECH	M-S69	S/N: 334684-108 FCC ID: JNZ211443
Joystick	Microsoft	X05-92626	S/N: 9262600296169 FCC ID: DoC
DVD player	LG Electronics Inc	LC-954	S/N: 3850R-Z674K FCC ID: DoC
Headset	GOWOONSORI	GW-500M	S/N: N/A FCC ID: DoC
Printer	Hewlett Packard	970CXI	S/N: MY9B01F1FG FCC ID: DoC
TV signal generator	FLUKE	54200	S/N: 831011 FCC ID: DoC
USB memory stick	INNATOR Co., Ltd.	XM2-128	S/N: N/A FCC ID: DoC
Wireless Ready Dongle	LG Electronics Inc.	-	S/N: N/A FCC ID: -

See “Appendix D – Test Setup Photographs” for actual system test set-up



3.2.2 Used Cable(s)

Cable Name	Condition	Description
Power cable	Connected to the EUT	1.8 m unshielded
Video(RGB) input cable	Connected to the EUT and PC	1.8 m shielded with two ferrite cores
Video(HDMI/DVI) input cable	Connected to the EUT and PC	1.95 m shielded
Audio input cable	Connected to the EUT and PC	1.8 m shielded
AV input cable	Connected to the EUT and DVD Player	3.0 m shielded
Component input cable	Connected to the EUT and DVD Player	2.0 m shielded
Component sound input cable	Connected to the EUT and DVD Player	3.0 m shielded
Antenna cable	Connected to the EUT and TV signal generator	10.0 m shielded
Headset cable	Connected to the EUT	2.75 m shielded
LAN cable	Connected to the EUT and Network	10.0 m unshielded
Wireless control cable	Connected to the EUT and Wireless Ready Dongle	0.25 m shielded
RS-232C (Service only) cable	Connected to the EUT and PC	1.8 m shielded
Component input 3 cable	Connected to the EUT and DVD player	2.1 m shielded
AV input 2 cable	Connected to the EUT and DVD player	2.24 m shielded

3.3 Modification Item(s)

- None



4. Description of tests

4.1 Test Condition

The EUT was installed, arranged and operated in a manner that is most representative of equipment as typically used. The measurements were carried out while varying operating modes and cable positions within typically arrangement to determine maximum emission level.

The representative and worst test mode(s) were noted in the test report.

- Test Voltage / Frequency : AC 120 V / 60 Hz

- Test Mode(s)

- . Monitor mode

Radiated emission: 1 920 * 1 080 / 60 Hz (RGB: Analog), 1 920 * 1 080 / 60 Hz (HDMI/DVI: Digital)

Conducted emission: 1 920 * 1 080 / 60 Hz (RGB: Analog), 1 920 * 1 080 / 60 Hz (HDMI/DVI: Digital),

1 024 * 768 / 60 Hz (RGB: Analog), 640 * 480 / 60 Hz (RGB: Analog)

◆ Operating test pattern

- . "H" character scrolling mode (Font size: 10)
- . Black background white character
- . Brightness and contrast was adjusted as maximum level
- . 1 kHz sound tone with winamp player
- . Network connecting

- . USB memory stick play mode

◆ Operating test pattern

- . Continuous playback mode with Picture file and 1 kHz audio files.

"The verification report for TV/AV mode would be issued by LG Electronics Inc."



4.2 Conducted Emission

The Line conducted emission test facility is inside a 4 m × 8 m × 2.5 m shielded enclosure. (FCC Registration No.: 100749)

The EUT was placed on a non-conducting 1.0 m by 1.5 m table, which is 0.8 m in height and 0.4 m away from the vertical wall of the shielded enclosure.

The EUT is powered from the Rohde & Schwarz LISN (ESH2-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH3-Z5). Powers to the LISN are filtered by high-current high insertion loss power line filter.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

The RF output of the LISN was connected to the EMI test receiver (Rohde & Schwarz, ESCS30).

The EMI test receiver was scanned from 150 kHz to 30 MHz with 20 ms sweep time to determine the frequency producing the maximum EME from the EUT. The frequency producing the maximum level was re-examined using Quasi-Peak mode of the EMI test receiver.

The bandwidth of Quasi-peak mode was set to 9 kHz. Each emission was maximized consistent with typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum diagram emission. Excess cable lengths were bundled at center with 30 cm ~ 40 cm.

Each EME reported was calibrated using the R/S signal generator




Fig 2. Impedance of LISN



4.3 Radiated Emission

The measurements were conducted 3 m anechoic chamber (FCC Registration No.: 443957) using broadband antennas to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The technology configuration, mode of operation and turntable azimuth with respect to antenna was note for each frequency found.

The spectrum was scanned from 30 to 1000 MHz, using bicornical log antenna (Schwarzbeck, VULB9160).

Above 1 GHz, horn antenna (Schwarzbeck, BBHA9120D / EMCO 3160) was used.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was re-examined and investigated using EMI test receiver. The detector function was set to CISPR quasi-peak mode average mode and the bandwidth of the receiver was set to 120 kHz or 1MHz depending on the frequency or type of signal.

The EUT, support equipment and interconnecting cables were reconfigured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8 m high non-metallic 1.0 m × 1.5 m table.

The turntable containing the test sample was rotated; the antenna height was varied 1 m to 4 m and stopped at the azimuth or height producing the maximum emission.

Each EME reported was calibrated using the R/S signal generator




Fig 3. Dimensions of test site.



5. Conducted Emission

5.1 Operating Environment

Temperature : 23 °C
Relative Humidity : 39 % R.H.

5.2 Test Set-up

The conducted emission measurements were performed in the shielded room.

The EUT was placed on wooden table, 0.8 m heights above the floor, 0.4 m from the reference ground plane (GRP) wall and 0.8 m from AMN.

AMN is bonded on horizontal reference ground plane.

The ground plane, which was electrically bonded to the shield room, ground system and all power lines entering the shield room, were filtered.

5.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO "Guide to the expression of uncertainty in measurement."

The measurement uncertainty was given with a confidence of 95 %.

Test Items	Uncertainty	Remark
Conducted emission (9 kHz ~ 150 kHz)	± 2.69 dB	Confidence levels of 95 % (k=2)
Conducted emission (150 kHz ~ 30 MHz)	± 4.16 dB	Confidence levels of 95 % (k=2)



5.4 Limit

RFI Conducted	FCC Limit(dB) Class B	
Freq. Range	Quasi-Peak	Average
150 kHz ~ 0.5 MHz	66 ~ 56*	56 ~ 46*
0.5 MHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50
*Limits decreases linearly with the logarithm of frequency.		

5.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESCS30	Rohde & Schwarz	EMI test receiver	839809/003	12. 10. 2010
■ - ESH3-Z5	Rohde & Schwarz	LISN	838979/020	12. 10. 2010
■ - ESH2-Z5	Rohde & Schwarz	LISN	829991/009	12. 10. 2010
■ - ISN T8	TESEQ. GmbH	ISN	24568	10. 16. 2010


5.6 Test data for Conducted Emission

-. Test Date : December 15, 2009
-. Resolution Bandwidth : 9 kHz
-. Frequency Range : 0.15 MHz ~ 30 MHz



◆ Test resolution: 1 920 * 1 080 / 60 Hz (RGB: Analog mode)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.302000	44.2	1000.000	9.000	GND	L1	10.0	15.8	60.0	
0.340000	46.9	1000.000	9.000	GND	L1	10.0	12.1	59.0	
0.486000	43.7	1000.000	9.000	GND	L1	10.0	12.5	56.2	
0.522000	40.9	1000.000	9.000	GND	L1	10.0	15.1	56.0	
0.738000	39.5	1000.000	9.000	GND	L1	10.0	16.5	56.0	
1.342000	38.5	1000.000	9.000	GND	L1	10.1	17.5	56.0	
1.562000	39.6	1000.000	9.000	GND	L1	10.1	16.4	56.0	
2.196000	39.2	1000.000	9.000	GND	L1	10.1	16.8	56.0	
3.254000	37.8	1000.000	9.000	GND	L1	10.1	18.2	56.0	
4.264000	41.3	1000.000	9.000	GND	L1	10.2	14.8	56.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.210000	42.4	1000.000	9.000	GND	L1	10.0	10.6	53.0	
0.236000	38.6	1000.000	9.000	GND	L1	10.0	13.4	52.0	
0.314000	45.4	1000.000	9.000	GND	L1	10.0	4.2	49.6	
0.518000	32.7	1000.000	9.000	GND	L1	10.0	13.3	46.0	
0.522000	36.2	1000.000	9.000	GND	L1	10.0	9.8	46.0	
0.728000	32.9	1000.000	9.000	GND	L1	10.0	13.1	46.0	
0.950000	31.2	1000.000	9.000	GND	L1	10.0	14.8	46.0	
1.350000	31.6	1000.000	9.000	GND	L1	10.1	14.4	46.0	
1.556000	29.9	1000.000	9.000	GND	L1	10.1	16.1	46.0	
4.246000	28.8	1000.000	9.000	GND	L1	10.2	17.2	46.0	

< Fig 4. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.358000	43.2	1000.000	9.000	GND	N	10.0	15.4	58.6	
0.370000	42.2	1000.000	9.000	GND	N	10.0	16.1	58.3	
0.492000	41.2	1000.000	9.000	GND	N	10.0	14.9	56.1	
0.728000	39.1	1000.000	9.000	GND	N	10.0	16.9	56.0	
1.378000	39.5	1000.000	9.000	GND	N	10.1	16.5	56.0	
1.564000	39.8	1000.000	9.000	GND	N	10.1	16.2	56.0	
2.184000	40.3	1000.000	9.000	GND	N	10.1	15.7	56.0	
2.410000	38.9	1000.000	9.000	GND	N	10.1	17.1	56.0	
3.442000	38.6	1000.000	9.000	GND	N	10.1	17.4	56.0	
4.260000	41.7	1000.000	9.000	GND	N	10.2	14.3	56.0	

Final Measurement Detector 2


Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.210000	42.4	1000.000	9.000	GND	N	10.0	10.6	53.0	
0.316000	43.9	1000.000	9.000	GND	N	10.0	5.7	49.6	
0.524000	36.6	1000.000	9.000	GND	N	10.0	9.4	46.0	
0.734000	33.5	1000.000	9.000	GND	N	10.0	12.5	46.0	
0.740000	34.0	1000.000	9.000	GND	N	10.0	12.0	46.0	
0.938000	32.3	1000.000	9.000	GND	N	10.0	13.7	46.0	
1.354000	31.7	1000.000	9.000	GND	N	10.1	14.3	46.0	
1.560000	30.9	1000.000	9.000	GND	N	10.1	15.1	46.0	
2.184000	31.4	1000.000	9.000	GND	N	10.1	14.6	46.0	
4.352000	30.9	1000.000	9.000	GND	N	10.2	15.1	46.0	

< Fig 5. Conducted emission result (Neutral line)>



◆ Test resolution: 1 920 * 1 080 / 60 Hz (HDMI/DVI: Digital mode)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.338000	47.0	1000.000	9.000	GND	L1	10.0	12.1	59.1	
0.492000	44.2	1000.000	9.000	GND	L1	10.0	11.9	56.1	
0.562000	39.9	1000.000	9.000	GND	L1	10.0	16.2	56.0	
0.734000	39.8	1000.000	9.000	GND	L1	10.0	16.2	56.0	
1.154000	38.7	1000.000	9.000	GND	L1	10.0	17.3	56.0	
1.398000	38.3	1000.000	9.000	GND	L1	10.1	17.7	56.0	
1.598000	38.5	1000.000	9.000	GND	L1	10.1	17.5	56.0	
2.450000	37.2	1000.000	9.000	GND	L1	10.1	18.8	56.0	
3.236000	38.5	1000.000	9.000	GND	L1	10.1	17.5	56.0	
4.254000	40.6	1000.000	9.000	GND	L1	10.2	15.4	56.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.212000	42.4	1000.000	9.000	GND	L1	10.0	10.5	52.9	
0.234000	38.9	1000.000	9.000	GND	L1	10.0	13.2	52.1	
0.318000	43.9	1000.000	9.000	GND	L1	10.0	5.6	49.5	
0.528000	37.7	1000.000	9.000	GND	L1	10.0	8.3	46.0	
0.734000	33.8	1000.000	9.000	GND	L1	10.0	12.2	46.0	
0.952000	32.0	1000.000	9.000	GND	L1	10.0	14.0	46.0	
1.366000	30.0	1000.000	9.000	GND	L1	10.1	16.0	46.0	
1.598000	26.7	1000.000	9.000	GND	L1	10.1	19.3	46.0	
2.206000	30.2	1000.000	9.000	GND	L1	10.1	15.8	46.0	
4.350000	30.5	1000.000	9.000	GND	L1	10.2	15.5	46.0	

< Fig 6. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.362000	43.6	1000.000	9.000	GND	N	10.0	14.9	58.5	
0.370000	42.8	1000.000	9.000	GND	N	10.0	15.5	58.3	
0.548000	38.0	1000.000	9.000	GND	N	10.0	18.0	56.0	
0.734000	39.8	1000.000	9.000	GND	N	10.0	16.2	56.0	
1.360000	39.8	1000.000	9.000	GND	N	10.1	16.2	56.0	
1.576000	39.3	1000.000	9.000	GND	N	10.1	16.7	56.0	
2.192000	39.8	1000.000	9.000	GND	N	10.1	16.2	56.0	
2.434000	39.1	1000.000	9.000	GND	N	10.1	16.9	56.0	
3.464000	38.6	1000.000	9.000	GND	N	10.2	17.4	56.0	
4.324000	40.8	1000.000	9.000	GND	N	10.2	15.2	56.0	

Final Measurement Detector 2


Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.212000	42.2	1000.000	9.000	GND	N	10.0	10.7	52.9	
0.318000	42.4	1000.000	9.000	GND	N	10.0	7.1	49.5	
0.526000	37.5	1000.000	9.000	GND	N	10.0	8.5	46.0	
0.734000	34.3	1000.000	9.000	GND	N	10.0	11.7	46.0	
0.736000	33.6	1000.000	9.000	GND	N	10.0	12.4	46.0	
0.944000	31.4	1000.000	9.000	GND	N	10.0	14.6	46.0	
1.380000	31.1	1000.000	9.000	GND	N	10.1	14.9	46.0	
1.580000	30.6	1000.000	9.000	GND	N	10.1	15.4	46.0	
2.840000	24.5	1000.000	9.000	GND	N	10.1	21.5	46.0	
4.308000	29.1	1000.000	9.000	GND	N	10.2	16.9	46.0	

< Fig 7. Conducted emission result (Neutral line)>



◆ Test resolution: 1 024 * 768 / 60 Hz (RGB: Analog mode)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.302000	43.8	1000.000	9.000	GND	L1	10.0	16.2	60.0	
0.354000	46.3	1000.000	9.000	GND	L1	10.0	12.4	58.7	
0.492000	42.9	1000.000	9.000	GND	L1	10.0	13.2	56.1	
0.544000	40.4	1000.000	9.000	GND	L1	10.0	15.6	56.0	
0.730000	40.8	1000.000	9.000	GND	L1	10.0	15.2	56.0	
1.356000	39.9	1000.000	9.000	GND	L1	10.1	16.1	56.0	
1.590000	39.8	1000.000	9.000	GND	L1	10.1	16.2	56.0	
2.400000	39.5	1000.000	9.000	GND	L1	10.1	16.5	56.0	
3.436000	39.4	1000.000	9.000	GND	L1	10.1	16.6	56.0	
4.346000	40.5	1000.000	9.000	GND	L1	10.2	15.5	56.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.210000	42.4	1000.000	9.000	GND	L1	10.0	10.6	53.0	
0.232000	38.2	1000.000	9.000	GND	L1	10.0	13.9	52.1	
0.316000	45.5	1000.000	9.000	GND	L1	10.0	4.2	49.6	
0.518000	31.4	1000.000	9.000	GND	L1	10.0	14.6	46.0	
0.526000	37.1	1000.000	9.000	GND	L1	10.0	8.9	46.0	
0.730000	34.1	1000.000	9.000	GND	L1	10.0	11.9	46.0	
1.148000	31.4	1000.000	9.000	GND	L1	10.0	14.6	46.0	
1.354000	31.9	1000.000	9.000	GND	L1	10.1	14.1	46.0	
1.590000	31.6	1000.000	9.000	GND	L1	10.1	14.4	46.0	
4.264000	32.3	1000.000	9.000	GND	L1	10.2	13.7	46.0	

< Fig 8. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.330000	44.0	1000.000	9.000	GND	N	10.0	15.3	59.3	
0.550000	38.9	1000.000	9.000	GND	N	10.0	17.1	56.0	
0.730000	40.4	1000.000	9.000	GND	N	10.0	15.6	56.0	
0.804000	38.3	1000.000	9.000	GND	N	10.0	17.7	56.0	
1.352000	40.2	1000.000	9.000	GND	N	10.1	15.8	56.0	
1.582000	39.6	1000.000	9.000	GND	N	10.1	16.4	56.0	
2.190000	39.6	1000.000	9.000	GND	N	10.1	16.4	56.0	
2.392000	40.0	1000.000	9.000	GND	N	10.1	16.0	56.0	
3.224000	38.9	1000.000	9.000	GND	N	10.1	17.1	56.0	
4.264000	41.5	1000.000	9.000	GND	N	10.2	14.5	56.0	

Final Measurement Detector 2


Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.210000	42.4	1000.000	9.000	GND	N	10.0	10.6	53.0	
0.316000	43.8	1000.000	9.000	GND	N	10.0	5.8	49.6	
0.526000	37.0	1000.000	9.000	GND	N	10.0	9.0	46.0	
0.732000	34.7	1000.000	9.000	GND	N	10.0	11.3	46.0	
0.736000	34.0	1000.000	9.000	GND	N	10.0	12.0	46.0	
0.940000	32.2	1000.000	9.000	GND	N	10.0	13.8	46.0	
1.380000	31.5	1000.000	9.000	GND	N	10.1	14.5	46.0	
1.590000	31.8	1000.000	9.000	GND	N	10.1	14.2	46.0	
2.400000	31.0	1000.000	9.000	GND	N	10.1	15.0	46.0	
4.266000	31.5	1000.000	9.000	GND	N	10.2	14.5	46.0	

< Fig 9. Conducted emission result (Neutral line)>



◆ Test resolution: 640 * 480 / 60 Hz (RGB: Analog mode)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.330000	47.1	1000.000	9.000	GND	L1	10.0	12.2	59.3	
0.492000	43.1	1000.000	9.000	GND	L1	10.0	13.0	56.1	
0.548000	41.1	1000.000	9.000	GND	L1	10.0	14.9	56.0	
0.732000	40.9	1000.000	9.000	GND	L1	10.0	15.1	56.0	
1.158000	38.3	1000.000	9.000	GND	L1	10.0	17.7	56.0	
1.358000	39.6	1000.000	9.000	GND	L1	10.1	16.4	56.0	
1.576000	39.8	1000.000	9.000	GND	L1	10.1	16.2	56.0	
2.406000	39.2	1000.000	9.000	GND	L1	10.1	16.8	56.0	
3.434000	39.4	1000.000	9.000	GND	L1	10.1	16.6	56.0	
4.272000	41.6	1000.000	9.000	GND	L1	10.2	14.4	56.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.210000	42.2	1000.000	9.000	GND	L1	10.0	10.8	53.0	
0.238000	37.5	1000.000	9.000	GND	L1	10.0	14.4	51.9	
0.316000	45.6	1000.000	9.000	GND	L1	10.0	4.0	49.6	
0.526000	37.2	1000.000	9.000	GND	L1	10.0	8.8	46.0	
0.734000	34.5	1000.000	9.000	GND	L1	10.0	11.5	46.0	
0.940000	32.5	1000.000	9.000	GND	L1	10.0	13.5	46.0	
1.358000	31.7	1000.000	9.000	GND	L1	10.1	14.3	46.0	
1.564000	31.9	1000.000	9.000	GND	L1	10.1	14.1	46.0	
2.444000	30.8	1000.000	9.000	GND	L1	10.1	15.2	46.0	
4.266000	31.8	1000.000	9.000	GND	L1	10.2	14.2	46.0	

< Fig 10. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.342000	44.0	1000.000	9.000	GND	N	10.0	15.0	59.0	
0.370000	42.9	1000.000	9.000	GND	N	10.0	15.4	58.3	
0.492000	41.4	1000.000	9.000	GND	N	10.0	14.7	56.1	
0.726000	39.6	1000.000	9.000	GND	N	10.0	16.4	56.0	
0.738000	40.3	1000.000	9.000	GND	N	10.0	15.7	56.0	
1.360000	39.5	1000.000	9.000	GND	N	10.1	16.5	56.0	
1.582000	39.6	1000.000	9.000	GND	N	10.1	16.4	56.0	
2.652000	38.6	1000.000	9.000	GND	N	10.1	17.4	56.0	
3.646000	39.7	1000.000	9.000	GND	N	10.2	16.3	56.0	
4.282000	40.8	1000.000	9.000	GND	N	10.2	15.2	56.0	

Final Measurement Detector 2


Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.210000	42.2	1000.000	9.000	GND	N	10.0	10.8	53.0	
0.316000	44.1	1000.000	9.000	GND	N	10.0	5.6	49.6	
0.526000	37.2	1000.000	9.000	GND	N	10.0	8.8	46.0	
0.732000	34.8	1000.000	9.000	GND	N	10.0	11.2	46.0	
0.738000	33.9	1000.000	9.000	GND	N	10.0	12.1	46.0	
0.940000	32.6	1000.000	9.000	GND	N	10.0	13.4	46.0	
1.356000	32.2	1000.000	9.000	GND	N	10.1	13.8	46.0	
1.566000	31.9	1000.000	9.000	GND	N	10.1	14.1	46.0	
2.398000	31.5	1000.000	9.000	GND	N	10.1	14.5	46.0	
4.268000	32.0	1000.000	9.000	GND	N	10.2	14.0	46.0	

< Fig 11. Conducted emission result (Neutral line)>



◆ Test resolution: USB memory stick play mode

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.332000	47.2	1000.000	9.000	GND	L1	10.0	12.0	59.2	
0.476000	43.3	1000.000	9.000	GND	L1	10.0	13.1	56.4	
0.590000	39.4	1000.000	9.000	GND	L1	10.0	16.6	56.0	
0.738000	40.4	1000.000	9.000	GND	L1	10.0	15.6	56.0	
1.156000	38.7	1000.000	9.000	GND	L1	10.0	17.3	56.0	
1.354000	39.4	1000.000	9.000	GND	L1	10.1	16.6	56.0	
1.582000	39.8	1000.000	9.000	GND	L1	10.1	16.2	56.0	
2.418000	39.1	1000.000	9.000	GND	L1	10.1	16.9	56.0	
3.446000	40.1	1000.000	9.000	GND	L1	10.1	15.9	56.0	
4.346000	40.6	1000.000	9.000	GND	L1	10.2	15.4	56.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.212000	41.6	1000.000	9.000	GND	L1	10.0	11.3	52.9	
0.236000	37.9	1000.000	9.000	GND	L1	10.0	14.1	52.0	
0.316000	45.6	1000.000	9.000	GND	L1	10.0	4.0	49.6	
0.528000	37.4	1000.000	9.000	GND	L1	10.0	8.6	46.0	
0.740000	34.3	1000.000	9.000	GND	L1	10.0	11.7	46.0	
0.956000	32.7	1000.000	9.000	GND	L1	10.0	13.3	46.0	
1.170000	31.6	1000.000	9.000	GND	L1	10.0	14.4	46.0	
1.568000	32.5	1000.000	9.000	GND	L1	10.1	13.5	46.0	
2.402000	31.5	1000.000	9.000	GND	L1	10.1	14.5	46.0	
4.280000	32.6	1000.000	9.000	GND	L1	10.2	13.4	46.0	

< Fig 12. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.324000	44.3	1000.000	9.000	GND	N	10.0	15.1	59.4	
0.542000	38.0	1000.000	9.000	GND	N	10.0	18.0	56.0	
0.710000	39.6	1000.000	9.000	GND	N	10.0	16.4	56.0	
0.736000	40.5	1000.000	9.000	GND	N	10.0	15.5	56.0	
1.356000	40.0	1000.000	9.000	GND	N	10.1	16.0	56.0	
1.564000	40.0	1000.000	9.000	GND	N	10.1	16.0	56.0	
2.230000	38.6	1000.000	9.000	GND	N	10.1	17.4	56.0	
2.402000	40.3	1000.000	9.000	GND	N	10.1	15.7	56.0	
3.702000	38.4	1000.000	9.000	GND	N	10.2	17.6	56.0	
4.288000	41.5	1000.000	9.000	GND	N	10.2	14.5	56.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.212000	41.5	1000.000	9.000	GND	N	10.0	11.4	52.9	
0.316000	43.8	1000.000	9.000	GND	N	10.0	5.8	49.6	
0.528000	37.6	1000.000	9.000	GND	N	10.0	8.4	46.0	
0.732000	34.1	1000.000	9.000	GND	N	10.0	11.9	46.0	
0.742000	34.5	1000.000	9.000	GND	N	10.0	11.5	46.0	
0.948000	31.4	1000.000	9.000	GND	N	10.0	14.6	46.0	
1.384000	31.9	1000.000	9.000	GND	N	10.1	14.1	46.0	
1.596000	31.6	1000.000	9.000	GND	N	10.1	14.4	46.0	
2.452000	31.4	1000.000	9.000	GND	N	10.1	14.6	46.0	
4.278000	31.7	1000.000	9.000	GND	N	10.2	14.3	46.0	

< Fig 13. Conducted emission result (Neutral line)>



6. Radiated Emission

6.1 Operating Environment

Temperature : 21 °C
Relative Humidity : 46 % R.H.

6.2 Test Set-up

A preliminary and final measurement was at 3 m anechoic chamber.

The EUT was placed on a non-conductive turntable approximately 0.8 m above the ground plane.

The turntable with EUT was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels.

This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

6.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO "Guide to the expression of uncertainty in measurement".

The measurement uncertainty was given with a confidence of 95 %.

Test Items	Uncertainty	Remark
Radiated emission (30 MHz ~ 300 MHz, 3 m, Vertical)	± 3.54 dB	Confidence levels of 95 % (k=2)
Radiated emission (30 MHz ~ 300 MHz, 3 m, Horizontal)	± 3.49 dB	Confidence levels of 95 % (k=2)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Vertical)	± 3.85 dB	Confidence levels of 95 % (k=2)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Horizontal)	± 3.76 dB	Confidence levels of 95 % (k=2)
Radiated emission (30 MHz ~ 300 MHz, 10 m, Vertical)	± 3.21 dB	Confidence levels of 95 % (k=2)
Radiated emission (30 MHz ~ 300 MHz, 10 m, Horizontal)	± 3.32 dB	Confidence levels of 95 % (k=2)
Radiated emission (300 MHz ~ 1 000 MHz, 10 m, Vertical)	± 3.77 dB	Confidence levels of 95 % (k=2)
Radiated emission (300 MHz ~ 1 000 MHz, 10 m, Horizontal)	± 3.84 dB	Confidence levels of 95 % (k=2)



6.4 Limit

Frequency (MHz)	FCC Limit @ 3 m. dB μ V/m	CISPR Limit @ 10 m. dB μ V/m
30 ~ 88	40.0	30.0
88 ~ 216	43.5	30.0
216 ~ 230	46.0	30.0
230 ~ 960	46.0	37.0
960 ~ 1 000	54.0	37.0
> 1 000	54.0	No Specified limit

6.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESI	Rohde & Schwarz	EMI test receiver	830482/010	12. 11. 2010
■ - VULB9160	Schwarzbeck	Broadband Test Antenna	3099	07. 21. 2011
■ - BBHA9120D	Schwarzbeck	Horn ANT	597	12. 18. 2010
■ - MCU066	matur GmbH	MCU066	1390306	N/A
■ - TT2.5SI	matur GmbH	Turntable	1390307	N/A
■ - AM 4.0	matur GmbH	Antenna Mast	1390308	N/A
■ - AFS 44 00101800- 25-10P-44	MITEQ	Preamplifier	1258943	11. 12. 2010


6.6 Test data for Radiated Emission

- Test Date : December 15, 2009
- Resolution Bandwidth : 120 kHz/1 MHz
- Frequency Range : 30 MHz ~ 5 000 MHz
- Measurement Distance : 3 m
- Note : The highest frequency of the internal source of the EUT is between 500 MHz and 1 000 MHz (667 MHz). The measurement was made up to 5 000 MHz



- ◆ Operating Condition: 1 920 * 1 080 / 60 Hz (RGB: Analog mode)
Detector mode: Quasi- peak detector mode

Frequency (MHz)	Measurement Level				Limit (dBμ V/m)	Margin (dB)	Positioning System		
	Reading	Antenna	Cable	Test Result			Pol.	Height	Angle
	Value(dBμ V)	Factor(dB/m)	Loss(dB)	(dBμ V/m)			(H/V)	(cm)	(°)
36.12	21.94	11.87	2.01	35.82	40.00	4.18	V	103	185
60.23	21.39	12.03	2.51	35.93	40.00	4.07	V	100	37
86.64	24.79	8.19	2.90	35.88	40.00	4.12	V	109	283
186.55	19.22	10.93	4.09	34.24	43.50	9.26	V	100	180
375.05	15.77	14.98	7.16	37.91	46.00	8.09	V	118	4
594.00	14.35	20.13	7.38	41.86	46.00	4.14	V	100	175
688.15	12.43	21.42	7.90	41.75	46.00	4.25	V	100	354
894.92	5.95	24.16	9.14	39.25	46.00	6.75	V	193	359




< Fig 14. Radiated emission result (30 MHz ~ 1 000 MHz)>



- ◆ Operating Condition: 1 920 * 1 080 / 60 Hz (HDMI/DVI: Digital mode)
Detector mode: Quasi- peak detector mode

Frequency (MHz)	Measurement Level				Limit (dB μ V/m)	Margin (dB)	Positioning System		
	Reading	Antenna	Cable	Test Result			Pol.	Height	Angle
	Value(dB μ V)	Factor(dB/m)	Loss(dB)	(dB μ V/m)			(H/V)	(cm)	(°)
36.12	22.02	11.87	2.01	35.90	40.00	4.10	V	100	190
60.25	21.35	12.02	2.51	35.88	40.00	4.12	V	100	88
87.66	24.50	8.21	2.91	35.62	40.00	4.38	V	100	273
123.78	23.57	11.63	3.38	38.58	43.50	4.92	H	172	261
272.29	21.19	12.33	5.25	38.77	46.00	7.23	V	100	77
374.88	13.50	14.98	7.16	35.64	46.00	10.36	V	110	0
450.05	11.92	17.12	7.18	36.22	46.00	9.78	V	210	342
600.11	12.82	20.34	7.42	40.58	46.00	5.42	V	206	0
702.00	12.32	21.59	7.97	41.88	46.00	4.12	V	153	359
808.45	9.37	23.28	8.64	41.29	46.00	4.71	V	100	358




< Fig 15. Radiated emission result (30 MHz ~ 1 000 MHz)>



- ◆ Operating Condition: USB memory stick play mode
Detector mode: Quasi- peak detector mode

Frequency (MHz)	Measurement Level				Limit (dBμ V/m)	Margin (dB)	Positioning System		
	Reading	Antenna	Cable	Test Result			Pol.	Height	Angle
	Value(dBμ V)	Factor(dB/m)	Loss(dB)	(dBμ V/m)			(H/V)	(cm)	(°)
35.34	21.84	11.85	1.99	35.68	40.00	4.32	V	100	180
56.05	20.72	12.22	2.43	35.37	40.00	4.63	V	100	330
87.66	22.88	8.21	2.91	34.00	40.00	6.00	V	108	0
108.78	23.41	10.30	3.18	36.89	43.50	6.61	V	100	297
128.41	11.95	11.93	3.44	27.32	43.50	16.18	V	104	95
203.23	17.14	9.41	4.33	30.88	43.50	12.62	H	106	112
250.03	14.94	11.56	4.95	31.45	46.00	14.55	H	118	182
513.65	4.36	17.83	7.05	29.24	46.00	16.76	H	142	354
654.54	5.36	21.09	7.73	34.18	46.00	11.82	V	199	25
722.51	7.97	22.08	8.12	38.17	46.00	7.83	H	125	188
960.00	4.00	25.56	9.59	39.15	54.00	14.85	H	143	209




< Fig 16. Radiated emission result (30 MHz ~ 1 000 MHz)>



◆ Operating Condition: 1 920 * 1 080 / 60 Hz (RGB: Analog mode)

Detector mode: Peak detector mode / Average detector mode

FCC_ESIB_Preamplifier with Scans



Final Result 1

Frequency (MHz)	MaxPeak-MaxHold (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1175.600000	54.7	100.0	V	0.0	-15.9	19.3	74.0	
2376.000000	55.7	100.0	H	90.0	-10.8	18.3	74.0	
3529.200000	58.6	200.0	V	0.0	-6.6	15.4	74.0	

Final Result 2


Frequency (MHz)	Average-MaxHold (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1026.000000	40.4	200.0	V	180.0	-16.5	13.6	54.0	
1282.400000	40.7	200.0	V	0.0	-15.1	13.3	54.0	
1395.200000	35.0	100.0	V	180.0	-14.8	19.0	54.0	
1539.200000	34.5	100.0	V	0.0	-14.6	19.5	54.0	
1620.000000	34.8	100.0	V	0.0	-14.4	19.2	54.0	
1633.600000	34.8	100.0	V	0.0	-14.4	19.2	54.0	
1795.600000	35.5	200.0	V	0.0	-13.9	18.5	54.0	
2052.000000	35.1	200.0	V	0.0	-12.5	18.9	54.0	
2565.200000	45.8	100.0	V	0.0	-10.0	8.2	54.0	
2628.000000	35.6	100.0	H	180.0	-9.8	18.4	54.0	
3572.800000	35.4	200.0	V	0.0	-6.3	18.6	54.0	
3638.400000	35.5	100.0	V	0.0	-5.8	18.5	54.0	
4158.000000	37.4	100.0	V	0.0	-3.3	16.6	54.0	
4608.000000	37.4	100.0	V	180.0	-3.2	16.6	54.0	
4678.000000	39.5	200.0	V	0.0	-3.1	14.5	54.0	

< Fig 17. Radiated emission result (1 000 MHz ~ 5 000 MHz)>



- ◆ Operating Condition: 1 920 * 1 080 / 60 Hz (HDMI/DVI: Digital mode)
Detector mode: Peak detector mode / Average detector mode

FCC_ESIB_Preamplifier with Scans



Final Result 1

Frequency (MHz)	Peak-MaxHold (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1282.400000	51.8	100.0	V	0.0	-15.1	22.2	74.0	
1395.200000	51.7	100.0	V	180.0	-14.8	22.3	74.0	
1945.200000	51.0	100.0	V	0.0	-13.1	23.0	74.0	
2401.200000	50.5	200.0	H	90.0	-10.7	23.5	74.0	
3527.200000	53.7	200.0	V	0.0	-6.6	20.3	74.0	

Final Result 2


Frequency (MHz)	Average-MaxHold (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1026.000000	40.0	200.0	V	180.0	-16.5	14.0	54.0	
1282.400000	40.7	100.0	V	0.0	-15.1	13.3	54.0	
1322.800000	35.4	100.0	V	180.0	-14.9	18.6	54.0	
1328.000000	37.0	100.0	V	180.0	-14.9	17.0	54.0	
1395.200000	45.7	100.0	V	180.0	-14.8	8.3	54.0	
1674.000000	36.5	100.0	V	0.0	-14.4	17.5	54.0	
2052.000000	36.3	200.0	V	0.0	-12.5	17.7	54.0	
2092.400000	38.4	200.0	V	180.0	-12.2	15.6	54.0	
2565.200000	45.5	100.0	V	0.0	-10.0	8.5	54.0	
2628.400000	36.2	100.0	H	180.0	-9.8	17.8	54.0	
2790.400000	42.2	100.0	V	180.0	-9.3	11.8	54.0	
3926.800000	35.4	200.0	V	0.0	-3.7	18.6	54.0	
4104.000000	37.3	100.0	H	180.0	-3.2	16.7	54.0	
4608.000000	37.4	100.0	V	180.0	-3.2	16.6	54.0	
4616.800000	37.7	100.0	H	180.0	-3.2	16.3	54.0	

< Fig 18. Radiated emission result (1 000 MHz ~ 5 000 MHz)>



- ◆ Operating Condition: USB memory stick play mode
Detector mode: Peak detector mode / Average detector mode

FCC_ESIB_Preamplifier with Scans



Final Result 1

Frequency (MHz)	MaxPeak-MaxHold (dBµV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
1043.200000	52.2	100.0	V	0.0	-16.4	22.1	74.0	
1936.800000	51.8	200.0	H	90.0	-13.2	22.0	74.0	
2626.000000	52.3	200.0	H	90.0	-9.8	22.0	74.0	

Final Result 2

Frequency (MHz)	Average-MaxHold (dBµV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
1039.600000	35.4	100.0	V	0.0	-16.4	18.6	54.0	
1282.400000	42.1	200.0	V	0.0	-15.1	11.9	54.0	
1538.800000	39.0	200.0	V	0.0	-14.6	15.0	54.0	
1944.000000	35.4	100.0	H	0.0	-13.2	18.6	54.0	
2565.200000	41.4	100.0	V	0.0	-10.0	12.6	54.0	
3591.200000	35.9	100.0	V	180.0	-6.2	18.1	54.0	
4065.200000	38.2	100.0	V	0.0	-3.2	15.8	54.0	
4608.000000	38.6	100.0	V	180.0	-3.2	15.4	54.0	

< Fig 19. Radiated emission result (1 000 MHz ~ 5 000 MHz)>



7. Sample Calculations

$$\begin{aligned}\text{dB}\mu\text{V} &= 20 \text{ Log}_{10}(\mu\text{V}/\text{m}) \\ \text{dB}\mu\text{V} &= \text{dBm} + 107 \\ \mu\text{V} &= 10^{(\text{dB}\mu\text{V}/20)}\end{aligned}$$

7.1 Example 1 :

■ 20.3 MHz

Class B Limit	= 250 μV = 48 dB μV
Reading	= 39.2 dB μV
$10^{(39.2\text{dB}\mu\text{V}/20)}$	= 91.2 μV
Margin	= 48 dB μV - 39.2 dB μV = 8.8 dB

7.2 Example 2 :

■ 66.7 MHz

Class B Limit	= 100 $\mu\text{V}/\text{m}$ = 40.0 dB $\mu\text{V}/\text{m}$
Reading	= 31.0 dB μV
Antenna Factor + Cable Loss = 5.8 dB	
Total	= 36.8 dB $\mu\text{V}/\text{m}$
Margin	= 40.0 dB $\mu\text{V}/\text{m}$ – 36.8 dB $\mu\text{V}/\text{m}$ = 3.2 dB



8. Recommendation & Conclusion

The data collected shows that the **LG Electronics Inc. LED LCD TV/Monitor (Model Name: 47LE7500-UC, 47LE5400-UC, 47LE5500-UA)** was complies with §15.107 and 15.109 of the FCC Rules.