

FCC EVALUATION REPORT FOR CERTIFICATION


Applicant : LG Electronics Inc.**19-1, Cheongho-ri, Jinwi-myeon,****Pyeongteak-si, Gyeonggi-do, Korea.****Attn: Mr. Do-Hyung Kim, Chief research engineer****Date of Issue : March 18, 2011****Order Number: GETEC-C1-11-053****Test Report Number: GETEC-E3-11-014****Test Site: Gumi College EMC Center****FCC Registration Number: (100749, 443957)****FCC ID. : BEJ47VL10****Applicant : LG Electronics Inc.**

Rule Part(s)	: FCC Part 15 Subpart B
Equipment Class	: Class B computing device peripheral (JBP)
EUT Type	: LCD Monitor
Type of Authority	: Certification
Model Name	: 47VL10
Trade Name	: LG

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003 / Canadian standard ICES-003

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the vest of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by,**Reviewed by,**



Soon-Hoon Jeong, Associate Engineer
GUMI College EMC center



Jae-Hoon Jeong, Senior Engineer
GUMI College EMC center



CONTENTS

1. GENERAL INFORMATION	3
2. INTRODUCTION	4
3. PRODUCT INFORMATION	5
3.1 DESCRIPTION OF EUT.....	5
3.2 SUPPORT EQUIPMENT / CABLES USED	6
3.3 MODIFICATION ITEM(S)	7
4. DESCRIPTION OF TESTS.....	8
4.1 TEST CONDITION.....	8
4.2 CONDUCTED EMISSION	9
4.3 RADIATED EMISSION.....	10
5. CONDUCTED EMISSION.....	11
5.1 OPERATING ENVIRONMENT	11
5.2 TEST SET-UP	11
5.3 MEASUREMENT UNCERTAINTY.....	11
5.4 LIMIT	12
5.5 TEST EQUIPMENT USED.....	12
5.6 TEST DATA FOR CONDUCTED EMISSION	12
6. RADIATED EMISSION	21
6.1 OPERATING ENVIRONMENT	21
6.2 TEST SET-UP	21
6.3 MEASUREMENT UNCERTAINTY.....	21
6.4 LIMIT	22
6.5 TEST EQUIPMENT USED.....	22
6.6 TEST DATA FOR RADIATED EMISSION	23
7. SAMPLE CALCULATIONS.....	27
7.1 EXAMPLE 1 :	27
7.2 EXAMPLE 2 :	27
8. RECOMMENDATION & CONCLUSION.....	28
APPENDIX A – ATTESTATION STATEMENT	
APPENDIX B – ID SAMPLE LABEL & LOCATION	
APPENDIX C – BLOCK DIAGRAM	
APPENDIX D – TEST SET-UP PHOTOGRAPHS	
APPENDIX E – EXTERNAL PHOTOGRAPHS	
APPENDIX F – INTERNAL PHOTOGRAPHS	
APPENDIX G – USER’S MANUAL	



Scope: Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and / or unintentional radiators for compliance with technical rules and regulations of the Federal Communications Commission.

1. General Information

Applicant: LG Electronics Inc.

Applicant Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Manufacturer: LG Electronics Inc.

Manufacturer Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Contact Person: Mr. Do-Hyung Kim, Chief research engineer

Tel Number: +82-31-610-9623

- **FCC ID.** BEJ47VL10
- **EUT Type** LCD Monitor
- **Model Name** 47VL10
- **Trade Name** LG
- **Serial Number** Prototype
- **Rule Part(s)** FCC Part 15 Subpart B
- **Type of Authority** Certification
- **Test Procedure(s)** ANSI C63.4 (2003) / Canadian standard ICES-003
- **Dates of Test** March 7 ~ 14, 2011
- **Place of Test** **Gumi College EMC Center** (FCC Registration Number: 100749, 443957)
407, Bugok-dong, Gumi-si, Gyeongbuk, Korea.
- **Test Report Number** GETEC-E3-11-014
- **Dates of Issue** March 18, 2011




2. Introduction

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Nose Emissions From Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ASNI C63.4-2003) was used in determining radiated and conducted emissions emanating from **LG Electronics Inc. LCD Monitor (Model Name: 47VL10)**

These measurement tests were conducted at **Gumi College EMC Center**.

The site address is 407, Bugok-dong, Gumi-si, Gyeongbuk, Korea.

This test site is one of the highest point of Gumi 1 college at about 200 km away from Seoul city and 40 km away from Daegu city. It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 (2003)



GUMI COLLEGE EMC CENTER
407, Bugok-dong, Gumi-si,
Gyeongbuk 730-711, Korea.
Tel: +82-54-440-1195
Fax: +82-54-440-1199

Fig 1. The map above shows the Gumi College in vicinity area.



3. Product Information

3.1 Description of EUT

The Equipment under Test (EUT) is the **LG Electronics Inc. LCD Monitor (Model Name: 47VL10) FCC ID.: BEJ47VL10**

- Screen Type	: 1 192.8 mm Wide (46.96 inch) TFT (Thin Film Transistor) LCD (Liquid Crystal Display) Panel. Visible diagonal size: 1 192. 8 mm
- Pixel Pitch	: 0.541 5 mm(H) × 0.541 5 mm(V)
- Maximum Resolution	: RGB: 1 920 × 1 080 @ 60 Hz HDMI/DVI: 1 920 × 1 080 @ 60 Hz
- Horizontal Frequency	: RGB: 30 kHz – 83 kHz HDMI/DVI: 30 kHz – 83 kHz
- Vertical Frequency	: RGB: 56 Hz – 76 Hz HDMI/DVI: 56 Hz – 61 Hz
- Rated Voltage	: AC (100 – 240) V~, (50/60) Hz, 3.0 A
- Power Consumption	: 300 W
- Size	: 1 117 mm(W) × 757.0 mm(H) × 302.6 mm(D)
- Weight	: 33.3 kg
- Maximum Frequency Range	: 250 MHz



3.2 Support Equipment / Cables used

3.2.1 Used Support Equipment

Description	Manufacturer	Model Name	S/N & FCC ID.
PC	Hewlett Packard	D530	S/N: CNG34800PY FCC ID.: DoC
Video card	ATI	ATI RV360(9600)	S/N: SN0402017176 FCC ID.: DoC
PS2 keyboard	COMPAQ	166516-AD6	S/N: B13BBOR391006D FCC ID.: AQ6-23K15
PS2 mouse	LOGITECH	M-S69	S/N: 334684-108 FCC ID.: JNZ211443
Joy stick	MICROSOFT	X05-92626	S/N: 9262600296169 FCC ID.: DoC
DVD player	LG Electronics Inc.	LC-954	S/N: 3850R-Z674K FCC ID.: DoC

See “Appendix D – Test Setup Photographs” for actual system test set-up

3.2.2 System configuration

Description	Manufacturer	Model Name	S/N & FCC ID.
Speaker	LG Electronics Inc.	SP-0000K	S/N: N/A FCC ID.: N/A



3.2.3 Used Cable(s)

Cable Name	Condition	Description
Power cable	Connected to the EUT	1.80 m unshielded
RGB(Analog) in cable	Connected to the EUT and PC	1.80 m shielded with two ferrite cores
HDMI/DVI(Digital) in cable	Connected to the EUT and PC	2.00 m shielded
Audio(RGB/DVI) in cable	Connected to the EUT and PC	1.80 m shielded
RS-232C in cable	Connected to the EUT and PC	1.80 m shielded
AV in cable	Connected to the EUT and DVD player	3.00 m shielded
Audio(AV) in cable	Connected to the EUT and DVD player	2.00 m shielded
LAN cable	Connected to the EUT and Network	10.00 m unshielded
Speaker out (Left, Right) cable	Connected to the EUT and speaker	0.90 m unshielded

3.3 Modification Item(s)

- None



4. Description of tests

4.1 Test Condition

The EUT was installed, arranged and operated in a manner that is most representative of equipment as typically used. The measurements were carried out while varying operating modes and cable positions within typically arrangement to determine maximum emission level.

The representative and worst test mode(s) were noted in the test report.

- Test Voltage / Frequency : AC 120 V / 60 Hz
- Test Mode(s)

- . Monitor mode

Radiated emission: 1 920 × 1 080 / 60 Hz (RGB: Analog, HDMI/DVI: Digital)

Conducted emission: 1 920 × 1 080 / 60 Hz (RGB: Analog, HDMI/DVI: Digital)

1 024 × 768 / 60 Hz (RGB: Analog), 640 × 480 / 60 Hz (RGB: Analog)

◆ Operating test pattern

- . “H” character scrolling mode (Font size: 10)
- . Black background white character
- . Brightness and contrast was adjusted as maximum level
- . Continuous playback of 1 kHz audio file with winamp player
- . Operated DDC function with the eZ manager software

* DDC is a communication channel over which the monitor automatically informs the host system (PC) about its capabilities

“The verification report for AV mode would be issued by LG Electronics Inc.”



4.2 Conducted Emission

The Line conducted emission test facility is inside a 4 m × 8 m × 2.5 m shielded enclosure. (FCC Registration No.: 100749)

The EUT was placed on a non-conducting 1.0 m by 1.5 m table, which is 0.8 m in height and 0.4 m away from the vertical wall of the shielded enclosure.

The EUT is powered from the Rohde & Schwarz LISN (ESH2-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH3-Z5). Powers to the LISN are filtered by high-current high insertion loss power line filter.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

The RF output of the LISN was connected to the EMI test receiver (Rohde & Schwarz, ESCS30).

The EMI test receiver was scanned from 150 kHz to 30 MHz with 20 ms sweep time to determine the frequency producing the maximum EME from the EUT. The frequency producing the maximum level was re-examined using Quasi-Peak mode of the EMI test receiver.

The bandwidth of Quasi-peak mode was set to 9 kHz. Each emission was maximized consistent with typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum diagram emission. Excess cable lengths were bundled at center with 30 cm ~ 40 cm.

Each EME reported was calibrated using the R/S signal generator




Fig 2. Impedance of LISN



4.3 Radiated Emission

Preliminary measurements were conducted 3 m semi anechoic chamber using broadband antennas to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The technology configuration, mode of operation and turntable azimuth with respect to antenna was note for each frequency found.

Final measurements were made 3 m chamber (FCC registration No.: 443957) and/or 10 m OATS (FCC registration No.: 100749).

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was re-examined and investigated using EMI test receiver. The detector function was set to CISPR quasi-peak mode average mode and the bandwidth of the receiver was set to 120 kHz or 1 MHz depending on the frequency or type of signal.

The EUT, support equipment and interconnecting cables were reconfigured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8 m high non-metallic 1.0 m × 1.5 m table.

The turntable containing the test sample was rotated; the antenna height was varied 1 to 4 meter and stopped at the azimuth or height producing the maximum emission.

Each EME reported was calibrated using the R/S signal generator




Fig 3. Dimensions of test site



5. Conducted Emission

5.1 Operating Environment

Temperature : 25 °C
Relative Humidity : 41 % R.H.

5.2 Test Set-up

The conducted emission measurements were performed in the shielded room.

The EUT was placed on wooden table, 0.8 m heights above the floor, 0.4 m from the reference ground plane (GRP) wall and 0.8 m from AMN & ISN.

AMN is bonded on horizontal reference ground plane.

The ground plane, which was electrically bonded to the shield room, ground system and all power lines entering the shield room, were filtered.

5.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement.”

The measurement uncertainty was given with a confidence of 95 %.

Test Items	Uncertainty	Remark
Conducted emission (9 kHz ~ 150 kHz)	± 2.71 dB	Confidence levels of 95 % ($k = 2$)
Conducted emission (150 kHz ~ 30 MHz)	± 3.34 dB	Confidence levels of 95 % ($k = 2$)



5.4 Limit

RFI Conducted	FCC Limit(dB μ V/m) Class B	
Freq. Range	Quasi-Peak	Average
150 kHz ~ 0.5 MHz	66 ~ 56*	56 ~ 46*
0.5 MHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50
*Limits decreases linearly with the logarithm of frequency.		

5.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESCS30	Rohde & Schwarz	EMI Test Receiver	839809/003	12. 10. 2011
■ - ESH3-Z5	Rohde & Schwarz	LISN	838979/020	12. 10. 2011
■ - ESH2-Z5	Rohde & Schwarz	LISN	829991/009	12. 10. 2011
■ - ISN T8	TESEQ. GmbH	ISN	24568	11. 09. 2011


5.6 Test data for Conducted Emission

-. Test Date : March 8, 2011
-. Resolution Bandwidth : 9 kHz
-. Frequency Range : 0.15 MHz ~ 30 MHz



◆ Operating condition: 1 920 × 1 080 / 60 Hz (RGB: Analog)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.186000	44.5	1000.000	9.000	GND	L1	10.1	19.6	64.1	
0.382000	51.9	1000.000	9.000	GND	L1	10.1	6.2	58.1	
0.406000	48.5	1000.000	9.000	GND	L1	10.1	9.1	57.6	
0.710000	36.7	1000.000	9.000	GND	L1	10.1	19.3	56.0	
1.666000	29.1	1000.000	9.000	GND	L1	10.1	26.9	56.0	
17.450000	36.7	1000.000	9.000	GND	L1	11.1	23.3	60.0	
17.530000	37.0	1000.000	9.000	GND	L1	11.1	23.0	60.0	


Final Measurement Detector 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.226000	31.9	1000.000	9.000	GND	L1	10.1	20.5	52.4	
0.366000	36.5	1000.000	9.000	GND	L1	10.1	11.9	48.4	
0.482000	40.3	1000.000	9.000	GND	L1	10.1	6.0	46.3	
0.706000	31.7	1000.000	9.000	GND	L1	10.1	14.3	46.0	
1.666000	23.1	1000.000	9.000	GND	L1	10.1	22.9	46.0	
17.398000	26.4	1000.000	9.000	GND	L1	11.1	23.6	50.0	
18.462000	26.0	1000.000	9.000	GND	L1	11.2	24.0	50.0	

< Fig 4. Conducted emission result (Live line) >



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.230000	45.2	1000.000	9.000	GND	N	10.1	17.1	62.3	
0.238000	44.3	1000.000	9.000	GND	N	10.1	17.7	62.0	
0.378000	50.9	1000.000	9.000	GND	N	10.1	7.3	58.2	
0.442000	43.5	1000.000	9.000	GND	N	10.1	13.5	57.0	
0.706000	36.4	1000.000	9.000	GND	N	10.1	19.6	56.0	
0.938000	29.7	1000.000	9.000	GND	N	10.1	26.3	56.0	
18.298000	35.7	1000.000	9.000	GND	N	10.9	24.3	60.0	

Final Measurement Detector 2


Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.226000	34.7	1000.000	9.000	GND	N	10.1	17.7	52.4	
0.234000	33.9	1000.000	9.000	GND	N	10.1	18.2	52.1	
0.366000	38.8	1000.000	9.000	GND	N	10.1	9.6	48.4	
0.482000	36.9	1000.000	9.000	GND	N	10.1	9.4	46.3	
0.706000	29.9	1000.000	9.000	GND	N	10.1	16.1	46.0	
0.958000	23.1	1000.000	9.000	GND	N	10.1	23.0	46.0	
17.406000	25.6	1000.000	9.000	GND	N	10.9	24.4	50.0	

< Fig 5. Conducted emission result (Neutral line) >



◆ Operating condition: 1 024 × 768 / 60 Hz (RGB: Analog)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.186000	44.1	1000.000	9.000	GND	L1	10.1	20.0	64.1	
0.378000	51.6	1000.000	9.000	GND	L1	10.1	6.6	58.2	
0.402000	50.5	1000.000	9.000	GND	L1	10.1	7.2	57.7	
0.706000	37.1	1000.000	9.000	GND	L1	10.1	18.9	56.0	
1.782000	27.9	1000.000	9.000	GND	L1	10.2	28.1	56.0	
17.266000	36.3	1000.000	9.000	GND	L1	11.1	23.7	60.0	
18.666000	36.4	1000.000	9.000	GND	L1	11.2	23.6	60.0	


Final Measurement Detector 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.222000	31.9	1000.000	9.000	GND	L1	10.1	20.6	52.5	
0.378000	36.5	1000.000	9.000	GND	L1	10.1	11.7	48.2	
0.482000	41.2	1000.000	9.000	GND	L1	10.1	5.1	46.3	
0.706000	31.0	1000.000	9.000	GND	L1	10.1	15.0	46.0	
1.666000	23.5	1000.000	9.000	GND	L1	10.1	22.5	46.0	
17.410000	26.4	1000.000	9.000	GND	L1	11.1	23.6	50.0	
17.638000	25.7	1000.000	9.000	GND	L1	11.1	24.3	50.0	

< Fig 6. Conducted emission result (Live line) >



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.190000	46.2	1000.000	9.000	GND	N	10.1	17.7	63.9	
0.298000	44.0	1000.000	9.000	GND	N	10.1	16.1	60.1	
0.382000	51.5	1000.000	9.000	GND	N	10.1	6.6	58.1	
0.442000	43.3	1000.000	9.000	GND	N	10.1	13.7	57.0	
0.706000	36.3	1000.000	9.000	GND	N	10.1	19.7	56.0	
12.190000	34.3	1000.000	9.000	GND	N	10.6	25.7	60.0	
18.414000	34.8	1000.000	9.000	GND	N	10.9	25.2	60.0	

Final Measurement Detector 2


Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.190000	32.0	1000.000	9.000	GND	N	10.1	21.9	53.9	
0.238000	35.3	1000.000	9.000	GND	N	10.1	16.6	51.9	
0.370000	37.8	1000.000	9.000	GND	N	10.1	10.5	48.3	
0.482000	38.0	1000.000	9.000	GND	N	10.1	8.3	46.3	
0.702000	28.9	1000.000	9.000	GND	N	10.1	17.1	46.0	
0.962000	22.7	1000.000	9.000	GND	N	10.1	23.3	46.0	
1.778000	22.5	1000.000	9.000	GND	N	10.2	23.5	46.0	

< Fig 7. Conducted emission result (Neutral line) >



◆ Operating condition: 640 × 480 / 60 Hz (RGB: Analog)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.210000	43.3	1000.000	9.000	GND	L1	10.1	19.7	63.0	
0.382000	52.0	1000.000	9.000	GND	L1	10.1	6.1	58.1	
0.406000	48.6	1000.000	9.000	GND	L1	10.1	9.0	57.6	
0.702000	35.4	1000.000	9.000	GND	L1	10.1	20.6	56.0	
1.674000	28.6	1000.000	9.000	GND	L1	10.2	27.4	56.0	
17.414000	36.9	1000.000	9.000	GND	L1	11.1	23.1	60.0	
17.798000	37.2	1000.000	9.000	GND	L1	11.1	22.8	60.0	


Final Measurement Detector 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.210000	30.2	1000.000	9.000	GND	L1	10.1	22.8	53.0	
0.382000	39.7	1000.000	9.000	GND	L1	10.1	8.4	48.1	
0.486000	41.3	1000.000	9.000	GND	L1	10.1	4.9	46.2	
0.702000	30.8	1000.000	9.000	GND	L1	10.1	15.2	46.0	
1.778000	24.0	1000.000	9.000	GND	L1	10.2	22.0	46.0	
17.414000	26.1	1000.000	9.000	GND	L1	11.1	23.9	50.0	
17.546000	25.8	1000.000	9.000	GND	L1	11.1	24.2	50.0	

< Fig 8. Conducted emission result (Live line) >



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.206000	45.9	1000.000	9.000	GND	N	10.1	17.3	63.2	
0.242000	44.4	1000.000	9.000	GND	N	10.1	17.4	61.8	
0.386000	50.7	1000.000	9.000	GND	N	10.1	7.3	58.0	
0.486000	44.5	1000.000	9.000	GND	N	10.1	11.7	56.2	
0.698000	34.5	1000.000	9.000	GND	N	10.1	21.5	56.0	
11.910000	35.2	1000.000	9.000	GND	N	10.6	24.8	60.0	
17.714000	35.8	1000.000	9.000	GND	N	10.9	24.2	60.0	

Final Measurement Detector 2


Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.214000	34.9	1000.000	9.000	GND	N	10.1	17.9	52.8	
0.302000	32.6	1000.000	9.000	GND	N	10.1	17.3	49.9	
0.386000	34.2	1000.000	9.000	GND	N	10.1	13.8	48.0	
0.486000	38.3	1000.000	9.000	GND	N	10.1	7.9	46.2	
0.698000	29.3	1000.000	9.000	GND	N	10.1	16.7	46.0	
0.970000	22.5	1000.000	9.000	GND	N	10.1	23.5	46.0	
17.634000	25.8	1000.000	9.000	GND	N	10.9	24.2	50.0	

< Fig 9. Conducted emission result (Neutral line) >



◆ Operating condition: 1 920 × 1 080 / 60 Hz (HDMI/DVI: Digital)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.218000	42.8	1000.000	9.000	GND	L1	10.1	19.9	62.7	
0.378000	52.0	1000.000	9.000	GND	L1	10.1	6.2	58.2	
0.398000	51.1	1000.000	9.000	GND	L1	10.1	6.7	57.8	
0.702000	36.2	1000.000	9.000	GND	L1	10.1	19.8	56.0	
1.670000	28.8	1000.000	9.000	GND	L1	10.2	27.2	56.0	
17.290000	36.4	1000.000	9.000	GND	L1	11.1	23.6	60.0	
17.518000	37.0	1000.000	9.000	GND	L1	11.1	23.0	60.0	


Final Measurement Detector 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.222000	31.4	1000.000	9.000	GND	L1	10.1	21.1	52.5	
0.378000	37.6	1000.000	9.000	GND	L1	10.1	10.6	48.2	
0.482000	41.1	1000.000	9.000	GND	L1	10.1	5.2	46.3	
0.702000	31.4	1000.000	9.000	GND	L1	10.1	14.6	46.0	
1.670000	23.8	1000.000	9.000	GND	L1	10.2	22.2	46.0	
17.418000	26.5	1000.000	9.000	GND	L1	11.1	23.5	50.0	
17.518000	26.5	1000.000	9.000	GND	L1	11.1	23.5	50.0	

< Fig 10. Conducted emission result (Live line) >



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.218000	44.9	1000.000	9.000	GND	N	10.1	17.8	62.7	
0.298000	43.9	1000.000	9.000	GND	N	10.1	16.2	60.1	
0.378000	51.7	1000.000	9.000	GND	N	10.1	6.5	58.2	
0.486000	44.2	1000.000	9.000	GND	N	10.1	12.0	56.2	
0.706000	35.9	1000.000	9.000	GND	N	10.1	20.1	56.0	
11.710000	35.5	1000.000	9.000	GND	N	10.6	24.5	60.0	
18.286000	34.4	1000.000	9.000	GND	N	10.9	25.6	60.0	

Final Measurement Detector 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.222000	33.9	1000.000	9.000	GND	N	10.1	18.6	52.5	
0.242000	33.5	1000.000	9.000	GND	N	10.1	18.3	51.8	
0.374000	38.3	1000.000	9.000	GND	N	10.1	9.9	48.2	
0.482000	38.0	1000.000	9.000	GND	N	10.1	8.3	46.3	
0.702000	29.7	1000.000	9.000	GND	N	10.1	16.3	46.0	
0.966000	22.6	1000.000	9.000	GND	N	10.1	23.4	46.0	
1.670000	22.4	1000.000	9.000	GND	N	10.2	23.6	46.0	

< Fig 11. Conducted emission result (Neutral line) >



6. Radiated Emission

6.1 Operating Environment

Temperature : 13 °C
Relative Humidity : 60 % R.H.

6.2 Test Set-up

A preliminary scan with peak mode was performed in the semi anechoic chamber and found frequency for test site. The formal radiated emission was measured at 10 m distance open area test site and 3 m distance anechoic chamber. The EUT was placed on a non-conductive turntable approximately 0.8 m above the ground plane. The turntable with EUT was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

6.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement”.

The measurement uncertainty was given with a confidence of 95 %.

Test Items(Open Area Test Site)	Uncertainty	Remark
Radiated emission (30 MHz ~ 300 MHz, 10 m, Vertical)	± 4.03 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (30 MHz ~ 300 MHz, 10 m, Horizontal)	± 3.96 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 10 m, Vertical)	± 4.01 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 10 m, Horizontal)	± 3.88 dB	Confidence levels of 95 % ($k = 2$)



6.4 Limit

Frequency (MHz)	FCC Limit @ 3 m. dB μ V/m	CISPR Limit @ 10 m. dB μ V/m
30 ~ 88	40.0	30.0
88 ~ 216	43.5	30.0
216 ~ 230	46.0	30.0
230 ~ 960	46.0	37.0
960 ~ 1 000	54.0	37.0
> 1 000	54.0	No Specified limit

6.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESCS30	Rohde & Schwarz	EMI Test Receiver	839809/003	12. 10. 2011
■ - HK116	Rohde & Schwarz	Biconical Antenna	832639/007	03. 15. 2012
■ - HL223	Rohde & Schwarz	Log Periodic Antenna	835998/004	03. 15. 2012
■ - HD100	HD GmbH	Position Controller	100/692/01	N/A
■ - DS415S	HD GmbH	Turntable	415/657/01	N/A
■ - MA240	HD GmbH	Antenna Mast	240/565/01	N/A
■ - ESIB26	Rohde & Schwarz	EMI Test Receiver	830482/010	12. 11. 2011
■ - BBHA9120D	Schwarzbeck	Horn Antenna	207	12. 22. 2011
■ - MCU066	maturo GmbH	Position Controller	1390306	N/A
■ - TT2.5SI	maturo GmbH	Turntable	1390307	N/A
■ - AM 4.0	maturo GmbH	Antenna Mast	1390308	N/A
■ - AFS 44 00101800-25-10P-44	MITEQ	Preamplifier	1258943	11. 12. 2011




6.6 Test data for Radiated Emission

- Test Date : March 7 ~ 14, 2011
- Resolution Bandwidth : 120 kHz/1 MHz
- Frequency Range : 30 MHz ~ 2 000 MHz
- Measurement Distance : 10 m/3 m
- Note : The highest frequency of the internal source of the EUT is between 108 MHz and 500 MHz (250 MHz). The measurement was made up to 2 000 MHz

◆ Operating Condition: 1 920 × 1 080 / 60 Hz (RGB: Analog)

Detector mode: Quasi-peak detector mode

Frequency (MHz)	Measurement Level				Limit (dBμ V/m)	Margin (dB)	Positioning System		
	Reading	Antenna	Cable	Test Result			Pol.	Height	Angle
	Value(dBμ V)	Factor(dB/m)	Loss(dB)	(dBμ V/m)			(H/V)	(cm)	(°)
49.14	5.08	9.46	1.70	16.24	30.00	13.76	V	100	109
73.75	6.36	8.61	2.14	17.11	30.00	12.89	V	100	0
93.00	5.40	8.89	2.44	16.73	30.00	13.27	V	100	0
111.40	12.77	10.48	2.68	25.93	30.00	4.07	H	193	63
167.31	9.83	12.62	3.39	25.84	30.00	4.16	H	128	69
738.07	0.85	20.63	7.97	29.45	37.00	7.55	V	217	8




< Fig 12. Radiated emission result (30 MHz ~ 1 000 MHz) >



- ◆ Operating Condition: 1 920 × 1 080 / 60 Hz (HDMI/DVI: Digital)
Detector mode: Quasi-peak detector mode


Frequency (MHz)	Measurement Level				Limit (dBμ V/m)	Margin (dB)	Positioning System		
	Reading	Antenna	Cable	Test Result			Pol.	Height	Angle
	Value(dBμ V)	Factor(dB/m)	Loss(dB)	(dBμ V/m)			(H/V)	(cm)	(°)
79.64	14.06	8.45	2.24	24.75	30.00	5.25	H	234	36
89.43	14.04	8.63	2.39	25.06	30.00	4.94	H	217	5
158.54	5.52	12.06	3.28	20.86	30.00	9.14	H	100	57
168.33	6.92	12.70	3.40	23.02	30.00	6.98	H	100	69
585.53	5.30	18.80	6.92	31.02	37.00	5.98	V	214	342
945.93	0.30	22.82	9.29	32.41	37.00	4.59	V	206	177



< Fig 13. Radiated emission result (30 MHz ~ 1 000 MHz) >



- ◆ Operating Condition: 1 920 × 1 080 / 60 Hz (RGB: Analog)
Green trace: Average detector, Blue trace: Peak detector



Final Result 1

Frequency (MHz)	MaxPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
1054.708217	58.3	100.0	1000.000	139.0	V	194.0	-14.2	15.7	74.0
1485.569940	55.9	100.0	1000.000	100.0	V	138.0	-13.1	18.1	74.0
1681.154709	55.9	100.0	1000.000	130.0	H	163.0	-12.6	18.1	74.0


Final Result 2

Frequency (MHz)	CAverage (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
1055.908217	34.1	100.0	1000.000	100.0	V	194.0	-14.2	19.9	54.0
1485.169940	31.7	100.0	1000.000	100.0	V	138.0	-13.1	22.3	54.0
1682.354709	34.5	100.0	1000.000	100.0	H	163.0	-12.6	19.5	54.0

< Fig 14. Radiated emission result (1 000 MHz ~ 2 000 MHz) >



- ◆ Operating Condition: 1 920 × 1 080 / 60 Hz (HDMI/DVI: Digital)
Green trace: Average detector, Blue trace: Peak detector



Final Result 1

Frequency (MHz)	MaxPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1043.488176	56.9	100.0	1000.000	100.0	V	188.0	-14.3	17.1	74.0
1677.954709	51.6	100.0	1000.000	100.0	H	182.0	-12.6	22.4	74.0
1981.363928	57.1	100.0	1000.000	122.0	H	127.0	-11.7	16.9	74.0

Final Result 2

Frequency (MHz)	CAverage (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1043.488176	33.5	100.0	1000.000	144.0	V	188.0	-14.3	20.5	54.0
1682.354709	31.9	100.0	1000.000	100.0	H	182.0	-12.6	22.1	54.0
1981.363928	36.2	100.0	1000.000	123.0	H	127.0	-11.7	17.8	54.0

< Fig 15. Radiated emission result (1 000 MHz ~ 2 000 MHz) >



7. Sample Calculations

$$\begin{aligned} \text{dB}\mu\text{V} &= 20 \text{ Log}_{10}(\mu\text{V}/\text{m}) \\ \text{dB}\mu\text{V} &= \text{dBm} + 107 \\ \mu\text{V} &= 10^{(\text{dB}\mu\text{V}/20)} \end{aligned}$$

7.1 Example 1 :

■ 20.3 MHz

Class B Limit	= 250 μV = 48 dB μV
Reading	= 39.2 dB μV
$10^{(39.2\text{dB}\mu\text{V}/20)}$	= 91.2 μV
Margin	= 48 dB μV - 39.2 dB μV = 8.8 dB

7.2 Example 2 :

■ 66.7 MHz

Class B Limit	= 100 $\mu\text{V}/\text{m}$ = 40.0 dB $\mu\text{V}/\text{m}$
Reading	= 31.0 dB μV
Antenna Factor + Cable Loss = 5.8 dB	
Total	= 36.8 dB $\mu\text{V}/\text{m}$
Margin	= 40.0 dB $\mu\text{V}/\text{m}$ - 36.8 dB $\mu\text{V}/\text{m}$ = 3.2 dB



8. Recommendation & Conclusion

The data collected shows that the **LG Electronics Inc. LCD Monitor (Model Name: 47VL10)** was complies with § 15.107 and 15.109 of the FCC Rules.