

FCC EVALUATION REPORT FOR CERTIFICATION

Applicant: LG Electronics Inc.

19-1, Cheongho-ri, Jinwi-myeon,

Pyeongteak-si, Gyeonggi-do, Korea.

Attn: Mr. Do-Hyung Kim, Chief research engineer

Date of Issue: December 26, 2011

Order Number: GETEC-C1-11-338

Test Report Number: GETEC-E3-11-149

Test Site: GUMI COLLEGE EMC CENTER

FCC Registration Number: (100749, 443957)

FCC ID. : BEJ50PA4900UD

Applicant : LG Electronics Inc.

Rule Part(s)	: FCC Part 15 Subpart B
Equipment Class	: Class B computing device peripheral (JBP)
EUT Type	: PLASMA TV/MONITOR
Type of Authority	: Certification
Model Name	: 50PA4900-UD
Trade Name	: LG

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003 / Canadian standard ICES-003

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by,

Reviewed by,


Seung-Chul Lee, Associate Engineer
GUMI COLLEGE EMC CENTER


Jae-Hoon Jeong, Senior Engineer
GUMI COLLEGE EMC CENTER



CONTENTS

1. GENERAL INFORMATION	3
2. INTRODUCTION	4
3. PRODUCT INFORMATION	5
3.1 DESCRIPTION OF EUT.....	5
3.2 SUPPORT EQUIPMENT / CABLES USED	6
3.3 MODIFICATION ITEM(S).....	7
4. DESCRIPTION OF TESTS.....	8
4.1 TEST CONDITION.....	8
4.2 CONDUCTED EMISSION	9
4.3 RADIATED EMISSION.....	10
5. CONDUCTED EMISSION.....	11
5.1 OPERATING ENVIRONMENT	11
5.2 TEST SET-UP	11
5.3 MEASUREMENT UNCERTAINTY.....	11
5.4 LIMIT	12
5.5 TEST EQUIPMENT USED.....	12
5.6 TEST DATA FOR CONDUCTED EMISSION	12
6. RADIATED EMISSION	17
6.1 OPERATING ENVIRONMENT	17
6.2 TEST SET-UP	17
6.3 MEASUREMENT UNCERTAINTY.....	17
6.4 LIMIT	18
6.5 TEST EQUIPMENT USED.....	18
6.6 TEST DATA FOR RADIATED EMISSION	18
7. SAMPLE CALCULATIONS.....	23
7.1 EXAMPLE 1 :	23
7.2 EXAMPLE 2 :	23
8. RECOMMENDATION & CONCLUSION.....	24
 APPENDIX A – ATTESTATION STATEMENT	
APPENDIX B – ID SAMPLE LABEL & LOCATION	
APPENDIX C – BLOCK DIAGRAM	
APPENDIX D – TEST SET-UP PHOTOGRAPHS	
APPENDIX E – EXTERNAL PHOTOGRAPHS	
APPENDIX F – INTERNAL PHOTOGRAPHS	
APPENDIX G – USER’S MANUAL	



Scope: Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and / or unintentional radiators for compliance with technical rules and regulations of the Federal Communications Commission.

1. General Information

Applicant: LG Electronics Inc.

Applicant Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Manufacturer: LG Electronics Inc.

Manufacturer Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Contact Person: Mr. Do-Hyung Kim, Chief research engineer

Tel Number: +82-31-610-9623

- **FCC ID.** BEJ50PA4900UD
- **EUT Type** PLASMA TV/MONITOR
- **Model Name** 50PA4900-UD
- **Trade Name** LG
- **Serial Number** Prototype
- **Rule Part(s)** FCC Part 15 Subpart B
- **Type of Authority** Certification
- **Test Procedure(s)** ANSI C63.4 (2003) / Canadian standard ICES-003
- **Dates of Test** December 14 ~ 19, 2011
- **Place of Test** **GUMI COLLEGE EMC CENTER** (FCC Registration Number: 100749, 443957)
407, Bugok-dong, Gumi-si, Gyeongsangbuk-do, Korea.
- **Test Report Number** GETEC-E3-11-149
- **Dates of Issue** December 26, 2011

EUT Type: PLASMA TV/MONITOR

FCC ID.: BEJ50PA4900UD



2. Introduction


The measurement procedure described in American National Standard for Methods of Measurement of Radio-Nose Emissions From Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ASNI C63.4-2003) was used in determining radiated and conducted emissions emanating from **LG Electronics Inc.**

PLASMA TV/MONITOR (Model Name: 50PA4900-UD)

These measurement tests were conducted at **GUMI COLLEGE EMC CENTER**

The site address is 407, Bugok-dong, Gumi-si, Gyeongsangbuk-do, Korea.

This test site is one of the highest point of Gumi 1 college at about 200 km away from Seoul city and 40 km away from Daegu city. It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 (2003)



GUMI COLLEGE EMC CENTER
407, Bugok-dong, Gumi-si,
Gyeongsangbuk-do, Korea.
Tel: +82-54-440-1195
Fax: +82-54-440-1199

Fig 1. The map above shows the Gumi College in vicinity area.



3. Product Information

3.1 Description of EUT

The Equipment under Test (EUT) is the **LG Electronics Inc.**

PLASMA TV/MONITOR (Model Name: 50PA4900-UD) FCC ID.: BEJ50PA4900UD

MODELS		42PA4900 (42PA4900-UD)	50PA4900 (50PA4900-UD)
Dimensions (W x H x D)	With stand	991.8 mm x 667.0 mm x 230.5 mm (39.0 inch x 26.2 inch x 9.0 inch)	1168.0 mm x 754.0 mm x 336 mm (45.9 inch x 29.6 inch x 13.2 inch)
	Without stand	991.8 mm x 613.8 mm x 52.5 mm (39.0 inch x 24.1 inch x 2.0 inch)	1168.0 mm x 704.0 mm x 52.5 mm (45.9 inch x 27.7 inch x 2.0 inch)
Weight	With stand	21.5 kg (47.3 lbs)	27.7 kg (61.0 lbs)
	Without stand	20.0 kg (44.0 lbs)	25.8 kg (56.8 lbs)
Power requirement		AC100 - 240 V ~ 50/60 Hz	
Television System		NTSC-M, ATSC, 64 & 256 QAM	
Program Coverage		VHF 2-13, UHF 14-69, CATV 1-135, DTV 2-69, CADTV 1-135	
External Antenna Impedance		75 Ω	
Environment condition	Operating Temperature	0 - 40°C	
	Operating Humidity	Less than 80%	
	Storage Temperature	-20 - 60°C	
	Storage Humidity	Less than 85%	

-. Maximum Frequency Range : 666 MHz

EUT Type: PLASMA TV/MONITOR

FCC ID.: BEJ50PA4900UD



3.2 Support Equipment / Cables used

3.2.1 Used Support Equipment

Description	Manufacturer	Model Name	S/N & FCC ID.
PC (Main board)	ASLOCK	770iCafe	S/N: 0AM0X3097310 FCC ID.: DoC
Video card	Rextechnology Co., Ltd.	HD4850	S/N: L5H401947 FCC ID.: DoC
PS2 keyboard	COMPAQ	166516-AD6	S/N: B13BBOR391006D FCC ID.: AQ6-23K15
USB mouse	Great Pleasure Electronics Co., Ltd.	GP-M3100UE	S/N: 14036766 FCC ID: DoC
DVD player	LG Electronics Inc.	LC-954	S/N: 3850R-Z674K FCC ID.: Verification
USB memory stick	SAMSUNG	SUM-PSB4	S/N: TBBB202478F FCC ID.: DoC
Digital TV pattern generator	Teleview	TPG430B	S/N: 93.01.20.05.09.00.00.02 FCC ID.: Verification
8-VSB modulator	Ktech	VSF-ENC-150E	S/N: 2005-726 FCC ID.: Verification

See "Appendix D – Test Setup Photographs" for actual system test set-up

3.2.2 System configuration

Description	Manufacturer	Model Name	S/N & FCC ID.
IR remote controller	OHSUNG ELECTRONICS CO., LTD.	AKB73615336	S/N: None. FCC ID.: BEJMR3007



3.2.3 Used Cable(s)

Cable Name	Condition	Description
Power cable	Connected to the EUT	1.80 m unshielded with two ferrite cores
RGB(Analog) in cable	Connected to the EUT and PC	1.80 m shielded with two ferrite cores
HDMI/DVI (Digital) in cable	Connected to the EUT and PC	2.00 m shielded
Audio(RGB/DVI) in cable	Connected to the EUT and PC	1.50 m shielded
RS-232C in cable	Connected to the EUT and PC	1.80 m shielded
Remote control in cable	Connected to the EUT and PC	1.50 m shielded
AV in cable	Connected to the EUT and DVD player	3.00 m shielded
Component in cable	Connected to the EUT and DVD player	3.00 m shielded
Antenna cable	Connected to the EUT and digital TV pattern generator	10.00 m shielded

3.3 Modification Item(s)

- None



4. Description of tests

4.1 Test Condition

The EUT was installed, arranged and operated in a manner that is most representative of equipment as typically used. The measurements were carried out while varying operating modes and cable positions within typically arrangement to determine maximum emission level.

The representative and worst test mode(s) were noted in the test report.

- Test Voltage / Frequency : AC 120 V / 60 Hz
- Test Mode(s)

-. Monitor mode

Radiated emission: 1 024 × 768 / 60 Hz (RGB: Analog, HDMI/DVI: Digital)

Conducted emission: 1 024 × 768 / 60 Hz (RGB: Analog, HDMI/DVI: Digital),
800 × 600 / 60 Hz (RGB: Analog), 640 × 480 / 60 Hz (RGB: Analog)

◆ Operating test pattern

- "H" character scrolling mode (Font size: 10)
- Black background white character
- Brightness and contrast was adjusted as maximum level
- Continuous playback of 1 kHz audio file with winamp player
- USB memory stick was connected to the USB port

"The verification report for TV/AV mode would be issued by LG Electronics Inc."



4.2 Conducted Emission

The Line conducted emission test facility is inside a 4 m × 8 m × 2.5 m shielded enclosure. (FCC Registration No.: 100749)

The EUT was placed on a non-conducting 1.0 m by 1.5 m table, which is 0.8 m in height and 0.4 m away from the vertical wall of the shielded enclosure.

The EUT is powered from the Rohde & Schwarz LISN (ESH2-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH3-Z5). Powers to the LISN are filtered by high-current high insertion loss power line filter.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

The RF output of the LISN was connected to the EMI test receiver (Rohde & Schwarz, ESCS30).

The EMI test receiver was scanned from 150 kHz to 30 MHz with 20 ms sweep time to determine the frequency producing the maximum EME from the EUT. The frequency producing the maximum level was re-examined using Quasi-Peak mode of the EMI test receiver.

The bandwidth of Quasi-peak mode was set to 9 kHz. Each emission was maximized consistent with typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum diagram emission. Excess cable lengths were bundled at center with 30 cm ~ 40 cm.

Each EME reported was calibrated using the R/S signal generator




Fig 2. Impedance of LISN



4.3 Radiated Emission

Preliminary measurements were conducted 3 m semi anechoic chamber using broadband antennas to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The technology configuration, mode of operation and turntable azimuth with respect to antenna was note for each frequency found.

Final measurements were made 3 m chamber (FCC registration No.: 443957) and/or 10 m OATS (FCC registration No.: 100749).

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was re-examined and investigated using EMI test receiver. The detector function was set to CISPR quasi-peak mode average mode and the bandwidth of the receiver was set to 120 kHz or 1 MHz depending on the frequency or type of signal.

The EUT, support equipment and interconnecting cables were reconfigured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8 m high non-metallic 1.0 m × 1.5 m table.

The turntable containing the test sample was rotated; the antenna height was varied 1 to 4 meter and stopped at the azimuth or height producing the maximum emission.

Each EME reported was calibrated using the R/S signal generator




Fig 3. Dimensions of test site



5. Conducted Emission

5.1 Operating Environment

Temperature : 24.0 °C
Relative Humidity : 39.0 % R.H.

5.2 Test Set-up

The conducted emission measurements were performed in the shielded room.

The EUT was placed on wooden table, 0.8 m heights above the floor, 0.4 m from the reference ground plane (GRP) wall and 0.8 m from AMN & ISN.

AMN is bonded on horizontal reference ground plane.

The ground plane, which was electrically bonded to the shield room, ground system and all power lines entering the shield room, were filtered.

5.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO "Guide to the expression of uncertainty in measurement."

The measurement uncertainty was given with a confidence of 95 %.

Test Items	Uncertainty	Remark
Conducted emission (9 kHz ~ 150 kHz)	± 2.71 dB	Confidence level of approximately 95 % ($k = 2$)
Conducted emission (150 kHz ~ 30 MHz)	± 3.34 dB	Confidence level of approximately 95 % ($k = 2$)



5.4 Limit

RFI Conducted	FCC Limit(dB μ V/m) Class B	
Freq. Range	Quasi-Peak	Average
150 kHz ~ 0.5 MHz	66 ~ 56*	56 ~ 46*
0.5 MHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50
*Limits decreases linearly with the logarithm of frequency.		

5.5 Test Equipment used


Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESCS30	Rohde & Schwarz	EMI Test Receiver	839809/003	12. 05. 2012
■ - ESH3-Z5	Rohde & Schwarz	LISN	838979/020	12. 07. 2012
■ - ESH2-Z5	Rohde & Schwarz	LISN	829991/009	12. 07. 2012
□ - ENY81-CA6	Rohde & Schwarz	ISN	101573	10. 19. 2012

5.6 Test data for Conducted Emission

- . Test Date : December 19, 2011
- . Resolution Bandwidth : 9 kHz
- . Frequency Range : 0.15 MHz ~ 30 MHz
- . Line : L1: Live, N: Neutral



◆ Operating condition: 1 024 × 768 / 60 Hz (RGB: Analog)



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.170000	56.5	1000.0	9.000	GND	N	10.0	8.5	65.0	
0.364000	43.1	1000.0	9.000	GND	L1	10.0	15.6	58.6	
0.444000	49.1	1000.0	9.000	GND	L1	10.0	7.9	57.0	
1.112000	45.0	1000.0	9.000	GND	L1	10.1	11.0	56.0	
1.972000	40.9	1000.0	9.000	GND	L1	10.1	15.1	56.0	
2.572000	43.5	1000.0	9.000	GND	L1	10.1	12.5	56.0	
3.620000	43.0	1000.0	9.000	GND	L1	10.2	13.0	56.0	
13.364000	36.1	1000.0	9.000	GND	N	10.5	23.9	60.0	


Final Result 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.170000	44.7	1000.0	9.000	GND	N	10.0	10.2	55.0	
0.364000	28.7	1000.0	9.000	GND	L1	10.0	19.9	48.6	
0.444000	28.7	1000.0	9.000	GND	L1	10.0	18.3	47.0	
1.112000	25.3	1000.0	9.000	GND	L1	10.1	20.7	46.0	
1.972000	17.2	1000.0	9.000	GND	L1	10.1	28.8	46.0	
2.572000	20.7	1000.0	9.000	GND	L1	10.1	25.3	46.0	
3.620000	21.5	1000.0	9.000	GND	L1	10.2	24.5	46.0	
13.364000	16.4	1000.0	9.000	GND	N	10.5	33.6	50.0	

< Fig 4. Conducted emission result >



◆ Operating condition: 800 × 600 / 60 Hz (RGB: Analog)



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.162000	58.7	1000.0	9.000	GND	N	10.0	6.7	65.4	
0.328000	45.1	1000.0	9.000	GND	N	10.0	14.4	59.5	
0.448000	47.8	1000.0	9.000	GND	L1	10.0	9.1	56.9	
1.196000	41.5	1000.0	9.000	GND	L1	10.1	14.5	56.0	
2.032000	37.9	1000.0	9.000	GND	L1	10.1	18.1	56.0	
2.228000	51.2	1000.0	9.000	GND	L1	10.1	4.8	56.0	
3.568000	43.6	1000.0	9.000	GND	L1	10.2	12.4	56.0	
22.964000	30.4	1000.0	9.000	GND	N	10.8	29.6	60.0	


Final Result 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.162000	48.5	1000.0	9.000	GND	N	10.0	6.9	55.4	
0.328000	32.4	1000.0	9.000	GND	N	10.0	17.1	49.5	
0.448000	27.8	1000.0	9.000	GND	L1	10.0	19.1	46.9	
1.196000	23.5	1000.0	9.000	GND	L1	10.1	22.5	46.0	
2.032000	14.4	1000.0	9.000	GND	L1	10.1	31.6	46.0	
2.228000	28.1	1000.0	9.000	GND	L1	10.1	17.9	46.0	
3.568000	22.5	1000.0	9.000	GND	L1	10.2	23.5	46.0	
22.964000	13.1	1000.0	9.000	GND	N	10.8	36.9	50.0	

< Fig 5. Conducted emission result >



◆ Operating condition: 640 × 480 / 60 Hz (RGB: Analog)



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.166000	57.4	1000.0	9.000	GND	N	10.0	7.8	65.2	
0.336000	44.6	1000.0	9.000	GND	N	10.0	14.7	59.3	
0.444000	48.6	1000.0	9.000	GND	L1	10.0	8.3	57.0	
0.892000	43.6	1000.0	9.000	GND	L1	10.0	12.4	56.0	
1.316000	40.2	1000.0	9.000	GND	L1	10.1	15.8	56.0	
2.228000	51.3	1000.0	9.000	GND	L1	10.1	4.7	56.0	
4.068000	39.7	1000.0	9.000	GND	L1	10.2	16.3	56.0	
9.188000	36.3	1000.0	9.000	GND	N	10.4	23.7	60.0	


Final Result 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.166000	47.7	1000.0	9.000	GND	N	10.0	7.4	55.2	
0.336000	33.0	1000.0	9.000	GND	N	10.0	16.3	49.3	
0.444000	28.3	1000.0	9.000	GND	L1	10.0	18.7	47.0	
0.892000	24.7	1000.0	9.000	GND	L1	10.0	21.3	46.0	
1.316000	20.4	1000.0	9.000	GND	L1	10.1	25.6	46.0	
2.228000	28.5	1000.0	9.000	GND	L1	10.1	17.5	46.0	
4.068000	19.6	1000.0	9.000	GND	L1	10.2	26.4	46.0	
9.188000	15.9	1000.0	9.000	GND	N	10.4	34.1	50.0	

< Fig 6. Conducted emission result >



◆ Operating condition: 1 024 × 768 / 60 Hz (HDMI/DVI: Digital)



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.166000	58.4	1000.0	9.000	GND	L1	10.0	6.7	65.2	
0.332000	45.1	1000.0	9.000	GND	N	10.0	14.3	59.4	
0.444000	47.9	1000.0	9.000	GND	L1	10.0	9.0	57.0	
1.112000	44.5	1000.0	9.000	GND	L1	10.1	11.5	56.0	
1.556000	44.1	1000.0	9.000	GND	L1	10.1	11.9	56.0	
2.672000	49.7	1000.0	9.000	GND	L1	10.1	6.3	56.0	
3.848000	39.1	1000.0	9.000	GND	L1	10.2	16.9	56.0	
9.188000	35.8	1000.0	9.000	GND	N	10.4	24.2	60.0	

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.166000	51.0	1000.0	9.000	GND	L1	10.0	4.1	55.2	
0.332000	34.3	1000.0	9.000	GND	N	10.0	15.1	49.4	
0.444000	26.3	1000.0	9.000	GND	L1	10.0	20.7	47.0	
1.112000	24.1	1000.0	9.000	GND	L1	10.1	21.9	46.0	
1.556000	23.4	1000.0	9.000	GND	L1	10.1	22.6	46.0	
2.672000	25.3	1000.0	9.000	GND	L1	10.1	20.7	46.0	
3.848000	18.2	1000.0	9.000	GND	L1	10.2	27.8	46.0	
9.188000	14.2	1000.0	9.000	GND	N	10.4	35.8	50.0	

< Fig 7. Conducted emission result >



6. Radiated Emission

6.1 Operating Environment

Temperature : 24.0 °C
Relative Humidity : 42.0 % R.H.

6.2 Test Set-up

A preliminary and final measurement was at 3 m anechoic chamber.

The EUT was placed on a non-conductive turntable approximately 0.8 m above the ground plane.

The turntable with EUT was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels.

This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

6.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement”.

The measurement uncertainty was given with a confidence of 95 %.

Test Items(Anechoic Chamber)	Uncertainty	Remark
Radiated emission (30 MHz ~ 300 MHz, 3 m, Vertical)	± 4.38 dB	Confidence level of approximately 95 % ($k = 2$)
Radiated emission (30 MHz ~ 300 MHz, 3 m, Horizontal)	± 3.50 dB	Confidence level of approximately 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Vertical)	± 3.75 dB	Confidence level of approximately 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Horizontal)	± 3.59 dB	Confidence level of approximately 95 % ($k = 2$)



6.4 Limit

Frequency (MHz)	FCC Limit @ 3 m. dB μ V/m	CISPR Limit @ 10 m. dB μ V/m
30 ~ 88	40.0	30.0
88 ~ 216	43.5	30.0
216 ~ 230	46.0	30.0
230 ~ 960	46.0	37.0
960 ~ 1 000	54.0	37.0
> 1 000	54.0	No Specified limit

6.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESIB26	Rohde & Schwarz	EMI Test Receiver	830482/010	12. 05. 2012
■ - VULB9160	Schwarzbeck	Broadband Test Antenna	3193	03. 15. 2012
■ - BBHA9120D	Schwarzbeck	Horn ANT	207	12. 22. 2011
■ - MCU066	maturo GmbH	Position Controller	1390306	N/A
■ - TT2.5SI	maturo GmbH	Turntable	1390307	N/A
■ - AM 4.0	maturo GmbH	Antenna Mast	1390308	N/A
■ - AFS 44 00101800-25-10P-44	MITEQ	Preamplifier	1258943	11. 12. 2012

6.6 Test data for Radiated Emission


-. Test Date : December 14 ~ 15, 2011
 -. Measurement Distance : 3 m
 -. Note : The highest frequency of the internal source of the EUT is between 500 MHz and 1 000 MHz (666 MHz). The measurement was made up to 5 000 MHz

-. Measurement

Frequency range	30 MHz ~ 1 GHz	Above 1 GHz
Detector type	Quasi peak	Peak / Average
IF bandwidth	120 kHz	1 MHz



- ◆ Operating Condition: 1 024 × 768 / 60 Hz (RGB: Analog)
Red trace: Vertical polarization, Blue trace: Horizontal polarization




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
33.803750	33.7	1000.0	120.000	100.0	V	148.0	12.4	6.3	40.0
50.237500	23.8	1000.0	120.000	100.0	V	185.0	13.1	16.2	40.0
85.630000	32.3	1000.0	120.000	205.0	H	-7.0	9.1	7.7	40.0
97.827500	33.1	1000.0	120.000	205.0	H	35.0	10.2	10.4	43.5
140.681250	33.7	1000.0	120.000	205.0	H	254.0	13.9	9.8	43.5
183.967500	35.3	1000.0	120.000	171.0	H	152.0	12.6	8.2	43.5
246.176250	34.0	1000.0	120.000	100.0	H	19.0	13.1	12.0	46.0

< Fig 8. Radiated emission result (30 MHz ~ 1 000 MHz) >



- ◆ Operating Condition: 1 024 × 768 / 60 Hz (HDMI/DVI: Digital)
Red trace: Vertical polarization, Blue trace: Horizontal polarization




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
33.888750	32.5	1000.0	120.000	100.0	V	295.0	12.4	7.5	40.0
49.820000	31.2	1000.0	120.000	100.0	V	166.0	13.1	8.8	40.0
85.537500	32.6	1000.0	120.000	196.0	H	35.0	9.1	7.4	40.0
88.976250	33.8	1000.0	120.000	200.0	H	19.0	9.2	9.7	43.5
243.421250	32.9	1000.0	120.000	100.0	H	255.0	13.0	13.1	46.0
245.288750	33.6	1000.0	120.000	100.0	H	30.0	13.0	12.4	46.0
389.567500	34.2	1000.0	120.000	100.0	H	202.0	17.4	11.8	46.0

< Fig 9. Radiated emission result (30 MHz ~ 1 000 MHz) >



- ◆ Operating Condition: 1 024 × 768 / 60 Hz (RGB: Analog)
Green marker: Average detector, Blue marker: Peak detector



Final Result 1

Frequency (MHz)	MaxPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
1188.168738	48.7	1000.0	1000.000	100.0	V	355.0	-13.5	25.3	74.0
1613.850501	47.3	1000.0	1000.000	100.0	H	32.0	-12.2	26.7	74.0
1938.507816	53.4	1000.0	1000.000	100.0	H	0.0	-11.5	20.6	74.0
2654.318637	53.9	1000.0	1000.000	176.0	V	3.0	-7.8	20.1	74.0
4146.532665	44.8	1000.0	1000.000	232.0	H	264.0	-2.2	29.2	74.0
4594.966333	51.5	1000.0	1000.000	100.0	V	3.0	-1.3	22.5	74.0


Final Result 2

Frequency (MHz)	CAverage (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
1188.168738	44.8	1000.0	1000.000	100.0	V	355.0	-13.5	9.2	54.0
1613.850501	25.4	1000.0	1000.000	100.0	H	32.0	-12.2	28.6	54.0
1938.507816	26.3	1000.0	1000.000	100.0	H	0.0	-11.5	27.7	54.0
2654.318637	30.4	1000.0	1000.000	176.0	V	3.0	-7.8	23.6	54.0
4146.532665	34.4	1000.0	1000.000	232.0	H	264.0	-2.2	19.6	54.0
4594.966333	34.6	1000.0	1000.000	100.0	V	3.0	-1.3	19.4	54.0

< Fig 10. Radiated emission result (1 000 MHz ~ 5 000 MHz) >



- ◆ Operating Condition: 1 024 × 768 / 60 Hz (HDMI/DVI: Digital)
Green marker: Average detector, Blue marker: Peak detector



Final Result 1

Frequency (MHz)	MaxPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1038.664128	60.1	1000.0	1000.000	115.0	V	44.0	-14.1	13.9	74.0
1623.034469	64.1	1000.0	1000.000	100.0	V	38.0	-12.2	9.9	74.0
2251.484970	47.5	1000.0	1000.000	100.0	H	30.0	-9.9	26.5	74.0
2654.318637	55.5	1000.0	1000.000	100.0	V	10.0	-7.8	18.5	74.0
4594.998397	49.1	1000.0	1000.000	187.0	H	35.0	-1.3	24.9	74.0

Final Result 2

Frequency (MHz)	CAverage (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1038.664128	48.2	1000.0	1000.000	115.0	V	44.0	-14.1	5.8	54.0
1623.034469	49.3	1000.0	1000.000	100.0	V	38.0	-12.2	4.7	54.0
2251.484970	27.6	1000.0	1000.000	100.0	H	30.0	-9.9	26.4	54.0
2654.318637	30.9	1000.0	1000.000	100.0	V	10.0	-7.8	23.1	54.0
4594.998397	34.2	1000.0	1000.000	187.0	H	35.0	-1.3	19.8	54.0

< Fig 11. Radiated emission result (1 000 MHz ~ 5 000 MHz) >



7. Sample Calculations

$$\begin{aligned} \text{dB}\mu\text{V} &= 20 \text{ Log}_{10}(\mu\text{V}/\text{m}) \\ \text{dB}\mu\text{V} &= \text{dBm} + 107 \\ \mu\text{V} &= 10^{(\text{dB}\mu\text{V}/20)} \end{aligned}$$

7.1 Example 1 :

■ 20.3 MHz

Class B Limit	= 250 μV = 48 dB μV
Reading	= 39.2 dB μV
$10^{(39.2\text{dB}\mu\text{V}/20)}$	= 91.2 μV
Margin	= 48 dB μV - 39.2 dB μV = 8.8 dB

7.2 Example 2 :

■ 66.7 MHz

Class B Limit	= 100 $\mu\text{V}/\text{m}$ = 40.0 dB $\mu\text{V}/\text{m}$
Reading	= 31.0 dB μV
Antenna Factor + Cable Loss = 5.8 dB	
Total	= 36.8 dB $\mu\text{V}/\text{m}$
Margin	= 40.0 dB $\mu\text{V}/\text{m}$ – 36.8 dB $\mu\text{V}/\text{m}$ = 3.2 dB



8. Recommendation & Conclusion

The data collected shows that the **LG Electronics Inc. PLASMA TV/MONITOR (Model Name: 50PA4900-UD)** was complies with §15.107 and 15.109 of the FCC Rules.

- The end -