

FCC EVALUATION REPORT FOR CERTIFICATION

Applicant : LG Electronics Inc.

19-1, Cheongho-ri, Jinwi-myeon,

Pyeongteak-si, Gyeonggi-do, Korea.

Attn: Mr. Sang-Wook Lee, Chief research engineer

Date of Issue : December 16, 2009

Order Number: GETEC-C1-09-257

Test Report Number: GETEC-E3-09-152

Test Site: Gumi College EMC Center

FCC Registration Number: (100749, 443957)

FCC ID.: BEJ52LD550UB

Applicant: LG Electronics Inc.


Rule Part(s)	: FCC Part 15 Subpart B
Equipment Class	: Class B computing device peripheral (JBP)
EUT Type	: LCD TV/Monitor
Type of Authority	: Certification
Model Name	: 52LD550-UB
Trade Name	: LG

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003 / Canadian standard ICES-003

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the vest of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by,

Reviewed by,


Hyounng Seop Kim, Associate Engineer
GUMI College EMC center
Jae-Hoon Jeong, Senior Engineer
GUMI College EMC center



CONTENTS

1. GENERAL INFORMATION	3
2. INTRODUCTION	4
3. PRODUCT INFORMATION	5
3.1 DESCRIPTION OF EUT.....	5
3.2 SUPPORT EQUIPMENT / CABLES USED	6
3.3 MODIFICATION ITEM(S)	7
4. DESCRIPTION OF TESTS.....	8
4.1 TEST CONDITION.....	8
4.2 CONDUCTED EMISSION	9
4.3 RADIATED EMISSION.....	10
5. CONDUCTED EMISSION.....	11
5.1 OPERATING ENVIRONMENT	11
5.2 TEST SET-UP	11
5.3 MEASUREMENT UNCERTAINTY.....	11
5.4 LIMIT	12
5.5 TEST EQUIPMENT USED.....	12
5.6 TEST DATA FOR CONDUCTED EMISSION	12
6. RADIATED EMISSION	23
6.1 OPERATING ENVIRONMENT	23
6.2 TEST SET-UP	23
6.3 MEASUREMENT UNCERTAINTY.....	23
6.4 LIMIT	24
6.5 TEST EQUIPMENT USED.....	24
6.6 TEST DATA FOR RADIATED EMISSION.....	24
7. SAMPLE CALCULATIONS.....	31
7.1 EXAMPLE 1 :	31
7.2 EXAMPLE 2 :	31
8. RECOMMENDATION & CONCLUSION.....	32
 APPENDIX A – ATTESTATION STATEMENT	
APPENDIX B – ID SAMPLE LABEL & LOCATION	
APPENDIX C – BLOCK DIAGRAM	
APPENDIX D – TEST SET-UP PHOTOGRAPHS	
APPENDIX E – EXTERNAL PHOTOGRAPHS	
APPENDIX F – INTERNAL PHOTOGRAPHS	
APPENDIX G – USER’S MANUAL	



Scope: Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and / or unintentional radiators for compliance with technical rules and regulations of the Federal Communications Commission.

1. General Information

Applicant: LG Electronics Inc.

Applicant Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Manufacturer: LG Electronics Inc.

Manufacturer Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Contact Person: Mr. Sang-Wook Lee, Chief research engineer

Tel Number: +82-31-610-9623

- **FCC ID.** BEJ52LD550UB
- **EUT Type** LCD TV/Monitor
- **Model Name** 52LD550-UB
- **Trade Name** LG
- **Serial Number** Prototype
- **Rule Part(s)** FCC Part 15 Subpart B
- **Type of Authority** Certification
- **Test Procedure(s)** ANSI C63.4 (2003) / Canadian standard ICES-003
- **Dates of Test** December 8 ~ 9, 2009
- **Place of Test** **Gumi College EMC Center** (FCC Registration Number: 100749, 443957)
407, Bugok-dong, Gumi-si, Gyeongbuk, Korea.
- **Test Report Number** GETEC-E3-09-152
- **Dates of Issue** December 16, 2009




2. Introduction

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Nose Emissions From Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ASNI C63.4-2003) was used in determining radiated and conducted emissions emanating from **LG Electronics Inc. LCD TV/Monitor (Model Name: 52LD550-UB)**

These measurement tests were conducted at **Gumi College EMC Center**.

The site address is 407, Bugok-dong, Gumi-si, Gyeongbuk, Korea.

This test site is one of the highest point of Gumi 1 college at about 200 km away from Seoul city and 40 km away from Daegu city. It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 (2003)



GUMI COLLEGE EMC CENTER
407, Bugok-dong, Gumi-si,
Gyeongbuk 730-711, Korea.
Tel: +82-54-440-1195
Fax: +82-54-440-1199

Fig 1. The map above shows the Gumi College in vicinity area.



3. Product Information

3.1 Description of EUT

The Equipment under Test (EUT) is the **LG Electronics Inc. LCD TV/Monitor (Model Name: 52LD550-UB) FCC ID.: BEJ52LD550UB**

MODELS		52LD550 (52LD550-UB)	60LD550 (60LD550-UB)
Dimensions (Width x Height x Depth)	With stand	49.8 x 33.5 x 13.0 inches 1266.0 x 851.0 x 330.0 mm	56.7 x 37.9 x 13.6 inches 1441.0 x 963.0 x 345.0 mm
	Without stand	49.8 x 29.3 x 3.8 inches 1266.0 x 745.0 x 96.4 mm	56.7 x 34.5 x 4.3 inches 1441.0 x 877.0 x 109.0 mm
Weight	With stand	59.3 lbs / 26.9 kg	86.6 lbs / 39.3 kg
	Without stand	52.0 lbs / 23.6 kg	78.2 lbs / 35.5 kg
Power requirement		AC100-240V ~ 50/60Hz	
Television System		NTSC-M, ATSC, 64 & 256 QAM	
Program Coverage		VHF 2-13, UHF 14-69, CATV 1-135, DTV 2-69, CADTV 1-135	
External Antenna Impedance		75 ohm	
Environment condition	Operating Temperature	32 ~ 104°F (0 ~ 40°C)	
	Operating Humidity	Less than 80%	
	Storage Temperature	-4 ~ 140°F (-20 ~ 60°C)	
	Storage Humidity	Less than 85%	

Maximum Frequency range : 667 MHz

EUT Type: LCD TV/Monitor

FCC ID.: BEJ52LD550UB



3.2 Support Equipment / Cables used

3.2.1 Used Support Equipment

Description	Manufacturer	Model Name	S/N & FCC ID
PC	Hewlett Packard	D530	S/N: CNG34800PY FCC ID: DoC
Video card	ATI	ARI RV360(9600)	S/N: SN0402017176 FCC ID: DoC
Keyboard	COMPAQ	166516-AD6	S/N: B13BBOR391006D FCC ID: AQ6-23K15
PS2 mouse	LOGITECH	M-S69	S/N: 334684-108 FCC ID: JNZ211443
Joystick	Microsoft	X05-92626	S/N: 9262600296169 FCC ID: DoC
DVD player	LG Electronics Inc	LC-954	S/N: 3850R-Z674K FCC ID: DoC
Headset	GOWOONSORI	GW-500M	S/N: N/A FCC ID: DoC
Printer	Hewlett Packard	970CXI	S/N: MY9B01F1FG FCC ID: DoC
TV signal generator	FLUKE	54200	S/N: 831011 FCC ID: DoC
USB memory stick	SM Electronics	UDD-32M	S/N: N/A FCC ID: DoC
Wireless Ready Dongle	LG Electronics Inc.	-	S/N: N/A FCC ID: -

See "Appendix D – Test Setup Photographs" for actual system test set-up



3.2.2 Used Cable(s)

Cable Name	Condition	Description
Power cable	Connected to the EUT	1.8 m unshielded
Video(RGB) input cable	Connected to the EUT and PC	1.8 m shielded with two ferrite cores
Video(HDMI/DVI) input cable	Connected to the EUT and PC	1.95 m shielded
Audio input cable	Connected to the EUT and PC	1.8 m shielded
RS-232C (Service only)	Connected to the EUT and PC	1.2 m shielded with two ferrite cores
Wireless control cable	Connected to the EUT and Wireless Ready Dongle	0.25 m shielded
Component input cable	Connected to the EUT and DVD Player	2.0 m shielded
Component sound input cable	Connected to the EUT and DVD Player	3.0 m shielded
AV input cable	Connected to the EUT and DVD Player	3.0 m shielded
Headset cable	Connected to the EUT	2.75 m shielded
Antenna cable	Connected to the EUT and TV signal generator	10.0 m shielded
LAN cable	Connected to the EUT and Network	10.0 m unshielded

3.3 Modification Item(s)

- None



4. Description of tests

4.1 Test Condition

The EUT was installed, arranged and operated in a manner that is most representative of equipment as typically used. The measurements were carried out while varying operating modes and cable positions within typically arrangement to determine maximum emission level.

The representative and worst test mode(s) were noted in the test report.

- Test Voltage / Frequency : AC 120 V / 60 Hz

- Test Mode(s)

- . **Monitor mode**

Radiated emission: 1 920 * 1 080 / 60 Hz (RGB: Analog), 1 920 * 1 080 / 60 Hz (HDMI/DVI: Digital)

Conducted emission: 1 920 * 1 080 / 60 Hz (RGB: Analog), 1 920 * 1 080 / 60 Hz (HDMI/DVI: Digital),

1 024 * 768 / 60 Hz (RGB: Analog), 640 * 480 / 60 Hz (RGB: Analog),

◆ Operating test pattern

- . "H" character scrolling mode (Font size: 10)
- . Black background white character
- . Brightness and contrast was adjusted as maximum level
- . 1 kHz sound tone with winamp player
- . Network connecting

- . **USB memory stick play mode**

◆ Operating test pattern

- . Continuous play mode of Picture file and 1 kHz audio file.

"The verification report for TV/AV mode would be issued by LG Electronics Inc."



4.2 Conducted Emission

The Line conducted emission test facility is inside a 4 m × 8 m × 2.5 m shielded enclosure. (FCC Registration No.: 100749)

The EUT was placed on a non-conducting 1.0 m by 1.5 m table, which is 0.8 m in height and 0.4 m away from the vertical wall of the shielded enclosure.

The EUT is powered from the Rohde & Schwarz LISN (ESH2-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH3-Z5). Powers to the LISN are filtered by high-current high insertion loss power line filter.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

The RF output of the LISN was connected to the EMI test receiver (Rohde & Schwarz, ESCS30).

The EMI test receiver was scanned from 150 kHz to 30 MHz with 20 ms sweep time to determine the frequency producing the maximum EME from the EUT. The frequency producing the maximum level was re-examined using Quasi-Peak mode of the EMI test receiver.

The bandwidth of Quasi-peak mode was set to 9 kHz. Each emission was maximized consistent with typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum diagram emission. Excess cable lengths were bundled at center with 30 cm ~ 40 cm.

Each EME reported was calibrated using the R/S signal generator




Fig 2. Impedance of LISN



4.3 Radiated Emission

The measurements were conducted 3 m anechoic chamber (FCC Registration No.: 443957) using broadband antennas to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The technology configuration, mode of operation and turntable azimuth with respect to antenna was note for each frequency found.

The spectrum was scanned from 30 to 1000 MHz, using bicornical log antenna (Schwarzbeck, VULB9160).

Above 1 GHz, horn antenna (Schwarzbeck, BBHA9120D / EMCO 3160) was used.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was re-examined and investigated using EMI test receiver. The detector function was set to CISPR quasi-peak mode average mode and the bandwidth of the receiver was set to 120 kHz or 1MHz depending on the frequency or type of signal.

The EUT, support equipment and interconnecting cables were reconfigured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8 m high non-metallic 1.0 m × 1.5 m table.

The turntable containing the test sample was rotated; the antenna height was varied 1 m to 4 m and stopped at the azimuth or height producing the maximum emission.

Each EME reported was calibrated using the R/S signal generator




Fig 3. Dimensions of test site.



5. Conducted Emission

5.1 Operating Environment

Temperature : 26 °C
Relative Humidity : 42 % R.H.

5.2 Test Set-up

The conducted emission measurements were performed in the shielded room.

The EUT was placed on wooden table, 0.8 m heights above the floor, 0.4 m from the reference ground plane (GRP) wall and 0.8 m from AMN.

AMN is bonded on horizontal reference ground plane.

The ground plane, which was electrically bonded to the shield room, ground system and all power lines entering the shield room, were filtered.

5.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO "Guide to the expression of uncertainty in measurement."

The measurement uncertainty was given with a confidence of 95 %.

Test Items	Uncertainty	Remark
Conducted emission (9 kHz ~ 150 kHz)	± 2.69 dB	Confidence levels of 95 % (k=2)
Conducted emission (150 kHz ~ 30 MHz)	± 4.16 dB	Confidence levels of 95 % (k=2)



5.4 Limit

RFI Conducted	FCC Limit(dB) Class B	
Freq. Range	Quasi-Peak	Average
150 kHz ~ 0.5 MHz	66 ~ 56*	56 ~ 46*
0.5 MHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50
*Limits decreases linearly with the logarithm of frequency.		

5.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESCS30	Rohde & Schwarz	EMI test receiver	839809/003	12. 13. 2009
■ - ESH3-Z5	Rohde & Schwarz	LISN	838979/020	12. 12. 2009
■ - ESH2-Z5	Rohde & Schwarz	LISN	829991/009	12. 12. 2009
■ - ISN T8	TESEQ. GmbH	ISN	24568	10. 16. 2010


5.6 Test data for Conducted Emission

- . Test Date : December 9, 2009
- . Resolution Bandwidth : 9 kHz
- . Frequency Range : 0.15 MHz ~ 30 MHz



◆ Test resolution: 1 920 * 1 080 / 60 Hz (RGB: Analog mode)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.200000	42.6	1000.000	9.000	GND	L1	10.0	20.9	63.5	
0.260000	41.7	1000.000	9.000	GND	L1	10.0	19.5	61.2	
0.325000	41.9	1000.000	9.000	GND	L1	10.0	17.5	59.4	
0.395000	38.4	1000.000	9.000	GND	L1	10.0	19.4	57.8	
0.460000	35.5	1000.000	9.000	GND	L1	10.0	21.1	56.6	
0.525000	32.9	1000.000	9.000	GND	L1	10.0	23.1	56.0	
0.590000	32.7	1000.000	9.000	GND	L1	10.0	23.4	56.0	
22.165000	33.5	1000.000	9.000	GND	L1	10.9	26.5	60.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.170000	40.8	1000.000	9.000	GND	L1	10.0	14.1	54.9	
0.200000	37.9	1000.000	9.000	GND	L1	10.0	15.5	53.4	
0.260000	37.4	1000.000	9.000	GND	L1	10.0	13.8	51.2	
0.330000	37.9	1000.000	9.000	GND	L1	10.0	11.3	49.2	
0.395000	34.2	1000.000	9.000	GND	L1	10.0	13.6	47.8	
0.460000	31.2	1000.000	9.000	GND	L1	10.0	15.4	46.6	
0.590000	28.7	1000.000	9.000	GND	L1	10.0	17.3	46.0	
24.530000	26.9	1000.000	9.000	GND	L1	10.9	23.1	50.0	

< Fig 4. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.195000	43.6	1000.000	9.000	GND	N	10.0	20.1	63.7	
0.260000	42.6	1000.000	9.000	GND	N	10.0	18.6	61.2	
0.330000	38.8	1000.000	9.000	GND	N	10.0	20.5	59.3	
0.420000	35.5	1000.000	9.000	GND	N	10.0	21.9	57.3	
0.460000	34.4	1000.000	9.000	GND	N	10.0	22.2	56.6	
0.525000	32.6	1000.000	9.000	GND	N	10.0	23.4	56.0	
21.570000	32.6	1000.000	9.000	GND	N	10.8	27.4	60.0	
24.740000	32.2	1000.000	9.000	GND	N	10.8	27.8	60.0	

Final Measurement Detector 2


Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.170000	40.3	1000.000	9.000	GND	N	10.0	14.6	54.9	
0.195000	39.4	1000.000	9.000	GND	N	10.0	14.3	53.7	
0.260000	38.6	1000.000	9.000	GND	N	10.0	12.6	51.2	
0.330000	34.1	1000.000	9.000	GND	N	10.0	15.1	49.2	
0.425000	32.1	1000.000	9.000	GND	N	10.0	15.2	47.2	
0.525000	27.6	1000.000	9.000	GND	N	10.0	18.4	46.0	
0.590000	27.8	1000.000	9.000	GND	N	10.0	18.2	46.0	
24.550000	30.1	1000.000	9.000	GND	N	10.8	19.9	50.0	

< Fig 5. Conducted emission result (Neutral line)>



◆ Test resolution: 1 920 * 1 080 / 60 Hz (HDMI/DVI: Digital mode)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.200000	42.4	1000.000	9.000	GND	L1	10.0	21.1	63.5	
0.260000	41.6	1000.000	9.000	GND	L1	10.0	19.6	61.2	
0.330000	40.7	1000.000	9.000	GND	L1	10.0	18.6	59.3	
0.390000	36.1	1000.000	9.000	GND	L1	10.0	21.8	57.9	
0.460000	35.0	1000.000	9.000	GND	L1	10.0	21.6	56.6	
0.525000	32.9	1000.000	9.000	GND	L1	10.0	23.1	56.0	
23.070000	32.0	1000.000	9.000	GND	L1	10.9	28.0	60.0	
24.060000	32.7	1000.000	9.000	GND	L1	10.9	27.3	60.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.175000	36.4	1000.000	9.000	GND	L1	10.0	18.2	54.6	
0.195000	39.0	1000.000	9.000	GND	L1	10.0	14.7	53.7	
0.260000	37.1	1000.000	9.000	GND	L1	10.0	14.1	51.2	
0.330000	37.2	1000.000	9.000	GND	L1	10.0	12.0	49.2	
0.390000	33.0	1000.000	9.000	GND	L1	10.0	14.9	47.9	
0.460000	30.5	1000.000	9.000	GND	L1	10.0	16.1	46.6	
0.525000	27.8	1000.000	9.000	GND	L1	10.0	18.2	46.0	
0.590000	27.4	1000.000	9.000	GND	L1	10.0	18.6	46.0	

< Fig 6. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.200000	41.8	1000.000	9.000	GND	N	10.0	21.7	63.5	
0.265000	42.0	1000.000	9.000	GND	N	10.0	19.1	61.1	
0.330000	38.5	1000.000	9.000	GND	N	10.0	20.9	59.3	
0.460000	33.7	1000.000	9.000	GND	N	10.0	22.9	56.6	
0.525000	32.5	1000.000	9.000	GND	N	10.0	23.5	56.0	
0.590000	30.1	1000.000	9.000	GND	N	10.0	25.9	56.0	
23.645000	31.6	1000.000	9.000	GND	N	10.8	28.4	60.0	
24.440000	31.9	1000.000	9.000	GND	N	10.8	28.1	60.0	

Final Measurement Detector 2


Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.175000	36.0	1000.000	9.000	GND	N	10.0	18.6	54.6	
0.195000	38.9	1000.000	9.000	GND	N	10.0	14.8	53.7	
0.260000	38.8	1000.000	9.000	GND	N	10.0	12.4	51.2	
0.330000	33.7	1000.000	9.000	GND	N	10.0	15.5	49.2	
0.395000	30.9	1000.000	9.000	GND	N	10.0	16.9	47.8	
0.525000	27.3	1000.000	9.000	GND	N	10.0	18.7	46.0	
0.590000	26.4	1000.000	9.000	GND	N	10.0	19.6	46.0	
27.000000	28.1	1000.000	9.000	GND	N	10.8	21.9	50.0	

< Fig 7. Conducted emission result (Neutral line)>



◆ Test resolution: 1 024 * 768 / 60 Hz (RGB: Analog mode)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.200000	42.6	1000.000	9.000	GND	L1	10.0	20.9	63.5	
0.260000	41.7	1000.000	9.000	GND	L1	10.0	19.5	61.2	
0.330000	41.5	1000.000	9.000	GND	L1	10.0	17.8	59.3	
0.395000	38.5	1000.000	9.000	GND	L1	10.0	19.3	57.8	
0.460000	35.8	1000.000	9.000	GND	L1	10.0	20.8	56.6	
0.525000	33.3	1000.000	9.000	GND	L1	10.0	22.7	56.0	
0.590000	32.8	1000.000	9.000	GND	L1	10.0	23.2	56.0	
17.255000	33.7	1000.000	9.000	GND	L1	10.7	26.3	60.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.170000	40.7	1000.000	9.000	GND	L1	10.0	14.2	54.9	
0.200000	37.8	1000.000	9.000	GND	L1	10.0	15.6	53.4	
0.260000	37.4	1000.000	9.000	GND	L1	10.0	13.8	51.2	
0.325000	38.3	1000.000	9.000	GND	L1	10.0	11.1	49.4	
0.395000	34.3	1000.000	9.000	GND	L1	10.0	13.5	47.8	
0.460000	31.4	1000.000	9.000	GND	L1	10.0	15.2	46.6	
0.525000	28.2	1000.000	9.000	GND	L1	10.0	17.8	46.0	
0.590000	28.9	1000.000	9.000	GND	L1	10.0	17.1	46.0	

< Fig 8. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.200000	42.0	1000.000	9.000	GND	N	10.0	21.5	63.5	
0.260000	42.3	1000.000	9.000	GND	N	10.0	18.9	61.2	
0.330000	38.3	1000.000	9.000	GND	N	10.0	21.0	59.3	
0.395000	36.3	1000.000	9.000	GND	N	10.0	21.5	57.8	
0.460000	34.4	1000.000	9.000	GND	N	10.0	22.2	56.6	
0.525000	32.6	1000.000	9.000	GND	N	10.0	23.4	56.0	
0.590000	32.3	1000.000	9.000	GND	N	10.0	23.7	56.0	
16.930000	35.5	1000.000	9.000	GND	N	10.6	24.5	60.0	

Final Measurement Detector 2


Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.170000	40.4	1000.000	9.000	GND	N	10.0	14.5	54.9	
0.195000	39.1	1000.000	9.000	GND	N	10.0	14.6	53.7	
0.260000	38.3	1000.000	9.000	GND	N	10.0	12.9	51.2	
0.325000	33.5	1000.000	9.000	GND	N	10.0	15.9	49.4	
0.425000	32.1	1000.000	9.000	GND	N	10.0	15.2	47.2	
0.460000	28.4	1000.000	9.000	GND	N	10.0	18.2	46.6	
0.590000	27.9	1000.000	9.000	GND	N	10.0	18.1	46.0	
17.125000	30.5	1000.000	9.000	GND	N	10.6	19.5	50.0	

< Fig 9. Conducted emission result (Neutral line)>



◆ Test resolution: 640 * 480 / 60 Hz (RGB: Analog mode)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.200000	42.1	1000.000	9.000	GND	L1	10.0	21.4	63.5	
0.260000	41.3	1000.000	9.000	GND	L1	10.0	19.9	61.2	
0.325000	41.9	1000.000	9.000	GND	L1	10.0	17.5	59.4	
0.390000	37.0	1000.000	9.000	GND	L1	10.0	20.9	57.9	
0.460000	35.4	1000.000	9.000	GND	L1	10.0	21.2	56.6	
0.525000	32.4	1000.000	9.000	GND	L1	10.0	23.6	56.0	
0.590000	32.9	1000.000	9.000	GND	L1	10.0	23.2	56.0	
17.190000	35.0	1000.000	9.000	GND	L1	10.7	25.0	60.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.170000	41.1	1000.000	9.000	GND	L1	10.0	13.8	54.9	
0.200000	37.2	1000.000	9.000	GND	L1	10.0	16.2	53.4	
0.260000	37.1	1000.000	9.000	GND	L1	10.0	14.1	51.2	
0.325000	38.4	1000.000	9.000	GND	L1	10.0	11.0	49.4	
0.390000	33.9	1000.000	9.000	GND	L1	10.0	14.0	47.9	
0.460000	31.1	1000.000	9.000	GND	L1	10.0	15.5	46.6	
0.525000	27.8	1000.000	9.000	GND	L1	10.0	18.2	46.0	
0.590000	29.0	1000.000	9.000	GND	L1	10.0	17.0	46.0	

< Fig 10. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.200000	41.8	1000.000	9.000	GND	N	10.0	21.7	63.5	
0.265000	40.6	1000.000	9.000	GND	N	10.0	20.5	61.1	
0.330000	38.0	1000.000	9.000	GND	N	10.0	21.3	59.3	
0.395000	36.0	1000.000	9.000	GND	N	10.0	21.8	57.8	
0.460000	34.2	1000.000	9.000	GND	N	10.0	22.4	56.6	
0.525000	32.3	1000.000	9.000	GND	N	10.0	23.7	56.0	
0.590000	32.5	1000.000	9.000	GND	N	10.0	23.5	56.0	
17.170000	34.3	1000.000	9.000	GND	N	10.6	25.7	60.0	

Final Measurement Detector 2


Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.170000	40.5	1000.000	9.000	GND	N	10.0	14.4	54.9	
0.195000	38.9	1000.000	9.000	GND	N	10.0	14.8	53.7	
0.255000	38.1	1000.000	9.000	GND	N	10.0	13.2	51.3	
0.325000	33.5	1000.000	9.000	GND	N	10.0	15.9	49.4	
0.425000	32.1	1000.000	9.000	GND	N	10.0	15.2	47.2	
0.460000	27.9	1000.000	9.000	GND	N	10.0	18.7	46.6	
0.525000	27.3	1000.000	9.000	GND	N	10.0	18.7	46.0	
0.590000	28.0	1000.000	9.000	GND	N	10.0	18.0	46.0	

< Fig 11. Conducted emission result (Neutral line)>



◆ Test resolution: USB memory stick play mode

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.195000	44.1	1000.000	9.000	GND	L1	10.0	19.6	63.7	
0.260000	42.0	1000.000	9.000	GND	L1	10.0	19.2	61.2	
0.325000	40.6	1000.000	9.000	GND	L1	10.0	18.8	59.4	
0.395000	37.8	1000.000	9.000	GND	L1	10.0	20.0	57.8	
0.525000	32.9	1000.000	9.000	GND	L1	10.0	23.1	56.0	
0.590000	31.8	1000.000	9.000	GND	L1	10.0	24.2	56.0	
20.460000	28.8	1000.000	9.000	GND	L1	10.8	31.2	60.0	
24.965000	30.7	1000.000	9.000	GND	L1	10.9	29.3	60.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.170000	36.2	1000.000	9.000	GND	L1	10.0	18.7	54.9	
0.195000	39.0	1000.000	9.000	GND	L1	10.0	14.7	53.7	
0.260000	37.3	1000.000	9.000	GND	L1	10.0	14.0	51.2	
0.325000	37.6	1000.000	9.000	GND	L1	10.0	11.8	49.4	
0.395000	33.3	1000.000	9.000	GND	L1	10.0	14.5	47.8	
0.480000	24.0	1000.000	9.000	GND	L1	10.0	22.3	46.3	
0.525000	27.8	1000.000	9.000	GND	L1	10.0	18.2	46.0	
0.590000	27.5	1000.000	9.000	GND	L1	10.0	18.5	46.0	

< Fig 12. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.195000	43.3	1000.000	9.000	GND	N	10.0	20.4	63.7	
0.260000	43.1	1000.000	9.000	GND	N	10.0	18.1	61.2	
0.325000	36.3	1000.000	9.000	GND	N	10.0	23.1	59.4	
0.395000	35.8	1000.000	9.000	GND	N	10.0	22.0	57.8	
0.465000	31.4	1000.000	9.000	GND	N	10.0	25.2	56.6	
0.595000	29.6	1000.000	9.000	GND	N	10.0	26.4	56.0	
23.725000	31.9	1000.000	9.000	GND	N	10.8	28.1	60.0	
23.955000	27.2	1000.000	9.000	GND	N	10.8	32.8	60.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.170000	35.9	1000.000	9.000	GND	N	10.0	19.0	54.9	
0.195000	39.0	1000.000	9.000	GND	N	10.0	14.7	53.7	
0.265000	37.3	1000.000	9.000	GND	N	10.0	13.7	51.0	
0.325000	33.1	1000.000	9.000	GND	N	10.0	16.3	49.4	
0.395000	31.0	1000.000	9.000	GND	N	10.0	16.8	47.8	
0.475000	21.3	1000.000	9.000	GND	N	10.0	25.1	46.4	
0.525000	27.4	1000.000	9.000	GND	N	10.0	18.6	46.0	
0.590000	26.2	1000.000	9.000	GND	N	10.0	19.8	46.0	

< Fig 13. Conducted emission result (Neutral line)>



6. Radiated Emission

6.1 Operating Environment

Temperature : 21 °C
Relative Humidity : 48 % R.H.

6.2 Test Set-up

A preliminary and final measurement was at 3 m anechoic chamber.

The EUT was placed on a non-conductive turntable approximately 0.8 m above the ground plane.

The turntable with EUT was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels.

This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

6.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement”.

The measurement uncertainty was given with a confidence of 95 %.

Test Items	Uncertainty	Remark
Radiated emission (30 MHz ~ 300 MHz, 3 m, Vertical)	± 3.54 dB	Confidence levels of 95 % (k=2)
Radiated emission (30 MHz ~ 300 MHz, 3 m, Horizontal)	± 3.49 dB	Confidence levels of 95 % (k=2)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Vertical)	± 3.85 dB	Confidence levels of 95 % (k=2)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Horizontal)	± 3.76 dB	Confidence levels of 95 % (k=2)
Radiated emission (30 MHz ~ 300 MHz, 10 m, Vertical)	± 3.21 dB	Confidence levels of 95 % (k=2)
Radiated emission (30 MHz ~ 300 MHz, 10 m, Horizontal)	± 3.32 dB	Confidence levels of 95 % (k=2)
Radiated emission (300 MHz ~ 1 000 MHz, 10 m, Vertical)	± 3.77 dB	Confidence levels of 95 % (k=2)
Radiated emission (300 MHz ~ 1 000 MHz, 10 m, Horizontal)	± 3.84 dB	Confidence levels of 95 % (k=2)



6.4 Limit

Frequency (MHz)	FCC Limit @ 3 m. dB μ V/m	CISPR Limit @ 10 m. dB μ V/m
30 ~ 88	40.0	30.0
88 ~ 216	43.5	30.0
216 ~ 230	46.0	30.0
230 ~ 960	46.0	37.0
960 ~ 1 000	54.0	37.0
> 1 000	54.0	No Specified limit

6.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESI	Rohde & Schwarz	EMI test receiver	830482/010	12. 14. 2009
■ - VULB9160	Schwarzbeck	Broadband Test Antenna	3193	12. 11. 2009
■ - BBHA9120D	Schwarzbeck	Horn ANT	207	12. 26. 2009
■ - MCU066	maturo GmbH	MCU066	1390306	N/A
■ - TT2.5SI	maturo GmbH	Turntable	1390307	N/A
■ - AM 4.0	maturo GmbH	Antenna Mast	1390308	N/A
■ - AFS 44 00101800-25-10P-44	MITEQ	Preamplifier	1258943	11. 12. 2010


6.6 Test data for Radiated Emission

- Test Date : December 8, 2009
- Resolution Bandwidth : 120 kHz/1 MHz
- Frequency Range : 30 MHz ~ 5 000 MHz
- Measurement Distance : 3 m
- Note : The highest frequency of the internal source of the EUT is between 500 MHz and 1000 MHz (667 MHz). The measurement was made up to 5 000 MHz



- ◆ Operating Condition: 1 920 * 1 080 / 60 Hz (RGB: Analog mode)
Detector mode: Quasi- peak detector mode

Frequency (MHz)	Measurement Level				Limit (dBμ V/m)	Margin (dB)	Positioning System		
	Reading	Antenna	Cable	Test Result			Pol.	Height	Angle
	Value(dBμ V)	Factor(dB/m)	Loss(dB)	(dBμ V/m)			(H/V)	(cm)	(°)
33.65	19.60	10.92	1.96	32.48	40.00	7.52	V	100	90
142.61	20.99	12.64	3.60	37.23	43.50	6.27	H	214	0
245.23	24.56	11.00	4.89	40.45	46.00	5.55	V	236	181
269.75	24.99	11.79	5.21	41.99	46.00	4.01	V	231	183
294.18	19.18	12.55	5.54	37.27	46.00	8.73	V	100	177
524.81	12.32	17.31	7.07	36.70	46.00	9.30	V	110	182
662.35	10.50	19.60	7.77	37.87	46.00	8.13	V	104	178
763.92	4.78	21.49	8.39	34.66	46.00	11.34	V	100	180
808.97	10.35	21.72	8.64	40.71	46.00	5.29	V	100	180




< Fig 14. Radiated emission result (30 MHz ~ 1 000 MHz)>



- ◆ Operating Condition: 1 920 * 1 080 / 60 Hz (HDMI/DVI: Digital mode)
Detector mode: Quasi- peak detector mode

Frequency (MHz)	Measurement Level				Limit (dBμ V/m)	Margin (dB)	Positioning System		
	Reading	Antenna	Cable	Test Result			Pol.	Height	Angle
	Value(dBμ V)	Factor(dB/m)	Loss(dB)	(dBμ V/m)			(H/V)	(cm)	(°)
33.95	17.85	10.91	1.96	30.72	40.00	9.28	V	100	90
112.50	13.29	10.38	3.23	26.90	43.50	16.60	H	218	181
147.19	15.29	12.64	3.66	31.59	43.50	11.91	V	105	166
216.00	24.07	9.93	4.50	38.50	46.00	7.50	V	100	90
302.42	23.08	12.78	5.69	41.55	46.00	4.45	V	132	171
563.55	5.14	18.27	7.21	30.62	46.00	15.38	H	100	90
702.00	11.56	20.01	7.97	39.54	46.00	6.46	V	100	270
808.94	4.35	21.72	8.64	34.71	46.00	11.29	V	112	180




< Fig 15. Radiated emission result (30 MHz ~ 1 000 MHz)>



- ◆ Operating Condition: USB memory stick play mode
Detector mode: Quasi- peak detector mode

Frequency (MHz)	Measurement Level				Limit (dBμ V/m)	Margin (dB)	Positioning System		
	Reading	Antenna	Cable	Test Result			Pol.	Height	Angle
	Value(dBμ V)	Factor(dB/m)	Loss(dB)	(dBμ V/m)			(H/V)	(cm)	(°)
33.21	16.52	10.93	1.95	29.40	40.00	10.60	V	100	90
96.77	17.39	8.64	3.02	29.05	43.50	14.45	H	211	0
147.05	15.18	12.64	3.66	31.48	43.50	12.02	V	100	181
224.16	21.70	10.23	4.61	36.54	46.00	9.46	V	191	169
292.66	16.63	12.50	5.52	34.65	46.00	11.35	V	100	181
487.01	0.97	16.61	7.06	24.64	46.00	21.36	V	215	180
599.20	10.25	19.21	7.41	36.87	46.00	9.13	V	224	185
645.78	9.88	19.47	7.68	37.03	46.00	8.97	H	104	134
816.12	4.57	21.80	8.68	35.05	46.00	10.95	V	100	0




< Fig 16. Radiated emission result (30 MHz ~ 1 000 MHz)>



- ◆ Operating Condition: 1 920 * 1 080 / 60 Hz (RGB: Analog mode)
Detector mode: Peak detector mode / Average detector mode

FCC_ESIB_Preamplifier_RE with Scans



Final Result 1

Frequency (MHz)	MaxPeak-MaxHold (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1049.600000	59.9	100.0	V	270.0	-15.8	14.1	74.0	
1051.600000	60.6	100.0	V	270.0	-15.8	13.4	74.0	
1053.600000	59.7	100.0	V	270.0	-15.8	14.3	74.0	
1056.000000	57.3	100.0	V	270.0	-15.8	16.7	74.0	
1339.200000	59.0	200.0	H	180.0	-14.5	15.0	74.0	
1540.800000	60.8	100.0	H	180.0	-14.1	13.2	74.0	
1875.600000	58.0	100.0	V	180.0	-13.0	16.0	74.0	
2060.400000	56.5	200.0	H	180.0	-12.3	17.5	74.0	
2073.200000	57.4	150.0	H	180.0	-12.2	16.6	74.0	
2592.400000	57.1	150.0	H	180.0	-10.0	16.9	74.0	

Final Result 2

Frequency (MHz)	Average-MaxHold (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1049.600000	43.0	100.0	V	270.0	-15.8	11.0	54.0	
1484.800000	45.3	100.0	V	180.0	-14.5	8.7	54.0	
1539.200000	49.1	150.0	H	180.0	-14.2	4.9	54.0	
1633.600000	47.3	200.0	V	180.0	-13.7	6.7	54.0	
1930.400000	44.7	100.0	V	180.0	-12.9	9.3	54.0	
2227.600000	42.8	200.0	V	180.0	-11.5	11.2	54.0	
4212.000000	43.2	150.0	V	270.0	-3.3	10.8	54.0	
4603.600000	42.4	100.0	V	180.0	-3.2	11.6	54.0	
4678.000000	43.7	150.0	V	180.0	-3.1	10.3	54.0	


< Fig 17. Radiated emission result (1 000 MHz ~ 5 000 MHz)>



◆ Operating Condition: 1 920 * 1 080 / 60 Hz (HDMI/DVI: Digital mode)

Detector mode: Peak detector mode / Average detector mode

FCC_ESIB_Preamplifier with Scans



Final Result 1

Frequency (MHz)	MaxPeak-MaxHold (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1186.400000	57.9	100.0	V	180.0	-15.3	16.1	74.0	
1282.400000	57.4	150.0	V	180.0	-14.6	16.6	74.0	
1484.000000	59.5	150.0	V	180.0	-14.5	14.5	74.0	
1539.600000	56.6	150.0	H	180.0	-14.2	17.4	74.0	
1558.400000	55.7	100.0	H	180.0	-14.0	18.3	74.0	
1631.600000	56.0	100.0	H	180.0	-13.7	18.0	74.0	
1792.800000	57.9	100.0	V	180.0	-13.1	16.1	74.0	
1795.200000	58.8	100.0	V	180.0	-13.1	15.2	74.0	
1854.000000	59.2	100.0	H	180.0	-13.1	14.8	74.0	

Final Result 2


Frequency (MHz)	Average-MaxHold (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1186.800000	48.9	100.0	V	180.0	-15.3	5.1	54.0	
1282.800000	47.1	150.0	V	180.0	-14.6	6.9	54.0	
1483.600000	49.4	100.0	V	0.0	-14.5	4.6	54.0	
1539.200000	47.3	150.0	H	180.0	-14.2	6.7	54.0	
1557.600000	47.6	100.0	V	180.0	-14.0	6.4	54.0	
1632.000000	47.5	100.0	H	270.0	-13.7	6.5	54.0	
1706.000000	47.9	150.0	H	180.0	-13.6	6.1	54.0	
2400.400000	47.9	100.0	V	0.0	-10.8	6.1	54.0	
4104.000000	46.7	150.0	V	180.0	-3.2	7.3	54.0	

< Fig 18. Radiated emission result (1 000 MHz ~ 5 000 MHz)>



- ◆ Operating Condition: USB memory stick play mode
Detector mode: Peak detector mode / Average detector mode

FCC_ESIB_Preamplifier_RE with Scans



Final Result 1

Frequency (MHz)	MaxPeak-MaxHold (dBµV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
1176.400000	57.4	100.0	H	180.0	-15.3	16.6	74.0	
1263.200000	54.6	150.0	V	180.0	-14.8	19.4	74.0	
1268.000000	55.7	150.0	V	180.0	-14.7	18.3	74.0	
1278.400000	56.2	150.0	V	180.0	-14.6	17.8	74.0	
1335.600000	56.0	150.0	V	180.0	-14.5	18.0	74.0	
1534.800000	59.1	200.0	H	180.0	-14.2	14.9	74.0	
1538.800000	62.8	100.0	H	180.0	-14.2	11.2	74.0	

Final Result 2

Frequency (MHz)	Average-MaxHold (dBµV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
1026.000000	41.1	150.0	V	180.0	-16.0	12.9	54.0	
1534.800000	47.5	200.0	H	180.0	-14.2	6.5	54.0	
1536.000000	44.2	200.0	H	180.0	-14.2	9.8	54.0	
2052.000000	42.6	100.0	V	180.0	-12.3	11.4	54.0	
2565.200000	42.0	200.0	H	180.0	-10.1	12.0	54.0	
4104.000000	39.5	150.0	V	180.0	-3.2	14.5	54.0	
4608.000000	39.5	100.0	H	180.0	-3.2	14.5	54.0	
4677.600000	43.2	150.0	V	180.0	-3.1	10.8	54.0	

< Fig 19. Radiated emission result (1 000 MHz ~ 5 000 MHz)>



7. Sample Calculations

$$\begin{aligned} \text{dB}\mu\text{V} &= 20 \text{ Log}_{10}(\mu\text{V}/\text{m}) \\ \text{dB}\mu\text{V} &= \text{dBm} + 107 \\ \mu\text{V} &= 10^{(\text{dB}\mu\text{V}/20)} \end{aligned}$$

7.1 Example 1 :

■ 20.3 MHz

Class B Limit	= 250 μV = 48 dB μV
Reading	= 39.2 dB μV
$10^{(39.2\text{dB}\mu\text{V}/20)}$	= 91.2 μV
Margin	= 48 dB μV - 39.2 dB μV = 8.8 dB

7.2 Example 2 :

■ 66.7 MHz

Class B Limit	= 100 $\mu\text{V}/\text{m}$ = 40.0 dB $\mu\text{V}/\text{m}$
Reading	= 31.0 dB μV
Antenna Factor + Cable Loss = 5.8 dB	
Total	= 36.8 dB $\mu\text{V}/\text{m}$
Margin	= 40.0 dB $\mu\text{V}/\text{m}$ - 36.8 dB $\mu\text{V}/\text{m}$ = 3.2 dB



8. Recommendation & Conclusion

The data collected shows that the **LG Electronics Inc. LCD TV/Monitor (Model Name: 52LD550-UB)** was complies with §15.107 and 15.109 of the FCC Rules.