

EMC TEST REPORT

Test item : LED TV Monitor
Model No. : 55LN5400-UA
Order No. : 1211-02718
Date of receipt : 2012-11-30
Test duration : 2012-12-03 ~ 2012-12-04
Use of report : FCC CoC Marking
Date of Issue : 2012-12-10

Applicant : LG Electronics Inc.

19-1, Cheongho-ri, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea

Test laboratory : Digital EMC Co., Ltd.

683-3, Yubang-Dong, Cheoin-Gu, Yongin-Si, Gyeonggi-Do, 449-080, Korea

Test specification : ANSI C 63.4:2003
FCC Part 15 Subpart B
(Type of Device : Class B Personal Computers
and Peripherals (JBP))

Test environment : Temperature : (19 ~ 23) °C,
Humidity : (41 ~ 47) % R.H.

Test result : ☒ Comply ☐ Not Comply

The test results presented in this test report are limited only to the sample supplied by applicant and
the use of this test report is inhibited other than its purpose.

This test report shall not be reproduced except in full, without the written approval of DIGITAL EMC CO., LTD.

Tested by:



Engineer
KyungMin Jeong

Reviewed by:



Manager
MyungJin Song

PRESIDENT OF DIGITAL EMC CO., LTD.

CONTENTS

1. General Remarks	3
2. Test Laboratory	3
3. General Information of EUT	4
4. Test Summary	5
4.1 Applied standards and test results	5
4.2 Test environment and conditions	5
4.3 Test result Summary	5
5. Test Set-up and operation mode	6
5.1 Principle of Configuration Selection	6
5.2 Test Operation Mode	6
5.3 Support Equipment Used	6
6. Test Results : Emission	7
6.1 Conducted Disturbance	7
6.2 Radiated Disturbance	12
Appendix 1	26
List of Test and Measurement Instruments	26

1. General Remarks

This report contains the result of tests performed by:

DIGITAL EMC CO., LTD.

Address : 683-3, Yubang-Dong, Cheoin-Gu, Yongin-Si, Gyeonggi-Do, 449-080, Korea

<http://www.digitalemcc.com>

Tel: +82-31-321-2664 Fax: +82-31-321-1664

2. Test Laboratory

Digital EMC Co., Ltd. has been accredited / filed / authorized by the agencies listed in the following table;

Certificate	Nation	Agency	Code	Mark
Accreditation	Korea	KOLAS	393	ISO/IEC 17025
Site Filing	USA	FCC	101842 678747	Test Facility list & NSA Data
	Canada	IC	5740A-1 5740A-2	Test Facility list & NSA Data
	Japan	VCCI	C-1427 R-1364, R-3385 T-1442, G-338	Test Facility list & NSA Data
Certification	Korea	KC	KR0034	Test Facility list & NSA Data
	Germany	TUV	ROK1124C	ISO/IEC 17025

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the "General requirements for the competent of calibration and testing laboratory".

3. General Information of EUT

Model No.	55LN5400-UA
EUT Type	LED TV Monitor
Serial No	NONE
FCC ID	BEJ55LN5400UA
Type of Sample Tested	Pre-Production
High Frequency	Max 800 MHz
Rating	AC 100-240 V~ 50/60 Hz, 1.5 A
Supplied Power for Test	AC 120 V, 60 Hz
Applicant	LG Electronics Inc. 19-1, Cheongho-ri, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea
Manufacturer	LG Electronics Inc. 19-1, Cheongho-ri, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea

Component supported mode

Resolution	Horizontal Frequency (KHz)	Vertical Frequency (Hz)
720 x 480i	31.47	59.94
	31.50	60.00
1280 x 720p	44.96	59.94
	45.00	60.00
1920 x 1080i	33.72	59.94
	33.75	60.00
1920 x 1080p	26.97	23.976
	27.00	24.00
	33.71	29.97
	33.75	30.00
	67.432	59.94
	67.50	60.00

4. Test Summary

4.1 Applied standards and test results

Test Items	Applied Standards	Results
Conducted Disturbance	ANSI C63.4:2003	C
Radiated Disturbance	ANSI C63.4:2003	C
C=Comply N/C=Not Comply N/T=Not Tested N/A=Not Applicable		

The data in this test report are traceable to the national or international standards.

4.2 Test environment and conditions

Test Items	Test date (MM-DD)	Temp (°C)	Humidity (% R.H.)
Conducted Disturbance	12-03	23	41
Radiated Disturbance	12-04	19	47

4.3 Test result Summary

(1) Conducted Emission (HDMI MODE)

Frequency [MHz]	Phase	Result [dB μ V]	Detector	Limit [dB μ V]	Margin [dB]
13.558	LI	44.8	Quasi-Peak	50.0	5.2

(2) Radiated Emission (HDMI MODE)

Frequency [MHz]	Pol.	Result [dB(μ V/m)]	Detector	Limit [dB(μ V/m)]	Margin [dB]
1798.514	H	43.6	Average	54.0	10.4

5. Test Set-up and operation mode

5.1 Principle of Configuration Selection

Emission : The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

5.2 Test Operation Mode

- HDMI MODE – Resolution : 1920x1080 Resolution (Worst Case)
- USB MODE

5.3 Support Equipment Used

Unit	Model No.	Serial No.	Manufacturer	CABLE				Backshell	FCC ID
				Connect type	Length (m)	ferrite core	shield		
PC	VOSTRO2 20	G3RZKBX	DELL INC.	POWER	1.8	Not use	Non-shield	Plastic	DOC
				HDMI	1.8	Not use	Shield		
				USB	1.8	Not use	Shield		
				USB	1.8	Not use	Shield		
				USB	1.5	Not use	Shield		
				LAN	1.6	Not use	Non-shield		
KEYBOARD	SKG-3000UB	TAKSB601236L	MONITEREY INTERNATIONAL CORP	USB	1.8	Not use	Shield	Plastic	DOC
MOUSE	1484	352700021373	MICROSOFT CORPORATION	USB	1.8	Not use	Shield	Plastic	DOC
CD/DVD PLAYER	DVP-NS92V	2001499	SONY EMCS.	POWER COMPONENT	1.8 1.6	Not use Not use	Non-shield Non-shield	Plastic	VER
USB MEMORY	Sandisk Cruzer Z37 4G	N/A	Sandisk	USB	-	-	-	-	DOC
Printer	SRP-770	SRP770080600 35	Bixolon	USB POWER	1.6 1.5	Not use Not use	Shield Non-shield	Plastic	DOC
Headset	COV903	N/A	Cosy	STEREO	1.5	Not use	Non-shield	Plastic	DOC

6. Test Results : Emission

6.1 Conducted Disturbance

6.1.1 Measurement Procedure

In the range of 0.15 MHz to 30 MHz, the conducted disturbance was measured and set-up was made accordance with **ANSI C63.4**.

If the EUT is table top equipment, it was placed on a wooden table with a height of 0.8 m above the reference ground plane and 0.4 m from the conducting wall of the shielded room.

Also if the EUT is floor-standing equipment, it was placed on a non-conducted support with a height up to 0.15 m above the reference ground plane.

Connect the EUT's power source lines to the appropriate power mains / peripherals through the LISN. All the other peripherals are connected to the 2nd LISN, if any.

Unused measuring port of the LISN was resistively terminated by 50 ohm terminator.

The measuring port of the LISN for EUT was connected to spectrum analyzer.

Using conducted emission test software, the emissions were scanned with peak detector mode.

After scanning over the frequency range, suspected emissions were selected to perform final measurement. When performing final measurement, the receiver was used which has Quasi-Peak detector and Average detector.

By varying the configuration of the test sample and the cable routing it was attempted to maximize the emission.

For further description of the configuration refer to the picture of the test set-up.

6.1.2 Limit for Conducted Disturbance

(1) Conducted disturbance at mains ports.

Frequency range (MHz)	Limits dB(μV)			
	Quasi-peak		Average	
	Class A	Class B	Class A	Class B
0.15 to 0.50	79	66 to 56	66	56 to 46
0.50 to 5	73	56	60	46
5 to 30		60		50
Note 1 The lower limit shall apply at the transition frequencies.				
Note 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

Note) 1. Emission Level = Reading Value + Correction Factor.

2. Correction Factor = Cable Loss + Insertion Loss of LISN

3. Margin = Limit - Emission level

Test Result

< HDMI MODE >



Results of Conducted Emission



Digital EMC
Date : 2012-12-03

Model No. : 55LN5400-UA
Type :
Serial No. :
Test Condition : HDMI

Reference No. :
Power Supply : 120 V 60 Hz
Temp/Humi. : 23 °C 41 % R.H.
Operator :

Memo :

LIMIT : CISPR22_B QP
CISPR22_B AV



Results of Conducted Emission

Digital EMC
Date : 2012-12-03

Model No. : 55LN5400-UA
Type :
Serial No. :
Test Condition : HDMI

Reference No. :
Power Supply : 120 V 60 Hz
Temp/Humi. : 23°C 41 % R.H.
Operator :

Memo :

LIMIT : CISPR22_B QP
CISPR22_B AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.15000	53.0	36.5	0.2	53.2	36.7	66.0	56.0	12.8	19.3	N
2	0.19903	44.2	33.2	0.2	44.4	33.4	63.7	53.7	19.3	20.3	N
3	0.45021	38.9	29.3	0.2	39.1	29.5	56.9	46.9	17.8	17.4	N
4	0.54550	39.2	27.9	0.2	39.4	28.1	56.0	46.0	16.6	17.9	N
5	11.73800	37.5	30.9	0.7	38.2	31.6	60.0	50.0	21.8	18.4	N
6	13.55700	45.4	43.7	0.7	46.1	44.4	60.0	50.0	13.9	5.6	N
7	0.15018	52.6	36.3	0.2	52.8	36.5	66.0	56.0	13.2	19.5	L1
8	0.19943	42.4	31.4	0.2	42.6	31.6	63.6	53.6	21.0	22.0	L1
9	0.51746	36.6	28.1	0.2	36.8	28.3	56.0	46.0	19.2	17.7	L1
10	13.55800	45.5	44.1	0.7	46.2	44.8	60.0	50.0	13.8	5.2	L1

< USB MODE >



Results of Conducted Emission



Digital EMC
Date : 2012-12-03

Model No. : 55LN5400-UA
Type :
Serial No. :
Test Condition : USB

Reference No. :
Power Supply : 120 V 60 Hz
Temp/Humi. : 23 °C 41 % R.H.
Operator :

Memo :

LIMIT : CISPR22_B QP
CISPR22_B AV



Results of Conducted Emission

Digital EMC
Date : 2012-12-03

Model No. : 55LN5400-UA
Type :
Serial No. :
Test Condition : USB

Reference No. :
Power Supply : 120 V 60 Hz
Temp/Humi. : 23°C 41 % R.H.
Operator :

Memo :

LIMIT : CISPR22_B QP
CISPR22_B AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.15006	58.7	40.4	0.2	58.9	40.6	66.0	56.0	7.1	15.4	N
2	0.31148	40.3	29.5	0.2	40.5	29.7	59.9	49.9	19.4	20.2	N
3	0.51336	41.0	32.1	0.2	41.2	32.3	56.0	46.0	14.8	13.7	N
4	0.71965	36.1	28.4	0.2	36.3	28.6	56.0	46.0	19.7	17.4	N
5	1.36800	37.5	26.7	0.3	37.8	27.0	56.0	46.0	18.2	19.0	N
6	7.76800	37.8	31.2	0.5	38.3	31.7	60.0	50.0	21.7	18.3	N
7	12.66900	37.4	31.2	0.7	38.1	31.9	60.0	50.0	21.9	18.1	N
8	0.15012	58.9	40.7	0.2	59.1	40.9	66.0	56.0	6.9	15.1	L1
9	0.52204	39.0	30.6	0.2	39.2	30.8	56.0	46.0	16.8	15.2	L1
10	0.70333	38.5	28.3	0.2	38.7	28.5	56.0	46.0	17.3	17.5	L1
11	10.76500	37.4	30.3	0.7	38.1	31.0	60.0	50.0	21.9	19.0	L1

6.2 Radiated Disturbance

6.2.1 Measurement Procedure

The radiated disturbance was measured and set-up was made accordance with **ANSI C63.4**.

If the EUT is tabletop equipment, it was placed on a wooden table with a height of 0.8 m above the reference ground plane and 3 m or 10 m away from the interference receiving antenna in the **10m semi-anechoic chamber**.

Also if the EUT is floor-standing equipment, it was placed on a non-conducted support with a height up to 0.15 m above the reference ground plane.

Rotate the EUT from (0 - 360)° and position the receiving antenna at heights from (1 - 4) m above the reference ground plane continuously to determine associated with higher emission levels and record them.

The measurement was made in both the vertical and horizontal polarization, and the maximum value is presented in the report.

For below 1 GHz frequency range, Quasi-Peak detector with 120 kHz RBW was used.

Also Peak and Average detector with 1 MHz RBW were used for above 1 GHz frequency range.

For further description of the configuration refer to the picture of the test set-up.

6.2.2 Limit for Radiated Disturbance

- The test frequency range of Radiated Disturbance measurements are listed below.

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 108	1 000
108 – 500	2 000
500 – 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

(1) Limit for Radiated Emission below 1 000MHz

Frequency range (MHz)	Class A Equipment (10 m distance)	Class B Equipment (3 m distance)
	Quasi-peak (dBμV/m)	Quasi-peak (dBμV/m)
30 to 88	39.1	40
88 to 216	43.5	43.5
216 to 960	46.4	46
960 to 1 000	49.5	54

Note 1 The lower limit shall apply at the transition frequency.

Note 2 Additional provisions may be required for cases where interference occurs.

Note 3 According to 15.109(g), as an alternative to the radiated emission limit shown above, digital devices may be shown to comply with the standards(CISPR), Pub. 22 shown as below.

Frequency range (MHz)	Class A Equipment (10 m distance)	Class B Equipment (10 m distance)
	Quasi-peak (dBμV/m)	Quasi-peak (dBμV/m)
30 to 230	40	30
230 to 1 000	47	37

(2) Limits for Radiated Emission above 1 000MHz at a measuring distance of 3 m

Frequency (GHz)	Class A Equipment		Class B Equipment	
	Peak (dBμV/m)	Average (dBμV/m)	Peak (dBμV/m)	Average (dBμV/m)
1 to 40	80	60	74	54

Note) 1. Emission Level = Reading Value + Correction Factor.

2. Correction Factor = Cable loss - Amp gain + Antenna Factor

3. Margin = Limit - Emission level

Test Result

< HDMI MODE_30 MHz ~ 1 GHz >

RADIATED EMISSION

Date : 2012-12-04

Model Name : 55LN5400-UA
Model No. :
Serial No. :
Test Condition : HDMI

Reference No. :
Power Supply : 120 V 60 Hz
Temp/Humi : 19 °C 47 % R.H.
Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m)
MARGIN: 6 dB



RADIATED EMISSION

Date : 2012-12-04

Model Name : 55LN5400-UA	Reference No. :
Model No. :	Power Supply : 120 V 60 Hz
Serial No. :	Temp/Humi : 19 °C 47 % R.H.
Test Condition : HDMI	Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m)
MARGIN: 6 dB

No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	95.493	37.7	10.1	1.5	22.8	26.5	43.5	17.0	201	288
2	190.839	39.2	9.2	2.2	23.3	27.3	43.5	16.2	201	112
3	319.661	36.5	13.6	3.0	24.0	29.1	46.0	16.9	100	296
----- Vertical -----										
4	94.302	37.6	9.9	1.5	22.8	26.2	43.5	17.3	100	329
5	131.443	38.3	11.8	1.5	23.0	28.6	43.5	14.9	100	332
6	394.295	34.4	15.5	3.5	24.4	29.0	46.0	17.0	201	198

< HDMI MODE _ (1 ~ 6) GHz _ Peak >

RADIATED EMISSION



Date : 2012-12-03

Model Name : 55LN5400-UA
Model No. :
Serial No. :
Test Condition : HDMI

Reference No. :
Power Supply : 120 V 60 Hz
Temp/Humi : 19 °C 47 % R.H.
Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Peak)
FCC Part15 Subpart.B Class B (3m) - 18G(Avg)



RADIATED EMISSION

Date : 2012-12-03

Model Name : 55LN5400-UA	Reference No. :
Model No. :	Power Supply : 120 V 60 Hz
Serial No. :	Temp/Humi : 19 °C 47 % R.H.
Test Condition : HDMI	Operator :

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Peak)
FCC Part15 Subpart B Class B (3m) - 18G(Avg)

No.	FREQ [MHz]	READING PEAK [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1032.051	63.9	23.9	5.9	41.8	51.9	74.0	22.1	100	358
2	1793.269	72.5	24.6	8.1	41.8	63.4	74.0	10.6	100	154
----- Vertical -----										
3	1673.077	62.4	24.6	7.8	41.7	53.1	74.0	20.9	100	1
4	1809.295	64.7	24.6	8.1	41.8	55.6	74.0	18.4	100	1
5	1985.577	61.4	24.6	8.4	41.7	52.7	74.0	21.3	100	1
6	2450.326	62.6	27.2	9.4	42.0	57.2	74.0	16.8	100	203

< HDMI MODE _ (1 ~ 6) GHz _ Average >

RADIATED EMISSION


Date : 2012-12-03

Model Name : 55LN5400-UA
Model No. :
Serial No. :
Test Condition : HDMI

Reference No. :
Power Supply : 120 V 60 Hz
Temp/Humi : 19 °C 47 % R.H.
Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
FCC Part15 Subpart.B Class B (3m) - 18G(Peak)



RADIATED EMISSION

Date : 2012-12-03

Model Name : 55LN5400-UA	Reference No. :
Model No. :	Power Supply : 120 V 60 Hz
Serial No. :	Temp/Humi : 19 °C 47 % R.H.
Test Condition : HDMI	Operator :

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Avg)
FCC Part15 Subpart B Class B (3m) - 18G(Peak)

No.	FREQ [MHz]	READING AV [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1043.660	42.9	23.9	5.9	41.8	30.9	54.0	23.1	100	358
2	1798.514	52.7	24.6	8.1	41.8	43.6	54.0	10.4	100	154
----- Vertical -----										
3	1690.782	45.0	24.6	7.9	41.7	35.8	54.0	18.2	100	1
4	1799.153	46.4	24.6	8.1	41.8	37.3	54.0	16.7	100	1
5	1986.514	44.9	24.6	8.4	41.7	36.2	54.0	17.8	100	1
6	2439.983	44.4	27.1	9.4	42.0	38.9	54.0	15.1	100	203

< USB MODE_30 MHz ~ 1 GHz >

RADIATED EMISSION


Date : 2012-12-04

Model Name : 55LN5400-UA
Model No. :
Serial No. :
Test Condition : USB

Reference No. :
Power Supply : 120 V 60 Hz
Temp/Humi : 19 °C 47 % R.H.
Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m)
MARGIN: 6 dB



RADIATED EMISSION

Date : 2012-12-04

Model Name : 55LN5400-UA	Reference No. :
Model No. :	Power Supply : 120 V 60 Hz
Serial No. :	Temp/Humi : 19 °C 47 % R.H.
Test Condition : USB	Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m)
MARGIN: 6 dB

No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	75.538	36.0	6.9	1.6	22.8	21.7	40.0	18.3	201	132
2	95.745	38.1	10.1	1.5	22.8	26.9	43.5	16.6	301	301
3	226.226	36.9	10.8	2.4	23.5	26.6	46.0	19.4	100	304
4	398.413	33.0	15.6	3.5	24.5	27.6	46.0	18.4	100	69
----- Vertical -----										
5	96.334	37.5	10.2	1.5	22.8	26.4	43.5	17.1	100	331
6	130.921	38.2	11.8	1.5	23.0	28.5	43.5	15.0	100	283
7	393.224	35.3	15.5	3.5	24.4	29.9	46.0	16.1	299	341

< USB MODE _ (1 ~ 6) GHz _ Peak >

RADIATED EMISSION



Date : 2012-12-04

Model Name : 55LN5400-UA
Model No. :
Serial No. :
Test Condition : USB

Reference No. :
Power Supply : 120 V 60 Hz
Temp/Humi : 19 °C 47 % R.H.
Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Peak)
FCC Part15 Subpart.B Class B (3m) - 18G(Avg)



RADIATED EMISSION

Date : 2012-12-04

Model Name : 55LN5400-UA	Reference No. :
Model No. :	Power Supply : 120 V 60 Hz
Serial No. :	Temp/Humi : 19 °C 47 % R.H.
Test Condition : USB	Operator :

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Peak)
FCC Part15 Subpart B Class B (3m) - 18G(Avg)

No.	FREQ [MHz]	READING PEAK [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1040.064	61.1	23.9	5.9	41.8	49.1	74.0	24.9	100	1
2	1793.269	69.2	24.6	8.1	41.8	60.1	74.0	13.9	100	1
----- Vertical -----										
3	1024.038	59.6	23.9	5.8	41.8	47.5	74.0	26.5	100	195
4	1192.308	60.2	24.2	6.4	41.9	48.9	74.0	25.1	100	358
5	1793.269	67.7	24.6	8.1	41.8	58.6	74.0	15.4	100	124
6	2450.326	60.7	27.2	9.4	42.0	55.3	74.0	18.7	100	205

< USB MODE _ (1 ~ 6) GHz _ Average >

RADIATED EMISSION



Date : 2012-12-04

Model Name : 55LN5400-UA
Model No. :
Serial No. :
Test Condition : USB

Reference No. :
Power Supply : 120 V 60 Hz
Temp/Humi : 19 °C 47 % R.H.
Operator :

Memo :

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
FCC Part15 Subpart.B Class B (3m) - 18G(Peak)



RADIATED EMISSION

Date : 2012-12-04

Model Name : 55LN5400-UA	Reference No. :
Model No. :	Power Supply : 120 V 60 Hz
Serial No. :	Temp/Humi : 19 °C 47 % R.H.
Test Condition : USB	Operator :

Memo :

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Avg)
FCC Part15 Subpart B Class B (3m) - 18G(Peak)

No.	FREQ [MHz]	READING AV [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1045.624	42.6	23.9	5.9	41.8	30.6	54.0	23.4	100	211
2	1797.518	45.3	24.6	8.1	41.8	36.2	54.0	17.8	100	87
----- Vertical -----										
3	1041.518	41.9	23.9	5.9	41.8	29.9	54.0	24.1	100	195
4	1200.031	42.9	24.2	6.4	41.9	31.6	54.0	22.4	100	358
5	1799.169	45.7	24.6	8.1	41.8	36.6	54.0	17.4	100	124
6	2455.209	46.2	27.2	9.4	42.0	40.8	54.0	13.2	100	205

Appendix 1

List of Test and Measurement Instruments

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment is identified by the Test Laboratory.

1. Conducted Disturbance

Name of Instrument	Model No.	Manufacturer	Serial No.	Cal. Date	Next Cal. Date
☐ SPECTRUM ANALYZER	8591E	H/P	3649A05889	2012.03.05	2013.03.05
☐ RFI/FIELD INTENSITY METER	KNM-2402	KYORITSU	4N-170-3	2012.07.02	2013.07.02
☐ LISN	KNW-407	KYORITSU	8-317-8	2012.01.09	2013.01.09
☐ LISN	PMM L2-16B	NARDA S.T.S. / PMM	000WX20305	2012.07.25	2013.07.25
☐ 50 OHM TERMINATOR	CT-01	TME	N/A	2012.01.09	2013.01.09
☒ EMI TEST RECEIVER	ESCI	ROHDE & SCHWARZ	100364	2012.03.06	2013.03.06
☒ LISN	ESH2-Z5	ROHDE & SCHWARZ	828739/006	2012.09.18	2013.09.18
☒ LISN	LISN1600	TTI	197204	2012.07.02	2013.07.02
☒ 50 OHM TERMINATOR	CT-01	TME	N/A	2012.01.09	2013.01.09

2. Radiated Disturbance

Name of Instrument	Model No.	Manufacturer	Serial No.	Cal. Date	Next Cal. Date
☒ EMI TEST RECEIVER	ESU	ROHDE & SCHWARZ	100014	2012.01.09	2013.01.09
☒ BILOG ANTENNA	CBL6112D	SCHAFFNER	22609	2011.12.21	2012.12.21
☒ HORN ANTENNA	BBHA9120A	SCHWARZBECK	322	2012.05.15	2014.05.15
☒ AMPLIFIER	8447E	H/P	2945A02865	2012.01.09	2013.01.09
☒ AMPLIFIER	MLA-100M18-B01-25	TSJ	1719458	2012.06.04	2013.06.04
☐ SPECTRUM ANALYZER	E4411B	AGILENT	US41062735	2012.07.11	2013.07.11
☐ AMPLIFIER	8447D	AGILENT	2443A03690	2012.07.01	2013.07.01
☐ BILOG ANTENNA	CBL6112B	SCHAFFNER	2737	2012.03.22	2014.03.22
☐ EMI TEST RECEIVER	ESCI	ROHDE & SCHWARZ	100364	2012.03.06	2013.03.06
☐ BICONICAL ANT.	VHA 9103	SCHWARZBECK	91032789	2012.04.10	2014.04.10
☐ LOG-PERIODIC ANT.	UHALP 9108A	SCHWARZBECK	590	2012.04.10	2014.04.10
☐ BICONICAL ANT.	VHA 9103	SCHWARZBECK	91031946	2012.03.12	2014.03.12
☐ LOG-PERIODIC ANT.	UHALP 9108-A1	SCHWARZBECK	1098	2012.03.12	2014.03.12
☐ AMPLIFIER	MLA-100K01-B01-26	TSJ	1252741	2012.03.05	2013.03.05