



Designs and specifications are subject to change without notice.
Weight and dimensions shown are approximate.

GENERAL

Head System	Four head helical scan azimuth system
Power Source	AC 100-240V, 50/60Hz
Power Consumption	Approx. 22 Watts
Dimensions (WxHxD)	360 x 98 x 274 mm (14.2" x 3.9" x 10.8")
Operating Temperature	5 °C~35 °C (41 °F~95 °F)
Operating Humidity	Less than 80% RH
Timer	12-hour display type with AM, PM
Weight	Approx. 3.4 kg (7.5 lbs)
Tape Speed	33.35 mm/sec (SP mode) 16.67 mm/sec (LP mode) 11.12 mm/sec (EP mode)
Tape Width	12.7 mm
Maximum Recording Time	2 HOURS (T-120, SP mode) 6 HOURS (T-120, EP mode) 8 HOURS (T-160, EP mode)
Rewind Time	About 60 seconds (T-120)

TUNER

Antenna	75 ohms (UHF), 75 ohms (VHF)
VHF Output Signal	Channel 3 or 4 (Switchable)
Channel Coverage	VHF; 2-13 UHF; 14-69 CATV; 4A, A~W, W+1~W+84, A-5~A-1

VIDEO

Video Signal System	EIA Standard (525 lines, 60 fields) NTSC type color signal
Input	1.0 Vp-p 75 ohms unbalanced
Output	1.0 Vp-p 75 ohms unbalanced
Signal to Noise Ratio	More than 43 dB (SP mode)

AUDIO

FM audio	
Frequency Range	20Hz to 20kHz
Dynamic Range	More than 83 dB
Channel Separation	More than 55 dB
Conventional audio	
Input	-6.0 dBm more than 47 kohms (LINE)
Output	-6.0 dBm less than 1.5 kohms (LINE)
S/N Ratio	More than 43 dB (SP mode)
Frequency Range	200 Hz to 10kHz (SP mode)

Supplied Accessories

Coaxial Cable (1)
Audio Cable (1)
Video Cable (1)
Remote control (1)

Specifications