

HCT CO., LTD.

CERTIFICATE OF COMPLIANCE

FCC Certification

Applicant Name:
LG Electronics Inc.

Date of Issue:
March 08, 2012

Address:
221, Yangjae-Dong Seocho-Gu, Seoul, Korea 137-130

Test Site/Location:
HCT CO., LTD., 105-1, Jangam-ri, Majang-Myeon,
Icheon-si, Kyunggi-Do, Korea

Report No.: HCTR1203FR11

HCT FRN: 0005866421

FCC ID: BEJ-ZB110

APPLICANT: LG Electronics Inc.

FCC Model(s): LG-ZB110
EUT Type: Zigbee coordinator of home network Appliances
Max. RF Output Power: 21.80 dBm
Frequency Range: 2415 MHz -2460 MHz
Modulation type DSSS
FCC Classification: Digital Transmission System(DTS)
FCC Rule Part(s): Part 15.247

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)



Report prepared by

: Jong Seok Lee

Test engineer of RF Team



Approved by

: Sang Jun Lee

Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1203FR11	Date of Issue: March 08, 2012	EUT Type: Zigbee coordinator of home network Appliances	FCC ID: BEJ-ZB110

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCTR1203FR11	March 08, 2012	- First Approval Report

Table of Contents

1. GENERAL INFORMATION	4
2. EUT DESCRIPTION	4
3. TEST METHODOLOGY	5
3.1 EUT CONFIGURATION	5
3.2 EUT EXERCISE	5
3.3 GENERAL TEST PROCEDURES	5
3.4 DESCRIPTION OF TEST MODES	5
4. INSTRUMENT CALIBRATION.....	6
5. FACILITIES AND ACCREDITATIONS	6
5.1 FACILITIES	6
5.2 EQUIPMENT	6
6. ANTENNA REQUIREMENTS	7
7. SUMMARY TEST OF RESULTS	8
8. TEST RESULT	9
8.1 6dB BANDWIDTH MEASUREMENT	9
8.2 OUTPUT POWER MEASUREMENT	1 2
8.3 POWER SPECTRAL DENSITY	1 8
8.4 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS ...	2 2
8.5 RADIATED MEASUREMENT.....	2 8
8.5.1 RADIATED SPURIOUS EMISSIONS.....	2 8
8.5.2 RADIATED RESTRICTED BAND EDGE MEASUREMENTS	3 6
8.6 POWERLINE CONDUCTED EMISSIONS	3 7
9. LIST OF TEST EQUIPMENT	4 2

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1203FR11	Date of Issue: March 08, 2012	EUT Type: Zigbee coordinator of home network Appliances	FCC ID: BEJ-ZB110

1. GENERAL INFORMATION

Applicant: LG Electronics Inc.

Address: 221, Yangjae-Dong Seocho-Gu, Seoul, Korea 137-130

Manufacture: Korea Infocom

FCC ID: BEJ-ZB110

EUT Type: Zigbee coordinator of home network Appliances

Model name(s): LG-ZB110

Date(s) of Tests: February 17, 2012 ~ March 07, 2012

Contact Person: Name: Jae Hong Kim
Phone #: +82-31-421-7711

Place of Tests: HCT Co., Ltd.
105-1, Jangam-ri , Majang-Myeon, Icheon-si, Kyunggi-Do, 467-811, KOREA.
(IC Recognition No. : 5944A-3)

2. EUT DESCRIPTION

EUT Type	Zigbee coordinator of home network Appliances
FCC Model Name	LG-ZB110
Power Supply	DC 5.0 V
Frequency Range	TX: 2415 MHz -2460 MHz RX: 2415 MHz -2460 MHz
Max. RF Output Power:	21.80 dBm
Modulation Type	DSSS
Antenna Specification	Manufacturer: Antenova Antenna type: SMD Antenna Peak Gain : 1.8 dBi

3. TEST METHODOLOGY

The measurement procedure described in the American National Standard for Testing Unlicensed Wireless Devices(ANSI C63.10-2009).

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2009) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.3 of ANSI C63.10. (Version: 2009).

3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1203FR11	Date of Issue: March 08, 2012	EUT Type: Zigbee coordinator of home network Appliances	FCC ID: BEJ-ZB110

4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 105-1, Jangam-ri, Majang-Myeon, Icheon-si, Kyunggi-Do, 467-811, Korea. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated March 02, 2011 (Registration Number: 90661)

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1203FR11	Date of Issue: March 08, 2012	EUT Type: Zigbee coordinator of home network Appliances	FCC ID: BEJ-ZB110

6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

* The antennas of this E.U.T are permanently attached.

*The E.U.T Complies with the requirement of §15.203

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1203FR11	Date of Issue: March 08, 2012	EUT Type: Zigbee coordinator of home network Appliances	FCC ID: BEJ-ZB110

7. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§15.247(a)(2)	> 500 kHz	CONDUCTED	PASS
Conducted Maximum Peak Output Power	§15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge(Out of Band Emissions)	§15.247(d)	Conducted < 20 dBc		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 8.6		PASS
Radiated Spurious Emissions	§15.205, 15.209	cf. Section 8.5.1	RADIATED	PASS
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 8.5.2		PASS

8. TEST RESULT


8.1 6dB BANDWIDTH MEASUREMENT

Test Requirements and limit, §15.247(a)(2)

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6dB bandwidth is 500 kHz.

■ TEST CONFIGURATION



■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to

RBW: 100 kHz

VBW: 130 kHz

SPAN: 10 MHz


■ TEST RESULTS

Conducted 6dB Bandwidth Measurements


Frequency[MHz]	Channel No.	Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
2415	13	1.695	0.500	Pass
2440	18	1.575	0.500	Pass
2460	22	1.582	0.500	Pass

■ RESULT PLOTS


6dB Bandwidth plot CH 13



6dB Bandwidth plot CH 18



6dB Bandwidth plot CH 22




8.2 OUTPUT POWER MEASUREMENT

Test Requirements and limit, §15.247(b)(3)

A transmitter antenna terminal of EUT is connected to the input of a Spectrum Analyzer. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

■ TEST CONFIGURATION



■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. We use the spectrum analyzer's integrated band power measurement function. We tested according to KDB 558074(issued 1/18/2012).

This EUT TX condition is actual operating mode(not near 100 % duty cycle) by Zigbee test program.

The Spectrum Analyzer is set to

- Peak Power

RBW = 1 MHz

VBW = 3 MHz

SPAN = 5 – 30 % greater than the EBW

Detector Mode = Peak

Integrated bandwidth = EBW

- Average Power

RBW = 1 MHz

VBW = 3 MHz

SPAN = 5 – 30 % greater than the EBW

Detector Mode = Average

Integrated bandwidth = EBW

■ Sample Calculation

Output Power = Reading Value + ATT loss + Cable loss(1 ea)
 = 10 dBm + 10 dB + 0.8 dB = 20.8 dBm

Where) Spectrum offset = ATT loss + Cable loss(1 ea)

Note: Power values in plot are applied offset.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1203FR11	Date of Issue: March 08, 2012	EUT Type: Zigbee coordinator of home network Appliances	FCC ID: BEJ-ZB110

■ TEST RESULTS-Peak

Conducted Output Power Measurements

Frequency[MHz]	Channel No.	Measured Power(dBm)	Limit (dBm)	Pass / Fail
2415	13	21.80	30	Pass
2440	18	21.69	30	Pass
2460	22	21.61	30	Pass


■ TEST RESULTS-Average

Conducted Output Power Measurements


Frequency[MHz]	Channel No.	Measured Power(dBm)	Limit (dBm)	Pass / Fail
2415	13	18.82	30	Pass
2440	18	18.75	30	Pass
2460	22	18.64	30	Pass

■ RESULT PLOTS-Peak


Conducted Output Power CH 13



Conducted Output Power CH 18




Conducted Output Power CH 22




FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1203FR11	Date of Issue: March 08, 2012	EUT Type: Zigbee coordinator of home network Appliances	FCC ID: BEJ-ZB110

■ RESULT PLOTS-Average


Conducted Output Power CH 13



Conducted Output Power CH 18



Conducted Output Power CH 22



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1203FR11	Date of Issue: March 08, 2012	EUT Type: Zigbee coordinator of home network Appliances	FCC ID: BEJ-ZB110


8.3 POWER SPECTRAL DENSITY

Test Requirements and limit, §15.247(e)

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

Minimum Standard – The transmitter power density average over 1-second interval shall not be greater than 8 dBm in any 3kHz BW.

■ TEST CONFIGURATION



■ TEST PROCEDURE

The spectrum analyzer is set to :

1. Span = 300 kHz
2. RBW = 3 kHz
3. VBW = 10 kHz
4. Sweep = 100 sec
5. Detector Mode = Peak

■ Sample Calculation

PSD = Reading Value + ATT loss + Cable loss(1 ea)

Output Power = -5 dBm + 10 dB + 0.8 dB = 5.8 dBm

Where) Spectrum offset = ATT loss + Cable loss(1 ea)

Note: Power values in plot is applied offset.


■ TEST RESULTS

Conducted Power Density Measurements


Frequency (MHz)	Channel No.	Test Result		Pass/Fail
		Power Density (dBm)	Limit (dBm)	
2415	13	3.66	8	Pass
2440	18	4.26	8	Pass
2460	22	4.11	8	Pass

■ RESULT PLOTS


Power Spectral Density CH 13



Power Spectral Density CH 18



Power Spectral Density CH 22




FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1203FR11	Date of Issue: March 08, 2012	EUT Type: Zigbee coordinator of home network Appliances	FCC ID: BEJ-ZB110

8.4 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS

Test Requirements and limit, §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

■ TEST CONFIGURATION



■ TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.


Detector Mode is set to a peak detector Mode.

Measurements are made over the 30 MHz to 26 GHz range with the transmitter set to the lowest, middle, and highest channels.


FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1203FR11	Date of Issue: March 08, 2012	EUT Type: Zigbee coordinator of home network Appliances	FCC ID: BEJ-ZB110

■ RESULT PLOTS

BandEdge CH 13




BandEdge CH 22




30 MHz ~ 1 GHz


Conducted Spurious Emission CH 13



Conducted Spurious Emission CH 18




Conducted Spurious Emission CH 22




1 GHz ~ 26 GHz


Conducted Spurious Emission CH 13



Conducted Spurious Emission CH 18



Conducted Spurious Emission CH 22



8.5 RADIATED MEASUREMENT.


8.5.1 RADIATED SPURIOUS EMISSIONS.

Test Requirements and limit, §15.205, §15.209


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1203FR11	Date of Issue: March 08, 2012	EUT Type: Zigbee coordinator of home network Appliances	FCC ID: BEJ-ZB110

TEST RESULTS

9 kHz – 30MHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)
4. Limit line = specific Limits (dB μ V) + Distance extrapolation factor

TEST RESULTS

Below 1 GHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

Above 1 GHz

Operating Frequency 2415 MHz
Channel No. 13 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4830	53.52	-0.20	V	53.32	74	20.68	PK
4830	41.13	-0.20	V	40.93	54	13.07	AV
7245	49.59	10.34	V	59.93	74	14.07	PK
7245	36.29	10.34	V	46.63	54	7.37	AV
9660	50.93	13.21	V	64.14	74	9.86	PK
9660	37.92	13.21	V	51.13	54	2.87	AV
4830	53.68	-0.20	H	53.48	74	20.52	PK
4830	40.13	-0.20	H	39.93	54	14.07	AV
7245	50.01	10.34	H	60.35	74	13.65	PK
7245	37.88	10.34	H	48.22	54	5.78	AV
9660	50.26	13.21	H	63.47	74	10.53	PK
9660	35.71	13.21	H	48.92	54	5.08	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

Operating Frequency 2440 MHz
Channel No. 18 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4880	52.35	0.25	V	52.60	74	21.40	PK
4880	40.15	0.25	V	40.40	54	13.60	AV
7320	50.41	10.01	V	60.42	74	13.58	PK
7320	36.75	10.01	V	46.76	54	7.24	AV
9760	50.16	12.93	V	63.09	74	10.91	PK
9760	37.44	12.93	V	50.37	54	3.63	AV
4880	51.86	0.25	H	52.11	74	21.89	PK
4880	38.80	0.25	H	39.05	54	14.95	AV
7320	49.78	10.01	H	59.79	74	14.21	PK
7320	36.92	10.01	H	46.93	54	7.07	AV
9760	49.95	12.93	H	62.88	74	11.12	PK
9760	35.67	12.93	H	48.60	54	5.40	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

Operating Frequency 2460 MHz
Channel No. 22 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4920	52.59	0.75	V	53.34	74	20.66	PK
4920	39.68	0.75	V	40.43	54	13.57	AV
7380	50.26	10.11	V	60.37	74	13.63	PK
7380	37.78	10.11	V	47.89	54	6.11	AV
9840	50.09	13.37	V	63.46	74	10.54	PK
9840	37.02	13.37	V	50.39	54	3.61	AV
4920	50.84	0.75	H	51.59	74	22.41	PK
4920	37.68	0.75	H	38.43	54	15.57	AV
7380	49.89	10.11	H	60.00	74	14.00	PK
7380	36.78	10.11	H	46.89	54	7.11	AV
9840	49.22	13.37	H	62.59	74	11.41	PK
9840	35.99	13.37	H	49.36	54	4.64	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MH.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

8.5.2 RADIATED RESTRICTED BAND EDGE MEASUREMENTS

Test Requirements and limit, §15.247(d) §15.205, §15.209

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c)).

Operating Frequency	2415 MHz, 2440 MHz
Channel No.	13 Ch, 22 Ch

Frequency [MHz]	Reading dBuV	AN.+CL [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
2390.0	29.64	33.86	H	63.50	74	10.50	PK
2390.0	17.29	33.86	H	51.15	54	2.85	AV
2390.0	25.53	33.86	V	59.39	74	14.61	PK
2390.0	13.99	33.86	V	47.85	54	6.15	AV
2483.5	30.09	34.02	H	64.11	74	9.89	PK
2483.5	17.46	34.02	H	51.48	54	2.52	AV
2483.5	25.91	34.02	V	59.93	74	14.07	PK
2483.5	13.71	34.02	V	47.73	54	6.27	AV

Notes:

1. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

8.6 POWERLINE CONDUCTED EMISSIONS

Test Requirements and limit, §15.207

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.

RESULT PLOTS

Conducted Emissions (Line 1)


HCT

EMC

EUT: LG-ZB110
 Manufacturer: LG
 Operating Condition: ZIGBEE MODE
 Test Site: SHIELD ROOM
 Operator: JS LEE
 Test Specification: FCC PART15 CLASS B
 Comment: N

SCAN TABLE: "FCC PART 15 B(N)"

Short Description:			FCC PART 15 CLASS B				
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer	
Frequency	Frequency	Width					
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				



MEASUREMENT RESULT: "PHONE_fin QP"

3/7/2012 5:20PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150010	49.20	10.3	66	16.8	---	---
0.242010	39.60	10.3	62	22.4	---	---
0.342010	33.20	10.3	59	26.0	---	---
2.944000	28.30	10.5	56	27.7	---	---
3.360000	32.50	10.5	56	23.5	---	---
3.524000	32.10	10.6	56	23.9	---	---
18.564000	42.50	11.6	60	17.5	---	---
20.480000	46.30	11.7	60	13.7	---	---
21.264000	42.00	11.7	60	18.0	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

3/7/2012 5:20PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.194010	23.50	10.3	54	30.4	---	---
0.258010	19.90	10.3	52	31.6	---	---
0.394010	14.90	10.3	48	33.1	---	---
1.940000	25.80	10.4	46	20.2	---	---
2.004000	26.20	10.4	46	19.8	---	---
2.128000	24.70	10.4	46	21.3	---	---
18.484000	36.10	11.6	50	13.9	---	---
20.588000	39.40	11.7	50	10.6	---	---
22.428000	33.90	11.8	50	16.1	---	---

Conducted Emissions (Line 2)


HCT

EMC

EUT: LG-ZB110
 Manufacturer: LG
 Operating Condition: ZIGBEE MODE
 Test Site: SHIELD ROOM
 Operator: JS LEE
 Test Specification: FCC PART15 CLASS B
 Comment: H

SCAN TABLE: "FCC PART 15 B(H)"

Short Description:			FCC PART 15 CLASS B			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	500.0 kHz	1.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



MEASUREMENT RESULT: "PHONE_fin QP"

3/7/2012 5:16PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.153010	48.10	10.1	66	17.7	---	---
0.228010	39.90	10.1	63	22.6	---	---
0.345010	31.60	10.1	59	27.5	---	---
3.464000	33.10	10.3	56	22.9	---	---
3.588000	32.00	10.4	56	24.0	---	---
3.604000	30.90	10.4	56	25.1	---	---
20.740000	46.60	11.9	60	13.4	---	---
20.916000	46.10	11.9	60	13.9	---	---
21.080000	43.60	11.9	60	16.4	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

3/7/2012 5:16PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.196010	21.90	10.1	54	31.8	---	---
0.247010	16.10	10.1	52	35.8	---	---
0.311010	14.10	10.1	50	35.8	---	---
1.940000	25.30	10.2	46	20.7	---	---
2.004000	25.50	10.2	46	20.5	---	---
2.068000	25.20	10.2	46	20.8	---	---
18.664000	36.10	11.8	50	13.9	---	---
20.796000	38.80	11.9	50	11.2	---	---
22.376000	33.00	12.0	50	17.0	---	---

9. LIST OF TEST EQUIPMENT

Manufacturer	Model / Equipment	Calibration Interval	Calibration Due	Serial No.
Rohde & Schwarz	ESH2-Z5/ LISN	Annual	02/03/2013	861741/013
Schwarzbeck	VULB 9168/ TRILOG Antenna	Biennial	02/09/2013	200
Rohde & Schwarz	ESI 40 / EMI TEST RECEIVER	Annual	05/26/2012	831564103
Agilent	E4440A/ Spectrum Analyzer	Annual	05/02/2012	US45303008
Agilent	N9020A/ SIGNAL ANALYZER	Annual	09/23/2012	MY51110020
HD	MA240/ Antenna Position Tower	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	12
Rohde & Schwarz	ESH3-Z2/ PULSE LIMITER	Annual	08/01/2012	375.8810.352
Rohde & Schwarz	SCU-18/ Signal Conditioning Unit	Annual	09/19/2012	10094
MITEQ	AFS44-00102650-42-10P-44-PS/ POWER AMP	Annual	09/23/2012	1532439
Schwarzbeck	BBHA 9120D/ Horn Antenna	Biennial	10/17/2013	937
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	Biennial	10/26/2012	BBHA9170342
Rohde & Schwarz	FSP / Spectrum Analyzer	Annual	02/09/2013	839117/011
Agilent	E4416A /Power Meter	Annual	11/07/2012	GB41291412
Agilent	E9327A /POWER SENSOR	Annual	05/02/2012	MY4442009
Wainwright Instrument	WHF3.3/18G-10EF / High Pass Filter	Annual	05/02/2012	1
Wainwright Instrument	WRCJ2400/2483.5-2370/2520-60/14SS / Band Reject Filter	Annual	05/02/2012	1
Hewlett Packard	11636B/Power Divider	Annual	11/07/2012	11377
Hewlett Packard	11667B / Power Splitter	Annual	11/04/2012	10126
DIGITAL	EP-3010 /DC POWER SUPPLY	Annual	11/07/2012	3110117
ITECH	IT6720 / DC POWER SUPPLY	Annual	11/07/2012	010002156287001199
TESCOM	TC-3000C / BLUETOOTH TESTER	Annual	11/14/2012	3000C000276
Rohde & Schwarz	CBT / BLUETOOTH TESTER	Annual	05/02/2012	100422
EMCO	6502.LOOP ANTENNA	Biennial	01/11/2014	9009-2536
MITEQ	AMF-6D-001180-35-20P/ POWER AMP	Annual	12/26/2012	990893
Agilent	8493C / Attenuator(10 dB)	Annual	09/23/2012	76649