

RF TEST REPORT

Test item : LG Miracast Dongle
Model No. : DWD-300
Order No. : DEMC1208-01489
Date of receipt : 2012-08-17
Test duration : 2012-09-17 ~ 2012-09-21
Date of issue : 2012-09-26
Use of report : FCC & IC Original Grant

Applicant : LG Electronics USA.
1000 Sylvan Avenue Englewood Cliffs, New Jersey, United States

Test laboratory : Digital EMC Co., Ltd.
683-3, Yubang-Dong, Cheoin-Gu, Yongin-Si, Kyunggi-Do, 449-080, Korea

Test specification : FCC Part 15 Subpart C 247, RSS-210 Issue 8
ANSI C63.4-2003, KDB558074

Test environment : See appended test report

Test result : ☒ Pass ☐ Fail

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DIGITAL EMC CO., LTD.

Tested by:




Engineer
H.H.LEE

Witnessed by:

N/A

Reviewed by:



Technical Director
Harvey sung

Table of Contents

1. GENERAL INFORMATION.....	3
2. EUT DESCRIPTION	3
3. SUMMARY OF TESTS	4
4. TEST METHODOLOGY	5
4.1 EUT CONFIGURATION	5
4.2 EUT EXERCISE	5
4.3 GENERAL TEST PROCEDURES	5
4.4 DESCRIPTION OF TEST MODES	5
5. INSTRUMENT CALIBRATION	6
6. FACILITIES AND ACCREDITATIONS	6
6.1 FACILITIES	6
6.2 EQUIPMENT	6
7. ANTENNA REQUIREMENTS.....	6
8. TEST RESULT	7
8.1 6dB Bandwidth	7
8.2 Maximum Peak Conducted Output Power	14
8.3 Maximum Power Spectral Density	22
8.4 Out of Band Emissions at the Band Edge/ Conducted Spurious Emissions.....	29
8.5 Radiated Spurious Emissions.....	45
8.6 Power-line Conducted Emissions	50
8.7 Occupied Bandwidth.....	57
9. LIST OF TEST EQUIPMENT.....	64

1. GENERAL INFORMATION

Applicant : LG Electronics USA.
Address : 1000 Sylvan Avenue Englewood Cliffs, New Jersey, United States
FCC ID : BEJDWD300
EUT : LG Miracast Dongle
Model : DWD-300
Additional Model(s) : N/A
Data of Test : 2012-09-17 ~ 2012-09-21
Contact person : Jacob Cho

2. EUT DESCRIPTION

Product	LG Miracast Dongle
Model Name	DWD-300
Power Supply	DC 5 V
Frequency Range	2.4GHz Band ▪ 802.11b/g/n(20MHz): 2412 ~ 2462 MHz
Max. RF Output Power	2.4GHz Band ▪ 802.11b: 19.50 dBm ▪ 802.11g: 15.92 dBm ▪ 802.11n (HT20): 13.41 dBm
Modulation Type	802.11b: DSSS/CCK 802.11g/n: OFDM
Antenna Specification	Internal Antenna (1TX 1RX) ▪ 2.4GHz Band Max. peak gain : 3.25 dBi

3. SUMMARY OF TESTS

FCC Part Section(s)	RSS Section(s)	Parameter	Limit	Test Condition	Status Note 1
I. Transmitter Mode (TX)					
15.247(a)	RSS-210 [A8.2]	6 dB Bandwidth	> 500 kHz	Conducted	C
15.247(b)	RSS-210 [A8.4]	Transmitter Output Power	< 1Watt		C
15.247(c)	RSS-210 [A8.5]	Out of Band Emissions / Band Edge	20dBc in any 100kHz BW		C
15.247(d)	RSS-210 [A8.2]	Transmitter Power Spectral Density	< 8dBm / 3kHz		C
-	RSS Gen Issue 3	Occupied Bandwidth (99%)	RSS-Gen(4.6.1)		C
15.205 15.209	RSS-210 [A8.5]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	< FCC 15.209 limits	Radiated	C ^{Note2}
15.207	RSS-Gen [7.2.4]	AC Conducted Emissions	< FCC 15.207 limits	AC Line Conducted	C
15.203	RSS-Gen [7.1.2]	Antenna Requirements	FCC 15.203	-	C
Note 1: C=Comply NC=Not Comply NT=Not Tested NA=Not Applicable Note 2: This test item was performed in each axis and the worst case data was reported.					

4. TEST METHODOLOGY

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz(ANSI C63.4-2003) and KDB558074

4.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

4.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version :2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the highest emission, the relative positions of the EUT were rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version: 2003)

4.4 DESCRIPTION OF TEST MODES

The EUT has been tested with several operating conditions for maximizing the emission characteristics. A test program is used to control the EUT for staying in continuous transmitting mode.

5. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

6. FACILITIES AND ACCREDITATIONS

6.1 FACILITIES

The open area test site(OATS) or semi anechoic chamber and conducted measurement facility used to collect the radiated and conducted test data are located at the 683-3, Yubang-Dong, Yongin-Si, Gyunggi-Do, 449-080, South Korea. The site is constructed in conformance with the requirements.

- Semi anechoic chamber registration Number : 678747

6.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and peak, quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

7. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203 & RSS-Gen [7.1.2]:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- * The internal antenna of this E.U.T is uniquely attached on the main PCB using specially spring contactors.
- * Therefore this E.U.T Complies with the requirement of §15.203

8. TEST RESULT

8.1 6dB Bandwidth

Test Requirements and limit, §15.247(a) & RSS-210 [A8.2]

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6dB bandwidth is 500 kHz.

■ TEST CONFIGURATION

Refer to the APPENDIX I.

■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer and used following test procedure of KDB558074.

1. Set resolution bandwidth (RBW) = 1-5 % of the emission bandwidth (EBW).
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
(**RBW:200KHz/VBW:620KHz** for EBW < 20 MHz , **RBW:390KHz/VBW:1.2MHz** for 20 MHz < EBW < 40 MHz)
3. Detector = **Peak**.
4. Trace mode = **max hold**.
5. Sweep = **auto couple**.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. Compare the resultant bandwidth with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is 1-5 %.


■ TEST RESULTS: **Comply**

Test Mode	Data Rate	Frequency [MHz]	Test Results [MHz]
802.11b	1Mbps	2412	10.200
		2437	10.220
		2462	10.200
802.11g	6Mbps	2412	16.410
		2437	16.410
		2462	16.430
802.11n (20MHz)	MCS0	2412	17.610
		2437	17.620
		2462	17.610

RESULT PLOTS


6 dB Bandwidth

Test Mode: 802.11b & 1Mbps & 2412MHz




6 dB Bandwidth

Test Mode: 802.11b & 1Mbps & 2437MHz




6 dB Bandwidth

Test Mode: 802.11b & 1Mbps & 2462MHz




6 dB Bandwidth

Test Mode: 802.11g & 6Mbps & 2412MHz




6 dB Bandwidth

Test Mode: 802.11g & 6Mbps & 2437MHz




6 dB Bandwidth

Test Mode: 802.11g & 6Mbps & 2462MHz




6 dB Bandwidth

Test Mode: 802.11n & MCS0 & 2412MHz




6 dB Bandwidth

Test Mode: 802.11n & MCS0 & 2437MHz



6 dB Bandwidth

Test Mode: 802.11n & MCS0 & 2462MHz



8.2 Maximum Peak Conducted Output Power

Test Requirements and limit, §15.247(b) & RSS-210 [A8.4]

A transmitter antenna terminal of EUT is connected to the input of a spectrum analyzer.

Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

■ TEST CONFIGURATION

Refer to the APPENDIX I.

■ TEST PROCEDURE :

Maximum Peak Conducted Output Power is measured using **the Measurement Procedure PK2 of KDB558074**.

1. Set the **RBW = 1 MHz**.
2. Set the **VBW = 3 MHz**.
3. Set the span to a value that is **5-30 %** greater than the EBW.
4. Detector = **peak**.
5. Sweep time = **auto couple**.
6. Trace mode = **max hold**.
7. Allow trace to fully stabilize.
8. Use the spectrum analyzer's integrated band power measurement function with band limits set equal to the EBW band edges (for some analyzers, this may require a manual override to ensure use of peak detector). If the spectrum analyzer does not have a band power function, sum the spectrum levels (in linear power units) at 1 MHz intervals extending across the EBW of the spectrum.

Note: Tests were performed all possible data rates and the worst case data were reported.

■ **TEST RESULTS : Comply**

- Measurement Data: **Comply**


- **Summary of Test Results**

Mode	Channel	Frequency [MHz]	Test Result	
			[dBm]	[W]
802.11b	1	2412	19.50	0.089
	6	2437	18.68	0.074
	11	2462	18.31	0.068
802.11g	1	2412	15.88	0.039
	6	2437	15.92	0.039
	11	2462	15.80	0.038
802.11n HT20	1	2412	13.37	0.022
	6	2437	13.41	0.022
	11	2462	12.96	0.020

RESULT PLOTS


Peak Output Power

Test Mode: 802.11b & 11Mbps & 2412MHz




Peak Output Power

Test Mode: 802.11b & 11Mbps & 2437MHz




Peak Output Power

Test Mode: 802.11b & 11Mbps & 2462MHz




Peak Output Power

Test Mode: 802.11g & 54Mbps & 2412MHz




Peak Output Power

Test Mode: 802.11g & 54Mbps & 2437MHz



Peak Output Power

Test Mode: 802.11g & 54Mbps & 2462MHz



Peak Output Power Test Mode: 802.11n HT20 & MCS0 & 2412MHz



Peak Output Power Test Mode: 802.11n HT20 & MCS0 & 2437MHz



Peak Output Power

Test Mode: 802.11n HT20 & MCS0 & 2462MHz



8.3 Maximum Power Spectral Density

Test requirements and limit, §15.247(e) & RSS-210 [A8.2]

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

Minimum Standard –specifies a conducted power spectral density (PSD) limit of 8 dBm in any 3 kHz band segment within the fundamental EBW during any time interval of continuous transmission.

■ TEST CONFIGURATION

Refer to the APPENDIX I.

■ TEST PROCEDURE:

The Measurement Procedure **PKPSD of KDB558074** is used.

1. Set the **RBW = 100 kHz**.
2. Set the **VBW ≥ 300 kHz**.
3. Set the span to **5-30 %** greater than the EBW.
4. Detector = **peak**.
5. Sweep time = **auto couple**.
6. Trace mode = **max hold**.
7. Allow trace to fully stabilize.
8. Use the **peak marker function** to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
9. Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where **BWCF = $10\log(3\text{ kHz}/100\text{ kHz} = -15.2\text{ dB})$** .
10. The resulting peak PSD level must be $\leq 8\text{ dBm}$.


■ TEST RESULTS: **Comply**

Test Mode	Data Rate	Frequency [MHz]	S/A Reading [dBm]	B.W.C.F [dB]	PKPSD [dBm]
802.11b	11Mbps	2412	5.117	-15.20	-10.08
		2437	4.174	-15.20	-11.03
		2462	3.792	-15.20	-11.41
802.11g	54Mbps	2412	-3.124	-15.20	-18.32
		2437	-2.972	-15.20	-18.17
		2462	-3.514	-15.20	-18.71
802.11n HT20	MCS0	2412	-5.389	-15.20	-20.59
		2437	-5.278	-15.20	-20.48
		2462	-5.823	-15.20	-21.02

RESULT PLOTS


Maximum PKPSD

Test Mode: 802.11b & 11Mbps & 2412MHz




Maximum PKPSD

Test Mode: 802.11b & 11Mbps & 2437MHz




Maximum PKPSD

Test Mode: 802.11b & 11Mbps & 2462MHz




Maximum PKPSD

Test Mode: 802.11g & 54Mbps & 2412MHz




Maximum PKPSD

Test Mode: 802.11g & 54Mbps & 2437MHz




Maximum PKPSD

Test Mode: 802.11g & 54Mbps & 2462MHz




Maximum PKPSD

Test Mode: 802.11n(HT20) & MCS0 & 2412MHz




Maximum PKPSD

Test Mode: 802.11n(HT20) & MCS0 & 2437MHz



Maximum PKPSD

Test Mode: 802.11n(HT20) & MCS0 & 2462MHz



8.4 Out of Band Emissions at the Band Edge/ Conducted Spurious Emissions

Test requirements and limit, §15.247(d)


§15.247(d) specifies that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

If **the peak output power procedure** is used to measure the fundamental emission power to demonstrate compliance to **15.247(b)(3)** requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated **by at least 20 dB** relative to the maximum measured in-band peak PSD level.

If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to **15.247(b)(3)** requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured inband average PSD level.

In either case, attenuation to levels below the general emission limits specified in **§15.209(a)** is not required.

■ TEST CONFIGURATION



■ TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer.

- Measurement Procedure 1 – Reference Level

1. Set the **RBW = 100 kHz**.
2. Set the **VBW ≥ 300 kHz**.
3. Set the span to **5-30 %** greater than the EBW.
4. Detector = **peak**.
5. Sweep time = **auto couple**.
6. Trace mode = **max hold**.
7. Allow trace to fully stabilize.
8. Use the **peak marker function** to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

Next, **determine the power** in 100 kHz band segments outside of the authorized frequency band using the following measurement:


- Measurement Procedure 2 - Unwanted Emissions

1. Set **RBW = 100 kHz**.
2. Set **VBW ≥ 300 kHz**.
3. Set **span to encompass the spectrum** to be examined.
4. Detector = **peak**.
5. Trace Mode = **max hold**.
6. Sweep = **auto couple**.
7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).


RESULT PLOTS

802.11b & 11Mbps & 2412MHz


Reference



Low Band-edge




Conducted Spurious Emissions




802.11b & 11Mbps & 2437MHz

Reference




Conducted Spurious Emissions




802.11b & 11Mbps & 2462MHz


Reference



High Band-edge




Conducted Spurious Emissions




802.11g & 54Mbps & 2412MHz


Reference



Low Band-edge




Conducted Spurious Emissions




802.11g & 54Mbps & 2437MHz

Reference




Conducted Spurious Emissions




802.11g & 54Mbps & 2462MHz


Reference



High Band-edge




Conducted Spurious Emissions




802.11n(HT20) & MCS0 & 2412MHz


Reference



Low Band-edge




Conducted Spurious Emissions




802.11n(HT20) & MCS0 & 2437MHz

Reference




Conducted Spurious Emissions




802.11n(HT20) & MCS0 & 2462MHz


Reference



High Band-edge



Conducted Spurious Emissions



8.5 Radiated Spurious Emissions

Test Requirements and limit, §15.247(d), §15.205, §15.209 & RSS-210 [A8.5], RSS-Gen [7.2.2]

In any 100kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a) and (b), then the 15.209(a) limit in the table below has to be followed

▪ FCC Part 15.209(a) and (b)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500


** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

▪ FCC Part 15.205 (a): Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	3600 ~ 4400	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	4.5 ~ 5.15	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~	149.9 ~ 150.05	1645.5 ~ 1646.5	5.35 ~ 5.46	17.7 ~ 21.4
4.125 ~ 4.128	12.52025	156.52475 ~	1660 ~ 1710	7.25 ~ 7.75	22.01 ~ 23.12
4.17725 ~ 4.17775	12.57675 ~	156.52525	1718.8 ~ 1722.2	8.025 ~ 8.5	23.6 ~ 24.0
4.20725 ~ 4.20775	12.57725	156.7 ~ 156.9	2200 ~ 2300	9.0 ~ 9.2	31.2 ~ 31.8
6.215 ~ 6.218	13.36 ~ 13.41	162.0125 ~ 167.17	2310 ~ 2390	9.3 ~ 9.5	36.43 ~ 36.5
6.26775 ~ 6.26825	16.42 ~ 16.423	167.72 ~ 173.2	2483.5 ~ 2500	10.6 ~ 12.7	Above 38.6
6.31175 ~ 6.31225	16.69475 ~	240 ~ 285	2655 ~ 2900	13.25 ~ 13.4	
8.291 ~ 8.294	16.69525	322 ~ 335.4	3260 ~ 3267		
8.362 ~ 8.366	16.80425 ~	399.90 ~ 410	3332 ~ 3339		
8.37625 ~ 8.38675	16.80475	608 ~ 614	3345.8 ~ 3358		
	25.5 ~ 25.67	960 ~ 1240			
	37.5 ~ 38.25				
	73 ~ 74.6				
	74.8 ~ 75.2				

▪ **FCC Part 15.205(b):** The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

Test Configuration



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

30MHz ~ 25GHz Data(802.11b & 11Mbps)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2386.000	H	Y	PK	66.08	-4.73	61.35	74.00	12.65
2387.360	H	Y	AV	55.15	-4.73	50.42	54.00	3.58
4823.873	H	Z	PK	56.74	2.23	58.97	74.00	15.03
4823.533	H	Z	AV	42.90	2.23	45.13	54.00	8.87
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4874.360	H	Z	PK	55.53	2.92	58.45	74.00	15.55
4873.674	H	Z	AV	42.10	2.92	45.02	54.00	8.98
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.583	H	Y	PK	69.97	-4.66	65.31	74.00	8.69
2483.555	H	Y	AV	51.39	-4.66	46.73	54.00	7.27
4924.010	H	Z	PK	55.12	2.67	57.79	74.00	16.21
4923.742	H	Z	AV	42.23	2.67	44.90	54.00	9.10
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-

Note.

1. No other spurious and harmonic emissions were found greater than listed emissions on above table.
2. Above listed point data is the worst case data.
3. Sample Calculation.

$$\text{Margin} = \text{Limit} - \text{Result} \quad / \quad \text{Result} = \text{Reading} + \text{T.F} \quad / \quad \text{T.F} = \text{AF} + \text{CL} - \text{AG}$$

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain

30MHz ~ 25GHz Data(802.11g & 54Mbps)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2388.930	H	Y	PK	64.58	-4.73	59.85	74.00	14.15
2390.000	H	Y	AV	46.21	-4.73	41.48	54.00	12.52
4825.000	H	Z	PK	51.20	2.23	53.43	74.00	20.57
4823.920	H	Z	AV	38.52	2.23	40.75	54.00	13.25
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4874.827	H	Z	PK	50.17	2.92	53.09	74.00	20.91
4873.923	H	Z	AV	36.28	2.92	39.20	54.00	14.80
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.528	H	Y	PK	65.29	-4.66	60.63	74.00	13.37
2483.500	H	Y	AV	46.95	-4.66	42.29	54.00	11.71
4923.958	H	Z	PK	51.21	2.67	53.88	74.00	20.12
4924.000	H	Z	AV	38.97	2.67	41.64	54.00	12.36
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-

Note.

1. No other spurious and harmonic emissions were found greater than listed emissions on above table..
2. Above listed point data is the worst case data.
3. Sample Calculation.

$$\text{Margin} = \text{Limit} - \text{Result} \quad / \quad \text{Result} = \text{Reading} + \text{T.F} \quad / \quad \text{T.F} = \text{AF} + \text{CL} - \text{AG}$$

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain

30MHz ~ 25GHz Data(802.11n HT20 & MCS0)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2388.130	H	Y	PK	63.13	-4.73	58.40	74.00	15.60
2390.000	H	Y	AV	46.22	-4.73	41.49	54.00	12.51
4823.830	H	Z	PK	47.87	2.23	50.10	74.00	23.90
4824.030	H	Z	AV	36.34	2.23	38.57	54.00	15.43
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4873.860	H	Z	PK	46.50	2.92	49.42	74.00	24.58
4873.742	H	Z	AV	34.46	2.92	37.38	54.00	16.62
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.995	H	Y	PK	59.42	-4.66	54.76	74.00	19.24
2483.500	H	Y	AV	43.02	-4.66	38.36	54.00	15.64
4924.600	H	Z	PK	47.01	2.67	49.68	74.00	24.32
4924.030	H	Z	AV	36.93	2.67	39.60	54.00	14.40
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-

Note.

1. No other spurious and harmonic emissions were found greater than listed emissions on above table..
2. Above listed point data is the worst case data.
3. Sample Calculation.

$$\text{Margin} = \text{Limit} - \text{Result} \quad / \quad \text{Result} = \text{Reading} + \text{T.F} \quad / \quad \text{T.F} = \text{AF} + \text{CL} - \text{AG}$$

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain

8.6 Power-line Conducted Emissions

Test Requirements and limit, §15.207 & RSS-Gen [7.2.2]

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network(LISN).

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to the test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.

■ RESULT PLOTS

AC Line Conducted Emissions (Graph)

Test Mode: 802.11b (2.4GHz Band)



Results of Conducted Emission



Digital EMC
Date : 2012-09-24

Model No. : DWD-300
Type :
Serial No. :
Test Condition :

Reference No. :
Power Supply : 120 V 50 Hz
Temp/Humi. : 23 °C 44 % R.H
Operator : H.H.LEE

Memo : WLAN 11B

LIMIT : CISPR22_B QP
CISPR22_B AV



AC Line Conducted Emissions (List)

Test Mode: 802.11b (2.4GHz Band)

Results of Conducted Emission

Digital EMC
Date : 2012-09-24

Model No. : DWD-300
Type :
Serial No. :
Test Condition :
Reference No. :
Power Supply : 120 V 50 Hz
Temp/Humi. : 23 'C 44 % R.H
Operator : H.H.LEE

Memo : WLAN 11B

LIMIT : CISPR22_B QP
CISPR22_B AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.15639	51.8	38.2	0.3	52.1	38.5	65.7	55.7	13.6	17.2	N
2	0.16819	45.8	25.6	0.2	46.0	25.8	65.0	55.0	19.0	29.2	N
3	0.21369	38.8	17.8	0.2	39.0	18.0	63.1	53.1	24.1	35.1	N
4	0.58028	40.2	28.0	0.2	40.4	28.2	56.0	46.0	15.6	17.8	N
5	3.38750	24.0	15.0	0.4	24.4	15.4	56.0	46.0	31.6	30.6	N
6	13.01950	24.5	17.0	0.9	25.4	17.9	60.0	50.0	34.6	32.1	N
7	0.15604	52.2	37.9	0.3	52.5	38.2	65.7	55.7	13.2	17.5	L1
8	0.16981	43.2	20.4	0.2	43.4	20.6	65.0	55.0	21.6	34.4	L1
9	0.21183	39.6	14.8	0.2	39.8	15.0	63.1	53.1	23.3	38.1	L1
10	0.57655	39.3	31.5	0.2	39.5	31.7	56.0	46.0	16.5	14.3	L1
11	3.25000	25.0	17.8	0.4	25.4	18.2	56.0	46.0	30.6	27.8	L1
12	13.69650	23.0	14.6	0.9	23.9	15.5	60.0	50.0	36.1	34.5	L1

■ RESULT PLOTS

AC Line Conducted Emissions (Graph)

Test Mode: 802.11g (2.4GHz Band)



Results of Conducted Emission



Digital EMC
Date : 2012-09-24

Model No. : DWD-300
Type :
Serial No. :
Test Condition :

Reference No. :
Power Supply : 120 V 50 Hz
Temp/Humi. : 23 °C 44 % R.H
Operator : H.H.LEE

Memo : WLAN 11G

LIMIT : CISPR22_B QP
CISPR22_B AV



AC Line Conducted Emissions (List)

Test Mode: 802.11g (2.4GHz Band)

Results of Conducted Emission

Digital EMC
Date : 2012-09-24

Model No. : DWD-300
Type :
Serial No. :
Test Condition :
Reference No. :
Power Supply : 120 V 50 Hz
Temp/Humi. : 23 'C 44 % R.H
Operator : H.H.LEE

Memo : WLAN 11G

LIMIT : CISPR22_B QP
CISPR22_B AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.15733	52.2	39.6	0.3	52.5	39.9	65.6	55.6	13.1	15.7	N
2	0.17600	46.8	23.6	0.2	47.0	23.8	64.7	54.7	17.7	30.9	N
3	0.58395	39.6	26.2	0.2	39.8	26.4	56.0	46.0	16.2	19.6	N
4	1.66900	25.8	14.9	0.3	26.1	15.2	56.0	46.0	29.9	30.8	N
5	13.11400	25.2	16.9	0.9	26.1	17.8	60.0	50.0	33.9	32.2	N
6	0.15686	52.6	39.5	0.3	52.9	39.8	65.6	55.6	12.7	15.8	L1
7	0.17716	46.6	23.4	0.2	46.8	23.6	64.6	54.6	17.8	31.0	L1
8	0.58173	38.8	26.8	0.2	39.0	27.0	56.0	46.0	17.0	19.0	L1
9	1.73450	23.4	14.0	0.3	23.7	14.3	56.0	46.0	32.3	31.7	L1
10	13.11150	22.4	14.6	0.9	23.3	15.5	60.0	50.0	36.7	34.5	L1

RESULT PLOTS

AC Line Conducted Emissions (Graph)

Test Mode: 802.11n HT20 (2.4GHz Band)



Results of Conducted Emission



Digital EMC
Date : 2012-09-24

Model No. : DWD-300
Type :
Serial No. :
Test Condition :

Reference No. :
Power Supply : 120 V 50 Hz
Temp/Humi. : 23 °C 44 % R.H
Operator : H.H.LEE

Memo : WLAN 11N

LIMIT : CISPR22_B QP
CISPR22_B AV



AC Line Conducted Emissions (List)

Test Mode: 802.11n HT20 (2.4GHz Band)

Results of Conducted Emission

Digital EMC
Date : 2012-09-24

Model No. : DWD-300
Type :
Serial No. :
Test Condition :
Reference No. :
Power Supply : 120 V 50 Hz
Temp/Humi. : 23 'C 44 % R.H
Operator : H.H.LEE

Memo : WLAN 11N

LIMIT : CISPR22_B QP
CISPR22_B AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.15643	52.3	39.5	0.3	52.6	39.8	65.7	55.7	13.1	15.9	N
2	0.19004	47.5	34.8	0.2	47.7	35.0	64.0	54.0	16.3	19.0	N
3	0.57946	40.4	26.9	0.2	40.6	27.1	56.0	46.0	15.4	18.9	N
4	0.77353	24.2	13.3	0.2	24.4	13.5	56.0	46.0	31.6	32.5	N
5	13.03600	24.4	16.8	0.9	25.3	17.7	60.0	50.0	34.7	32.3	N
6	0.15701	52.3	39.0	0.3	52.6	39.3	65.6	55.6	13.0	16.3	L1
7	0.18893	47.8	34.3	0.2	48.0	34.5	64.1	54.1	16.1	19.6	L1
8	0.57684	39.2	30.1	0.2	39.4	30.3	56.0	46.0	16.6	15.7	L1
9	0.77789	24.4	16.6	0.2	24.6	16.8	56.0	46.0	31.4	29.2	L1
10	13.06350	23.9	15.5	0.9	24.8	16.4	60.0	50.0	35.2	33.6	L1

8.7 Occupied Bandwidth

Test Requirements, RSS-Gen [4.6.1]

When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99% emission bandwidth, as calculated or measured.

■ TEST CONFIGURATION

Refer to the APPENDIX I.

■ TEST PROCEDURE

The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used given that a peak or peak hold may produce a wider bandwidth than actual.


■ TEST RESULTS: **Comply**

Test Mode	Data Rate	Frequency [MHz]	Test Results [MHz]
802.11b	11Mbps	2412	13.676
		2437	13.682
		2462	13.709
802.11g	54Mbps	2412	16.489
		2437	16.480
		2462	16.480
802.11n (20MHz)	MCS0	2412	17.635
		2437	17.640
		2462	17.628

RESULT PLOTS


Occupied Bandwidth (99%)

Test Mode: 802.11b & 1Mbps & 2412MHz




Occupied Bandwidth (99%)

Test Mode: 802.11b & 1Mbps & 2437MHz




Occupied Bandwidth (99%)

Test Mode: 802.11b & 1Mbps & 2462MHz




Occupied Bandwidth (99%)

Test Mode: 802.11g & 6Mbps & 2412MHz




Occupied Bandwidth (99%)

Test Mode: 802.11g & 6Mbps & 2437MHz




Occupied Bandwidth (99%)

Test Mode: 802.11g & 6Mbps & 2462MHz




Occupied Bandwidth (99%)

Test Mode: 802.11n & MCS0 & 2412MHz




Occupied Bandwidth (99%)

Test Mode: 802.11n & MCS0 & 2437MHz



Occupied Bandwidth (99%)

Test Mode: 802.11n & MCS0 & 2462MHz



9. LIST OF TEST EQUIPMENT

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent	E4440A	12/09/18	13/09/18	MY45304199
Spectrum Analyzer	Rohde Schwarz	FSQ26	12/01/09	13/01/09	200445
Spectrum Analyzer	Agilent	N9020A	12/01/09	13/01/09	MY49100833
Digital Multimeter	H.P	34401A	12/03/05	13/03/05	3146A13475, US36122178
Signal Generator	Rohde Schwarz	SMR20	12/03/05	13/03/05	101251
Vector Signal Generator	Rohde Schwarz	SMJ100A	12/01/09	13/01/09	100148
Thermo hygrometer	BODYCOM	BJ5478	12/01/13	13/01/13	090205-2
DC Power Supply	HP	6622A	12/03/05	13/03/05	3448A03760
High-pass filter	Wainwright	WHNX3.0	12/09/17	13/09/17	9
BILOG ANTENNA	SCHAFFNER	CBL 6112D	10/12/21	12/12/21	22609
HORN ANT	ETS	3115	12/02/20	14/02/20	6419
HORN ANT	A.H.Systems	SAS-574	11/03/25	13/03/25	154
Amplifier (22dB)	H.P	8447E	12/01/09	13/01/09	2945A02865
Amplifier (30dB)	Agilent	8449B	12/03/05	13/03/05	3008A00370
EMI TEST RECEIVER	R&S	ESU	12/03/05	13/03/05	100014
EMI TEST RECEIVER	R&S	ESCI	12/03/06	13/03/06	100364
CVCF	KIKUSUI	PCR1000L	12/09/15	13/09/15	14110610
LISN	R&S	ESH2-Z5	12/09/18	13/09/18	828739/006
RFI/Field intensity Meter	KYORITSU	KNM-2402	12/07/02	13/07/02	4N-170-3