

Equipment Description

The Equipment Under Test (EUT) is the LG Electronics U.S.A., Inc. LCD Monitor.

General Specification

Display	63.44 cm (25 inch) Flat Panel Active matrix-TFT LCD Anti-Glare coating Visible diagonal size : 63.44 cm 0.288 mm x 0.288 mm (Pixel pitch)		
Sync Input	Horizontal Freq. Vertical Freq. Input Form	30 kHz to 83 kHz (Automatic) 56 Hz to 75 Hz (Automatic) Separate Sync. Digital	
Video Input	Signal Input Input Form	15 pin D-Sub Connector DVI-D Connector (Digital) RGB Analog (0.7 Vp-p/ 75 ohm), Digital	
Resolution	Max Recommend	VESA 1920 x 1080 @ 60 Hz VESA 1920 x 1080 @ 60 Hz	
Plug&Play	DDC 2B(Analog,Digital)		
Power Consumption	On Mode Sleep Mode Off Mode	: < <	33 W(Typ.) 0.3 W 0.3 W
Dimensions & Weight	With Stand Width 59.4 cm (23.38 inch) Height 43.4 cm (17.08 inch) Depth 17.9 cm (7.04 inch)		Without Stand Width 59.4 cm (23.38 inch) Height 37.1 cm (14.60 inch) Depth 6.1 cm (2.40 inch)
	Weight(excl. packing)		4.4 kg (9.70 lb)
Range	Tilt : -5° to 15°		
Power Input	AC 100-240 V~ 50 / 60 Hz 1.2 A		
Environmental Conditions	Operating Conditions Temperature 10 °C to 35 °C Humidity 10 % to 80 % non-Condensing Storage Conditions Temperature -20 °C to 60 °C Humidity 5 % to 90 % non-Condensing		
Stand Base	Attached (), Detached (O)		
Power cord	Wall-outlet type		
NOTE ■ Information in this document is subject to change without notice.			

EUT Operating Conditions

- a. Setup the EUT and Peripherals as shown in Sec. 3.2 of the test report.
- b. Turn on the power of all equipment and the EUT.
- c. Set the contrast & brightness of EUT to maximum.
- d. PC system ran the self-test program "EMC Test" by windows XP and sent "H" characters to EUT through graphic card (we use white letters on a black background to represent all colors), the EUT's screen displayed and filled with "H" pattern by its resolution (Via D-Sub & DVI Input).
- e. Repeat above procedure from c to d for difference test mode.
- f. The other peripherals devices were driven and operated during the test.
- g. The test modes are as follows:

Test Mode
D-Sub 640*480@60Hz
D-Sub 1280*1024@75Hz
D-Sub 1680*1050@60Hz
D-Sub 1920*1080@60Hz
DVI 640*480@60Hz
DVI 1280*1024@75Hz
DVI 1680*1050@60Hz
DVI 1920*1080@60Hz