



FCC TEST REPORT

According to

47 CFR, Part 2, Part 15 and CISPR PUB. 22

Applicant	: LG Electronics USA
Address	: 1000 Sylvan Avenue Englewood Cliffs New Jersey United States
Manufacturer	: LG Electronics Nanjing Display Co., Ltd.
Address	: No.346,Yaoxin Road Economic & Technical Development Zone Nanjing China
Equipment	: LCD Monitor
Model No.	: IPS206TX
FCC ID	: BEJIPS206TX
Trade Name	: LG

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of **CerpPASS Technology Corp.** the test report shall not be reproduced except in full.
- The test report must not be used by the clients to claim product certification approval by **NVLAP** or any agency of the Government.



Table of Contents

1. Summary of Test Procedure and Test Result	5
2. Test Configuration of Equipment under Test.....	6
2.1. Feature of Equipment under Test	6
2.2. Test Manner.....	7
2.3. Description of Test System	8
2.4. Connection Diagram of Test System	8
2.5. General Information of Test	9
2.6. Measurement Uncertainty	9
3. Test of Conducted Emission	10
3.1. Test Limit	10
3.2. Test Procedures.....	10
3.3. Typical test Setup	11
3.4. Measurement equipment.....	11
3.5. Test Result and Data	12
4. Test of Radiated Emission	13
4.1. Test Limit	13
4.2. Test Procedures.....	14
4.3. Typical test Setup	14
4.4. Measurement equipment.....	15
4.5. Test Result and Data	16

Document history

[illegible]



FCC TEST REPORT

According to

47 CFR, Part 2, Part 15 and CISPR PUB. 22

Applicant	: LG Electronics USA
Address	: 1000 Sylvan Avenue Englewood Cliffs New Jersey United States
Manufacturer	: LG Electronics Nanjing Display Co., Ltd.
Address	: No.346,Yaoxin Road Economic & Technical Development Zone Nanjing China
Equipment	: LCD Monitor
Model No.	: IPS206TX
FCC ID	: BEJIPS206TX
Trade Name	: LG

I **HEREBY** CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 – 2003** and the energy emitted by this equipment was **passed** **CISPR PUB. 22 and FCC Part 15** in both radiated and conducted emission class B limits. Testing was carried out on Sep 17, 2010 at **CerpPASS Technology Corp.**

Documented By:

Approved By:

Sophie Li/ Administration

Hill Chen/ Technical director



1. Summary of Test Procedure and Test Result

Test Item	Normative References	Test Result
Conducted Emission	ANSI C63.4-2003 FCC Part 15 Subpart B	PASS
Radiated Emission	ANSI C63.4-2003 FCC Part 15 Subpart B	PASS



2. Test Configuration of Equipment under Test

2.1. Feature of Equipment under Test

LCD Monitor	Model No:	IPS206TX
ADAPTER 1#	Manufacturer:	LG
	Model No:	PA-1650-68
	Input:	100-240V~, 50-60Hz 2.0A
	Output:	19V $\overline{\text{---}}$ 3.42A
DC Cable	Non-Shielded, 1.5m, with one ferrite core bonded	
ADAPTER 2#	Manufacturer:	DELTA
	Model No:	EADP-40LB B
	Input:	100-240V~1.3A, 50-60Hz
	Output:	19V $\overline{\text{---}}$ 2.1A
DC Cable	Non-Shielded, 1.5m	
VGA Cable	Shielded, 1.8m, with two ferrite cores bonded	
VGA Cable	Shielded, 1.8m	
DVI Cable	Shielded, 1.8m, with two ferrite cores bonded	
DVI Cable	Shielded, 1.8m	
Power Supply cable	Non-Shielded, 1.8m	
Note : The VGA Cable and DVI Cable are alternative on selling.		



2.2. Test Manner


Test Software	
a	During testing, the interface cables and equipment positions were varied according to ANSI C63.4.
b	The complete test system included the PC, USB Mouse, USB Keyboard, Printer and EUT for EMI test.
c	During the test, setup up the EUT and all system, turn on the power of all Equipments, run the EMC test software "H", set the contrast control to maximum, set the brightness control to maximum, use white letters on a black background to represent all colors, make the EUT at the test mode and it is normal operation, and then test.
The pre-test modes	
	Test Mode 1: Full system (VGA mode 1024*768@60Hz) with ADAPTER 1#
	Test Mode 2: Full system (VGA mode 1600*900@60Hz) with ADAPTER 1#
	Test Mode 3: Full system (VGA mode 720*400@70Hz) with ADAPTER 1#
	Test Mode 4: Full system (DVI mode 1024*768@60Hz) with ADAPTER 1#
	Test Mode 5: Full system (DVI mode 1600*900@60Hz) with ADAPTER 1#
	Test Mode 6: Full system (DVI mode 720*400@70Hz) with ADAPTER 1#
	Test Mode 7: Full system (VGA mode 1024*768@60Hz) with ADAPTER 2#
	Test Mode 8: Full system (VGA mode 1600*900@60Hz) with ADAPTER 2#
	Test Mode 9: Full system (VGA mode 720*400@70Hz) with ADAPTER 2#
	Test Mode 10: Full system (DVI mode 1024*768@60Hz) with ADAPTER 2#
	Test Mode 11: Full system (DVI mode 1600*900@60Hz) with ADAPTER 2#
	Test Mode 12: Full system (DVI mode 720*400@70Hz) with ADAPTER 2#
Select the worst case of the pre-test modes as the final test mode	
	Test Mode 1: Full system (VGA mode 1024*768@60Hz) with ADAPTER 1#



2.3. Description of Test System

No	Device	Manufacturer	Model No.	Description
1	PC	Dell	DCSM	N/A
2	USB Keyboard	DELL	SK-8115	N/A
3	USB Mouse	DELL	G0K02XYK	N/A
4	Printer	Epson	EX3	N/A

2.4. Connection Diagram of Test System



No	Cable	Quantity	Description
A	VGA Cable	1	Shielded, 1.8m, with two ferrite cores bonded
B	DVI Cable	1	Shielded, 1.8m
C	USB Cable	1	Shielded, 1.8m, with one ferrite core bonded
D	USB Cable	1	Shielded, 1.5m
E	Parallel Cable	1	Shielded, 1.8m



2.5. General Information of Test

Test Site:	CerpPASS Technology Corp.
Performand Location :	No.66,Tangzhuang Road, Suzhou Industrial Park, Jiangsu 215006, China
NVLAP LAB Code :	200814-0
FCC Registration Number :	916572, 331395
IC Registration Number :	7290A-1, 7290A-2
VCCI Registration Number :	T-343 for Telecommunication Test C-2919 for Conducted emission test R-2670 for Radiated emission test below 1GHz G-227 for Radiated emission test above 1GHz
Frequency Range Investigated :	Conducted Emission Test: from 150kHz to 30 MHz Radiated Emission Test: from 30 MHz to 1,000 MHz Radiated Emission Test: from 1GHz to 18GHz
Test Distance :	The test distance of radiated emission below 1GHz from antenna to EUT is 3 M. The test distance of radiated emission above 1GHz from antenna to EUT is 3 M.

Laboratory accreditation



2.6. Measurement Uncertainty

Conducted Emission		
The measurement uncertainty is evaluated as ± 2.71 dB.		
Radiated Emission		
(30MHz -1000MHz)	Horizontal	The measurement uncertainty is evaluated as ± 3.89 dB.
	Vertical	The measurement uncertainty is evaluated as ± 3.59 dB.
(1G-18GHz)	Horizontal	The measurement uncertainty is evaluated as ± 2.31 dB.
	Vertical	The measurement uncertainty is evaluated as ± 2.15 dB.



3. Test of Conducted Emission

3.1. Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2003 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

3.2. Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



3.3. Typical test Setup




3.4. Measurement equipment

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date
Test Receiver	R&S	ESCI	100565	2010.01.15
AMN	R&S	ESH2-Z5	100182	2010.06.23
Two-Line V-Network	R&S	ENV216	100325	2010.04.18
ISN	FCC	FCC-TLISN-T2-02	20379	2010.06.23
ISN	FCC	FCC-TLISN-T4-02	20380	2010.06.23
ISN	FCC	FCC-TLISN-T8-02	20381	2010.06.23
Current Probe	R&S	EZ-17	100303	2010.06.23
Attenuator	R&S	ESH3-Z2	100529	2010.01.11
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-004	2010.08.14



3.5. Test Result and Data

Test Mode :	Mode 1: Full system (VGA mode 1024*768@60Hz) with ADAPTER 1#		
AC Power :	AC 120V/60Hz	Phase :	L&N
EUT :	LCD Monitor	Model No.:	IPS206TX
Temperature :	22°C	Humidity :	50%
Pressur(mbar) :	1002	Date :	2010/09/17



Frequency MHz	Line Phase	Reading dB(uV) QP	Reading dB(uV) AV	Factor dB	Level dB(uV) QP	Level dB(uV) AV	Limit dB(uV) QP	Limit dB(uV) AV	Margin dB QP	Margin dB AV	Pass/Fail
0.150	L1	38.7	19.1	19.9	58.6	39.0	66.0	56.0	7.4	17.0	Pass
0.21063	L1	29.2	12.6	19.9	49.1	32.5	63.2	53.2	14.1	20.7	Pass
1.07693	L1	2.7	-5.8	19.7	22.4	13.9	56.0	46.0	33.6	32.1	Pass
3.28242	L1	7.5	0.9	19.7	27.2	20.6	56.0	46.0	28.8	25.4	Pass
10.9554	L1	12.5	5.4	19.7	32.2	25.1	60.0	50.0	27.8	24.9	Pass
12.5376	L1	10.2	3.4	19.8	30.0	23.2	60.0	50.0	30.0	26.8	Pass
0.150	N	38.1	18.5	19.5	57.6	38.0	66.0	56.0	8.4	18.0	Pass
0.20927	N	28.8	12.2	19.5	48.3	31.7	63.2	53.2	14.9	21.5	Pass
4.4246	N	10.3	1.7	19.6	29.9	21.3	56.0	46.0	26.1	24.7	Pass
10.7516	N	11.9	4.7	19.9	31.8	24.6	60.0	50.0	28.2	25.4	Pass
1.14638	N	0.9	-7.1	19.4	20.3	12.3	56.0	46.0	35.7	33.7	Pass
22.546	N	10.2	8.1	19.9	30.1	28.0	60.0	50.0	29.9	22.0	Pass

Note: Measurement Level = Reading Level + Correct Factor

Test engineer: cheney yan



4. Test of Radiated Emission

4.1. Test Limit

Radiated emissions from 30 MHz to 1,000 MHz were measured with a bandwidth of 120 kHz according to the methods defines in ANSI C63.4-2003. The EUT was placed on a nonmetallic stand in the open-field site, 0.8 meter above the ground plane, as shown in section 3.2. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (m)	Level (dBuV/m)	Level (dBuV/m)
30 - 88	3	40(QP)	N/A
88 - 216	3	43(QP)	N/A
216-960	3	46(QP)	N/A
960-1000	3	54(QP)	N/A
1000-18000	3	74(PK)	54(AV)

For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the below table.

Frequency (MHz)	Distance Meters	Radiated (dB μ V/ M)
30-230	10	30
230-1000	10	37





4.2. Test Procedures

- The EUT was placed on a Rota table top 0.8 meter above ground.
- The EUT and its simulators are placed on the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters or 1 meter.
- The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.
- Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated on radiated measurement.
- Radiated emissions were investigated over the frequency range from 30MHz to 1GHz using a receiver bandwidth of 120KHz and the frequency range from 1GHz to 18GHz using a receiver bandwidth of 1MHz.

4.3. Typical test Setup

Below 1GHz Test Setup



**Above 1GHz Test Setup****4.4. Measurement equipment**


Instrument	Model No.	Manufacturer	Serial No.	Calibration Date
EMI Test Receiver	R&S	ESCI	100563	2010.06.23
H64 Amplifier	HP	8447F	3113A05582	2010.08.14
Preamplifier	Agilent	8449B	ED-HE-EMI-077	2010.02.10
Ultra Broadband Antenna	R&S	HL562	100363	2009.11.03
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-619	2009.11.10
Spectrum Analyzer	R&S	FSP40	100324	2010.08.14
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2010.08.17



4.5. Test Result and Data

Under 1G

Engineer : Fred	
Site : EMC Lab AC 102	Time : 2010/09/15 - 17:35
Limit : FCC_CLASS_B_03M_QP	Margin : 6
EUT : LCD Monitor	Probe : (30-1000MHz) - HORIZONTAL
Power : AC 120V/60Hz	Note : Mode 1: Full system (VGA mode 1024*768@60Hz) with ADAPTER 1#




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		34.245	-5.940	34.527	28.587	-11.413	40.000	QUASIPeAK	200.000	158.600
2	*	189.651	-14.247	48.947	34.700	-8.800	43.500	QUASIPeAK	186.300	142.700
3		201.987	-13.160	45.827	32.667	-10.833	43.500	QUASIPeAK	200.000	24.900
4		299.631	-11.277	41.724	30.448	-15.552	46.000	QUASIPeAK	200.000	248.700
5		432.817	-7.483	36.413	28.931	-17.069	46.000	QUASIPeAK	200.000	342.800
6		592.547	-3.011	31.824	28.813	-17.187	46.000	QUASIPeAK	200.000	318.700

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Engineer : Fred	
Site : EMC Lab AC 102	Time : 2010/09/15 - 17:35
Limit : FCC_CLASS_B_03M_QP	Margin : 6
EUT : LCD Monitor	Probe : (30-1000MHz) - VERTICAL
Power : AC 120V/60Hz	Note : Mode 1: Full system (VGA mode 1024*768@60Hz) with ADAPTER 1#




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		144.152	-9.931	42.400	32.469	-11.031	43.500	QUASIPeAK	100.000	152.800
2	*	196.567	-8.252	43.595	35.344	-8.156	43.500	QUASIPeAK	100.000	243.800
3		203.015	-6.798	40.980	34.181	-9.319	43.500	QUASIPeAK	100.000	345.700
4		433.128	-7.130	43.562	36.432	-9.568	46.000	QUASIPeAK	100.000	12.800
5		542.514	-5.485	38.675	33.191	-12.809	46.000	QUASIPeAK	100.000	51.800
6		789.561	2.401	30.253	32.654	-13.346	46.000	QUASIPeAK	100.000	314.200

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Engineer : Fred	
Site : EMC Lab AC 102	Time : 2010/09/15 - 19:58
Limit : FCC_15_03M_PK	Margin : 6
EUT : LCD Monitor	Probe : (1-18GHz) - HORIZONTAL
Power : AC 120V/60Hz	Note : Mode 1: Full system (VGA mode 1024*768@60Hz) with ADAPTER 1#




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1621.370	-3.949	57.320	53.371	-20.629	74.000	PEAK	200.000	315.800
2		2975.480	1.556	56.870	58.426	-15.574	74.000	PEAK	200.000	21.700
3	*	3847.590	4.506	54.470	58.976	-15.024	74.000	PEAK	400.000	158.700

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Engineer : Fred	
Site : EMC Lab AC 102	Time : 2010/09/15 - 19:58
Limit : FCC_15_03M_AV	Margin : 6
EUT : LCD Monitor	Probe : (1-18GHz) - HORIZONTAL
Power : AC 120V/60Hz	Note : Mode 1: Full system (VGA mode 1024*768@60Hz) with ADAPTER 1#




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1621.370	-3.949	43.130	39.181	-14.819	54.000	AVERAGE	200.000	315.800
2	*	2975.480	1.556	42.590	44.146	-9.854	54.000	AVERAGE	200.000	21.700
3		3847.590	4.506	39.280	43.786	-10.214	54.000	AVERAGE	400.000	158.700

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Engineer : Fred	
Site : EMC Lab AC 102	Time : 2010/09/15 - 19:58
Limit : FCC_15_03M_PK	Margin : 6
EUT : LCD Monitor	Probe : (1-18GHz) - VERTICAL
Power : AC 120V/60Hz	Note : Mode 1: Full system (VGA mode 1024*768@60Hz) with ADAPTER 1#




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1698.430	-3.988	56.980	52.991	-21.009	74.000	PEAK	100.000	345.800
2		2798.540	1.360	57.320	58.679	-15.321	74.000	PEAK	100.000	152.100
3	*	4103.780	5.038	54.740	59.778	-14.222	74.000	PEAK	100.000	55.400

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Engineer : Fred	
Site : EMC Lab AC 102	Time : 2010/09/15 - 19:58
Limit : FCC_15_03M_AV	Margin : 6
EUT : LCD Monitor	Probe : (1-18GHz) - VERTICAL
Power : AC 120V/60Hz	Note : Mode 1: Full system (VGA mode 1024*768@60Hz) with ADAPTER 1#



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1	1698.430	-3.988	39.270	35.281	-18.719	54.000	AVERAGE	100.000	345.800
2	2798.540	1.360	40.470	41.829	-12.171	54.000	AVERAGE	100.000	152.100
3	* 4103.780	5.038	38.270	43.308	-10.692	54.000	AVERAGE	100.000	55.400

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Test engineer: Fred Guo