



FCC EVALUATION REPORT FOR CERTIFICATION

Manufacturer : LG Electronics Inc.

642, Jinpyung-Dong, Gumi-Si

Gyeongsangbuk-Do, 730-360, Korea

Attn: Mr. Sang-Wook Lee, Chief research engineer

Date of Issue : May 16, 2007

Test Report No. : GETEC-E3-07-039

**Test Site : Gumi College EMC Center
(Registration No.: 100749)**

FCC ID.: BEJL206WUQ

Applicant.: LG Electronics Inc.

Rule Part(s)	: FCC Part 15 Subpart B
Equipment Class	: Class B computing device peripheral (JBP)
EUT Type	: 20.1" LCD Monitor
Type of Authority	: Certification
Model No.	: L206WUQ
Trade name	: LG


This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003 / Canadian standard ICES-003

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by,

Reviewed by,


Jae-Hoon Jeong, Senior Engineer
GUMI College EMC center


Tae-Sig Park, Technical Manager
GUMI College EMC center

CONTENTS

1. GENERAL INFORMATION	3
2. INTRODUCTION	4
3. PRODUCT INFORMATION	5
3.1 DESCRIPTION OF EUT.....	5
3.2 SUPPORT EQUIPMENT / CABLES USED	6
3.3 MODIFICATION ITEM(S)	6
4. DESCRIPTION OF TESTS	7
4.1 TEST CONDITION.....	7
4.2 CONDUCTED EMISSION	8
4.3 RADIATED EMISSION	9
5. CONDUCTED EMISSION.....	10
5.1 OPERATING ENVIRONMENT	10
5.2 TEST SET-UP.....	10
5.3 MEASUREMENT UNCERTAINTY	10
5.4 LIMIT	11
5.5 TEST EQUIPMENT USED	11
5.6 TEST DATA FOR POWER LINE CONDUCTED EMISSION	12
6. RADIATED EMISSION	17
6.1 OPERATING ENVIRONMENT	17
6.2 TEST SET-UP.....	17
6.3 MEASUREMENT UNCERTAINTY	17
6.4 LIMIT	18
6.5 TEST EQUIPMENT USED	18
6.6 TEST DATA FOR RADIATED EMISSION	19
7. SAMPLE CALCULATIONS.....	24
7.1 EXAMPLE 1 :	24
7.2 EXAMPLE 2 :	24
8. RECOMMENDATION & CONCLUSION.....	25
APPENDIX A – ATTESTATION STATEMENT	
APPENDIX B – PLOTS OF CONDUCTED EMISSIONS	
APPENDIX C – ID SAMPLE LABEL & LOCATION	
APPENDIX D – BLOCK DIAGRAM	
APPENDIX E – TEST SET-UP PHOTOGRAPHS	
APPENDIX F – EXTERNAL PHOTOGRAPHS	
APPENDIX G –INTERNAL PHOTOGRAPHS	
APPENDIX H – USER’S MANUAL	

Scope: Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and / or unintentional radiators for compliance with technical rules and regulations of the Federal Communications Commission.

1. General Information

Applicant: LG Electronics Inc.

Applicant Address: 642, Jinpyung-Dong, Gumi-Si, Gyeongsangbuk-do, Korea

Manufacturer: LG Electronics Inc.

Manufacturer Address: 642, Jinpyung-Dong, Gumi-Si, Gyeongsangbuk-do, Korea

Contact Person: Mr. Sang -Wook Lee, Chief research engineer

Tel No.: +82-54-470-5640

- **FCC ID** BEJL206WUQ
- **EUT Type** 20.1" LCD Monitor
- **Model No.** L206WUQ
- **Trade Name** LG
- **Serial No.** Proto type
- **Rule Part(s)** FCC Part 15 Subpart B
- **Type of Authority** Certification
- **Test Procedure(s)** ANSI C63.4 (2003) / Canadian standard ICES-003
- **Dates of Test** May 9 ~ 11, 2007
- **Place of Test** **Gumi College EMC Center** (FCC Registration No.: 100749)
407, Bugok-Dong, Gumi-si, Gyeongsangbuk-Do, Korea
- **Test Report No.** GETEC-E3-07-039
- **Dates of Issue** May 16, 2007

2. Introduction

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Nose Emissions From Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ASNI C63.4-2003) was used in determining radiated and conducted emissions emanating from **LG Electronics Inc. 20.1" LCD Monitor (Model No.: L206WUQ)**

These measurement tests were conducted at **Gumi College EMC Center**.

The site address is 407, Bugok-Dong, Gumi-si, Gyeongsangbuk-Do, Korea

This test site is one of the highest point of Gumi 1 college at about 200 kilometers away from Seoul city and 40 kilometers away from Daegu city. It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 on October 19, 1992



Fig 1. The map above shows the Gumi College in vicinity area.

3. Product Information

3.1 Description of EUT

The Equipment Under Test (EUT) is the **LG Electronics Inc. 20.1" LCD Monitor (Model No.: L206WUQ)**
FCC ID.: BEJL206WUQ

Display	20.1 inches (51.133 cm) Flat Panel Active matrix-TFT LCD Anti-Glare coating 20.1 inches viewable 0.258*0.258 mm pixel pitch	
Sync Input	Horizontal Freq.	Analog : 30 - 83 kHz (Automatic) Digital : 30 - 83 kHz (Automatic) USB : 30 - 83 kHz (Automatic)
	Vertical Freq.	56 - 75 Hz (Automatic)
	Input Form	Separate TTL, Positive/Negative SOG (Sync On Green) Digital (HDCP)
Video Input	Signal Input	15 pin D-Sub Connector DVI - D Connector (Digital) USB Connector (Digital)
	Input Form	RGB Analog (0.7 Vp-p/ 75 ohm) Digital, USB
Resolution	Max	Analog : VESA 1680 x 1050 @60 Hz Digital : VESA 1680 x 1050 @60 Hz USB : VESA 1680 x 1050 @60 Hz
	Recommend	VESA 1680 x 1050 @60 Hz
Plug&Play	DDC 2B	
Power Consumption	On Mode	: 50 W(Typ.)
	Sleep Mode	≤ 2 W
	Off Mode	≤ 1 W
Dimensions & Weight	With Stand	
	Width	47.10 cm / 18.54 inches
	Height	42.00 cm / 16.54 inches
	Depth	27.11 cm / 10.67 inches
	Net	5.8 kg (12.79 lbs)
Tilt Range	Tilt Range	-3°~17° (Head)
	Height Range	5.51inch (140.0mm)
	Rotate	90° clockwise (Landscape->Portrait)
Power Input	AC 100-240V~ 50/60Hz 1.2A	

3.2 Support Equipment / Cables used

3.2.1 Used Support Equipment

Description	Manufacturer	Model No.	S/N & FCC ID
PC	Hewlett Packard	D530	S/N: CNG34800PY FCC ID: DoC
Video card	ATI	ATI RV360(9600)	S/N: SN0402017176 FCC ID: DoC
Printer	Hewlett Packard	970CXI	S/N: MY9B01F1FG FCC ID: DoC
Serial Mouse	LOGITECH	M-S69	S/N: 334684-108 FCC ID: JNZ211443
Key-board	COMPAQ	166516-AD6	S/N: B13BBOR391006D FCC ID: AQ6-23K15
Joystick	Microsoft	X05-92626	S/N: 9262600296169 FCC ID: DoC

See “Appendix E – Test Setup Photographs” for actual system test set-up

3.2.2 Used Cable(s)

Cable No.	Condition	Description
Power cable	Connected to the EUT	1.8m unshielded
Video cable(D-sub)	Connected to the EUT and PC	1.8m shielded with two ferrite cores
Video cable(DVI-D)	Connected to the EUT and PC	1.8m shielded with two ferrite cores
Video cable(USB)	Connected to the UET and PC	1.8m shielded
Joystick cable	Connected to the EUT	1.8m shielded

3.3 Modification Item(s)

- None

4. Description of tests

4.1 Test Condition

The EUT was installed, arranged and operated in a manner that is most representative of equipment as typically used. The measurements were carried out while varying operating modes and cable positions within typically arrangement to determine maximum emission level.

The representative and worst test mode(s) were noted in the test report.

- Test Voltage / Frequency : AC 120V / 60Hz
- Test Mode(s)
 - . Monitor mode
 - . Radiated emission : 1680*1050/60Hz (Analog), 1680*1050/60Hz (Digital), 1680*1050/60Hz (USB)
 - . Conducted emission: 1680*1050/60Hz (Analog), 1680*1050/60Hz (Digital), 1680*1050/60Hz (USB),
1024*768/75Hz (Analog), 640*480/60Hz (Analog)
- Operating test pattern
 - . "H" character scrolling mode (Font size: 10)
 - . Black background white character
 - . Brightness and contrast was adjusted as maximum level

4.2 Conducted Emission

The Line conducted emission test facility is inside a 4×8×2.5 meter shielded enclosure.

The EUT was placed on a non-conducting 1.0 by 1.5 meter table, which is 0.8 meters in height and 0.4 meters away from the vertical wall of the shielded enclosure.

The EUT is powered from the Rohde & Schwarz LISN (ESH2-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH3-Z5). Powers to the LISN are filtered by high-current high insertion loss power line filter.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

The RF output of the LISN was connected to the EMI test receiver (Rohde & Schwarz, ESCS30).

The EMI test receiver was scanned from 150 kHz to 30MHz with 20msec sweep time to determine the frequency producing the maximum EME from the EUT. The frequency producing the maximum level was re-examined using Quasi-Peak mode of the EMI test receiver.

The bandwidth of Quasi-peak mode was set to 9 kHz. Each emission was maximized consistent with typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum diagram emission. Excess cable lengths were bundled at center with 30 – 40 centi-meters.

Each EME reported was calibrated using the R/S signal generator




Fig 2. Impedance of LISN

4.3 Radiated Emission

Preliminary measurements were conducted 3m semi anechoic chamber using broadband antennas to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The technology configuration, mode of operation and turntable azimuth with respect to antenna was note for each frequency found.

The spectrum was scanned from 30 to 1000MHz using bicornical log antenna (Schwarzbeck, VULB9160). Above 1GHz, horn antenna (Schwarzbeck, BBHA9120D) was used.

Final measurements were made outdoors at 3m/10m-test range.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was re-examined and investigated using EMI test receiver. The detector function was set to CISPR quasi-peak mode average mode and the bandwidth of the receiver was set to 120 kHz or 1MHz depending on the frequency or type of signal.

The EUT, support equipment and interconnecting cables were reconfigured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8m high non-metallic 1.0×1.5 meter table.

The turntable containing the test sample was rotated; the antenna height was varied 1 to 4 meter and stopped at the azimuth or height producing the maximum emission.

Each EME reported was calibrated using the R/S signal generator




Fig 3. Dimensions of Open Site Test Area

5. Conducted Emission

5.1 Operating environment

Temperature : 22 °C
Relative humidity : 35 %

5.2 Test set-up

The conducted emission measurements were performed in the shielded room.

The EUT was placed on wooden table, 0.8m heights above the floor, 0.4m from the reference ground plane (GRP) wall and 0.8m from AMN.

AMN is bonded on horizontal reference ground plane.

The ground plane, which was electrically bonded to the shield room, ground system and all power lines entering the shield room, were filtered.

5.3 Measurement uncertainty

The measurement uncertainty was calculated in accordance with ISO "Guide to the expression of uncertainty in measurement".

The measurement uncertainty was given with a confidence of 95%.

Contribution	Probability Distribution	Uncertainty (±dB)	
		Power Port	Communication port
Receiver specification	Rectangular	0.50	0.50
LISN coupling specification	Rectangular	1.50	
ISN coupling specification	Rectangular		1.50
Mismatch LISN VRC : $\Gamma_l =$ 0.20 ISN VRC : $\Gamma_l =$ 0.20 ATT VRC(IN) : $\Gamma_g =$ 0.03 Uncertainty limits $20\log(1 \pm \Gamma_l \Gamma_g)$	U-shaped	0.05 -0.05	0.05 -0.05
Mismatch Receiver VRC : $\Gamma_l =$ 0.09 ATT VRC : $\Gamma_g =$ 0.11 Uncertainty limits $20\log(1 \pm \Gamma_l \Gamma_g)$	U-shaped	0.09 -0.09	0.09 -0.09
System repeatability	Std Deviation	0.55	0.55
Cable and input attenuator calibration	Normal (k=2)	0.08	0.08
Repeatability of EUT			
Combined standard uncertainty $U_c(y)$	Normal	1.07 -1.07	1.07 -1.07
Extended uncertainty U	Normal (k=2)	2.15 -2.15	2.15 -2.15

5.4 Limit

RFI Conducted	FCC Limit(dB) Class B	
Freq. Range	Quasi-Peak	Average
150kHz – 0.5MHz	66 – 56*	56 – 46*
0.5MHz – 5MHz	56	46
5MHz – 30MHz	60	50
*Limits decreases linearly with the logarithm of frequency.		

5.5 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Due to calibration
■ - ESCS30	Rohde & Schwarz	EMI test receiver	839809/003	11. 27. 2007
■ - ESH3-Z5	Rohde & Schwarz	Artificial mains network	838979/020	12. 09. 2007
■ - ESH2-Z5	Rohde & Schwarz	Artificial mains network	829991/009	12. 09. 2007

5.6 Test data for power line conducted emission

- Test Date : May 9, 2007
 - Resolution bandwidth : 9 kHz
 - Frequency range : 0.15MHz ~ 30MHz

◆ Test resolution: 1680*1050/60Hz (Analog)

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.155	0.11	-0.15	L1	65.73	45.3	45.26	55.73	27.3	27.26	20.47	28.47
0.200	0.12	-0.23	L1	63.61	46.2	46.09	53.61	40.4	40.29	17.52	13.32
0.395	0.13	-0.12	L1	57.96	35.5	35.51	47.96	32.3	32.31	22.45	15.65
0.595	0.14	-0.23	L1	56.00	32.9	32.81	46.00	31.3	31.21	23.19	14.79
0.720	0.13	-0.23	N	56.00	32.0	31.90	46.00	30.4	30.30	24.10	15.70
1.185	0.12	-0.25	N	56.00	31.1	30.98	46.00	28.8	28.68	25.02	17.32
1.315	0.12	-0.26	N	56.00	29.7	29.56	46.00	28.6	28.46	26.44	17.54
1.780	0.10	-0.30	N	56.00	31.3	31.10	46.00	29.5	29.30	24.90	16.70
2.240	0.15	-0.28	L1	56.00	30.9	30.78	46.00	29.6	29.48	25.22	16.52
3.030	0.09	-0.14	N	56.00	37.8	37.75	46.00	26.6	26.55	18.25	19.45
4.740	0.19	-0.15	L1	56.00	34.9	34.93	46.00	34.1	34.13	21.07	11.87
6.845	0.22	-0.10	L1	60.00	32.0	32.11	50.00	30.4	30.51	27.89	19.49
9.855	0.23	0.00	L1	60.00	29.7	29.93	50.00	27.4	27.63	30.07	22.37
11.270	0.28	0.00	L1	60.00	22.1	22.38	50.00	26.1	26.38	37.62	23.62

*Comment : Pol : H (Live), N(Neut)

Insertion Loss : Insertion Loss of LISN

Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

◆ Test resolution: 1680*1050/60Hz (Digital)

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.150	0.11	-0.14	L1	66.00	45.1	45.07	56.00	26.2	26.17	20.93	29.83
0.265	0.11	-0.19	N	61.27	40.9	40.82	51.27	37.2	37.12	20.46	14.16
0.465	0.12	-0.16	N	56.60	32.7	32.66	46.60	27.4	27.36	23.94	19.24
0.595	0.12	-0.23	N	56.00	31.0	30.90	46.00	29.1	29.00	25.10	17.00
0.720	0.13	-0.23	N	56.00	31.8	31.70	46.00	30.3	30.20	24.30	15.80
1.315	0.12	-0.26	N	56.00	29.0	28.86	46.00	28.2	28.06	27.14	17.94
1.780	0.15	-0.30	L1	56.00	32.4	32.25	46.00	30.1	29.95	23.75	16.05
2.245	0.15	-0.28	L1	56.00	29.8	29.68	46.00	28.5	28.38	26.32	17.62
2.835	0.16	-0.17	L1	56.00	36.0	35.99	46.00	28.7	28.69	20.01	17.31
3.030	0.09	-0.14	N	56.00	38.0	37.95	46.00	27.4	27.35	18.05	18.65
4.285	0.18	-0.15	L1	56.00	32.7	32.73	46.00	33.1	33.13	23.27	12.87
6.525	0.21	-0.13	L1	60.00	31.0	31.08	50.00	30.7	30.78	28.92	19.22
9.855	0.23	0.00	L1	60.00	29.7	29.93	50.00	27.2	27.43	30.07	22.57
10.505	0.25	0.00	L1	60.00	27.3	27.55	50.00	25.5	25.75	32.45	24.25

*Comment : Pol : H (Live), N(Neut)

Insertion Loss : Insertion Loss of LISN

Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

◆ Test resolution: 1680*1050/60Hz (USB)

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.150	0.11	-0.14	L1	66.00	45.3	45.27	56.00	26.5	26.47	20.73	29.53
0.265	0.11	-0.19	N	61.27	41.4	41.32	51.27	37.3	37.22	19.96	14.06
0.465	0.12	-0.16	N	56.60	33.5	33.46	46.60	32.2	32.16	23.14	14.44
0.720	0.14	-0.23	L1	56.00	26.3	26.21	46.00	26.5	26.41	29.79	19.59
0.925	0.13	-0.23	N	56.00	27.9	27.80	46.00	27.8	27.70	28.20	18.30
1.185	0.12	-0.25	N	56.00	30.6	30.48	46.00	29.6	29.48	25.52	16.52
1.780	0.10	-0.30	N	56.00	32.4	32.20	46.00	24.0	23.80	23.80	22.20
2.835	0.16	-0.17	L1	56.00	35.8	35.79	46.00	29.7	29.69	20.21	16.31
3.030	0.16	-0.14	L1	56.00	38.3	38.32	46.00	29.7	29.72	17.68	16.28
4.610	0.18	-0.15	L1	56.00	34.1	34.13	46.00	33.9	33.93	21.87	12.07
6.785	0.22	-0.11	L1	60.00	32.8	32.91	50.00	30.6	30.71	27.09	19.29
9.975	0.23	0.00	L1	60.00	28.4	28.63	50.00	26.1	26.33	31.37	23.67
10.490	0.25	0.00	L1	60.00	26.7	26.95	50.00	24.7	24.95	33.05	25.05
21.930	0.85	0.13	L1	60.00	28.2	29.17	50.00	22.6	23.57	30.83	26.43

*Comment : Pol : H (Live), N(Neut)

Insertion Loss : Insertion Loss of LISN

Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

◆ Test resolution: 1024*768/75Hz (Analog)

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.150	0.11	-0.14	L1	66.00	45.4	45.37	56.00	27.2	27.17	20.63	28.83
0.265	0.11	-0.19	N	61.27	42.4	42.32	51.27	37.7	37.62	18.96	13.66
0.395	0.13	-0.12	L1	57.96	35.3	35.31	47.96	32.4	32.41	22.65	15.55
0.465	0.12	-0.16	N	56.60	32.4	32.36	46.60	30.8	30.76	24.24	15.84
0.720	0.13	-0.23	N	56.00	32.1	32.00	46.00	30.4	30.30	24.00	15.70
1.185	0.12	-0.25	N	56.00	30.8	30.68	46.00	28.7	28.58	25.32	17.42
1.780	0.15	-0.30	L1	56.00	30.9	30.75	46.00	29.2	29.05	25.25	16.95
2.240	0.15	-0.28	L1	56.00	31.0	30.88	46.00	29.7	29.58	25.12	16.42
2.830	0.09	-0.17	N	56.00	35.5	35.42	46.00	27.3	27.22	20.58	18.78
3.030	0.09	-0.14	N	56.00	37.4	37.35	46.00	27.0	26.95	18.65	19.05
4.740	0.19	-0.15	L1	56.00	35.2	35.23	46.00	34.6	34.63	20.77	11.37
6.580	0.21	-0.13	L1	60.00	32.8	32.89	50.00	32.1	32.19	27.11	17.81
9.975	0.23	0.00	L1	60.00	28.7	28.93	50.00	27.0	27.23	31.07	22.77
11.235	0.28	0.00	L1	60.00	27.0	27.28	50.00	25.8	26.08	32.72	23.92

*Comment : Pol : H (Live), N(Neut)

Insertion Loss : Insertion Loss of LISN

Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

◆ Test resolution: 640*480/60Hz (Analog)

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.155	0.11	-0.15	L1	65.73	44.2	44.16	55.73	26.0	25.96	21.57	29.77
0.330	0.11	-0.16	N	59.45	38.7	38.66	49.45	36.8	36.76	20.80	12.70
0.465	0.12	-0.16	N	56.60	32.4	32.36	46.60	28.8	28.76	24.24	17.84
0.720	0.13	-0.23	N	56.00	32.1	32.00	46.00	30.4	30.30	24.00	15.70
1.185	0.12	-0.25	N	56.00	30.8	30.68	46.00	28.7	28.58	25.32	17.42
1.315	0.12	-0.26	N	56.00	29.6	29.46	46.00	28.3	28.16	26.54	17.84
1.780	0.15	-0.30	L1	56.00	31.9	31.75	46.00	29.4	29.25	24.25	16.75
2.240	0.09	-0.28	N	56.00	29.8	29.61	46.00	29.5	29.31	26.39	16.69
3.030	0.09	-0.14	N	56.00	37.7	37.65	46.00	27.1	27.05	18.35	18.95
6.790	0.22	-0.11	L1	60.00	32.3	32.41	50.00	31.7	31.81	27.59	18.19
6.920	0.22	-0.10	L1	60.00	32.5	32.62	50.00	31.6	31.72	27.38	18.28
10.115	0.23	0.00	L1	60.00	28.7	28.93	50.00	25.8	26.03	31.07	23.97

*Comment : Pol : H (Live), N(Neut)

Insertion Loss : Insertion Loss of LISN

Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

6. Radiated Emission

6.1 Operating environment

Temperature : 24°C
Relative humidity : 39 %

6.2 Test set-up

A preliminary scan with peak mode was performed in the semi anechoic chamber and found frequency for open area test site.

The formal radiated emission was measured at 3m/10m-distance open area test site.

The EUT was placed on a non-conductive turntable approximately 0.8 meters above the ground plane.

The turntable with EUT was rotated 360°, and the antenna was varied in height between 1.0 and 4.0 meters in order to determine the maximum emission levels.

This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

6.3 Measurement uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement”.

The measurement uncertainty was given with a confidence of 95%.

Contribution	Probability Distribution	Uncertainty (dB)			
		Biconical Ant.		Log-periodic Ant.	
		3m	10m	3m	10m
Ambient signal					
Antenna factor calibration	Normal (k=2)	0.50	0.50	0.50	0.50
Receiver specification	Rectangular	0.50	0.50	0.50	0.50
Antenna directivity	Rectangular	0.25	0.00	1.50	0.25
Antenna phase center variation	Rectangular	0.00	0.00	1.00	0.20
Antenna factor frequency interpolation	Rectangular	0.25	0.25	0.25	0.25
Measure distance variation	Rectangular	0.60	0.40	0.60	0.40
Site imperfections	Rectangular	-2.00	-2.40	2.50	2.40
Mismatch Receiver VRC : $\Gamma_l = 0.09$ Antenna VRC : $\Gamma_g = 0.43$ (Bi) 0.23 (Lp) Uncertainty limits $20\log(1 \pm \Gamma_l \Gamma_g)$	U-shaped	0.33 -0.35	0.33 -0.35	0.18 -0.18	0.18 -0.18
System repeatability	Std Deviation	0.82	0.82	0.79	0.79
Cable loss calibration	Normal (k=2)	0.09	0.09	0.09	0.09
Combined standard uncertainty $U_c(y)$	Normal	1.54 -1.54	1.70 -1.70	2.03 -2.03	1.68 -1.68
Extended uncertainty U	Normal (k=2)	3.09 -3.09	3.39 -3.40	4.05 -4.05	3.36 -3.36

6.4 Limit

Frequency (MHz)	FCC Limit @ 3m. dB μ V/m	CISPR Limit @ 10m. dB μ V/m
30 – 88	40.0	30.0
88 – 216	43.5	30.0
216 – 230	46.0	30.0
230 – 960	46.0	37.0
960 – 1000	54.0	37.0
> 1000	54.0	No Specified limit

6.5 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESCS30	Rohde & Schwarz	EMI test receiver	839809/003	11. 27. 2007
■ - ESI	Rohde & Schwarz	EMI test receiver	830482/010	12. 14. 2007
■ - HK116	Rohde & Schwarz	Biconical ANT	826861/018	11. 27. 2007
■ - HL223	Rohde & Schwarz	Log-periodic antenna	829228/011	11. 27. 2007
■ - HD100	HD GmbH	Position Controller	100/692/01	N/A
■ - DS415S	HD GmbH	Turntable	415/657/01	N/A
■ - MA240	HD GmbH	Antenna Mast	240/565/01	N/A
■ - BBHA9120D	Schwarzbeck	Horn ANT	207	11. 20. 2007
■ - 87405A	Agilent	Preamplifier	MY39500777	N/A


6.6 Test data for radiated emission

- Test Date : May 11, 2007
- Resolution bandwidth : 120 kHz / 1MHz
- Frequency range : 30MHz ~ 2000MHz
- Measurement distance : 10m / 3m

◆ Operating Condition: 1680*1050/60Hz (Analog)

Detector mode: Quasi- peak detector mode

Frequency (MHz)	Measurement Level				Limit (dBuV/m)	Margin (dBuV/m)	Positioning System		
	Reading	Antenna	Cable	Test Result			Pol.	Height	Angle
	Value(dBuV)	Factor(dB)	Loss(dB)	(dBuV/m)			(H/V)	(cm)	(deg)
31.15	10.9	13.30	1.65	25.8	30.0	4.2	V	100	12
41.59	13.0	10.52	1.83	25.4	30.0	4.6	V	120	95
43.14	13.9	10.24	1.86	26.0	30.0	4.0	V	100	357
85.78	7.1	8.58	2.52	18.2	30.0	11.8	H	100	3
120.01	3.2	11.04	2.90	17.1	30.0	12.9	H	386	149
199.87	1.2	13.79	3.90	18.9	30.0	11.1	H	400	67
300.68	5.1	12.71	5.11	22.9	37.0	14.1	H	120	187
596.24	7.1	18.34	7.37	32.8	37.0	4.2	H	386	277




< Fig 4. Radiated emission result (30MHz ~ 1000MHz)>

◆ Operating Condition: 1680*1050/60Hz (Digital)

Detector mode: Quasi- peak detector mode

Frequency (MHz)	Measurement Level				Limit (dBuV/m)	Margin (dBuV/m)	Positioning System		
	Reading	Antenna	Cable	Test Result			Pol.	Height	Angle
	Value(dBuV)	Factor(dB)	Loss(dB)	(dBuV/m)			(H/V)	(cm)	(deg)
30.27	10.5	13.58	1.61	25.7	30.0	4.3	V	100	28
40.26	13.4	10.76	1.81	26.0	30.0	4.0	V	100	0
45.06	14.1	9.89	1.90	25.9	30.0	4.1	V	100	0
85.79	5.2	8.58	2.52	16.3	30.0	13.7	H	305	298
120.01	7.1	11.04	2.90	21.0	30.0	9.0	V	111	354
162.18	4.0	12.64	3.51	20.2	30.0	9.8	H	400	320
199.87	1.1	13.79	3.90	18.8	30.0	11.2	H	390	242
300.69	9.5	12.71	5.11	27.3	37.0	9.7	H	244	276
596.24	5.0	18.34	7.37	30.7	37.0	6.3	V	100	284




< Fig 5. Radiated emission result (30MHz ~ 1000MHz)>

◆ Operating Condition: 1680*1050/60Hz (USB)

Detector mode: Quasi- peak detector mode


Frequency (MHz)	Measurement Level				Limit (dBuV/m)	Margin (dBuV/m)	Positioning System		
	Reading	Antenna	Cable	Test Result			Pol.	Height	Angle
	Value(dBuV)	Factor(dB)	Loss(dB)	(dBuV/m)			(H/V)	(cm)	(deg)
82.26	5.2	8.36	2.45	16.0	30.0	14.0	V	103	0
90.05	3.4	8.85	2.60	14.9	30.0	15.1	V	100	354
198.03	8.2	13.73	3.87	25.8	30.0	4.2	H	400	288
260.89	4.8	16.36	4.63	25.8	37.0	11.2	H	100	183
333.15	5.2	13.70	5.43	24.3	37.0	12.7	H	100	90
405.02	1.0	15.74	6.13	22.9	37.0	14.1	V	396	176
702.01	4.3	20.69	7.91	32.9	37.0	4.1	V	400	180
842.26	0.3	22.39	8.75	31.4	37.0	5.6	V	400	0



< Fig 6. Radiated emission result (30MHz ~ 1000MHz)>

- ◆ Operating Condition: 1680*1050 / 60Hz (Analog)
 Detector mode: Peak detector mode / Average detector mode

Frequency (MHz)	Measurement Level						AV Limit (dBuV/m)	Margin (dBuV/m)	Positioning System		
	Reading Value(dBuV)		AF	AMP / CL	Test Result (dBuV/m)				Pol. (H/V)	Height (cm)	Angle (deg)
	Peak	Average	(dB)	(dB)	Peak	Average					
1050.4	67.2	50.5	24.9	-41.0	51.1	34.4	54.0	19.6	V	400	0
1358.0	55.7	49.8	25.5	-40.0	41.2	35.3	54.0	18.7	V	105	12
1544.4	62.3	51.5	25.8	-39.6	48.4	37.6	54.0	16.4	V	100	187
1663.2	66.4	54.6	25.9	-39.4	52.9	41.1	54.0	12.9	V	400	180
1782.0	67.5	57.8	26.0	-39.1	54.4	44.7	54.0	9.3	H	390	274
1821.6	56.1	47.1	26.1	-38.8	43.4	34.4	54.0	19.6	V	100	180




*Comment :AMP/CL : Cable loss + AMP gain

< Fig 7. Radiated emission result (1000MHz ~ 2000MHz)>

- ◆ Operating Condition: 1680*1050 / 60Hz (Digital)
 Detector mode: Peak detector mode / Average detector mode

Frequency (MHz)	Measurement Level						AV Limit (dBuV/m)	Margin (dBuV/m)	Positioning System		
	Reading Value(dBuV)		AF	AMP / CL	Test Result (dBuV/m)				Pol. (H/V)	Height (cm)	Angle (deg)
	Peak	Average	(dB)	(dB)	Peak	Average					
1050.0	56.0	48.8	24.9	-41.0	39.9	32.7	54.0	21.3	V	100	90
1358.0	56.0	49.7	25.5	-40.0	41.5	35.2	54.0	18.8	V	100	0
1544.4	63.7	52.5	25.8	-39.6	49.8	38.6	54.0	15.4	V	110	185
1663.2	62.3	52.7	25.9	-39.4	48.8	39.2	54.0	14.8	V	400	180
1782.1	70.1	60.6	26.0	-39.1	57.0	47.5	54.0	6.5	H	400	270




*Comment :AMP/CL : Cable loss + AMP gain

< Fig 8. Radiated emission result (1000MHz ~ 2000MHz)>

- ◆ Operating Condition: 1680*1050 / 60Hz (USB)
 Detector mode: Peak detector mode / Average detector mode

Frequency (MHz)	Measurement Level						AV Limit (dBuV/m)	Margin (dBuV/m)	Positioning System		
	Reading Value(dBuV)		AF	AMP / CL	Test Result (dBuV/m)				Pol. (H/V)	Height (cm)	Angle (deg)
	Peak	Average	(dB)	(dB)	Peak	Average					
1050.0	55.6	48.8	24.9	-41.0	39.5	32.7	54.0	21.3	V	100	90
1358.0	55.7	49.8	25.5	-40.0	41.2	35.3	54.0	18.7	V	100	0
1544.4	61.2	51.4	25.8	-39.6	47.3	37.5	54.0	16.5	V	100	180
1663.2	63.3	53.3	25.9	-39.4	49.8	39.8	54.0	14.2	V	400	180
1752.0	67.1	57.5	26.0	-39.2	53.9	44.3	54.0	9.7	H	400	270
1821.6	56.4	48.1	26.1	-38.8	43.7	35.4	54.0	18.6	V	400	180



*Comment :AMP/CL : Cable loss + AMP gain

< Fig 8. Radiated emission result (1000MHz ~ 2000MHz)>

7. Sample Calculations

$$\begin{aligned} \text{dB}\mu\text{V} &= 20 \text{ Log}_{10}(\mu\text{V}/\text{m}) \\ \text{dB}\mu\text{V} &= \text{dBm} + 107 \\ \mu\text{V} &= 10^{(\text{dB}\mu\text{V}/20)} \end{aligned}$$

7.1 Example 1 :

■ 20.3 MHz

Class B Limit	=	250 μV	=	48 dB μV
Reading	=	- 67.8 dBm(Calibrated level)		
Convert to dB μV	=	- 67.8 dBm + 107	=	39.2 dB μV
$10^{(39.2\text{dB}\mu\text{V}/20)}$	=	91.2 μV		
Margin	=	39.2 – 48	=	-8.8
	=	8.8 dB below Limit		

7.2 Example 2 :

■ 66.7 MHz

Class B Limit	=	100 $\mu\text{V}/\text{m}$	=	40.0 dB $\mu\text{V}/\text{m}$
Reading	=	- 76.0 dBm(Calibrated level)		
Convert to dB $\mu\text{V}/\text{m}$	=	- 76.0 dBm + 107	=	31.0 dB $\mu\text{V}/\text{m}$
Antenna Factor + Cable Loss	=	5.8 dB		
Total	=	36.8 dB $\mu\text{V}/\text{m}$		
Margin	=	36.8 – 40.0	=	-3.2
	=	3.2 dB below Limit		

8. Recommendation & conclusion

The data collected shows that the **LG Electronics Inc. 20.1" LCD Monitor (Model No.: L206WUQ)** was complies with §15.107 and 15.109 of the FCC Rules.