



HCT CO., LTD.

CERTIFICATE OF COMPLIANCE
FCC Certification**Applicant Name:**
LG Electronics Inc.**Date of Issue:**
March 21, 2012**Address:**
60-39, Gasan-dong, Gumchon-gu,
Seoul 153-023, Korea**Location:**
HCT CO., LTD., 105-1, Jangam-ri, Majang-Myeon,
Icheon-si, Kyunggi-Do, Korea**Test Report No.:** HCTR1202FR20-2**HCT FRN:** 0005866421**FCC ID:** BEJLTGEN97GL**APPLICANT:** LG Electronics Inc.

FCC Model(s): TG97AATJU
EUT Type: GSM Transceiver with Bluetooth (Telematics module)
FCC Classification: PCS Licensed Transmitter (PCB)
FCC Rule Part(s): §22, §24, §2
Tx Frequency: 824.20 - 848.80 MHz (GSM850)
1 850.20 - 1 909.80 MHz (GSM1900)
Rx Frequency: 869.20 - 893.80 MHz (GSM850)
1 930.20 - 1 989.80 MHz (GSM1900)
Max. Conducted Power: 2.366 W GSM850 (33.74 dBm) / 1.191 W GSM1900 (30.76 dBm)
0.746 W EDGE850 (28.73 dBm) / 0.426 W EDGE1900 (26.29 dBm)
Emission Designator(s): 248 KGXW (GSM850) 246 KGXW (GSM1900)
248 KG7W (GSM850 EDGE) 246 KG7W (GSM1900 EDGE)

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)


Report prepared by
: Hyo Sun Kwak
Test engineer of RF Team
Approved by
: Chang Seok Choi
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1202FR20-2	Date of Issue: March 21, 2012	EUT Type: GSM Transceiver with Bluetooth (Telematics module)	FCC ID: BEJLTGEN97GL

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCTR1202FR20	February 23, 2012	First Approval Report
HCTR1202FR20-1	March 20, 2012	Changed Band Edge (Page 29 ~ 36) Modified page 9,14,16,18
HCTR1202FR20-2	March 21, 2012	Changed Band Edge Plot (Page 31~32)

Table of Contents

1. GENERAL INFORMATION	4
2. INTRODUCTION	5
2.1. EUT DESCRIPTION.....	5
2.2. MEASURING INSTRUMENT CALIBRATION.....	5
2.3. TEST FACILITY	5
3. DESCRIPTION OF TESTS	6
3.1 EFFECTIVE RADIATED POWER/EQUIVALENT ISOTROPIC RADIATED POWER.....	6
3.2 PEAK- TO- AVERAGE RATIO	7
3.3 OCCUPIED BANDWIDTH.	8
3.4 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	9
3.5 RADIATED SPURIOUS AND HARMONIC EMISSIONS	10
3.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	11
4. LIST OF TEST EQUIPMENT	12
5. SUMMARY OF TEST RESULTS	13
6. SAMPLE CALCULATION	14
7. TEST DATA	15
7.1 CONDUCTED OUTPUT POWER	15
7.2 PEAK-TO-AVERAGE RATIO	16
7.3 OCCUPIED BANDWIDTH	17
7.4 CONDUCTED SPURIOUS EMISSIONS	18
7.4.1 BAND EDGE.....	18
7.5 RADIATED SPURIOUS EMISSIONS	19
7.5.1 RADIATED SPURIOUS EMISSIONS (GSM850)	19
7.5.2 RADIATED SPURIOUS EMISSIONS (GSM1900)	20
7.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	21
7.6.1 FREQUENCY STABILITY (GSM850)	21
7.6.2 FREQUENCY STABILITY (GSM1900)	22
8. TEST PLOTS.....	23

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name: LG Electronics Inc.
Address: 60-39, Gasan-dong, Gumchon-gu, Seoul 153-023, Korea

FCC ID: BEJLTGEN97GL
Application Type: Certification
FCC Classification: PCS Licensed Transmitter (PCB)
FCC Rule Part(s): §22, §24, §2
EUT Type: GSM Transceiver with Bluetooth (Telematics module)
FCC Model(s): TG97AATJU
Tx Frequency: 824.20 - 848.80 MHz (GSM850)
1 850.20 - 1 909.80 MHz (GSM1900)

Rx Frequency: 869.20 - 893.80 MHz (GSM850)
1 930.20 - 1 989.80 MHz (GSM1900)

Max. Conducted Power: 2.366 W GSM850 (33.74 dBm) / 1.191 W GSM1900 (30.76 dBm)
0.746 W EDGE850 (28.73 dBm) / 0.426 W EDGE1900 (26.29 dBm)

Emission Designator(s): 248 KGXW (GSM850) 246 KGXW (GSM1900)
248 KG7W (GSM850 EDGE) 246 KG7W (GSM1900 EDGE)

Date(s) of Tests: February 03, 2012 ~ February 13, 2012

2. INTRODUCTION

2.1. EUT DESCRIPTION

The LG Electronics Inc. TG97AATJU GSM Transceiver with Bluetooth (Telematics module) of GSM850, GSM1900.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 105-1, Jangam-ri , Majang-Myeon, Icheon-si, 467-811, KOREA.


The site is constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated March 02, 2011 (Registration Number: 90661)

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1202FR20-2	Date of Issue: March 21, 2012	EUT Type: GSM Transceiver with Bluetooth (Telematics module)	FCC ID: BEJLTGEN97GL

3. DESCRIPTION OF TESTS

3.1 EFFECTIVE RADIATED POWER/EQUIVALENT ISOTROPIC RADIATED POWER

Test Set-up



Test Procedure

Radiated emission measurements were performed at an Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters from the receive antenna. A turntable was rotated 360° and the receiving antenna scanned from 1-4m in order to capture the maximum emission. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the previously recorded signal was duplicated.

The maximum EIRP was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried out with the receiving antenna in both vertical and horizontal polarization. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration


3.2 PEAK- TO- AVERAGE RATIO

A peak to average ratio measurement is performed at the conducted port of the EUT. For CDMA and WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. Plots of the EUT's Peak- to- Average Ratio are shown herein.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1202FR20-2	Date of Issue: March 21, 2012	EUT Type: GSM Transceiver with Bluetooth (Telematics module)	FCC ID: BEJLTGEN97GL

3.3 OCCUPIED BANDWIDTH.

Test set-up



(Configuration of conducted Emission measurement)
Test Procedure

The EUT was setup to maximum output power at its lowest channel. The occupied bandwidth was measured using a spectrum analyzer. The measurements are repeated for the highest and a middle channel. The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Plots of the EUT's occupied bandwidth are shown herein.

3.4 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.

Test Procedure

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer.

The EUT was setup to maximum output power at its lowest channel. The Resolution BW of the analyzer is set to 1 % of the emission bandwidth to show compliance with the – 13 dBm limit, in the 1 MHz bands immediately outside and adjacent to the edge of the frequency block. The 1 MHz RBW was used to scan from 10 MHz to 10 GHz. (GSM1900 Mode: 10 MHz to 20 GHz). A display line was placed at – 13 dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements.

- Band Edge Requirement : In the 1MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions. Limit, -13dBm.

FACTORS FOR FREQUENCY

Freq(MHz)	Factor(dB)	Freq(MHz)	Factor(dB)
30	26.57	4000	28.08
100	26.30	5000	28.16
200	26.08	6000	27.98
300	26.17	7000	27.64
400	26.69	8000	27.94
500	26.94	9000	27.96
600	26.44	10000	29.50
700	26.25	11000	29.19
800	26.70	12000	28.69
824*	26.53	13000	28.90
836*	26.56	14000	28.12
849*	26.70	15000	28.43
900	27.04	16000	28.64
1000	26.93	17000	28.31
1850*	27.18	18000	28.35
1880*	27.30	19000	28.28
1910*	27.55	20000	28.22
3000	27.01		


Note : 1. “*” is fundamental frequency range.

2. Factor = Cable loss + Attenuator loss + Splitter

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1202FR20-2	Date of Issue: March 21, 2012	EUT Type: GSM Transceiver with Bluetooth (Telematics module)	FCC ID: BEJLTGEN97GL

3.5 RADIATED SPURIOUS AND HARMONIC EMISSIONS

Test Set-up



The measurement facilities used for this test have been documented in previous filings with the commission pursuant to section § 2.948. The Fully-anechoic chamber meets requirements in ANSI C63.4 –2003. A mast capable of lifting the receiving antenna from a height of one to four meters is used together with a rotatable platform mounted at three from the antenna mast.

- 1) The unit mounted on a turntable 1.5 m × 1.0 m × 0.80 m is 0.8 meter above test site ground level.
- 2) During the emission test, the turntable is rotated and the EUT is manipulated to find the configuration resulting in maximum emission under normal condition of installation and operation.
- 3) The antenna height and polarization are also varied from 1 to 4 meters until the maximum signal is found.
- 4) The spectrum shall be scanned up to the 10th harmonic of the fundamental frequency.

Test Procedure


The equipment under test is placed on a non-conductive table 3-meters from the receive antenna. A turntable was rotated 360° and the receiving antenna scanned from 1-4m in order to capture the maximum emission. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the previously recorded signal was duplicated.

The maximum EIRP was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried out with the receiving antenna in both vertical and horizontal polarization. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1202FR20-2	Date of Issue: March 21, 2012	EUT Type: GSM Transceiver with Bluetooth (Telematics module)	FCC ID: BEJLTGEN97GL

3.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

Test Set-up



* Nominal Operating Voltage

Test Procedure

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from battery end point to 115 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.000\ 25\ \%$ ($\pm 2.5\ \text{ppm}$) of the center frequency.

Time Period and Procedure:

The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).

1. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

NOTE: The EUT is tested down to the battery endpoint.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1202FR20-2	Date of Issue: March 21, 2012	EUT Type: GSM Transceiver with Bluetooth (Telematics module)	FCC ID: BEJLTGEN97GL

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Interval	Calibration Due
R&S	N9020A	MY51110020	Annual	09/23/2012
Agilent	E9327A/ Power Sensor	MY4442009	Annual	05/02/2012
R&S	CMW500/ Base Station	1201.0002K50_10395	Annual	04/20/2012
MITEQ	AMF-6D-001180-35-20P/AMP	1081666	Annual	09/24/2012
Wainwright	WHK1.2/15G-10EF/H.P.F	2	Annual	05/02/2012
Wainwright	WHK3.3/18G-10EF/H.P.F	1	Annual	05/02/2012
Agilent	11636B/ Power Divider	11377	Annual	11/07/2012
Digital	EP-3010/ Power Supply	3110117	Annual	11/07/2012
Schwarzbeck	UHAP/ Dipole Antenna	557	Biennial	05/03/2012
Schwarzbeck	UHAP/ Dipole Antenna	558	Biennial	05/03/2012
Korea Engineering	KR-1005L / Chamber	KRAB05063-3CH	Annual	11/07/2012
Schwarzbeck	BBHA 9120D/ Horn Antenna	147	Biennial	04/13/2012
Agilent	E4440A/Spectrum Analyzer	US45303008	Annual	05/02/2012
WEINSCHL	ATTENUATOR	BR0592	Annual	11/07/2012
REOHDE&SCHWARZ	FSP30/Spectrum Analyzer	839117/011	Annual	03/23/2012
Agilent	8960 (E5515C)/ Base Station	GB44400269	Annual	02/10/2013
Hewlett Packard	11667B / Power Splitter	10126	Annual	11/04/2012
REOHDE&SCHWARZ	CMU200/ Base Station	114136	Annual	01/20/2013

5. SUMMARY OF TEST RESULTS

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result
2.1049, 22.917(a), 24.238(a)	Occupied Bandwidth	N/A	CONDUCTED	PASS
2.1051, 22.917(a), 24.238(a)	Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	$< 43 + 10\log_{10} (P[\text{Watts}])$ at Band Edge and for all out-of-band emissions		PASS
2.1046	Conducted Output Power	-		PASS
24.232(d)	Peak- to- Average Ratio	$< 13 \text{ dB}$		PASS
2.1055, 22.355, 24.235	Frequency stability / variation of ambient temperature	$< 2.5 \text{ ppm}$		PASS
2.1053, 22.917(a), 24.238(a)	Radiated Spurious and Harmonic Emissions	$< 43 + 10\log_{10} (P[\text{Watts}])$ for all out-of band emissions	RADIATED	PASS

6. SAMPLE CALCULATION

A. ERP Sample Calculation

Mode	Ch./ Freq.		Measured	Substitute	Ant. Gain	C.L	Pol.	ERP	
	channel	Freq.(MHz)	Level(dBm)	LEVEL(dBm)				W	dBm
GSM850	128	824.20	-11.56	34.28	-8.32	1.17	H	0.30	24.79

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a wooden tripod is 0.8 meter above test site ground level.
- 2) During the test , the turn table is rotated and the antenna height is also varied from 1 to 4 meters until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power (ERP).

B. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

C. Conducted Output Power and PAR Sample Calculation

Conducted Output Power

$$\begin{aligned} \text{Output Power} &= \text{Reading Value} + \text{Cable loss(1 ea)} \\ &= 30 \text{ dBm} + 0.8 \text{ dB} = 30.6 \text{ dBm} \end{aligned}$$

Note: Power values in Base-Station power Measurement function are applied offset.

PAR

$$\begin{aligned} \text{PAR} &= \text{Reading Value} + \text{ATT(20 dB)} + \text{Splitter} + \text{Cable loss(2 ea)} \\ &= 5 \text{ dBm} + 20 \text{ dB} + 6 \text{ dB} + 1.2 \text{ dB} = 32.2 \text{ dBm} \end{aligned}$$

Note: Power values in plots of spectrum analyzer are applied offset.


(where) offset = ATT(20 dB) + Splitter + Cable loss(2 ea)

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1202FR20-2	Date of Issue: March 21, 2012	EUT Type: GSM Transceiver with Bluetooth (Telematics module)	FCC ID: BEJLTGEN97GL

7. TEST DATA

7.1 CONDUCTED OUTPUT POWER

A base station simulator was used to establish communication with the EUT. The base station simulator parameters were set to produce the maximum power from the EUT. This device was tested under all configurations and the highest power is reported. Conducted Output Powers of EUT are reported below.



Test Result

Band	Channel	Voice		GPRS Data							
		GSM		GPRS 1 TX Slot		GPRS 2 TX Slot		GPRS 3 TX Slot		GPRS 4 TX Slot	
		Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
GSM 850	128	33.70	33.81	33.68	33.80	32.16	32.33	31.00	31.17	29.75	29.83
	190	33.74	33.82	33.72	33.81	32.12	32.29	30.63	30.75	29.61	29.78
	251	33.68	33.79	33.65	33.78	32.05	32.21	30.79	31.03	29.60	29.78
GSM 1900	512	30.61	30.76	30.54	30.63	30.12	30.19	28.95	28.99	28.02	28.12
	661	30.76	30.90	30.68	30.78	29.95	30.03	28.85	28.94	27.93	28.06
	810	30.62	30.83	30.61	30.71	30.10	30.19	28.83	28.92	27.90	30.07

(GSM Conducted Output Powers)

Band	Channel	EDGE Data							
		EDGE 1 TX Slot		EDGE 2 TX Slot		EDGE 3 TX Slot		EDGE 4 TX Slot	
		Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
GSM 850	128	26.98	30.16	26.83	30.00	25.73	28.41	24.32	27.38
	190	26.92	30.19	26.77	29.42	25.65	27.96	24.28	27.27
	251	26.86	30.06	26.73	29.86	25.62	28.74	24.25	26.98
GSM 1900	512	26.19	28.62	26.19	29.25	26.29	29.22	25.29	28.34
	661	26.13	28.77	26.24	28.85	26.22	29.02	25.22	28.00
	810	26.15	28.83	26.26	28.97	26.24	28.80	24.90	27.75

(GSM EDGE Conducted Output Powers)

Note :

1. We apply to cable loss in base-station for testing conducted output power.
2. Actual offset values are 0.55 dB in GSM850 and 0.89 dB in GSM1900.

7.2 PEAK-TO-AVERAGE RATIO

- Plots of the EUT's Peak- to- Average Ratio are shown Page 28.

Note :

1. We apply to cable loss, splitter and attenuation for testing PAR.
2. Actual offset values is 27.3 dB in GSM1900.

7.3 OCCUPIED BANDWIDTH

Band	Channel	Frequency(MHz)	Data (GSM: kHz / WCDMA : MHz)
GSM850	128	824.20	242.3884
	190	836.60	244.4816
	251	848.80	247.9002
GSM850 EDGE	251	848.80	247.5107
GSM1900	512	1850.20	246.1209
	661	1880.00	245.1458
	810	1909.80	245.0978
GSM1900 EDGE	512	1850.20	245.6275

- Plots of the EUT's Occupied Bandwidth are shown Page 24 ~ 27.

7.4 CONDUCTED SPURIOUS EMISSIONS

Band	Channel	Frequency of Maximum Harmonic (GHz)	Maximum Data (dBm)
GSM850	128	7.100	-31.62
	190	6.825	-31.76
	251	7.088	-32.26
GSM1900	512	15.040	-29.30
	661	15.710	-29.37
	810	14.000	-28.75

- Plots of the EUT's Conducted Spurious Emissions are shown Page 37 ~ 42.

7.4.1 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 29 ~ 36.

Note : Actual offset values is included the table on page 9.

7.5 RADIATED SPURIOUS EMISSIONS

7.5.1 RADIATED SPURIOUS EMISSIONS (GSM850)

MODULATION SIGNAL: GSM850

DISTANCE: 3 meters

LIMIT: - 13 dBm

Ch.	Freq.(MHz)	Measured Level [dBm]	Ant. Gain (dBd)	Substitute Level [dBm]	C.L	Pol.	ERP (dBm)	Margin
128 (824.2)	1,648.40	-53.21	9.66	-57.84	2.63	H	-50.81	37.81
	2,472.60	-42.53	10.79	-45.37	3.55	V	-38.13	25.13
	3,296.80	-54.94	11.76	-58.31	4.79	H	-51.34	38.34
190 (836.6)	1,673.20	-53.27	9.77	-57.97	2.67	H	-50.87	37.87
	2,509.80	-42.91	10.82	-46.02	3.61	V	-38.81	25.81
	3,346.40	-	-	-	-	-	-	-
251 (848.8)	1,697.60	-54.33	9.94	-59.46	2.61	V	-52.13	39.13
	2,546.40	-49.58	10.84	-53.22	3.60	V	-45.98	32.98
	3,395.20	-	-	-	-	-	-	-

NOTES: 1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method

according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5th Harmonic for all channel.

3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

4. Spectrum setting:

- Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.

7.5.2 RADIATED SPURIOUS EMISSIONS (GSM1900)

MODULATION SIGNAL: GSM1900

DISTANCE: 3 meters

LIMIT: - 13 dBm

Ch.	Freq.(MHz)	Measured Level [dBm]	Ant. Gain (dBi)	Substitute Level [dBm]	C.L	Pol.	EIRP (dBm)	Margin
512 (1850.2)	3,700.40	-37.59	12.36	-39.38	4.87	H	-31.89	18.89
	5,550.60	-53.89	12.61	-50.34	6.66	H	-44.39	31.39
	7,400.80	-	-	-	-	-	-	-
661 (1880.0)	3,760.00	-32.53	12.40	-34.25	4.88	H	-26.73	13.73
	5,640.00	-54.40	12.65	-50.61	6.54	V	-44.50	31.5
	7,520.00	-	-	-	-	-	-	-
810 (1909.8)	3,819.60	-40.41	12.45	-42.64	5.02	H	-35.21	22.21
	5,729.40	-54.24	12.71	-50.71	6.54	V	-44.54	31.54
	7,639.20	-57.52	10.87	-44.61	7.78	V	-41.52	28.52

NOTES: 1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method

according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5th Harmonic for all channel.

3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

4. Spectrum setting:


- Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.

7.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

7.6.1 FREQUENCY STABILITY (GSM850)

OPERATING FREQUENCY: 836,600,000 Hz
 CHANNEL: 190
 REFERENCE VOLTAGE: 3.7 VDC
 DEVIATION LIM IT: ± 0.000 25 % or 2.5 ppm


Voltage (%)	Power (VDC)	Temp. ()	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.700	+20(Ref)	836 600 022	0	0.000 000	0.000
100%		-30	836 600 001	-21.13	-0.000 003	-0.025
100%		-20	836 599 998	-23.92	-0.000 003	-0.029
100%		-10	836 599 995	-27.09	-0.000 003	-0.032
100%		0	836 600 002	-19.85	-0.000 002	-0.024
100%		+10	836 600 000	-21.73	-0.000 003	-0.026
100%		+30	836 599 997	-24.86	-0.000 003	-0.030
100%		+40	836 600 000	-22.21	-0.000 003	-0.027
100%		+50	836 599 996	-25.86	-0.000 003	-0.031
115%	4.255	+20	836 599 997	-24.46	-0.000 003	-0.029
Batt. Endpoint	3.400	+20	836 599 997	-24.81	-0.000 003	-0.030



7.6.2 FREQUENCY STABILITY (GSM1900)

OPERATING FREQUENCY: 1880,000,000 Hz
 CHANNEL: 661
 REFERENCE VOLTAGE: 3.7 VDC
 DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm


Voltage (%)	Power (VDC)	Temp. ()	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.700	+20(Ref)	1879 999 970	0	0.000 000	0.000
100%		-30	1880 000 002	32.09	0.000 002	0.017
100%		-20	1880 000 003	32.67	0.000 002	0.017
100%		-10	1880 000 000	30.31	0.000 002	0.016
100%		0	1880 000 005	35.19	0.000 002	0.019
100%		+10	1880 000 006	35.71	0.000 002	0.019
100%		+30	1880 000 005	35.09	0.000 002	0.019
100%		+40	1880 000 004	34.04	0.000 002	0.018
100%		+50	1880 000 004	33.42	0.000 002	0.018
115%	4.255	+20	1880 000 002	32.06	0.000 002	0.017
Batt. Endpoint	3.400	+20	1880 000 007	37.30	0.000 002	0.020



8. TEST PLOTS

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1202FR20-2	Date of Issue: March 21, 2012	EUT Type: GSM Transceiver with Bluetooth (Telematics module)	FCC ID: BEJLTGEN97GL


■ GSM850 MODE (128 CH.) Occupied Bandwidth



■ GSM850 MODE (190 CH.) Occupied Bandwidth




■ GSM850 MODE (251 CH.) Occupied Bandwidth




■ GSM850 EDGE (251 CH.) Occupied Bandwidth




■ GSM1900 MODE (512 CH.) Occupied Bandwidth




■ GSM1900 MODE (661 CH.) Occupied Bandwidth




■ GSM1900 MODE (810 CH.) Occupied Bandwidth




■ GSM1900 EDGE (512 CH.) Occupied Bandwidth




■ GSM1900 MODE (661 CH.) Peak-to-Average Ratio




■ GSM1900 EDGE MODE (661 CH.) Peak-to-Average Ratio




■ GSM850 MODE (128 CH.) Block Edge 1




■ GSM850 MODE (128 CH.) Block Edge 2




■ GSM850 MODE (251 CH.) Block Edge 1




■ GSM850 MODE (251 CH.) Block Edge 2




■ EDGE MODE (128 CH.) Block Edge 1




■ EDGE MODE (128 CH.) Block Edge 2




■ EDGE MODE (251 CH.) Block Edge 1




■ EDGE MODE (251 CH.) Block Edge 2




■ GSM1900 MODE (512 CH.) Block Edge 1




■ GSM1900 MODE (512 CH.) Block Edge 2




■ GSM1900 MODE (810 CH.) Block Edge 1




■ GSM1900 MODE (810 CH.) Block Edge 2




■ EDGE MODE (512 CH.) Block Edge 1




■ EDGE MODE (512 CH.) Block Edge 2




■ EDGE MODE (810 CH.) Block Edge 1




■ EDGE MODE (810 CH.) Block Edge 2




■ GSM850 MODE (128 CH.) Conducted Spurious Emissions1




■ GSM850 MODE (128 CH.) Conducted Spurious Emissions2




■ GSM850 MODE (190 CH.) Conducted Spurious Emissions1




■ GSM850 MODE (190 CH.) Conducted Spurious Emissions2




■ GSM850 MODE (251 CH.) Conducted Spurious Emissions1




■ GSM850 MODE (251 CH.) Conducted Spurious Emissions2




■ GSM1900 MODE (512 CH.) Conducted Spurious Emissions1




■ GSM1900 MODE (512 CH.) Conducted Spurious Emissions2




■ GSM1900 MODE (661 CH) Conducted Spurious Emissions1



■ GSM1900 MODE (661 CH.) Conducted Spurious Emissions2



■ GSM1900 MODE (810 CH.) Conducted Spurious Emissions1



■ GSM1900 MODE (810 CH.) Conducted Spurious Emissions2

