

Equipment Description

The Equipment Under Test (EUT) is the LG Electronics U.S.A., Inc. Network Monitor.

General Specification

Display	19 inches (48.2 cm) Flat Panel Active matrix-TFT LCD, Anti-Glare coating Visible diagonal size: 48.2 cm 0.294 mm pixel pitch		
Sync Input	D-SUB	Horizontal Freq.	30 - 66 kHz (Automatic)
		Vertical Freq.	57 - 63 Hz (Automatic)
	D-SUB support 60Hz only(except Dos mode)		
	X-PORT	1440 x 900 (60Hz)	1280 x 720 (60Hz)
		1280 x 1024 (60Hz)	800 x 600 (72Hz)
		1024 x 768 (60Hz)	
Video Input	D-SUB	Signal Input Input Form	15 pin D-Sub Connector RGB Analog (0.7 Vp-p/ 75 ohm)
	X-PORT	Signal Input Input Form	X-PORT Connector X-PORT Signal
Resolution	Max	VESA 1280 x 1024 @60 Hz	
	Recommend	D-SUB	VESA 1280 x 1024 @60 Hz
		X-PORT	VESA 1024 x 768 @60 Hz
Plug&Play	DDC 2B (Only for D-SUB Input)		
Power Consumption	On Mode	:	40 W(Max.)
	Sleep Mode	≤	1 W
	Off Mode	≤	1 W
Dimensions & Weight	With Stand		Without Stand
	Width	40.63 cm / 16.00 inches	40.63 cm / 16.00 inches
	Height	42.27 cm / 16.64 inches	34.45 cm / 13.56 inches
		53.27 cm / 20.97 inches	
	Depth	24.16 cm / 9.51 inches	5.84 cm / 2.30 inches
	Net	4.5 kg (10.00 lbs)	
Tilt Range	Tilt	-5° ~ 18°	
Power Input	AC 100-240V~ 50/60Hz 0.8A		
Environmental Conditions	Operating Conditions		
	Temperature	10°C to 35 °C	
	Humidity	10 % to 80 % non-Condensing	
	Storage Conditions		
	Temperature	-20°C to 60 °C	
	Humidity	5 % to 90 % non-Condensing	
Stand Base	Attached (), Detached (O)		
Power cord	Wall-outlet type		

EUT Operating Conditions

- a. Setup the EUT and Peripherals as shown in Sec. 3.2 of the test report.
- b. Turn on the power of all equipment and the EUT.
- c. Set the contrast & brightness of EUT to maximum.
- d. PC system ran the self-test program “EMC Test” by windows XP and sent “H” characters to EUT through graphic card, the EUT’s screen displayed and filled with “H” pattern by its resolution (Via D-Sub & X-PORT Input).
- e. In X- PORT mode, PC system played music and sent audio signal to EUT through the X-PORT of EUT.
- f. Repeat above procedure from c to e for difference test mode.
- g. The other peripherals devices were driven and operated during the test.
- h. The test modes are as follows:

Test Mode
D-Sub 640*480@60Hz
D-Sub 1024*768@60Hz
D-Sub 1280*1024@75Hz
X-PORT 800*600@72Hz
X-PORT 1024*768@60Hz
X-PORT 1440*900@60Hz