



Test Report

Report Number	ESTR0410-008			
Applicant	Company Name	LG Electronics Inc.		
	Address	459-9, Kasan-dong, Keumchun-ku, Seoul 153-023, Korea		
	Telephone	82-2-850-3860		
Product	Product Name	Single Band, Single Mode CDMA Mobile Phone		
	Model No.	LG-RD5330, LG-SD5330, LG-ID5330	Manufacturer	LG Electronics Inc.
	Serial No.	NONE	Country of origin	Korea
	Date of Issue	2004-10-14	Date of Test	2004-09-24 ~2004-10-13
Testing Lab.	ESTECH. Co., Ltd			
Standard	FCC PART 22 Subpart H			
Tested by	S.R. Kim/ Engineer (Signature) 			
Approved by	Jay Kim/ Manager Engineer (Signature) 			
* Note - This test report is not permitted to copy partly without our permission - This test result is dependent on only equipment to be used - This test result based on a single evaluation of one sample of the above mentioned				



TABLE OF CONTENTS

ATTACHMENT: TEST RESULT CERTIFICATION.....	1
1. INTRODUCTION.....	3
2. DESCRIPTION OF EUT.....	4
3. DESCRIPTION OF TEST.....	5
4. TEST DATA	
4.1 EFFECTIVE RADIATED POWER OUTPUT (E.R.P.).....	7
4.2 OCCUPIED BANDWIDTH	9
4.3 FIELD STRENGTH OF SPURIOUS RADIATION.....	11
4.4 SPURIOUS EMISSION AT ANTENNA TERMINAL.....	14
4.5 FREQUENCY STABILITY.....	16
5. TEST PLOTS	
5.1 PLOTS OF EMISSIONS.....	17
5.1.1 PLOTS OF EMISSION (CDMA): BAND EDGE.....	19
5.1.2 PLOTS OF EMISSION (CDMA): OUT OF BAND.....	20
5.2 MOBILE EMISSION IN BASE FREQUENCY RANGE.....	21



ESTECH Co., Ltd.
3rd Fl., Chungdam Bldg.,
119-1 Chungdam-dong,
Kangnamgu, Seoul

Testing and Certification Laboratory
TEL: (822) 549-0485 FAX: (822) 549-0487
<http://www.estech.co.kr>

1. INSTROCTION

1.1 General

This EUT (Equipment Under Test) has been shown to be capable of compliance with the applicable technical standards and tested in accordance with the measurement procedures as indicated in this report ESTECH Lab attests to accuracy of test data. All measurement reported herein were performed by ESTECH Co., Ltd.

ESTECH Lab., assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

1.2 Test Lab.

Corporation Name: ESTECH Co. Ltd.

Head Office: 3 rd Fl., Chungdam Bldg., 119-1, Chungdam-dong Kangnam-gu , Seoul, Korea
(Safety & Telecom. Test Lab)

EMC Test Lab.: 58-1, Osan-Ri, GaNam-Myon, YeoJoo-Gun, KyungKi-Do, Korea
97-1, Hoiuk-Ri Majang-Myon, Icheon-city, KyungKi-Do, Korea



ESTECH Co., Ltd.
3rd Fl., Chungdam Bldg.,
119-1 Chungdam-dong,
Kangnamgu, Seoul

Testing and Certification Laboratory
TEL: (822) 549-0485 FAX: (822) 549-0487
<http://www.estech.co.kr>

2. Description of EUT

2.1 Summary of Equipment Under Test

- ◆ FCC ID : BEJRD5330
- ◆ Freq. Range : Tx : 824.820 ~ 848.190 MHz
Rx : 869.820 ~ 893.190 MHz
- ◆ Power Rating : 3.7VDC(3.2 ~ 4.2VDC)
- ◆ EUT Type : Single Band, Single Mode CDMA Mobile Phone
- ◆ Modulation(s) :
CDMA - FM



3. DESCRIPTION OF TEST

3.1 RF Power Output

- The EUT was placed on a wooden turn table 3 meters from the receive antenna. The receive antenna height and turn table rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For reading 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

3.5 Occupied Bandwidth

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% of the Emission bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled.

3.6 Spurious and Harmonic Emission at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to 10GHz.

Set the RES BW to 1% of the emission bandwidth to show compliance with the -13dBm, limit, in the 1MHz bands immediately outside and adjacent to the top and bottom edges of the frequency block.

For the Out-of-Band measurements a 1MHz RBW was used to scan from 10MHz to 10xfo of the fundamental carrier for all frequency block. A display line was placed at -13dBm to show compliance for spurious, and harmonics.

Mobile emission in base frequency range. The mean power of any emissions appearing in the base station frequency range from cellular mobile transmit antenna connector.

3.7 Radiation Spurious and Harmonic Emissions

Radiation and harmonic emission are measured outdoors at our 3 meters test range. The equipment under test is placed on a wooden turntable 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.



3. DESCRIPTION OF TEST(CONTINUE)

3.8 Frequency stability (Temperature Variation)

The frequency stability of the transmitter is measured by:

- a) **Temperature:** The temperature is varied from -30℃ to +60℃ using an environmental chamber.
- b) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

※ The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 2.5\text{ppm}$ of the center frequency.

Time Period and Procedure

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (22℃ to 25℃ to provide a reference.)
2. The equipment is subjected to an overnight “soak” at -30℃ without any power applied.
3. After the overnight “soak” at -30℃ (usually 14 – 16hours), the equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements are made at 10℃ interval up to room temperature. At least a period of one and one half hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting -30℃ up to +50℃ allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.



4. TEST DATA

4.1 EFFECTIVE RADIATED POWER OUTPUT (E.R.P.)

MEASUREMENT INSTRUMENTS

EQUIPMENT	MANUFACTURE	MODEL NO.
Spectrum Analyzer	HP	8563E
Signal Generator	HP	E4432B
Power Meter	HP	EPM-442A
Pre Amplifier	SONOMA INSTRUMENT	310 N
Log-bicon Antenna	SCHWARZBECK	VULB 9160
Horn Antenna	SCHWARZBECK	BBHA 9120 D
Dipole Antenna	Schmid & Partner Engineering	D835V2, D1800V2

*TEST RESULT

- Company Name: LG Electronics Inc.
- EUT Description: Single Band, Single Mode CDMA Mobile Phone

CDMA

	Ch. No.	Freq. (MHz)	Peak Power Meter(dBm)	Peak Power ERP(dBm)
Low Ch.	1017	824.82	24.74	24.61
Mid Ch.	383	836.49	24.40	20.73
High Ch.	772	848.19	24.62	21.86



ESTECH Co., Ltd.
3rd Fl., Chungdam Bldg.,
119-1 Chungdam-dong,
Kangnamgu, Seoul

Testing and Certification Laboratory
TEL:(822)549-0485 FAX:(822)549-0487
<http://www.estech.co.kr>

4. TEST DATA(CONTINUED)

FREQ. (MHz)	SA Reading (dBuV/m)	Correction Factor (dB)		Peak Value (dBm)		Limit (dBm)	POL (H/V)
		Antenna gain (dBd)	CL (dB)	SG Reading	Result		
824.82	88.89	-2.2	0.5	27.31	24.61	38.5	V
836.49	84.97	-2.2	0.5	24.56	21.86	38.5	V
848.19	87.49	-2.2	0.5	23.43	20.73	38.5	V



4. TEST DATA(CONTINUED)

4.2 OCCUPIED BANDWIDTH


* MEASUREMENT INSTRUMENTS

EQUIPMENT	MANUFACTURE	MODEL NO.
Spectrum Analyzer	HP, Agilent	8563E, E4402B
Attenuator	INMET CORP.	6N25W-10

Test Result:

Channel	Frequency(MHz)	26dB BW(MHz)
1017	824.82	1.370
383	836.49	1.423
772	848.19	1.423


26dB BANDWIDTH (CH 1017)






4. TEST DATA(CONTINUE)

26dB BANDWIDTH (CH 383)



26dB BANDWIDTH (CH 772)





4. TEST DATA(CONTINUE)

4.3 FIELD STRENGTH OF SPURIOUS RADIATION

a) MEASUREMENT INSTRUMENTS

EQUIPMENT	MANUFACTURE	MODEL NO.
Receiver	Rohde & Schwarz	ESVS10
Pre Amplifier	SONOMA INSTRUMENT	310 N
Log-bicon Antenna	SCHWARZBECK	VULB 9160
Horn Antenna	SCHWARZBECK	BBHA 9120 D
Spectrum Analyzer	ADVANTEST	R33261B

b) MEASUREMENT PROCEDURE

- The EUT was placed on a wooden turn table 3 meters from the receive antenna. The receive antenna height and turn table rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For reading 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration



4. TEST DATA(CONTINUED)

- CDMA (CH 1017)

FREQ. (MHz)	SA Reading (dBuV/m)	Correction Factor (dB)		Peak Value (dBm)		Limit (dBm)	POL (H/V)
		Antenna gain(dBd)	CL (dB)	SG Reading	Result		
1649.64	70.85	7.69	0.5	-59.12	-51.93	-13.0	V
2472.49	67.97	8.25	0.5	-63.80	-56.10	-13.0	V

- CDMA (CH 383)

FREQ. (MHz)	SA Reading (dBuV/m)	Correction Factor (dB)		Peak Value (dBm)		Limit (dBm)	POL (H/V)
		Antenna gain(dBd)	CL (dB)	SG Reading	Result		
1672.98	68.61	7.79	0.5	-60.19	-52.9	-13.0	V
2509.47	64.93	8.45	0.5	-68.37	-61.42	-13.0	V



ESTECH Co., Ltd.
3rd Fl., Chungdam Bldg.,
119-1 Chungdam-dong,
Kangnamgu, Seoul

Testing and Certification Laboratory
TEL: (822) 549-0485 FAX: (822) 549-0487
<http://www.estech.co.kr>

4. TEST DATA(CONTINUED)

- CDMA (CH 772)

FREQ. (MHz)	SA Reading (dBuV/m)	Correction Factor (dB)		Peak Value (dBm)		Limit (dBm)	POL (H/V)
		Antenna gain(dBd)	CL (dB)	SG Reading	Result		
1696.38	73.22	7.79	0.5	-54.70	-47.41	-13.0	V
2544.57	67.24	8.45	0.5	-68.83	-60.88	-13.0	V



4. TEST DATA(CONTINUED)

4.4 SPURIOUS EMISSION AT ANTENNA TERMINAL

a) MEASUREMENT INSTRUMENTS

EQUIPMENT	MANUFACTURE	MODEL NO.
Spectrum Analyzer	HP, Agilent	8563E, E4402B
Attenuator	INMET CORP.	6N25W-10

b) MEASUREMENT PROCEDURE

- The EUT's RF output connector (made solely for the purpose of the test) is connected to the spectrum analyzer, and set as close as possible to the bottom of the block edge and one set as close as possible to the top of the block edge. Set the RES BW to 1% of the emission bandwidth to show compliance with the -13dBm limit, in the 1MHz bands immediately outside and adjacent to the top and bottom edges of the frequency block.

For the Out-of -Band measurements a 1MHz RES BW was used to scan from 15MHz to $10 \times f_0$ the fundamental carrier for all frequency block. A display line was placed at -13dBm to show compliance for spurious, and harmonics.

22.917(f): Mobile emission in base frequency range. The mean power of any emissions appearing in the base station frequency range from cellular mobile transmitter operated must be attenuated to a level not to exceed -80dBm at the transmit antenna connector.

*TEST RESULT

- EUT Description: Single Band, Single Mode CDMA Mobile Phone

CDMA(Spurious Emission: Block Edge)

Freq. (MHz)	Channel	Measurement Value(dBm)	Limit(dBm)	Margin(dB)
824.82	1017	-20.06	-13	7..06
848.19	772	-21.80	-13	8.80



ESTECH Co., Ltd.
3rd Fl., Chungdam Bldg.,
119-1 Chungdam-dong,
Kangnamgu, Seoul

Testing and Certification Laboratory
TEL: (822) 549-0485 FAX: (822) 549-0487
<http://www.estech.co.kr>

4. TEST DATA(CONTINUED)

CDMA (Spurious Emission: Out of Band)

Freq. (MHz)	Channel	Measurement Value(dBm)	Limit(dBm)	Margin(dB)
824.82	1011	-31.83	-13	18.83
836.49	383	-33.50	-13	20.50
848.19	779	-33.17	-13	20.17



4. TEST DATA(CONTINUED)

4.5 FREQUENCY STABILITY (CDMA)

OPERATING FREQUENCY: 836,490,000 Hz

CHANNEL: 383

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5ppm


VOLTAGE (%)	POWER (VDC)	TEMP. (°C)	FREQ. (Hz)	Deviation (%)
100 %	3.70	+20 °C (Ref)	836,489,992	0.000000
100 %		-30	836,489,965	0.000003
100 %		-20	836,489,958	0.000004
100 %		-10	836,489,972	0.000002
100 %		0	836,489,975	0.000002
100 %		+10	836,489,982	0.000001
100 %		+20	836,489,992	0.000000
100 %		+25	836,489,983	0.000001
100 %		+30	836,489,976	0.000002
100 %		+40	836,489,985	0.000001
100 %		+50	836,489,988	0.000001
100 %		+60	836,489,979	0.000002
85 %	3.15	+20	836,489,990	0.0000002
115 %	4.26	+20	836,489,988	0.000001
BATT. ENDPOINT	3.00	+20	836,489,980	0.000001




5. TEST PLOTS

5.1.1 PLOTS OF EMISSION (CDMA): BAND EDGE

- Ch 1017



- Ch 772







5. TEST PLOTS (CONTINUED)

5.1.2 PLOTS OF EMISSION (CDMA): OUT OF BAND



- Ch 1017





5. TEST PLOTS (CONTINUED)

- Ch 383







ESTECH Co., Ltd.
3rd Fl., Chungdam Bldg.,
119-1 Chungdam-dong,
Kangnamgu, Seoul

Testing and Certification Laboratory

TEL: (822) 549-0485 FAX: (822) 549-0487
http://www.estech.co.kr

5. TEST PLOTS (CONTINUED)

- Ch 772





ESTECH Co., Ltd.
3rd Fl., Chungdam Bldg.,
119-1 Chungdam-dong,
Kangnamgu, Seoul

Testing and Certification Laboratory

TEL: (822) 549-0485 FAX: (822) 549-0487
http://www.estech.co.kr

5. TEST PLOTS

5.2 MOBILE EMISSION IN BASE FREQUENCY RANGE

