


	ESTECH Co., Ltd. Rm. 1015, World Venture Center II, 426-5 Gasan-dong, Guncheon-gu, Seoul, 158-803, Korea	   	Electromagnetic Interference Test Report

Compliance Test Report for FCC

Report Number		ESTF150511-003			
Applicant	Company name	LG Electronics Inc.			
	Address	459-9, Kasna-dong, Keumchun-ku, Seoul 153-023, Korea			
	Telephone	82-2-2033-3847 FAX :82-2-2033-3855			
Product	Product name	PCS GSM Phone			
	Model No.	S5000, S5100	Manufacturer	LG Electronics Inc.	
	Serial No.	NONE	Country of origin	KOREA	
Test date	2005-10-27 ~ 2005-11-07		Date of issue	2005-11-07	
Testing location	ESTECH. Co., Ltd. 97-1 Hoiuk-Ri Majang-Myon, Icheon-city, KyungKi-Do, Korea				
Standard	FCC PART 15 2002 , ANSI C 63.4 2003				
Test item	☒ Conducted Emission	☐ Class A	☒ Class B	Test result	OK
	☒ Radiated Emission	☐ Class A	☒ Class B	Test result	OK
Measurement facility registration number		94696			
Tested by	Engineer J.H.Kim 				
Reviewed by	Manager Engineer J.M.Yang 				
Abbreviation	OK, Pass = Passed, Fail = Failed, N/A = not applicable				
* Note - This test report is not permitted to copy partly without our permission - This test result is dependent on only equipment to be used - This test result based on a single evaluation of one sample of the above mentioned -S5000 and S5100 are same product, only model name is different.					

Contents

1. Laboratory Information	4
2. Description of EUT	5
3. Test Standards	6
4. Measurement condition	7
5. Carrier Frequency Separation	10
5.1 Test procedure	10
5.2 Test instruments and measurement setup	10
5.3 Measurement results	10
5.4 Trace data	11
6. Maximum Peak Output Power	12
7. Number of Hopping Frequency	13
7.1 Test procedure	13
7.2 Measurement results	13
8. Time of Occupancy (Dwell Time)	15
8.1 Test procedure	15
8.2 Test instruments and measurement setup	15
8.3 Measurement results	15
8.4 Trace data	15
9. Band-Edge and Out of Band Emissions	17
9.1 Test procedure	17
9.2 Test instruments and measurement setup	17
9.3 Measurement results	17
9.4 Trace data of band-edge & out of emissioin	18

10. Measurement of radiated emission	20
10.1 Measurement equipment	20
10.2 Environmental conditions	20
10.3 Test data	21
11. Measurement of conducted emission	25
11.1 Measurement equipment	25
11.2 Environmental conditions	25
11.3 Test data	26
12. Antenna Requirement	29
12.1 Standard Applicable	29
12.2 Antenna connected construction	29

Appendix 1. Spectral diagram

1. Laboratory Information

1.1 General

This EUT (Equipment Under Test) has been shown to be capable of compliance with the applicable technical standards and is tested in accordance with the measurement procedures as indicated in this report.

ESTECH Lab attests to accuracy of test data. All measurement reported herein were performed by ESTECH Co., Ltd.

ESTECH Lab assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

1.2 Test Lab.

Corporation Name : ESTECH Co. Ltd

Head Office : Rm 1015, World Venture Center II, 426-5, Gasan-dong, Geumcheon-gu, Seoul, Korea
(Safety & Telecom. Test Lab)

EMC Test Lab : 58-1 Osan-Ri, GaNam-Myon, YeoJoo-Gun, KyungKi-Do, Korea
97-1 Hoiuk-Ri Majang-Myon, Icheon-city, KyungKi-Do, Korea

1.3 Official Qualification(s)

MIC : Granted Accreditation from Ministry of Information & Communication for EMC, Safety and Telecommunication

KOLAS : Accredited Lab By Korea Laboratory Accreditation Schema base on CENELEC requirements

FCC : Filed Laboratory at Federal Communications Commission

VCCI : Granted Accreditation from Voluntary Control Council for Interference from ITE

2. Description of EUT

2.1 Summary of Equipment Under Test (Bluetooth)

Product Name : PCS GSM Phone
 Model Number : S5000, S5100
 Modulation Type : FHSS, GFSK
 Transfer Rate : 1Mbps
 Number of Channels : 79 ch
 Serial Number : NONE
 Manufacturer : LG Electronics Inc.
 Country of origin : KOREA
 Rating : INPUT:AC120V , 50/60Hz 150~100mA Output:DC 5.2V,800mA
 Receipt Date : 2005-10-27

2.2 General descriptions of EUT

The S5000,S5100 PCS GSM Phone offers Bluetooth as a feature. The Bluetooth frequency hopping transceiver is designed to operate between 2400 and 2483.5MHz.

3. Test Standards

Test Standard : FCC PART 15 (2002)

This Standard sets out the regulations under which an intentional, unintentional, or incidental radiator may be operated without an individual license. It also contains the technical specifications, administrative requirements and other conditions relating to the marketing of Part 15 devices.

Test Method : ANSI C 63.4 (2003)

This standard sets forth uniform methods of measurement of radio-frequency (RF) signals and noise emitted from both unintentional and intentional emitters of RF energy in the frequency range 9 kHz to 40 GHz. Methods for the measurement of radiated and AC power-line conducted radio noise are covered and may be applied to any such equipment unless otherwise specified by individual equipment requirements. These methods cover measurement of certain devices that deliberately radiate energy, such as intentional emitters, but does not cover licensed transmitters. This standard is not intended for certification/approval of avionic equipment or for industrial, scientific, and medical (ISM) equipment. These methods apply to the measurement of individual units or systems comprised of multiple units.

Summary of Test Results

Applied Standard : 47 CFR Part 15, Subpart C				
Standard	Test Type	Result	Remark	Limit
15.207	AC Power Conducted Emission	Pass	Meet the requirement	
15.247(a)(1)	Carrier Frequency Separation & 20 Bandwidth	Pass	Meet the requirement	>25kHz
15.247(b)	Maximum Peak output power	Pass	Meet the requirement	30dBm(1W)
15.247(a)(1)(ii)	Number of Hopping Frequency	Pass	Meet the requirement	>75
15.247(c)	Transmitter Radiated Emission	Pass	Meet the requirement	
15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Pass	Meet the requirement	<400ms
15.247(c)	Band Edge Measurement	Pass	Meet the requirement	

4. Measurement Condition

4.1 EUT Operation.

a. Channel

Ch.	Frequency	Ch.	Frequency
0	2402 MHz	40	2442 MHz
1	2403 MHz	41	2443 MHz
2	2404 MHz	42	2444 MHz
3	2405 MHz	43	2445 MHz
4	2406 MHz	...	...
...	...	78	2480 MHz
39	2441 MHz		

b. Measurement Channel : Low(2402MHz), Middle(2441MHz),High(2480MHz)


c. Test Mode : FHSS, GFSK

d. Test rate : 1Mbps

4.2 EUT Operation.

- * The EUT was in the following operation mode during all testing
- * The operational conditions of the EUT was determined by the manufacturer according to the typical use of the EUT with respect to the expected highest level of emission

4.3 Configuration and Peripherals



4.4 EUT and Support equipment

Equipment Name	Model Name	S/N	Manufacturer	Remark (FCC ID)
PCS GSM Phone	S5000,S51003	NONE	LG Electronics Inc.	EUT
Travel Adapter	TA-25GR2	050324BE03966	LG Electronics Inc.	—
Headset	NONE	NONE	LG Electronics Inc.	
Bluetooth Tester	TC-3000A	3000A570224	TESCOM Co., Ltd.	
Antenna	MBMMC-2600-2	4104186	GAMANU	

4.5 Cable Connecting

Start Equipment		End Equipment		Cable Standard		Remark
Name	I/O port	Name	I/O port	Length	Shielded	
PCS GSM Phone	Power	Adapter	—	2	Y	—
PCS GSM Phone	MIC	Headset	—	2	N	—
PCS GSM Phone	Speaker	Headset	—	2	N	—

5. Carrier Frequency Separation

5.1 Test procedure

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

5.2 Test instruments and measurement setup

The spectrum analyzer is set to as following.

- . RBW= 300KHz
- . VBW= 300KHz
- . Span= 3MHz
- . Sweep= suitable duration based on the EUT specification.

6dB Bandwidth Test Instruments

Description	Model	Serial Number
Spectrum Analyzer	E4407B	US42041281
Bluetooth Tester	TC-3000A	3000A570224
Dual Directional Coupler	778D	17575
-Spectrum Analyzer <=> EUT	Loss: 2.0dB	-

5.3 Measurement results

EUT	Bluetooth	MODEL	S5000,S5100
MODE	FHSS	ENVIRONMENTAL CONDITION	25℃, 44%RH
INPUT POWER	120Vac, 60Hz		

CHANNEL	Channel Frequency (MHz)	Bandwidth at 20dB below(kHz)	Channel Separation (MHz)	Limit (kHz)	PASS /FAIL
39	2402	841.2	1.0	>25	PASS



ESTECH Co., Ltd.


Rm 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea




**Electromagnetic
Interference
Test Report**

5.4 Trace data

Channel Separation



20dB bandwidth



6. MAXIMUM PEAK OUTPUT POWER

6.1 Test procedure

The transmitter antenna terminal is connected to the input of a Spectrum Analyzer. Measurement is made while EUT is operating in transmission mode at the appropriate center frequency. The maximum peak output power measurement is 30dBm.

Maximum Peak Output Power Test Instruments

Description	Model	Serial Number
Spectrum Analyzer	E4407B	US42041281
Bluetooth Tester	TC-3000A	3000A570224
Dual Directional Coupler	778D	17575
-Spectrum Analyzer <=> EUT	Loss: 2.0dB	-

6.2 Measurement results

EUT	Bluetooth	MODEL	S5000,S5100
MODE	GFSK, DH5	ENVIRONMENTAL CONDITION	25℃, 44%RH
INPUT POWER	120Vac, 60Hz		

CHANNEL	Channel Frequency (MHz)	Peak Power Output(dBm)		Limit[1W] (dBm)	PASS/ FAIL
		(dBm)	(W)		
0	2402	-1.97	0.0006	30.0	PASS
39	2441	-0.15	0.0010	30.0	PASS
78	2480	-1.82	0.0007	30.0	PASS

7. Number of Hopping Frequency

7.1 Test procedure

According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz–2483.5MHz bands shall use at least 75 hopping frequencies.

7.2 Test instruments and measurement setup

The spectrum analyzer is set to as following.

- . RBW= 300KHz
- . VBW= 300KHz
- . Span= the frequency band of operation
- . Sweep= suitable duration based on the EUT specification.

The Number of Hopping Frequency Test Instruments

Description	Model	Serial Number
Spectrum Analyzer	E4407B	US42041281
Bluetooth Tester	TC-3000A	3000A570224
Dual Directional Coupler	778D	17575
–Spectrum Analyzer <=> EUT	Loss: 2.0dB	

7.3 Measurement results

EUT	Bluetooth	MODEL	S5000,S5100
MODE	FHSS	ENVIRONMENTAL CONDITION	25℃, 44%RH
INPUT POWER	120Vac, 60Hz		
Number of CH	Limit (Number of CH)	PASS/FAIL	
79	>75	PASS	





ESTECH Co., Ltd.

Rm 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea



**Electromagnetic
Interference
Test Report**

7.4 Trace data



8. Time of Occupancy (Dwell Time)

8.1 Test procedure

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz–2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

8.2 Test instruments and measurement setup

The spectrum analyzer is set to as following.

- . RBW= 1MHz
- . VBW= 1MHz
- . Span= zero
- . Sweep= suitable duration based on the EUT specification.

The Time of Occupancy Test Instruments


Description	Model	Serial Number
Spectrum Analyzer	E4407B	US42041281
Bluetooth Tester	TC-3000A	3000A570224
Dual Directional Coupler	778D	17575
-Spectrum Analyzer <=> EUT	Loss: 1.0dB	

8.3 Measurement results


EUT	Bluetooth	MODEL	S5000,S5100
MODE	FHSS	ENVIRONMENTAL CONDITION	25℃, 43%RH
INPUT POWER	120Vac, 60Hz		
Channel	Pulse Time(ms) (DH1/DH5)	Limit (ms)	PASS/FAIL
39	0.43/2.95	400.0	PASS

8.4 Trace data

DH1



DH5



9. band-edge and out of band emissions.

9.1 Test procedure

The radio frequency power at 20dB down from the highest inband power level is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency. The band edge&out of band emission shall be at least 20dB below of the highest inband power level.

9.2 Test instruments and measurement setup

The spectrum analyzer is set to as following.

- . RBW= 100KHz
- . VBW= 100KHz
- . Span= suitable frequency span
- . Sweep= suitable duration based on the EUT specification.

Band Edge&Out of Emission Test Instruments

Description	Model	Serial Number
Spectrum Analyzer	E4407B	US42041281
Bluetooth Tester	TC-3000A	3000A570224
Dual Drectional Coupler	778D	17575
-Spectrum Analyzer <=> EUT	Loss: 2.0dB	-

9.3 Measurement results of band-edge & out of emission

EUT	Bluetooth	MODEL	LG-G692
MODE	GFSK	ENVIRONMENTAL CONDITION	25℃, 43%RH
INPUT POWER	120Vac, 60Hz		

* Refer to attach spectrum analyzer data chart.



ESTECH Co., Ltd.


Rm 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea




**Electromagnetic
Interference
Test Report**

9.4 Trace data of band-edge & Out of Emission

CH 0



CH78






ESTECH Co., Ltd.

Rm. 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea




Electromagnetic Interference Test Report

CH 0



CH78



10. Measurement of radiated disturbance

Above 30 MHz Electric Field strength was measured in accordance with FCC Part 15 (2002) & ANSI C 63.4 (2003). The test setup was made according to FCC Part 15 (2002) & ANSI C 63.4 (2003) on an open test site, which allows a 3m distance measurement. The EUT was placed in the center of wooden turntable. The height of this table was 0.8m. The measurement was conducted with both horizontal and vertical antenna polarization. The turntable has fully rotated. For further description of the configuration refer to the picture of the test set-up.

10.1 Measurement equipments

Equipment Name	Type	Manufacturer	Serial No.	Next Calibration date
TEST Receiver	ESVS10	Rohde & Schwarz	838562/002	2006. 1. 19
TEST Receiver	ESPI7	Rohde & Schwarz	100185	2006. 8. 22
Spectrum Analyzer	R3261C	ADVANTEST	61720116	2006. 4. 10
LogBicon Antenna	VULB 9160	S/B	3142	2006. 7. 04
Horn Antenna	BBHA 9120 D	SCHWARZBECK	352	2006. 4. 06
Horn Antenna	BBHA 9120 D	SCHWARZBECK	469	2006. 3. 01
Spectrum Analyzer	8563E	HP	3623A05297	2006. 3. 3
PREAMPLIFIER	8449B	HP	3008A00581	2006. 3. 14
BLUETOOTH TESTER	TC-3000A	TESCOM	3000A570224	–
Turn Table	2087	EMCO	2129	–
Antenna Mast	2070-01	EMCO	9702-203	–
ANT Mast Controller	2090	EMCO	1535	–
Turn Table Controller	2090	EMCO	1535	–

10.2 Environmental Condition

Test Place : Open site(3m)
 Temperature (°C) : 22 °C
 Humidity (%) : 45 %

10.3 Test data

Measurement Distance : 3 m

Frequency (MHz)	Reading (dB μ V)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dB μ V/m)	Result (dB μ V/m)	Margin (dB μ V/m)
38.25	7.40	V	1.0	12.43	0.9	40.0	20.77	-19.23
73.62	4.40	H	2.1	11.04	1.3	40.0	16.74	-23.26
112.11	4.20	H	1.9	11.10	1.6	43.5	16.91	-26.59
158.97	5.60	H	1.8	13.97	1.9	43.5	21.49	-22.01
194.25	3.90	H	1.6	11.19	2.2	43.5	17.29	-26.21
216.01	4.90	H	1.3	10.72	2.3	43.5	17.89	-25.61
332.85	5.30	H	1.0	13.92	2.8	46.0	22.03	-23.97
404.64	4.60	H	1.0	15.42	3.2	46.0	23.19	-22.81
540.84	3.50	V	1.0	17.70	3.7	46.0	24.85	-21.15
685.69	2.80	H	1.0	19.97	4.2	46.0	26.96	-19.04
753.09	4.10	V	2.1	21.26	4.4	46.0	29.78	-16.22
833.24	3.10	H	1.0	21.98	4.8	46.0	29.86	-16.14
938.62	6.80	V	1.6	23.37	5.0	46.0	35.16	-10.84
Remark	H : Horizontal, V : Vertical							

10.3-1 Test data(CH0)

Measurement Distance : 3 m

Frequency (MHz)	Reading (dBμV)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dBμV/m)	Result (dBμV/m)	Margin (dBμV/m)
PEAK								
2402.00	102.83	H	1.4	27.62	-33.0	*OB	97.45	-
4804.00	51.50	H	1.2	31.27	-32.3	74.0	50.47	-23.53
7260.00	45.67	H	1.2	36.55	-32.0	74.0	50.22	-23.78
2402.00	94.50	V	1.7	27.62	-33.0	*OB	89.12	-
4804.00	54.67	V	1.7	31.27	-32.3	74.0	53.64	-20.36
7260.00	44.00	V	1.7	36.55	-32.0	74.0	48.55	-25.45
AV								
2402.00	65.50	H	1.4	27.62	-33.0	*OB	60.12	-
4804.00	38.17	H	1.2	31.27	-32.3	54.0	37.14	-16.86
7260.00	34.33	H	1.2	36.55	-32.0	54.0	38.88	-15.12
2402.00	61.33	V	1.7	27.62	-33.0	*OB	55.95	-
4804.00	38.67	V	1.7	31.27	-32.3	54.0	37.64	-16.36
7260.00	34.67	V	1.7	36.55	-32.0	54.0	39.22	-14.78
Remark	H : Horizontal, V : Vertical TEST MODE : CH 0(2402MHz) *The TX signal isn't detected from 3th harmonics. *OB = Operating band *CL = Cable Loss-Amplifier Gain(In case of above1000Mhz) *CL = Cable Loss(In case of below1000Mhz)							

10.3-2 Test data(CH39)

Measurement Distance : 3 m

Frequency (MHz)	Reading (dB μ V)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dB μ V/m)	Result (dB μ V/m)	Margin (dB μ V/m)
PEAK								
2441.00	104.33	H	1.7	27.60	-33.0	*OB	98.93	-
4882.00	56.17	H	1.3	31.38	-32.3	74.0	55.25	-18.75
7323.00	46.33	H	1.3	36.57	-32.1	74.0	50.80	-23.20
2441.00	97.33	V	1.3	27.60	-33.0	*OB	91.93	-
4882.00	57.67	V	1.6	31.38	-32.3	74.0	56.75	-17.25
7323.00	45.17	V	1.6	36.57	-32.1	74.0	49.64	-24.36
AV								
2441.00	63.33	H	1.7	27.60	-33.0	*OB	57.93	-
4882.00	39.67	H	1.3	31.38	-32.3	54.0	38.75	-15.25
7323.00	34.50	H	1.3	36.57	-32.1	54.0	38.97	-15.03
2441.00	62.00	V	1.3	27.60	-33.0	*OB	56.60	-
4882.00	40.83	V	1.6	31.38	-32.3	54.0	39.91	-14.09
7323.00	34.17	V	1.6	36.57	-32.1	54.0	38.64	-15.36
Remark	H : Horizontal, V : Vertical TEST MODE : CH 39 (2441MHz) *The TX signal isn't detected from 3th harmonics. *OB = Operating band *CL = Cable Loss-Amplifier Gain(In case of above1000Mhz) *CL = Cable Loss(In case of below1000Mhz)							

10.3-3 Test data(CH78)

Measurement Distance : 3 m

Frequency (MHz)	Reading (dB μ V)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dB μ V/m)	Result (dB μ V/m)	Margin (dB μ V/m)
PEAK								
2480.00	104.17	H	1.8	27.59	-33.0	*OB	98.76	-
4960.00	54.83	H	1.8	31.49	-32.3	74.0	54.02	-19.98
7440.00	44.83	H	1.6	36.55	-32.1	74.0	49.28	-24.72
2480.00	98.33	V	1.4	27.59	-33.0	*OB	92.92	-
4960.00	58.83	V	1.6	31.49	-32.3	74.0	58.02	-15.98
7440.00	44.67	V	1.5	36.55	-32.1	74.0	49.12	-24.88
AV								
2480.00	66.33	H	1.8	27.59	-33.0	*OB	60.92	-
4960.00	39.00	H	1.8	31.49	-32.3	54.0	38.19	-15.81
7440.00	34.17	H	1.6	36.55	-32.1	54.0	38.62	-15.38
2480.00	63.00	V	1.4	27.59	-33.0	*OB	57.59	-
4960.00	40.17	V	1.6	31.49	-32.3	54.0	39.36	-14.64
7440.00	34.17	V	1.5	36.55	-32.1	54.0	38.62	-15.38
Remark	H : Horizontal, V : Vertical TEST MODE : CH 78 (2480MHz) *The TX signal isn't detected from 3th harmonics. *OB = Operating band *CL = Cable Loss-Amplifier Gain(In case of above1000Mhz) *CL = Cable Loss(In case of below1000Mhz)							

11. Measurement of conducted disturbance

The continuous disturbance voltage of AC Mains in the frequency from 0.15 to 30 MHz was measured in accordance to FCC Part 15 (2002) & ANSI C 63.4 (2003). The test setup was made according to FCC Part 15 (2002) & ANSI C 63.4 (2003) in a shielded. The EUT was placed on a non-conductive table at least 80 above the ground plane. A grounded vertical reference plane was positioned in a distance of 40cm from the EUT. The distance from the EUT to other metal surfaces was at least 0.8m. The EUT was only earthen by its power cord through the line impedance stabilizing network. The power cord has been bundled to a length of 1.0m.. The test receiver with Quasi Peak detector complies with CISPR 16.

11.1 Measurement equipments

Equipment Name	Type	Manufacturer	Serial No.	Next Calibration date
LISN	ESH3-Z5	Rohde & Schwarz	838979/010	2006. 2. 18
LISN	NNLA8120A	Schwarzbeck	NONE	2006. 2. 18
TEST Receive	ESPI7	Rohde & Schwarz	100185	2006. 8. 22
Pulse Limiter	ESH3Z2	Rohde & Schwarz	NONE	2006. 6. 15
BLUETOOTH TESTER	TC-3000A	TESCOM	3000A570224	-

11.2 Environmental Condition

Test Place : Shield Room
 Temperature (°C) : 21 °C
 Humidity (%) : 42 %

10.3-1 Test data(CH0)

Frequency (MHz)	Correction Factor		Line (H/N)	Quasi-peak Value			Average Value		
	Lisn (dB)	Cable (dB)		Limit (dB μ V)	Reading (dB μ V)	Result (dB μ V)	Limit (dB μ V)	Reading (dB μ V)	Result (dB μ V)
0.17	0.07	0.0	H	64.96	28.42	28.50	54.96	—	—
0.19	0.07	0.0	N	64.04	32.49	32.59	54.04	—	—
0.20	0.07	0.0	N	63.61	30.34	30.44	53.61	—	—
0.29	0.07	0.1	N	60.52	32.69	32.85	50.52	—	—
0.41	0.07	0.2	H	57.65	26.94	27.17	47.65	—	—
0.64	0.08	0.2	H	56.00	27.24	27.52	46.00	—	—
0.70	0.08	0.2	H	56.00	29.05	29.33	46.00	—	—
0.82	0.09	0.2	H	56.00	29.63	29.92	46.00	—	—
0.94	0.09	0.2	H	56.00	27.72	28.01	46.00	—	—
1.35	0.10	0.2	H	56.00	31.75	32.08	46.00	—	—
1.82	0.11	0.3	H	56.00	30.45	30.84	46.00	—	—
2.23	0.12	0.3	H	56.00	29.80	30.22	46.00	—	—
2.29	0.12	0.3	H	56.00	29.41	29.83	46.00	—	—
5.58	0.22	0.3	N	60.00	29.81	30.36	50.00	—	—
5.64	0.23	0.3	H	60.00	30.97	31.53	50.00	—	—
5.70	0.23	0.3	H	60.00	30.11	30.67	50.00	—	—
5.82	0.23	0.3	N	60.00	30.10	30.67	50.00	—	—
Remark	H : Hot Line, N : Neutral Line TEST MODE : CH 0.(2402MHz)								

10.3-2 Test data(CH39)

Frequency (MHz)	Correction Factor		Line (H/N)	Quasi-peak Value			Average Value		
	Lisn (dB)	Cable (dB)		Limit (dB μ V)	Reading (dB μ V)	Result (dB μ V)	Limit (dB μ V)	Reading (dB μ V)	Result (dB μ V)
0.17	0.07	0.0	N	64.96	30.44	30.52	54.96	—	—
0.19	0.07	0.0	N	64.04	36.67	36.77	54.04	—	—
0.20	0.07	0.0	N	63.61	35.51	35.61	53.61	—	—
0.29	0.07	0.1	H	60.52	32.25	32.41	50.52	—	—
0.70	0.08	0.2	H	56.00	27.63	27.91	46.00	—	—
0.88	0.09	0.2	H	56.00	29.50	29.79	46.00	—	—
1.23	0.09	0.2	H	56.00	29.97	30.29	46.00	—	—
1.29	0.10	0.2	H	56.00	30.53	30.85	46.00	—	—
1.47	0.10	0.2	H	56.00	28.47	28.82	46.00	—	—
1.82	0.11	0.3	H	56.00	30.37	30.76	46.00	—	—
2.23	0.12	0.3	H	56.00	30.18	30.60	46.00	—	—
2.29	0.12	0.3	H	56.00	29.47	29.89	46.00	—	—
5.58	0.22	0.3	H	60.00	31.06	31.61	50.00	—	—
5.75	0.23	0.3	N	60.00	30.11	30.68	50.00	—	—
5.82	0.23	0.3	H	60.00	32.53	33.10	50.00	—	—
Remark	H : Hot Line, N : Neutral Line TEST MODE : CH 39 (2441MHz)								

10.3-3 Test data(CH78)

Frequency (MHz)	Correction Factor		Line (H/N)	Quasi-peak Value			Average Value		
	Lisn (dB)	Cable (dB)		Limit (dB μ V)	Reading (dB μ V)	Result (dB μ V)	Limit (dB μ V)	Reading (dB μ V)	Result (dB μ V)
0.17	0.07	0.0	H	64.96	29.81	29.89	54.96	—	—
0.19	0.07	0.0	N	64.04	32.95	33.05	54.04	—	—
0.20	0.07	0.0	N	63.61	29.30	29.40	53.61	—	—
0.23	0.07	0.1	H	62.45	27.70	27.82	52.45	—	—
0.29	0.07	0.1	N	60.52	28.47	28.63	50.52	—	—
0.35	0.07	0.1	N	58.96	29.91	30.11	48.96	—	—
0.46	0.07	0.2	H	56.69	27.84	28.09	46.69	—	—
0.52	0.07	0.2	H	56.00	28.21	28.48	46.00	—	—
0.58	0.08	0.2	H	56.00	27.31	27.59	46.00	—	—
1.05	0.09	0.2	H	56.00	28.17	28.47	46.00	—	—
1.17	0.09	0.2	H	56.00	30.22	30.53	46.00	—	—
1.29	0.10	0.2	H	56.00	30.21	30.53	46.00	—	—
1.87	0.11	0.3	H	56.00	28.72	29.11	46.00	—	—
2.28	0.12	0.3	H	56.00	26.97	27.39	46.00	—	—
5.57	0.22	0.3	H	60.00	32.21	32.76	50.00	—	—
5.63	0.23	0.3	N	60.00	30.17	30.73	50.00	—	—
5.69	0.23	0.3	N	60.00	30.01	30.57	50.00	—	—
5.92	0.24	0.3	H	60.00	31.97	32.55	50.00	—	—
6.69	0.27	0.4	H	60.00	26.75	27.40	50.00	—	—
Remark	H : Hot Line, N : Neutral Line TEST MODE : CH 78 (2480MHz)								

14. Antenna Requirement

14.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.24

14.2 Antenna Connected Construction

The antenna types used in this product are Multilayer Chip Antenna. The maximum Gain of this antenna is 0.52dBi.