

LG Electronics Inc.
Home Appliance Company, EMC Center

391-2, Ga Eum Jeong – Dong, Changwon City, Gyeong Nam
641-711, KOREA
Tel: + 82 55 260 3966, Fax: +82 55 260 3968

CERTIFICATION OF COMPLIANCE

Date of Issue: March 29, 2010

Test Report No: 10-EMUS-0060

Test Site: LG Electronics Changwon EMC Center

Applicant:	LG Electronics Inc.
Regulation:	FCC Part 18 – ISM Consumer Device
Test Procedure:	MP-5: 1985
Equipment Class:	Industrial, Scientific, and Medical equipment
EUT Type:	Microwave oven
Magnetron Type:	2M246 (LG)
Brand Name(s):	LG or GE
Model No.:	MX1788VSDL
FCC ID:	BEJX178NSB

This device has been verified to comply with the applicable requirements in the FCC Part 18 and was tested in accordance with the measurement procedures specified in MP-5: 1985.

I assure full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Kim Dae Woong/ Chief Research Engineer
Home Appliance Company,
EMC Center
LG Electronics Inc.

REPORT FOR A MICROWAVE OVEN

Scope - Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission

EUT Type:	Microwave oven
Model No.:	MX1788VSDL
FCC ID:	BEJX178NSB
Rule Part:	FCC Part 18
Test Procedure:	MP-5: 1985
Date of Test:	March 18, 2010 – March 24, 2010
Date of Issue:	March 29, 2010
Test Result:	Pass

EMC Center authorizes the above-named applicant to reproduce this report provided it is reproduced in its entirety.


EMC Center reports apply only to the specific sample(s) tested under stated test conditions. It is the manufacturer's responsibilities to assure that additional production unit of this model are manufactured with identical electrical and mechanical components.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

This report must not be used by the client to claim product endorsement by any agency of the U.S. Government.

The EMC Center facilities has been placed on file and the name of our organization added to the FCC's list for the FCC Part 15 and 18 of the Commission's Rules under Registration Number 93197.

Tested by:



Kim Tae Yul / Research Engineer
Home Appliance Company,
EMC Center
LG Electronics Inc.

Reviewed by:



Son Kwang Mu / Senior Research Engineer
Home Appliance Company,
EMC Center
LG Electronics Inc.

CONTENTS

	Page
1. CLIENT INFORMATION.....	3
2. EQUIPMENT UNDER TEST (EUT).....	3
3. TEST SITE.....	4
4. CALIBRATIONS OF MEASURING INSTRUMENT.....	4
5. DESCRIPTION OF TEST CONDITION.....	4
5.1 POWER LINE CONDUCTED EMISSION MEASUREMENTS	4
5.2 RADIATED EMISSIONS MEASUREMENT.....	5
6. MEASURING INSTRUMENT	9
7. TEST DATA	10
7.1 INPUT POWER.....	10
7.2 RF POWER OUTPUT MEASUREMENT ACCORDING TO MP-5.....	10
7.3 RF POWER OUTPUT MEASUREMENT ACCORDING TO IEC 60705.	11
7.4 FREQUENCY MEASUREMENTS.....	12
7.5 POWER DENSITY SAFETY CHECK	13
7.6 CONDUCTED EMISSIONS (SECTION 18.307).....	13
7.7 RADIATED EMISSIONS (SECTION 18.305)	14
APPENDIX A. TEST PLOT	15
APPENDIX B. LABELING REQUIREMENTS.....	19
APPENDIX C. BLOCK DIAGRAM / SCHEMATICS.....	20
APPENDIX D. TEST PHOTOS.....	21
APPENDIX E. EUT PHOTOS.....	22
APPENDIX F. OWNER'S MANUAL WITH REGARD TO FCC INSTRUCTION	27

1. CLIENT INFORMATION

The EUT has been tested by request of:

Company:	1. LG Electronics Inc. Cooking Appliances Division
(Manufacturer)	391-2, Ga Eum Jeong - Dong, Changwon City, Gyeong Nam, 641-711, Korea
	2. LG Electronics Tianjin Appliance Co., Ltd.
	Xing Dian Road, Bei Chen Distr., Tianjin 300402, People's Republic of China
Name of contact:	Jang Sup Lee
Telephone:	+82-551-260-3463
Fax:	+82-551-260-3223

2. EQUIPMENT UNDER TEST (EUT)

EUT is the LG Electronics Inc. Microwave Oven as followings:

Equipment:	Microwave oven
Model:	MX1788VSDL
Brand name:	LG or GE
Serial number:	N/A
Magnetron:	2M246 by LG
RF Frequency:	2,450 ± 50 MHz
RF Power Output (IEC 705):	900 W
Power Consumption	
Microwave Mode:	1650 W
Rated Input Voltage:	120 V~, 60 Hz
Rated Input Current	
Microwave Mode:	13.9 A
Cavity Volume:	1.7 Cu.ft
Oven Type:	Countertop / Household
Mode Stirrer:	Turntable and Stirrer
Power Cord:	Shielded
Outer Dimensions (inch)	29.9 (W) * 16.9 (H) * 15.7 (D)

EMI suppression device(s) installed in production: See schematics (Appendix C)

EMI suppression device(s) added and/or modified during test: None

3. TEST SITE

Measurement of radiated emissions from EUT was made at semi-anechoic chamber that has been in compliance with Federal Communications Commissions (FCC) requirements of clause 2.948 according to ANSI C63.4-1992 on March 21, 2009.

4. CALIBRATIONS OF MEASURING INSTRUMENT

All measurement was made with instruments calibrated according to the recommendation by manufacturer. Measurement of radiated emissions and power line conducted emissions were made with instruments conforming to American National Standard Specification, ANSI C63.4-1992. The calibration of measuring instrument, including any accessories that may affect test results, was performed according to the recommendation by manufacturer.

5. DESCRIPTION OF TEST CONDITION

5.1 Power line conducted emission measurements

Power line conducted emission measurements were based on the std. CISPR 11:2003+A2:2006.

5.1.1 Shielded enclosure

The measurement for power-line emissions from EUT was made in shielded enclosure that provides sufficient shielding effectiveness enough not to affect test results.

5.1.2 Detector function selection and bandwidth

During conducted emission measurement, a radio noise meter that has a CISPR quasi-peak detector with 10 kHz IF bandwidth of 6 dB was utilized.

5.1.3 Frequency range to be scanned

For conducted emissions measurement, frequency range of 150 kHz to 30 MHz included was investigated.

5.1.4 Unit of measurement

Test results for conducted emissions are reported in micro-volt.

5.1.5 Line impedance stabilization network (LISN)

A LISN with characteristics that conform to the requirements of ANSI C63.4-1992 was used for the measurement of conducted power-line radio noise; (50 micro-henries / 50 ohms). Chassis and earth-points for grounding of the LISN were earth-grounded.

5.1.6 Test conditions and configuration of EUT

The EUT was configured and operated in all modes of operation so as to find the maximum enumeration of emissions from EUT.

The EUT has designed to use the public AC lines with rated AC voltage as specified in owner's manual and Installation's manual of EUT and filtered to meet the requirement. AC

power was supplied to the EUT through LISN with characteristics described in 5.1.5 of part I of this report.

The EUT was placed on a 1 m×1.5 m×40 cm high wooden table which is placed on the earth-grounded conducting surface larger than 2 square meter. The vertical conducting surface was replaced with horizontal ground plane. Length of the power lead in excess of 80 cm horizontally separating the EUT from LISN was folded back-and-forth form at the center of the power cord not exceeding 40 cm in length.

The EUT was operated with a load of 1000 ml water initially at 20 ± 5 °C placed at the center of the load-carrying surface.

Each type of accessory provided by manufacturer or typically used and support equipment were connected to the EUT during measurement to the typical usage and applicable as nearly as practicable.

5.1.7 Measurement uncertainty

The measurement uncertainty describes the overall uncertainty of the given measured value during the operation of the EUT in the above-mentioned way.

The measurement uncertainty was calculated in accordance with NAMAS NIS 81:

“The treatment of uncertainty in EMC measurement.”

For calculated uncertainty of each item, refer the next page.

The measurement uncertainty was given with a confidence of 95%.

5.2 Radiated emissions measurement

5.2.1 Test site

Measurement was made in semi-anechoic chamber as described at Clause 3 in this report.

5.2.2 Detector function selection and bandwidth

In radiated emissions measurement, field strength meter that has CISPR quasi-peak and average detector was used. The bandwidth of the detector of instrument is 120 kHz for frequency range of 30 MHz – 1,000 MHz, and 1 MHz for frequency range of 1 GHz to 26 GHz. Emissions be measured are detected in average mode.

5.2.3 Unit of measurement

Test results of radiated emissions measurement are reported in microvolts per meter at the specific distance. Using the unit of dBμV on the test instrument, the indication unit was converted to field strength unit of μV/m as following method;

$$F / S = 10^{\{(R+AF+CF)/20\}} (\mu V/m)$$

here,

F / S: Field Strength in μV/m, R: Meter Reading Level in dB(μV),

AF: Antenna Factor in dB/m

CF: Conversion Factor

* 30 MHz ~ 1 GHz: CF = CL

* Above 1 GHz: CF = CL – PG + FL + AL

CL: Cable Loss (dB)

FL: Filter Loss (dB)

PG: Preamplifier Gain (dB)

AL: Attenuator Loss (dB)

5.2.4 Antennas

Measurements were made using calibrated biconical antenna in range of 30 MHz to 300 MHz, log-periodic antenna in range of 300 MHz to 1,000 MHz and horn antenna in range of 1 to 26 GHz to determine the emission characteristics of the EUT. Measurements were also made for both horizontal and vertical polarization.

The horizontal distance between the receiving antenna and the closest periphery of the EUT was 3 meters for horn antenna and 10 meters for biconical and log-periodic antenna.

5.2.5 Frequency range to be scanned

For radiated emissions measurements, the spectrum in the range of 30 to 1,000 MHz and above, if found, was investigated.

5.2.6 Test conditions and configuration of EUT

The EUT was configured and operated in all modes of operation so as to find the maximum RF energy generated from EUT.

The power was furnished with rated (normal) AC 120 volts, as specified in the Owner's manual of EUT. The EUT was placed on a 1 m high non-metallic table. The turntable containing the system was rotated and the antenna height was varied 4 m to find the maximum RF energy detected from EUT.

Each type of accessory provided by manufacturer or typically used and support equipment were connected to the EUT during measurement to the typical usage and applicable as nearly as practicable.

5.2.7 Measurement uncertainty

The measurement uncertainty describes the overall uncertainty of the given measured value during the operation of the EUT in mentioned above way.

The measurement uncertainty was calculated in accordance with NAMAS NIS 81: "The treatment of uncertainty in EMC measurement."

For calculated uncertainty of each item, refer the next page.

The measurement uncertainty was given with a confidence of 95%.

< Fundamental Frequency Uncertainty (2,450 MHz) >

Symbol	Contribution	Value (dB)		Probability Distribution	Divisor	Standard Uncertainty	Standard Uncertainty Squared
			3 m			Horn Antenna (Value / Divisor)	
V ₁	Ambient signals				1	0.00	0.0
V ₂	Antenna factor calibration	Expanded Uncertainty	1.5	normal (k = 2)	2	0.75	0.6
V ₃	Cable loss calibration	Expanded Uncertainty	0.5	normal (k = 2)	2	0.25	0.1
V ₄	Receiver specification	Tolerance	1.0	rectangular	1.732	0.58	0.3
V ₅	Measurement distance variation	Tolerance	0.3	rectangular	1.732	0.17	0.0
V ₆	Site imperfections	Tolerance	0.2	rectangular	1.732	0.12	0.0
V ₇	Mismatch Receiver VRC: $\gamma_r = 0.33$ Antenna VRC: $\gamma_a = 0.20$ Uncertainty limits $20\text{Log}(1 \pm \gamma_r \gamma_a)$	Tolerance	1.0	rectangular	1.732	0.58	0.3
V ₈	System repeatability (previous assessment of $s(q_k)$ from 5 repeats, 1 reading on EUT Repeatability of EUT*)		0.5	Std Deviation	1	0.50	0.3
	Combined standard uncertainty $u_c(y)$		1.26	normal			
	Expanded uncertainty U		2.52	normal (k = 2)			

$$u_c(y) = \sqrt{\left(\frac{0.0}{1}\right)^2 + \left(\frac{1.5}{2}\right)^2 + \left(\frac{1.5}{2}\right)^2 + \frac{1.0^2 + 0.3^2 + 0.2^2}{3} + \frac{1}{2}^2 + 0.5^2}$$

The level of confidence will be approximately 95% (The coverage factor: k=2)

$$U = 2 u_c(y) = 2 \times 1.26 = \pm 2.52 \text{ dB}$$

< Radiated Emission Uncertainty (Above 1 GHz) >

Symbol	Contribution	Value (dB)		Probability Distribution	Divisor	Standard Uncertainty	Standard Uncertainty Squared
			3 m			Horn Antenna (Value / Divisor)	
V ₁	Ambient signals			-	1	0.00	0.0
V ₂	Antenna factor calibration #1	Expanded Uncertainty	1.5	normal (k = 2)	2	0.75	0.6
V ₃	Antenna factor calibration #2	Expanded Uncertainty	1.5	normal (k = 2)	2	0.75	0.6
V ₄	Cable loss calibration	Expanded Uncertainty	0.5	normal (k = 2)	2	0.25	0.1
V ₅	Receiver specification	Tolerance	1.0	rectangular	1.732	0.58	0.3
V ₆	Highpass filter	Tolerance	0.12	rectangular	2	0.06	0.0
V ₇	Measurement distance variation	Tolerance	0.3	rectangular	1.732	0.17	0.0
V ₈	Site imperfections	Tolerance	1.0	rectangular	2	0.50	0.3
V ₉	Mismatch Receiver VRC: $\gamma_r = 0.33$ Antenna VRC: $\gamma_a = 0.2$ Uncertainty limits $20\text{Log}(1 \pm \gamma_r \gamma_a)$	Tolerance	0.15	U-shaped	1.414	0.11	0.0
V ₁₀	System repeatability (previous assessment of $s(q_k)$ from 5 repeats, 1 reading on EUT Repeatability of EUT*)		0.5	Std Deviation	1	0.50	0.3
	Combined standard uncertainty $u_c(y)$		1.44	normal			
	Expanded uncertainty U		2.87	normal (k = 2)			

$$u_c(y) = \sqrt{\left(\frac{0.0}{1}\right)^2 + \left(\frac{1.5}{2}\right)^2 + \left(\frac{1.5}{2}\right)^2 + \left(\frac{0.5}{2}\right)^2 + \frac{1.0^2}{3} + \left(\frac{0.12}{2}\right)^2 + \frac{0.3^2}{3} + \left(\frac{1.0}{2}\right)^2 + \frac{0.15^2}{2} + 0.5^2}$$

The level of confidence will be approximately 95%. (The coverage factor: k=2)

$$U = 2 u_c(y) = 2 \times 1.44 = \pm 2.87 \text{ dB}$$

< Electric Field Strength Uncertainty (30 MHz – 1 GHz) >

Symbol	Contribution	Value (dB)		Probability Distribution	Divisor	Standard Uncertainty	Standard U Squared
			10 m			UltraLog Antenna (Value / Divisor) 10 m	
V ₁	Ambient signals			Std Deviation	1	0.00	0.
V ₂	Antenna factor calibration	Tolerance	0.5	rectangular	2	0.25	0.
V ₃	Cable loss calibration	Expanded Uncertainty	0.5	normal (k = 2)	2	0.25	0.
V ₄	Receiver specification	Tolerance	1.0	rectangular	1.732	0.58	0.
V ₅	Antenna directivity	Tolerance	0.5	rectangular	1.732	0.29	0.
V ₆	Antenna factor variation with height	Tolerance	2.0	rectangular	1.732	1.15	1.
V ₇	Antenna phase center variation	Tolerance	0.0	rectangular	1.732	0.0	0.
V ₈	Antenna factor frequency interpolation	Tolerance	0.25	rectangular	1.732	0.14	0.
V ₉	Measurement distance variation	Tolerance	0.1	rectangular	1.732	0.06	0.
V ₁₀	Site imperfections	Tolerance	1.0	normal	2	0.50	0.
V ₁₁	Mismatch Receiver VRC: $\pi_1 = 0.09$ Antenna VRC: $\pi_2 = 0.33$ Uncertainty limits $20\text{Log}(1 + \pi_1 + \pi_2)$	Tolerance	0.25	U-shaped	1.414	0.18	0.
V ₁₂	System repeatability (previous assessment of $s(q_k)$ from 5 repeats, 1 reading on EUT Repeatability of EUT*)		0.5	Std Deviation	1	0.50	0.
	Combined standard uncertainty $u_c(y)$		1.56	normal	2		
	Expanded uncertainty U		3.12	normal (k = 2)	2		

$$u_c(y) = \sqrt{\left(\frac{0.0}{1}\right)^2 + \left(\frac{0.5}{2}\right)^2 + \left(\frac{0.5}{2}\right)^2 + \frac{1.0^2 + 0.5^2 + 2.0^2 + 0.0^2 + 0.25^2 + 0.1^2}{3} + \left(\frac{1.0}{2}\right)^2 + \frac{0.25^2}{2} + 0.5^2}$$

The level of confidence will be approximately 95%. (The coverage factor: k=2)

$$U = 2 u_c(y) = 2 \times 1.56 = \pm 3.1 \text{ dB}$$

< Line Conducted Uncertainty >

Symbol	Contribution	Value (dB)		Probability Distribution	Divisor	Standard Uncertainty (dB)	Standard U Squared
						150 kHz - 30 MHz (Value / Divisor)	
V ₁	Receiver specification	Tolerance	1.0	rectangular	1.732	0.58	0.
V ₂	LISN coupling specification	Tolerance	1.0	rectangular	1.732	0.58	0.
V ₃	Cable and input attenuator calibration	Expanded Uncertainty	0.5	normal (k = 2)	2	0.25	0.
V ₄	Mismatch Receiver VRC: $\pi_1 = 0.09$ LISN VRC: $\pi_2 = 0.8$ Uncertainty limits $20\text{Log}(1 + \pi_1 + \pi_2)$	Tolerance	0.75	U-shaped	1.414	0.53	0.2
V ₅	System repeatability (previous assessment of $s(q_k)$ from 10 repeats, 1 reading on EUT)		0.50	standard deviation	1	0.50	0.2
	Combined standard uncertainty $u_c(y)$		1.12	normal			
	Expanded uncertainty U		2.25	normal (k = 2)			

$$u_c(y) = \sqrt{\frac{1.0^2 + 1.0^2}{3} + \left(\frac{0.5}{2}\right)^2 + \frac{0.75^2}{2} + 0.50^2} = 1.12 \text{ dB}$$

The level of confidence will be approximately 95%. (The coverage factor: k=2)

$$U = 2 u_c(y) = 2 \times 1.12 = \pm 2.25 \text{ dB}$$

6. MEASURING INSTRUMENT

Instrument	Model	Cal. Due date	Serial No.	Control No.
Accessory Kit	-	-	7044/45-002	99-IRE-16
Microwave Amp	83006A	10/21/2010	39550M00118	00-IRE-31
Horn Antenna	RGA-180 (Electro Metrics)	09/23/2011	2517	99-IRE-22
	RGA-60 (Electro Metrics)	09/10/2010	6104	99-IRE-21
Antenna Master	2070-2 (EMKO)	-	9903-2231	99-IRE-23
Ultra Log Antenna	HL562 (Chase)	08/28/2010	830547/007	99-IRE-26
High Pass Filter	11SH10-4500/ X1800-010	10/21/2010	2	99-IRE-07
EMI Receiver	ESI26 (R&S)	10/19/2010	835336/008	00-IRE-30
	ESU26 (R&S)	10/20/2010	100164	08-IRE-01
LISN	ESH2-Z5 (R&S)	06/11/2010	825640/003	99-ICE-02
Microwave Cable	Sucoflex 104	-	125484/4	-
Microwave Cable	Sucoflex 106	-	13417/6	-
Microwave Cable	Sucoflex 106	-	13419/6	-
Microwave Cable	Sucoflex 106	-	13418/6	-
Microwave Cable	Sucoflex 104	-	125483/4	-
Microwave Cable	Sucoflex 104	-	12548/4	-
Microwave Cable	Sucoflex 106	-	13416/6	-
Microwave Cable	Sucoflex 106	-	13416/6	-
Microwave Cable	Sucoflex 104PE	-	46894/4PE	-
Microwave Cable	Sucoflex 104PE	-	46895/PE	-
Semi Anechoic Chamber	YES INC.	-	-	99-CFA-01
Shield Screen Room	YES INC.	-	-	99-CFA-02
Microwave Survey Meter	Holaday HI-1710/HI-2623	02/02/2011	93083	FJZ431HA

7. TEST DATA

7.1 Input Power

The input power was measured using Wattmeter. A 275 ml water load in a polypropylene beaker is placed in the center of the oven. The 275 ml water was chosen for its compatibility with UL procedure to determine input ratings. The oven was operated at the rated input and full output power for 6 minutes.

1) Magnetron type: 2M246 by LG

<u>Mode</u>	<u>Input Voltage</u>	<u>Current [A]</u>	<u>Power Consumption</u> <u>[W]</u>	<u>Manufacturer</u> <u>Rating [A]</u>
Microwave	120 Vac, 60 Hz	12.4	1390	13.9

7.2 RF Power Output Measurement according to MP-5.

The Calorimetric Method was used to determine maximum output power. A 1,000 ml water load was placed in the center of the oven. A mercury thermometer was used to measure temperature rise. The test method was described in MP-5.

1) Magnetron type: 2M246 by LG

$$\text{Power [W]} = \frac{(4.187 \text{ Joules/Cal}) * (\text{Volume in ml}) * (\text{Temperature Rise})}{\text{Time in Seconds}}$$

<u>Quantity of Water</u>	<u>Starting Temperature</u>	<u>Final Temperature</u>	<u>Elapsed Time</u>
1,000 ml	21.5 °C	39.5 °C	120 Sec

$$\text{Power [W]} = \frac{4.187 * 1,000 * 18}{120}$$

$$\text{Power [W]} = 628.1 \text{ Watts}$$

7.3 RF Power Output Measurement according to IEC 60705.

The test was performed according to the IEC Publication 60705/1999.

A cylindrical container of borosilicate glass was used. It has a maximum thickness of 3 mm, external diameter of approximately 190 mm and height of approximately 90 mm.

Water having an initial temperature of $10\text{ }^{\circ}\text{C} \pm 1\text{ }^{\circ}\text{C}$ and quantity of $1000\text{ g} \pm 5\text{ g}$ was used.

Before starting the measurement, measure the initial temperature of water.

And then the container was placed in the center of the oven. The oven was operated until attaining temperature of water as $20\text{ }^{\circ}\text{C} \pm 2\text{ }^{\circ}\text{C}$ and then measured the final water temperature.

A mercury thermometer was used to measure temperature rise. The RF output power was calculated as below formula.


$$\text{Power [W]} = \frac{(4.187) * M_w * (T_2 - T_1) + 0.55 * M_c * (T_2 - T_0)}{t}$$

1) Magnetron type: 2M246 by LG

M_w : Mass of the water, in grams	1000
M_c : Mass of the container, in grams	440
T_2 : Final temperature of the water, in $^{\circ}\text{C}$	20.2
T_1 : Initial temperature of the water, in $^{\circ}\text{C}$	10.0
T_0 : Ambient temperature, in $^{\circ}\text{C}$	19.7
t : Heating time in seconds, excluding the magnetron filament heat-up time.	47

$$\text{Power [W]} = \frac{4.187 * 1,000 * 10.2 + 0.55 * 440 * (0.5)}{47} = 911.2 \text{ Watts}$$

7.4 Frequency measurements



1) Magnetron type: 2M246 by LG

(1) Frequency vs Line Voltage Variation Test

Variation of line voltage from 80 % (96 V) to 125 % (150 V)

Load: 1,000 ml

Fundamental Frequency: 2,450 MHz

Limit: $2.4 \text{ GHz} < f < 2.5 \text{ GHz}$

Maximum Frequency Observed: 2,479 MHz

Minimum Frequency Observed: 2,467 MHz

Result: Pass

(2) Frequency vs Load Variation Test

Frequency was measured at the rated input voltage (AC 120 V).

Initial Load: 1,000 ml

Final Load: 200 ml

Fundamental Frequency: 2,450 MHz

Limit: $2.4 \text{ GHz} < f < 2.5 \text{ GHz}$

Maximum Frequency Observed: 2,479 MHz

Minimum Frequency Observed: 2,469 MHz

Result: Pass

7.5 Power Density Safety Check

The power density was checked to ensure that the power is not greater than 1.0 mW/cm^2 at any location of the oven. The 1.0 mW/cm^2 is in accordance with CDRH and UL923 standard.

A microwave survey meter was placed on all sides, door and viewing, bottom, top and rear. The leakage microwave did not exceed the specified limits.

1) Magnetron type: 2M246 by LG

Maximum Leakage Microwave Observed: 0.35 mW/cm^2

Result: Pass

7.6 Conducted emissions (Section 18.307)

Conducted emission was measured at a frequency range 150 kHz to 30 MHz. The Power Line disturbance voltage was measured with the equipment under test (EUT) in a shielded room. The EUT was connected to a line impedance stabilization network (LISN) placed on the floor. The EUT was placed on a non-metallic table 0.4 m above the metallic, grounded floor. The distance to other metallic surfaces was at least 0.4 m.

The line conducted emission measurement procedure and test configuration is based on CISPR 11:2003 and Amendment 2:2006.

Amplitude measurements were performed with a quasi-peak detector and, if required, with an average detector.

Below data are the highest levels in Microwave mode.

An overview sweep performed with peak detector is included in the APPENDIX A (Test Plot).

1) Magnetron type: 2M246 by LG

Frequency [MHz]	Quasi-Peak			Average			Result
	Disturbance Level [dBuV]	Permitted Limit [dBuV]	Margin [dB]	Disturbance Level [dBuV]	Permitted Limit [dBuV]	Margin [dB]	
0.150	52.6	66.0	-13.4	33.1	56.0	-22.9	PASS
0.794	36.9	56.0	-19.1	11.3	46.0	-34.7	PASS
2.858	24.6	56.0	-31.4	8.2	46.0	-37.8	PASS
12.458	37.2	60.0	-22.8	11.3	50.0	-38.7	PASS
13.194	32.3	60.0	-27.7	14.9	50.0	-35.1	PASS

Remark: 1. "<<" means that disturbance level is lower than 20 dB below the limit.
2. The measured disturbance level includes all related factor. (LISN Insertion loss and Cable loss).

7.7 Radiated emissions (Section 18.305)

Radiated emission was measured at a frequency range 30 MHz to 26 GHz. The EUT was supported by a 1 m high wood table, measurement above 1 GHz and below 1 GHz.

Radiated emission measurement in frequency range 1 GHz to 26 GHz was made inside an anechoic chamber at 3 m to determine the emission characteristics of EUT. The EUT is configured and operated in a manner, which produces the maximum emission in a typical configuration. Final measurements were made outdoor in control room at 3-meter test method.

1) Magnetron type: 2M246 by LG

Test distance: 3 m

Freq. [MHz]	Ant. Factor [dB]	Cable Loss [dB]	Load [ml]	Load Location	Meter Reading [dBuV]	Field Strength @ 3 m [dBuV/m]	Field Strength @ 3 m [uV/m]	Field Strength @ 300 m [uV/m]	FCC Limit @ 300 m [uV/m]	Result
2.205	27.5	0.42	700	Center	28.8	56.7	683.9	6.8	28.0	PASS
2.389	28.3	0.44	700	Center	21.6	50.3	327.3	3.3	28.0	PASS
2.527	28.8	0.45	700	Center	15.2	44.4	166.0	1.7	28.0	PASS
2.740	29.5	0.47	700	Center	20.2	50.2	323.6	3.2	28.0	PASS
4.414	33.1	0.69	700	Center	18.9	52.7	431.5	4.3	28.0	PASS
4.956	33.4	0.90	700	Center	30.3	64.6	1698.2	17.0	28.0	PASS
4.955	33.4	0.90	700	Rt. Front	31.1	65.4	1862.1	18.6	28.0	PASS
4.960	33.4	0.90	300	Center	31.2	65.5	1883.6	18.8	28.0	PASS
4.954	33.4	0.90	300	Rt. Front	27.3	61.6	1202.3	12.0	28.0	PASS
7.353	35.8	1.10	700	Center	13.9	50.8	346.7	3.5	28.0	PASS
7.355	35.8	1.10	700	Rt. Front	11.8	48.7	272.3	2.7	28.0	PASS
7.433	35.8	1.10	300	Center	11.4	48.3	260.0	2.6	28.0	PASS
7.356	35.8	1.10	300	Rt. Front	15.4	52.3	412.1	4.1	28.0	PASS
8.126	36.7	0.83	700	Center	3.8	41.3	116.1	1.2	28.0	PASS
9.912	37.9	1.10	700	Center	17.2	56.2	645.7	6.5	28.0	PASS
12.405	39.4	1.20	700	Center	-0.3	40.3	103.5	1.0	28.0	PASS
17.262	41.3	1.60	700	Center	3.2	46.1	201.8	2.0	28.0	PASS

Other frequencies: No detected.

For measurement of 30 MHz – 1,000 MHz, refer to APPENDIX A (Test Plot).

Result: Pass

* Limit (at 300 m) = $25 * (\text{RF Power}/500)^{1/2}$ [uV/m]

* Field Strength below 1,000 MHz (at 300 m) [uV/m] = $10^{[(\text{Field strength at } 10\text{m(dBuV/m)}-29.5)/20]}$

* Field Strength above 1,000 MHz (at 300 m) [uV/m] = $K * 10^{[(\text{Field strength at } 3\text{m(dBuV/m)})/20]}$

NOTES:


- Two representative modes (full power and defrost) of operation were investigated.
- A glass beaker was used as the container and the test was made with a shelf in its initial normal position.
- Load for measurement of radiation on second and third harmonic: Two loads, one of 700 and the other of 300 ml, of water were used. Each load was tested both with the beaker located in the center of the oven and with it in the corner.
- Load for all other measurements: 700 ml of water, with the beaker located in the center of the oven
- All other emissions are non-significant.
- The tests were made with average detector for frequency range of 30 MHz to 26 GHz.

APPENDIX A. Test Plot


◆ 150 kHz ~ 30 MHz (Magnetron type: 2M246 by LG)

- Operating Mode: Maximum RF Power Output
- Detect Mode: Quasi-Peak(x)/Average(+), Scan Mode: Peak

<Phase: L1>




<Phase: N>




◆ 30 MHz ~ 1000 MHz (Magnetron type: 2M246 by LG)

- Operating Mode: Maximum RF Power Output
- Detect Mode: Average, Scan Mode: Peak
- Measurement Distance: 10 meters

<Antenna Polarization: Horizontal>




<Antenna Polarization: Vertical>



◆ Voltage Variation (Magnetron type: 2M246 by LG)


- Detect Mode: Average, Scan Mode: Peak

<Maximum Frequency Observed: 2,479 MHz>



MX1788VSDL Fundamental 150V
Date: 19.MAR.2010 12:16:00

<Minimum Frequency Observed: 2,467 MHz>



MX1788VSDL Fundamental 132V
Date: 19.MAR.2010 11:56:05

◆ Load Variation (Magnetron type: 2M246 by LG)

- Detect Mode: Average, Scan Mode: Peak

<Maximum Frequency Observed: 2,479MHz >



< Minimum Frequency Observed: 2,469 MHz >



APPENDIX B. Labeling Requirements

Labeling requirements per Section 2.925 and 15.19.

The label shown shall be permanently affixed at a conspicuous location on the device and be readily visible to the user at the time purchase.




<Fig. 1. Sample Label of Nameplate>

* Alternate location:
The nameplate may be alternatively affixed on the left side of control panel or internal surface of oven cavity or rear surface of oven.



< Fig. 2. Photo of the physical location of the label>

APPENDIX C. Block Diagram / Schematics



<Fig. 3. Schematic Diagram>

APPENDIX D. Test Photos

Test photos show the worst case configuration and cable placement with a minimum margin to the specifications.





APPENDIX E. EUT Photos











APPENDIX F. Owner's Manual with regard to FCC Instruction

WARNING **PACEMAKERS**

Most pacemakers are shielded from interference from electronic products, including microwaves. However, patients with pacemakers may wish to consult their physicians if they have concerns.

READ AND FOLLOW THIS SAFETY INFORMATION CAREFULLY. SAVE THESE INSTRUCTIONS

Things that are normal

Interference

- TV/radio interference might be noticed while using the microwave, similar to the interference caused by other small appliances. It does not indicate a problem with the microwave. Move the radio or TV as far away from the microwave as possible, or check the position of the TV/radio antenna.

Oven Heat

- Cookware may become hot because of heat transferred from the heated food. Oven mitts may be needed to handle the cookware.
- Steam or vapor may escape from around the door.

Cooking tips

- When cooking bacon, layer strips on a plate. Cover each layer with a paper towel.
- When cooking vegetables, use a microwave-safe casserole or bowl. Cover with a microwave-safe lid or vented plastic wrap.
- For frozen vegetables, follow the package instructions for adding water.
- For fresh vegetables, add 2 tablespoons of water for each serving.

23