



Test Report

For

Applicant : D-Link Corporation
Equipment Type : Dual Speed Hub
Model : DSH-8 , Ether-DH8E
FCC ID : KA2ED2DSH8H

Report No. : 994020FI



Test Report Certification

QuieTek Corporation

No.75-1, Wang-Yeh Valley, Yung-Hsing, Chiung-Lin,
Hsin-Chu County, Taiwan, R.O.C.

Tel : 886-3-592-8858, Fax: 886-3-592-8859

E-Mail : quietek@ms24.hinet.net

Accredited by NIST(NVLAP), VCCI, BSML, DNV, TUV

Applicant : D-Link Corporation
Address : No.20, Park Ave. II, Science-Based Industrial Park, Hsin-Chu ,
Taiwan, R.O.C.
Equipment Type : Dual Speed Hub
Model : DSH-8 , Ether-DH8E
FCC ID : KA2ED2DSH8H
Measurement Standard : CISPR 22/1994
Measurement Procedure : ANSI C63.4 /1992
Operation Voltage : 120Vac/60Hz
Classification : Class B
Test Result : Complied
Test Date : April 26, 1999
Report No. : 994020FI

The Test Results relate only to the samples tested.
The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented by: Lisa Chen

Test Engineer: Jack Wu

Approved: Kevin Wang

Lisa Chen

Jack Wu

Kevin Wang



TABLE OF CONTENTS

	Description	Page
1.	GENERAL INFORMATION	4
1.1	EUT DESCRIPTION	4
1.2	TESTED SYSTEM DETAILS	5
1.3	EUT CONFIGURATION	8
1.4	EUT EXERCISE SOFTWARE	8
1.5	TEST PERFORMED	10
1.6	TEST FACILITY	11
2.	CONDUCTED EMISSION	11
2.1	TEST EQUIPMENT LIST	11
2.2	TEST SETUP	11
2.3	LIMITS	12
2.4	TEST PROCEDURE	12
2.5	TEST RESULTS	13
3.	RADIATED EMISSION	13
3.1	TEST EQUIPMENT	13
3.2	TEST SETUP	14
3.3	LIMITS	14
3.4	TEST PROCEDURE	14
3.5	TEST RESULTS	15
4.	SUMMARY OF TEST RESULTS	24
5.	EMI REDUCTION METHOD DURING COMPLIANCE TESTING	25
6.	TEST PHOTOGRAPHS	29
7.	EUT DETAIL PHOTOGRAPHS	29

1. General Information

1.1 EUT Description

Applicant : D-Link Corporation

Address : No.20, Park Ave. II, Science-Based Industrial
Park, Hsin-Chu , Taiwan, R.O.C.

Equipment Type : Dual Speed Hub

Model : DSH-8 , Ether-DH8E

FCC ID : KA2ED2DSH8H

Operation Voltage : 120Vac/60Hz

Power Adaptor : Non-shielded,1.8m
KENTEX MODEL MA15-050

Data Cable : Non-shielded,1.2m

LAN Cable : STP,shielded,3m,7pcs;STP,shielded,20m,2pcs

- o 1 DOWNLINK PORT CONNECTED TO DOWNLINK HOST PC*
- o 7 DOWNLINK PORTS CONNECTED TO SHIELDED TWISTED
TERMINATED WITH DUMMY*
- o 1 UPLINK PORT CONNECTED TO HOST PC ON TEST TABLE*

1.2 Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

1.2.1 Host Personal Computer

Model Number	: P2L97
Serial Number	: 9842
FCC ID	: DoC
Manufacturer	: ASUS
Power Cord	: Non-Shielded, 1.8m
LAN CARD	: D-Link , FCC ID: KA2APG500X3

1.2.2 Monitor

Model Number	: CM752ET-311
Serial Number	: T8F006364
FCC ID	: DoC
Manufacturer	: HITACHI
Data Cable	: Shielded, 1.5m
Power Cord	: Shielded, 1.8m

1.2.3 Keyboard

Model Number	: 6311-TW2C
Serial Number	: N/A
FCC ID	: DoC
Manufacturer	: ACER
Data Cable	: Shielded, 1.8m

1.2.4 Mouse

Model Number	: M-S34
Serial Number	: LZB75078478
FCC ID	: DZL211029
Manufacturer	: HP
Data Cable	: Shielded, 1.8m

- 1.2.5 Modem**
Model Number : 1414
Serial Number : 980033039
FCC ID : IFAXDM1414
Manufacturer : ACEEX
Data Cable : Shielded,, 1.5m
Power Adapter : ACCEX, M/N: SCP41-91000A
Cable Output : Shielded, 1.5m
- 1.2.6 Modem**
Model Number : 1414
Serial Number : 980033033
FCC ID : IFAXDM1414
Manufacturer : ACEEX
Data Cable : Shielded,, 1.5m
Power Adapter : ACCEX, M/N: SCP41-91000A
Cable Output : Shielded, 1.5m
- 1.2.7 Printer**
Model Number : C2642A
Serial Number : MY75J1D1D2
FCC ID : B94C2642X
Manufacturer : HP
Data Cable : Shielded,, 1.2m
Power Adapter : NMB, M/N: C2175A
Cable for AC IN: Non-Shielded, 0.7m
Cable for AC Out: Non-Shielded, 1.5m
- 1.2.8 Joystick**
Model Number : JPD110
Serial Number : 9814A15646
FCC ID : DoC
Manufacturer : Maxxtro
Data Cable : Shielded, 1.7m
- 1.2.9 Video Camera**
Model Number : Vcam 3X
Serial Number : N/A
FCC ID : DoC
Manufacturer : Mustek
Data Cable (USB) : Shielded, 1.5m

Partner PC System1

1.2.10 Host Personal Computer

Model Number : P2L97
Serial Number : AS10233
FCC ID : DoC
Manufacturer : ASUS
Power Cord : Non-Shielded, 1.8m
LAN CARD : D-LINK, FCC ID: KA2APC500X3

1.2.11 Monitor


Model Number : CM752ET-311
Serial Number : T8D003312
FCC ID : DoC
Manufacturer : HITACHI
Data Cable : Shielded, 1.6m
Power Cord : Shielded, 1.8m

1.2.12 Keyboard

Model Number : 6311-TW2C
Serial Number : N/A
FCC ID : DoC
Manufacturer : ACER
Data Cable : Shielded, 1.8m



1.3 EUT Configuration



1.4 EUT Exercise Software

The EUT exercise program used during conducted testing was designed to exercise the EUT in a manner similar to a typical use. The exercise sequence is listed as below:

- 1.4.1 Setup the EUT and simulators as shown on 1.3
- 1.4.2 Turn on the power of all equipment.
- 1.4.3 Boot the PC from Hard Disk .
- 1.4.4 Data will communicate between host personal computer and partner personal computer through Hub (EUT).
- 1.4.5 The host computer's and partner computer's monitor will show the transmitting and receiving status when the communication is success.
- 1.4.6 Repeat the above procedure 1.4.4 to 1.4.6

1.5 Test performed

Conducted emissions were invested over the frequency range

from **0.15MHz to 30MHz** using a receiver bandwidth of 9KHz.

Radiated emissions were investigated over the frequency range
from **30MHz to 1000MHz** using a receiver bandwidth of 120KHz. Radiated testing was
performed at an antenna to EUT distance of 10 meters .

1.6 Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

Site Description: November 3, 1998 File on
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
Reference 31040/SIT1300F2



September 30, 1998 Accreditation on NVLAP
NVLAP Lab Code: 200347-0

February 23, 1999 Accreditation on DNV
Statement No. : 413-99-LAB11



December 8, 1998 Registration on VCCI
Registration No. for No.2 Shielded Room C-858
Registration No. for No.1 Open Area Test Site R-823
Registration No. for No.2 Open Area Test Site R-835



January 04, 1999 Accreditation on TÜV Rheinland
Certificate No.: 19865712-9901



Name of firm : QuieTek Corporation

Site location : No.75-1, Wang-Yeh Valley, Yung-Hsing Tsuen,
Chiung-Lin, Hsin-Chu County, Taiwan, R.O.C.



2. Conducted Emission


2.1 Test Equipment List

The following test equipment are used during the conducted emission test:

Item	Instrument	Manufacturer	Type No./Serial No	Last Cal.	Remark
1	Test Receiver	R & S	ESCS 30/825442/17	May, 1998	
2	L.I.S.N.	R & S	ESH3-Z5/825016/6	May, 1998	EUT
3	L.I.S.N.	Kyoritsu	KNW-407/8-1420-3	May, 1998	Peripherals
4	Pulse Limiter	R & S	ESH3-Z2/345J2356	May, 1998	
5	N0.2 Shielded Room			N/A	

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

2.2 Test Setup



2.3 Limits

CISPR 22 Limits (dBuV)					FCC Part 15 Subpart B (dBuV)				
Frequency MHz	Class A		Class B		Frequency MHz	Class A		Class B	
	QP	AV	MHz	AV		uV	dBuV	uV	dBuV
0.15 - 0.50	79	66	66-56	56-46	0.45-1.705	1000	60.0	250	48.0
0.50-5.0	73	60	56	46	1.705-30	3000	69.5	250	48.0
5.0 - 30	73	60	60	50					

Remarks : In the above table, the tighter limit applies at the band edges.

2.4 Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 /1992 on conducted measurement.

The bandwidth of the field strength meter (R & S Test Receiver ESCS 30) is set at 9KHz.

2.5 Test Results

The emission from the EUT was below the specified limits. The worst case emissions are shown in Chapter 4. The acceptance criterion was met and the EUT passed the test.

3. Radiated Emission


3.1 Test Equipment

The following test equipment are used during the radiated emission test:

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Site # 1	X	Test Receiver	R & S	ESCS 30 / 825442/14	May, 1998
		Spectrum Analyzer	Advantest	R3261C / 71720140	May, 1998
		Pre-Amplifier	HP	8447D/3307A01812	May, 1998
SITE # 2	X	Bilog Antenna	Chase	CBL6112B / 12452	Sep., 1998
	X	Horn Antenna	EM	EM6917 / 103325	May, 1998
	X	Test Receiver	R & S	ESCS 30 / 825442/17	May, 1998
		Spectrum Analyzer	Advantest	R3261C / 71720609	May, 1998
		Pre-Amplifier	HP	8447D/3307A01814	May, 1998
	X	Bilog Antenna	Chase	CBL6112B / 2455	Sep., 1998
	X	Horn Antenna	EM	EM6917 / 103325	May, 1998

Note: 1. All equipment upon which need to calibrated are with calibration period of 1 year.
2.. Mark "X" test instruments are used to measure the final test results.

3.2 Test Setup



3.3

Limits

CISPR 22 Limits (dBuV)					FCC Part 15 Subpart B (dBuV)				
Frequency	Class A		Class B		Frequency	Class A		Class B	
MHz	Distance (m)	dBuV/m	Distance (m)	dBuV/m		uV	dBuV	uV	dBuV
30 – 230	10	40	10	30	30 – 88	90	39	100	40.0
230 – 1000	10	47	10	37	88 – 216	150	43.5	150	43.5
					216 – 960	210	46.5	200	46.0
					960 - 2000	300	49.5	500	54.0

Remark: 1. The tighter limit shall apply at the edge between two frequency bands.

2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

3. RF Line Voltage (dBuV) = 20 log RF Line Voltage (uV)

3.4 Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 10 meters . The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4 /1992 on radiated measurement.

The bandwidth below 1GHz setting on the field strength meter (R&S Test Receiver ESCS 30) is 120 KHz.

3.5 Test Results

The emission from the EUT was below the specified limits. The worst case emissions are shown in Chapter 4. The acceptance criterion was met and the EUT passed the test.

4. Summary of Test Results

The test results in the emission was performed according to the requirements of measurement standard and process. QuieTek Corporation is assumed full responsibility for the accuracy and completeness of these measurements. The test data of the emission are listed as the attached data.

All the tests were carried out with the EUT in normal operation, which was defined as:

- (1) Mode 1 : DSH-8(100 MHz)
- (2) Mode 2 :Ether-DH8E(10 MHZ)

The EUT passed all the tests.

The uncertainty is calculated in accordance with NAMAS NIS 81, The total uncertainty for this test is as follows:

➤ **Emission Test**

- Uncertainty in the Conducted Emission Test: $< \pm 2.0 \text{ dB}$
- Uncertainty in the field strength measured: $< \pm 4.0 \text{ dB}$

CONDUCTED EMISSION DATA

Date of Test : April 26, 1999 EUT : Dual Speed Hub
 Test Mode : Mode 1 Detect Mode : Quasi-Peak & Average

Frequency	Cable	LISN	Reading Level	Measurement Level	Limits
MHz	Loss	Factor	Line1	Line1	
	dB	dB	dBuV	dBuV	dBuV
*0.150	0.00	0.10	56.91	57.01	66.00
0.201	0.02	0.10	47.93	48.05	63.58
0.213	0.02	0.10	42.89	43.01	63.11
0.228	0.02	0.10	41.31	41.43	62.52
0.275	0.03	0.10	36.17	36.30	60.97
0.291	0.03	0.10	34.79	34.92	60.51

Average:

0.150	0.00	0.10	48.20	48.30	56.00
0.200	0.02	0.10	39.00	39.12	53.61
0.212	0.02	0.10	13.90	14.02	53.13
0.228	0.02	0.10	12.60	12.72	52.52
0.275	0.03	0.10	7.50	7.63	50.97
0.290	0.03	0.10	12.60	12.73	50.52

Remarks :

1. " * " means that this data is the worst emission level.



CONDUCTED EMISSION DATA

Date of Test : April 26, 1999 EUT : Dual Speed Hub
 Test Mode : Mode 1 Detect Mode : Quasi-Peak & Average

Frequency	Cable	LISN	Reading Level	Measurement Level	Limits
MHz	Loss	Factor	Line2	Line2	
	dB	dB	dBuV	dBuV	dBuV
*0.150	0.00	0.10	58.05	58.15	66.00
0.185	0.01	0.10	45.28	45.39	64.25
0.201	0.02	0.10	49.12	49.24	63.58
0.216	0.02	0.10	42.70	42.82	62.96
0.252	0.03	0.10	41.14	41.27	61.71
0.326	0.04	0.10	32.98	33.12	59.56

Average:

0.150	0.00	0.10	48.60	48.70	56.00
0.185	0.01	0.10	16.50	16.61	54.26
0.200	0.02	0.10	40.20	40.32	53.61
0.216	0.02	0.10	13.30	13.42	52.97
0.251	0.03	0.10	33.00	33.13	51.72
0.325	0.04	0.10	4.80	4.94	49.58

Remarks :

1. " * " means that this data is the worst emission level.

CONDUCTED EMISSION DATA

Date of Test : April 26, 1999 EUT : Dual Speed Hub
 Test Mode : Mode 2 Detect Mode : Quasi-Peak & Average

Frequency	Cable	LISN	Reading Level	Measurement Level	Limits
MHz	Loss	Factor	Line1	Line1	
	dB	dB	dBuV	dBuV	dBuV
*0.150	0.00	0.10	59.49	59.59	66.00
0.201	0.02	0.10	50.74	50.86	63.58
0.248	0.03	0.10	42.50	42.63	61.84
0.255	0.03	0.10	40.45	40.58	61.58
0.302	0.04	0.10	37.56	37.70	60.18
17.693	0.34	0.41	41.02	41.77	60.00

Average:

0.150	0.00	0.10	50.20	50.30	56.00
0.200	0.02	0.10	41.48	41.60	53.61
0.247	0.03	0.10	32.90	33.03	51.86
0.255	0.03	0.10	28.80	28.93	51.59
0.302	0.04	0.10	29.30	29.44	50.19
17.690	0.34	0.41	39.60	40.35	50.00

Remarks :

1. " * " means that this data is the worst emission level.



CONDUCTED EMISSION DATA

Date of Test : April 26, 1999 EUT : Dual Speed Hub
 Test Mode : Mode 2 Detect Mode : Quasi-Peak & Average

Frequency	Cable	LISN	Reading Level	Measurement Level	Limits
MHz	Loss	Factor	Line2	Line2	
	dB	dB	dBuV	dBuV	dBuV
*0.150	0.00	0.10	58.75	58.85	66.00
0.170	0.01	0.10	46.69	46.80	64.98
0.201	0.02	0.10	49.79	49.91	63.58
0.248	0.03	0.10	42.38	42.51	61.84
0.283	0.03	0.10	36.73	36.86	60.73
17.693	0.34	0.41	41.26	42.01	60.00

Average:

0.150	0.00	0.10	49.30	49.40	56.00
0.169	0.01	0.10	19.10	19.21	55.01
0.200	0.02	0.10	40.90	41.02	53.61
0.247	0.03	0.10	33.20	33.33	51.86
0.282	0.03	0.10	10.30	10.43	50.76
17.690	0.34	0.41	40.00	40.75	50.00

Remarks :

1. " * " means that this data is the worst emission level.



Radiated Emission Data

Date of Test : April 26, 1999 EUT : Dual Speed Hub
 Test Mode : Mode 1 Detect Mode : Quasi-Peak

Freq.	Cable	Probe	PreAMP	Reading	Measurement	Margin	Limit	Ant	Turn
	Loss	Factor		Level	Horizontal				
MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	dBuV/m	cm	deg
150.000	2.31	10.72	0.00	3.11	16.14	13.86	30.00	400	65
200.000	2.78	9.30	0.00	3.34	15.42	14.58	30.00	400	41
*225.000	3.03	9.83	0.00	11.97	24.83	5.17	30.00	400	92
250.000	3.27	12.61	0.00	14.07	29.95	7.05	37.00	400	102
275.000	3.51	12.91	0.00	3.02	19.45	17.55	37.00	400	14
325.000	3.88	13.64	0.00	4.07	21.60	15.40	37.00	400	35
375.000	4.14	15.00	0.00	4.93	24.07	12.93	37.00	368	82

Remarks:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. " * ", means this data is the worst emission level.
3. Emission Level = Reading Level + Antenna Factor + Cable loss

Radiated Emission Data

Date of Test	:	April 26, 1999	EUT	:	Dual Speed Hub
Test Mode	:	Mode 1	Detect Mode	:	Quasi-Peak

Freq.	Cable	Probe	PreAMP	Reading	Measurement	Margin	Limit	Ant	Turn
		Loss	Factor		Level	Vertical			
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	dBuV/m	cm deg
75.000		1.58	6.83	0.00	5.33	13.74	16.26	30.00	100 63
150.000		2.31	10.43	0.00	7.56	20.30	9.70	30.00	100 72
175.000		2.55	9.32	0.00	8.65	20.52	9.48	30.00	100 107
200.000		2.78	9.07	0.00	3.69	15.55	14.45	30.00	100 27
*250.000		3.27	12.26	0.00	14.01	29.54	7.46	37.00	100 72
325.000		3.88	14.29	0.00	1.07	19.24	17.76	37.00	100 82
375.000		4.14	15.40	0.00	5.13	24.67	12.33	37.00	100 3

Remarks:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. " * ", means this data is the worst emission level.
3. Emission Level = Reading Level + Antenna Factor + Cable loss

Radiated Emission Data

Date of Test : April 26, 1999 EUT : Dual Speed Hub
 Test Mode : Mode 2 Detect Mode : Quasi-Peak

Freq.	Cable	Probe	PreAMP	Reading	Measurement	Margin	Limit	Ant	Turn
		Loss	Factor		Level	Horizontal			
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	dBuV/m	cm deg
150.000		2.31	10.72	0.00	3.05	16.08	13.92	30.00	400 69
200.000		2.78	9.30	0.00	3.87	15.95	14.05	30.00	400 81
225.000		3.03	9.83	0.00	10.25	23.11	6.89	30.00	400 105
*250.000		3.27	12.61	0.00	14.65	30.53	6.47	37.00	400 77
325.000		3.88	13.64	0.00	5.21	22.74	14.26	37.00	400 94
375.000		4.14	15.00	0.00	4.20	23.34	13.66	37.00	400 84

Remarks:

4. All Readings below 1GHz are Quasi-Peak, above are average value.
5. " * ", means this data is the worst emission level.
6. Emission Level = Reading Level + Antenna Factor + Cable loss



Radiated Emission Data

Date of Test : April 26, 1999 EUT : Dual Speed Hub
 Test Mode : Mode 2 Detect Mode : Quasi-Peak

Freq.	Cable	Probe	PreAMP	Reading	Measurement	Margin	Limit	Ant	Turn
		Loss Factor		Level	Vertical				
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	dBuV/m	cm deg
150.000		2.31	10.43	0.00	7.88	20.62	9.38	30.00	100 65
175.000		2.55	9.32	0.00	8.54	20.41	9.59	30.00	100 20
200.000		2.78	9.07	0.00	4.85	16.71	13.29	30.00	100 92
*250.000		3.27	12.26	0.00	14.02	29.55	7.45	37.00	100 35
325.000		3.88	14.29	0.00	2.05	20.22	16.78	37.00	100 77
375.000		4.14	15.40	0.00	5.42	24.96	12.04	37.00	100 68

Remarks:

7. All Readings below 1GHz are Quasi-Peak, above are average value.
8. " * ", means this data is the worst emission level.
9. Emission Level = Reading Level + Antenna Factor + Cable loss

5. EMI Reduction Method During Compliance Testing

No modification was made during testing.

