



FCC ID: P27MDC845
Report No.: T191003D02-RP2

Page: 1 / 131
Rev.: 01

FCC RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART E

Test Standard	FCC Part 15.407
Brand name	ADT
Product name	FHD WiFi Mini Dome Camera
Model No.	MDC845xxxxxxxx (the 1st x should be "blank" or "-"; the rest x could be 0 to 9, A to Z, a to z, "blank" or "-", for marketing purpose)
Test Result	Pass
Statements of Conformity	Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory)

Approved by:

Kevin Tsai
Deputy Manager

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部分複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T191003D02-RP2

Page: 2 / 131
Rev.: 01

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	December 30, 2019	Initial Issue	ALL	Doris Chu
01	January 21, 2020	1. Modify Test Procedure in section 4.2.2. 2. Modify 5180MHz 99% test result. 3. Modify test result in section 4.6.4.	P.17-18, P.19, P130-131	Doris Chu



Report No.: T191003D02-RP2

Page: 3 / 131
Rev.: 01

Table of contents

1. GENERAL INFORMATION.....	4
1.1 EUT INFORMATION	4
1.2 EUT CHANNEL INFORMATION	5
1.3 ANTENNA INFORMATION.....	6
1.4 MEASUREMENT UNCERTAINTY.....	6
1.5 FACILITIES AND TEST LOCATION	7
1.6 INSTRUMENT CALIBRATION	8
1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT.....	9
1.8 TEST METHODOLOGY AND APPLIED STANDARDS.....	9
2. TEST SUMMERY	10
3. DESCRIPTION OF TEST MODES.....	11
3.1 THE WORST MODE OF OPERATING CONDITION.....	11
3.2 THE WORST MODE OF MEASUREMENT	12
3.3 EUT DUTY CYCLE	13
4. TEST RESULT	14
4.1 AC POWER LINE CONDUCTED EMISSION	14
4.2 26dB BANDWIDTH, 6DB BANDWIDTH AND OCCUPIED BANDWIDTH (99%).....	17
4.3 OUTPUT POWER MEASUREMENT	41
4.4 POWER SPECTRAL DENSITY	45
4.5 RADIATION BANDEDGE AND SPURIOUS EMISSION.....	59
4.6 FREQUENCY STABILITY	129
APPENDIX 1 - PHOTOGRAPHS OF EUT	

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	Sercomm Corporation 8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan			
Manufacturer	Sercomm Corporation 8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan			
Equipment	FHD WiFi Mini Dome Camera			
Model Name	MDC845xxxxxxxx (the 1st x should be "blank" or "-"; the rest x could be 0 to 9, A to Z, a to z, "blank" or "-", for marketing purpose)			
Model Discrepancy	All the above models are identical except for the designation of model numbers. The suffix of (The 1st x should be "blank" or "-"; the rest x could be 0 to 9, A to Z, a to z, "blank" or "-") on model number is just for marketing purpose only.			
Trade Name	ADT			
Received Date	October 03, 2019			
Date of Test	October 14 ~ November 14, 2019			
Power Supply	VDC from Power Adapter APD / WB-18D12FU I/P: 100-240V~, 50-60Hz, 0.5A Max O/P: 12VDC, 1.5A			
Output Power(W)	Band	Mode	Frequency Range (MHz)	Output Power (W)
	U-NII-1	IEEE 802.11a	5180 ~ 5240	0.0630
		IEEE 802.11n HT 20 MHz	5180 ~ 5240	0.0880
		IEEE 802.11n HT 40 MHz	5190 ~ 5230	0.0939
		IEEE 802.11ac VHT 80 MHz	5210	0.0982
	U-NII-3	IEEE 802.11a	5745 ~ 5825	0.1879
		IEEE 802.11n HT 20 MHz	5745 ~ 5825	0.5047
		IEEE 802.11n HT 40 MHz	5755 ~ 5795	0.5260
		IEEE 802.11ac VHT 80 MHz	5775	0.2524

1.2 EUT CHANNEL INFORMATION

Frequency Range	<table border="1"> <tr> <td colspan="2">UNII-1</td></tr> <tr> <td>IEEE 802.11a</td><td>5180 ~ 5240 MHz</td></tr> <tr> <td>IEEE 802.11n HT 20 MHz</td><td>5180 ~ 5240 MHz</td></tr> <tr> <td>IEEE 802.11n HT 40 MHz</td><td>5190 ~ 5230 MHz</td></tr> <tr> <td>IEEE 802.11ac VHT 20 MHz</td><td>5180 ~ 5240 MHz</td></tr> <tr> <td>IEEE 802.11ac VHT 40 MHz</td><td>5190 ~ 5230 MHz</td></tr> <tr> <td>IEEE 802.11ac VHT 80 MHz</td><td>5210 MHz</td></tr> <tr> <td colspan="2">UNII-3</td></tr> <tr> <td>IEEE 802.11a</td><td>5745 ~ 5825 MHz</td></tr> <tr> <td>IEEE 802.11n HT 20 MHz</td><td>5745 ~ 5825 MHz</td></tr> <tr> <td>IEEE 802.11n HT 40 MHz</td><td>5755 ~ 5795 MHz</td></tr> <tr> <td>IEEE 802.11ac VHT 20 MHz</td><td>5745 ~ 5825 MHz</td></tr> <tr> <td>IEEE 802.11ac VHT 40 MHz</td><td>5755 ~ 5795 MHz</td></tr> <tr> <td>IEEE 802.11ac VHT 80 MHz</td><td>5775 MHz</td></tr> </table>	UNII-1		IEEE 802.11a	5180 ~ 5240 MHz	IEEE 802.11n HT 20 MHz	5180 ~ 5240 MHz	IEEE 802.11n HT 40 MHz	5190 ~ 5230 MHz	IEEE 802.11ac VHT 20 MHz	5180 ~ 5240 MHz	IEEE 802.11ac VHT 40 MHz	5190 ~ 5230 MHz	IEEE 802.11ac VHT 80 MHz	5210 MHz	UNII-3		IEEE 802.11a	5745 ~ 5825 MHz	IEEE 802.11n HT 20 MHz	5745 ~ 5825 MHz	IEEE 802.11n HT 40 MHz	5755 ~ 5795 MHz	IEEE 802.11ac VHT 20 MHz	5745 ~ 5825 MHz	IEEE 802.11ac VHT 40 MHz	5755 ~ 5795 MHz	IEEE 802.11ac VHT 80 MHz	5775 MHz
UNII-1																													
IEEE 802.11a	5180 ~ 5240 MHz																												
IEEE 802.11n HT 20 MHz	5180 ~ 5240 MHz																												
IEEE 802.11n HT 40 MHz	5190 ~ 5230 MHz																												
IEEE 802.11ac VHT 20 MHz	5180 ~ 5240 MHz																												
IEEE 802.11ac VHT 40 MHz	5190 ~ 5230 MHz																												
IEEE 802.11ac VHT 80 MHz	5210 MHz																												
UNII-3																													
IEEE 802.11a	5745 ~ 5825 MHz																												
IEEE 802.11n HT 20 MHz	5745 ~ 5825 MHz																												
IEEE 802.11n HT 40 MHz	5755 ~ 5795 MHz																												
IEEE 802.11ac VHT 20 MHz	5745 ~ 5825 MHz																												
IEEE 802.11ac VHT 40 MHz	5755 ~ 5795 MHz																												
IEEE 802.11ac VHT 80 MHz	5775 MHz																												
Modulation Type	1. IEEE 802.11a mode: OFDM 2. IEEE 802.11n HT 20 MHz mode: OFDM 3. IEEE 802.11n HT 40 MHz mode: OFDM 4. IEEE 802.11ac VHT 80 MHz mode: OFDM																												

Remark:

Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
☐ 1 MHz or less	1	Middle
☐ 1 MHz to 10 MHz	2	1 near top and 1 near bottom
☒ More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

Antenna Type	☐ PIFA ☐ PCB ☒ Dipole ☐ Coils
Antenna Gain	Antenna 1: Gain: 4.3 dBi Antenna 2: Gain: 3.8 dBi Power Directional Gain: 4.06

Notes:

1. Power Directional Gain: $10\text{LOG}(((10^{(Ant1/10)}+10^{(Ant2/10)}))/2))$

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 30M~200M	+/- 4.12
3M Semi Anechoic Chamber / 200M~1000M	+/- 4.68
3M Semi Anechoic Chamber / 1G~8G	+/- 5.18
3M Semi Anechoic Chamber / 8G~18G	+/- 5.47
3M Semi Anechoic Chamber / 18G~26G	+/- 3.81
3M Semi Anechoic Chamber / 26G~40G	+/- 3.87

Remark:

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.



Report No.: T191003D02-RP2

Page: 7 / 131
Rev.: 01

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)

Test site	Test Engineer	Remark
AC Conduction Room	Dally Hong	
Radiation	Dally Hong	
RF Conducted	Dally Hong	

Remark: *The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22*

1.6 INSTRUMENT CALIBRATION

RF Conducted Test Site					
Equipment	Manufacturer	Model	S/N	Cal Date	Cal Due
Coaxial Cable	Woken	WC12	CC003	06/28/2019	06/27/2020
Power Meter	Anritsu	ML2495A	1149001	02/12/2019	02/11/2020
Power Seneor	Anritsu	MA2491A	030982	02/12/2019	02/11/2020
EXA Signal Analyzer	KEYSIGHT	N9010B	MY55460167	07/31/2019	07/30/2020
Software	N/A				

3M 966 Chamber Test Site					
Equipment	Manufacturer	Model	S/N	Cal Date	Cal Due
Bilog Antenna	Sunol Sciences	JB3	A030105	07/26/2019	07/25/2020
Coaxial Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/26/2019	02/25/2020
Coaxial Cable	EMCI	EMC105	190914+25111	09/20/2019	09/19/2020
Digital Thermo-Hygro Meter	WISEWIND	1206	D07	01/30/2019	01/29/2020
double Ridged Guide Horn Antenna	ETC	MCTD 1209	DRH13M02003	10/04/2019	10/03/2020
High Pass Filters	MICRO TRONICS	HPM13195	003	02/26/2019	02/25/2020
Horn Antenna	ETS LINDGREN	3116	00026370	12/26/2018	12/25/2019
Loop Ant	COM-POWER	AL-130	121051	03/22/2019	03/21/2020
Pre-Amplifier	EMEC	EM330	060609	02/26/2019	02/25/2020
Pre-Amplifier	HP	8449B	3008A00965	02/26/2019	02/25/2020
Pre-Amplifier	MITEQ	AMF-6F-260400-40-8P	985646	02/26/2019	02/25/2020
PSA Series Spectrum Analyzer	Agilent	E4446A	MY46180323	05/29/2019	05/28/2020
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180413				

AC Conducted Emissions Test Site					
Equipment	Manufacturer	Model	S/N	Cal Date	Cal Due
CABLE	EMCI	CFD300-NL	CERF	06/27/2019	06/26/2020
EMI Test Receiver	R&S	ESCI	100064	07/26/2019	07/25/2020
LISN	SCHWARZBECK	NSLK 8127	8127-541	01/31/2019	01/30/2020
LISN	SCHAFFNER	NNB 41	03/10013	02/13/2019	02/12/2020
Software	EZ-EMC(CCS-3A1-CE)				

Remark: Each piece of equipment is scheduled for calibration once a year.



Report No.: T191003D02-RP2

Page: 9 / 131
Rev.: 01

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
	N/A				

Support Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
1.	NB(J)	TOSHIBA	PT345T-00L002	N/A	PD97260H

1.8 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.407, KDB 662911 D01, KDB 789033 D02.



Report No.: T191003D02-RP2

Page: 10 / 131
Rev.: 01

2. TEST SUMMERY

FCC Standard Sec.	Chapter	Test Item	Result
15.203	1.4	Antenna Requirement	Pass
15.207	4.1	AC Conducted Emission	Pass
15.403(i)	4.2	26dB Bandwidth	Pass
15.403(i)	4.2	6dB Bandwidth	Pass
15.403(i)	4.2	Occupied Bandwidth (99%)	Pass
15.407(a)	4.3	Output Power Measurement	Pass
15.407(a)	4.4	Power Spectral Density	Pass
15.407(b)	4.5	Radiation Band Edge	Pass
15.407(b)	4.5	Radiation Spurious Emission	Pass
15.407(g)	4.6	Frequency Stability	Pass

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	1. IEEE 802.11a mode: 6Mbps 2. IEEE 802.11n HT 20 MHz mode: MCS0 3. IEEE 802.11n HT 40 MHz mode: MCS0 4. IEEE 802.11ac VHT 80 MHz mode: MCS8																																												
Operating Frequency Range & Number of Channels	<table border="1"> <thead> <tr> <th></th><th>Mode</th><th>Frequency Range (MHz)</th><th>Number of Channels</th></tr> </thead> <tbody> <tr> <td rowspan="6">U-NII-1</td><td>IEEE 802.11a</td><td>5180 ~ 5240</td><td>4 Channels</td></tr> <tr> <td>IEEE 802.11n HT 20 MHz</td><td>5180 ~ 5240</td><td>4 Channels</td></tr> <tr> <td>IEEE 802.11n HT 40 MHz</td><td>5190 ~ 5230</td><td>2 Channels</td></tr> <tr> <td>IEEE 802.11ac VHT 20 MHz</td><td>5180 ~ 5240</td><td>4 Channels</td></tr> <tr> <td>IEEE 802.11ac VHT 40 MHz</td><td>5190 ~ 5230</td><td>2 Channels</td></tr> <tr> <td>IEEE 802.11ac VHT 80 MHz</td><td>5210</td><td>1 Channels</td></tr> <tr> <td rowspan="6">U-NII-3</td><td>IEEE 802.11a</td><td>5745 ~ 5825</td><td>5 Channels</td></tr> <tr> <td>IEEE 802.11n HT 20 MHz</td><td>5745 ~ 5825</td><td>5 Channels</td></tr> <tr> <td>IEEE 802.11n HT 40 MHz</td><td>5755 ~ 5795</td><td>2 Channels</td></tr> <tr> <td>IEEE 802.11ac VHT 20 MHz</td><td>5745 ~ 5825</td><td>5 Channels</td></tr> <tr> <td>IEEE 802.11ac VHT 40 MHz</td><td>5755 ~ 5795</td><td>2 Channels</td></tr> <tr> <td>IEEE 802.11ac VHT 80 MHz</td><td>5775</td><td>1 Channels</td></tr> </tbody> </table>				Mode	Frequency Range (MHz)	Number of Channels	U-NII-1	IEEE 802.11a	5180 ~ 5240	4 Channels	IEEE 802.11n HT 20 MHz	5180 ~ 5240	4 Channels	IEEE 802.11n HT 40 MHz	5190 ~ 5230	2 Channels	IEEE 802.11ac VHT 20 MHz	5180 ~ 5240	4 Channels	IEEE 802.11ac VHT 40 MHz	5190 ~ 5230	2 Channels	IEEE 802.11ac VHT 80 MHz	5210	1 Channels	U-NII-3	IEEE 802.11a	5745 ~ 5825	5 Channels	IEEE 802.11n HT 20 MHz	5745 ~ 5825	5 Channels	IEEE 802.11n HT 40 MHz	5755 ~ 5795	2 Channels	IEEE 802.11ac VHT 20 MHz	5745 ~ 5825	5 Channels	IEEE 802.11ac VHT 40 MHz	5755 ~ 5795	2 Channels	IEEE 802.11ac VHT 80 MHz	5775	1 Channels
	Mode	Frequency Range (MHz)	Number of Channels																																										
U-NII-1	IEEE 802.11a	5180 ~ 5240	4 Channels																																										
	IEEE 802.11n HT 20 MHz	5180 ~ 5240	4 Channels																																										
	IEEE 802.11n HT 40 MHz	5190 ~ 5230	2 Channels																																										
	IEEE 802.11ac VHT 20 MHz	5180 ~ 5240	4 Channels																																										
	IEEE 802.11ac VHT 40 MHz	5190 ~ 5230	2 Channels																																										
	IEEE 802.11ac VHT 80 MHz	5210	1 Channels																																										
U-NII-3	IEEE 802.11a	5745 ~ 5825	5 Channels																																										
	IEEE 802.11n HT 20 MHz	5745 ~ 5825	5 Channels																																										
	IEEE 802.11n HT 40 MHz	5755 ~ 5795	2 Channels																																										
	IEEE 802.11ac VHT 20 MHz	5745 ~ 5825	5 Channels																																										
	IEEE 802.11ac VHT 40 MHz	5755 ~ 5795	2 Channels																																										
	IEEE 802.11ac VHT 80 MHz	5775	1 Channels																																										

Remark:

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.
2. The mode IEEE 802.11ac VHT20 and VHT40 are only different in control messages with IEEE 802.11n HT20 and HT40, and have same power setting. Therefore, the highest power(IEEE 802.11n HT20 and HT40) were test conducted and radiated measurement and recorded in this report.

3.2 THE WORST MODE OF MEASUREMENT

AC Power Line Conducted Emission	
Test Condition	AC Power line conducted emission for line and neutral
Power supply Mode	Mode 1: EUT power by adapter (DC 12V)
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by adapter (DC 12V)
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☒ Placed in fixed position at X-Plane (E2-Plane) ☐ Placed in fixed position at Y-Plane (E1-Plane) ☐ Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by adapter (DC 12V)
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4


Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z for radiated measurement. The worst case(X-Plane) were recorded in this report
3. AC power line conducted emission and for below 1G radiation emission were performed the EUT transmit at the highest output power channel as worse case.


3.3 EUT DUTY CYCLE

Duty Cycle					
Configuration	TX ON (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T (kHz)	VBW setting (kHz)
802.11a	2.063	96.22	0.17	0.48	1.00
802.11n HT20	1.919	97.12	0.13	0.52	1.00
802.11n HT40	0.943	85.81	0.66	1.06	2.00
802.11ac VHT80	2.066	92.23	0.35	0.48	1.00


802.11a




802.11n HT20



802.11n HT40



802.11ac VHT80



Remark:

$a = 96.22\%$, $n_{ht_20} = 97.12\%$, $n_{ht_40} = 85.81\%$, $n_{vht_80} = 92.23\%$

Duty Cycle Factor: $10 * \log(1/0.9622) = 0.17$

Duty Cycle Factor: $10 * \log(1/0.9712) = 0.13$

Duty Cycle Factor: $10 * \log(1/0.8581) = 0.66$

Duty Cycle Factor: $10 * \log(1/0.9223) = 0.35$

4. TEST RESULT

4.1 AC POWER LINE CONDUCTED EMISSION

4.1.1 Test Limit

According to §15.207(a),

Frequency Range (MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


* Decreases with the logarithm of the frequency.

4.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

4.1.3 Test Setup




4.1.4 Test Result

Pass.


Test Data

Test Mode	Mode 1	Temp/Hum	24(°C)/ 50%RH
Test Voltage	120Vac / 60Hz	Test Date	October 14, 2019
Phase	Line	Test Engineer	Dally Hong



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.2100	23.73	16.62	10.13	33.86	26.75	63.21	53.21	-29.35	-26.46	Pass
0.2580	30.44	22.60	10.13	40.57	32.73	61.50	51.50	-20.93	-18.77	Pass
0.3220	24.62	14.97	10.14	34.76	25.11	59.66	49.66	-24.90	-24.55	Pass
0.4540	19.48	11.46	10.14	29.62	21.60	56.80	46.80	-27.18	-25.20	Pass
0.7060	15.06	8.71	10.16	25.22	18.87	56.00	46.00	-30.78	-27.13	Pass
0.9260	20.65	13.13	10.17	30.82	23.30	56.00	46.00	-25.18	-22.70	Pass

Test Mode	Mode 1	Temp/Hum	24(°C)/ 50%RH
Test Voltage	120Vac / 60Hz	Test Date	October 14, 2019
Phase	Neutral	Test Engineer	Dally Hong



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1820	24.72	16.65	10.02	34.74	26.67	64.39	54.39	-29.65	-27.72	Pass
0.2508	33.81	27.22	10.02	43.83	37.24	61.73	51.73	-17.90	-14.49	Pass
0.2803	29.98	22.04	10.02	40.00	32.06	60.81	50.81	-20.81	-18.75	Pass
0.3420	21.66	14.98	10.03	31.69	25.01	59.15	49.15	-27.46	-24.14	Pass
0.4780	18.74	12.09	10.03	28.77	22.12	56.37	46.37	-27.60	-24.25	Pass
0.9220	19.66	11.95	10.04	29.70	21.99	56.00	46.00	-26.30	-24.01	Pass

4.2 26dB BANDWIDTH, 6dB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)

4.2.1 Test Limit

26 dB Bandwidth : For reporting purposes only.

6 dB Bandwidth : Least 500kHz.

Occupied Bandwidth(99%) : For reporting purposes only.

4.2.2 Test Procedure

26dB


1. This measurement setting are specified in section D of KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set RBW: approximately 1% of the emission bandwidth.
3. Set the VBW>RBW.
4. Detoctor = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26dB down from the peak of the emission. Compare this with the RBW setting of the analyser. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

6dB

1. This measurement setting are specified in section D of KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set RBW = 100 kHz.
3. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
4. Detoctor = Peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

99%

1. This measurement setting are specified in section D of KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set center frequency to the nominal EUT channel center frequency.
3. Set span = 1.5 times to 5.0 times the OBW.
4. Set RBW = 1 % to 5% of the OBW.
5. Set VBW $\geq 3 \times \text{RBW}$

4.2.3 Test Setup


4.2.4 Test Result

UNII-1					
Test mode: IEEE 802.11a mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5180	17.857	-	29.99	-
Mid	5220	19.491	-	30.00	-
High	5240	17.107	-	29.99	-
Test mode: IEEE 802.11n HT20 mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5180	16.757	17.844	20.72	21.62
Mid	5220	16.706	17.897	20.71	21.80
High	5240	16.733	17.884	20.98	22.94
Test mode: IEEE 802.11n HT40 mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5190	36.199	36.175	42.18	42.60
High	5230	36.263	36.253	43.70	43.29
Test mode: IEEE 802.11ac VHT80 mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Mid	5210	75.027	75.189	81.74	97.97

UNII-3					
Test mode: IEEE 802.11a mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)
Low	5745	16.933	-	16.52	-
Mid	5785	17.055	-	16.50	-
High	5825	17.209	-	16.49	-
Test mode: IEEE 802.11n HT20 mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)
Low	5745	16.810	18.215	16.55	17.79
Mid	5785	16.844	18.340	16.55	17.76
High	5825	16.852	18.842	16.57	17.72
Test mode: IEEE 802.11n HT40 mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)
Low	5755	36.239	36.328	36.52	36.53
High	5795	36.280	36.382	36.52	36.39
Test mode: IEEE 802.11ac VHT80 mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)
Mid	5775	75.293	75.043	75.96	75.23


Report No.: T191003D02-RP2

Test Data




UNII-1 IEEE 802.11n HT20 mode- chain 0 26 BANDWIDTH

Low CH



Mid CH




High CH




UNII-1 IEEE 802.11n HT20 mode- chain 1 26 BANDWIDTH


Low CH



Mid CH




High CH



UNII-1 IEEE 802.11n HT40 mode- chain 0

26 BANDWIDTH

Low CH




High CH




UNII-1 IEEE 802.11n HT40 mode- chain 1

Low CH




High CH






UNII-3 IEEE 802.11a mode- chain 0 6 BANDWIDTH


Low CH



Mid CH



High CH




UNII-3 IEEE 802.11n HT20 mode- chain 0 6 BANDWIDTH

Low CH



Mid CH



High CH




Report No.: T191003D02-RP2

UNII-3 IEEE 802.11n HT20 mode- chain 1 6 BANDWIDTH

Low CH



Mid CH



High CH



UNII-3 IEEE 802.11n HT40 mode- chain 0 6 BANDWIDTH

Low CH




High CH





UNII-3 IEEE 802.11n HT40 mode- chain 1 6 BANDWIDTH

Low CH



High CH






Report No.: T191003D02-RP2

UNII-1 IEEE 802.11a mode- chain 0 BANDWIDTH (99%)

Low CH



Mid CH




High CH




UNII-1 IEEE 802.11n HT20 mode- chain 0 BANDWIDTH (99%)

Low CH



Mid CH




High CH




UNII-1 IEEE 802.11n HT20 mode- chain 1 BANDWIDTH (99%)


Low CH



Mid CH




High CH



UNII-1 IEEE 802.11n HT40 mode- chain 0 BANDWIDTH (99%)

Low CH




High CH





UNII-1 IEEE 802.11n HT40 mode- chain 1 BANDWIDTH (99%)

Low CH



High CH






Report No.: T191003D02-RP2

UNII-3 IEEE 802.11a mode- chain 0 BANDWIDTH (99%)

Low CH



Mid CH



High CH




Report No.: T191003D02-RP2

UNII-3 IEEE 802.11n HT20 mode- chain 0 BANDWIDTH (99%)


Low CH



Mid CH



High CH




Report No.: T191003D02-RP2

UNII-3 IEEE 802.11n HT20 mode- chain 1 BANDWIDTH (99%)

Low CH



Mid CH



High CH



