



FCC RADIO EXPOSURE TEST REPORT

FCC ID : PPQ-WP8333V5
Equipment : 802.11ac Tri Band PoE Access Point
Brand Name : LITE-ON, WatchGuard
Model Name : WP8333V5, C-110, AP325
Applicant : LITE-ON Technology Corp.
Bldg. C, 90, Chien 1 Rd., Chung-Ho, New Taipei
City, 23585 Taiwan
Manufacturer (1) : Lite-On Network Communication (Dongguan)
Limited
30#Keji Rd., Yin Hu Industrial Area, Qingxi
Town, DongGuan City, Guangdong, China
Manufacturer (2) : LITE-ON Technology Corp. Networking Plant
No. 101, Neihuan N. Rd., Nanzi Processing Export,
Nanzi Dist., Kaohsiung City 811, Taiwan
Standard : 47 CFR Part 2.1091

The product was received on Nov. 11, 2019, and testing was started from Nov. 11, 2019 and completed on Dec. 26, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Cliff Chang

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 EUT General Information	5
1.2 Table for Multiple Listing	5
1.3 Table for Explanation of Flash.....	5
1.4 Testing Location	6
2 Maximum Permissible Exposure	7
2.1 Limit of Maximum Permissible Exposure	7
2.2 MPE Calculation Method.....	7
2.3 Calculated Result and Limit.....	8
Photographs of EUT v01	



TEL : 886-3-656-9065
FAX : 886-3-656-9085
Report Template No.: CB-A1_1 Ver1.0



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Sam Chen

Report Producer: Wendy Pan



1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT20/VHT40: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) LE: GFSK

Note: The EUT contain Radio 3 (2.4G)/(5G) RF module (Model Name: WM862FEMD, FCC ID: PPQ-WM862FEMD).

1.2 Table for Multiple Listing

The brand/model names in the following table are all refer to the identical product.

Brand Name	Model Name	Description
LITE-ON	WP8333V5	All the models are identical, the difference model for difference brand served as marketing strategy.
WatchGuard	C-110, AP325	

From the above models, model: AP325 was selected as representative model for the test and its data was recorded in this report.

1.3 Table for Explanation of Flash

Brand name	Model name	Flash
winbond	25Q256JVFQ	32M+32M



1.4 Testing Location

Testing Location		
☐	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
☒	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

Test site Designation No. TW0006 with FCC.

Test site registered number IC 4086D with Industry Canada.



2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 22 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

For EUT:

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;D1D (Radio 1)	6.50	24.12	30.62	0.50	31.12	1.29420	22	0.21279	1.00000
5.2G;D1D (Radio 2)	5.60	25.72	31.32	0.50	31.82	1.52055	22	0.25000	1.00000
5.8G;D1D (Radio 2)	5.90	27.92	33.82	0.50	34.32	2.70396	22	0.44457	1.00000
2.4G;BT-BR (Radio 4)	2.10	6.91	9.01	0.50	9.51	0.00893	22	0.00147	1.00000
2.4G;BT-LE (Radio 4)	2.10	8.35	10.45	0.50	10.95	0.01245	22	0.00205	1.00000

For RF module (Model Name: WM862FEMD, FCC ID: PPQ-WM862FEMD):

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;G1D (Radio 3)	6.50	24.89	31.39	0.50	31.89	1.54525	22	0.25406	1.00000
5.2G;D1D (Radio 3)	4.80	22.01	26.81	0.50	27.31	0.53827	22	0.08850	1.00000
5.8G;D1D (Radio 3)	6.00	22.23	28.23	0.50	28.73	0.74645	22	0.12273	1.00000



Simultaneous Transmission Analysis Mode: Radio 1 + Radio 2 + Radio 3 (WLAN 2.4GHz) + Radio 4

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
2.4G;D1D (Radio 1)	6.50	24.12	30.62	0.50	31.12	1.29420	22	0.21278	1.00000	0.21278
5.8G;D1D (Radio 2)	5.90	27.92	33.82	0.50	34.32	2.70396	22	0.44456	1.00000	0.44456
2.4G;G1D (Radio 3)	6.50	24.89	31.39	0.50	31.89	1.54525	22	0.25406	1.00000	0.25406
2.4G;BT-LE (Radio 4)	2.10	8.35	10.45	0.50	10.95	0.01245	22	0.00205	1.00000	0.00205
									Sum Ratio	0.91345
									Ratio Limit	1

Simultaneous Transmission Analysis Mode: Radio 1 + Radio 2 + Radio 3 (WLAN 5GHz) + Radio 4

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
2.4G;D1D (Radio 1)	6.50	24.12	30.62	0.50	31.12	1.29420	22	0.21278	1.00000	0.21278
5.8G;D1D (Radio 2)	5.90	27.92	33.82	0.50	34.32	2.70396	22	0.44456	1.00000	0.44456
5.8G;D1D (Radio 3)	6.00	22.23	28.23	0.50	28.73	0.74645	22	0.12273	1.00000	0.12273
2.4G;BT-LE (Radio 4)	2.10	8.35	10.45	0.50	10.95	0.01245	22	0.00205	1.00000	0.00205
									Sum Ratio	0.78212
									Ratio Limit	1

Note: The above antenna gain was declared by manufacturer.

————THE END————