

承认书

SPECIFICATION FOR APPROVEAL

客户名称(CUSTOMER): ZLGD-A1-0414

客户料号(PART NO.): ZLGD-Y16×38-190-FR

品名(DESCRIPTION): Coil+Magnetic DiSc

规格(SPECIFICATION): 16x38,0.08×105P, Magnetic edge starting 190MM

日期 DATE: 20230812

本司确认 (TRX APPROVAL)		
make	review	Admitted date
Xiaoxian Zeng	review	20230812
客户确认 (CUSTOMER APPROVAL)		
make	批准	dmitted date
确认结果(Result): ☐ qualified ☐ unqualified ☐ other		

东莞市德弗力五金电子材料有限公司

Dongguan city DFL Electronic Technology Co.,LTD

107 Xinfeng West Road, Shijie Town, Dongguan City

telephone: 0769-86016320

fax: 0769-86372427

东莞市德弗力五金电子材料有限公司
Dongguan city DFL Electronic Technology Co.,LTD

SPECIFICATION					
产品型号: DESC	ZLGD-Y16×38-190-FR	版本 Rev:A	Customer:	ZLGD-A1-0414	
			Description:	Coil+Magnetic Disc	
			Date:	20230812	
一、尺寸DIMENSION:(mm)			A	16.0±1.0	
			B	38.0±2.0	
			C	190.0±5.0	
			D	3.0±2.0	
			E	44.0±1.0	
			F	0.8±0.2	
			G	14.0±1.0	
			H	1.25±0.2	
			I		
			J		
			K		
			L		
			M		
			N		
			O		
			P		
			Note:		
			1. Apply G44 * 0.8 hard magnets to the coil, and 14 * 1.25 non perforated hard magnets in the middle of the inner diameter		
			2. Wrap 8MM high-temperature tape around the coil outlet position		
			3. Magnetic patch with white tape and double-sided tape for ears		
			4. The coil cannot be loosened		
二、原理图 (schematic diagram:)					
三、绕线参数(WindingSpecification:)					
序号 NO.	端子 TERMINAL	线径 WIRE	圈数 Turns	绕线方向 Winding Direction	
1		0.08×105Psilk-covered wire	11TS	counterclockwise	
四、电气特性 ELECTRICAL CHARACTERISTICS: 温度 TEMPERATURE:25±10℃,湿度 RELATIVE HUMIDITY:65±20%					
序号 NO.	项目 ITEM	端子 TERMINAL	标准 SPECIFICATION	测试条件 TEST FREQUENCY	测试仪器 TEST EQUIPMENTS
1	IND.		6.8uH±0.3 Add magnetic plates	100KHz/1.0V	SHDA 1062
2	IND.				
3	Qvalue				
4	DCR				
拟制/日期PREPARED BY/DATE		审核/日期CHECKED BY/DATE		客户/日期CUSTOMEU/DATE	