



Choose Scandinavian trust

RF Exposure Compliance – MPE Calculation Report

Applicant company:	TrellisWare Technologies Inc.
Model:	TW-135
FCC Identification:	FCC ID: 2A6X2-135
Product type:	Mobile or Fixed Device
Device category:	Consumer Device for General Population/Uncontrolled Exposure
Date of issue:	June 30, 2026
Compliance Specifications:	FCC 47 CFR Part 1 Subpart I, §§1.1307, 1.1310 FCC 47 CFR Part 2 Subpart J, §§2.1091, 2.1093 FCC KDB 447498 D01 General RF Exposure Guidance v06 FCC KDB 865664 D01 RF Exposure Procedures and Equipment Authorization Policies

Nemko Canada Inc., a testing laboratory, is accredited by ANSI National Accreditation Board (ANAB).
The test results included in this report are within the scope of this accreditation.
The ANAB symbol is an official symbol of the ANSI National Accreditation Board, used under licence.



Test locations of Nemko Canada Inc.

	Ottawa site	Montréal site	GTA Cambridge site
Facility address	303 River Road Ottawa, Ontario Canada K1V 1H2 Tel: +1 613 737 9680 Fax: +1 613 737 9691	292 Labrosse Avenue Pointe-Claire, Québec Canada H9R 5L8 Tel: +1 514 694 2684 Fax: +1 514 694 3528	1-130 Saltsman Drive Cambridge, Ontario Canada N3E 0B2 Tel: +1 519 650 4811
Test site identifier - FCC	CA2040	CA2041	CA0101
Test site identifier – ISED Canada	2040A-4	2040G-5	24676
ANAB File Number	AT-3195	AT-3193	AT-3194

Andrey Adelberg

Senior EMC/Wireless Specialist

Prepared by



Signature

Limits of responsibility

The results presented in this report apply solely to the specific device model tested and are valid only for the operating conditions and installation requirements specified herein. Testing was conducted in accordance with ISO/IEC 17025:2017 requirements, and all results fall within the scope of Nemko Canada's accreditation.

This MPE evaluation is based on the maximum power levels and operating conditions specified. Any modifications to the device hardware, software, or installation that could affect RF output power or antenna characteristics may invalidate this compliance demonstration.

Copyright notification

This report may be reproduced by the applicant in its entirety for regulatory submission and internal use. Any use of this report by third parties, including reliance on its contents or decisions made based on it, is solely at the risk of those third parties. Nemko Canada Inc. assumes no responsibility for any damages incurred by third parties as a result of actions taken based on this report.

© Nemko Canada Inc. All rights reserved.



1. Executive Summary

This report presents the Maximum Permissible Exposure (MPE) analysis to demonstrate compliance with FCC RF exposure requirements. The evaluation considers both single transmitter operation and simultaneous multi-transmitter scenarios where applicable.

2. Key Findings

Compliance status	Complies
Critical separation distances	67 cm
Special conditions or limitations	N/A

MPE calculations for stand-alone transmission

Device Classification Requirements

Portable Device Definition (§2.1093)	Devices designed for use by a person where the radiating structure is within 20 cm of the user's body require SAR evaluation rather than MPE calculation.
Mobile Device Definition	Devices installed in vehicles or with permanently installed antennas may use MPE calculations if minimum separation distances can be established.
Fixed/Base Station Definition	Stationary transmitters with controlled access to antenna locations may use MPE calculations for both occupational and general population exposure scenarios.

3. References, definitions and limits for FCC

FCC §2.1091(d)

- (2) For operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in Table 1 in paragraph (e)(1) of this section, may be used instead of whole-body SAR limits as set forth in paragraphs (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b) of this part, except for portable devices as defined in §2.1093 of this chapter as these evaluations shall be performed according to the SAR provisions in §2.1093.

Table 1: §1.1310(e)(1)—Power Density Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure		
0.3–3.0	*(100)	≤6
3.0–30	*(900 / f ²)	<6
30–300	1.0	<6
300–1500	f / 300	<6
1500–100000	5	<6
(ii) Limits for General Population/Uncontrolled Exposure		
0.3–1.34	*(100)	<30
1.34–30	*(180 / f ²)	<30
30–300	0.2	<30
300–1500	f / 1500	<30
1500–100000	1.0	<30

Notes: f = frequency in MHz. * = Plane-wave equivalent power density.

4. Power density calculation formula

The fundamental equation (from page 18 of OET Bulletin 65, Edition 97-01) for calculating power density at a specified distance from an RF source is derived from the far-field assumption:

$$S = \frac{PG}{4\pi R^2}$$

where:

- S = Power density (mW/cm² or W/m²)
- P = Power input to antenna (mW or W)
- G = Antenna gain (linear ratio, not dB)
- R = Distance from radiation center (cm or m)

This equation assumes:

- Far-field conditions ($R > 2D^2/\lambda$, where D is largest antenna dimension) are assumed at the evaluation distance of 20 cm
- Isotropic power distribution (conservative approach)
- Free-space propagation conditions
- Worst-case antenna orientation

Multiple Transmitter Analysis (if applicable)

Total Exposure Ratio (TER) Calculation: $TER = \sum(S_i/L_i) \leq 1.0$

Where:

- S_i = Power density from transmitter i
- L_i = Applicable limit for transmitter i

5. EUT technical information for a single/simultaneous transmitter operation

	1.3 GHz band	1.4 GHz band			
Prediction frequency	1392.5 MHz	1433 MHz			
Antenna gain	5 dBi	5 dBi			
Number of antennas	1	1			
Maximum transmitter power	42.15 dBm	41.19 dBm			
Declared separation distance	67 cm	59 cm			
Duty cycle	100%	100%			

6. Test report references

Transmitter maximum output power measurement result was taken from the following RF test reports:

Report 1			
Report ID	REP134049-1R3TRFWL		
Issue date	30-Jun-26	Click or tap to enter a date.	Click or tap to enter a date.
Test standard	FCC Part 27		

7. Verdict

The calculated power density at the declared separation distance is below the applicable regulatory limits. Therefore, the product **COMPLIES** with FCC RF exposure requirements for single transmitter operation.

8. MPE calculation (conducted method) for FCC Uncontrolled environment (General population) for 1.3 GHz operation

Band, type	Frequency, MHz	Conducted power (measured), dBm	Cable loss, dB	Maximum power at antenna terminal, dBm	Duty cycle, %	Average power adjusted for duty cycle, mW	Antenna gain, dBi	Number of antennas	Total system gain, dBi	Declared distance, cm	Average power density at declared distance, mW/cm ²	MPE limit, mW/cm ²	Exposure ratio	Minimum calculated prediction distance for compliance, cm	Margin of Compliance, dB	Maximum permitted total system gain, dBi
1.3G	1392.5	42.15	0	42.15	100	16405.898	5.00	1	5.00	67	0.919688	0.928333	0.990687	67	0.04	5.04

9. MPE calculation (conducted method) for FCC Uncontrolled environment (General population) for 1.4 GHz operation

Band, type	Frequency, MHz	Conducted power (measured), dBm	Cable loss, dB	Maximum power at antenna terminal, dBm	Duty cycle, %	Average power adjusted for duty cycle, mW	Antenna gain, dBi	Number of antennas	Total system gain, dBi	Declared distance, cm	Average power density at declared distance, mW/cm ²	MPE limit, mW/cm ²	Exposure ratio	Minimum calculated prediction distance for compliance, cm	Margin of Compliance, dB	Maximum permitted total system gain, dBi
1.4G	1433	41.19	0	41.19	100	13152.248	5.00	1	5.00	59	0.950793	0.955333	0.995248	59	0.02	5.02

End of the test report