

TEST REPORT

Application No.: KSCR2604000990AT
FCC ID: 2A7ZZ-GT00-04
Applicant: Visir Inc.
Address of Applicant: 700 International Pkwy, Ste 102, Richardson, TX 75081
Manufacturer: Visir Inc.
Address of Manufacturer: 700 International Pkwy, Ste 102, Richardson, TX 75081
Factory: Visir Inc.
Address of Factory: 700 International Pkwy, Ste 102, Richardson, TX 75081
Equipment Under Test (EUT):
EUT Name: THERMAL IMAGING SCOPE
Model No.: GLINT G2; GLINT G3 ♣
 ♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Trade Mark: RIX
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2026-04-30
Date of Test: 2026-05-08 to 2026-05-26
Date of Issue: 2026-05-27

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record			
Version	Description	Date	Remark
00	Original	2026-05-27	/

Authorized for issue by:			
Tested By		<i>Tommie Tang</i>	
		<u>Tommie_Tang/Project Engineer</u>	
Approved By		<i>Terry Hou</i>	
		<u>Terry Hou /Reviewer</u>	

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5 & 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6 & 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Maximum Conducted Output Power		ANSI C63.10 (2020) Section 11.9.2	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectral Density		ANSI C63.10 (2020) Section 11.10.3	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass

Declaration of EUT Family Grouping:

Note: There are series models mentioned in this report, and they are identical in electrical and electronic characters. Only the model GLINT G2 was tested since their differences were the model number, lens size, detector core board and flexible printed circuit (FPC).

3 Contents

	Page
1 COVER PAGE	1
2 Test Summary	3
3 Contents.....	4
4 General Information.....	5
4.1 Details of E.U.T.	5
4.2 Power level setting using in test.....	5
4.3 Description of Support Units	5
4.4 Measurement Uncertainty	6
4.5 Test Location	7
4.6 Test Facility	7
4.7 Deviation from Standards.....	7
4.8 Abnormalities from Standard Conditions.....	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement.....	9
6.1 Antenna Requirement	9
7 Radio Spectrum Matter Test Results	10
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz).....	10
7.2 Radiated Emissions which fall in the restricted bands	14
7.3 Radiated Spurious Emissions Below 1GHz	49
7.4 Radiated Spurious Emissions Above 1GHz.....	54
7.5 Maximum Conducted Output Power	80
7.6 Minimum 6dB Bandwidth.....	82
7.7 Power Spectral Density	83
7.8 Conducted Band Edges Measurement	84
7.9 Conducted Spurious Emissions	86
8 Test Setup Photo	88
9 EUT Constructional Details (EUT Photos).....	88
10 Appendix.....	89

4 General Information

4.1 Details of E.U.T.

Power supply:	DC 5V,2A by USB or DC 3.6V by rechargeable Li-ion battery
Operation Frequency:	802.11b/g/n(HT20)/ax(HEW20): 2412MHz to 2462MHz; 802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (DBPSK, DQPSK, CCK); 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM); 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024-QAM)
Number of Channels:	802.11b/g/n(HT20)/ax(HEW20):11;802.11n(HT40):7
Channel Spacing:	5MHz
Antenna Type:	FPC Antenna
Antenna Gain:	3dBi (Provided by the manufacturer)

4.2 Power level setting using in test

Channel	802.11b	802.11g	802.11n(HT20)	802.11ax(HE20)
	Ant 1	Ant 1	Ant 1	Ant 1
1	13	13	13	13
6	13	13	13	13
11	13	13	13	13
Channel	802.11n(HT40)			
	Ant 1			
3	13			
6	13			
9	13			

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Notebook	LENOVO	K27	/
Adapter	Sichuan Jiuzhou Electronic Technology Co.,Ltd	DYS05200CQ-U	/

4.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	8.4×10^{-8}
2	Timeout	2s
3	Duty Cycle	0.37%
4	Occupied Bandwidth	3%
5	RF Conducted Power	0.6dB
6	RF Power Density	2.9dB
7	Conducted Spurious Emissions	0.75dB
8	RF Radiated Power	5.2dB (Below 1GHz)
		5.9dB (Above 1GHz)
9	Radiated Spurious Emission Test	4.2dB (Below 30MHz)
		4.5dB (30MHz-1GHz)
		5.1dB (1GHz-18GHz)
		5.4dB (Above 18GHz)
10	Temperature Test	1°C
11	Humidity Test	3%
12	Supply Voltages	1.5%
13	Time	3%
Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.		

4.5 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

1. SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).
2. SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).
3. Sample source: sent by customer.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 2541.01)**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA).

- **FCC (Designation Number: CN1172)**

Compliance Certification Services (Kunshan) Inc. has been recognized as an accredited testing laboratory.

- **ISED (CAB Identifier: CN0072)**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 2324E

- **VCCI (Member No:1938)**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None

5 Equipment List

Item	Equipment	Manufacturer	Model	Inventory No	Cal Date	Cal. Due Date
Conducted Emission at Mains Terminals						
1	EMI Test Receive	R&S	ESCI	KS301196	07/09/2025	07/08/2026
2	LISN	R&S	ENV216	KS301197	01/08/2026	01/07/2027
3	LISN	Schwarzbeck	NNLK 8129	KS301091	01/08/2026	01/07/2027
4	Pulse Limiter	R&S	ESH3-Z2	KUS1902E001	12/18/2025	12/17/2026
5	CE test Cable	Thermax	/	CZ301102	12/18/2025	12/17/2026
6	Software	Faratronic	E3	/	N.C.R	N.C.R
RF Conducted Test						
1	Spectrum Analyzer	Keysight	N9020A	KUS1911E004-2	07/09/2025	07/08/2026
2	Spectrum Analyzer	Keysight	N9020A	KUS2001M001-2	07/09/2025	07/08/2026
3	Spectrum Analyzer	Keysight	N9030B	KSEM021-1	12/17/2025	12/16/2026
4	Signal Generator	R&S	SMBV100B	KSEM032	12/17/2025	12/16/2026
5	Signal Generator	R&S	SMW200A	KSEM020-1	07/09/2025	07/08/2026
6	Signal Generator	Agilent	N5182A	KUS2001M001-1	07/08/2025	07/07/2026
7	Signal Generator	Agilent	E8257C	KS301066	07/22/2025	07/21/2026
8	Radio Communication Test Station	Anritsu	MT8000A	KSEM001-1	07/09/2025	07/08/2026
9	Radio Communication Analyzer	Anritsu	MT8821C	KSEM002-1	12/17/2025	12/16/2026
10	Universal Radio Communication Tester	R&S	CMW500	KUS1911E004-1	07/08/2025	07/07/2026
11	Switcher	TST	FY562	KUS2001M001-4	12/17/2025	12/16/2026
12	Conducted Test Cable	Thermax	RF01-RF04	CZ301111- CZ301120	12/17/2025	12/16/2026
13	Temp. / Humidity Chamber	TERCHY	MHK-120AK	KS301190	07/15/2025	07/14/2026
14	Temperature & Humidity Recorder	Renke Control	RS-WS-N01-6J	KSEM024-5	12/30/2025	12/29/2026
15	Software	BST	TST-PASS	/	NCR	NCR
RF Radiated Test						
1	Spectrum Analyzer	R&S	FSV40	KUS1806E003	07/09/2025	07/08/2026
2	Universal Radio Communication Tester	R&S	CMW500	KSEM009-1	12/17/2025	12/16/2026
3	Signal Generator	Agilent	E8257C	KS301066	07/22/2025	07/21/2026
4	Loop Antenna (9KHz-30MHz)	COM-POWER	AL-130R	KUS1806E001	07/11/2025	07/10/2026
5	Bilog Antenna (30MHz-1GHz)	TESEQ	CBL 6112D	KUS1806E005	07/12/2025	07/11/2026
6	Horn-antenna(1-18GHz)	Schwarzbeck	BBHA9120D	KS301079	01/11/2026	01/10/2028
7	Horn Antenna(18-40GHz)	Schwarzbeck	BBHA9170	CZ301058	01/11/2026	01/10/2028
8	Amplifier(30MHz~1GHz)	TST	LNA009100G30	KSEM061	12/18/2025	12/17/2026
9	Amplifier(400MHz~8GHz)	TST	LNA004080G30	KSEM062	12/18/2025	12/17/2026
10	Amplifier(1GHz~18GHz)	TST	LNA010180G45	KSEM039	07/09/2025	07/08/2026
11	Amplifier(18~40GHz)	TST	LNA180400G40	KSEM038	07/09/2025	07/08/2026
12	RF Test Cable	REBES MICROWAVE	A81-SMSM-10M	CZ301097- CZ301100	11/14/2025	11/13/2026
13	Temperature & Humidity Recorder	Renke Control	RS-WS-N01-6J	KSEM024-4	12/30/2025	12/29/2026
14	Software	ESE	E3_V 6.111221a	/	NCR	NCR
15	Measurement Software	Tonscend	JS32-RE V5.0.0.1	/	NCR	NCR
16	Measurement Software	Tonscend	JS32-RSE V5.0.0.0	/	NCR	NCR

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna FPC Antenna and no consideration of replacement. The best case gain of the antenna is 3 dBi.

Antenna location: Refer to internal photo.

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2020) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 28.8 °C


Humidity: 55.6 % RH

Atmospheric Pressure: 1010 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax 20. Only the data of worst case is recorded in the report.

7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.


Remark: Level=Read Level+ Cable Loss+ LISN Factor

Test Mode: 00; Line: Live line



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1567	4.18	20.36	24.54	55.63	-31.09	Average
2	0.1567	22.32	20.36	42.68	65.63	-22.95	QP
3	0.2393	-3.53	20.13	16.60	52.12	-35.52	Average
4	0.2393	12.46	20.13	32.59	62.12	-29.53	QP
5	0.5456	-8.86	20.21	11.35	46.00	-34.65	Average
6	0.5456	-1.38	20.21	18.83	56.00	-37.17	QP
7	2.4360	-11.42	20.12	8.70	46.00	-37.30	Average
8	2.4360	-6.06	20.12	14.06	56.00	-41.94	QP
9	3.8670	-11.16	20.09	8.93	46.00	-37.07	Average
10	3.8670	-5.78	20.09	14.31	56.00	-41.69	QP
11	22.9080	-12.78	20.54	7.76	50.00	-42.24	Average
12	22.9080	-7.84	20.54	12.70	60.00	-47.30	QP

Test Mode: 00; Line: Neutral Line



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1501	3.85	20.44	24.29	56.00	-31.71	Average
2	0.1501	21.85	20.44	42.29	66.00	-23.71	QP
3	0.1753	1.53	20.36	21.89	54.71	-32.82	Average
4	0.1753	18.86	20.36	39.22	64.71	-25.49	QP
5	0.4506	-2.67	20.18	17.51	46.86	-29.35	Average
6	0.4506	9.49	20.18	29.67	56.86	-27.19	QP
7	1.0440	-11.39	19.99	8.60	46.00	-37.40	Average
8	1.0440	-3.97	19.99	16.02	56.00	-39.98	QP
9	7.1210	-14.37	19.74	5.37	50.00	-44.63	Average
10	7.1210	-9.26	19.74	10.48	60.00	-49.52	QP
11	29.7470	-6.18	20.79	14.61	50.00	-35.39	Average
12	29.7470	6.75	20.79	27.54	60.00	-32.46	QP

7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.10.5 & 11.12

Measurement Distance: 3M

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 45.6 % RH

Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax 20. Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1: $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.


11b_TX_CH_01_Horizontal_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2385.92	46.76	26.66	-26.15	47.27	74.00	26.73	Horizontal
2	2389.43	46.71	26.69	-26.13	47.27	74.00	26.73	Horizontal




11b_TX_CH_01_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBµV]	AF [dB/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity
1	2385.14	34.59	26.65	-26.15	35.09	54.00	18.91	Horizontal
2	2389.17	34.64	26.69	-26.13	35.20	54.00	18.80	Horizontal

11b_TX_CH_01_Vertical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2382.41	46.83	26.62	-26.16	47.29	74.00	26.71	Vertical
2	2389.43	46.72	26.69	-26.13	47.28	74.00	26.72	Vertical

11b_TX_CH_01_Vertical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2386.44	34.65	26.66	-26.14	35.17	54.00	18.83	Vertical
2	2389.69	34.61	26.70	-26.13	35.18	54.00	18.82	Vertical

11b_TX_CH_11_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.7	46.31	27.15	-26.24	47.22	74.00	26.78	Horizontal
2	2487.1	45.66	27.13	-26.25	46.54	74.00	27.46	Horizontal

11b_TX_CH_11_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.52	34.60	27.15	-26.24	35.51	54.00	18.49	Horizontal
2	2486.92	34.53	27.13	-26.25	35.41	54.00	18.59	Horizontal

11b_TX_CH_11_Vertical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.1	46.15	27.16	-26.24	47.07	74.00	26.93	Vertical
2	2485.84	46.96	27.14	-26.24	47.86	74.00	26.14	Vertical


11b_TX_CH_11_Vertical_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.16	34.42	27.16	-26.24	35.34	54.00	18.66	Vertical
2	2486.56	34.37	27.13	-26.24	35.26	54.00	18.74	Vertical




11n(HT20)_TX_CH_01_Horizontal_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2383.97	49.68	26.64	-26.16	50.16	74.00	23.84	Horizontal
2	2388.91	56.18	26.69	-26.13	56.74	74.00	17.26	Horizontal


11n(HT20)_TX_CH_01_Horizontal_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2384.75	35.27	26.65	-26.15	35.77	54.00	18.23	Horizontal
2	2389.3	39.76	26.69	-26.13	40.32	54.00	13.68	Horizontal




11n(HT20)_TX_CH_01_Vertical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2384.36	49.60	26.64	-26.15	50.09	74.00	23.91	Vertical
2	2388.91	55.96	26.69	-26.13	56.52	74.00	17.48	Vertical




11n(HT20)_TX_CH_01_Vetical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBµV]	AF [dB/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity
1	2386.7	36.34	26.67	-26.14	36.87	54.00	17.13	Vertical
2	2389.3	39.15	26.69	-26.13	39.71	54.00	14.29	Vertical

11n(HT20)_TX_CH_11_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.22	50.02	27.16	-26.24	50.94	74.00	23.06	Horizontal
2	2487.16	46.97	27.13	-26.25	47.85	74.00	26.15	Horizontal

11n(HT20)_TX_CH_11_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2483.92	36.23	27.16	-26.24	37.15	54.00	16.85	Horizontal
2	2485.54	35.71	27.14	-26.24	36.61	54.00	17.39	Horizontal

11n(HT20)_TX_CH_11_Vertical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.1	48.58	27.16	-26.24	49.50	74.00	24.50	Vertical
2	2485.78	48.76	27.14	-26.24	49.66	74.00	24.34	Vertical

11n(HT20)_TX_CH_11_Vertical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2483.98	35.85	27.16	-26.24	36.77	54.00	17.23	Vertical
2	2486.02	35.27	27.14	-26.24	36.17	54.00	17.83	Vertical

11n(HT40)_TX_CH_03_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2388.28	49.45	26.68	-26.14	49.99	74.00	24.01	Horizontal
2	2486.13	43.37	27.14	-26.24	44.27	74.00	29.73	Horizontal

11n(HT40)_TX_CH_03_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2387.33	44.20	26.67	-26.14	44.73	54.00	9.27	Horizontal
2	2484.99	28.80	27.15	-26.24	29.71	54.00	24.29	Horizontal

11n(HT40)_TX_CH_03_Vetical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2388.28	50.52	26.68	-26.14	51.06	74.00	22.94	Vertical
2	2485.18	43.39	27.15	-26.24	44.30	74.00	29.70	Vertical


11n(HT40)_TX_CH_03_Vetical_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2387.52	44.80	26.68	-26.14	45.34	54.00	8.66	Vertical
2	2485.75	26.72	27.14	-26.24	27.62	54.00	26.38	Vertical




11n(HT40)_TX_CH_09_Horizontal_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBµV]	AF [dB/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity
1	2387.9	39.00	26.68	-26.14	39.54	74.00	34.46	Horizontal
2	2485.94	55.46	27.14	-26.24	56.36	74.00	17.64	Horizontal


11n(HT40)_TX_CH_09_Horizontal_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2389.04	28.00	26.69	-26.13	28.56	54.00	25.44	Horizontal
2	2485.56	40.90	27.14	-26.24	41.80	54.00	12.20	Horizontal




11n(HT40)_TX_CH_09_Vertical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBµV]	AF [dB/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity
1	2389.04	39.04	26.69	-26.13	39.60	74.00	34.40	Vertical
2	2484.23	56.79	27.16	-26.24	57.71	74.00	16.29	Vertical

11n(HT40)_TX_CH_09_Vertical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2388.47	28.34	26.68	-26.13	28.89	54.00	25.11	Vertical
2	2484.8	42.11	27.15	-26.24	43.02	54.00	10.98	Vertical

11(HE20)_TX_CH_01_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2385.27	50.07	26.65	-26.15	50.57	74.00	23.43	Horizontal
2	2388.39	57.51	26.68	-26.13	58.06	74.00	15.94	Horizontal

11(HE20)_TX_CH_01_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2386.96	37.44	26.67	-26.14	37.97	54.00	16.03	Horizontal
2	2389.3	40.23	26.69	-26.13	40.79	54.00	13.21	Horizontal

11(HE20)_TX_CH_01_Vertical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2386.57	54.51	26.67	-26.14	55.04	74.00	18.96	Vertical
2	2388.78	58.92	26.69	-26.13	59.48	74.00	14.52	Vertical

11(HE20)_TX_CH_01_Veritical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2387.61	37.81	26.68	-26.14	38.35	54.00	15.65	Vertical
2	2389.04	40.53	26.69	-26.13	41.09	54.00	12.91	Vertical

11(HE20)_TX_CH_11_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2387.9	39.49	26.68	-26.14	40.03	74.00	33.97	Horizontal
2	2484.61	60.38	27.15	-26.24	61.29	74.00	12.71	Horizontal

11(HE20)_TX_CH_11_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2388.09	28.33	26.68	-26.14	28.87	54.00	25.13	Horizontal
2	2484.42	41.64	27.16	-26.24	42.56	54.00	11.44	Horizontal

11(HE20)_TX_CH_11_Vertical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2387.52	40.08	26.68	-26.14	40.62	74.00	33.38	Vertical
2	2485.94	60.97	27.14	-26.24	61.87	74.00	12.13	Vertical

11(HE20)_TX_CH_11_Veritical_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2389.04	28.83	26.69	-26.13	29.39	54.00	24.61	Vertical
2	2484.23	41.30	27.16	-26.24	42.22	54.00	11.78	Vertical

7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

Measurement Distance: 3M

Limit:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	Field strength (dBµV/m@3m)
0.009-0.490	2400/F(kHz)	300	128.5 to 93.8
0.490-1.705	24000/F(kHz)	30	73.8 to 62.9
1.705-30.0	30	30	69.60
30-88	100	3	40.0
88-216	150	3	43.5
216-960	200	3	46.0
960-1000	500	3	54.0

Note : The above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 45.6 % RH

Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax 20. Only the data of worst case is recorded in the report.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8m above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3m or 10m away from the interference-receiving antenna, which was mounted on the variable-height antenna tower.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1m) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. At frequencies below 1GHz, measurements may be performed at a distance different to specified in the regulations.

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.


EX. Below 30MHz, Aux Factor = 40 dB/decade of distance, the aux factor is $40\log(3/300) = -80\text{dB}$ (for 3m test distance).

EX. Above 30MHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(10/3) = 10.46\text{dB}$ (for 10m test distance).

2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.


Test Mode: 00; Polarity: Horizontal



Final Data List

NO.	Frequency [MHz]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	42.61	9.93	-32.39	22.62	40.00	17.38	255	306	Horizontal
2	95.96	11.42	-31.87	16.21	43.50	27.29	255	239	Horizontal
3	133.5475	13.75	-31.61	18.30	43.50	25.20	255	292	Horizontal
4	434.005	17.58	-30.42	23.60	46.00	22.40	255	54	Horizontal
5	619.0325	20.82	-29.87	29.89	46.00	16.11	255	306	Horizontal
6	799.9375	22.21	-29.27	29.86	46.00	16.14	255	355	Horizontal

Test Mode: 00; Polarity: Vertical



Final Data List

NO.	Frequency [MHz]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	32.1825	17.77	-32.51	22.24	40.00	17.76	255	172	Vertical
2	68.8	6.78	-32.09	26.40	40.00	13.60	255	359	Vertical
3	235.155	12.61	-31.13	17.42	46.00	28.58	255	27	Vertical
4	380.8975	15.75	-30.69	15.63	46.00	30.37	255	344	Vertical
5	511.8475	19.00	-30.15	20.40	46.00	25.60	255	95	Vertical
6	714.335	21.71	-29.52	24.81	46.00	21.19	255	148	Vertical

7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.6 & 11.12

Measurement Distance: 3M

Limit:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

Note:

At Above 18GHz, measurements may be performed at a distance shorter than that specified in the regulations

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Above 18GHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(1/3) = -9.54\text{dB}$ (for 1m test distance).

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 45.6 % RH

Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax 20. Only the data of worst case is recorded in the report.

7.4.3 Test Setup Diagram




7.4.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5m above the ground at a 3m fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3m away from the interference-receiving antenna from 1GHz to 18GHz, and 3m away from the interference-receiving antenna above 18GHz.
- b. The interference-receiving antenna was mounted on the variable-height antenna tower, with its boresight facing the EUT throughout the test.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- g. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- h. Repeat above procedures until all frequencies measured was complete.

Remark:


1. Scan from 1GHz to 10th harmonic of the highest frequency or 40 GHz, whichever is lower.
2. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
3. Scan for the frequency above 18GHz, the disturbance above 18GHz was very low. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
4. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s).

11b_TX_CH_01_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4824.5	61.57	31.45	-50.19	42.83	54.00	11.17	Horizontal
2	12839	45.91	39.77	-43.21	42.47	54.00	11.53	Horizontal
3	17999	48.57	43.20	-41.18	50.59	54.00	3.41	Horizontal
4	1599.5	47.32	23.71	-28.14	42.89	74.00	31.11	Horizontal
5	4824	65.04	31.45	-50.19	46.30	74.00	27.70	Horizontal
6	12838.5	54.55	39.76	-43.20	51.11	74.00	22.89	Horizontal
7	17994	56.34	43.20	-41.26	58.28	74.00	15.72	Horizontal

11b_TX_CH_01_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	1594.1667	47.72	23.76	-28.14	43.34	74.00	30.66	Vertical
2	4824	66.44	31.45	-50.19	47.70	74.00	26.30	Vertical
3	7233	60.17	36.33	-48.63	47.87	74.00	26.13	Vertical
4	17998	56.11	43.20	-41.19	58.12	74.00	15.88	Vertical

11b_TX_CH_06_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4874.5	60.28	31.45	-50.56	41.17	54.00	12.83	Horizontal
2	6459.5	50.66	34.20	-46.82	38.04	54.00	15.96	Horizontal
3	17983.5	48.85	43.20	-41.44	50.61	54.00	3.39	Horizontal
4	1789	47.98	24.06	-27.67	44.37	74.00	29.63	Horizontal
5	4874	63.94	31.45	-50.56	44.83	74.00	29.17	Horizontal
6	6510	58.49	34.30	-46.43	46.36	74.00	27.64	Horizontal
7	17991	56.02	43.20	-41.31	57.91	74.00	16.09	Horizontal

11b_TX_CH_06_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4874.5	62.12	31.45	-50.56	43.01	54.00	10.99	Vertical
2	7309	55.06	36.32	-48.60	42.78	54.00	11.22	Vertical
3	17989	49.25	43.20	-41.35	51.10	54.00	2.90	Vertical
4	1804	46.19	23.98	-27.63	42.54	74.00	31.46	Vertical
5	4874	66.12	31.45	-50.56	47.01	74.00	26.99	Vertical
6	7314	59.48	36.33	-48.56	47.25	74.00	26.75	Vertical
7	17994.5	56.88	43.20	-41.25	58.83	74.00	15.17	Vertical

11b_TX_CH_11_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4924.5	60.35	31.50	-50.73	41.12	54.00	12.88	Horizontal
2	6505.5	49.83	34.26	-46.31	37.78	54.00	16.22	Horizontal
3	17994	49.10	43.20	-41.26	51.04	54.00	2.96	Horizontal
4	1802.1667	46.33	23.94	-27.62	42.65	74.00	31.35	Horizontal
5	4924	64.46	31.50	-50.73	45.23	74.00	28.77	Horizontal
6	6515	58.23	34.35	-46.56	46.02	74.00	27.98	Horizontal
7	17987	55.94	43.20	-41.38	57.76	74.00	16.24	Horizontal

11b_TX_CH_11_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4924.5	63.32	31.50	-50.73	44.09	54.00	9.91	Vertical
2	7385	54.32	36.33	-47.99	42.66	54.00	11.34	Vertical
3	17993.5	48.85	43.20	-41.27	50.78	54.00	3.22	Vertical
4	1801	46.36	23.92	-27.62	42.66	74.00	31.34	Vertical
5	4924	64.93	31.50	-50.73	45.70	74.00	28.30	Vertical
6	7386.5	59.89	36.33	-47.98	48.24	74.00	25.76	Vertical
7	17997.5	56.32	43.20	-41.20	58.32	74.00	15.68	Vertical

11n(HT20)_TX_CH_01_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4830	53.45	31.44	-50.23	34.66	54.00	19.34	Horizontal
2	8953	48.68	37.81	-46.17	40.32	54.00	13.68	Horizontal
3	17974	48.74	43.20	-41.61	50.33	54.00	3.67	Horizontal
4	1782.3333	46.10	23.79	-27.70	42.19	74.00	31.81	Horizontal
5	4822	62.13	31.46	-50.17	43.42	74.00	30.58	Horizontal
6	9075.5	56.38	37.85	-46.33	47.90	74.00	26.10	Horizontal
7	17996	56.53	43.20	-41.23	58.50	74.00	15.50	Horizontal

11n(HT20)_TX_CH_01_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4824.5	56.11	31.45	-50.19	37.37	54.00	16.63	Vertical
2	7232	52.63	36.33	-48.63	40.33	54.00	13.67	Vertical
3	17990.5	49.17	43.20	-41.32	51.05	54.00	2.95	Vertical
4	4820	63.15	31.46	-50.16	44.45	74.00	29.55	Vertical
5	7240.5	59.93	36.36	-48.63	47.66	74.00	26.34	Vertical
6	17994	55.63	43.20	-41.26	57.57	74.00	16.43	Vertical

11n(HT20)_TX_CH_06_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4801	55.66	31.50	-50.02	37.14	54.00	16.86	Horizontal
2	6500.5	50.00	34.21	-46.18	38.03	54.00	15.97	Horizontal
3	17995.5	48.50	43.20	-41.24	50.46	54.00	3.54	Horizontal
4	1620.6667	46.27	23.79	-28.12	41.94	74.00	32.06	Horizontal
5	4799	60.98	31.49	-50.02	42.45	74.00	31.55	Horizontal
6	6524	58.86	34.44	-46.80	46.50	74.00	27.50	Horizontal
7	17998	56.48	43.20	-41.19	58.49	74.00	15.51	Horizontal

11n(HT20)_TX_CH_06_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4874.5	56.33	31.45	-50.56	37.22	54.00	16.78	Vertical
2	7311.5	51.38	36.32	-48.58	39.12	54.00	14.88	Vertical
3	18000	48.33	43.20	-41.16	50.37	54.00	3.63	Vertical
4	1661.8333	46.45	23.70	-28.09	42.06	74.00	31.94	Vertical
5	4874	63.25	31.45	-50.56	44.14	74.00	29.86	Vertical
6	7313.5	60.12	36.33	-48.56	47.89	74.00	26.11	Vertical
7	17983	55.78	43.20	-41.45	57.53	74.00	16.47	Vertical

11n(HT20)_TX_CH_11_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4800	54.13	31.50	-50.01	35.62	54.00	18.38	Horizontal
2	9277.5	49.26	38.15	-46.72	40.69	54.00	13.31	Horizontal
3	18000	48.49	43.20	-41.16	50.53	54.00	3.47	Horizontal
4	1804.1667	47.24	23.98	-27.63	43.59	74.00	30.41	Horizontal
5	4799.5	60.49	31.50	-50.02	41.97	74.00	32.03	Horizontal
6	9355.5	58.13	38.31	-46.80	49.64	74.00	24.36	Horizontal
7	17990.5	55.99	43.20	-41.32	57.87	74.00	16.13	Horizontal

11n(HT20)_TX_CH_11_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4925.5	55.09	31.50	-50.73	35.86	54.00	18.14	Vertical
2	11226	47.71	39.55	-44.25	43.01	54.00	10.99	Vertical
3	17992.5	49.04	43.20	-41.29	50.95	54.00	3.05	Vertical
4	1825.3333	46.57	24.01	-27.66	42.92	74.00	31.08	Vertical
5	4916.5	61.26	31.50	-50.74	42.02	74.00	31.98	Vertical
6	11230.5	55.30	39.56	-44.26	50.60	74.00	23.40	Vertical
7	17996	56.90	43.20	-41.23	58.87	74.00	15.13	Vertical

11n(HT40)_TX_CH_03_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4801.5	55.25	31.50	-50.02	36.73	54.00	17.27	Horizontal
2	11226	47.30	39.55	-44.25	42.60	54.00	11.40	Horizontal
3	17994.5	48.71	43.20	-41.25	50.66	54.00	3.34	Horizontal
4	1199.8333	49.25	23.60	-27.99	44.86	74.00	29.14	Horizontal
5	4801	62.58	31.50	-50.02	44.06	74.00	29.94	Horizontal
6	11226	54.92	39.55	-44.25	50.22	74.00	23.78	Horizontal
7	17973.5	56.43	43.20	-41.62	58.01	74.00	15.99	Horizontal

11n(HT40)_TX_CH_03_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4800	54.84	31.50	-50.01	36.33	54.00	17.67	Vertical
2	8000	52.91	36.90	-47.75	42.06	54.00	11.94	Vertical
3	17989.5	48.92	43.20	-41.34	50.78	54.00	3.22	Vertical
4	1584.5	47.35	23.75	-28.13	42.97	74.00	31.03	Vertical
5	4798.5	61.60	31.49	-50.03	43.06	74.00	30.94	Vertical
6	7999.5	59.16	36.90	-47.75	48.31	74.00	25.69	Vertical
7	18000	55.77	43.20	-41.16	57.81	74.00	16.19	Vertical

11n(HT40)_TX_CH_06_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4801.5	54.42	31.50	-50.02	35.90	54.00	18.10	Horizontal
2	11211	46.54	39.52	-44.23	41.83	54.00	12.17	Horizontal
3	17991.5	48.60	43.20	-41.31	50.49	54.00	3.51	Horizontal
4	1742	47.28	23.60	-27.88	43.00	74.00	31.00	Horizontal
5	4799.5	60.36	31.50	-50.02	41.84	74.00	32.16	Horizontal
6	11211	54.75	39.52	-44.23	50.04	74.00	23.96	Horizontal
7	17989	56.42	43.20	-41.35	58.27	74.00	15.73	Horizontal

11n(HT40)_TX_CH_06_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4400.5	53.82	30.40	-52.12	32.10	54.00	21.90	Vertical
2	11199.5	46.09	39.50	-44.21	41.38	54.00	12.62	Vertical
3	17995.5	48.35	43.20	-41.24	50.31	54.00	3.69	Vertical
4	1763.3333	45.42	23.77	-27.78	41.41	74.00	32.59	Vertical
5	4400	61.29	30.40	-52.12	39.57	74.00	34.43	Vertical
6	11179.5	54.06	39.42	-44.39	49.09	74.00	24.91	Vertical
7	17995	55.92	43.20	-41.25	57.87	74.00	16.13	Vertical

11n(HT40)_TX_CH_09_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4802	52.59	31.50	-50.02	34.07	54.00	19.93	Horizontal
2	8690.5	48.40	37.48	-45.81	40.07	54.00	13.93	Horizontal
3	17988	48.11	43.20	-41.37	49.94	54.00	4.06	Horizontal
4	1890.3333	46.15	24.30	-27.76	42.69	74.00	31.31	Horizontal
5	4801.5	60.69	31.50	-50.02	42.17	74.00	31.83	Horizontal
6	8690	56.35	37.48	-45.82	48.01	74.00	25.99	Horizontal
7	17995	55.34	43.20	-41.25	57.29	74.00	16.71	Horizontal

11n(HT40)_TX_CH_09_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4917.5	54.81	31.50	-50.74	35.57	54.00	18.43	Vertical
2	7381	50.90	36.34	-48.02	39.22	54.00	14.78	Vertical
3	17992	48.00	43.20	-41.30	49.90	54.00	4.10	Vertical
4	4920.5	63.71	31.50	-50.74	44.47	74.00	29.53	Vertical
5	7480	57.15	36.44	-47.05	46.54	74.00	27.46	Vertical
6	17983.5	55.65	43.20	-41.44	57.41	74.00	16.59	Vertical

11ax(HE20)_TX_CH_01_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4400.5	57.18	30.40	-52.12	35.46	54.00	18.54	Horizontal
2	15020.5	45.37	39.68	-40.93	44.12	54.00	9.88	Horizontal
3	17997.5	49.29	43.20	-41.20	51.29	54.00	2.71	Horizontal
4	1438.6667	47.33	23.71	-28.03	43.01	74.00	30.99	Horizontal
5	4400	65.64	30.40	-52.12	43.92	74.00	30.08	Horizontal
6	14944.5	54.52	39.81	-41.76	52.57	74.00	21.43	Horizontal
7	17994.5	56.51	43.20	-41.25	58.46	74.00	15.54	Horizontal

11ax(HE20)_TX_CH_01_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4790	56.46	31.42	-50.11	37.77	54.00	16.23	Vertical
2	11253	47.27	39.59	-44.30	42.56	54.00	11.44	Vertical
3	17999.5	49.21	43.20	-41.17	51.24	54.00	2.76	Vertical
4	1822.3333	46.42	23.95	-27.66	42.71	74.00	31.29	Vertical
5	4789.5	62.87	31.42	-50.12	44.17	74.00	29.83	Vertical
6	11228	55.45	39.56	-44.26	50.75	74.00	23.25	Vertical
7	17999.5	56.35	43.20	-41.17	58.38	74.00	15.62	Vertical

11ax(HE20)_TX_CH_06_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4801	54.00	31.50	-50.02	35.48	54.00	18.52	Horizontal
2	11203	46.24	39.51	-44.22	41.53	54.00	12.47	Horizontal
3	17994.5	48.34	43.20	-41.25	50.29	54.00	3.71	Horizontal
4	1998	47.54	25.18	-27.10	45.62	74.00	28.38	Horizontal
5	4801	61.22	31.50	-50.02	42.70	74.00	31.30	Horizontal
6	11144.5	54.14	39.33	-44.70	48.77	74.00	25.23	Horizontal
7	17988	55.18	43.20	-41.37	57.01	74.00	16.99	Horizontal

11ax(HE20)_TX_CH_06_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4880	56.43	31.46	-50.60	37.29	54.00	16.71	Vertical
2	7306.5	53.07	36.31	-48.62	40.76	54.00	13.24	Vertical
3	17991	48.18	43.20	-41.31	50.07	54.00	3.93	Vertical
4	1931.8333	46.31	24.40	-27.56	43.15	74.00	30.85	Vertical
5	4879.5	64.15	31.46	-50.60	45.01	74.00	28.99	Vertical
6	7313.5	59.06	36.33	-48.56	46.83	74.00	27.17	Vertical
7	17983.5	55.28	43.20	-41.44	57.04	74.00	16.96	Vertical

11ax(HE20)_TX_CH_11_Horizontal



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4800.5	56.32	31.50	-50.01	37.81	54.00	16.19	Horizontal
2	6502.5	49.61	34.23	-46.24	37.60	54.00	16.40	Horizontal
3	17996	48.33	43.20	-41.23	50.30	54.00	3.70	Horizontal
4	1556.3333	45.95	23.84	-28.11	41.68	74.00	32.32	Horizontal
5	4800	62.21	31.50	-50.01	43.70	74.00	30.30	Horizontal
6	6528	58.53	34.48	-46.91	46.10	74.00	27.90	Horizontal
7	17993.5	57.00	43.20	-41.27	58.93	74.00	15.07	Horizontal

11ax(HE20)_TX_CH_11_Vertical



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4924.5	57.31	31.50	-50.73	38.08	54.00	15.92	Vertical
2	7390	51.77	36.32	-47.95	40.14	54.00	13.86	Vertical
3	17999.5	47.64	43.20	-41.17	49.67	54.00	4.33	Vertical
4	2075.8333	47.58	25.59	-26.94	46.23	74.00	27.77	Vertical
5	4923	63.67	31.50	-50.73	44.44	74.00	29.56	Vertical
6	7389.5	59.86	36.32	-47.95	48.23	74.00	25.77	Vertical
7	17992	55.71	43.20	-41.30	57.61	74.00	16.39	Vertical

7.5 Maximum Conducted Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2020) Section 11.9.2

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 28.8 °C


Humidity: 55.6 % RH

Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax 20. Only the data of worst case is recorded in the report.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details

7.6 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2020) Section 11.8.1

Limit:

≥500 kHz

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 28.8 °C


Humidity: 55.6 % RH

Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax 20. Only the data of worst case is recorded in the report.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.7 Power Spectral Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2020) Section 11.10.3

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 28.8 °C


Humidity: 55.6 % RH

Atmospheric Pressure: 1010 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax 20. Only the data of worst case is recorded in the report.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.8 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 6.10.4

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 28.8 °C


Humidity: 55.6 % RH

Atmospheric Pressure: 1010 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax 20. Only the data of worst case is recorded in the report.

7.8.3 Test Setup Diagram





Report No.: KSCR260400099001

Page: 85 of 146

7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.9 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 28.8 °C


Humidity: 55.6 % RH

Atmospheric Pressure: 1010 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax 20. Only the data of worst case is recorded in the report.

7.9.3 Test Setup Diagram





Report No.: KSCR260400099001

Page: 87 of 146

7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Report No.: KSCR260400099001

Page: 88 of 146

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for KSCR2604000990AT

9 EUT Constructional Details (EUT Photos)

Refer to Appendix_Photographs of EUT Constructional Details for KSCR2604000990AT



10 Appendix

1. Duty Cycle

1.1 Test Result


1.1.1 Ant1

Ant1									
Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	/	/	4.210	4.268	98.64	0.06	0.68
802.11g	SISO	2412	/	/	1.404	1.476	95.12	0.22	2.31
802.11n (HT20)	SISO	2412	/	/	1.309	1.383	94.65	0.24	2.22
802.11n (HT40)	SISO	2422	/	/	0.649	0.718	90.39	0.44	4.38
802.11ax (HEW20)	SISO	2412	SU	/	1.188	1.264	93.99	0.27	2.04


1.2 Test Graph

1.2.1 Ant1


802.11b LCH 2412MHz Ant1 (SISO) NTN




802.11g LCH 2412MHz Ant1 (SISO) NTN




802.11n(HT20) LCH_2412MHz_Ant1 (SISO) NTN



802.11n(HT40) LCH_2422MHz_Ant1 (SISO) NTN



802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTNv



2. Bandwidth

2.1 Test Result

2.1.1 OBW


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	11.853	/	Pass
		2437	/	/	1	11.907	/	Pass
		2462	/	/	1	11.836	/	Pass
802.11g	SISO	2412	/	/	1	16.748	/	Pass
		2437	/	/	1	16.781	/	Pass
		2462	/	/	1	16.746	/	Pass
802.11n (HT20)	SISO	2412	/	/	1	17.663	/	Pass
		2437	/	/	1	17.668	/	Pass
		2462	/	/	1	17.673	/	Pass
802.11n (HT40)	SISO	2422	/	/	1	35.963	/	Pass
		2437	/	/	1	36.020	/	Pass
		2452	/	/	1	35.973	/	Pass
802.11ax (HEW20)	SISO	2412	SU	/	1	18.909	/	Pass
		2437	SU	/	1	18.913	/	Pass
		2462	SU	/	1	18.897	/	Pass

2.1.2 6dB BW


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	6dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	9.997	>=0.5	Pass
		2437	/	/	1	10.019	>=0.5	Pass
		2462	/	/	1	9.994	>=0.5	Pass
802.11g	SISO	2412	/	/	1	16.589	>=0.5	Pass
		2437	/	/	1	16.597	>=0.5	Pass
		2462	/	/	1	16.579	>=0.5	Pass
802.11n (HT20)	SISO	2412	/	/	1	17.687	>=0.5	Pass
		2437	/	/	1	17.672	>=0.5	Pass
		2462	/	/	1	17.679	>=0.5	Pass
802.11n (HT40)	SISO	2422	/	/	1	35.753	>=0.5	Pass
		2437	/	/	1	35.872	>=0.5	Pass
		2452	/	/	1	35.826	>=0.5	Pass
802.11ax (HEW20)	SISO	2412	SU	/	1	19.073	>=0.5	Pass
		2437	SU	/	1	19.030	>=0.5	Pass
		2462	SU	/	1	19.067	>=0.5	Pass

2.2 Test Graph


2.2.1 OBW




802.11b HCH 2462MHz_Ant1 (SISO)_NTNV




802.11g LCH 2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH 2412MHz Ant1 (SISO) NTN




802.11n(HT20) MCH 2437MHz Ant1 (SISO) NTN




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40) MCH_2437MHz_Ant1 (SISO) NTN




802.11n(HT40) HCH_2452MHz_Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTN



802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTN




802.11ax(HEW20) HCH 2462MHz SU / Ant1 (SISO) NTN




2.2.2 6dB BW


802.11b LCH 2412MHz Ant1 (SISO) NTN




802.11b MCH 2437MHz_Ant1 (SISO)_NTNV




802.11b HCH 2462MHz_Ant1 (SISO)_NTNV




802.11g LCH 2412MHz Ant1 (SISO) NTN




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20) MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT40) LCH 2422MHz Ant1 (SISO) NTN




802.11n(HT40) MCH_2437MHz_Ant1 (SISO) NTN




802.11n(HT40) HCH_2452MHz_Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTNv



802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTNv



802.11ax(HEW20) HCH 2462MHz SU / Ant1 (SISO) NTNv



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power


Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Average Conducted Output Power (dBm)		Verdict
					ANT1	Limit	
802.11b	SISO	2412	/	/	14.95	<=30	Pass
		2437	/	/	14.79	<=30	Pass
		2462	/	/	15.35	<=30	Pass
802.11g	SISO	2412	/	/	15.26	<=30	Pass
		2437	/	/	14.66	<=30	Pass
		2462	/	/	14.88	<=30	Pass
802.11n (HT20)	SISO	2412	/	/	14.46	<=30	Pass
		2437	/	/	14.49	<=30	Pass
		2462	/	/	14.63	<=30	Pass
802.11n (HT40)	SISO	2422	/	/	14.52	<=30	Pass
		2437	/	/	14.63	<=30	Pass
		2452	/	/	14.98	<=30	Pass
802.11ax (HEW20)	SISO	2412	SU	/	15.06	<=30	Pass
		2437	SU	/	15.00	<=30	Pass
		2462	SU	/	15.16	<=30	Pass

Note1: Antenna Gain: Ant1: 3.00dBi;


3.2 Test Graph

3.2.1 Power


802.11b LCH 2412MHz Ant1 (SISO) NTN




802.11b MCH 2437MHz Ant1 (SISO) NTN




802.11b HCH 2462MHz_Ant1 (SISO)_NTNV




802.11g LCH 2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH_2412MHz_Ant1 (SISO) NTN




802.11n(HT20) MCH_2437MHz_Ant1 (SISO) NTN




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT40) LCH 2422MHz Ant1 (SISO) NTN




802.11n(HT40) MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40) HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTNv



802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTNv





4. Maximum Power Spectral Density

4.1 Test Result

4.1.1 PSD


Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm)		Verdict
					ANT1	Limit(dBm/3kHz)	
802.11b	SISO	2412	/	/	-8.58dBm/3kHz	<=8	Pass
		2437	/	/	-13.86dBm/3kHz	<=8	Pass
		2462	/	/	-8.40dBm/3kHz	<=8	Pass
802.11g	SISO	2412	/	/	-16.13dBm/3kHz	<=8	Pass
		2437	/	/	-17.11dBm/3kHz	<=8	Pass
		2462	/	/	-16.73dBm/3kHz	<=8	Pass
802.11n (HT20)	SISO	2412	/	/	-17.32dBm/3kHz	<=8	Pass
		2437	/	/	-17.57dBm/3kHz	<=8	Pass
		2462	/	/	-17.59dBm/3kHz	<=8	Pass
802.11n (HT40)	SISO	2422	/	/	-18.74dBm/3kHz	<=8	Pass
		2437	/	/	-18.06dBm/3kHz	<=8	Pass
		2452	/	/	-18.25dBm/3kHz	<=8	Pass
802.11ax (HEW20)	SISO	2412	SU	/	-16.16dBm/3kHz	<=8	Pass
		2437	SU	/	-16.13dBm/3kHz	<=8	Pass
		2462	SU	/	-15.99dBm/3kHz	<=8	Pass

Note1: Antenna Gain: Ant1: 3.00dBi;


4.2 Test Graph

4.2.1 PSD


802.11b LCH 2412MHz Ant1 (SISO) NTNV




802.11b MCH 2437MHz Ant1 (SISO) NTNV




802.11b HCH 2462MHz Ant1 (SISO) NTN




802.11g LCH 2412MHz Ant1 (SISO) NTN




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20) MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT40) LCH 2422MHz Ant1 (SISO) NTN




802.11n(HT40) MCH_2437MHz_Ant1 (SISO) NTN




802.11n(HT40) HCH_2452MHz_Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTN



802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTN



802.11ax(HEW20) HCH 2462MHz SU / Ant1 (SISO) NTN



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	Level of Reference (dBm)
802.11b	SISO	2412	/	/	1	6.15
		2437	/	/	1	6.39
		2462	/	/	1	6.35
802.11g	SISO	2412	/	/	1	4.42
		2437	/	/	1	3.87
		2462	/	/	1	3.85
802.11n (HT20)	SISO	2412	/	/	1	3.55
		2437	/	/	1	3.70
		2462	/	/	1	3.39
802.11n (HT40)	SISO	2422	/	/	1	0.70
		2437	/	/	1	1.26
		2452	/	/	1	1.38
802.11ax (HEW20)	SISO	2412	SU	/	1	3.79
		2437	SU	/	1	4.00
		2462	SU	/	1	4.13


5.1.2 CSE

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
802.11b	SISO	2412	/	/	1	6.39	-23.61	Pass
		2437	/	/	1	6.39	-23.61	Pass
		2462	/	/	1	6.39	-23.61	Pass
802.11g	SISO	2412	/	/	1	4.42	-25.58	Pass
		2437	/	/	1	4.42	-25.58	Pass
		2462	/	/	1	4.42	-25.58	Pass
802.11n (HT20)	SISO	2412	/	/	1	3.70	-26.30	Pass
		2437	/	/	1	3.70	-26.30	Pass
		2462	/	/	1	3.70	-26.30	Pass
802.11n (HT40)	SISO	2422	/	/	1	1.38	-28.62	Pass
		2437	/	/	1	1.38	-28.62	Pass
		2452	/	/	1	1.38	-28.62	Pass
802.11ax (HEW20)	SISO	2412	SU	/	1	4.13	-25.87	Pass
		2437	SU	/	1	4.13	-25.87	Pass
		2462	SU	/	1	4.13	-25.87	Pass


5.2 Test Graph

5.2.1 Ref


802.11b LCH 2412MHz Ant1 (SISO) NTN




802.11b MCH 2437MHz Ant1 (SISO) NTN




802.11b HCH 2462MHz Ant1 (SISO) NTN




802.11g LCH 2412MHz Ant1 (SISO) NTN




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20) MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT40) LCH 2422MHz Ant1 (SISO) NTN




802.11n(HT40) MCH_2437MHz_Ant1 (SISO) NTN




802.11n(HT40) HCH_2452MHz_Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTNv



802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTNv




802.11ax(HEW20) HCH 2462MHz SU / Ant1 (SISO) NTN




5.2.2 CSE


802.11b LCH 2412MHz Ant1 (SISO) NTN




802.11b LCH 2412MHz_Ant1 (SISO) NTN




802.11b MCH 2437MHz_Ant1 (SISO) NTN




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g LCH 2412MHz Ant1 (SISO) NTN




802.11g LCH 2412MHz Ant1 (SISO) NTN




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20) MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20) HCH_2462MHz_Ant1 (SISO) NTN




802.11n(HT20) HCH_2462MHz_Ant1 (SISO) NTN




802.11n(HT40) LCH_2422MHz_Ant1 (SISO) NTN




802.11n(HT40) LCH_2422MHz_Ant1 (SISO) NTN




802.11n(HT40) MCH_2437MHz_Ant1 (SISO) NTN




802.11n(HT40) HCH_2452MHz_Ant1 (SISO) NTN




802.11n(HT40) HCH 2452MHz Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTN




802.11ax(HEW20) LCH 2412MHz SU / Ant1 (SISO) NTN




802.11ax(HEW20) MCH 2437MHz SU / Ant1 (SISO) NTN



802.11ax(HEW20) HCH 2462MHz SU / Ant1 (SISO) NTN



802.11ax(HEW20) HCH 2462MHz SU / Ant1 (SISO) NTN



- End of the Report -