

47 CFR PART 15 SUBPART C TEST REPORT

for

X5W Meter

Model No.: X5W

FCC ID: 2ADBKX5W

of

Applicant: Yamaha Motor Co.,Ltd.

Address: 2500 Shingai, Iwata-shi, Shizuoka-ken, Japan

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634



Report No.: W6M22508-24669-C-1



TABLE OF CONTENTS

1	GENERAL INFORMATION	2
1.1	NOTES	2
1.2	TESTING LABORATORY	3
1.3	APPLICATION DETAILS	3
1.4	GENERAL INFORMATION OF TEST ITEM	4
1.5	DUTY CYCLE AND FACTOR	5
1.6	TEST STANDARDS.....	7
2	TEST CONFIGURATION	8
2.1	TEST ENVIRONMENT	8
2.2	MEASUREMENT UNCERTAINTY	8
2.3	TEST EQUIPMENT LIST	9
3	TEST RESULTS (ENCLOSURE)	10
3.1	PEAK OUTPUT POWER (TRANSMITTER)	11
3.2	SPURIOUS EMISSIONS RADIATED – TRANSMITTER OPERATING	16
3.3	EMISSIONS IN NONRESTRICTED FREQUENCY BANDS	18
3.4	MINIMUM 6 DB BANDWIDTH	22
3.5	PEAK POWER SPECTRAL DENSITY	27
3.6	POWER LINE CONDUCTED EMISSION	32

Appendix: Diagrams



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

Laboratory disclaimer-

1. The test results of this test report relate exclusively to the item tested as specified in 1.5.
2. The test report may only be reproduced or published in full.
3. Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.
4. Antenna gain is provided by applicant and laboratory issue relevant data and results.

Tester:

November 19, 2025

Sora Kuo

Sora

Date

WTS-Lab.

Name

Signature

Technical responsibility for area of testing:

November 19, 2025

Kevin Wang

Kevin Wang

Date

WTS

Name

Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

1.2 Testing laboratory

1.2.1 Location

10m OATS

No.5-1, Lishui, Shuang Sing Village, Wanli Dist.,
New Taipei City 207, Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No. 99, Sec. 1, Balian Rd., Xizhi Dist.,
New Taipei City 221032, Taiwan (R.O.C.)

Worldwide Testing Services (Taiwan) Co., Ltd.

6F., No. 58, Ln. 188, Ruiguang Rd., Neihu Dist.,

Taipei City 114 , Taiwan (R.O.C.)

Tel: 886-2-6606-8877

1.2.2 Details of accreditation status

Accredited testing laboratory

FCC filed test laboratory Reg. No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634

Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: ./.

Accredited no.: ./.

Street: ./.

Town: ./.

Country: ./.

1.3 Application details

Approval holder

Name: Yamaha Motor Co.,Ltd.

Street: 2500 Shingai, Iwata-shi,

Town: Shizuoka-ken,

Country: Japan

Manufacturer: (if applicable)

Name: ./.

Street: ./.

Town: ./.

Country: ./.



Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

Application details

Date of receipt of test item: August 26, 2025

Date of test: from August 27, 2025 to September 26, 2025

1.4 General information of Test item

Type of test item: X5W Meter
Model no.: X5W
Multi-listing model no.: ./.
Brand name: YAMAHA
Power supply: Battery 36Vd.c.
Type of antenna: Chip antenna
Antenna gain: 1.5 dBi

Technical data

Mode	Channel	Conducted Power (dBm)
BLE 1M	Ch 0 : 2402 MHz	-5.10
	Ch 19 : 2440 MHz	-5.39
	Ch 39 : 2480 MHz	-6.00
BLE 2M	Ch 0 : 2402 MHz	-5.04
	Ch 19 : 2440 MHz	-5.27
	Ch 39 : 2480 MHz	-5.87

Mode	Channel	Conducted Power (dBm)
ANT+	2457 MHz	-6.15

Operation modes: Duplex
Modulation type: GFSK
Sample no.: #04
Special statement: ./.

Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

1.5 Duty cycle and factor

The duty factor is computed as $[10 \log (1 / D)]$, where D is the duty cycle.


Mode	T _{on} (ms)	T _{on} +T _{off} (ms)	Duty cycle (%)	1/T - VBW (kHz)
BLE 1M	0.405	0.625	64.80%	2.47
BLE 2M	0.216	0.625	34.56%	4.63

Mode	T _{on} (ms)	T _{on} +T _{off} (ms)	Duty cycle (%)	1/T - VBW (kHz)
ANT+	100	100	100.00%	0.01


Duty cycle plot

BLE

1M




DUTY BLE 1M
Date: 9.SEP.2025 09:20:16




Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W




DUTY BLE 1M
Date: 9.SEP.2025 09:20:23


2M



DUTY BLE 2M
Date: 9.SEP.2025 09:19:15




Registration number: W6M22508-24669-C-1
FCC ID: 2ADBKX5W



DUTY BLE 2M
Date: 9.SEP.2025 09:19:25

ANT+



DUTY ANT+ 2457MHz
Date: 22.SEP.2025 09:56:34

1.6 Test standards

47 CFR PART 15 SUBPART C § 15.247 (2024-10)
ANSI C63.10-2020+Cor.1-2023+C63.10a-2024



Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

2 Test configuration

2.1 Test environment

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Extreme conditions parameters: ./.

2.2 Measurement uncertainty

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Emission (Power Line Conducted Emission)	Expanded Uncertainty : AMN : 0.94 dB Voltage probe : 1.21 dB Include Pulse Limiter : 1.5 dB
Estimation Result of Uncertainty of Radiated Emission(3M-966A) (Spurious Emissions radiated – Transmitter operating)	Expanded Uncertainty : 0.009-30 MHz : 1.85 dB 30-1000 MHz : 3.92 dB 1-18 GHz : 3.19 dB 18-40 GHz : 1.90 dB
Estimation Result of Uncertainty of Bandwidth Measurement (Minimum 6 dB Bandwidth)	Expanded Uncertainty : 0.37 kHz
Estimation Result of Uncertainty of Conducted Output Power Measurement (Peak Output Power (transmitter))	Expanded Uncertainty : 1.63 dB
Estimation Result of Uncertainty of Power Density Measurement (Peak Power Spectral Density)	Expanded Uncertainty : 1.63 dB
Estimation Result of Uncertainty of Band Edge Measurement (Emissions in nonrestricted frequency bands)	Expanded Uncertainty : 0.63 dBc

The decision rule is: Measurement uncertainty is not included in the calculation of test results.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

2.3 Test Equipment List

Max Output Power, 6DB Bandwidth, Band edge, Power Density, Duty

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2025/2/14	2026/2/13
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2025/3/5	2026/3/4
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2025/2/14	2026/2/13
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2025/2/14	2026/2/13

Spurious Emission (966A)

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 153	Signal Analyzer	FSV40	101929	R&S	2025/9/10	2026/9/9
ETSTW-RE 154	EMI Test Receiver	ESR3	102829	R&S	2025/2/14	2026/4/8
ETSTW-RE 160	Amplifier Module	CHC 3	None	WTS	2025/7/11	2026/7/10
ETSTW-RE 177	TRILOG Broadband Antenna	VULB 9168&EMCI-N-6-06	01380&AT-06007	SCHWARZBECK&EMC	2025/3/10	2026/3/9
ETSTW-RE 178	Double Ridged Guide Horn Antenna	DRH18-E	210505A18ES	RFSPIN	2025/3/7	2026/3/6
ETSTW-Cable 077	SMA type cable (10m)	EMC104-SM-SM-10000	230511	EMCI	2025/7/11	2026/7/10
ETSTW-Cable 084	SMA type cable (1m)	SF104-11SMA-1000	816477/4	HONOVA	2025/7/11	2026/7/10
ETSTW-Cable 089	SMA type cable (2m)	SF104-11SMA-2000	SN 811889/4	HUBER+SUHNER	2025/7/11	2026/7/10
WTSTW-SW 002	EMI TEST SOFTWARE	EZ_EMC	None	Farad	Version ETS-03A1 Version EMEC-3A1+	
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2025/7/31	2026/7/30
ETSTW-RE 088	SOLID STATE AMPLIFIER	KMA180265A01	99057	KMIC	2025/9/12	2026/9/11
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2025/9/12	2026/9/11
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2025/9/12	2026/9/11



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)(3)	☒	☒	☐
Spurious Emissions radiated – Transmitter operating	15.247(d), 15.205, 15.209	☒	☒	☐
Emissions in nonrestricted frequency bands	15.247(d)	☒	☒	☐
Minimum 6 dB Bandwidth	15.247(a)(2)	☒	☒	☐
Peak Power Spectral Density	15.247(e)	☒	☒	☐
Power Line Conducted Emission	15.207(a)	☐	☐	☐

The following is intentionally left blank.



Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

3.1 Peak Output Power (transmitter)

3.1.1 Applicable Standard

FCC Rule: 15.247(b)(3)


For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.1.2 Test procedure

Following Subclause 11.9.1.1 of ANSI C63.10

1. Set the RBW $\geq$ DTS bandwidth , VBW $\geq$ $[3 \times \text{RBW}]$, span $\geq$ $[3 \times \text{RBW}]$.
2. Sweep time = auto couple , Detector = peak , Trace mode = max hold.
3. Allow trace to fully stabilize and determine the peak amplitude level.


3.1.3 Test Setup



3.1.4 Limits

Frequency (MHz)	Power (dBm)
902 - 928	30
2400 – 2483.5	30
5725 – 5850	30

In case of employing transmitter antennas having antenna gain > 6 dBi and using fixed point-to point operation consider §15.247 (b)(4)



Registration number: W6M22508-24669-C-1
FCC ID: 2ADBKX5W


3.1.5 Test Environmental Conditions

Test date: 2025-09-09~
2025-09-22 Temperature: 28.5°C Humidity: 52.6% Tester: Sora


3.1.6 Test results

Mode	Channel	Power (dBm)	Limit (dBm)
BLE 1M	Ch 0 : 2402 MHz	-5.10	30
	Ch 19 : 2440 MHz	-5.39	30
	Ch 39 : 2480 MHz	-6.00	30
BLE 2M	Ch 0 : 2402 MHz	-5.04	30
	Ch 19 : 2440 MHz	-5.27	30
	Ch 39 : 2480 MHz	-5.87	30

BLE
1M




MAX OUTPUT POWER BLE 1M CH00
Date: 9.SEP.2025 08:55:04




Registration number: W6M22508-24669-C-1


FCC ID: 2ADBKX5W



MAX OUTPUT POWER BLE 1M CH19
Date: 9.SEP.2025 08:55:58




MAX OUTPUT POWER BLE 1M CH39
Date: 9.SEP.2025 08:56:48



Registration number: W6M22508-24669-C-1


FCC ID: 2ADBKX5W

2M




MAX OUTPUT POWER BLE 2M CH00

Date: 9.SEP.2025 08:57:56




MAX OUTPUT POWER BLE 2M CH19

Date: 9.SEP.2025 08:58:54



Registration number: W6M22508-24669-C-1


FCC ID: 2ADBKX5W



MAX OUTPUT POWER BLE 2M CH39
Date: 9.SEP.2025 08:59:36

ANT+

Band	Mode	Channel	Power (dBm)	Limit (dBm)
2.4GHz	ANT+	2457 MHz	-6.15	30



MAX OUTPUT POWER ANT+ 2457MHz
Date: 22.SEP.2025 09:47:13



Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

3.2 Spurious Emissions radiated – Transmitter operating

3.2.1 Applicable Standard

FCC Rules: 15.247 (d), 15.205, 15.209

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

3.2.2 Test procedure

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. Below 1GHz measurement the EUT is placed on turntable which is 0.8m above ground plane. And above 1GHz measurement EUT was placed on low permittivity and low tangent turn table which is 1.5m above ground plane.
2. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m height to find out the highest emissions.
3. Receiver or Spectrum analyzer configuration
 - (a)120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
 - (b)RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
 - (c)RBW=1MHz, VBW=10Hz(1/T) and Peak detector is for average measured value of radiated emission above 1GHz.


3.2.3 Limits

Frequency (MHz)	Field strength (uV/m)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

3.2.4 Test Setup




Below 1 GHz



Above 1 GHz

3.2.5 Test results (With Environmental Conditions)

Explanation: See attached diagrams in Appendix.



Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

3.3 Emissions in nonrestricted frequency bands

3.3.1 Applicable Standard

FCC Rules: 15.247(d)


In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.

In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.

3.3.2 Test procedure

1. Set RBW = 100 kHz , VBW $\geq [3 \times \text{RBW}]$
2. Set Detector = peak , Sweep time = auto , Trace mode = max hold, and allow sweep to continue until the trace stabilizes
3. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

3.3.3 Test setup




3.3.4 Limits

See 3.3.1

3.3.5 Test Environmental Conditions

Test date: 2025-09-09~ Temperature: 28.5°C Humidity: 52.6% Tester: Sora
 2025-09-22




Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

3.3.6 Test results


BLE

1M




BANDEDGE BLE 1M CH00

Date: 9.SEP.2025 08:55:34



BANDEDGE BLE 1M CH39


Date: 9.SEP.2025 08:57:18




Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W


2M



BANDEGE BLE 2M CH00
Date: 9.SEP.2025 08:58:26



BANDEGE BLE 2M CH39
Date: 9.SEP.2025 09:00:04




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

ANT+



BANDEDGE ANT+ 2457MHz
Date: 22.SEP.2025 09:49:34



BANDEDGE ANT+ 2457MHz
Date: 22.SEP.2025 09:50:12



Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

3.4 Minimum 6 dB Bandwidth

3.4.1 Applicable Standard


FCC Rules: 15.247(a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.4.2 Test procedure

1. Set RBW = 100 kHz , Set the VBW $\geq [3 \times \text{RBW}]$.
2. Set Detector = peak , Trace mode = max hold , Sweep = auto couple and allow the trace to stabilize.
3. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.4.3 Test setup




3.4.4 Limits

Frequency Range (MHz)	Limits (kHz)
902-928	≥ 500
2400-2483.5	
5725-5850	

3.4.5 Test Environmental Conditions

Test date: 2025-09-09~ Temperature: 28.5°C Humidity: 52.6% Tester: Sora
 2025-09-22




Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W


3.4.6 Test results

BLE


1M



6DB BANDWIDTH BLE 1M CH00
Date: 9.SEP.2025 08:55:14




6DB BANDWIDTH BLE 1M CH19
Date: 9.SEP.2025 08:56:08




Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W




6DB BANDWIDTH BLE 1M CH39
Date: 9.SEP.2025 08:56:58

2M




6DB BANDWIDTH BLE 2M CH00
Date: 9.SEP.2025 09:16:15




Registration number: W6M22508-24669-C-1


FCC ID: 2ADBKX5W



6DB BANDWIDTH BLE 2M CH19
Date: 9.SEP.2025 09:14:58




6DB BANDWIDTH BLE 2M CH39
Date: 9.SEP.2025 09:13:30



Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W


ANT+



6DB BANDWIDTH ANT+ 2457MHz
Date: 22.SEP.2025 09:46:46



FCC ID: 2ADBKX5W




Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W


3.5.6 Test results

BLE


1M



POWER DENSITY BLE 1M CH00
Date: 9.SEP.2025 08:55:26




POWER DENSITY BLE 1M CH19
Date: 9.SEP.2025 08:56:20




Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W




POWER DENSITY BLE 1M CH39
Date: 9.SEP.2025 08:57:10

2M




POWER DENSITY BLE 2M CH00
Date: 9.SEP.2025 08:58:18




Registration number: W6M22508-24669-C-1


FCC ID: 2ADBKX5W



POWER DENSITY BLE 2M CH19
Date: 9.SEP.2025 08:59:16



POWER DENSITY BLE 2M CH39
Date: 9.SEP.2025 08:59:56




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

ANT+



POWER DENSITY ANT+ 2457MHz
Date: 22.SEP.2025 09:51:27

Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

3.6 Power Line Conducted Emission

3.6.1 Applicable Standard


FCC Rules:15.207(a)

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

3.6.2 Test procedure


1. EUT is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. Connect EUT to a 50 μ H/50 ohms line impedance stabilization network (LISN). AC input is 120V/60Hz
3. This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

3.6.3 Test setup



3.6.4 Limits

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50




Registration number: W6M22508-24669-C-1

FCC ID: 2ADBKX5W

3.6.5 Test results (With Environmental Conditions)

The test is not required because the EUT was powered by battery.



Registration number: W6M22508-24669-C-1
FCC ID: 2ADBKX5W

Appendix

Measurement diagrams

Radiated Emission



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File: 1_BLE(1M)_TX 2402MHz Data: #1


Date: 2025/9/18

Temperature: 28.0 °C

80.0 dBuV/m

Time: 下午 03:30:06

Humidity: 44.0 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

EUT : W6M22508-24669

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	218.5571	45.52	peak	-10.48	35.04	46.00	100	82	-10.96	
	304.0881	41.08	peak	-6.19	34.89	46.00	100	230	-11.11	
*	393.5070	47.52	QP	-4.53	42.99	46.00	100	335	-3.01	
	473.2064	41.08	peak	-3.11	37.97	46.00	100	0	-8.03	
	640.3807	33.04	peak	0.24	33.28	46.00	100	249	-12.72	
	729.7996	38.34	peak	1.82	40.16	46.00	100	76	-5.84	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File: 1_BLE(1M)_TX 2402MHz Data: #2

Date: 2025/9/18

Temperature: 28.0 °C

80.0 dBuV/m

Time: 下午 03:31:04

Humidity: 44.0 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

EUT : W6M22508-24669

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	236.0521	40.07	peak	-8.88	31.19	46.00	100	259	-14.81	
*	393.5070	42.15	peak	-4.53	37.62	46.00	100	146	-8.38	
	519.8597	33.39	peak	-2.33	31.06	46.00	100	56	-14.94	
	640.3808	33.58	peak	0.24	33.82	46.00	100	98	-12.18	
	729.7996	30.41	peak	1.82	32.23	46.00	100	318	-13.77	
	961.1222	29.43	peak	5.70	35.13	54.00	100	158	-18.87	

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#1


Date: 2025/9/11

Temperature:33.0 °C

90.0 dBuV/m

Time: 上午 03:16:21

Humidity:29.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22508-24669

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: *Horizontal*

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #6


Date: 2025/9/11

Temperature: 33.0 °C

90.0 dBuV/m

Time: 上午 03:22:09

Humidity: 29.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22508-24669

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #2


Date: 2025/9/11

Temperature: 33.0 °C

90.0 dBuV/m

Time: 上午 03:17:12

Humidity: 29.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22508-24669

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4801.603	59.36	peak	-1.64	57.72	74.00	150	211	-16.28	
*	4801.603	51.51	AVG	-1.64	49.87	54.00	150	211	-4.13	
	7206.000	36.90	peak	3.88	40.78	74.00	150	307	-33.22	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #7


Date: 2025/9/11

Temperature: 33.0 °C

90.0 dBuV/m

Time: 上午 03:23:02

Humidity: 29.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22508-24669

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4801.603	57.26	peak	-1.64	55.62	74.00	150	306	-18.38	
*	4801.603	49.39	AVG	-1.64	47.75	54.00	150	306	-6.25	
	7206.000	38.96	peak	3.88	42.84	74.00	150	359	-31.16	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #3


Date: 2025/9/11

Temperature: 33.0 °C

90.0 dBuV/m

Time: 上午 03:19:28

Humidity: 29.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22508-24669

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9608.000	34.23	peak	6.72	40.95	74.00	150	40	-33.05	
*	12010.000	33.01	peak	11.18	44.19	74.00	150	320	-29.81	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #8


Date: 2025/9/11

Temperature: 33.0 °C

90.0 dBuV/m

Time: 上午 03:28:48

Humidity: 29.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22508-24669

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9608.000	34.15	peak	6.72	40.87	74.00	150	360	-33.13	
*	12010.000	32.75	peak	11.18	43.93	74.00	150	224	-30.07	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #4

Date: 2025/9/11

Temperature: 33.0 °C

90.0 dBuV/m

Time: 上午 03:19:50

Humidity: 29.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22508-24669

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #9


Date: 2025/9/11

Temperature: 33.0 °C

90.0 dBuV/m

Time: 上午 03:29:11

Humidity: 29.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22508-24669

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Vertical**

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#5


Date: 2025/9/11

Temperature:33.0 °C

90.0 dBuV/m

Time: 上午 03:20:08

Humidity:29.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22508-24669

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: *Horizontal*

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No.99, Sec.1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#10


Date: 2025/9/11

Temperature: 33.0 °C

90.0 dBuV/m

Time: 上午 03:29:29

Humidity: 29.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22508-24669

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Vertical**

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : Bandedge

Data : #1


Date: 2025/9/11

Temperature: 33.0 °C

120.0 dBuV/m

Time: 上午 07:16:24

Humidity: 29.2 %



Site : 966A Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22508-24669

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2390.000	9.72	peak	37.26	46.98	74.00	150	194	-27.02	
*	2390.000	0.91	AVG	37.26	38.17	54.00	150	194	-15.83	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : Bandedge

Data : #2


Date: 2025/9/11

Temperature: 33.0 °C

120.0 dBuV/m

Time: 上午 07:13:09

Humidity: 29.2 %



Site : 966A Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22508-24669

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2390.000	9.33	peak	37.26	46.59	74.00	150	347	-27.41	
*	2390.000	0.86	AVG	37.26	38.12	54.00	150	347	-15.88	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #1


Date: 2025/9/11

Temperature: 33.0 °C

90.0 dBuV/m

Time: 上午 03:43:06

Humidity: 29.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22508-24669

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Horizontal**

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#6


Date: 2025/9/11

Temperature:33.0 °C

90.0 dBuV/m

Time: 上午 03:47:53

Humidity:29.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22508-24669

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: Vertical

Power : 5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin